

GUROBI
OPTIMIZATION

Gurobi Example Tour

Version 14.0

Copyright © 2026, Gurobi Optimization, LLC

Nov 10, 2026

Revision: 27037e0ff

CONTENTS

1 Example Tour 3

2 Example Source Code 27

Version 14.0

The Gurobi distribution includes an extensive set of examples that illustrate commonly used features of the Gurobi libraries. Most examples have versions for C, C++, C#, Java, Python, and Visual Basic. A few, however, illustrate features that are specific to the Python interface.

The distribution also includes examples for our MATLAB and R interfaces. Note, however, that our interfaces to these languages are built around the assumption that you will use the rich matrix-oriented capabilities of the underlying languages to build your optimization models. Thus, our examples for these languages don't attempt to show you how to build models. We have instead chosen to provide a few simple examples that demonstrate how to pass matrices into our interface.

This document provides a brief tour of these examples. We won't go through each example in detail. Instead, we'll start with an *Overview* of the set of tasks that you are likely to want to perform with the Gurobi Optimizer. Later sections will then describe how specific examples accomplish each of these tasks. Alternatively, we provide a *Structured List* of all of our examples, which you can use to dive directly into an example of interest to you. In either case, we suggest that you browse the example source code (in a text editor, or in another browser window) while reading this document. This document includes *Source Code* for all of the examples, in all available languages. Source files are also available in the `examples` directory of the Gurobi distribution.

If you would like further details on any of the Gurobi routines used in these examples, please consult the Gurobi Reference Manual.

CHAPTER

ONE

EXAMPLE TOUR

This document provides a quick guided tour of the Gurobi examples; we will try to highlight some of the most important features of these examples. Full source code is provided in this document, so you are free to explore the examples in full detail.

Wherever possible, we try to discuss the examples in a manner that is independent of programming languages. We will refer to each example using a brief, language independent name. You will need to map this name to the specific source file name for your language. For example, the `facility` example corresponds to six different implementations, one in C (*facility_c.c*), one in C++ (*facility_c++.cpp*), one in Java (*Facility.java*), one in C# (*facility_cs.cs*), one in Visual Basic (*facility_vb.vb*), and one in Python (*facility.py*). If you would like to look at the language implementation for a particular example, please refer to the appropriate example source file.

1.1 Topics covered in the examples

The easiest place to start your introduction to the Gurobi examples is probably with the examples that *load and solve a model from a file*. These demonstrate the most basic capabilities of the Gurobi libraries. They also demonstrate the use of model attributes, which are an important concept in the Gurobi Optimizer.

Once you are comfortable with these examples, you should move on to the examples that *build a model* from scratch. These show you how to create variables and constraints, and add them to an optimization model.

The next topic covered in this document is *model modification*. The Gurobi distribution includes examples that add and remove constraints, add variables, and change variable types, bounds and objective coefficients. You modify a model in much the same way that you build a model from scratch, but there are some important differences involving the use of the solution information.

Next, this document covers *parameter changes*. The `params` example shows you how to change parameters, and in particular how to use different parameter settings for different models.

The *infeasibility* section considers a few examples that cope with model infeasibility. Some use an Irreducible Inconsistent Subsystem (IIS) to handle the infeasibility, while others relax constraints.

One useful MIP feature that is worth understanding is *MIP starts*. A MIP start allows you to specify a known feasible solution to the MIP solver. The solution provides a bound on the objective of the best possible solution, which can help to limit the MIP search. The solution also provides a potential start point for the local search heuristics that are utilized by the Gurobi MIP solver.

It is possible to achieve model-data separation when using our Python interface, as is often done in modeling languages, but you need to make use of Python modules to do so. The *model-data separation* section provides an example of how this is done. It considers three versions of the diet example. All three use the same function to formulate and solve the actual optimization model, but they obtain model data from very different places.

The final topic we cover in this document is *Gurobi callbacks*. Callbacks allow the user to obtain periodic progress information related to the optimization.

1.1.1 A list of the Gurobi examples

We recommend that you begin by reading the overview of the examples (which begins in the *next section*). However, if you'd like to dive directly into a specific example, the following is a list of all of the examples included in the Gurobi distribution, organized by basic function. The source for the examples can be found by following the provided links, or in the `examples` directory of the Gurobi distribution.

Read a model from a file

Example	Description	Available Languages
lp	A very simple example that reads a continuous model from a file, optimizes it, and writes the solution to a file. If the model is infeasible, it writes an Irreducible Inconsistent Subsystem (IIS) instead.	*C*, *C++*, *C#*, *Java*, *Python*, *R*, *Visual Basic*
mip2	Reads a MIP model from a file, optimizes it, and then solves the fixed version of the MIP model.	*C*, *C++*, *C#*, *Java*, *Python*, *Visual Basic*

Build a simple model

Example	Description	Available Languages
mip1	Builds a trivial MIP model, solves it, and prints the solution.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
qp	Builds a trivial QP model, solves it, converts it to an MIQP model, and solves it again.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
qcp	Builds and solves a trivial QCP model.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
bilinear	Builds and solves a trivial bilinear model.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
sos	Builds and solves a trivial SOS model.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
dense	Solves a model stored using dense matrices. We don't recommend using dense matrices, but this example may be helpful if your data is already in this format.	*C*, *C++*, *C#*, *Java*, *Python*, *Visual Basic*
genconstr	Demonstrates the use of simple general constraints.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
nlconstr	Demonstrates the use of nonlinear constraints.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Visual Basic*
nlobj	Demonstrates the use of nonlinear objectives.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Visual Basic*
matrix1	A Python-only example that formulates and solves a simple MIP model using the matrix API.	*Python*
multiobj	Demonstrates the use of multi-objective optimization.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
piecewise	Demonstrates the use of piecewise-linear objective functions.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
gc_pwl	Demonstrates the use of piecewise-linear constraint.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
poolsearch	Demonstrates the use of solution pools.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*

A few simple applications

Example	Description	Available Languages
ACOPF	A Python-only example that solves a simple ACOPF problem on four buses. It demonstrates the use of several Python modeling constructs, including vectorized constraints and nonlinear expressions.	*Python*
diet	Builds and solves the classic diet problem. Demonstrates model construction and simple model modification - after the initial model is solved, a constraint is added to limit the number of dairy servings.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
diet2, *diet3*, *diet4*, *dietmodel*	Python-only variants of the diet example that illustrate model-data separation.	*Python*
facility	Simple facility location model: given a set of plants and a set of warehouses, with transportation costs between them, this example finds the least expensive set of plants to open in order to satisfy product demand. This example demonstrates the use of MIP starts —- the example computes an initial, heuristic solution and passes that solution to the MIP solver.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
matrix2	Python-only example that solves the n-queens problem using the matrix-oriented Python interface.	*Python*
netflow	A Python-only example that solves a multi-commodity network flow model. It demonstrates the use of several Python modeling constructs, including dictionaries, tuples, tupledict, and tuplelist objects.	*Python*
portfolio	A Python-only example that solves a financial portfolio optimization model, where the historical return data is stored using the pandas package and the result is plotted using the matplotlib package. It demonstrates the use of pandas, NumPy, and Matplotlib in conjunction with Gurobi.	*Python*
sudoku	Reads a Sudoku puzzle data set from a file, builds a MIP model to solve that model, solves it, and prints the solution.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
workforce1	Formulates and solves a workforce scheduling model. If the model is infeasible, the example computes and prints an Irreducible Inconsistent Subsystem (IIS).	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
workforce2	An enhancement of *workforce1*. This example solves the same workforce scheduling model, but if the model is infeasible, it computes an IIS, removes one of the associated constraints from the model, and re-solves. This process is repeated until the model becomes feasible. Demonstrates constraint removal.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
workforce3	A different enhancement of *workforce1*. This example solves the same workforce scheduling model, but if the model is infeasible, it adds artificial variables to each constraint and minimizes the sum of the artificial variables. This corresponds to finding the minimum total change in the right-hand side vector required in order to make the model feasible. Demonstrates variable addition.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
workforce4	An enhancement of *workforce3*. This example solves the same workforce scheduling model, but it starts with artificial variables in each constraint. It first minimizes the sum of the artificial variables. Then, it introduces a new quadratic objective to balance the workload among the workers. Demonstrates optimization with multiple objective functions.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
workforce5	An alternative enhancement of *workforce3*. This example solves the same workforce scheduling model, but it starts with artificial variables in each constraint. It formulates a multi-objective model where the primary objective is to minimize the sum of the artificial variables (uncovered shifts), and the secondary objective is to minimize the maximum difference in the number of shifts worked between any pair of workers. Demonstrates multi-objective optimization.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*

Illustrating specific features

Example	Description	Available Languages
feasopt	Reads a MIP model from a file, adds artificial slack variables to relax each constraint, and then minimizes the sum of the artificial variables. It then computes the same relaxation using the *feasibility relaxation* feature. The example demonstrates simple model modification by adding slack variables. It also demonstrates the feasibility relaxation feature.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
lpmethod	Demonstrates the use of different LP algorithms. Reads a continuous model from a file and solves it using multiple algorithms, reporting which is the quickest for that model.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
lpmod	Demonstrates the use of advanced starts in LP. Reads a continuous model from a file, solves it, and then modifies one variable bound. The resulting model is then solved in two different ways: starting from the solution of the original model, or restarting from scratch.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
params	Demonstrates the use of Gurobi parameters. Reads a MIP model from a file, and then spends 5 seconds solving the model with each of four different values of the MIPFocus parameter. It compares the optimality gaps for the four different runs, and continues with the MIPFocus value that produced the smallest gap.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
sensitivity	MIP sensitivity analysis. Reads a MIP model, solves it, and then computes the objective impact of fixing each binary variable in the model to 0 or 1. Demonstrates the multi-scenario feature.	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
tune	Uses the parameter tuning tool to search for improved parameter settings for a model.	*C*, *C++*, *C#*, *Java*, *Python*, *Visual Basic*
fixanddive	Implements a simple MIP heuristic. It reads a MIP model from a file, relaxes the integrality conditions, and then solves the relaxation. It then chooses a set of integer variables that take integer or nearly integer values in the relaxation, fixes them to the nearest integer, and solves the relaxation again. This process is repeated until the relaxation is either integer feasible or linearly infeasible. The example demonstrates different types of model modification (relaxing integrality conditions, changing variable bounds, etc.).	*C*, *C++*, *C#*, *Java*, *MATLAB*, *Python*, *R*, *Visual Basic*
multiscenario	Simple facility location model: given a set of plants and a set of warehouses, with transportation costs between them, this example finds the least expensive set of plants to open in order to satisfy product demand. Since the plant fixed costs and the warehouse demands are uncertain, multiple scenarios are created to capture different possible values. A multi-scenario model is constructed and solved, and the solutions for the different scenarios are retrieved and displayed.	*C*, *C++*, *C#*, *Java*, *Python*, *Visual Basic*
batchmode	Demonstrates the use of batch optimization.	*C*, *C++*, *C#*, *Java*, *Python*, *Visual Basic*
workforce_batc	Example which formulates a workforce scheduling model. The model is solved using batch optimization. The VTag attribute is used to identify the set of variables whose solution information is needed to construct the schedule.	*Python*
mip1_remo	Example that shows the use of context managers to create and dispose of environment and model objects.	*Python*

More advanced features

Example	Description	Available Languages
tsp	Solves a traveling salesman problem using lazy constraints.	*C*, *C++*, *C#*, *Java*, *Python*, *Visual Basic*
callback	Demonstrates the use of Gurobi callbacks.	*C*, *C++*, *C#*, *Java*, *Python*, *Visual Basic*

1.1.2 Load and solve a model from a file

Examples

batchmode, *callback*, *feasopt*, *fixanddive*, *lp*, *lpmethod*, *lpmod*, *mip2*, *params*, *sensitivity*

One of the most basic tasks you can perform with the Gurobi libraries is to read a model from a file, optimize it, and report the result. The *lp example* is a simple illustration of how this is done in the various supported Gurobi languages. While the specifics vary from one language to another, the basic structure remains the same for all languages.

After initializing the Gurobi environment, the examples begin by reading the model from the specified file.

C

C++

C#

Java

Python

Visual Basic

```
error = GRBreadmodel(env, argv[1], &model);
if (error) goto QUIT;
```

```
GRBModel model = GRBModel(env, argv[1]);
```

```
GRBModel model = new GRBModel(env, args[0]);
```

```
GRBModel model = new GRBModel(env, args[0]);
```

```
model = gp.read(sys.argv[1])
```

```
Dim model As GRBModel = New GRBModel(env, args(0))
```

The next step is to invoke the Gurobi Optimizer on the model.

C

C++

C#

Java

Python

Visual Basic

```
error = GRBoptimize(model);
if (error) goto QUIT;
```

```
model.optimize();
```

```
model.Optimize();
```

```
model.optimize();
```

```
model.optimize()
```

```
model.Optimize()
```

A successful `optimize` call populates a set of solution attributes in the model. For example, once the call completes, the X variable attribute contains the solution value for each variable. Similarly, for continuous models, the Pi constraint attribute contains the dual value for each constraint.

The examples then retrieve the value of the model Status attribute to determine the result of the optimization. In the *lp example*, an optimal solution is written to a solution file (`model.sol`).

There are many other things you can do once you have read and solved the model. For example, *lp example* checks the solution status – which is highly recommended. If the model is found to be infeasible, this example computes an Irreducible Inconsistent Subsystem (IIS) to isolate the source of the infeasibility.

1.1.3 Build a model

Examples

bilinear, *diet*, *facility*, *gc_pwl*, *genconstr*, *matrix1*, *mip1*, *multiobj*, *multiscenario*, *piecewise*, *poolsearch*, *qcp*, *qp*, *sensitivity*, *sos*, *sudoku*, *workforce1*, *workforce_batchmode*, *workforce2*, *workforce3*, *workforce4*, *workforce5*

Several of the Gurobi examples build models from scratch. We start by focusing on two: *mip1 example* and *sos example*. Both build very simple models to illustrate the basic process.

Typically, the first step in building a model is to create an empty model.

C

C++

C#

Java

Python

Visual Basic

```
error = GRBnewmodel(env, &model, "mip1", 0, NULL, NULL, NULL, NULL, NULL);
if (error) goto QUIT;
```

You can optionally create a set of variables when you create the model, as well as specifying bounds, objective coefficients, and names for these variables. These examples add new variables separately.

```
GRBModel model = new GRBModel(env);
```

```
GRBModel model = new GRBModel(env);
```

```
GRBModel model = new GRBModel(env);
```

```
m = gp.Model("mip1")
```

```
Dim model As GRBModel = New GRBModel(env)
```

Once the model has been created, the typical next step is to add variables.

C

C++

C#

Java

Python

Visual Basic

```
error = GRBaddvars(model, 3, 0, NULL, NULL, NULL, obj, NULL, NULL, vtype, NULL);
if (error) goto QUIT;
```

```
GRBVar x = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, "x");
```

```
GRBVar x = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, "x");
```

```
GRBVar x = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, "x");
```

```
GRBVar x = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, "x")
```

```
Dim x As GRBVar = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, "x")
```

The new variable's lower bound, upper bound, objective coefficient, type, and name are specified as arguments. In C++ and Python, you can omit these arguments and use default values; see the Gurobi Reference Manual for details.

The next step is to add (linear) constraints to the model.

C

C++

C#

Java

Python

Visual Basic

```
error = GRBaddconstr(model, 3, ind, val, GRB_LESS_EQUAL, 4.0, "c0");
if (error) goto QUIT;
```

To add a linear constraint in C, you must specify a list of variable indices and coefficients for the left-hand side, a sense for the constraint (e.g., GRB_LESS_EQUAL), and a right-hand side constant. You can also give the constraint a name; if you omit the name, Gurobi will assign a default name for the constraint.

In C++ you build a linear constraint by first building linear expressions for the left- and right-hand sides. For C++ the standard mathematical operators such as +, *, <= have been overloaded so that the linear expression resembles a traditional mathematical expression.

```
model.addConstr(x + 2 * y + 3 * z <= 4.0, "c0");
```

In C# you build a linear constraint by first building linear expressions for the left- and right-hand sides. For C# the standard mathematical operators such as +, *, <= have been overloaded so that the linear expression resembles a traditional mathematical expression.

```
model.AddConstr(x + 2 * y + 3 * z <= 4.0, "c0");
```

In Java you build a linear constraint by first building linear expressions for the left- and right-hand sides. In Java, which doesn't support operator overloading, you build an expression as follows:

```
GRBLinExpr expr = new GRBLinExpr();
expr.addTerm(1.0, x); expr.addTerm(2.0, y); expr.addTerm(3.0, z);
```

You then use the addConstr method on the GRBModel object to add a constraint using these linear expressions for the left- and right-hand sides:

```
model.addConstr(expr, GRB.LESS_EQUAL, 4.0, "c0");
```

In Python you build a linear constraint by first building linear expressions for the left- and right-hand sides. For Python the standard mathematical operators such as +, *, <= have been overloaded so that the linear expression resembles a traditional mathematical expression.

```
model.addConstr(x + 2 * y + 3 * z <= 4.0, "c0")
```

In Visual Basic you build a linear constraint by first building linear expressions for the left- and right-hand sides. For Python the standard mathematical operators such as +, *, <= have been overloaded so that the linear expression resembles a traditional mathematical expression.

```
model.AddConstr(x + 2 * y + 3 * z <= 4.0, "c0")
```

Once the model has been built, the typical next step is to optimize it (using GRBoptimize() in C, model.optimize in C++, Java, and Python, or model.Optimize in C#). You can then query the X attribute on the variables to retrieve the solution (and the VarName attribute to retrieve the variable name for each variable).

C

C++

C#

Java

Python

Visual Basic

```
error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 3, sol);
if (error) goto QUIT;
```

```
cout << x.get(GRB_StringAttr_VarName) << " " << x.get(GRB_DoubleAttr_X) << endl;
cout << y.get(GRB_StringAttr_VarName) << " " << y.get(GRB_DoubleAttr_X) << endl;
cout << z.get(GRB_StringAttr_VarName) << " " << z.get(GRB_DoubleAttr_X) << endl;
```

```
Console.WriteLine(x.VarName + " " + x.X);
Console.WriteLine(y.VarName + " " + y.X);
Console.WriteLine(z.VarName + " " + z.X);
```

```
System.out.println(x.get(GRB.StringAttr.VarName) + " " + x.get(GRB.DoubleAttr.X));
System.out.println(y.get(GRB.StringAttr.VarName) + " " + y.get(GRB.DoubleAttr.X));
System.out.println(z.get(GRB.StringAttr.VarName) + " " + z.get(GRB.DoubleAttr.X));
```

```
for v in m.getVars():
    print(f"{v.VarName} {v.X:g}")
```

```
Console.WriteLine(x.VarName & " " & x.X)
Console.WriteLine(y.VarName & " " & y.X)
Console.WriteLine(z.VarName & " " & z.X)
```

When querying or modifying attribute values for an array of constraints or variables, it is generally more efficient to perform the action on the whole array at once. This is quite natural in the C interface, where most of the attribute routines take array arguments. In the C++, C#, Java, and Python interfaces, you can use the `get` and `set` methods on the `GRBModel` object to work directly with arrays of attribute values (`getAttr`/`getAttr` in Python).

C

C++

C#

Java

Python

Visual Basic

In the *mip1*, C example, this is done as follows:

```
error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 3, sol);
if (error) goto QUIT;
```

In the *sensitivity* C++ example, this is done as follows:

```
origX = model.get(GRB_DoubleAttr_X, vars, numVars);
```

In the *sudoku* C# example, this is done as follows:

```
double[,,] x = model.Get(GRB.DoubleAttr.X, vars);
```

In the *sudoku* Java example, this is done as follows:

```
double[][][] x = model.get(GRB.DoubleAttr.X, vars);
```

In the *sudoku* Python example, this is done as follows:

```
solution = model.getAttr('X', vars)
```

In the *sudoku* Visual Basic example, this is done as follows:

```
Dim x As Double(,,) = model.Get(GRB.DoubleAttr.X, vars)
```

Important: We should point out one important subtlety in our interface. We use a *lazy update* approach to building and modifying a model. When you make changes, they are added to a queue. The queue is only flushed when you optimize the model (or write it to a file). In the uncommon situation where you want to query information about your model before optimizing it, you should call the *update* method before making your query.

1.1.4 Additional modeling elements

Examples

bilinear, *gc_pwl*, *genconstr*, *multiobj*, *multiscenario*, *piecewise*, *qcp*, *qp*, *sensitivity*, *sos*

A mathematical programming model in its traditional form consists of a linear objective, a set of linear constraints, and a set of continuous or integer decision variables. Gurobi supports a number of additional modeling constructs. In addition to linear constraints, Gurobi also supports SOS constraints, quadratic constraints, and general constraints. In addition to a single linear objective, Gurobi also supports quadratic objectives, piecewise-linear objectives, and multiple linear objectives. Consult the corresponding examples from the Gurobi distribution for simple examples of how to use each of these modeling elements.

1.1.5 Modify a model

Examples

diet, *feasopt*, *fixanddive*, *lpmod*, *sensitivity*, *workforce3*, *workforce4*, *workforce5*

This section considers model modification. Modification can take many forms, including adding constraints or variables, deleting constraints or variables, modifying constraint and variable attributes, changing constraint coefficients, etc. The Gurobi examples don't cover all possible modifications, but they cover the most common types.

Diet example

This example builds a linear model that solves the classic diet problem: to find the minimum cost diet that satisfies a set of daily nutritional requirements. Once the model has been formulated and solved, it adds an additional constraint to limit the number of servings of dairy products and solves the model again. Let's focus on the model modification.

Adding constraints to a model that has already been solved is no different from adding constraints when constructing an initial model. In the different APIs, we can introduce a limit of 6 dairy servings through the following constraint (where variables 6 and 7 capture the number of servings of milk and ice cream, respectively):

C

C++

C#

Java

Python

Visual Basic

```
printf("\nAdding constraint: at most 6 servings of dairy\n");
cind[0] = 7;
cval[0] = 1.0;
cind[1] = 8;
cval[1] = 1.0;
error = GRBaddconstr(model, 2, cind, cval, GRB_LESS_EQUAL, 6.0, "limit_dairy");
if (error) goto QUIT;
```

```
cout << "\nAdding constraint: at most 6 servings of dairy" << endl;
model.addConstr(buy[7] + buy[8] <= 6.0, "limit_dairy");
```

```
Console.WriteLine("\nAdding constraint: at most 6 servings of dairy");
model.AddConstr(buy[7] + buy[8] <= 6.0, "limit_dairy");
```

```
lhs.addTerm(1.0, buy[8]);
model.addConstr(lhs, GRB.LESS_EQUAL, 6.0, "limit_dairy");
```

```
print("\nAdding constraint: at most 6 servings of dairy")
m.addConstr(buy.sum(["milk", "ice cream"]) <= 6, "limit_dairy")
```

```
Console.WriteLine(vbLf & "Adding constraint: at most 6 servings of dairy")
model.AddConstr(buy(7) + buy(8) <= 6, "limit_dairy")
```

For linear models, the previously computed solution can be used as an efficient *warm start* for the modified model. The Gurobi solver retains the previous solution, so the next `optimize` call automatically starts from the previous solution.

Lpmod example

Changing a variable bound is also straightforward. The *lpmod example* changes a single variable bound, then re-solves the model in two different ways. A variable bound can be changed by modifying the `UB` or `LB` attribute of the variable.

C

C++

C#

Java

Python

Visual Basic

```
error = GRBsetdblattrelement(model, "UB", minVar, 0.0);
if (erro) goto QUIT;
```

```
v[minVar].set(GRB_DoubleAttr_UB, 0.0);
```

```
minVar.UB = 0.0;
```

```
minVar.set(GRB.DoubleAttr.UB, 0.0);
```

```
minVar.UB = 0.0
```

```
minVar.UB = 0
```

The model is re-solved simply by calling the `optimize` method again. For a continuous model, this starts the optimization from the previous solution. To illustrate the difference when solving the model from an initial, unsolved state, the *lpmod example* calls the `reset` function.

C

C++

C#

Java

Python

Visual Basic

```
error = GRBreset(model, 0);
if (error) goto QUIT;
```

```
model.reset();
```

```
model.Reset();
```

```
model.reset();
```

```
model.reset();
```

```
model.Reset()
```

When we call the optimize method after resetting the model, optimization starts from scratch. Although the difference in computation time is insignificant for this tiny example, a warm start can make a big difference for larger models.

Fix-and-dive example

The *fixanddive example* provides another example of bound modification. In this case, we repeatedly modify a set of variable bounds, utilizing warm starts each time. In the different APIs, variables are fixed as follows:

C

C++

C#

Java

Python

Visual Basic

```
for (j = 0; j < nfix; ++j)
{
  fixval = floor(fractional[j].X + 0.5);
  error = GRBsetdblattrelement(model, "LB", fractional[j].index, fixval);
  if (error) goto QUIT;
  error = GRBsetdblattrelement(model, "UB", fractional[j].index, fixval);
  if (error) goto QUIT;
  error = GRBgetstrattrelement(model, "VarName", fractional[j].index, &vname);
  if (error) goto QUIT;
  printf("  Fix %s to %f ( rel %f )\n", vname, fixval, fractional[j].X);
}
```

```
for (int i = 0; i < nfix; ++i)
{
  GRBVar* v = fractional[i];
  double fixval = floor(v->get(GRB_DoubleAttr_X) + 0.5);
  v->set(GRB_DoubleAttr_LB, fixval);
  v->set(GRB_DoubleAttr_UB, fixval);
  cout << "  Fix " << v->get(GRB_StringAttr_VarName) << " to " <<
  fixval << " ( rel " << v->get(GRB_DoubleAttr_X) << " )" <<
  endl;
}
```

```
for (int i = 0; i < nfix; ++i) {
  GRBVar v = fractional[i];
  double fixval = Math.Floor(v.X + 0.5);
  v.LB = fixval;
  v.UB = fixval;
  Console.WriteLine("  Fix " + v.VarName +
      " to " + fixval + " ( rel " + v.X + " )");
}
```

```
for (int i = 0; i < nfix; ++i) {
  GRBVar v = fractional.get(i);
  double fixval = Math.floor(v.get(GRB.DoubleAttr.X) + 0.5);
  v.set(GRB.DoubleAttr.LB, fixval);
  v.set(GRB.DoubleAttr.UB, fixval);
  System.out.println("  Fix " + v.get(GRB.StringAttr.VarName) +
      " to " + fixval + " ( rel " + v.get(GRB.DoubleAttr.X) + " )");
}
```

```
for i in range(nfix):
    v = fractional[i]
    fixval = int(v.X + 0.5)
    v.LB = fixval
    v.UB = fixval
    print(f"  Fix {v.VarName} to {fixval:g} (rel {v.X:g})")
```

```
Dim nfix As Integer = Math.Max(fractional.Count / 4, 1)
For i As Integer = 0 To nfix - 1
```

(continues on next page)

(continued from previous page)

```
    Dim v As GRBVar = fractional(i)
    Dim fixval As Double = Math.Floor(v.X + 0.5)
    v.LB = fixval
    v.UB = fixval
    Console.WriteLine("  Fix " & v.VarName & " to " & fixval & _
                      " ( rel " & v.X & " )")
Next
```

Again, the subsequent call to `optimize` starts from the previous solution.

Sensitivity analysis example

The *sensitivity example* computes the optimal objective value associated with fixing each binary variable to 0 or 1. It first solves the given model to optimality. It then constructs a multi-scenario model, where in each scenario a binary variable is fixed to the complement of the value it took in the optimal solution. The resulting multi-scenario model is solved, giving the objective degradation associated with forcing each binary variable off of its optimal value.

Feasopt example

The last modification example we consider is the *feasopt example*, which adds variables to existing constraints and also changes the optimization objective. Setting the objective to zero is straightforward. In C, set the Obj attribute to 0. In the object-oriented interfaces, call `setObjective` with an empty linear expression.

C

C++

C#

Java

Python

Visual Basic

```
for (j = 0; j < numvars; ++j)
{
  error = GRBsetdblattrelement(model, "Obj", j, 0.0);
  if (error) goto QUIT;
}
```

```
feasmodel.setObjective(GRBLinExpr(0.0));
```

```
feasmodel.SetObjective(new GRBLinExpr());
```

```
feasmodel.setObjective(new GRBLinExpr());
```

```
feasmodel.setObjective(0.0)
```

```
feasmodel.SetObjective(New GRBLinExpr())
```

Adding new variables is somewhat more complex. In the example, we want to add artificial variable(s) to each constraint in order to allow the constraint to be relaxed. We use two artificial variables for equality constraints and one for inequality constraints.

C

C++

C#

Java

Python

Visual Basic

```
error = GRBgetstrattrelement(model, "ConstrName", i, &cname);
if (error) goto QUIT;
vname = malloc(sizeof(char) * (6 + strlen(cname)));
if (!vname) goto QUIT;
strcpy(vname, "ArtN_");
strcat(vname, cname);
vind[0] = i;
vval[0] = -1.0;
error = GRBaddvar(model, 1, vind, vval, 1.0, 0.0, GRB_INFINITY, GRB_CONTINUOUS, vname);
if (error) goto QUIT;
```

```
double coef = -1.0;
feasmodel.addVar(0.0, GRB_INFINITY, 1.0, GRB_CONTINUOUS, 1,
                 &c[i], &coef, "ArtN_" + c[i].get(GRB_StringAttr_ConstrName));
```

```
GRBConstr[] constrs = new GRBConstr[] { c[i] };
double[] coeffs = new double[] { -1 };
feasmodel.AddVar(0.0, GRB.INFINITY, 1.0, GRB.CONTINUOUS, constrs,
                 coeffs, "ArtN_" + c[i].ConstrName);
```

```
GRBConstr[] constrs = new GRBConstr[] { c[i] };
double[] coeffs = new double[] { -1 };
feasmodel.addVar(0.0, GRB.INFINITY, 1.0, GRB.CONTINUOUS, constrs,
                 coeffs, "ArtN_" + c[i].get(GRB.StringAttr.ConstrName));
```

```
feasmodel.addVar(
    obj=1.0, name=f"ArtN_{c.ConstrName}", column=gp.Column([-1], [c])
)
```

We use the `column` argument of the `addVar` method to specify the set of constraints in which the new variable participates, as well as the associated coefficients. In this example, the new variable only participates in the constraint to be relaxed. Default values are used here for all variables attributes except the objective and the variable name.

```
Dim constrs As GRBConstr() = New GRBConstr() {c(i)}
Dim coeffs As Double() = New Double() {-1}
feasmodel.AddVar(0.0, GRB.INFINITY, 1.0, GRB.CONTINUOUS, _
                 constrs, coeffs, _
                 "ArtN_" & c(i).ConstrName)
```

1.1.6 Change parameters

Examples

batchmode, *callback*, *fixanddive*, *lp*, *lpmethod*, *mip2*, *multiscenario*, *params*, *sensitivity*, *workforce_batchmode*

This section illustrates the use of Gurobi parameters. *Example params* reads a MIP model from a file, then solves the model using four different values of the MIPFocus parameter, running for five seconds per value (MIPFocus chooses the high-level strategy that the MIP solver uses to solve the problem). It then chooses the parameter value that produced the smallest MIP gap, and continues solving the model until it achieves optimality.

The mechanics of setting a parameter are quite simple. To set the MIPFocus parameter in different APIs, do the following:

C

C++

C#

Java

Python

Visual Basic

```
error = GRBsetintparam(modelenv, "MIPFocus", i);
if (error) goto QUIT;
```

```
m->set(GRB_IntParam_MIPFocus, i);
```

```
m.Parameters.MIPFocus = i;
```

```
m.set(GRB.IntParam.MIPFocus, i);
```

```
m.Params.MIPFocus = i
```

```
m.Parameters.MIPFocus = i
```

Note: We should add one quick comment about how parameter settings propagate between different models. When we set the TimeLimit parameter on a model, then make a copy of that model, the parameter setting is carried over to the copy. When we set the MIPFocus parameter on the copy, that parameter change has no effect on the other copies, nor on the original model.

1.1.7 Diagnose and cope with infeasibility

Examples

feasopt, *lp*, *multiscenario*, *sensitivity*, *workforce1*, *workforce2*, *workforce3*

When solving optimization models, there are some situations where the specified constraints cannot be satisfied. When this happens, you often need to either identify and repair the root cause of the infeasibility, or alternatively find a set of constraints to relax in order to obtain a feasible model. The *workforce1 example*, *workforce2 example*, and *workforce3 example* illustrate these different strategies.

Starting with the simplest of the three examples, *workforce1 example* formulates a simple workforce scheduling model and solves it. If the model is infeasible, it computes an Irreducible Inconsistent Subsystem (IIS). The user can then inspect this information to understand and hopefully address the source of the infeasibility in the model.

Example workforce2 is similar, except that if the model is infeasible, the example repeatedly identifies an IIS and removes one of the associated constraints from the model until the model becomes feasible. Note that it is sufficient to remove one constraint from the IIS to address that source of infeasibility, but that one IIS may not capture all sources of infeasibility. It is therefore necessary to repeat the process until the model is feasible.

Example workforce3 takes a different approach to addressing infeasibility. Rather than identifying and removing IIS members, it allows the constraints of the model to be relaxed. Like the *feasopt example*, an artificial variable is added to each constraint. The example sets the objective on the original variables to zero, and then solves a model that minimizes the total magnitude of the constraint relaxation.

The *feasopt example* demonstrates another approach to relaxing an infeasible model. It computes a *feasibility relaxation* for the infeasible model. A feasibility relaxation is a model that, when solved, minimizes the amount by which the solution violates the bounds and linear constraints of the original model. This method is invoked as follows:

C

C++

C#

Java

Python

Visual Basic

```
error = GRBfeasrelax(feasmodel, GRB_FEASRELAX_LINEAR, 1, NULL, NULL, rhspen, &feasobj);
if (error) goto QUIT;
```

```
feasmodel1.feasRelax(GRB_FEASRELAX_LINEAR, true, false, true);
```

```
feasmodel1.FeasRelax(GRB.FEASRELAX_LINEAR, true, false, true);
```

```
feasmodel1.feasRelax(GRB.FEASRELAX_LINEAR, true, false, true);
```

```
feasmodel1.feasRelaxS(0, True, False, True)
```

```
feasmodel1.FeasRelax(GRB.FEASRELAX_LINEAR, true, false, true)
```

The arguments to this method select the objective function for the relaxed model, the specific set of bounds and constraints that are allowed to be relaxed, and the penalties for relaxing specific bounds and constraints.

1.1.8 MIP starts

Examples

facility, *sensitivity*

A MIP modeler often knows how to compute a feasible solution to their problem. In cases where the MIP solver is slow in finding an initial feasible solution, it can be helpful for the modeler to provide a feasible solution along with the model itself. This is done through the Start attribute on the variables. This is illustrated in the *facility examples*.

The *facility examples* solves a simple facility location problem. The model contains a set of warehouses, and a set of plants that produce the products required in the warehouses. Each plant has a maximum production capacity and a fixed operating cost. Additionally, there is a cost associated with shipping products from a plant to a warehouse. The goal is to decide which plants should satisfy the demand for the product, given the associated capacities and costs.

The example uses a simple heuristic for choosing an initial solution: it closes the plant with the highest fixed cost. The associated solution may not be optimal, but it could produce a reasonable starting solution for the MIP optimization. The MIP start is passed to the MIP solver by setting the Start attribute before the optimization begins. In the different APIs, we set the start attribute to open all plants using the following code:

C

C++

C#

Java

Python

Visual Basic

```
/* First, open all plants */
for (p = 0; p < nPlants; ++p)
{
  error = GRBsetdblattrelement(model, "Start", opencol(p), 1.0);
  if (error) goto QUIT;
}
```

```
// First, open all plants
for (p = 0; p < nPlants; ++p)
{
  open[p].set(GRB_DoubleAttr_Start, 1.0);
}
```

```
// First, open all plants
for (int p = 0; p < nPlants; ++p) {
  open[p].Start = 1.0;
}
```

```
// First, open all plants
for (int p = 0; p < nPlants; ++p) {
  open[p].set(GRB.DoubleAttr.Start, 1.0);
}
```

```
# First open all plants
for p in plants:
    open[p].Start = 1.0
```

```
' First, open all plants
For p As Integer = 0 To nPlants - 1
    open(p).Start = 1.0
Next
```

When you run the example, the MIP solver reports that the start produced a feasible initial solution:

```
User MIP start produced solution with objective 210500 (0.01s)
Loaded user MIP start with objective 210500
```

This initial solution turns out to be optimal for the sample data. Although the computation difference is insignificant for this tiny example, providing a good starting solution can sometimes help for more difficult models.

Note: The MIP start in this example only specifies values for some of the variables – the variables that determine which plants to leave open and which plants to close. The Gurobi MIP solve uses whatever start information is provided to try to construct a complete solution.

1.1.9 Model-data separation in Python

Examples (Python only)

diet2, *diet3*, *diet4*

When building an optimization model in a modeling language, it is typical to separate the optimization model itself from the data used to create an instance of the model. These two model ingredients are often stored in completely different files. We show how a similar result can be achieved in our Python interface with our *diet2 example*, *diet3 example* and *diet4 example*. These examples illustrate alternate approaches to providing data to the optimization model: *diet2 example* embeds the data in the source file, *diet3 example* reads the data from an SQL database (using the Python `sqlite3` package), and *diet4 example* reads the data from an Excel spreadsheet (using the Python `xlrd` package). *dietmodel.py* contains the optimization model itself. The same model is used by *diet2 example*, *diet3 example* and *diet4 example*.

The key construct that enables the separation of the model from the data is the Python module. A module is simply a set of functions and variables, stored in a file. You import a module into a program using the `import` statement. *diet2 example*, *diet3 example* and *diet4 example* all populate a set of variables, and then pass them to the `solve` function of the *dietmodel module* using the following pair of statements:

```
import dietmodel
dietmodel.solve(categories, minNutrition, maxNutrition, foods, cost, nutritionValues)
```

The first statement imports the *dietmodel module*, which must be stored in file *dietmodel.py* in the current directory. The second passes the model data to the `solve` function in the newly imported module.

1.1.10 Callbacks

Examples

callback

The final example we consider is the *callback example*, which demonstrates the use of Gurobi callbacks. Callbacks are used to report on the progress of the optimization or to modify the behavior of the Gurobi solver. To use a callback, the user writes a routine that implements the desired behavior. The routine is passed to the Gurobi Optimizer when optimization begins, and the routine is called regularly during the optimization process. One argument of the user routine is a `where` value, which indicates from where in the optimization process the callback is invoked. The user callback routine can call the optimization library to query certain values. We refer the reader to the callback section of the Gurobi Reference Manual for more precise details.

Our callback example implements a simple termination scheme: the user passes a node count (`limit`) into the callback, and the callback asks the optimizer to terminate when that node count is reached. This is implemented as follows:

C

C++

C#

Java

Python

Visual Basic

```
double nodecnt;
GRBcbget(cbdata, where, GRB_CB_MIP_NODCNT, &nodecnt);
if (nodecnt > limit)
  GRBterminate(model);
```

```
double nodecnt = getDoubleInfo(GRB_CB_MIP_NODCNT);
if (nodecnt > limit)
  abort();
```

```
double nodecnt = GetDoubleInfo(GRB.Callback.MIP_NODCNT);
if (nodecnt > limit)
  Abort();
```

```
double nodecnt = getDoubleInfo(GRB.CB_MIP_NODCNT);
if (nodecnt > limit)
  abort();
```

```
nodecnt = model.cbGet(GRB.Callback.MIP_NODCNT)
if nodecnt > model._mynodelimit:
    model.terminate()
```

```
Dim nodecnt As Double = GetDoubleInfo(GRB.Callback.MIP_NODCNT)
If nodecnt > limit Then
    Abort()
End If
```

Our *callback example* also prints progress information.

C

C++

C#

Java

Python

Visual Basic

```
GRBcbget(cbdata, where, GRB_CB_MIP_NODCNT, &nodecnt);
if (nodecnt - mydata->lastmsg >= 100) {
  ...
  printf("%7.0f ...", nodecnt, ...);
}
```

```
double nodecnt = getDoubleInfo(GRB_CB_MIP_NODCNT);
if (nodecnt - lastnode >= 100) {
  lastnode = nodecnt;
  ...
  cout << nodecnt << " " << ...;
}
```

```
double nodecnt = GetDoubleInfo(GRB.Callback.MIP_NODCNT);
if (nodecnt - lastnode >= 100) {
  lastnode = nodecnt;
  ...
  Console.WriteLine(nodecnt + " " ...);
}
```

```
double nodecnt = getDoubleInfo(GRB.CB_MIP_NODCNT);
if (nodecnt - lastnode >= 100) {
  lastnode = nodecnt;
  ...
  System.out.println(nodecnt + " " ...);
}
```

```
nodecnt = model.cbGet(GRB.Callback.MIP_NODCNT)
if nodecnt % 100 == 0:
    print(f"{nodecnt} ...")
```

```
Dim nodecnt As Double = GetDoubleInfo(GRB.Callback.MIP_NODCNT)
If nodecnt - lastnode >= 100 Then
    lastnode = nodecnt
    ...
    Console.WriteLine(nodecnt & " "  ...)
End If
```

CHAPTER

TWO

EXAMPLE SOURCE CODE

We have included source code for all of the distributed examples in this section. The identical example source code is included in the `examples` directory in the Gurobi distribution.

2.1 API oriented

2.1.1 C Examples

This section includes source code for all of the Gurobi C examples. The same source code can be found in the `examples/c` directory of the Gurobi distribution.

batchmode_c.c

```c
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, solves it in batch mode,
 * and prints the JSON solution string. */

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include <time.h>
#include <string.h>
#if defined (WIN32) || defined (WIN64)
#include <Windows.h>
#define sleep(n) Sleep(1000*n)
#else
#include <unistd.h>
#endif
#include "gurobi_c.h"

/* setup gurobi environment */
int setupbatchconnection(GRBenv **envP)
{
  int     error = 0;
  GRBenv *env   = NULL;

  /* setup a batch environment */
```

(continues on next page)

(continued from previous page)

```
  error = GRBemptyenv(envP);
  if (error) goto QUIT;
  env = *envP;
  error = GRBsetintparam(env, "CSBatchMode", 1);
  if (error) goto QUIT;
  error = GRBsetstrparam(env, "LogFile", "batchmode.log");
  if (error) goto QUIT;
  error = GRBsetstrparam(env, "CSManager", "http://localhost:61080");
  if (error) goto QUIT;
  error = GRBsetstrparam(env, "UserName", "gurobi");
  if (error) goto QUIT;
  error = GRBsetstrparam(env, "ServerPassword", "pass");
  if (error) goto QUIT;
  error = GRBstartenv(env);
  if (error) goto QUIT;

QUIT:

  if (error) {
    printf("Failed to setup environment, error code %d\n", error);
  } else {
    printf("Successfully created environment\n");
  }
  return error;
}

/* display batch-error code if any */
void batcherrorinfo(GRBbatch *batch)
{
  int error = 0;
  int errorCode;
  char *errorMsg;
  char *BatchID;

  if (!batch) goto QUIT;

  /* query the last error code */
  error = GRBgetbatchintattr(batch, "BatchErrorCode", &errorCode);
  if (error || !errorCode) goto QUIT;

  /* query the last error message */
  error = GRBgetbatchstrattr(batch, "BatchErrorMessage", &errorMsg);
  if (error) goto QUIT;

  error = GRBgetbatchstrattr(batch, "BatchID", &BatchID);
  if (error) goto QUIT;

  printf("Batch ID %s Error Code %d (%s)\n", BatchID, errorCode, errorMsg);

QUIT:

  return;
```

(continues on next page)

(continued from previous page)

```
}

/* create a batch request for given problem file */
int newbatchrequest(const char *filename,
                    char       *BatchID)
{
  int       error = 0;
  GRBenv   *env   = NULL;
  GRBenv   *menv  = NULL;
  GRBmodel *model = NULL;
  char tag[128];
  int cols, j;

  /* setup a batch connection */
  error = setupbatchconnection(&env);
  if (error) goto QUIT;

  /* read a model */
  error = GRBreadmodel(env, filename, &model);
  if (error) goto QUIT;

  /* set some params */
  menv = GRBgetenv(model);
  assert(menv != NULL);
  error = GRBsetdblparam(menv, "MIPGap", 0.01);
  if (error) goto QUIT;
  /* for extra detailed information on JSON solution string */
  error = GRBsetintparam(menv, "JSONSolDetail", 1);
  if (error) goto QUIT;

  /* setup some tags, we need tags to be able to query results later on */
  error = GRBgetintattr(model, "NumVars", &cols);
  if (error) goto QUIT;

  if (cols > 10) cols = 10;
  for (j = 0; j < cols; j++) {
    sprintf(tag, "MyUniqueVariableID%d",j);
    error = GRBsetstrattrelement(model, "VTag", j, tag);
  }

  /* submit batch request to the Manager */
  error = GRBoptimizebatch(model, BatchID);
  if (error) goto QUIT;

QUIT:

  if (error) {
    printf("Failed to submit a new batch request, error code %d\n", error);
  } else {
    printf("Successfully submitted new batch request %s\n", BatchID);
  }
  GRBfreemodel(model);
```

(continues on next page)

(continued from previous page)

```
  GRBfreeenv(env);
  return error;
}

/* wait for final bstatus */
int waitforfinalstatus(const char *BatchID)
{
  int       error = 0;
  GRBenv   *env   = NULL;
  GRBbatch *batch = NULL;
  time_t start, current;
  int bstatus;

  /* setup a batch connection */
  error = setupbatchconnection(&env);
  if (error) goto QUIT;

  /* create batch-object */
  error = GRBgetbatch(env, BatchID, &batch);
  if (error) goto QUIT;

  /* query bstatus, and wait for completed */
  error = GRBgetbatchintattr(batch, "BatchStatus",  &bstatus);
  if (error) goto QUIT;
  start = time(NULL);

  while (bstatus == GRB_BATCH_SUBMITTED) {

    /* abort if taking too long */
    current = time(NULL);
    if (current - start >= 3600) {
      /* request to abort the batch */
      error = GRBabortbatch(batch);
      if (error) goto QUIT;
    }

    /* do not bombard the server */
    sleep(1u);

    /* update local attributes */
    error = GRBupdatebatch(batch);
    if (error) goto QUIT;

    /* query bstatus */
    error = GRBgetbatchintattr(batch, "BatchStatus",  &bstatus);
    if (error) goto QUIT;

    /* deal with failed bstatus */
    if (bstatus == GRB_BATCH_FAILED) {
      /* retry the batch request */
      error = GRBretrybatch(batch);
      if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
      bstatus = GRB_BATCH_SUBMITTED;
    }
  }


QUIT:

  if (error) {
    printf("Failed to wait for final bstatus, error code %d\n", error);
  } else {
    printf("Final Batch Status %d\n", bstatus);
  }
  batcherrorinfo(batch);
  /* release local resources */
  GRBfreebatch(batch);
  GRBfreeenv(env);
  return error;
}

/* final report on batch request */
int finalreport(const char *BatchID)
{
  int       error   = 0;
  GRBenv   *env     = NULL;
  GRBbatch *batch   = NULL;
  char     *jsonsol = NULL;
  int bstatus;

  /* setup a batch connection */
  error = setupbatchconnection(&env);
  if (error) goto QUIT;

  /* create batch object */
  error = GRBgetbatch(env, BatchID, &batch);
  if (error) goto QUIT;

  /* query bstatus, and wait for completed */
  error = GRBgetbatchintattr(batch, "BatchStatus",  &bstatus);
  if (error) goto QUIT;

  /* display depending on batch bstatus */
  switch (bstatus) {
    case GRB_BATCH_CREATED:
      printf("Batch is 'CREATED'\n");
      printf("maybe batch-creation process was killed?\n");
      break;
    case GRB_BATCH_SUBMITTED:
      printf("Batch is 'SUBMITTED'\n");
      printf("Some other user re-submitted this Batch object?\n");
      break;
    case GRB_BATCH_ABORTED:
      printf("Batch is 'ABORTED'\n");
```

(continues on next page)

(continued from previous page)

```
      break;
    case GRB_BATCH_FAILED:
      printf("Batch is 'FAILED'\n");
      break;
    case GRB_BATCH_COMPLETED:

      /* print JSON solution into string */
      error = GRBgetbatchjsonsolution(batch, &jsonsol);
      if (error) goto QUIT;
      printf("JSON solution: %s\n", jsonsol);

      /* save solution into a file */
      error = GRBwritebatchjsonsolution(batch, "batch-sol.json.gz");
      if (error) goto QUIT;
      break;
    default:
      printf("This should not happen, probably points to a"
             " user-memory corruption problem\n");
      exit(EXIT_FAILURE);
      break;
  }

QUIT:

  if (error) {
    printf("Failed to perform final report, error code %d\n", error);
  } else {
    printf("Reporting done\n");
  }
  batcherrorinfo(batch);

  if (jsonsol)
    GRBfree(jsonsol);

  GRBfreebatch(batch);
  GRBfreeenv(env);
  return error;
}

/* remove batch ID from manager */
int discardbatch(const char *BatchID)
{
  int       error   = 0;
  GRBenv   *env     = NULL;
  GRBbatch *batch   = NULL;

  /* setup a batch connection */
  error = setupbatchconnection(&env);
  if (error) goto QUIT;

  /* create batch object */
  error = GRBgetbatch(env, BatchID, &batch);
```

(continues on next page)

(continued from previous page)

```
  if (error) goto QUIT;

  /* discard the batch object in the manager */
  error = GRBdiscardbatch(batch);
  if (error) goto QUIT;

QUIT:

  batcherrorinfo(batch);
  GRBfreebatch(batch);
  GRBfreeenv(env);
  return error;
}

int
main(int    argc,
     char **argv)
{
  int error = 0;
  char BatchID[GRB_MAX_STRLEN+1];

  /* ensure enough parameters */
  if (argc < 2) {
    fprintf(stderr, "Usage: %s filename\n", argv[0]);
    goto QUIT;
  }

  /* create a new batch request */
  error = newbatchrequest(argv[1], BatchID);
  if (error) goto QUIT;

  /* wait for final bstatus */
  error = waitforfinalstatus(BatchID);
  if (error) goto QUIT;

  /* query final bstatus, and if completed, print JSON solution */
  error = finalreport(BatchID);
  if (error) goto QUIT;

  /* eliminate batch from the manager */
  error = discardbatch(BatchID);
  if (error) goto QUIT;

QUIT:

  return error;
}
```

bilinear_c.c

```c
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple bilinear model:

     maximize    x
     subject to  x + y + z <= 10
                 x * y <= 2          (bilinear inequality)
                 x * z + y * z == 1  (bilinear equality)
                 x, y, z non-negative (x integral in second version)
*/

#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  double    sol[3];
  int       ind[3];
  double    val[3];
  double    obj[] = {1, 0, 0};
  int       qrow[2];
  int       qcol[2];
  double    qval[2];
  int       optimstatus;
  double    objval;

  /* Create environment */

  error = GRBloadenv(&env, "bilinear.log");
  if (error) goto QUIT;

  /* Create an empty model */

  error = GRBnewmodel(env, &model, "bilinear", 0, NULL, NULL, NULL, NULL,
                      NULL);
  if (error) goto QUIT;


  /* Add variables */

  error = GRBaddvars(model, 3, 0, NULL, NULL, NULL, obj, NULL, NULL, NULL,
                     NULL);
  if (error) goto QUIT;

  /* Change sense to maximization */
```

(continues on next page)

(continued from previous page)

```
error = GRBsetintattr(model, GRB_INT_ATTR_MODELSENSE, GRB_MAXIMIZE);
if (error) goto QUIT;

/* Linear constraint: x + y + z <= 10 */

ind[0] = 0; ind[1] = 1; ind[2] = 2;
val[0] = 1; val[1] = 1; val[2] = 1;

error = GRBaddconstr(model, 3, ind, val, GRB_LESS_EQUAL, 10.0, "c0");
if (error) goto QUIT;

/* Bilinear inequality: x * y <= 2 */

qrow[0] = 0; qcol[0] = 1; qval[0] = 1.0;

error = GRBaddqconstr(model, 0, NULL, NULL, 1, qrow, qcol, qval,
                      GRB_LESS_EQUAL, 2.0, "bilinear0");
if (error) goto QUIT;

/* Bilinear equality: x * z + y * z == 1 */

qrow[0] = 0; qcol[0] = 2; qval[0] = 1.0;
qrow[1] = 1; qcol[1] = 2; qval[1] = 1.0;

error = GRBaddqconstr(model, 0, NULL, NULL, 2, qrow, qcol, qval,
                      GRB_EQUAL, 1, "bilinear1");
if (error) goto QUIT;

/* Optimize model */

error = GRBoptimize(model);
if (error) goto QUIT;

/* Write model to 'bilinear.lp' */

error = GRBwrite(model, "bilinear.lp");
if (error) goto QUIT;

/* Capture solution information */

error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
if (error) goto QUIT;

error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
if (error) goto QUIT;

error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 3, sol);
if (error) goto QUIT;

printf("\nOptimization complete\n");
if (optimstatus == GRB_OPTIMAL) {
```

(continues on next page)

(continued from previous page)

```
    printf("Optimal objective: %.4e\n", objval);

    printf("  x=%.2f, y=%.2f, z=%.2f\n", sol[0], sol[1], sol[2]);
  } else if (optimstatus == GRB_INF_OR_UNBD) {
    printf("Model is infeasible or unbounded\n");
  } else {
    printf("Optimization was stopped early\n");
  }

  /* Now constrain 'x' to be integral and solve again */

  error = GRBsetcharattrelement(model, GRB_CHAR_ATTR_VTYPE, 0, GRB_INTEGER);
  if (error) goto QUIT;

  error = GRBoptimize(model);
  if (error) goto QUIT;

  /* Capture solution information */

  error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
  if (error) goto QUIT;

  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;

  error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 3, sol);
  if (error) goto QUIT;

  printf("\nOptimization complete\n");
  if (optimstatus == GRB_OPTIMAL) {
    printf("Optimal objective: %.4e\n", objval);

    printf("  x=%.2f, y=%.2f, z=%.2f\n", sol[0], sol[1], sol[2]);
  } else if (optimstatus == GRB_INF_OR_UNBD) {
    printf("Model is infeasible or unbounded\n");
  } else {
    printf("Optimization was stopped early\n");
  }

QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */

  GRBfreemodel(model);
```

(continues on next page)

(continued from previous page)

```
  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

callback_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/*
   This example reads a model from a file, sets up a callback that
   monitors optimization progress and implements a custom
   termination strategy, and outputs progress information to the
   screen and to a log file.

   The termination strategy implemented in this callback stops the
   optimization of a MIP model once at least one of the following two
   conditions have been satisfied:
     1) The optimality gap is less than 10%
     2) At least 10000 nodes have been explored, and an integer feasible
        solution has been found.
   Note that termination is normally handled through Gurobi parameters
   (MIPGap, NodeLimit, etc.).  You should only use a callback for
   termination if the available parameters don't capture your desired
   termination criterion.
*/

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"

/* Define structure to pass my data to the callback function */

struct callback_data {
  double  lastiter;
  double  lastnode;
  double *solution;
  FILE   *logfile;
};

/* Define my callback function */

int __stdcall
mycallback(GRBmodel *model,
           void     *cbdata,
           int       where,
           void     *usrdata)
```

(continues on next page)

(continued from previous page)

```
{
  struct callback_data *mydata = (struct callback_data *) usrdata;

  if (where == GRB_CB_POLLING) {
    /* Ignore polling callback */
  } else if (where == GRB_CB_PRESOLVE) {
    /* Presolve callback */
    int cdels, rdels;
    GRBcbget(cbdata, where, GRB_CB_PRE_COLDEL, &cdels);
    GRBcbget(cbdata, where, GRB_CB_PRE_ROWDEL, &rdels);
    if (cdels || rdels) {
      printf("%7d columns and %7d rows are removed\n", cdels, rdels);
    }
  } else if (where == GRB_CB_SIMPLEX) {
    /* Simplex callback */
    double itcnt, obj, pinf, dinf;
    int    ispert;
    char   ch;
    GRBcbget(cbdata, where, GRB_CB_SPX_ITRCNT, &itcnt);
    if (itcnt - mydata->lastiter >= 100) {
      mydata->lastiter = itcnt;
      GRBcbget(cbdata, where, GRB_CB_SPX_OBJVAL, &obj);
      GRBcbget(cbdata, where, GRB_CB_SPX_ISPERT, &ispert);
      GRBcbget(cbdata, where, GRB_CB_SPX_PRIMINF, &pinf);
      GRBcbget(cbdata, where, GRB_CB_SPX_DUALINF, &dinf);
      if      (ispert == 0) ch = ' ';
      else if (ispert == 1) ch = 'S';
      else                  ch = 'P';
      printf("%7.0f %14.7e%c %13.6e %13.6e\n", itcnt, obj, ch, pinf, dinf);
    }
  } else if (where == GRB_CB_MIP) {
    /* General MIP callback */
    double nodecnt, objbst, objbnd, actnodes, itcnt;
    int    solcnt, cutcnt;
    GRBcbget(cbdata, where, GRB_CB_MIP_NODCNT, &nodecnt);
    GRBcbget(cbdata, where, GRB_CB_MIP_OBJBST, &objbst);
    GRBcbget(cbdata, where, GRB_CB_MIP_OBJBND, &objbnd);
    GRBcbget(cbdata, where, GRB_CB_MIP_SOLCNT, &solcnt);
    if (nodecnt - mydata->lastnode >= 100) {
      mydata->lastnode = nodecnt;
      GRBcbget(cbdata, where, GRB_CB_MIP_NODLFT, &actnodes);
      GRBcbget(cbdata, where, GRB_CB_MIP_ITRCNT, &itcnt);
      GRBcbget(cbdata, where, GRB_CB_MIP_CUTCNT, &cutcnt);
      printf("%7.0f %7.0f %8.0f %13.6e %13.6e %7d %7d\n",
             nodecnt, actnodes, itcnt, objbst, objbnd, solcnt, cutcnt);
    }
    if (fabs(objbst - objbnd) < 0.1 * (1.0 + fabs(objbst))) {
      printf("Stop early - 10%% gap achieved\n");
      GRBterminate(model);
    }
    if (nodecnt >= 10000 && solcnt) {
      printf("Stop early - 10000 nodes explored\n");
```

(continues on next page)

(continued from previous page)

```
      GRBterminate(model);
    }
  } else if (where == GRB_CB_MIPSOL) {
    /* MIP solution callback */
    double nodecnt, obj;
    int    solcnt;
    GRBcbget(cbdata, where, GRB_CB_MIPSOL_NODCNT, &nodecnt);
    GRBcbget(cbdata, where, GRB_CB_MIPSOL_OBJ, &obj);
    GRBcbget(cbdata, where, GRB_CB_MIPSOL_SOLCNT, &solcnt);
    GRBcbget(cbdata, where, GRB_CB_MIPSOL_SOL, mydata->solution);
    printf("**** New solution at node %.0f, obj %g, sol %d, x[0] = %.2f ****\n",
           nodecnt, obj, solcnt, mydata->solution[0]);
  } else if (where == GRB_CB_MIPNODE) {
    int status;
    /* MIP node callback */
    printf("**** New node ****\n");
    GRBcbget(cbdata, where, GRB_CB_MIPNODE_STATUS, &status);
    if (status == GRB_OPTIMAL) {
      GRBcbget(cbdata, where, GRB_CB_MIPNODE_REL, mydata->solution);
      GRBcbsolution(cbdata, mydata->solution, NULL);
    }
  } else if (where == GRB_CB_BARRIER) {
    /* Barrier callback */
    int    itcnt;
    double primobj, dualobj, priminf, dualinf, compl;
    GRBcbget(cbdata, where, GRB_CB_BARRIER_ITRCNT, &itcnt);
    GRBcbget(cbdata, where, GRB_CB_BARRIER_PRIMOBJ, &primobj);
    GRBcbget(cbdata, where, GRB_CB_BARRIER_DUALOBJ, &dualobj);
    GRBcbget(cbdata, where, GRB_CB_BARRIER_PRIMINF, &priminf);
    GRBcbget(cbdata, where, GRB_CB_BARRIER_DUALINF, &dualinf);
    GRBcbget(cbdata, where, GRB_CB_BARRIER_COMPL, &compl);
    printf("%d %.4e %.4e %.4e %.4e %.4e\n",
           itcnt, primobj, dualobj, priminf, dualinf, compl);
  } else if (where == GRB_CB_IIS) {
    int constrmin, constrmax, constrguess, boundmin, boundmax, boundguess;
    GRBcbget(cbdata, where, GRB_CB_IIS_CONSTRMIN, &constrmin);
    GRBcbget(cbdata, where, GRB_CB_IIS_CONSTRMAX, &constrmax);
    GRBcbget(cbdata, where, GRB_CB_IIS_CONSTRGUESS, &constrguess);
    GRBcbget(cbdata, where, GRB_CB_IIS_BOUNDMIN, &boundmin);
    GRBcbget(cbdata, where, GRB_CB_IIS_BOUNDMAX, &boundmax);
    GRBcbget(cbdata, where, GRB_CB_IIS_BOUNDGUESS, &boundguess);
    printf("IIS: %d,%d,%d %d,%d,%d\n",
           constrmin, constrmax, constrguess,
           boundmin, boundmax, boundguess);
  } else if (where == GRB_CB_MESSAGE) {
    /* Message callback */
    char *msg;
    GRBcbget(cbdata, where, GRB_CB_MSG_STRING, &msg);
    fprintf(mydata->logfile, "%s", msg);
  }
  return 0;
}
```

(continues on next page)

(continued from previous page)

```
int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  int       numvars, solcount, optimstatus, j;
  double    objval, x;
  char     *varname;
  struct callback_data mydata;

  mydata.lastiter = -GRB_INFINITY;
  mydata.lastnode = -GRB_INFINITY;
  mydata.solution = NULL;
  mydata.logfile  = NULL;

  if (argc < 2) {
    fprintf(stderr, "Usage: callback_c filename\n");
    goto QUIT;
  }

  /* Open log file */
  mydata.logfile = fopen("cb.log", "w");
  if (!mydata.logfile) {
    fprintf(stderr, "Cannot open cb.log for callback message\n");
    goto QUIT;
  }

  /* Create environment */

  error = GRBloadenv(&env, NULL);
  if (error) goto QUIT;

  /* Turn off display and heuristics */

  error = GRBsetintparam(env, GRB_INT_PAR_OUTPUTFLAG, 0);
  if (error) goto QUIT;

  error = GRBsetdblparam(env, GRB_DBL_PAR_HEURISTICS, 0.0);
  if (error) goto QUIT;

  /* Read model from file */

  error = GRBreadmodel(env, argv[1], &model);
  if (error) goto QUIT;

  /* Allocate space for solution */

  error = GRBgetintattr(model, GRB_INT_ATTR_NUMVARS, &numvars);
  if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
  mydata.solution = malloc(numvars*sizeof(double));
  if (mydata.solution == NULL) {
    fprintf(stderr, "Failed to allocate memory\n");
    exit(1);
  }

  /* Set callback function */

  error = GRBsetcallbackfunc(model, mycallback, (void *) &mydata);
  if (error) goto QUIT;

  /* Solve model */

  error = GRBoptimize(model);
  if (error) goto QUIT;

  /* Capture solution information */

  printf("\nOptimization complete\n");

  error = GRBgetintattr(model, GRB_INT_ATTR_SOLCOUNT, &solcount);
  if (error) goto QUIT;

  error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
  if (error) goto QUIT;

  if (solcount == 0) {
    printf("No solution found, optimization status = %d\n", optimstatus);
    goto QUIT;
  }

  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;

  printf("Solution found, objective = %.4e\n", objval);

  for ( j = 0; j < numvars; ++j ) {
    error = GRBgetstrattrelement(model, GRB_STR_ATTR_VARNAME, j, &varname);
    if (error) goto QUIT;
    error = GRBgetdblattrelement(model, GRB_DBL_ATTR_X, j, &x);
    if (error) goto QUIT;
    if (x != 0.0) {
      printf("%s %f\n", varname, x);
    }
  }

QUIT:

  /* Error reporting */

  if (error) {
```

(continues on next page)

(continued from previous page)

```
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Close log file */

  if (mydata.logfile)
    fclose(mydata.logfile);

  /* Free solution */

  if (mydata.solution)
    free(mydata.solution);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

dense_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QP model:

     minimize    x + y + x^2 + x*y + y^2 + y*z + z^2
     subject to  x + 2 y + 3 z >= 4
                 x +   y       >= 1
                 x, y, z non-negative

   The example illustrates the use of dense matrices to store A and Q
   (and dense vectors for the other relevant data).  We don't recommend
   that you use dense matrices, but this example may be helpful if you
   already have your data in this format.
*/

#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

/*
  Solve an LP/QP/MILP/MIQP represented using dense matrices.  This
  routine assumes that A and Q are both stored in row-major order.
  It returns 1 if the optimization succeeds.  When successful,
```

(continues on next page)

(continued from previous page)

```
  it returns the optimal objective value in 'objvalP', and the
  optimal solution vector in 'solution'.
*/

static int
dense_optimize(GRBenv *env,
               int     rows,
               int     cols,
               double *c,     /* linear portion of objective function */
               double *Q,     /* quadratic portion of objective function */
               double *A,     /* constraint matrix */
               char   *sense, /* constraint senses */
               double *rhs,   /* RHS vector */
               double *lb,    /* variable lower bounds */
               double *ub,    /* variable upper bounds */
               char   *vtype, /* variable types (continuous, binary, etc.) */
               double *solution,
               double *objvalP)
{
  GRBmodel *model = NULL;
  int       i, j, optimstatus;
  int       error = 0;
  int       success = 0;

  /* Create an empty model */

  error = GRBnewmodel(env, &model, "dense", cols, c, lb, ub, vtype, NULL);
  if (error) goto QUIT;

  error = GRBaddconstrs(model, rows, 0, NULL, NULL, NULL, sense, rhs, NULL);
  if (error) goto QUIT;

  /* Populate A matrix */

  for (i = 0; i < rows; i++) {
    for (j = 0; j < cols; j++) {
      if (A[i*cols+j] != 0) {
        error = GRBchgcoeffs(model, 1, &i, &j, &A[i*cols+j]);
        if (error) goto QUIT;
      }
    }
  }

  /* Populate Q matrix */

  if (Q) {
    for (i = 0; i < cols; i++) {
      for (j = 0; j < cols; j++) {
        if (Q[i*cols+j] != 0) {
          error = GRBaddqpterms(model, 1, &i, &j, &Q[i*cols+j]);
          if (error) goto QUIT;
        }
```

(continues on next page)

(continued from previous page)

```
      }
    }
  }

  /* Optimize model */

  error = GRBoptimize(model);
  if (error) goto QUIT;

  /* Write model to 'dense.lp' */

  error = GRBwrite(model, "dense.lp");
  if (error) goto QUIT;

  /* Capture solution information */

  error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
  if (error) goto QUIT;

  if (optimstatus == GRB_OPTIMAL) {

    error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, objvalP);
    if (error) goto QUIT;

    error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, cols, solution);
    if (error) goto QUIT;

    success = 1;
  }

QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */

  GRBfreemodel(model);

  return success;
}

int
main(int   argc,
     char *argv[])
{
  GRBenv *env     = NULL;
  int     error   = 0;
```

(continues on next page)

(continued from previous page)

```
  double  c[]     = {1, 1, 0};
  double  Q[3][3] = {{1, 1, 0}, {0, 1, 1}, {0, 0, 1}};
  double  A[2][3] = {{1, 2, 3}, {1, 1, 0}};
  char    sense[] = {'>', '>'};
  double  rhs[]   = {4, 1};
  double  lb[]    = {0, 0, 0};
  double  sol[3];
  int     solved;
  double  objval;

  /* Create environment */

  error = GRBloadenv(&env, "dense.log");
  if (error) goto QUIT;

  /* Solve the model */

  solved = dense_optimize(env, 2, 3, c, &Q[0][0], &A[0][0], sense, rhs, lb,
                          NULL, NULL, sol, &objval);

  if (solved)
    printf("Solved: x=%.4f, y=%.4f, z=%.4f\n", sol[0], sol[1], sol[2]);

QUIT:

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

diet_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Solve the classic diet model, showing how to add constraints
   to an existing model. */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"

int printSolution(GRBmodel* model, int nCategories, int nFoods);


int
main(int   argc,
     char *argv[])
```

(continues on next page)

(continued from previous page)

```
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  int       i, j;
  int      *cbeg, *cind, idx;
  double   *cval, *rhs;
  char     *sense;

  /* Nutrition guidelines, based on
     USDA Dietary Guidelines for Americans, 2005
     http://www.health.gov/DietaryGuidelines/dga2005/ */

  const int nCategories = 4;
  char *Categories[] =
    { "calories", "protein", "fat", "sodium" };
  double minNutrition[] = { 1800, 91, 0, 0 };
  double maxNutrition[] = { 2200, GRB_INFINITY, 65, 1779 };

  /* Set of foods */
  const int nFoods = 9;
  char* Foods[] =
    { "hamburger", "chicken", "hot dog", "fries",
      "macaroni", "pizza", "salad", "milk", "ice cream" };
  double cost[] =
    { 2.49, 2.89, 1.50, 1.89, 2.09, 1.99, 2.49, 0.89, 1.59 };

  /* Nutrition values for the foods */
  double nutritionValues[][4] = {
                                  { 410, 24, 26, 730 },
                                  { 420, 32, 10, 1190 },
                                  { 560, 20, 32, 1800 },
                                  { 380, 4, 19, 270 },
                                  { 320, 12, 10, 930 },
                                  { 320, 15, 12, 820 },
                                  { 320, 31, 12, 1230 },
                                  { 100, 8, 2.5, 125 },
                                  { 330, 8, 10, 180 }
                                };

  /* Create environment */
  error = GRBloadenv(&env, "diet.log");
  if (error) goto QUIT;

  /* Create initial model */
  error = GRBnewmodel(env, &model, "diet", nFoods + nCategories,
                      NULL, NULL, NULL, NULL, NULL);
  if (error) goto QUIT;

  /* Initialize decision variables for the foods to buy */
  for (j = 0; j < nFoods; ++j)
  {
```

(continues on next page)

(continued from previous page)

```
  error = GRBsetdblattrelement(model, "Obj", j, cost[j]);
  if (error) goto QUIT;
  error = GRBsetstrattrelement(model, "VarName", j, Foods[j]);
  if (error) goto QUIT;
}

/* Initialize decision variables for the nutrition information,
   which we limit via bounds */
for (j = 0; j < nCategories; ++j)
{
  error = GRBsetdblattrelement(model, "LB", j + nFoods, minNutrition[j]);
  if (error) goto QUIT;
  error = GRBsetdblattrelement(model, "UB", j + nFoods, maxNutrition[j]);
  if (error) goto QUIT;
  error = GRBsetstrattrelement(model, "VarName", j + nFoods, Categories[j]);
  if (error) goto QUIT;
}

/* The objective is to minimize the costs */
error = GRBsetintattr(model, "ModelSense", GRB_MINIMIZE);
if (error) goto QUIT;

/* Nutrition constraints */
cbeg = malloc(sizeof(int) * nCategories);
if (!cbeg) goto QUIT;
cind = malloc(sizeof(int) * nCategories * (nFoods + 1));
if (!cind) goto QUIT;
cval = malloc(sizeof(double) * nCategories * (nFoods + 1));
if (!cval) goto QUIT;
rhs = malloc(sizeof(double) * nCategories);
if (!rhs) goto QUIT;
sense = malloc(sizeof(char) * nCategories);
if (!sense) goto QUIT;
idx = 0;
for (i = 0; i < nCategories; ++i)
{
  cbeg[i] = idx;
  rhs[i] = 0.0;
  sense[i] = GRB_EQUAL;
  for (j = 0; j < nFoods; ++j)
  {
    cind[idx] = j;
    cval[idx++] = nutritionValues[j][i];
  }
  cind[idx] = nFoods + i;
  cval[idx++] = -1.0;
}

error = GRBaddconstrs(model, nCategories, idx, cbeg, cind, cval, sense,
                      rhs, Categories);
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
  /* Solve */
  error = GRBoptimize(model);
  if (error) goto QUIT;
  error = printSolution(model, nCategories, nFoods);
  if (error) goto QUIT;

  printf("\nAdding constraint: at most 6 servings of dairy\n");
  cind[0] = 7;
  cval[0] = 1.0;
  cind[1] = 8;
  cval[1] = 1.0;
  error = GRBaddconstr(model, 2, cind, cval, GRB_LESS_EQUAL, 6.0,
                       "limit_dairy");
  if (error) goto QUIT;

  /* Solve */
  error = GRBoptimize(model);
  if (error) goto QUIT;
  error = printSolution(model, nCategories, nFoods);
  if (error) goto QUIT;



QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */

  free(cbeg);
  free(cind);
  free(cval);
  free(rhs);
  free(sense);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

(continues on next page)

(continued from previous page)

```
int printSolution(GRBmodel* model, int nCategories, int nFoods)
{
  int error, status, i, j;
  double obj, x;
  char* vname;

  error = GRBgetintattr(model, "Status", &status);
  if (error) return error;
  if (status == GRB_OPTIMAL)
  {
    error = GRBgetdblattr(model, "ObjVal", &obj);
    if (error) return error;
    printf("\nCost: %f\n\nBuy:\n", obj);
    for (j = 0; j < nFoods; ++j)
    {
      error = GRBgetdblattrelement(model, "X", j, &x);
      if (error) return error;
      if (x > 0.0001)
      {
        error = GRBgetstrattrelement(model, "VarName", j, &vname);
        if (error) return error;
        printf("%s %f\n", vname, x);
      }
    }
    printf("\nNutrition:\n");
    for (i = 0; i < nCategories; ++i)
    {
      error = GRBgetdblattrelement(model, "X", i + nFoods, &x);
      if (error) return error;
      error = GRBgetstrattrelement(model, "VarName", i + nFoods, &vname);
      if (error) return error;
      printf("%s %f\n", vname, x);
    }
  }
  else
  {
    printf("No solution\n");
  }

  return 0;
}
```

facility_c.c

```c
/* Copyright 2026, Gurobi Optimization, LLC */

/* Facility location: a company currently ships its product from 5 plants
   to 4 warehouses. It is considering closing some plants to reduce
   costs. What plant(s) should the company close, in order to minimize
   transportation and fixed costs?

   Based on an example from Frontline Systems:
   http://www.solver.com/disfacility.htm
   Used with permission.
 */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"


#define opencol(p)         p
#define transportcol(w,p)  nPlants*(w+1)+p
#define MAXSTR             128

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  int       p, w, col;
  int      *cbeg = NULL;
  int      *cind = NULL;
  int       idx, rowct;
  double   *cval = NULL;
  double   *rhs = NULL;
  char     *sense = NULL;
  char     vname[MAXSTR];
  int      cnamect = 0;
  char   **cname = NULL;
  double   maxFixed = -GRB_INFINITY, sol, obj;

  /* Number of plants and warehouses */
  const int nPlants = 5;
  const int nWarehouses = 4;

  /* Warehouse demand in thousands of units */
  double Demand[] = { 15, 18, 14, 20 };

  /* Plant capacity in thousands of units */
  double Capacity[] = { 20, 22, 17, 19, 18 };
```

(continues on next page)

(continued from previous page)

```
/* Fixed costs for each plant */
double FixedCosts[] =
  { 12000, 15000, 17000, 13000, 16000 };

/* Transportation costs per thousand units */
double TransCosts[4][5] = {
                            { 4000, 2000, 3000, 2500, 4500 },
                            { 2500, 2600, 3400, 3000, 4000 },
                            { 1200, 1800, 2600, 4100, 3000 },
                            { 2200, 2600, 3100, 3700, 3200 }
                          };

/* Create environment */
error = GRBloadenv(&env, "facility.log");
if (error) goto QUIT;

/* Create initial model */
error = GRBnewmodel(env, &model, "facility", nPlants * (nWarehouses + 1),
                    NULL, NULL, NULL, NULL, NULL);
if (error) goto QUIT;

/* Initialize decision variables for plant open variables */
for (p = 0; p < nPlants; ++p)
{
  col = opencol(p);
  error = GRBsetcharattrelement(model, "VType", col, GRB_BINARY);
  if (error) goto QUIT;
  error = GRBsetdblattrelement(model, "Obj", col, FixedCosts[p]);
  if (error) goto QUIT;
  sprintf(vname, "Open%i", p);
  error = GRBsetstrattrelement(model, "VarName", col, vname);
  if (error) goto QUIT;
}

/* Initialize decision variables for transportation decision variables:
   how much to transport from a plant p to a warehouse w */
for (w = 0; w < nWarehouses; ++w)
{
  for (p = 0; p < nPlants; ++p)
  {
    col = transportcol(w, p);
    error = GRBsetdblattrelement(model, "Obj", col, TransCosts[w][p]);
    if (error) goto QUIT;
    sprintf(vname, "Trans%i.%i", p, w);
    error = GRBsetstrattrelement(model, "VarName", col, vname);
    if (error) goto QUIT;
  }
}

/* The objective is to minimize the total fixed and variable costs */
error = GRBsetintattr(model, "ModelSense", GRB_MINIMIZE);
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
/* Make space for constraint data */
rowct = (nPlants > nWarehouses) ? nPlants : nWarehouses;
cbeg = malloc(sizeof(int) * rowct);
if (!cbeg) goto QUIT;
cind = malloc(sizeof(int) * (nPlants * (nWarehouses + 1)));
if (!cind) goto QUIT;
cval = malloc(sizeof(double) * (nPlants * (nWarehouses + 1)));
if (!cval) goto QUIT;
rhs = malloc(sizeof(double) * rowct);
if (!rhs) goto QUIT;
sense = malloc(sizeof(char) * rowct);
if (!sense) goto QUIT;
cname = calloc(rowct, sizeof(char*));
if (!cname) goto QUIT;

/* Production constraints
   Note that the limit sets the production to zero if
   the plant is closed */
idx = 0;
for (p = 0; p < nPlants; ++p)
{
  cbeg[p] = idx;
  rhs[p] = 0.0;
  sense[p] = GRB_LESS_EQUAL;
  cname[p] = malloc(sizeof(char) * MAXSTR);
  if (!cname[p]) goto QUIT;
  cnamect++;
  sprintf(cname[p], "Capacity%i", p);
  for (w = 0; w < nWarehouses; ++w)
  {
    cind[idx] = transportcol(w, p);
    cval[idx++] = 1.0;
  }
  cind[idx] = opencol(p);
  cval[idx++] = -Capacity[p];
}
error = GRBaddconstrs(model, nPlants, idx, cbeg, cind, cval, sense,
                      rhs, cname);
if (error) goto QUIT;

/* Demand constraints */
idx = 0;
for (w = 0; w < nWarehouses; ++w)
{
  cbeg[w] = idx;
  sense[w] = GRB_EQUAL;
  sprintf(cname[w], "Demand%i", w);
  for (p = 0; p < nPlants; ++p)
  {
    cind[idx] = transportcol(w, p);
    cval[idx++] = 1.0;
```

(continues on next page)

(continued from previous page)

```
  }
}
error = GRBaddconstrs(model, nWarehouses, idx, cbeg, cind, cval, sense,
                      Demand, cname);
if (error) goto QUIT;

/* Guess at the starting point: close the plant with the highest
   fixed costs; open all others */

/* First, open all plants */
for (p = 0; p < nPlants; ++p)
{
  error = GRBsetdblattrelement(model, "Start", opencol(p), 1.0);
  if (error) goto QUIT;
}

/* Now close the plant with the highest fixed cost */
printf("Initial guess:\n");
for (p = 0; p < nPlants; ++p)
{
  if (FixedCosts[p] > maxFixed)
  {
    maxFixed = FixedCosts[p];
  }
}
for (p = 0; p < nPlants; ++p)
{
  if (FixedCosts[p] == maxFixed)
  {
    error = GRBsetdblattrelement(model, "Start", opencol(p), 0.0);
    if (error) goto QUIT;
    printf("Closing plant %i\n\n", p);
    break;
  }
}

/* Use barrier to solve root relaxation */
error = GRBsetintparam(GRBgetenv(model),
                       GRB_INT_PAR_METHOD,
                       GRB_METHOD_BARRIER);
if (error) goto QUIT;

/* Solve */
error = GRBoptimize(model);
if (error) goto QUIT;

/* Print solution */
error = GRBgetdblattr(model, "ObjVal", &obj);
if (error) goto QUIT;
printf("\nTOTAL COSTS: %f\n", obj);
printf("SOLUTION:\n");
for (p = 0; p < nPlants; ++p)
```

(continues on next page)

(continued from previous page)

```
  {
    error = GRBgetdblattrelement(model, "X", opencol(p), &sol);
    if (error) goto QUIT;
    if (sol > 0.99)
    {
      printf("Plant %i open:\n", p);
      for (w = 0; w < nWarehouses; ++w)
      {
        error = GRBgetdblattrelement(model, "X", transportcol(w, p), &sol);
        if (error) goto QUIT;
        if (sol > 0.0001)
        {
          printf("  Transport %f units to warehouse %i\n", sol, w);
        }
      }
    }
    else
    {
      printf("Plant %i closed!\n", p);
    }
  }


QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */

  free(cbeg);
  free(cind);
  free(cval);
  free(rhs);
  free(sense);
  for (p = 0; p < cnamect; ++p) {
    free(cname[p]);
  }
  free(cname);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);
```

(continues on next page)

(continued from previous page)

```
  return 0;
}
```

feasopt_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, adds artificial
   variables to each constraint, and then minimizes the sum of the
   artificial variables.  A solution with objective zero corresponds
   to a feasible solution to the input model.
   We can also use FeasRelax feature to do it. In this example, we
   use minrelax=1, i.e. optimizing the returned model finds a solution
   that minimizes the original objective, but only from among those
   solutions that minimize the sum of the artificial variables. */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env       = NULL;
  GRBmodel *model     = NULL;
  GRBmodel *feasmodel = NULL;
  double   *rhspen    = NULL;
  int       error = 0;
  int       i, j;
  int       numvars, numconstrs;
  char      sense;
  int       vind[1];
  double    vval[1];
  double    feasobj;
  char      *cname, *vname;

  if (argc < 2)
  {
    fprintf(stderr, "Usage: feasopt_c filename\n");
    exit(1);
  }

  error = GRBloadenv(&env, "feasopt.log");
  if (error) goto QUIT;

  error = GRBreadmodel(env, argv[1], &model);
```

(continues on next page)

(continued from previous page)

```
if (error) goto QUIT;

/* Create a copy to use FeasRelax feature later */

feasmodel = GRBcopymodel(model);
if (error) goto QUIT;

/* clear objective */
error = GRBgetintattr(model, "NumVars", &numvars);
if (error) goto QUIT;
for (j = 0; j < numvars; ++j)
{
  error = GRBsetdblattrelement(model, "Obj", j, 0.0);
  if (error) goto QUIT;
}

/* add slack variables */
error = GRBgetintattr(model, "NumConstrs", &numconstrs);
if (error) goto QUIT;
for (i = 0; i < numconstrs; ++i)
{
  error = GRBgetcharattrelement(model, "Sense", i, &sense);
  if (error) goto QUIT;
  if (sense != '>')
  {
    error = GRBgetstrattrelement(model, "ConstrName", i, &cname);
    if (error) goto QUIT;
    vname = malloc(sizeof(char) * (6 + strlen(cname)));
    if (!vname) goto QUIT;
    strcpy(vname, "ArtN_");
    strcat(vname, cname);
    vind[0] = i;
    vval[0] = -1.0;
    error = GRBaddvar(model, 1, vind, vval, 1.0, 0.0, GRB_INFINITY,
                      GRB_CONTINUOUS, vname);
    if (error) goto QUIT;
    free(vname);
  }
  if (sense != '<')
  {
    error = GRBgetstrattrelement(model, "ConstrName", i, &cname);
    if (error) goto QUIT;
    vname = malloc(sizeof(char) * (6 + strlen(cname)));
    if (!vname) goto QUIT;
    strcpy(vname, "ArtP_");
    strcat(vname, cname);
    vind[0] = i;
    vval[0] = 1.0;
    error = GRBaddvar(model, 1, vind, vval, 1.0, 0.0, GRB_INFINITY,
                      GRB_CONTINUOUS, vname);
    if (error) goto QUIT;
    free(vname);
```

(continues on next page)

(continued from previous page)

```
    }
  }

  /* Optimize modified model */

  error = GRBoptimize(model);
  if (error) goto QUIT;

  error = GRBwrite(model, "feasopt.lp");
  if (error) goto QUIT;

  /* Use FeasRelax feature */

  rhspen = (double *) malloc(numconstrs*sizeof(double));
  if (rhspen == NULL) {
    printf("ERROR: out of memory\n");
    goto QUIT;
  }

  /* set penalties for artificial variables */
  for (i = 0; i < numconstrs; i++) rhspen[i] = 1;

  /* create a FeasRelax model with the original objective recovered
     and enforcement on minimum of aretificial variables */
  error = GRBfeasrelax(feasmodel, GRB_FEASRELAX_LINEAR, 1,
                       NULL, NULL, rhspen, &feasobj);
  if (error) goto QUIT;

  /* optimize FeasRelax model */
  error = GRBwrite(feasmodel, "feasopt1.lp");
  if (error) goto QUIT;

  error = GRBoptimize(feasmodel);
  if (error) goto QUIT;


QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free models, env and etc. */

  if (rhspen) free(rhspen);

  GRBfreemodel(model);
  GRBfreemodel(feasmodel);
```

(continues on next page)

(continued from previous page)

```
  GRBfreeenv(env);

  return 0;
}
```

fixanddive_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Implement a simple MIP heuristic.  Relax the model,
   sort variables based on fractionality, and fix the 25% of
   the fractional variables that are closest to integer variables.
   Repeat until either the relaxation is integer feasible or
   linearly infeasible. */

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"

typedef struct
{
  int index;
  double X;
}
var_t ;

int vcomp(const void* v1, const void* v2);


int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL, *modelenv = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  int       j, iter, nfix;
  int       numvars, numintvars, numfractional;
  int      *intvars = NULL;
  int       status;
  char      vtype, *vname;
  double    sol, obj, fixval;
  var_t    *fractional = NULL;

  if (argc < 2)
  {
    fprintf(stderr, "Usage: fixanddive_c filename\n");
```

(continues on next page)

(continued from previous page)

```
  exit(1);
}

error = GRBloadenv(&env, "fixanddive.log");
if (error) goto QUIT;

/* Read model */
error = GRBreadmodel(env, argv[1], &model);
if (error) goto QUIT;

/* Collect integer variables and relax them */
error = GRBgetintattr(model, "NumVars", &numvars);
if (error) goto QUIT;
error = GRBgetintattr(model, "NumIntVars", &numintvars);
if (error) goto QUIT;
intvars = malloc(sizeof(int) * numintvars);
if (!intvars) goto QUIT;
fractional = malloc(sizeof(var_t) * numintvars);
if (!fractional) goto QUIT;
numfractional = 0;
for (j = 0; j < numvars; j++)
{
  error = GRBgetcharattrelement(model, "VType", j, &vtype);
  if (error) goto QUIT;
  if (vtype != GRB_CONTINUOUS)
  {
    intvars[numfractional++] = j;
    error = GRBsetcharattrelement(model, "VType", j, GRB_CONTINUOUS);
    if (error) goto QUIT;
  }
}

modelenv = GRBgetenv(model);
assert(modelenv != NULL);
error = GRBsetintparam(modelenv, "OutputFlag", 0);
if (error) goto QUIT;
error = GRBoptimize(model);
if (error) goto QUIT;

/* Perform multiple iterations. In each iteration, identify the first
   quartile of integer variables that are closest to an integer value
   in the relaxation, fix them to the nearest integer, and repeat. */

for (iter = 0; iter < 1000; ++iter)
{

  /* create a list of fractional variables, sorted in order of
     increasing distance from the relaxation solution to the nearest
     integer value */

  numfractional = 0;
  for (j = 0; j < numintvars; ++j)
```

(continues on next page)

(continued from previous page)

```
  {
    error = GRBgetdblattrelement(model, "X", intvars[j], &sol);
    if (error) goto QUIT;
    if (fabs(sol - floor(sol + 0.5)) > 1e-5)
    {
      fractional[numfractional].index = intvars[j];
      fractional[numfractional++].X = sol;
    }
  }

  error = GRBgetdblattr(model, "ObjVal", &obj);
  if (error) goto QUIT;
  printf("Iteration %i, obj %f, fractional %i\n",
         iter, obj, numfractional);

  if (numfractional == 0)
  {
    printf("Found feasible solution - objective %f\n", obj);
    break;
  }

  /* Fix the first quartile to the nearest integer value */
  qsort(fractional, numfractional, sizeof(var_t), vcomp);
  nfix = numfractional / 4;
  nfix = (nfix > 1) ? nfix : 1;
  for (j = 0; j < nfix; ++j)
  {
    fixval = floor(fractional[j].X + 0.5);
    error = GRBsetdblattrelement(model, "LB", fractional[j].index, fixval);
    if (error) goto QUIT;
    error = GRBsetdblattrelement(model, "UB", fractional[j].index, fixval);
    if (error) goto QUIT;
    error = GRBgetstrattrelement(model, "VarName",
                                 fractional[j].index, &vname);
    if (error) goto QUIT;
    printf("  Fix %s to %f ( rel %f )\n", vname, fixval, fractional[j].X);
  }

  error = GRBoptimize(model);
  if (error) goto QUIT;

  /* Check optimization result */

  error = GRBgetintattr(model, "Status", &status);
  if (error) goto QUIT;
  if (status != GRB_OPTIMAL)
  {
    printf("Relaxation is infeasible\n");
    break;
  }
}
```

(continues on next page)

(continued from previous page)

```
QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */

  free(intvars);
  free(fractional);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}


int vcomp(const void* v1, const void* v2)
{
  double sol1, sol2, frac1, frac2;
  sol1 = fabs(((var_t *)v1)->X);
  sol2 = fabs(((var_t *)v2)->X);
  frac1 = fabs(sol1 - floor(sol1 + 0.5));
  frac2 = fabs(sol2 - floor(sol2 + 0.5));
  return (frac1 < frac2) ? -1 : ((frac1 == frac2) ? 0 : 1);
}
```

gc_pwl_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC

 This example formulates and solves the following simple model
 with PWL constraints:

  maximize
        sum c[j] * x[j]
  subject to
        sum A[i,j] * x[j] <= 0,  for i = 0, ..., m-1
        sum y[j] <= 3
```

(continues on next page)

(continued from previous page)

```
       y[j] = pwl(x[j]),        for j = 0, ..., n-1
       x[j] free, y[j] >= 0,    for j = 0, ..., n-1
  where pwl(x) = 0,     if x  = 0
               = 1+|x|, if x != 0

  Note
   1. sum pwl(x[j]) <= b is to bound x vector and also to favor sparse x vector.
      Here b = 3 means that at most two x[j] can be nonzero and if two, then
      sum x[j] <= 1
   2. pwl(x) jumps from 1 to 0 and from 0 to 1, if x moves from negative 0 to 0,
      then to positive 0, so we need three points at x = 0. x has infinite bounds
      on both sides, the piece defined with two points (-1, 2) and (0, 1) can
      extend x to -infinite. Overall we can use five points (-1, 2), (0, 1),
      (0, 0), (0, 1) and (1, 2) to define y = pwl(x)
*/

#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

int
main(int argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int      *cbeg  = NULL;
  int      *clen  = NULL;
  int      *cind  = NULL;
  double   *cval  = NULL;
  double   *rhs   = NULL;
  char     *sense = NULL;
  double   *lb    = NULL;
  double   *obj   = NULL;
  int       nz, i, j;
  int       status;
  double    objval;
  int       error = 0;

  int n = 5;
  int m = 5;
  double c[] = { 0.5, 0.8, 0.5, 0.1, -1 };
  double A[][5] = { {0, 0, 0, 1, -1},
                    {0, 0, 1, 1, -1},
                    {1, 1, 0, 0, -1},
                    {1, 0, 1, 0, -1},
                    {1, 0, 0, 1, -1} };
  int npts = 5;
  double xpts[] = {-1, 0, 0, 0, 1};
  double ypts[] = {2, 1, 0, 1, 2};

  /* Create environment */
```

(continues on next page)

(continued from previous page)

```
error = GRBloadenv(&env, NULL);
if (error) goto QUIT;

/* Allocate memory and build the model */
nz = n; /* count nonzeros for n y variables */
for (i = 0; i < m; i++) {
  for (j = 0; j < n; j++) {
    if (A[i][j] != 0.0) nz++;
  }
}

cbeg  = (int *) malloc(2*n*sizeof(int));
clen  = (int *) malloc(2*n*sizeof(int));
cind  = (int *) malloc(nz*sizeof(int));
cval  = (double *) malloc(nz*sizeof(double));
rhs   = (double *) malloc((m+1)*sizeof(double));
sense = (char *) malloc((m+1)*sizeof(char));
lb    = (double *) malloc(2*n*sizeof(double));
obj   = (double *) malloc(2*n*sizeof(double));

for (j = 0; j < n; j++) {
  /* for x variables */
  lb[j]  = -GRB_INFINITY;
  obj[j] = c[j];
  /* for y variables */
  lb[j+n] = 0.0;
  obj[j+n] = 0.0;
}

for (i = 0; i < m; i++) {
  rhs[i] = 0.0;
  sense[i] = GRB_LESS_EQUAL;
}
sense[m] = GRB_LESS_EQUAL;
rhs[m] = 3;

nz = 0;
for (j = 0; j < n; j++) {
  cbeg[j] = nz;
  for (i = 0; i < m; i++) {
    if (A[i][j] != 0.0 ) {
      cind[nz] = i;
      cval[nz] = A[i][j];
      nz++;
    }
  }
  clen[j] = nz - cbeg[j];
}

for (j = 0; j < n; j++) {
  cbeg[n+j] = nz;
  clen[n+j] = 1;
```

(continues on next page)

(continued from previous page)

```
    cind[nz] = m;
    cval[nz] = 1.0;
    nz++;
  }

  error = GRBloadmodel(env, &model, "gc_pwl_c", 2*n, m+1,
                       GRB_MAXIMIZE, 0.0, obj, sense, rhs,
                       cbeg, clen, cind, cval, lb, NULL,
                       NULL, NULL, NULL);
  if (error) goto QUIT;

  /* Add piecewise constraints */
  for (j = 0; j < n; j++) {
    error = GRBaddgenconstrPWL(model, NULL, j, n+j, npts, xpts, ypts);
    if (error) goto QUIT;
  }

  /* Optimize model */
  error = GRBoptimize(model);
  if (error) goto QUIT;

  for (j = 0; j < n; j++) {
    double x;
    error = GRBgetdblattrelement(model, "X", j, &x);
    if (error) goto QUIT;
    printf("x[%d] = %g\n", j, x);
  }

  /* Report the result */
  error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &status);
  if (error) goto QUIT;

  if (status != GRB_OPTIMAL) {
    fprintf(stderr, "Error: it isn't optimal\n");
    goto QUIT;
  }

  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;
  printf("Obj: %g\n", objval);

QUIT:

  /* Error reporting */
  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */
  if (cbeg)  free(cbeg);
  if (clen)  free(clen);
```

(continues on next page)

(continued from previous page)

```
  if (cind)  free(cind);
  if (cval)  free(cval);
  if (rhs)   free(rhs);
  if (sense) free(sense);
  if (lb)    free(lb);
  if (obj)   free(obj);

  /* Free model */
  GRBfreemodel(model);

  /* Free environment */
  GRBfreeenv(env);

  return 0;
}
```

genconstr_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* In this example we show the use of general constraints for modeling
 * some common expressions. We use as an example a SAT-problem where we
 * want to see if it is possible to satisfy at least four (or all) clauses
 * of the logical form
 *
 * L = (x0 or ~x1 or x2)  and (x1 or ~x2 or x3)  and
 *     (x2 or ~x3 or x0)  and (x3 or ~x0 or x1)  and
 *     (~x0 or ~x1 or x2) and (~x1 or ~x2 or x3) and
 *     (~x2 or ~x3 or x0) and (~x3 or ~x0 or x1)
 *
 * We do this by introducing two variables for each literal (itself and its
 * negated value), one variable for each clause, one variable indicating
 * whether we can satisfy at least four clauses, and one last variable to
 * identify the minimum of the clauses (so if it is one, we can satisfy all
 * clauses). Then we put these last two variables in the objective.
 * The objective function is therefore
 *
 * maximize Obj0 + Obj1
 *
 *  Obj0 = MIN(Clause1, ... , Clause8)
 *  Obj1 = 1 -> Clause1 + ... + Clause8 >= 4
 *
 * thus, the objective value will be two if and only if we can satisfy all
 * clauses; one if and only if at least four but not all clauses can be satisfied,
 * and zero otherwise.
 */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
```

(continues on next page)

(continued from previous page)

```c
#include <string.h>
#include "gurobi_c.h"

#define MAXSTR    128
#define NLITERALS 4
#define NCLAUSES  8
#define NOBJ      2
#define NVARS     (2 * NLITERALS + NCLAUSES + NOBJ)
#define LIT(n)    (n)
#define NOTLIT(n) (NLITERALS + n)
#define CLA(n)    (2 * NLITERALS + n)
#define OBJ(n)    (2 * NLITERALS + NCLAUSES + n)


int
main(void)
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  int       cind[NVARS];
  double    cval[NVARS];
  char      buffer[MAXSTR];
  int col, i, status;
  double objval;

  /* Example data */
  const int Clauses[][3] = {{LIT(0), NOTLIT(1), LIT(2)},
                            {LIT(1), NOTLIT(2), LIT(3)},
                            {LIT(2), NOTLIT(3), LIT(0)},
                            {LIT(3), NOTLIT(0), LIT(1)},
                            {NOTLIT(0), NOTLIT(1), LIT(2)},
                            {NOTLIT(1), NOTLIT(2), LIT(3)},
                            {NOTLIT(2), NOTLIT(3), LIT(0)},
                            {NOTLIT(3), NOTLIT(0), LIT(1)}};

  /* Create environment */
  error = GRBloadenv(&env, "genconstr_c.log");
  if (error) goto QUIT;

  /* Create initial model */
  error = GRBnewmodel(env, &model, "genconstr_c", NVARS, NULL,
                      NULL, NULL, NULL, NULL);
  if (error) goto QUIT;

  /* Initialize decision variables and objective */
  for (i = 0; i < NLITERALS; i++) {
    col = LIT(i);
    sprintf(buffer, "X%d", i);
    error = GRBsetcharattrelement(model, "VType", col, GRB_BINARY);
    if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
  error = GRBsetstrattrelement(model, "VarName", col, buffer);
  if (error) goto QUIT;

  col = NOTLIT(i);
  sprintf(buffer, "notX%d", i);
  error = GRBsetcharattrelement(model, "VType", col, GRB_BINARY);
  if (error) goto QUIT;

  error = GRBsetstrattrelement(model, "VarName", col, buffer);
  if (error) goto QUIT;
}

for (i = 0; i < NCLAUSES; i++) {
  col = CLA(i);
  sprintf(buffer, "Clause%d", i);
  error = GRBsetcharattrelement(model, "VType", col, GRB_BINARY);
  if (error) goto QUIT;

  error = GRBsetstrattrelement(model, "VarName", col, buffer);
  if (error) goto QUIT;
}

for (i = 0; i < NOBJ; i++) {
  col = OBJ(i);
  sprintf(buffer, "Obj%d", i);
  error = GRBsetcharattrelement(model, "VType", col, GRB_BINARY);
  if (error) goto QUIT;

  error = GRBsetstrattrelement(model, "VarName", col, buffer);
  if (error) goto QUIT;

  error = GRBsetdblattrelement(model, "Obj", col, 1.0);
  if (error) goto QUIT;
}

/* Link Xi and notXi */
for (i = 0; i < NLITERALS; i++) {
  sprintf(buffer,"CNSTR_X%d",i);
  cind[0] = LIT(i);
  cind[1] = NOTLIT(i);
  cval[0] = cval[1] = 1;
  error = GRBaddconstr(model, 2, cind, cval, GRB_EQUAL, 1.0, buffer);
  if (error) goto QUIT;
}

/* Link clauses and literals */
for (i = 0; i < NCLAUSES; i++) {
  sprintf(buffer,"CNSTR_Clause%d",i);
  error = GRBaddgenconstrOr(model, buffer, CLA(i), 3, Clauses[i]);
  if (error) goto QUIT;
}
```

(continues on next page)

(continued from previous page)

```
/* Link objs with clauses */
for (i = 0; i < NCLAUSES; i++) {
  cind[i] = CLA(i);
  cval[i] = 1;
}
error = GRBaddgenconstrMin(model, "CNSTR_Obj0", OBJ(0), NCLAUSES, cind, GRB_INFINITY);
if (error) goto QUIT;

/* note that passing 4 instead of 4.0 will produce undefined behavior */
error = GRBaddgenconstrIndicator(model, "CNSTR_Obj1",
                                 OBJ(1), 1, NCLAUSES, cind, cval,
                                 GRB_GREATER_EQUAL, 4.0);
if (error) goto QUIT;

/* Set global objective sense */
error = GRBsetintattr(model, GRB_INT_ATTR_MODELSENSE, GRB_MAXIMIZE);
if (error) goto QUIT;

/* Save problem */
error = GRBwrite(model, "genconstr_c.mps");
if (error) goto QUIT;

error = GRBwrite(model, "genconstr_c.lp");
if (error) goto QUIT;

/* Optimize */
error = GRBoptimize(model);
if (error) goto QUIT;

/* Status checking */
error = GRBgetintattr(model, "Status", &status);
if (error) goto QUIT;

if (status == GRB_INF_OR_UNBD ||
    status == GRB_INFEASIBLE  ||
    status == GRB_UNBOUNDED     ) {
  printf("The model cannot be solved "
         "because it is infeasible or unbounded\n");
  goto QUIT;
}
if (status != GRB_OPTIMAL) {
  printf("Optimization was stopped with status %i\n", status);
  goto QUIT;
}

/* Print result */
error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
if (error) goto QUIT;

if (objval > 1.9)
  printf("Logical expression is satisfiable\n");
else if (objval > 0.9)
```

(continues on next page)

(continued from previous page)

```
    printf("At least four clauses can be satisfied\n");
  else
    printf("At most three clauses may be satisfied\n");

QUIT:

  if (model != NULL) GRBfreemodel(model);
  if (env != NULL)   GRBfreeenv(env);

  return error;
}
```

nlconstr_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple nonlinear model
   using the nonlinear constraint API:

     minimize    x - y
     subject to  sin(x) * x + x^2 * y  <= 1
                 y = cos(x) (<=> cos(x) - y = 0)
                -1 <= x <= 2
                 0 <= y <= 2

   The nonlinear constraint is set via GRBaddnlconstr() using an expression tree.
   Then we retrieve the tree with GRBgetnlconstr() and verify it, delete it with
   GRBdelnlconstrs(), replace it with a simple linear constraint, and re-optimize.
*/

#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;

  /* Variable data: x (index 0), y (index 1) */
  double  lb[2]       = {-1.0, 0.0};
  double  ub[2]       = { 2.0, 2.0};
  char   *varnames[2] = {"x", "y"};
  double  obj[2]      = {1.0, -1.0};

  /* Expression tree for sin(x) * x + x^2 * y (10 nodes)
   *
```

(continues on next page)

(continued from previous page)

```
 *   node 0: PLUS       (root)
 *   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
 *   node 2: SIN        (child of 1)
 *   node 3: VARIABLE x (child of 2)
 *   node 4: VARIABLE x (child of 1)
 *   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
 *   node 6: POW        (child of 5)
 *   node 7: VARIABLE x (child of 6)
 *   node 8: CONSTANT 2 (child of 6)
 *   node 9: VARIABLE y (child of 5)
 */
int    nnodes1   = 10;
int    opcode1[10] = {GRB_OPCODE_PLUS,      /* 0: root         */
                      GRB_OPCODE_MULTIPLY,  /* 1: sin(x)*x     */
                      GRB_OPCODE_SIN,       /* 2: sin(...)      */
                      GRB_OPCODE_VARIABLE,  /* 3: x             */
                      GRB_OPCODE_VARIABLE,  /* 4: x             */
                      GRB_OPCODE_MULTIPLY,  /* 5: x^2 * y      */
                      GRB_OPCODE_POW,       /* 6: x^2           */
                      GRB_OPCODE_VARIABLE,  /* 7: x             */
                      GRB_OPCODE_CONSTANT,  /* 8: 2.0           */
                      GRB_OPCODE_VARIABLE}; /* 9: y             */
double data1[10]   = {-1.0, -1.0, -1.0,
                       0.0,  /* x index */
                       0.0,  /* x index */
                      -1.0, -1.0,
                       0.0,  /* x index */
                       2.0,
                       1.0}; /* y index */
int    parent1[10] = {-1, 0, 1, 2, 1, 0, 5, 6, 6, 5};

/* Expression tree for cos(x) - y = 0 (4 nodes)
 *
 *   node 0: MINUS      (root)
 *   node 1: COS        (child of 0)
 *   node 2: VARIABLE x (child of 1)
 *   node 3: VARIABLE y (child of 0)
 */
int    nnodes2    = 4;
int    opcode2[4] = {GRB_OPCODE_MINUS,      /* 0: root         */
                     GRB_OPCODE_COS,        /* 1: cos(...)     */
                     GRB_OPCODE_VARIABLE,   /* 2: x            */
                     GRB_OPCODE_VARIABLE};  /* 3: y            */
double data2[4]   = {-1.0, -1.0,
                      0.0,  /* x index */
                      1.0}; /* y index */
int    parent2[4] = {-1, 0, 1, 0};

/* Data for querying solution and NL constraint */
double  sol[2];
int     optimstatus;
double  objval;
```

(continues on next page)

(continued from previous page)

```
int     nnodes_out;

/* Create environment */
error = GRBloadenv(&env, "nlconstr.log");
if (error) goto QUIT;

/* Create model with two variables */
error = GRBnewmodel(env, &model, "nlconstr", 2, obj, lb, ub, NULL,
                    varnames);
if (error) goto QUIT;

/* Add constraint: sin(x) * x + x^2 * y <= 1 */
error = GRBaddnlconstr(model, nnodes1, opcode1, data1, parent1,
                       GRB_LESS_EQUAL, 1.0, "NonlinearConstraint1");
if (error) goto QUIT;

/* Add constraint: cos(x) - y = 0 */
error = GRBaddnlconstr(model, nnodes2, opcode2, data2, parent2,
                       GRB_EQUAL, 0.0, "NonlinearConstraint2");
if (error) goto QUIT;

/* Optimize model */
error = GRBoptimize(model);
if (error) goto QUIT;

/* Capture solution information */
error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
if (error) goto QUIT;

printf("\nFirst solve (nonlinear constraints)\n");
if (optimstatus == GRB_OPTIMAL) {
  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;

  error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 2, sol);
  if (error) goto QUIT;

  printf("Optimal objective: %.4e\n", objval);
  printf("  x=%.6f, y=%.6f\n", sol[0], sol[1]);
} else if (optimstatus == GRB_INF_OR_UNBD) {
  printf("Model is infeasible or unbounded\n");
} else {
  printf("Optimization was stopped early\n");
}

/* Retrieve number of nodes of first nonlinear constraint and print it */
error = GRBgetnlconstr(model, 0, &nnodes_out, NULL, NULL, NULL);
if (error) goto QUIT;
printf("\nRetrieved NL constraint with %d nodes\n", nnodes_out);

/* Delete both nonlinear constraints */
{
```

(continues on next page)

(continued from previous page)

```
    int ind[2] = {0, 1};
    error = GRBdelnlconstrs(model, 2, ind);
    if (error) goto QUIT;
    printf("Deleted nonlinear constraints\n");
  }

  /* Add a simple linear constraint instead: x + y >= 1 */
  {
    int    ind[2] = {0, 1};
    double val[2] = {1.0, 1.0};
    error = GRBaddconstr(model, 2, ind, val, GRB_GREATER_EQUAL, 1.0, "LinearConstraint");
    if (error) goto QUIT;
  }

  /* Re-optimize */
  error = GRBoptimize(model);
  if (error) goto QUIT;

  error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
  if (error) goto QUIT;

  printf("\nSecond solve (linear constraint)\n");
  if (optimstatus == GRB_OPTIMAL) {
    error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
    if (error) goto QUIT;

    error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 2, sol);
    if (error) goto QUIT;

    printf("Optimal objective: %.4e\n", objval);
    printf("  x=%.6f, y=%.6f\n", sol[0], sol[1]);
  } else if (optimstatus == GRB_INF_OR_UNBD) {
    printf("Model is infeasible or unbounded\n");
  } else {
    printf("Optimization was stopped early\n");
  }


QUIT:

  /* Error reporting */
  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */
  GRBfreemodel(model);

  /* Free environment */
  GRBfreeenv(env);
```

(continues on next page)

(continued from previous page)

```
  return 0;
}
```

nlobj_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple nonlinear model
   using the nonlinear objective API:

     minimize    sin(x) * x + x^2 * y
     subject to  x + y  >= 1
                -1 <= x <= 2
                 0 <= y <= 2

   The nonlinear objective is set via GRBsetnlobj() using an expression tree.
   Then we retrieve the tree with GRBgetnlobj() and verify it, delete it with
   GRBdelnlobj(), replace it with a simple linear objective, and re-optimize.
*/

#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;

  /* Variable data: x (index 0), y (index 1) */
  double  lb[2]       = {-1.0, 0.0};
  double  ub[2]       = { 2.0, 2.0};
  char   *varnames[2] = {"x", "y"};

  /* Expression tree for sin(x) * x + x^2 * y (10 nodes)
   *
   *   node 0: PLUS       (root)
   *   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
   *   node 2: SIN        (child of 1)
   *   node 3: VARIABLE x (child of 2)
   *   node 4: VARIABLE x (child of 1)
   *   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
   *   node 6: POW        (child of 5)
   *   node 7: VARIABLE x (child of 6)
   *   node 8: CONSTANT 2 (child of 6)
   *   node 9: VARIABLE y (child of 5)
   */
```

(continues on next page)

(continued from previous page)

```
int    nnodes    = 10;
int    opcode[10] = {GRB_OPCODE_PLUS,      /* 0: root         */
                     GRB_OPCODE_MULTIPLY,  /* 1: sin(x)*x     */
                     GRB_OPCODE_SIN,       /* 2: sin(...)      */
                     GRB_OPCODE_VARIABLE,  /* 3: x             */
                     GRB_OPCODE_VARIABLE,  /* 4: x             */
                     GRB_OPCODE_MULTIPLY,  /* 5: x^2 * y      */
                     GRB_OPCODE_POW,       /* 6: x^2           */
                     GRB_OPCODE_VARIABLE,  /* 7: x             */
                     GRB_OPCODE_CONSTANT,  /* 8: 2.0           */
                     GRB_OPCODE_VARIABLE}; /* 9: y             */
double data[10]   = {-1.0, -1.0, -1.0,
                      0.0,  /* x index */
                      0.0,  /* x index */
                     -1.0, -1.0,
                      0.0,  /* x index */
                      2.0,
                      1.0}; /* y index */
int    parent[10] = {-1, 0, 1, 2, 1, 0, 5, 6, 6, 5};

/* Data for querying solution and NL objective */
double  sol[2];
int     optimstatus;
double  objval;
int     nnodes_out;
double  linobj[2];

/* Create environment */
error = GRBloadenv(&env, "nlobj.log");
if (error) goto QUIT;

/* Create model with two variables, no linear objective */
error = GRBnewmodel(env, &model, "nlobj", 2, NULL, lb, ub, NULL,
                    varnames);
if (error) goto QUIT;

/* Add constraint: x + y >= 1 */
{
  int    cind[2] = {0, 1};
  double cval[2] = {1.0, 1.0};
  error = GRBaddconstr(model, 2, cind, cval, GRB_GREATER_EQUAL, 1.0, "c0");
  if (error) goto QUIT;
}

/* Set nonlinear objective */
error = GRBsetnlobj(model, nnodes, opcode, data, parent);
if (error) goto QUIT;

/* Optimize model */
error = GRBoptimize(model);
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
/* Capture solution information */
error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
if (error) goto QUIT;

printf("\nFirst solve (nonlinear objective)\n");
if (optimstatus == GRB_OPTIMAL) {
  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;

  error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 2, sol);
  if (error) goto QUIT;

  printf("Optimal objective: %.4e\n", objval);
  printf("  x=%.6f, y=%.6f\n", sol[0], sol[1]);
} else if (optimstatus == GRB_INF_OR_UNBD) {
  printf("Model is infeasible or unbounded\n");
} else {
  printf("Optimization was stopped early\n");
}

/* Retrieve the nonlinear objective and print the number of nodes */
error = GRBgetnlobj(model, &nnodes_out, NULL, NULL, NULL);
if (error) goto QUIT;
printf("\nRetrieved NL objective with %d nodes\n", nnodes_out);

/* Delete the nonlinear objective */
error = GRBdelnlobj(model);
if (error) goto QUIT;
printf("Deleted nonlinear objective\n");

/* Set a simple linear objective instead: minimize x + y */
linobj[0] = 1.0;
linobj[1] = 1.0;
error = GRBsetdblattrarray(model, GRB_DBL_ATTR_OBJ, 0, 2, linobj);
if (error) goto QUIT;

/* Re-optimize */
error = GRBoptimize(model);
if (error) goto QUIT;

error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
if (error) goto QUIT;

printf("\nSecond solve (linear objective)\n");
if (optimstatus == GRB_OPTIMAL) {
  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;

  error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 2, sol);
  if (error) goto QUIT;

  printf("Optimal objective: %.4e\n", objval);
```

(continues on next page)

(continued from previous page)

```
    printf("  x=%.6f, y=%.6f\n", sol[0], sol[1]);
  } else if (optimstatus == GRB_INF_OR_UNBD) {
    printf("Model is infeasible or unbounded\n");
  } else {
    printf("Optimization was stopped early\n");
  }


QUIT:

  /* Error reporting */
  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */
  GRBfreemodel(model);

  /* Free environment */
  GRBfreeenv(env);

  return 0;
}
```

lp_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads an LP model from a file and solves it.
   If the model is infeasible or unbounded, the example turns off
   presolve and solves the model again. If the model is infeasible,
   the example computes an Irreducible Inconsistent Subsystem (IIS),
   and writes it to a file */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  int       optimstatus;
  double    objval;
```

(continues on next page)

(continued from previous page)

```
if (argc < 2) {
  fprintf(stderr, "Usage: lp_c filename\n");
  exit(1);
}

/* Create environment */

error = GRBloadenv(&env, "lp.log");
if (error) goto QUIT;

/* Read model from file */

error = GRBreadmodel(env, argv[1], &model);
if (error) goto QUIT;

/* Solve model */

error = GRBoptimize(model);
if (error) goto QUIT;

/* Capture solution information */

error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
if (error) goto QUIT;

/* If model is infeasible or unbounded, turn off presolve and resolve */

if (optimstatus == GRB_INF_OR_UNBD) {
  /* Change parameter on model environment.  The model now has
     a copy of the original environment, so changing the original will
     no longer affect the model.  */

  error = GRBsetintparam(GRBgetenv(model), "PRESOLVE", 0);
  if (error) goto QUIT;

  error = GRBoptimize(model);
  if (error) goto QUIT;

  error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
  if (error) goto QUIT;
}

if (optimstatus == GRB_OPTIMAL) {
  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;
  printf("Optimal objective: %.4e\n\n", objval);
} else if (optimstatus == GRB_INFEASIBLE) {
  printf("Model is infeasible\n\n");

  error = GRBcomputeIIS(model);
  if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
    error = GRBwrite(model, "model.ilp");
    if (error) goto QUIT;
  } else if (optimstatus == GRB_UNBOUNDED) {
    printf("Model is unbounded\n\n");
  } else {
    printf("Optimization was stopped with status = %d\n\n", optimstatus);
  }

QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

lpmethod_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Solve a model with different values of the Method parameter;
   show which value gives the shortest solve time. */

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env = NULL, *menv;
  GRBmodel *m = NULL;
  int       error = 0;
  int       i;
  int       optimstatus;
  int       bestMethod = -1;
```

(continues on next page)

(continued from previous page)

```
  double    bestTime;

  if (argc < 2)
  {
    fprintf(stderr, "Usage: lpmethod_c filename\n");
    exit(1);
  }

  error = GRBloadenv(&env, "lpmethod.log");
  if (error) goto QUIT;

  /* Read model */
  error = GRBreadmodel(env, argv[1], &m);
  if (error) goto QUIT;
  menv = GRBgetenv(m);
  assert(menv != NULL);
  error = GRBgetdblparam(menv, "TimeLimit", &bestTime);
  if (error) goto QUIT;

  /* Solve the model with different values of Method */
  for (i = 0; i <= 2; ++i)
  {
    error = GRBreset(m, 0);
    if (error) goto QUIT;
    error = GRBsetintparam(menv, "Method", i);
    if (error) goto QUIT;
    error = GRBoptimize(m);
    if (error) goto QUIT;
    error = GRBgetintattr(m, "Status", &optimstatus);
    if (error) goto QUIT;
    if (optimstatus == GRB_OPTIMAL) {
      error = GRBgetdblattr(m, "Runtime", &bestTime);
      if (error) goto QUIT;
      bestMethod = i;
      /* Reduce the TimeLimit parameter to save time
         with other methods */
      error = GRBsetdblparam(menv, "TimeLimit", bestTime);
      if (error) goto QUIT;
    }
  }

  /* Report which method was fastest */
  if (bestMethod == -1) {
    printf("Unable to solve this model\n");
  } else {
    printf("Solved in %f seconds with Method: %i\n",
           bestTime, bestMethod);
  }

QUIT:

  /* Error reporting */
```

(continues on next page)

(continued from previous page)

```
  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */

  GRBfreemodel(m);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

lpmod_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads an LP model from a file and solves it.
   If the model can be solved, then it finds the smallest positive variable,
   sets its upper bound to zero, and resolves the model two ways:
   first with an advanced start, then without an advanced start
   (i.e. 'from scratch'). */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  int       j;
  int       numvars, isMIP, status, minVar = 0;
  double    minVal = GRB_INFINITY, sol, lb;
  char     *varname;
  double    warmCount, warmTime, coldCount, coldTime;

  if (argc < 2)
  {
    fprintf(stderr, "Usage: lpmod_c filename\n");
```

(continues on next page)

(continued from previous page)

```
  exit(1);
}

error = GRBloadenv(&env, "lpmod.log");
if (error) goto QUIT;

/* Read model and determine whether it is an LP */
error = GRBreadmodel(env, argv[1], &model);
if (error) goto QUIT;
error = GRBgetintattr(model, "IsMIP", &isMIP);
if (error) goto QUIT;
if (isMIP)
{
  printf("The model is not a linear program\n");
  goto QUIT;
}

error = GRBoptimize(model);
if (error) goto QUIT;

error = GRBgetintattr(model, "Status", &status);
if (error) goto QUIT;

if ((status == GRB_INF_OR_UNBD) || (status == GRB_INFEASIBLE) ||
    (status == GRB_UNBOUNDED))
{
  printf("The model cannot be solved because it is ");
  printf("infeasible or unbounded\n");
  goto QUIT;
}

if (status != GRB_OPTIMAL)
{
  printf("Optimization was stopped with status %i\n", status);
  goto QUIT;
}

/* Find the smallest variable value */
error = GRBgetintattr(model, "NumVars", &numvars);
if (error) goto QUIT;
for (j = 0; j < numvars; ++j)
{
  error = GRBgetdblattrelement(model, "X", j, &sol);
  if (error) goto QUIT;
  error = GRBgetdblattrelement(model, "LB", j, &lb);
  if (error) goto QUIT;
  if ((sol > 0.0001) && (sol < minVal) &&
      (lb == 0.0))
  {
    minVal = sol;
    minVar = j;
  }
```

(continues on next page)

(continued from previous page)

```
  }

  error = GRBgetstrattrelement(model, "VarName", minVar, &varname);
  if (error) goto QUIT;
  printf("\n*** Setting %s from %f to zero ***\n\n", varname, minVal);
  error = GRBsetdblattrelement(model, "UB", minVar, 0.0);
  if (error) goto QUIT;

  /* Solve from this starting point */
  error = GRBoptimize(model);
  if (error) goto QUIT;

  /* Save iteration & time info */
  error = GRBgetdblattr(model, "IterCount", &warmCount);
  if (error) goto QUIT;
  error = GRBgetdblattr(model, "Runtime", &warmTime);
  if (error) goto QUIT;

  /* Reset the model and resolve */
  printf("\n*** Resetting and solving ");
  printf("without an advanced start ***\n\n");
  error = GRBreset(model, 0);
  if (error) goto QUIT;
  error = GRBoptimize(model);
  if (error) goto QUIT;

  /* Save iteration & time info */
  error = GRBgetdblattr(model, "IterCount", &coldCount);
  if (error) goto QUIT;
  error = GRBgetdblattr(model, "Runtime", &coldTime);
  if (error) goto QUIT;

  printf("\n*** Warm start: %f iterations, %f seconds\n",
         warmCount, warmTime);
  printf("*** Cold start: %f iterations, %f seconds\n",
         coldCount, coldTime);


QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */

  GRBfreemodel(model);
```

(continues on next page)

(continued from previous page)

```
  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

mip1_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple MIP model:

     maximize    x +   y + 2 z
     subject to  x + 2 y + 3 z <= 4
                 x +   y       >= 1
                 x, y, z binary
*/

#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  double    sol[3];
  int       ind[3];
  double    val[3];
  double    obj[3];
  char      vtype[3];
  int       optimstatus;
  double    objval;

  /* Create environment */
  error = GRBemptyenv(&env);
  if (error) goto QUIT;

  error = GRBsetstrparam(env, "LogFile", "mip1.log");
  if (error) goto QUIT;

  error = GRBstartenv(env);
  if (error) goto QUIT;

  /* Create an empty model */
  error = GRBnewmodel(env, &model, "mip1", 0, NULL, NULL, NULL, NULL, NULL);
```

(continues on next page)

(continued from previous page)

```
if (error) goto QUIT;

/* Add variables */
obj[0] = 1; obj[1] = 1; obj[2] = 2;
vtype[0] = GRB_BINARY; vtype[1] = GRB_BINARY; vtype[2] = GRB_BINARY;
error = GRBaddvars(model, 3, 0, NULL, NULL, NULL, obj, NULL, NULL, vtype,
                   NULL);
if (error) goto QUIT;

/* Change objective sense to maximization */
error = GRBsetintattr(model, GRB_INT_ATTR_MODELSENSE, GRB_MAXIMIZE);
if (error) goto QUIT;

/* First constraint: x + 2 y + 3 z <= 4 */
ind[0] = 0; ind[1] = 1; ind[2] = 2;
val[0] = 1; val[1] = 2; val[2] = 3;

error = GRBaddconstr(model, 3, ind, val, GRB_LESS_EQUAL, 4.0, "c0");
if (error) goto QUIT;

/* Second constraint: x + y >= 1 */
ind[0] = 0; ind[1] = 1;
val[0] = 1; val[1] = 1;

error = GRBaddconstr(model, 2, ind, val, GRB_GREATER_EQUAL, 1.0, "c1");
if (error) goto QUIT;

/* Optimize model */
error = GRBoptimize(model);
if (error) goto QUIT;

/* Write model to 'mip1.lp' */
error = GRBwrite(model, "mip1.lp");
if (error) goto QUIT;

/* Capture solution information */
error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
if (error) goto QUIT;

error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
if (error) goto QUIT;

error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 3, sol);
if (error) goto QUIT;

printf("\nOptimization complete\n");
if (optimstatus == GRB_OPTIMAL) {
  printf("Optimal objective: %.4e\n", objval);

  printf("  x=%.0f, y=%.0f, z=%.0f\n", sol[0], sol[1], sol[2]);
} else if (optimstatus == GRB_INF_OR_UNBD) {
  printf("Model is infeasible or unbounded\n");
```

(continues on next page)

(continued from previous page)

```
  } else {
    printf("Optimization was stopped early\n");
  }

QUIT:

  /* Error reporting */
  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */
  GRBfreemodel(model);

  /* Free environment */
  GRBfreeenv(env);

  return 0;
}
```

mip2_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, solves it and
   prints the objective values from all feasible solutions
   generated while solving the MIP. Then it creates the fixed
   model and solves that model. */

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  GRBmodel *fixed = NULL;
  int       error = 0;
  int       ismip;
  int       j, k, solcount, numvars;
  double    objn;
  int       optimstatus, foptimstatus;
  double    objval, fobjval;
  char      *varname;
```

(continues on next page)

(continued from previous page)

```
double    x;

/* To change settings for a loaded model, we need to get
   the model environment, which will be freed when the model
   is freed. */

GRBenv   *menv, *fenv;

if (argc < 2) {
  fprintf(stderr, "Usage: mip2_c filename\n");
  exit(1);
}

/* Create environment */

error = GRBloadenv(&env, "mip2.log");
if (error) goto QUIT;

/* Read model from file */

error = GRBreadmodel(env, argv[1], &model);
if (error) goto QUIT;

error = GRBgetintattr(model, "IsMIP", &ismip);
if (error) goto QUIT;

if (ismip == 0) {
  printf("Model is not a MIP\n");
  goto QUIT;
}

/* Get model environment */

menv = GRBgetenv(model);
assert(menv != NULL);

/* Solve model */

error = GRBoptimize(model);
if (error) goto QUIT;

/* Capture solution information */

error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
if (error) goto QUIT;

printf("\nOptimization complete\n");
if (optimstatus == GRB_OPTIMAL) {
  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;
  printf("Optimal objective: %.4e\n\n", objval);
} else if (optimstatus == GRB_INF_OR_UNBD) {
```

(continues on next page)

(continued from previous page)

```
  printf("Model is infeasible or unbounded\n\n");
  goto QUIT;
} else if (optimstatus == GRB_INFEASIBLE) {
  printf("Model is infeasible\n\n");
  goto QUIT;
} else if (optimstatus == GRB_UNBOUNDED) {
  printf("Model is unbounded\n\n");
  goto QUIT;
} else {
  printf("Optimization was stopped with status = %d\n\n", optimstatus);
  goto QUIT;
}

/* Iterate over the solutions and compute the objectives */

error = GRBgetintattr(model, "SolCount", &solcount);
if (error) goto QUIT;

printf("\n");
for ( k = 0; k < solcount; ++k ) {
  error = GRBsetintparam(menv, "SolutionNumber", k);
  if (error) goto QUIT;
  error = GRBgetdblattr(model, GRB_DBL_ATTR_POOLNOBJVAL, &objn);
  if (error) goto QUIT;
  printf("Solution %i has objective: %f\n", k, objn);
}
printf("\n");

/* Create a fixed model, turn off presolve and solve */

error = GRBfixmodel(model, &fixed);
if (error || !fixed) {
  fprintf(stderr, "Error: could not create fixed model\n");
  goto QUIT;
}

fenv = GRBgetenv(fixed);
assert(fenv != NULL);

error = GRBsetintparam(fenv, "PRESOLVE", 0);
if (error) goto QUIT;

error = GRBoptimize(fixed);
if (error) goto QUIT;

error = GRBgetintattr(fixed, GRB_INT_ATTR_STATUS, &foptimstatus);
if (error) goto QUIT;

if (foptimstatus != GRB_OPTIMAL) {
  fprintf(stderr, "Error: fixed model isn't optimal\n");
  goto QUIT;
}
```

(continues on next page)

(continued from previous page)

```
  error = GRBgetdblattr(fixed, GRB_DBL_ATTR_OBJVAL, &fobjval);
  if (error) goto QUIT;

  if (fabs(fobjval - objval) > 1.0e-6 * (1.0 + fabs(objval))) {
    fprintf(stderr, "Error: objective values are different\n");
  }

  error = GRBgetintattr(model, "NumVars", &numvars);
  if (error) goto QUIT;

  /* Print values of nonzero variables */
  for ( j = 0; j < numvars; ++j ) {
    error = GRBgetstrattrelement(fixed, "VarName", j, &varname);
    if (error) goto QUIT;
    error = GRBgetdblattrelement(fixed, "X", j, &x);
    if (error) goto QUIT;
    if (x != 0.0) {
      printf("%s %f\n", varname, x);
    }
  }


QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free models */

  GRBfreemodel(model);
  GRBfreemodel(fixed);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

multiobj_c.c

```c
/* Copyright 2026, Gurobi Optimization, LLC */

/* Want to cover four different sets but subject to a common budget of
 * elements allowed to be used. However, the sets have different priorities to
 * be covered; and we tackle this by using multi-objective optimization. */

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include "gurobi_c.h"

#define MAXSTR 128

int
main(void)
{
  GRBenv   *env   = NULL;
  GRBenv   *menv  = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  int      *cind  = NULL;
  double   *cval  = NULL;
  char      buffer[MAXSTR];
  int e, i, status, nSolutions;
  double objn;

  /* Sample data */
  const int groundSetSize = 20;
  const int nSubsets      = 4;
  const int Budget        = 12;
  double Set[][20] =
    { { 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0 },
      { 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1 },
      { 0, 0, 0, 1, 1, 0, 1, 1, 0, 0, 0, 0, 0, 1, 1, 0, 1, 1, 0, 0 },
      { 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0 } };
  int    SetObjPriority[] = {3, 2, 2, 1};
  double SetObjWeight[]   = {1.0, 0.25, 1.25, 1.0};

  /* Create environment */
  error = GRBloadenv(&env, "multiobj_c.log");
  if (error) goto QUIT;

  /* Create initial model */
  error = GRBnewmodel(env, &model, "multiobj_c", groundSetSize, NULL,
                      NULL, NULL, NULL, NULL);
  if (error) goto QUIT;

  /* get model environment */
  menv = GRBgetenv(model);
```

(continues on next page)

(continued from previous page)

```
assert(menv != NULL);

/* Initialize decision variables for ground set:
 * x[e] == 1 if element e is chosen for the covering. */
for (e = 0; e < groundSetSize; e++) {
  sprintf(buffer, "El%d", e);
  error = GRBsetcharattrelement(model, "VType", e, GRB_BINARY);
  if (error) goto QUIT;

  error = GRBsetstrattrelement(model, "VarName", e, buffer);
  if (error) goto QUIT;
}

/* Make space for constraint data */
cind = malloc(sizeof(int) * groundSetSize);
if (!cind) goto QUIT;
cval = malloc(sizeof(double) * groundSetSize);
if (!cval) goto QUIT;

/* Constraint: limit total number of elements to be picked to be at most
 * Budget */
for (e = 0; e < groundSetSize; e++) {
  cind[e] = e;
  cval[e] = 1.0;
}
sprintf (buffer, "Budget");
error = GRBaddconstr(model, groundSetSize, cind, cval, GRB_LESS_EQUAL,
                     (double)Budget, buffer);
if (error) goto QUIT;

/* Set global sense for ALL objectives */
error = GRBsetintattr(model, GRB_INT_ATTR_MODELSENSE, GRB_MAXIMIZE);
if (error) goto QUIT;

/* Limit how many solutions to collect */
error = GRBsetintparam(menv, GRB_INT_PAR_POOLSOLUTIONS, 100);
if (error) goto QUIT;

/* Set and configure i-th objective */
for (i = 0; i < nSubsets; i++) {
  sprintf(buffer, "Set%d", i+1);

  error = GRBsetobjectiven(model, i, SetObjPriority[i], SetObjWeight[i],
                           1.0 + i, 0.01, buffer, 0.0, groundSetSize,
                           cind, Set[i]);
  if (error) goto QUIT;
}

/* Save problem */
error = GRBwrite(model, "multiobj_c.lp");
if (error) goto QUIT;
error = GRBwrite(model, "multiobj_c.mps");
```

(continues on next page)

(continued from previous page)

```
if (error) goto QUIT;

/* Optimize */
error = GRBoptimize(model);
if (error) goto QUIT;

/* Status checking */
error = GRBgetintattr(model, "Status", &status);
if (error) goto QUIT;

if (status == GRB_INF_OR_UNBD ||
    status == GRB_INFEASIBLE  ||
    status == GRB_UNBOUNDED     ) {
  printf("The model cannot be solved "
         "because it is infeasible or unbounded\n");
  goto QUIT;
}
if (status != GRB_OPTIMAL) {
  printf("Optimization was stopped with status %i\n", status);
  goto QUIT;
}

/* Print best selected set */
error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, groundSetSize, cval);
if (error) goto QUIT;

printf("Selected elements in best solution:\n\t");
for (e = 0; e < groundSetSize; e++) {
  if (cval[e] < .9) continue;
  printf("El%d ", e);
}

/* Print number of solutions stored */
error = GRBgetintattr(model, GRB_INT_ATTR_SOLCOUNT, &nSolutions);
if (error) goto QUIT;
printf("\nNumber of solutions found: %d\n", nSolutions);

/* Print objective values of solutions */

if (nSolutions > 10) nSolutions = 10;
printf("Objective values for first %d solutions:\n", nSolutions);
for (i = 0; i < nSubsets; i++) {
  error = GRBsetintparam(menv, GRB_INT_PAR_OBJNUMBER, i);
  if (error) goto QUIT;

  printf("\tSet %d:", i);
  for (e = 0; e < nSolutions; e++) {
    error = GRBsetintparam(menv, GRB_INT_PAR_SOLUTIONNUMBER, e);
    if (error) goto QUIT;

    error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJNVAL, &objn);
    if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
      printf(" %6g", objn);
    }
    printf("\n");
  }

QUIT:

  if (cind != NULL)  free(cind);
  if (cval != NULL)  free(cval);
  if (model != NULL) GRBfreemodel(model);
  if (env != NULL)   GRBfreeenv(env);

  return error;
}
```

multiscenario_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Facility location: a company currently ships its product from 5 plants
   to 4 warehouses. It is considering closing some plants to reduce
   costs. What plant(s) should the company close, in order to minimize
   transportation and fixed costs?

   Since the plant fixed costs and the warehouse demands are uncertain, a
   scenario approach is chosen.

   Note that this example is similar to the facility_c.c example. Here we
   added scenarios in order to illustrate the multi-scenario feature.

   Based on an example from Frontline Systems:
   http://www.solver.com/disfacility.htm
   Used with permission.
 */

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"


#define opencol(p)         p
#define transportcol(w,p)  nPlants*(w+1)+p
#define demandconstr(w)    nPlants+w
#define MAXSTR             128

int
main(int   argc,
```

(continues on next page)

(continued from previous page)

```
    char *argv[])
{
  GRBenv   *env      = NULL;
  GRBenv   *modelenv = NULL;
  GRBmodel *model    = NULL;

  double  *cval         = NULL;
  double  *rhs          = NULL;
  int     *cbeg         = NULL;
  int     *cind         = NULL;
  char   **cname        = NULL;
  char    *sense        = NULL;

  double maxFixed = -GRB_INFINITY;
  double minFixed = GRB_INFINITY;
  int    cnamect  = 0;
  int    error    = 0;

  int    p, s, w, col;
  int    idx, rowct;
  int    nScenarios;
  char   vname[MAXSTR];

  /* Number of plants, warehouses and scenarios */
  const int nPlants     = 5;
  const int nWarehouses = 4;

  /* Warehouse demand in thousands of units */
  double Demand[] = { 15, 18, 14, 20 };

  /* Plant capacity in thousands of units */
  double Capacity[] = { 20, 22, 17, 19, 18 };

  /* Fixed costs for each plant */
  double FixedCosts[] =
    { 12000, 15000, 17000, 13000, 16000 };

  /* Transportation costs per thousand units */
  double TransCosts[4][5] = {
    { 4000, 2000, 3000, 2500, 4500 },
    { 2500, 2600, 3400, 3000, 4000 },
    { 1200, 1800, 2600, 4100, 3000 },
    { 2200, 2600, 3100, 3700, 3200 }
  };

  /* Compute minimal and maximal fixed cost */
  for (p = 0; p < nPlants; p++) {
    if (FixedCosts[p] > maxFixed)
      maxFixed = FixedCosts[p];

    if (FixedCosts[p] < minFixed)
      minFixed = FixedCosts[p];
```

(continues on next page)

(continued from previous page)

```
}

/* Create environment */
error = GRBloadenv(&env, "multiscenario.log");
if (error) goto QUIT;

/* Create initial model */
error = GRBnewmodel(env, &model, "multiscenario", nPlants * (nWarehouses + 1),
                    NULL, NULL, NULL, NULL, NULL);
if (error) goto QUIT;

modelenv = GRBgetenv(model);
assert(modelenv != NULL);

/* Initialize decision variables for plant open variables */
for (p = 0; p < nPlants; p++) {
  col = opencol(p);
  error = GRBsetcharattrelement(model, GRB_CHAR_ATTR_VTYPE,
                                col, GRB_BINARY);
  if (error) goto QUIT;
  error = GRBsetdblattrelement(model, GRB_DBL_ATTR_OBJ,
                               col, FixedCosts[p]);
  if (error) goto QUIT;
  sprintf(vname, "Open%i", p);
  error = GRBsetstrattrelement(model, GRB_STR_ATTR_VARNAME,
                               col, vname);
  if (error) goto QUIT;
}

/* Initialize decision variables for transportation decision variables:
   how much to transport from a plant p to a warehouse w */
for (w = 0; w < nWarehouses; w++) {
  for (p = 0; p < nPlants; p++) {
    col = transportcol(w, p);
    error = GRBsetdblattrelement(model, GRB_DBL_ATTR_OBJ,
                                 col, TransCosts[w][p]);
    if (error) goto QUIT;
    sprintf(vname, "Trans%i.%i", p, w);
    error = GRBsetstrattrelement(model, GRB_STR_ATTR_VARNAME,
                                 col, vname);
    if (error) goto QUIT;
  }
}

/* The objective is to minimize the total fixed and variable costs */
error = GRBsetintattr(model, GRB_INT_ATTR_MODELSENSE, GRB_MINIMIZE);
if (error) goto QUIT;

/* Make space for constraint data */
rowct = (nPlants > nWarehouses) ? nPlants : nWarehouses;
cbeg = malloc(sizeof(int) * rowct);
if (!cbeg) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
cind = malloc(sizeof(int) * (nPlants * (nWarehouses + 1)));
if (!cind) goto QUIT;
cval = malloc(sizeof(double) * (nPlants * (nWarehouses + 1)));
if (!cval) goto QUIT;
rhs = malloc(sizeof(double) * rowct);
if (!rhs) goto QUIT;
sense = malloc(sizeof(char) * rowct);
if (!sense) goto QUIT;
cname = calloc(rowct, sizeof(char*));
if (!cname) goto QUIT;

/* Production constraints
   Note that the limit sets the production to zero if
   the plant is closed */
idx = 0;
for (p = 0; p < nPlants; p++) {
  cbeg[p] = idx;
  rhs[p] = 0.0;
  sense[p] = GRB_LESS_EQUAL;
  cname[p] = malloc(sizeof(char) * MAXSTR);
  if (!cname[p]) goto QUIT;
  cnamect++;
  sprintf(cname[p], "Capacity%i", p);
  for (w = 0; w < nWarehouses; w++) {
    cind[idx] = transportcol(w, p);
    cval[idx++] = 1.0;
  }
  cind[idx] = opencol(p);
  cval[idx++] = -Capacity[p];
}
error = GRBaddconstrs(model, nPlants, idx, cbeg, cind, cval, sense,
                      rhs, cname);
if (error) goto QUIT;

/* Demand constraints */
idx = 0;
for (w = 0; w < nWarehouses; w++) {
  cbeg[w] = idx;
  sense[w] = GRB_EQUAL;
  sprintf(cname[w], "Demand%i", w);
  for (p = 0; p < nPlants; p++) {
    cind[idx] = transportcol(w, p);
    cval[idx++] = 1.0;
  }
}
error = GRBaddconstrs(model, nWarehouses, idx, cbeg, cind, cval, sense,
                      Demand, cname);
if (error) goto QUIT;

/* We constructed the base model, now we add 7 scenarios

   Scenario 0: Represents the base model, hence, no manipulations.
```

(continues on next page)

(continued from previous page)

```
    Scenario 1: Manipulate the warehouses demands slightly (constraint right
                hand sides).
    Scenario 2: Double the warehouses demands (constraint right hand sides).
    Scenario 3: Manipulate the plant fixed costs (objective coefficients).
    Scenario 4: Manipulate the warehouses demands and fixed costs.
    Scenario 5: Force the plant with the largest fixed cost to stay open
                (variable bounds).
    Scenario 6: Force the plant with the smallest fixed cost to be closed
                (variable bounds). */

error = GRBsetintattr(model, GRB_INT_ATTR_NUMSCENARIOS, 7);
if (error) goto QUIT;

/* Scenario 0: Base model, hence, nothing to do except giving the
               scenario a name */
error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, 0);
if (error) goto QUIT;
error = GRBsetstrattr(model, GRB_STR_ATTR_SCENNNAME, "Base model");
if (error) goto QUIT;

/* Scenario 1: Increase the warehouse demands by 10% */
error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, 1);
if (error) goto QUIT;
error = GRBsetstrattr(model, GRB_STR_ATTR_SCENNNAME,
                      "Increased warehouse demands");
if (error) goto QUIT;

for (w = 0; w < nWarehouses; w++) {
  error = GRBsetdblattrelement(model, GRB_DBL_ATTR_SCENNRHS,
                               demandconstr(w), Demand[w] * 1.1);
  if (error) goto QUIT;
}

/* Scenario 2: Double the warehouse demands */
error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, 2);
if (error) goto QUIT;
error = GRBsetstrattr(model, GRB_STR_ATTR_SCENNNAME,
                      "Double the warehouse demands");
if (error) goto QUIT;

for (w = 0; w < nWarehouses; w++) {
  error = GRBsetdblattrelement(model, GRB_DBL_ATTR_SCENNRHS,
                               demandconstr(w), Demand[w] * 2.0);
  if (error) goto QUIT;
}

/* Scenario 3: Decrease the plant fixed costs by 5% */
error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, 3);
if (error) goto QUIT;
error = GRBsetstrattr(model, GRB_STR_ATTR_SCENNNAME,
                      "Decreased plant fixed costs");
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
for (p  = 0; p < nPlants; p++) {
  error = GRBsetdblattrelement(model, GRB_DBL_ATTR_SCENNOBJ,
                               opencol(p), FixedCosts[p] * 0.95);
  if (error) goto QUIT;
}

/* Scenario 4: Combine scenario 1 and scenario 3 */
error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, 4);
if (error) goto QUIT;
error = GRBsetstrattr(model, GRB_STR_ATTR_SCENNNAME,
                      "Increased warehouse demands and decreased plant fixed costs");

for (w = 0; w < nWarehouses; w++) {
  error = GRBsetdblattrelement(model, GRB_DBL_ATTR_SCENNRHS,
                               demandconstr(w), Demand[w] * 1.1);
  if (error) goto QUIT;
}
for (p  = 0; p < nPlants; p++) {
  error = GRBsetdblattrelement(model, GRB_DBL_ATTR_SCENNOBJ,
                               opencol(p), FixedCosts[p] * 0.95);
  if (error) goto QUIT;
}

/* Scenario 5: Force the plant with the largest fixed cost to stay
               open */
error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, 5);
if (error) goto QUIT;
error = GRBsetstrattr(model, GRB_STR_ATTR_SCENNNAME,
                      "Force plant with largest fixed cost to stay open");
if (error) goto QUIT;

for (p  = 0; p < nPlants; p++) {
  if (FixedCosts[p] == maxFixed) {
    error = GRBsetdblattrelement(model, GRB_DBL_ATTR_SCENNLB,
                                 opencol(p), 1.0);
    if (error) goto QUIT;
    break;
  }
}

/* Scenario 6: Force the plant with the smallest fixed cost to be
               closed */
error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, 6);
if (error) goto QUIT;
error = GRBsetstrattr(model, GRB_STR_ATTR_SCENNNAME,
                      "Force plant with smallest fixed cost to be closed");
if (error) goto QUIT;

for (p  = 0; p < nPlants; p++) {
  if (FixedCosts[p] == minFixed) {
    error = GRBsetdblattrelement(model, GRB_DBL_ATTR_SCENNUB,
```

(continues on next page)

(continued from previous page)

```
                                    opencol(p), 0.0);
    if (error) goto QUIT;
    break;
  }
}

/* Guess at the starting point: close the plant with the highest
   fixed costs; open all others */

/* First, open all plants */
for (p = 0; p < nPlants; p++) {
  error = GRBsetdblattrelement(model, GRB_DBL_ATTR_START, opencol(p), 1.0);
  if (error) goto QUIT;
}

/* Now close the plant with the highest fixed cost */
printf("Initial guess:\n");
for (p = 0; p < nPlants; p++) {
  if (FixedCosts[p] == maxFixed) {
    error = GRBsetdblattrelement(model, GRB_DBL_ATTR_START, opencol(p), 0.0);
    if (error) goto QUIT;
    printf("Closing plant %i\n\n", p);
    break;
  }
}

/* Use barrier to solve root relaxation */
error = GRBsetintparam(modelenv,
                       GRB_INT_PAR_METHOD,
                       GRB_METHOD_BARRIER);
if (error) goto QUIT;

/* Solve multi-scenario model */
error = GRBoptimize(model);
if (error) goto QUIT;

error = GRBgetintattr(model, GRB_INT_ATTR_NUMSCENARIOS, &nScenarios);
if (error) goto QUIT;

/* Print solution for each */
for (s = 0; s < nScenarios; s++) {
  char   *scenarioName;
  double  scenNObjBound;
  double  scenNObjVal;
  int     modelSense = GRB_MINIMIZE;

  /* Set the scenario number to query the information for this
     scenario */
  error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, s);
  if (error) goto QUIT;

  /* Collect result for the scenario */
```

(continues on next page)

(continued from previous page)

```
  error = GRBgetstrattr(model, GRB_STR_ATTR_SCENNNAME, &scenarioName);
  if (error) goto QUIT;
  error = GRBgetdblattr(model, GRB_DBL_ATTR_SCENNOBJBOUND, &scenNObjBound);
  if (error) goto QUIT;
  error = GRBgetdblattr(model, GRB_DBL_ATTR_SCENNOBJVAL, &scenNObjVal);
  if (error) goto QUIT;

  printf("\n\n------ Scenario %d (%s)\n", s, scenarioName);

  /* Check if we found a feasible solution for this scenario */
  if (modelSense * scenNObjVal >= GRB_INFINITY)
    if (modelSense * scenNObjBound >= GRB_INFINITY)
      /* Scenario was proven to be infeasible */
      printf("\nINFEASIBLE\n");
    else
      /* We did not find any feasible solution - should not happen in
         this case, because we did not set any limit (like a time
         limit) on the optimization process */
      printf("\nNO SOLUTION\n");
  else {
    printf("\nTOTAL COSTS: %g\n", scenNObjVal);
    printf("SOLUTION:\n");
    for (p = 0; p < nPlants; p++) {
      double scenNX;

      error = GRBgetdblattrelement(model, GRB_DBL_ATTR_SCENNX,
                                   opencol(p), &scenNX);
      if (error) goto QUIT;

      if (scenNX > 0.5) {
        printf("Plant %i open\n", p);
        for (w = 0; w < nWarehouses; w++) {
          error = GRBgetdblattrelement(model, GRB_DBL_ATTR_SCENNX,
                                       transportcol(w, p), &scenNX);
          if (error) goto QUIT;
          if (scenNX > 0.0001)
            printf("  Transport %g units to warehouse %i\n",
                   scenNX, w);
        }
      } else
        printf("Plant %i closed!\n",  p);
    }
  }
}

/* Print a summary table: for each scenario we add a single summary
   line */
printf("\n\nSummary: Closed plants depending on scenario\n\n");
printf("%8s | %17s %13s\n", "", "Plant", "|");

printf("%8s |", "Scenario");
for (p = 0; p < nPlants; p++)
```

(continues on next page)

(continued from previous page)

```
    printf(" %5d", p);
  printf(" | %6s  %s\n", "Costs", "Name");

  for (s = 0; s < nScenarios; s++) {
    char   *scenarioName;
    double  scenNObjBound;
    double  scenNObjVal;
    int     modelSense = GRB_MINIMIZE;

    /* Set the scenario number to query the information for this scenario */
    error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, s);
    if (error) goto QUIT;

    /* collect result for the scenario */
    error = GRBgetstrattr(model, GRB_STR_ATTR_SCENNNAME, &scenarioName);
    if (error) goto QUIT;
    error = GRBgetdblattr(model, GRB_DBL_ATTR_SCENNOBJBOUND, &scenNObjBound);
    if (error) goto QUIT;
    error = GRBgetdblattr(model, GRB_DBL_ATTR_SCENNOBJVAL, &scenNObjVal);
    if (error) goto QUIT;

    printf("%-8d |", s);

    /* Check if we found a feasible solution for this scenario */
    if (modelSense * scenNObjVal >= GRB_INFINITY)
      if (modelSense * scenNObjBound >= GRB_INFINITY)
        /* Scenario was proven to be infeasible */
        printf(" %-30s| %6s  %s\n", "infeasible", "-", scenarioName);
      else
        /* We did not find any feasible solution - should not happen in
           this case, because we did not set any limit (like a time
           limit) on the optimization process */
        printf(" %-30s| %6s  %s\n", "no solution found", "-", scenarioName);
    else {
      for (p = 0; p < nPlants; p++) {
        double scenNX;

        error = GRBgetdblattrelement(model, GRB_DBL_ATTR_SCENNX,
                                     opencol(p), &scenNX);
        if (scenNX  > 0.5)
          printf(" %5s", " ");
        else
          printf(" %5s", "x");
      }

      printf(" | %6g  %s\n", scenNObjVal, scenarioName);
    }
  }


QUIT:
```

(continues on next page)

(continued from previous page)

```
  /* Error reporting */
  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */
  free(cbeg);
  free(cind);
  free(cval);
  free(rhs);
  free(sense);
  for (p = 0; p < cnamect; p++)
    free(cname[p]);
  free(cname);

  /* Free model */
  GRBfreemodel(model);

  /* Free environment */
  GRBfreeenv(env);

  return 0;
}
```

params_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Use parameters that are associated with a model.

   A MIP is solved for a few seconds with different sets of parameters.
   The one with the smallest MIP gap is selected, and the optimization
   is resumed until the optimal solution is found.
*/

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL, *modelenv = NULL, *bestenv = NULL;
  GRBmodel *model = NULL, *bestmodel = NULL;
  int       error = 0;
  int       ismip, i, mipfocus;
```

(continues on next page)

(continued from previous page)

```
  double    bestgap, gap;

  if (argc < 2)
  {
    fprintf(stderr, "Usage: params_c filename\n");
    exit(1);
  }

  error = GRBloadenv(&env, "params.log");
  if (error) goto QUIT;

  /* Read model and verify that it is a MIP */
  error = GRBreadmodel(env, argv[1], &model);
  if (error) goto QUIT;
  error = GRBgetintattr(model, "IsMIP", &ismip);
  if (error) goto QUIT;
  if (ismip == 0)
  {
    printf("The model is not an integer program\n");
    exit(1);
  }

  /* Set a 2 second time limit */
  modelenv = GRBgetenv(model);
  assert(modelenv != NULL);
  error = GRBsetdblparam(modelenv, "TimeLimit", 2);
  if (error) goto QUIT;

  /* Now solve the model with different values of MIPFocus */
  bestmodel = GRBcopymodel(model);
  if (!bestmodel) {
    printf("Cannot copy model\n");
    exit(1);
  }
  error = GRBoptimize(bestmodel);
  if (error) goto QUIT;
  error = GRBgetdblattr(bestmodel, "MIPGap", &bestgap);
  if (error) goto QUIT;
  for (i = 1; i <= 3; ++i)
  {
    error = GRBreset(model, 0);
    if (error) goto QUIT;
    error = GRBsetintparam(modelenv, "MIPFocus", i);
    if (error) goto QUIT;
    error = GRBoptimize(model);
    if (error) goto QUIT;
    error = GRBgetdblattr(model, "MIPGap", &gap);
    if (error) goto QUIT;
    if (bestgap > gap)
    {
      GRBmodel *tmp = bestmodel;
      bestmodel = model;
```

(continues on next page)

(continued from previous page)

```
      model = tmp;
      bestgap = gap;
    }
  }

  /* Finally, free the extra model, reset the time limit and
     continue to solve the best model to optimality */
  GRBfreemodel(model);
  bestenv = GRBgetenv(bestmodel);
  if (!bestenv) {
    printf("Cannot retrieve best model environment\n");
    exit(1);
  }
  error = GRBsetdblparam(bestenv, "TimeLimit", GRB_INFINITY);
  if (error) goto QUIT;
  error = GRBoptimize(bestmodel);
  if (error) goto QUIT;
  error = GRBgetintparam(bestenv, "MIPFocus", &mipfocus);
  if (error) goto QUIT;

  printf("Solved with MIPFocus: %i\n", mipfocus);

QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free best model */

  GRBfreemodel(bestmodel);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

piecewise_c.c

```c
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example considers the following separable, convex problem:

     minimize    f(x) - y + g(z)
     subject to  x + 2 y + 3 z <= 4
                 x +   y       >= 1
                 x,    y,    z <= 1

   where f(u) = exp(-u) and g(u) = 2 u^2 - 4 u, for all real u. It
   formulates and solves a simpler LP model by approximating f and
   g with piecewise-linear functions. Then it transforms the model
   into a MIP by negating the approximation for f, which corresponds
   to a non-convex piecewise-linear function, and solves it again.
*/

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"

double f(double u) { return exp(-u); }
double g(double u) { return 2 * u * u - 4 * u; }

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  double    lb, ub;
  int       npts, i;
  double   *ptu = NULL;
  double   *ptf = NULL;
  double   *ptg = NULL;
  int       ind[3];
  double    val[3];
  int       ismip;
  double    objval;
  double    sol[3];

  /* Create environment */

  error = GRBloadenv(&env, NULL);
  if (error) goto QUIT;

  /* Create a new model */

  error = GRBnewmodel(env, &model, NULL, 0, NULL, NULL, NULL, NULL, NULL);
  if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
/* Add variables */

lb = 0.0; ub = 1.0;

error = GRBaddvar(model, 0, NULL, NULL, 0.0, lb, ub, GRB_CONTINUOUS, "x");
if (error) goto QUIT;
error = GRBaddvar(model, 0, NULL, NULL, 0.0, lb, ub, GRB_CONTINUOUS, "y");
if (error) goto QUIT;
error = GRBaddvar(model, 0, NULL, NULL, 0.0, lb, ub, GRB_CONTINUOUS, "z");
if (error) goto QUIT;

/* Set objective for y */

error = GRBsetdblattrelement(model, GRB_DBL_ATTR_OBJ, 1, -1.0);
if (error) goto QUIT;

/* Add piecewise-linear objective functions for x and z */

npts = 101;
ptu = (double *) malloc(npts * sizeof(double));
ptf = (double *) malloc(npts * sizeof(double));
ptg = (double *) malloc(npts * sizeof(double));

for (i = 0; i < npts; i++) {
  ptu[i] = lb + (ub - lb) * i / (npts - 1);
  ptf[i] = f(ptu[i]);
  ptg[i] = g(ptu[i]);
}

error = GRBsetpwlobj(model, 0, npts, ptu, ptf);
if (error) goto QUIT;
error = GRBsetpwlobj(model, 2, npts, ptu, ptg);
if (error) goto QUIT;

/* Add constraint: x + 2 y + 3 z <= 4 */

ind[0] = 0; ind[1] = 1; ind[2] = 2;
val[0] = 1; val[1] = 2; val[2] = 3;

error = GRBaddconstr(model, 3, ind, val, GRB_LESS_EQUAL, 4.0, "c0");
if (error) goto QUIT;

/* Add constraint: x + y >= 1 */

ind[0] = 0; ind[1] = 1;
val[0] = 1; val[1] = 1;

error = GRBaddconstr(model, 2, ind, val, GRB_GREATER_EQUAL, 1.0, "c1");
if (error) goto QUIT;

/* Optimize model as an LP */
```

(continues on next page)

(continued from previous page)

```
  error = GRBoptimize(model);
  if (error) goto QUIT;

  error = GRBgetintattr(model, "IsMIP", &ismip);
  if (error) goto QUIT;
  error = GRBgetdblattr(model, "ObjVal", &objval);
  if (error) goto QUIT;
  error = GRBgetdblattrarray(model, "X", 0, 3, sol);
  if (error) goto QUIT;

  printf("IsMIP: %d\n", ismip);
  printf("x %g\ny %g\nz %g\n", sol[0], sol[1], sol[2]);
  printf("Obj: %g\n", objval);
  printf("\n");

  /* Negate piecewise-linear objective function for x */

  for (i = 0; i < npts; i++) {
    ptf[i] = -ptf[i];
  }

  error = GRBsetpwlobj(model, 0, npts, ptu, ptf);
  if (error) goto QUIT;

  /* Optimize model as a MIP */

  error = GRBoptimize(model);
  if (error) goto QUIT;

  error = GRBgetintattr(model, "IsMIP", &ismip);
  if (error) goto QUIT;
  error = GRBgetdblattr(model, "ObjVal", &objval);
  if (error) goto QUIT;
  error = GRBgetdblattrarray(model, "X", 0, 3, sol);
  if (error) goto QUIT;

  printf("IsMIP: %d\n", ismip);
  printf("x %g\ny %g\nz %g\n", sol[0], sol[1], sol[2]);
  printf("Obj: %g\n", objval);

QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */
```

(continues on next page)

(continued from previous page)

```
  free(ptu);
  free(ptf);
  free(ptg);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

poolsearch_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* We find alternative epsilon-optimal solutions to a given knapsack
 * problem by using PoolSearchMode */

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include "gurobi_c.h"

#define MAXSTR 128


int main(void)
{
  GRBenv   *env   = NULL;
  GRBenv   *menv  = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  char      buffer[MAXSTR];
  int e, status, nSolutions, prlen;
  double objval, *cval = NULL;
  int *cind = NULL;

  /* Sample data */
  const int groundSetSize = 10;
  double objCoef[10] =
    {32, 32, 15, 15, 6, 6, 1, 1, 1, 1};
  double knapsackCoef[10] =
    {16, 16,  8,  8, 4, 4, 2, 2, 1, 1};
  double Budget = 33;
```

(continues on next page)

(continued from previous page)

```
  /* Create environment */
  error = GRBloadenv(&env, "poolsearch_c.log");
  if (error) goto QUIT;

  /* Create initial model */
  error = GRBnewmodel(env, &model, "poolsearch_c", groundSetSize, NULL,
                      NULL, NULL, NULL, NULL);
  if (error) goto QUIT;

  /* get model environment */
  menv = GRBgetenv(model);
  assert(menv != NULL);

  /* set objective function */
  error = GRBsetdblattrarray(model, "Obj", 0, groundSetSize, objCoef);
  if (error) goto QUIT;

  /* set variable types and names */
  for (e = 0; e < groundSetSize; e++) {
    sprintf(buffer, "El%d", e);
    error = GRBsetcharattrelement(model, "VType", e, GRB_BINARY);
    if (error) goto QUIT;

    error = GRBsetstrattrelement(model, "VarName", e, buffer);
    if (error) goto QUIT;
  }

  /* Make space for constraint data */
  cind = malloc(sizeof(int) * groundSetSize);
  if (!cind) goto QUIT;
  for (e = 0; e < groundSetSize; e++)
    cind[e] = e;

  /* Constraint: limit total number of elements to be picked to be at most
   * Budget */
  sprintf (buffer, "Budget");
  error = GRBaddconstr(model, groundSetSize, cind, knapsackCoef,
                       GRB_LESS_EQUAL, Budget, buffer);
  if (error) goto QUIT;

  /* set global sense for ALL objectives */
  error = GRBsetintattr(model, GRB_INT_ATTR_MODELSENSE, GRB_MAXIMIZE);
  if (error) goto QUIT;

  /* Limit how many solutions to collect */
  error = GRBsetintparam(menv, GRB_INT_PAR_POOLSOLUTIONS, 1024);
  if (error) goto QUIT;

  /* Limit the search space by setting a gap for the worst possible solution that will␣
↪be accepted */
  error = GRBsetdblparam(menv, GRB_DBL_PAR_POOLGAP, 0.10);
```

(continues on next page)

(continued from previous page)

```
if (error) goto QUIT;

/* do a systematic search for the k-best solutions */
error = GRBsetintparam(menv, GRB_INT_PAR_POOLSEARCHMODE, 2);
if (error) goto QUIT;

/* save problem */
error = GRBwrite(model, "poolsearch_c.lp");
if (error) goto QUIT;
error = GRBwrite(model, "poolsearch_c.mps");
if (error) goto QUIT;

/* Optimize */
error = GRBoptimize(model);
if (error) goto QUIT;

/* Status checking */
error = GRBgetintattr(model, "Status", &status);
if (error) goto QUIT;

if (status == GRB_INF_OR_UNBD ||
    status == GRB_INFEASIBLE  ||
    status == GRB_UNBOUNDED     ) {
  printf("The model cannot be solved "
         "because it is infeasible or unbounded\n");
  goto QUIT;
}
if (status != GRB_OPTIMAL) {
  printf("Optimization was stopped with status %d\n", status);
  goto QUIT;
}

/* make space for optimal solution */
cval = malloc(sizeof(double) * groundSetSize);
if (!cval) goto QUIT;

/* Print best selected set */
error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, groundSetSize, cval);
if (error) goto QUIT;

printf("Selected elements in best solution:\n\t");
for (e = 0; e < groundSetSize; e++) {
  if (cval[e] < .9) continue;
  printf("El%d ", e);
}

/* print number of solutions stored */
error = GRBgetintattr(model, GRB_INT_ATTR_SOLCOUNT, &nSolutions);
if (error) goto QUIT;
printf("\nNumber of solutions found: %d\nValues:", nSolutions);

/* print objective values of alternative solutions */
```

(continues on next page)

(continued from previous page)

```
  prlen = 0;
  for (e = 0; e < nSolutions; e++) {
    error = GRBsetintparam(menv, GRB_INT_PAR_SOLUTIONNUMBER, e);
    if (error) goto QUIT;

    error = GRBgetdblattr(model, GRB_DBL_ATTR_POOLNOBJVAL, &objval);
    if (error) goto QUIT;

    prlen += printf(" %g", objval);
    if (prlen >= 75 && e+1 < nSolutions) {
      prlen = printf("\n    ");
    }
  }
  printf("\n");

  /* print fourth best set if available */
  if (nSolutions >= 4) {
    error = GRBsetintparam(menv, GRB_INT_PAR_SOLUTIONNUMBER, 3);
    if (error) goto QUIT;

    /* get the solution vector */
    error = GRBgetdblattrarray(model, GRB_DBL_ATTR_POOLNX, 0, groundSetSize, cval);
    if (error) goto QUIT;

    printf("Selected elements in fourth best solution:\n\t");
    for (e = 0; e < groundSetSize; e++) {
      if (cval[e] < .9) continue;
      printf("El%d ", e);
    }
    printf("\n");
  }

QUIT:
  if (model != NULL) GRBfreemodel(model);
  if (env != NULL)   GRBfreeenv(env);
  if (cind != NULL)  free(cind);
  if (cval != NULL)  free(cval);
  return error;
}
```

qcp_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QCP model:

     maximize    x
     subject to  x + y + z = 1
                 x^2 + y^2 <= z^2 (second-order cone)
                 x^2 <= yz        (rotated second-order cone)
```

(continues on next page)

(continued from previous page)

```
                x, y, z non-negative
*/

#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  double    sol[3];
  int       ind[3];
  double    val[3];
  double    obj[] = {1, 0, 0};
  int       qrow[3];
  int       qcol[3];
  double    qval[3];
  int       optimstatus;
  double    objval;

  /* Create environment */

  error = GRBloadenv(&env, "qcp.log");
  if (error) goto QUIT;

  /* Create an empty model */

  error = GRBnewmodel(env, &model, "qcp", 0, NULL, NULL, NULL, NULL, NULL);
  if (error) goto QUIT;


  /* Add variables */

  error = GRBaddvars(model, 3, 0, NULL, NULL, NULL, obj, NULL, NULL, NULL,
                     NULL);
  if (error) goto QUIT;

  /* Change sense to maximization */

  error = GRBsetintattr(model, GRB_INT_ATTR_MODELSENSE, GRB_MAXIMIZE);
  if (error) goto QUIT;

  /* Linear constraint: x + y + z = 1 */

  ind[0] = 0; ind[1] = 1; ind[2] = 2;
  val[0] = 1; val[1] = 1; val[2] = 1;

  error = GRBaddconstr(model, 3, ind, val, GRB_EQUAL, 1.0, "c0");
```

(continues on next page)

(continued from previous page)

```
if (error) goto QUIT;

/* Cone: x^2 + y^2 <= z^2 */

qrow[0] = 0; qcol[0] = 0; qval[0] = 1.0;
qrow[1] = 1; qcol[1] = 1; qval[1] = 1.0;
qrow[2] = 2; qcol[2] = 2; qval[2] = -1.0;

error = GRBaddqconstr(model, 0, NULL, NULL, 3, qrow, qcol, qval,
                      GRB_LESS_EQUAL, 0.0, "qc0");
if (error) goto QUIT;

/* Rotated cone: x^2 <= yz */

qrow[0] = 0; qcol[0] = 0; qval[0] = 1.0;
qrow[1] = 1; qcol[1] = 2; qval[1] = -1.0;

error = GRBaddqconstr(model, 0, NULL, NULL, 2, qrow, qcol, qval,
                      GRB_LESS_EQUAL, 0.0, "qc1");
if (error) goto QUIT;

/* Optimize model */

error = GRBoptimize(model);
if (error) goto QUIT;

/* Write model to 'qcp.lp' */

error = GRBwrite(model, "qcp.lp");
if (error) goto QUIT;

/* Capture solution information */

error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
if (error) goto QUIT;

error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
if (error) goto QUIT;

error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 3, sol);
if (error) goto QUIT;

printf("\nOptimization complete\n");
if (optimstatus == GRB_OPTIMAL) {
  printf("Optimal objective: %.4e\n", objval);

  printf("  x=%.2f, y=%.2f, z=%.2f\n", sol[0], sol[1], sol[2]);
} else if (optimstatus == GRB_INF_OR_UNBD) {
  printf("Model is infeasible or unbounded\n");
} else {
  printf("Optimization was stopped early\n");
}
```

(continues on next page)

(continued from previous page)

```
QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

qp_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QP model:

     minimize    x^2 + x*y + y^2 + y*z + z^2 + 2 x
     subject to  x + 2 y + 3 z >= 4
                 x +   y       >= 1
                 x, y, z non-negative

   It solves it once as a continuous model, and once as an integer model.
*/

#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  double    sol[3];
  int       ind[3];
  double    val[3];
  int       qrow[5];
```

(continues on next page)

(continued from previous page)

```
int       qcol[5];
double    qval[5];
char      vtype[3];
int       optimstatus;
double    objval;

/* Create environment */

error = GRBloadenv(&env, "qp.log");
if (error) goto QUIT;

/* Create an empty model */

error = GRBnewmodel(env, &model, "qp", 0, NULL, NULL, NULL, NULL, NULL);
if (error) goto QUIT;

/* Add variables */

error = GRBaddvars(model, 3, 0, NULL, NULL, NULL, NULL, NULL, NULL, NULL,
                   NULL);
if (error) goto QUIT;

/* Quadratic objective terms */

qrow[0] = 0; qrow[1] = 0; qrow[2] = 1; qrow[3] = 1; qrow[4] = 2;
qcol[0] = 0; qcol[1] = 1; qcol[2] = 1; qcol[3] = 2; qcol[4] = 2;
qval[0] = 1; qval[1] = 1; qval[2] = 1; qval[3] = 1; qval[4] = 1;

error = GRBaddqpterms(model, 5, qrow, qcol, qval);
if (error) goto QUIT;

/* Linear objective term */

error = GRBsetdblattrelement(model, GRB_DBL_ATTR_OBJ, 0, 2.0);
if (error) goto QUIT;

/* First constraint: x + 2 y + 3 z <= 4 */

ind[0] = 0; ind[1] = 1; ind[2] = 2;
val[0] = 1; val[1] = 2; val[2] = 3;

error = GRBaddconstr(model, 3, ind, val, GRB_GREATER_EQUAL, 4.0, "c0");
if (error) goto QUIT;

/* Second constraint: x + y >= 1 */

ind[0] = 0; ind[1] = 1;
val[0] = 1; val[1] = 1;

error = GRBaddconstr(model, 2, ind, val, GRB_GREATER_EQUAL, 1.0, "c1");
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
/* Optimize model */

error = GRBoptimize(model);
if (error) goto QUIT;

/* Write model to 'qp.lp' */

error = GRBwrite(model, "qp.lp");
if (error) goto QUIT;

/* Capture solution information */

error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
if (error) goto QUIT;

error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
if (error) goto QUIT;

error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 3, sol);
if (error) goto QUIT;

printf("\nOptimization complete\n");
if (optimstatus == GRB_OPTIMAL) {
  printf("Optimal objective: %.4e\n", objval);

  printf("  x=%.4f, y=%.4f, z=%.4f\n", sol[0], sol[1], sol[2]);
} else if (optimstatus == GRB_INF_OR_UNBD) {
  printf("Model is infeasible or unbounded\n");
} else {
  printf("Optimization was stopped early\n");
}


/* Modify variable types */

vtype[0] = GRB_INTEGER; vtype[1] = GRB_INTEGER; vtype[2] = GRB_INTEGER;

error = GRBsetcharattrarray(model, GRB_CHAR_ATTR_VTYPE, 0, 3, vtype);
if (error) goto QUIT;

/* Optimize model */

error = GRBoptimize(model);
if (error) goto QUIT;

/* Write model to 'qp2.lp' */

error = GRBwrite(model, "qp2.lp");
if (error) goto QUIT;

/* Capture solution information */
```

(continues on next page)

(continued from previous page)

```
  error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
  if (error) goto QUIT;

  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;

  error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 3, sol);
  if (error) goto QUIT;

  printf("\nOptimization complete\n");
  if (optimstatus == GRB_OPTIMAL) {
    printf("Optimal objective: %.4e\n", objval);

    printf("  x=%.4f, y=%.4f, z=%.4f\n", sol[0], sol[1], sol[2]);
  } else if (optimstatus == GRB_INF_OR_UNBD) {
    printf("Model is infeasible or unbounded\n");
  } else {
    printf("Optimization was stopped early\n");
  }

QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

sensitivity_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* A simple sensitivity analysis example which reads a MIP model from a
 * file and solves it. Then uses the scenario feature to analyze the impact
 * w.r.t. the objective function of each binary variable if it is set to
 * 1-X, where X is its value in the optimal solution.
 *
 * Usage:
```

(continues on next page)

(continued from previous page)

```
 *     sensitivity_c <model filename>
 */

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include "gurobi_c.h"

/* Maximum number of scenarios to be considered */
#define MAXSCENARIOS 100

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env      = NULL;
  GRBenv   *modelenv = NULL;
  GRBmodel *model    = NULL;

  double *origx = NULL;
  double  origObjVal;

  int ismip, status, numvars, i;
  int scenarios;
  int error = 0;

  if (argc < 2) {
    fprintf(stderr, "Usage: sensitivity_c filename\n");
    goto QUIT;
  }

  /* Create environment */
  error = GRBloadenv(&env, "sensitivity.log");
  if (error) goto QUIT;

  /* Read model */
  error = GRBreadmodel(env, argv[1], &model);
  if (error) goto QUIT;

  modelenv = GRBgetenv(model);
  assert(modelenv != NULL);

  error = GRBgetintattr(model, GRB_INT_ATTR_IS_MIP, &ismip);
  if (error) goto QUIT;
  if (ismip == 0) {
    printf("Model is not a MIP\n");
    goto QUIT;
  }

  /* Solve model */
  error = GRBoptimize(model);
  if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &status);
if (error) goto QUIT;
if (status != GRB_OPTIMAL) {
  printf("Optimization ended with status %d\n", status);
  goto QUIT;
}

/* Store the optimal solution */
error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &origObjVal);
if (error) goto QUIT;
error = GRBgetintattr(model, GRB_INT_ATTR_NUMVARS, &numvars);
if (error) goto QUIT;
origx = (double *) malloc(numvars * sizeof(double));
if (origx == NULL) {
  printf("Out of memory\n");
  goto QUIT;
}
error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, numvars, origx);
if (error) goto QUIT;

scenarios = 0;

/* Count number of unfixed, binary variables in model. For each we create a
 * scenario.
 */
for (i = 0; i < numvars; i++) {
  double lb, ub;
  char   vtype;

  error = GRBgetdblattrelement(model, GRB_DBL_ATTR_LB, i, &lb);
  if (error) goto QUIT;
  error = GRBgetdblattrelement(model, GRB_DBL_ATTR_UB, i, &ub);
  if (error) goto QUIT;
  error = GRBgetcharattrelement(model, GRB_CHAR_ATTR_VTYPE, i, &vtype);
  if (error) goto QUIT;

  if (lb == 0.0 && ub == 1.0                          &&
      (vtype == GRB_BINARY || vtype == GRB_INTEGER)   ) {
    scenarios++;

    if (scenarios >= MAXSCENARIOS)
      break;
  }
}

printf("###  construct multi-scenario model with %d scenarios\n", scenarios);

/* Set the number of scenarios in the model */
error = GRBsetintattr(model, GRB_INT_ATTR_NUMSCENARIOS, scenarios);
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
scenarios = 0;

/* Create a (single) scenario model by iterating through unfixed binary
 * variables in the model and create for each of these variables a
 * scenario by fixing the variable to 1-X, where X is its value in the
 * computed optimal solution
 */
for (i = 0; i < numvars; i++) {
  double lb, ub;
  char   vtype;

  error = GRBgetdblattrelement(model, GRB_DBL_ATTR_LB, i, &lb);
  if (error) goto QUIT;
  error = GRBgetdblattrelement(model, GRB_DBL_ATTR_UB, i, &ub);
  if (error) goto QUIT;
  error = GRBgetcharattrelement(model, GRB_CHAR_ATTR_VTYPE, i, &vtype);
  if (error) goto QUIT;

  if (lb == 0.0 && ub == 1.0                          &&
      (vtype == GRB_BINARY || vtype == GRB_INTEGER) &&
      scenarios < MAXSCENARIOS                          ) {

    /* Set ScenarioNumber parameter to select the corresponding scenario
     * for adjustments
     */
    error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, scenarios);
    if (error) goto QUIT;

    /* Set variable to 1-X, where X is its value in the optimal solution */
    if (origx[i] < 0.5) {
      error = GRBsetdblattrelement(model, GRB_DBL_ATTR_SCENNLB, i, 1.0);
      if (error) goto QUIT;
    } else {
      error = GRBsetdblattrelement(model, GRB_DBL_ATTR_SCENNUB, i, 0.0);
      if (error) goto QUIT;
    }


    scenarios++;
  } else {
    /* Add MIP start for all other variables using the optimal solution
     * of the base model
     */
    error = GRBsetdblattrelement(model, GRB_DBL_ATTR_START, i, origx[i]);
    if (error) goto QUIT;
  }
}

/* Solve multi-scenario model */
error = GRBoptimize(model);
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
/* Collect the status */
error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &status);
if (error) goto QUIT;

/* In case we solved the scenario model to optimality capture the
 * sensitivity information
 */
if (status == GRB_OPTIMAL) {
  int modelSense;

  scenarios = 0;

  /* Get model sense (minimization or maximization) */
  error = GRBgetintattr(model, GRB_INT_ATTR_MODELSENSE, &modelSense);
  if (error) goto QUIT;

  for (i = 0; i < numvars; i++) {
    double lb, ub;
    char   vtype;

    error = GRBgetdblattrelement(model, GRB_DBL_ATTR_LB, i, &lb);
    if (error) goto QUIT;
    error = GRBgetdblattrelement(model, GRB_DBL_ATTR_UB, i, &ub);
    if (error) goto QUIT;
    error = GRBgetcharattrelement(model, GRB_CHAR_ATTR_VTYPE, i, &vtype);
    if (error) goto QUIT;

    if (lb == 0.0 && ub == 1.0                          &&
        (vtype == GRB_BINARY || vtype == GRB_INTEGER)   ) {

      double scenarioObjVal;
      double scenarioObjBound;
      char  *varName;

      /* Set scenario parameter to collect the objective value of the
       * corresponding scenario
       */
      error = GRBsetintparam(modelenv, GRB_INT_PAR_SCENARIONUMBER, scenarios);
      if (error) goto QUIT;

      /* Collect objective value and bound for the scenario */
      error = GRBgetdblattr(model, GRB_DBL_ATTR_SCENNOBJVAL, &scenarioObjVal);
      if (error) goto QUIT;
      error = GRBgetdblattr(model, GRB_DBL_ATTR_SCENNOBJBOUND, &scenarioObjBound);
      if (error) goto QUIT;

      error = GRBgetstrattrelement(model, GRB_STR_ATTR_VARNAME, i, &varName);
      if (error) goto QUIT;

      /* Check if we found a feasible solution for this scenario */
      if (modelSense * scenarioObjVal >= GRB_INFINITY) {
        /* Check if the scenario is infeasible */
```

(continues on next page)

(continued from previous page)

```
          if (modelSense * scenarioObjBound >= GRB_INFINITY)
            printf("Objective sensitivity for variable %s is infeasible\n",
                   varName);
          else
            printf("Objective sensitivity for variable %s is unknown (no solution␣
↪available)\n",
                   varName);
        } else {
          /* Scenario is feasible and a solution is available */
          printf("Objective sensitivity for variable %s is %g\n",
                 varName, modelSense * (scenarioObjVal - origObjVal));
        }

        scenarios++;

        if (scenarios >= MAXSCENARIOS)
          break;
      }
    }
  }

QUIT:

  /* Error reporting */
  if (error != 0) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */
  free(origx);

  /* Free model */
  GRBfreemodel(model);

  /* Free environment */
  GRBfreeenv(env);

  return 0;
}
```

sos_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example creates a very simple Special Ordered Set (SOS) model.
   The model consists of 3 continuous variables, no linear constraints,
   and a pair of SOS constraints of type 1. */

#include <stdlib.h>
```

(continues on next page)

(continued from previous page)

```c
#include <stdio.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0;
  double    x[3];
  double    obj[3];
  double    ub[3];
  int       sostype[2];
  int       sosbeg[2];
  int       sosind[4];
  double    soswt[4];
  int       optimstatus;
  double    objval;

  /* Create environment */

  error = GRBloadenv(&env, "sos.log");
  if (error) goto QUIT;

  /* Create an empty model */

  error = GRBnewmodel(env, &model, "sos", 0, NULL, NULL, NULL, NULL, NULL);
  if (error) goto QUIT;


  /* Add variables */

  obj[0] = -2; obj[1] = -1; obj[2] = -1;
  ub[0] = 1.0; ub[1] = 1.0; ub[2] = 2.0;
  error = GRBaddvars(model, 3, 0, NULL, NULL, NULL, obj, NULL, ub, NULL,
                     NULL);
  if (error) goto QUIT;

  /* Build first SOS1: x0=0 or x1=0 */

  sosind[0] = 0; sosind[1] = 1;
  soswt[0] = 1.0; soswt[1] = 2.0;
  sosbeg[0] = 0; sostype[0] = GRB_SOS_TYPE1;

  /* Build second SOS1: x0=0 or x2=0 */

  sosind[2] = 0; sosind[3] = 2;
  soswt[2] = 1.0; soswt[3] = 2.0;
  sosbeg[1] = 2; sostype[1] = GRB_SOS_TYPE1;

  /* Add SOSs to model */
```

(continues on next page)

(continued from previous page)

```
  error = GRBaddsos(model, 2, 4, sostype, sosbeg, sosind, soswt);
  if (error) goto QUIT;

  /* Optimize model */

  error = GRBoptimize(model);
  if (error) goto QUIT;

  /* Write model to 'sos.lp' */

  error = GRBwrite(model, "sos.lp");
  if (error) goto QUIT;

  /* Capture solution information */

  error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
  if (error) goto QUIT;

  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;

  error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, 3, x);
  if (error) goto QUIT;

  printf("\nOptimization complete\n");
  if (optimstatus == GRB_OPTIMAL) {
    printf("Optimal objective: %.4e\n", objval);

    printf("  x=%.4f, y=%.4f, z=%.4f\n", x[0], x[1], x[2]);
  } else if (optimstatus == GRB_INF_OR_UNBD) {
    printf("Model is infeasible or unbounded\n");
  } else {
    printf("Optimization was stopped early\n");
  }

QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);
```

(continues on next page)

(continued from previous page)

```
  return 0;
}
```

sudoku_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */
/*
  Sudoku example.

  The Sudoku board is a 9x9 grid, which is further divided into a 3x3 grid
  of 3x3 grids.  Each cell in the grid must take a value from 0 to 9.
  No two grid cells in the same row, column, or 3x3 subgrid may take the
  same value.

  In the MIP formulation, binary variables x[i,j,v] indicate whether
  cell <i,j> takes value 'v'.  The constraints are as follows:
    1. Each cell must take exactly one value (sum_v x[i,j,v] = 1)
    2. Each value is used exactly once per row (sum_i x[i,j,v] = 1)
    3. Each value is used exactly once per column (sum_j x[i,j,v] = 1)
    4. Each value is used exactly once per 3x3 subgrid (sum_grid x[i,j,v] = 1)

  Input datasets for this example can be found in examples/data/sudoku*.
*/

#include <stdlib.h>
#include <stdio.h>
#include <string.h>
#include "gurobi_c.h"

#define SUBDIM  3
#define DIM     (SUBDIM*SUBDIM)

int
main(int   argc,
     char *argv[])
{
  FILE     *fp     = NULL;
  GRBenv   *env    = NULL;
  GRBmodel *model  = NULL;
  int       board[DIM][DIM];
  char      inputline[100];
  int       ind[DIM];
  double    val[DIM];
  double    lb[DIM*DIM*DIM];
  char      vtype[DIM*DIM*DIM];
  char     *names[DIM*DIM*DIM];
  char      namestorage[10*DIM*DIM*DIM];
  char     *cursor;
  int       optimstatus;
```

(continues on next page)

(continued from previous page)

```
double    objval;
int       i, j, v, ig, jg, count;
int       error = 0;

if (argc < 2) {
  fprintf(stderr, "Usage: sudoku_c datafile\n");
  exit(1);
}

fp = fopen(argv[1], "r");
if (fp == NULL) {
  fprintf(stderr, "Error: unable to open input file %s\n", argv[1]);
  exit(1);
}

for (i = 0; i < DIM; i++) {
  fgets(inputline, 100, fp);
  if (strlen(inputline) < 9) {
    fprintf(stderr, "Error: not enough board positions specified\n");
    exit(1);
  }
  for (j = 0; j < DIM; j++) {
    board[i][j] = (int) inputline[j] - (int) '1';
    if (board[i][j] < 0 || board[i][j] >= DIM)
      board[i][j] = -1;
  }
}

/* Create an empty model */

cursor = namestorage;
for (i = 0; i < DIM; i++) {
  for (j = 0; j < DIM; j++) {
    for (v = 0; v < DIM; v++) {
      if (board[i][j] == v)
        lb[i*DIM*DIM+j*DIM+v] = 1;
      else
        lb[i*DIM*DIM+j*DIM+v] = 0;
      vtype[i*DIM*DIM+j*DIM+v] = GRB_BINARY;

      names[i*DIM*DIM+j*DIM+v] = cursor;
      sprintf(names[i*DIM*DIM+j*DIM+v], "x[%d,%d,%d]", i, j, v+1);
      cursor += strlen(names[i*DIM*DIM+j*DIM+v]) + 1;
    }
  }
}

/* Create environment */

error = GRBloadenv(&env, "sudoku.log");
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
/* Create new model */

error = GRBnewmodel(env, &model, "sudoku", DIM*DIM*DIM, NULL, lb, NULL,
                    vtype, names);
if (error) goto QUIT;

/* Each cell gets a value */

for (i = 0; i < DIM; i++) {
  for (j = 0; j < DIM; j++) {
    for (v = 0; v < DIM; v++) {
      ind[v] = i*DIM*DIM + j*DIM + v;
      val[v] = 1.0;
    }

    error = GRBaddconstr(model, DIM, ind, val, GRB_EQUAL, 1.0, NULL);
    if (error) goto QUIT;
  }
}

/* Each value must appear once in each row */

for (v = 0; v < DIM; v++) {
  for (j = 0; j < DIM; j++) {
    for (i = 0; i < DIM; i++) {
      ind[i] = i*DIM*DIM + j*DIM + v;
      val[i] = 1.0;
    }

    error = GRBaddconstr(model, DIM, ind, val, GRB_EQUAL, 1.0, NULL);
    if (error) goto QUIT;
  }
}

/* Each value must appear once in each column */

for (v = 0; v < DIM; v++) {
  for (i = 0; i < DIM; i++) {
    for (j = 0; j < DIM; j++) {
      ind[j] = i*DIM*DIM + j*DIM + v;
      val[j] = 1.0;
    }

    error = GRBaddconstr(model, DIM, ind, val, GRB_EQUAL, 1.0, NULL);
    if (error) goto QUIT;
  }
}

/* Each value must appear once in each subgrid */

for (v = 0; v < DIM; v++) {
  for (ig = 0; ig < SUBDIM; ig++) {
```

(continues on next page)

(continued from previous page)

```
      for (jg = 0; jg < SUBDIM; jg++) {
        count = 0;
        for (i = ig*SUBDIM; i < (ig+1)*SUBDIM; i++) {
          for (j = jg*SUBDIM; j < (jg+1)*SUBDIM; j++) {
            ind[count] = i*DIM*DIM + j*DIM + v;
            val[count] = 1.0;
            count++;
          }
        }

        error = GRBaddconstr(model, DIM, ind, val, GRB_EQUAL, 1.0, NULL);
        if (error) goto QUIT;
      }
    }
  }

  /* Optimize model */

  error = GRBoptimize(model);
  if (error) goto QUIT;

  /* Write model to 'sudoku.lp' */

  error = GRBwrite(model, "sudoku.lp");
  if (error) goto QUIT;

  /* Capture solution information */

  error = GRBgetintattr(model, GRB_INT_ATTR_STATUS, &optimstatus);
  if (error) goto QUIT;

  error = GRBgetdblattr(model, GRB_DBL_ATTR_OBJVAL, &objval);
  if (error) goto QUIT;

  printf("\nOptimization complete\n");
  if (optimstatus == GRB_OPTIMAL)
    printf("Optimal objective: %.4e\n", objval);
  else if (optimstatus == GRB_INF_OR_UNBD)
    printf("Model is infeasible or unbounded\n");
  else
    printf("Optimization was stopped early\n");
  printf("\n");

QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }
```

(continues on next page)

(continued from previous page)

```
  fclose(fp);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

tsp_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/*
  Solve a traveling salesman problem on a randomly generated set of
  points using lazy constraints.   The base MIP model only includes
  'degree-2' constraints, requiring each node to have exactly
  two incident edges.  Solutions to this model may contain subtours -
  tours that don't visit every node.  The lazy constraint callback
  adds new constraints to cut them off.
*/

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"


/* Define structure to pass data to the callback function */

struct callback_data {
  int n;
};


/* Given an integer-feasible solution 'sol', find the smallest
   sub-tour.  Result is returned in 'tour', and length is
   returned in 'tourlenP'. */

static void
findsubtour(int     n,
            double *sol,
            int    *tourlenP,
            int    *tour)
{
  int i, node, len, start;
```

(continues on next page)

(continued from previous page)

```
  int bestind, bestlen;
  int *seen = NULL;

  seen = (int *) malloc(n*sizeof(int));
  if (seen == NULL) {
    fprintf(stderr, "Out of memory\n");
    exit(1);
  }

  for (i = 0; i < n; i++)
    seen[i] = 0;

  start   = 0;
  bestlen = n+1;
  bestind = -1;
  while (start < n) {
    for (node = 0; node < n; node++)
      if (seen[node] == 0)
        break;
    if (node == n)
      break;
    for (len = 0; len < n; len++) {
      tour[start+len] = node;
      seen[node] = 1;
      for (i = 0; i < n; i++) {
        if (sol[node*n+i] > 0.5 && !seen[i]) {
          node = i;
          break;
        }
      }
      if (i == n) {
        len++;
        if (len < bestlen) {
          bestlen = len;
          bestind = start;
        }
        start += len;
        break;
      }
    }
  }

  for (i = 0; i < bestlen; i++)
    tour[i] = tour[bestind+i];
  *tourlenP = bestlen;

  free(seen);
}


/* Subtour elimination callback.  Whenever a feasible solution is found,
   find the shortest subtour, and add a subtour elimination constraint
```

(continues on next page)

(continued from previous page)

```
   if that tour doesn't visit every node. */

int __stdcall
subtourelim(GRBmodel *model,
            void     *cbdata,
            int       where,
            void     *usrdata)
{
  struct callback_data *mydata = (struct callback_data *) usrdata;
  int n = mydata->n;
  int *tour = NULL;
  double *sol = NULL;
  int i, j, len, nz;
  int error = 0;

  if (where == GRB_CB_MIPSOL) {
    sol  = (double *) malloc(n*n*sizeof(double));
    tour = (int *)    malloc(n*sizeof(int));
    if (sol == NULL || tour == NULL) {
      fprintf(stderr, "Out of memory\n");
      exit(1);
    }

    GRBcbget(cbdata, where, GRB_CB_MIPSOL_SOL, sol);

    findsubtour(n, sol, &len, tour);

    if (len < n) {
      int    *ind = NULL;
      double *val = NULL;

      ind = (int *)    malloc(len*(len-1)/2*sizeof(int));
      val = (double *) malloc(len*(len-1)/2*sizeof(double));

      if (ind == NULL || val == NULL) {
        fprintf(stderr, "Out of memory\n");
        exit(1);
      }

      /* Add subtour elimination constraint */

      nz = 0;
      for (i = 0; i < len; i++)
        for (j = i+1; j < len; j++)
          ind[nz++] = tour[i]*n+tour[j];
      for (i = 0; i < nz; i++)
        val[i] = 1.0;

      error = GRBcblazy(cbdata, nz, ind, val, GRB_LESS_EQUAL, len-1);

      free(ind);
      free(val);
```

(continues on next page)

(continued from previous page)

```
    }

    free(sol);
    free(tour);
  }

  return error;
}

/* Euclidean distance between points 'i' and 'j'. */

static double
distance(double *x,
         double *y,
         int     i,
         int     j)
{
  double dx = x[i] - x[j];
  double dy = y[i] - y[j];

  return sqrt(dx*dx + dy*dy);
}

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       i, j, len, n, solcount;
  int       error = 0;
  char      name[100];
  double   *x = NULL;
  double   *y = NULL;
  int      *ind = NULL;
  double   *val = NULL;
  struct callback_data mydata;

  if (argc < 2) {
    fprintf(stderr, "Usage: tsp_c size\n");
    exit(1);
  }

  n = atoi(argv[1]);
  if (n == 0) {
    fprintf(stderr, "Argument must be a positive integer.\n");
  } else if (n > 100) {
    printf("It will be a challenge to solve a TSP this large.\n");
  }

  x   = (double *) malloc(n*sizeof(double));
  y   = (double *) malloc(n*sizeof(double));
```

(continues on next page)

(continued from previous page)

```
ind = (int *)    malloc(n*sizeof(int));
val = (double *) malloc(n*sizeof(double));

if (x == NULL || y == NULL || ind == NULL || val == NULL) {
  fprintf(stderr, "Out of memory\n");
  exit(1);
}

/* Create random points */

for (i = 0; i < n; i++) {
  x[i] = ((double) rand())/RAND_MAX;
  y[i] = ((double) rand())/RAND_MAX;
}

/* Create environment */

error = GRBloadenv(&env, "tsp.log");
if (error) goto QUIT;

/* Create an empty model */

error = GRBnewmodel(env, &model, "tsp", 0, NULL, NULL, NULL, NULL, NULL);
if (error) goto QUIT;


/* Add variables - one for every pair of nodes */
/* Note: If edge from i to j is chosen, then x[i*n+j] = x[j*n+i] = 1. */
/* The cost is split between the two variables. */

for (i = 0; i < n; i++) {
  for (j = 0; j < n; j++) {
    sprintf(name, "x_%d_%d", i, j);
    error = GRBaddvar(model, 0, NULL, NULL, distance(x, y, i, j)/2,
                      0.0, 1.0, GRB_BINARY, name);
    if (error) goto QUIT;
  }
}

/* Degree-2 constraints */

for (i = 0; i < n; i++) {
  for (j = 0; j < n; j++) {
    ind[j] = i*n+j;
    val[j] = 1.0;
  }

  sprintf(name, "deg2_%d", i);

  error = GRBaddconstr(model, n, ind, val, GRB_EQUAL, 2, name);
  if (error) goto QUIT;
}
```

(continues on next page)

(continued from previous page)

```
/* Forbid edge from node back to itself */

for (i = 0; i < n; i++) {
  error = GRBsetdblattrelement(model, GRB_DBL_ATTR_UB, i*n+i, 0);
  if (error) goto QUIT;
}

/* Symmetric TSP */

for (i = 0; i < n; i++) {
  for (j = 0; j < i; j++) {
    ind[0] = i*n+j;
    ind[1] = i+j*n;
    val[0] = 1;
    val[1] = -1;
    error = GRBaddconstr(model, 2, ind, val, GRB_EQUAL, 0, NULL);
    if (error) goto QUIT;
  }
}

/* Set callback function */

mydata.n = n;

error = GRBsetcallbackfunc(model, subtourelim, (void *) &mydata);
if (error) goto QUIT;

/* Must set LazyConstraints parameter when using lazy constraints */

error = GRBsetintparam(GRBgetenv(model), GRB_INT_PAR_LAZYCONSTRAINTS, 1);
if (error) goto QUIT;

/* Optimize model */

error = GRBoptimize(model);
if (error) goto QUIT;

/* Extract solution */

error = GRBgetintattr(model, GRB_INT_ATTR_SOLCOUNT, &solcount);
if (error) goto QUIT;

if (solcount > 0) {
  int *tour = NULL;
  double *sol = NULL;

  sol = (double *) malloc(n*n*sizeof(double));
  tour = (int *) malloc(n*sizeof(int));
  if (sol == NULL || tour == NULL) {
    fprintf(stderr, "Out of memory\n");
    exit(1);
```

(continues on next page)

(continued from previous page)

```
    }

    error = GRBgetdblattrarray(model, GRB_DBL_ATTR_X, 0, n*n, sol);
    if (error) goto QUIT;

    /* Print tour */

    findsubtour(n, sol, &len, tour);

    printf("Tour: ");
    for (i = 0; i < len; i++)
      printf("%d ", tour[i]);
    printf("\n");

    free(tour);
    free(sol);
  }

QUIT:

  /* Free data */

  free(x);
  free(y);
  free(ind);
  free(val);

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

tune_c.c

```c
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a model from a file and tunes it.
   It then writes the best parameter settings to a file
   and solves the model using these parameters. */

#include <assert.h>
#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"

int
main(int   argc,
     char *argv[])
{
  GRBenv   *env      = NULL;
  GRBenv   *modelenv = NULL;
  GRBmodel *model    = NULL;

  int tuneresultcount;
  int error = 0;

  if (argc < 2) {
    fprintf(stderr, "Usage: tune_c filename\n");
    exit(1);
  }

  /* Create environment */

  error = GRBloadenv(&env, "tune_c.log");
  if (error) goto QUIT;

  /* Read model from file */

  error = GRBreadmodel(env, argv[1], &model);
  if (error) goto QUIT;

  /* Retrieve model env to set some parameters */

  modelenv = GRBgetenv(model);
  assert(modelenv != NULL);

  /* Set a time limit for the model */

  error = GRBsetdblparam(modelenv, GRB_DBL_PAR_TIMELIMIT, 5);
  if (error) goto QUIT;

  /* Set a time limit for the whole tuning run
   * Note that both time limits are chosen to have a quick demonstration.
   * In general, a total tune time limit should be set such that the
```

(continues on next page)

(continued from previous page)

```
   * tuning tool can test several hundreds of parameter settings.
   */

  error = GRBsetdblparam(modelenv, GRB_DBL_PAR_TUNETIMELIMIT, 60);
  if (error) goto QUIT;

  /* Set the TuneResults parameter to 2
   *
   * The first parameter setting is the result for the first solved
   * setting. The second entry the parameter setting of the best parameter
   * setting.
   */
  error = GRBsetintparam(modelenv, GRB_INT_PAR_TUNERESULTS, 2);
  if (error) goto QUIT;

  /* Tune the model */

  error = GRBtunemodel(model);
  if (error) goto QUIT;

  /* Get the number of tuning results */

  error = GRBgetintattr(model, GRB_INT_ATTR_TUNE_RESULTCOUNT, &tuneresultcount);
  if (error) goto QUIT;

  if (tuneresultcount >= 2) {

    /* Load the best tuned parameters into the model's environment
     *
     * Note, the first parameter setting is associated to the first solved
     * setting and the second parameter setting to best tune result.
     */
    error = GRBgettuneresult(model, 1);
    if (error) goto QUIT;

    /* Write tuned parameters to a file */

    error = GRBwrite(model, "tune.prm");
    if (error) goto QUIT;

    /* Solve the model using the tuned parameters */

    error = GRBoptimize(model);
    if (error) goto QUIT;
  }

QUIT:

  /* Error reporting */

  if (error) {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
```

(continues on next page)

(continued from previous page)

```
    exit(1);
  }

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

workforce1_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, use IIS to find a set of
   conflicting constraints. Note that there may be additional conflicts
   besides what is reported via IIS. */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include "gurobi_c.h"


#define xcol(w,s)  nShifts*w+s
#define MAXSTR     128


int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0, status;
  int       s, w, col;
  int      *cbeg = NULL;
  int      *cind = NULL;
  int       idx;
  double   *cval = NULL;
  char     *sense = NULL;
  char      vname[MAXSTR];
  double    obj;
  int       i, iis, numconstrs;
  char     *cname;
```

(continues on next page)

(continued from previous page)

```
/* Sample data */
const int nShifts = 14;
const int nWorkers = 7;

/* Sets of days and workers */
char* Shifts[] =
  { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
    "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
    "Sun14" };
char* Workers[] =
  { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

/* Number of workers required for each shift */
double shiftRequirements[] =
  { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

/* Amount each worker is paid to work one shift */
double pay[] = { 10, 12, 10, 8, 8, 9, 11 };

/* Worker availability: 0 if the worker is unavailable for a shift */
double availability[][14] =
  { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
    { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
    { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
    { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
    { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

/* Create environment */
error = GRBloadenv(&env, "workforce1.log");
if (error) goto QUIT;

/* Create initial model */
error = GRBnewmodel(env, &model, "workforce1", nWorkers * nShifts,
                    NULL, NULL, NULL, NULL, NULL);
if (error) goto QUIT;

/* Initialize assignment decision variables:
   x[w][s] == 1 if worker w is assigned
   to shift s. Since an assignment model always produces integer
   solutions, we use continuous variables and solve as an LP. */
for (w = 0; w < nWorkers; ++w)
{
  for (s = 0; s < nShifts; ++s)
  {
    col = xcol(w, s);
    sprintf(vname, "%s.%s", Workers[w], Shifts[s]);
    error = GRBsetdblattrelement(model, "UB", col, availability[w][s]);
    if (error) goto QUIT;
    error = GRBsetdblattrelement(model, "Obj", col, pay[w]);
```

(continues on next page)

(continued from previous page)

```
    if (error) goto QUIT;
    error = GRBsetstrattrelement(model, "VarName", col, vname);
    if (error) goto QUIT;
  }
}

/* The objective is to minimize the total pay costs */
error = GRBsetintattr(model, "ModelSense", GRB_MINIMIZE);
if (error) goto QUIT;

/* Make space for constraint data */
cbeg = malloc(sizeof(int) * nShifts);
if (!cbeg) goto QUIT;
cind = malloc(sizeof(int) * nShifts * nWorkers);
if (!cind) goto QUIT;
cval = malloc(sizeof(double) * nShifts * nWorkers);
if (!cval) goto QUIT;
sense = malloc(sizeof(char) * nShifts);
if (!sense) goto QUIT;

/* Constraint: assign exactly shiftRequirements[s] workers
   to each shift s */
idx = 0;
for (s = 0; s < nShifts; ++s)
{
  cbeg[s] = idx;
  sense[s] = GRB_EQUAL;
  for (w = 0; w < nWorkers; ++w)
  {
    cind[idx] = xcol(w, s);
    cval[idx++] = 1.0;
  }
}
error = GRBaddconstrs(model, nShifts, idx, cbeg, cind, cval, sense,
                      shiftRequirements, Shifts);
if (error) goto QUIT;

/* Optimize */
error = GRBoptimize(model);
if (error) goto QUIT;
error = GRBgetintattr(model, "Status", &status);
if (error) goto QUIT;
if (status == GRB_UNBOUNDED)
{
  printf("The model cannot be solved because it is unbounded\n");
  goto QUIT;
}
if (status == GRB_OPTIMAL)
{
  error = GRBgetdblattr(model, "ObjVal", &obj);
  if (error) goto QUIT;
  printf("The optimal objective is %f\n", obj);
```

(continues on next page)

(continued from previous page)

```
    goto QUIT;
  }
  if ((status != GRB_INF_OR_UNBD) && (status != GRB_INFEASIBLE))
  {
    printf("Optimization was stopped with status %i\n", status);
    goto QUIT;
  }

  /* do IIS */
  printf("The model is infeasible; computing IIS\n");
  error = GRBcomputeIIS(model);
  if (error) goto QUIT;
  printf("\nThe following constraint(s) cannot be satisfied:\n");
  error = GRBgetintattr(model, "NumConstrs", &numconstrs);
  if (error) goto QUIT;
  for (i = 0; i < numconstrs; ++i)
  {
    error = GRBgetintattrelement(model, "IISConstr", i, &iis);
    if (error) goto QUIT;
    if (iis)
    {
      error = GRBgetstrattrelement(model, "ConstrName", i, &cname);
      if (error) goto QUIT;
      printf("%s\n", cname);
    }
  }



QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */

  free(cbeg);
  free(cind);
  free(cval);
  free(sense);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */
```

(continues on next page)

(continued from previous page)

```
  GRBfreeenv(env);

  return 0;
}
```

workforce2_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, use IIS iteratively to
   find all conflicting constraints. */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include "gurobi_c.h"


#define xcol(w,s)  nShifts*w+s
#define MAXSTR     128


int
main(int   argc,
     char *argv[])
{
  GRBenv   *env   = NULL;
  GRBmodel *model = NULL;
  int       error = 0, status;
  int       s, w, col;
  int      *cbeg = NULL;
  int      *cind = NULL;
  int       idx;
  double   *cval = NULL;
  char     *sense = NULL;
  char      vname[MAXSTR];
  double    obj;
  int       i, iis, numconstrs, numremoved = 0;
  char     *cname;
  char    **removed = NULL;

  /* Sample data */
  const int nShifts = 14;
  const int nWorkers = 7;

  /* Sets of days and workers */
  char* Shifts[] =
    { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
```

(continues on next page)

(continued from previous page)

```
    "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
    "Sun14" };
char* Workers[] =
  { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

/* Number of workers required for each shift */
double shiftRequirements[] =
  { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

/* Amount each worker is paid to work one shift */
double pay[] = { 10, 12, 10, 8, 8, 9, 11 };

/* Worker availability: 0 if the worker is unavailable for a shift */
double availability[][14] =
  { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
    { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
    { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
    { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
    { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

/* Create environment */
error = GRBloadenv(&env, "workforce2.log");
if (error) goto QUIT;

/* Create initial model */
error = GRBnewmodel(env, &model, "workforce2", nWorkers * nShifts,
                    NULL, NULL, NULL, NULL, NULL);
if (error) goto QUIT;

/* Initialize assignment decision variables:
   x[w][s] == 1 if worker w is assigned
   to shift s. Since an assignment model always produces integer
   solutions, we use continuous variables and solve as an LP. */
for (w = 0; w < nWorkers; ++w)
{
  for (s = 0; s < nShifts; ++s)
  {
    col = xcol(w, s);
    sprintf(vname, "%s.%s", Workers[w], Shifts[s]);
    error = GRBsetdblattrelement(model, "UB", col, availability[w][s]);
    if (error) goto QUIT;
    error = GRBsetdblattrelement(model, "Obj", col, pay[w]);
    if (error) goto QUIT;
    error = GRBsetstrattrelement(model, "VarName", col, vname);
    if (error) goto QUIT;
  }
}

/* The objective is to minimize the total pay costs */
error = GRBsetintattr(model, "ModelSense", GRB_MINIMIZE);
```

(continues on next page)

(continued from previous page)

```
if (error) goto QUIT;

/* Make space for constraint data */
cbeg = malloc(sizeof(int) * nShifts);
if (!cbeg) goto QUIT;
cind = malloc(sizeof(int) * nShifts * nWorkers);
if (!cind) goto QUIT;
cval = malloc(sizeof(double) * nShifts * nWorkers);
if (!cval) goto QUIT;
sense = malloc(sizeof(char) * nShifts);
if (!sense) goto QUIT;

/* Constraint: assign exactly shiftRequirements[s] workers
   to each shift s */
idx = 0;
for (s = 0; s < nShifts; ++s)
{
  cbeg[s] = idx;
  sense[s] = GRB_EQUAL;
  for (w = 0; w < nWorkers; ++w)
  {
    cind[idx] = xcol(w, s);
    cval[idx++] = 1.0;
  }
}
error = GRBaddconstrs(model, nShifts, idx, cbeg, cind, cval, sense,
                      shiftRequirements, Shifts);
if (error) goto QUIT;

/* Optimize */
error = GRBoptimize(model);
if (error) goto QUIT;
error = GRBgetintattr(model, "Status", &status);
if (error) goto QUIT;
if (status == GRB_UNBOUNDED)
{
  printf("The model cannot be solved because it is unbounded\n");
  goto QUIT;
}
if (status == GRB_OPTIMAL)
{
  error = GRBgetdblattr(model, "ObjVal", &obj);
  if (error) goto QUIT;
  printf("The optimal objective is %f\n", obj);
  goto QUIT;
}
if ((status != GRB_INF_OR_UNBD) && (status != GRB_INFEASIBLE))
{
  printf("Optimization was stopped with status %i\n", status);
  goto QUIT;
}
```

(continues on next page)

(continued from previous page)

```
/* do IIS */
printf("The model is infeasible; computing IIS\n");

/* Loop until we reduce to a model that can be solved */
error = GRBgetintattr(model, "NumConstrs", &numconstrs);
if (error) goto QUIT;
removed = calloc(numconstrs, sizeof(char*));
if (!removed) goto QUIT;
while (1)
{
  error = GRBcomputeIIS(model);
  if (error) goto QUIT;
  printf("\nThe following constraint cannot be satisfied:\n");
  for (i = 0; i < numconstrs; ++i)
  {
    error = GRBgetintattrelement(model, "IISConstr", i, &iis);
    if (error) goto QUIT;
    if (iis)
    {
      error = GRBgetstrattrelement(model, "ConstrName", i, &cname);
      if (error) goto QUIT;
      printf("%s\n", cname);
      /* Remove a single constraint from the model */
      removed[numremoved] = malloc(sizeof(char) * (1+strlen(cname)));
      if (!removed[numremoved]) goto QUIT;
      strcpy(removed[numremoved++], cname);
      cind[0] = i;
      error = GRBdelconstrs(model, 1, cind);
      if (error) goto QUIT;
      break;
    }
  }

  printf("\n");
  error = GRBoptimize(model);
  if (error) goto QUIT;
  error = GRBgetintattr(model, "Status", &status);
  if (error) goto QUIT;
  if (status == GRB_UNBOUNDED)
  {
    printf("The model cannot be solved because it is unbounded\n");
    goto QUIT;
  }
  if (status == GRB_OPTIMAL)
  {
    break;
  }
  if ((status != GRB_INF_OR_UNBD) && (status != GRB_INFEASIBLE))
  {
    printf("Optimization was stopped with status %i\n", status);
    goto QUIT;
  }
```

(continues on next page)

(continued from previous page)

```
  }

  printf("\nThe following constraints were removed to get a feasible LP:\n");
  for (i = 0; i < numremoved; ++i)
  {
    printf("%s ", removed[i]);
  }
  printf("\n");



QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */

  free(cbeg);
  free(cind);
  free(cval);
  free(sense);
  for (i=0; i<numremoved; ++i)
  {
    free(removed[i]);
  }
  free(removed);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

workforce3_c.c

```c
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, relax the model
   to determine which constraints cannot be satisfied, and how much
   they need to be relaxed. */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include "gurobi_c.h"


#define xcol(w,s)  nShifts*w+s
#define MAXSTR     128


int
main(int   argc,
     char *argv[])
{
  GRBenv   *env = NULL;
  GRBmodel *model = NULL;
  int       error = 0, status;
  int       s, w, col;
  int      *cbeg = NULL;
  int      *cind = NULL;
  int       idx;
  double   *cval = NULL;
  char     *sense = NULL;
  char      vname[MAXSTR];
  double    obj;
  int       i, j, orignumvars, numvars, numconstrs;
  double   *rhspen = NULL;
  double    sol;
  char     *sname;

  /* Sample data */
  const int nShifts = 14;
  const int nWorkers = 7;

  /* Sets of days and workers */
  char* Shifts[] =
    { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
      "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
      "Sun14" };
  char* Workers[] =
    { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

  /* Number of workers required for each shift */
```

(continues on next page)

(continued from previous page)

```
double shiftRequirements[] =
  { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

/* Amount each worker is paid to work one shift */
double pay[] = { 10, 12, 10, 8, 8, 9, 11 };

/* Worker availability: 0 if the worker is unavailable for a shift */
double availability[][14] =
  { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
    { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
    { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
    { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
    { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

/* Create environment */
error = GRBloadenv(&env, "workforce3.log");
if (error) goto QUIT;

/* Create initial model */
error = GRBnewmodel(env, &model, "workforce3", nWorkers * nShifts,
                    NULL, NULL, NULL, NULL, NULL);
if (error) goto QUIT;

/* Initialize assignment decision variables:
   x[w][s] == 1 if worker w is assigned
   to shift s. Since an assignment model always produces integer
   solutions, we use continuous variables and solve as an LP. */
for (w = 0; w < nWorkers; ++w)
{
  for (s = 0; s < nShifts; ++s)
  {
    col = xcol(w, s);
    sprintf(vname, "%s.%s", Workers[w], Shifts[s]);
    error = GRBsetdblattrelement(model, "UB", col, availability[w][s]);
    if (error) goto QUIT;
    error = GRBsetdblattrelement(model, "Obj", col, pay[w]);
    if (error) goto QUIT;
    error = GRBsetstrattrelement(model, "VarName", col, vname);
    if (error) goto QUIT;
  }
}

/* The objective is to minimize the total pay costs */
error = GRBsetintattr(model, "ModelSense", GRB_MINIMIZE);
if (error) goto QUIT;

/* Make space for constraint data */
cbeg = malloc(sizeof(int) * nShifts);
if (!cbeg) goto QUIT;
cind = malloc(sizeof(int) * nShifts * nWorkers);
```

(continues on next page)

(continued from previous page)

```
if (!cind) goto QUIT;
cval = malloc(sizeof(double) * nShifts * nWorkers);
if (!cval) goto QUIT;
sense = malloc(sizeof(char) * nShifts);
if (!sense) goto QUIT;

/* Constraint: assign exactly shiftRequirements[s] workers
   to each shift s */
idx = 0;
for (s = 0; s < nShifts; ++s)
{
  cbeg[s] = idx;
  sense[s] = GRB_EQUAL;
  for (w = 0; w < nWorkers; ++w)
  {
    cind[idx] = xcol(w, s);
    cval[idx++] = 1.0;
  }
}
error = GRBaddconstrs(model, nShifts, idx, cbeg, cind, cval, sense,
                      shiftRequirements, Shifts);
if (error) goto QUIT;

/* Optimize */
error = GRBoptimize(model);
if (error) goto QUIT;
error = GRBgetintattr(model, "Status", &status);
if (error) goto QUIT;
if (status == GRB_UNBOUNDED)
{
  printf("The model cannot be solved because it is unbounded\n");
  goto QUIT;
}
if (status == GRB_OPTIMAL)
{
  error = GRBgetdblattr(model, "ObjVal", &obj);
  if (error) goto QUIT;
  printf("The optimal objective is %f\n", obj);
  goto QUIT;
}
if ((status != GRB_INF_OR_UNBD) && (status != GRB_INFEASIBLE))
{
  printf("Optimization was stopped with status %i\n", status);
  goto QUIT;
}

/* Relax the constraints to make the model feasible */
printf("The model is infeasible; relaxing the constraints\n");

/* Determine the matrix size before relaxing the constraints */
error = GRBgetintattr(model, "NumVars", &orignumvars);
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
  error = GRBgetintattr(model, "NumConstrs", &numconstrs);
  if (error) goto QUIT;

  /* Use FeasRelax feature with penalties for constraint violations */
  rhspen = malloc(sizeof(double) * numconstrs);
  if (!rhspen) goto QUIT;
  for (i = 0; i < numconstrs; i++) rhspen[i] = 1;
  error = GRBfeasrelax(model, GRB_FEASRELAX_LINEAR, 0,
                       NULL, NULL, rhspen, NULL);
  if (error) goto QUIT;
  error = GRBoptimize(model);
  if (error) goto QUIT;
  error = GRBgetintattr(model, "Status", &status);
  if (error) goto QUIT;
  if ((status == GRB_INF_OR_UNBD) || (status == GRB_INFEASIBLE) ||
      (status == GRB_UNBOUNDED))
  {
    printf("The relaxed model cannot be solved "
           "because it is infeasible or unbounded\n");
    goto QUIT;
  }
  if (status != GRB_OPTIMAL)
  {
    printf("Optimization was stopped with status %i\n", status);
    goto QUIT;
  }

  printf("\nSlack values:\n");
  error = GRBgetintattr(model, "NumVars", &numvars);
  if (error) goto QUIT;
  for (j = orignumvars; j < numvars; ++j)
  {
    error = GRBgetdblattrelement(model, "X", j, &sol);
    if (error) goto QUIT;
    if (sol > 1e-6)
    {
      error = GRBgetstrattrelement(model, "VarName", j, &sname);
      if (error) goto QUIT;
      printf("%s = %f\n", sname, sol);
    }
  }

QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }
```

(continues on next page)

(continued from previous page)

```
  /* Free data */

  free(cbeg);
  free(cind);
  free(cval);
  free(sense);
  free(rhspen);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

workforce4_c.c

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. We use Pareto optimization to solve the model:
   first, we minimize the linear sum of the slacks. Then, we constrain
   the sum of the slacks, and we minimize a quadratic objective that
   tries to balance the workload among the workers. */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include "gurobi_c.h"

int solveAndPrint(GRBmodel* model,
                  int nShifts, int nWorkers, char** Workers,
                  int* status);


#define xcol(w,s)         nShifts*w+s
#define slackcol(s)       nShifts*nWorkers+s
#define totSlackcol       nShifts*(nWorkers+1)
#define totShiftscol(w)   nShifts*(nWorkers+1)+1+w
#define avgShiftscol      (nShifts+1)*(nWorkers+1)
#define diffShiftscol(w)  (nShifts+1)*(nWorkers+1)+1+w
#define MAXSTR     128


int
```

(continues on next page)

(continued from previous page)

```
main(int   argc,
     char *argv[])
{
  GRBenv   *env = NULL;
  GRBmodel *model = NULL;
  int       error = 0, status;
  int       s, w, col;
  int      *cbeg = NULL;
  int      *cind = NULL;
  int       idx;
  double   *cval = NULL;
  char     *sense = NULL;
  char      vname[MAXSTR], cname[MAXSTR];
  double    val;

  /* Sample data */
  const int nShifts = 14;
  const int nWorkers = 7;

  /* Sets of days and workers */
  char* Shifts[] =
    { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
      "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
      "Sun14" };
  char* Workers[] =
    { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

  /* Number of workers required for each shift */
  double shiftRequirements[] =
    { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

  /* Worker availability: 0 if the worker is unavailable for a shift */
  double availability[][14] =
    { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
      { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
      { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
      { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
      { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
      { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
      { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

  /* Create environment */
  error = GRBloadenv(&env, "workforce4.log");
  if (error) goto QUIT;

  /* Create initial model */
  error = GRBnewmodel(env, &model, "workforce4",
                      (nShifts + 1) * (nWorkers + 1),
                      NULL, NULL, NULL, NULL, NULL);
  if (error) goto QUIT;

  /* Initialize assignment decision variables:
```

(continues on next page)

(continued from previous page)

```
   x[w][s] == 1 if worker w is assigned to shift s.
   This is no longer a pure assignment model, so we must
   use binary variables. */
for (w = 0; w < nWorkers; ++w)
{
  for (s = 0; s < nShifts; ++s)
  {
    col = xcol(w, s);
    sprintf(vname, "%s.%s", Workers[w], Shifts[s]);
    error = GRBsetcharattrelement(model, "VType", col, GRB_BINARY);
    if (error) goto QUIT;
    error = GRBsetdblattrelement(model, "UB", col, availability[w][s]);
    if (error) goto QUIT;
    error = GRBsetstrattrelement(model, "VarName", col, vname);
    if (error) goto QUIT;
  }
}

/* Initialize slack decision variables */
for (s = 0; s < nShifts; ++s)
{
  sprintf(vname, "%sSlack", Shifts[s]);
  error = GRBsetstrattrelement(model, "VarName", slackcol(s), vname);
  if (error) goto QUIT;
}

/* Initialize total slack decision variable */
error = GRBsetstrattrelement(model, "VarName", totSlackcol, "totSlack");
if (error) goto QUIT;

/* Initialize variables to count the total shifts worked by each worker */
for (w = 0; w < nWorkers; ++w)
{
  sprintf(vname, "%sTotShifts", Workers[w]);
  error = GRBsetstrattrelement(model, "VarName", totShiftscol(w), vname);
  if (error) goto QUIT;
}

/* The objective is to minimize the sum of the slacks */
error = GRBsetintattr(model, "ModelSense", GRB_MINIMIZE);
if (error) goto QUIT;
error = GRBsetdblattrelement(model, "Obj", totSlackcol, 1.0);
if (error) goto QUIT;

/* Make space for constraint data */
cbeg = malloc(sizeof(int) * nShifts);
if (!cbeg) goto QUIT;
cind = malloc(sizeof(int) * nShifts * (nWorkers + 1));
if (!cind) goto QUIT;
cval = malloc(sizeof(double) * nShifts * (nWorkers + 1));
if (!cval) goto QUIT;
sense = malloc(sizeof(char) * nShifts);
```

(continues on next page)

(continued from previous page)

```
if (!sense) goto QUIT;

/* Constraint: assign exactly shiftRequirements[s] workers
   to each shift s, plus the slack */
idx = 0;
for (s = 0; s < nShifts; ++s)
{
  cbeg[s] = idx;
  sense[s] = GRB_EQUAL;
  for (w = 0; w < nWorkers; ++w)
  {
    cind[idx] = xcol(w, s);
    cval[idx++] = 1.0;
  }
  cind[idx] = slackcol(s);
  cval[idx++] = 1.0;
}
error = GRBaddconstrs(model, nShifts, idx, cbeg, cind, cval, sense,
                      shiftRequirements, Shifts);
if (error) goto QUIT;

/* Constraint: set totSlack column equal to the total slack */
idx = 0;
for (s = 0; s < nShifts; ++s)
{
  cind[idx] = slackcol(s);
  cval[idx++] = 1.0;
}
cind[idx] = totSlackcol;
cval[idx++] = -1.0;
error = GRBaddconstr(model, idx, cind, cval, GRB_EQUAL,
                     0.0, "totSlack");
if (error) goto QUIT;

/* Constraint: compute the total number of shifts for each worker */
for (w = 0; w < nWorkers; ++w)
{
  idx = 0;
  for (s = 0; s < nShifts; ++s)
  {
    cind[idx] = xcol(w,s);
    cval[idx++] = 1.0;
  }
  sprintf(cname, "totShifts%s", Workers[w]);
  cind[idx] = totShiftscol(w);
  cval[idx++] = -1.0;
  error = GRBaddconstr(model, idx, cind, cval, GRB_EQUAL, 0.0, cname);
  if (error) goto QUIT;
}

/* Optimize */
error = solveAndPrint(model, nShifts, nWorkers, Workers, &status);
```

(continues on next page)

(continued from previous page)

```
if (error) goto QUIT;
if (status != GRB_OPTIMAL) goto QUIT;

/* Constrain the slack by setting its upper and lower bounds */
error = GRBgetdblattrelement(model, "X", totSlackcol, &val);
if (error) goto QUIT;
error = GRBsetdblattrelement(model, "UB", totSlackcol, val);
if (error) goto QUIT;
error = GRBsetdblattrelement(model, "LB", totSlackcol, val);
if (error) goto QUIT;

/* Variable to count the average number of shifts worked */
error = GRBaddvar(model, 0, NULL, NULL, 0, 0, GRB_INFINITY, GRB_CONTINUOUS,
                  "avgShifts");
if (error) goto QUIT;

/* Variables to count the difference from average for each worker;
   note that these variables can take negative values. */
error = GRBaddvars(model, nWorkers, 0, NULL, NULL, NULL, NULL, NULL, NULL,
                   NULL, NULL);
if (error) goto QUIT;

for (w = 0; w < nWorkers; ++w)
{
  sprintf(vname, "%sDiff", Workers[w]);
  error = GRBsetstrattrelement(model, "VarName", diffShiftscol(w), vname);
  if (error) goto QUIT;
  error = GRBsetdblattrelement(model, "LB", diffShiftscol(w), -GRB_INFINITY);
  if (error) goto QUIT;
}

/* Constraint: compute the average number of shifts worked */
idx = 0;
for (w = 0; w < nWorkers; ++w)
{
  cind[idx] = totShiftscol(w);
  cval[idx++] = 1.0;
}
cind[idx] = avgShiftscol;
cval[idx++] = -nWorkers;
error = GRBaddconstr(model, idx, cind, cval, GRB_EQUAL, 0.0, "avgShifts");
if (error) goto QUIT;

/* Constraint: compute the difference from the average number of shifts */
for (w = 0; w < nWorkers; ++w)
{
  cind[0] = totShiftscol(w);
  cval[0] = 1.0;
  cind[1] = avgShiftscol;
  cval[1] = -1.0;
  cind[2] = diffShiftscol(w);
  cval[2] = -1.0;
```

(continues on next page)

(continued from previous page)

```
    sprintf(cname, "%sDiff", Workers[w]);
    error = GRBaddconstr(model, 3, cind, cval, GRB_EQUAL, 0.0, cname);
    if (error) goto QUIT;
  }

  /* Objective: minimize the sum of the square of the difference from the
     average number of shifts worked */
  error = GRBsetdblattrelement(model, "Obj", totSlackcol, 0.0);
  if (error) goto QUIT;

  for (w = 0; w < nWorkers; ++w)
  {
    cind[w] = diffShiftscol(w);
    cval[w] = 1.0;
  }
  error = GRBaddqpterms(model, nWorkers, cind, cind, cval);
  if (error) goto QUIT;

  /* Optimize */
  error = solveAndPrint(model, nShifts, nWorkers, Workers, &status);
  if (error) goto QUIT;
  if (status != GRB_OPTIMAL) goto QUIT;


QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */

  free(cbeg);
  free(cind);
  free(cval);
  free(sense);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}
```

(continues on next page)

(continued from previous page)

```
int solveAndPrint(GRBmodel* model,
                  int nShifts, int nWorkers, char** Workers,
                  int* status)
{
  int error, w;
  double val;

  error = GRBoptimize(model);
  if (error) return error;

  error = GRBgetintattr(model, "Status", status);
  if (error) return error;

  if ((*status == GRB_INF_OR_UNBD) || (*status == GRB_INFEASIBLE) ||
      (*status == GRB_UNBOUNDED))
  {
    printf("The model cannot be solved "
           "because it is infeasible or unbounded\n");
    return 0;
  }
  if (*status != GRB_OPTIMAL)
  {
    printf("Optimization was stopped with status %i\n", *status);
    return 0;
  }

  /* Print total slack and the number of shifts worked for each worker */
  error = GRBgetdblattrelement(model, "X", totSlackcol, &val);
  if (error) return error;

  printf("\nTotal slack required: %f\n", val);
  for (w = 0; w < nWorkers; ++w)
  {
    error = GRBgetdblattrelement(model, "X", totShiftscol(w), &val);
    if (error) return error;
    printf("%s worked %f shifts\n", Workers[w], val);
  }
  printf("\n");
  return 0;
}
```

workforce5_c.c

```c
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. We use multi-objective optimization to solve the model.
   The highest-priority objective minimizes the sum of the slacks
   (i.e., the total number of uncovered shifts). The secondary objective
   minimizes the difference between the maximum and minimum number of
   shifts worked among all workers.  The second optimization is allowed
   to degrade the first objective by up to the smaller value of 10% and 2 */

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include "gurobi_c.h"

int solveAndPrint(GRBmodel* model,
                  int nShifts, int nWorkers, char** Workers,
                  int* status);


#define xcol(w,s)         nShifts*w+s
#define slackcol(s)       nShifts*nWorkers+s
#define totSlackcol       nShifts*(nWorkers+1)
#define totShiftscol(w)   nShifts*(nWorkers+1)+1+w
#define minShiftcol       (nShifts+1)*(nWorkers+1)
#define maxShiftcol       (nShifts+1)*(nWorkers+1)+1
#define MAXSTR     128


int
main(int   argc,
     char *argv[])
{
  GRBenv   *env = NULL;
  GRBmodel *model = NULL;
  int       error = 0, status;
  int       s, w, col;
  int      *cbeg = NULL;
  int      *cind = NULL;
  int       idx;
  double   *cval = NULL;
  char     *sense = NULL;
  char      vname[MAXSTR], cname[MAXSTR];

  /* Sample data */
  const int nShifts = 14;
  const int nWorkers = 8;

  /* Sets of days and workers */
  char* Shifts[] =
```

(continues on next page)

(continued from previous page)

```
  { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
    "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
    "Sun14" };
char* Workers[] =
  { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu", "Tobi" };

/* Number of workers required for each shift */
double shiftRequirements[] =
  { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

/* Worker availability: 0 if the worker is unavailable for a shift */
double availability[][14] =
  { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
    { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
    { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
    { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
    { 0, 1, 1, 1, 0, 1, 1, 0, 1, 1, 1, 0, 1, 1 },
    { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

/* Create environment */
error = GRBloadenv(&env, "workforce5.log");
if (error) goto QUIT;

/* Create initial model */
error = GRBnewmodel(env, &model, "workforce5",
                    (nShifts + 1) * (nWorkers + 1) + 2,
                    NULL, NULL, NULL, NULL, NULL);
if (error) goto QUIT;

/* Initialize assignment decision variables:
   x[w][s] == 1 if worker w is assigned to shift s.
   This is no longer a pure assignment model, so we must
   use binary variables. */
for (w = 0; w < nWorkers; ++w)
{
  for (s = 0; s < nShifts; ++s)
  {
    col = xcol(w, s);
    sprintf(vname, "%s.%s", Workers[w], Shifts[s]);
    error = GRBsetcharattrelement(model, "VType", col, GRB_BINARY);
    if (error) goto QUIT;
    error = GRBsetdblattrelement(model, "UB", col, availability[w][s]);
    if (error) goto QUIT;
    error = GRBsetstrattrelement(model, "VarName", col, vname);
    if (error) goto QUIT;
  }
}

/* Initialize slack decision variables */
for (s = 0; s < nShifts; ++s)
```

(continues on next page)

(continued from previous page)

```
{
  sprintf(vname, "%sSlack", Shifts[s]);
  error = GRBsetstrattrelement(model, "VarName", slackcol(s), vname);
  if (error) goto QUIT;
}


/* Initialize total slack decision variable */
error = GRBsetstrattrelement(model, "VarName", totSlackcol, "totSlack");
if (error) goto QUIT;

/* Initialize variables to count the total shifts worked by each worker */
for (w = 0; w < nWorkers; ++w)
{
  sprintf(vname, "%sTotShifts", Workers[w]);
  error = GRBsetstrattrelement(model, "VarName", totShiftscol(w), vname);
  if (error) goto QUIT;
}

/* Initialize max and min #shifts variables */
sprintf(vname, "minShifts");
error = GRBsetstrattrelement(model, "VarName", minShiftcol, vname);
sprintf(vname, "maxShifts");
error = GRBsetstrattrelement(model, "VarName", maxShiftcol, vname);

/* Make space for constraint data */
cbeg = malloc(sizeof(int) * nShifts);
if (!cbeg) goto QUIT;
cind = malloc(sizeof(int) * nShifts * (nWorkers + 1));
if (!cind) goto QUIT;
cval = malloc(sizeof(double) * nShifts * (nWorkers + 1));
if (!cval) goto QUIT;
sense = malloc(sizeof(char) * (nShifts + nWorkers));
if (!sense) goto QUIT;

/* Constraint: assign exactly shiftRequirements[s] workers
   to each shift s, plus the slack */
idx = 0;
for (s = 0; s < nShifts; ++s)
{
  cbeg[s] = idx;
  sense[s] = GRB_EQUAL;
  for (w = 0; w < nWorkers; ++w)
  {
    cind[idx] = xcol(w, s);
    cval[idx++] = 1.0;
  }
  cind[idx] = slackcol(s);
  cval[idx++] = 1.0;
}
error = GRBaddconstrs(model, nShifts, idx, cbeg, cind, cval, sense,
                      shiftRequirements, Shifts);
```

(continues on next page)

(continued from previous page)

```
if (error) goto QUIT;

/* Constraint: set totSlack column equal to the total slack */
idx = 0;
for (s = 0; s < nShifts; ++s)
{
  cind[idx] = slackcol(s);
  cval[idx++] = 1.0;
}
cind[idx] = totSlackcol;
cval[idx++] = -1.0;
error = GRBaddconstr(model, idx, cind, cval, GRB_EQUAL,
                     0.0, "totSlack");
if (error) goto QUIT;

/* Constraint: compute the total number of shifts for each worker */
for (w = 0; w < nWorkers; ++w)
{
  idx = 0;
  for (s = 0; s < nShifts; ++s)
  {
    cind[idx] = xcol(w,s);
    cval[idx++] = 1.0;
  }
  sprintf(cname, "totShifts%s", Workers[w]);
  cind[idx] = totShiftscol(w);
  cval[idx++] = -1.0;
  error = GRBaddconstr(model, idx, cind, cval, GRB_EQUAL, 0.0, cname);
  if (error) goto QUIT;
}

/* Constraint: set minShift/maxShift variable to less <=/>= to the
 * number of shifts among all workers */
for (w = 0; w < nWorkers; w++) {
  cind[w] = totShiftscol(w);
}
error = GRBaddgenconstrMin(model, NULL, minShiftcol, nWorkers, cind, GRB_INFINITY);
if (error) goto QUIT;
error = GRBaddgenconstrMax(model, NULL, maxShiftcol, nWorkers, cind, -GRB_INFINITY);
if (error) goto QUIT;

/* Set global sense for ALL objectives */
error = GRBsetintattr(model, GRB_INT_ATTR_MODELSENSE, GRB_MINIMIZE);
if (error) goto QUIT;

/* Set primary objective */
cind[0] = totSlackcol;
cval[0] = 1.0;
error = GRBsetobjectiven(model, 0, 2, 1.0, 2.0, 0.10, "TotalSlack",
                         0.0, 1, cind, cval);
if (error) goto QUIT;
```

(continues on next page)

(continued from previous page)

```
  /* Set secondary objective */
  cind[0] = maxShiftcol;
  cval[0] = 1.0;
  cind[1] = minShiftcol;
  cval[1] = -1.0;
  error = GRBsetobjectiven(model, 1, 1, 1.0, 0, 0, "Fairness",
                           0.0, 2, cind, cval);
  if (error) goto QUIT;

  /* Save problem */
  error = GRBwrite(model, "workforce5.lp");
  if (error) goto QUIT;
  error = GRBwrite(model, "workforce5.mps");
  if (error) goto QUIT;

  /* Optimize */
  error = solveAndPrint(model, nShifts, nWorkers, Workers, &status);
  if (error) goto QUIT;
  if (status != GRB_OPTIMAL) goto QUIT;

QUIT:

  /* Error reporting */

  if (error)
  {
    printf("ERROR: %s\n", GRBgeterrormsg(env));
    exit(1);
  }

  /* Free data */

  free(cbeg);
  free(cind);
  free(cval);
  free(sense);

  /* Free model */

  GRBfreemodel(model);

  /* Free environment */

  GRBfreeenv(env);

  return 0;
}


int solveAndPrint(GRBmodel* model,
                  int nShifts, int nWorkers, char** Workers,
                  int* status)
```

(continues on next page)

(continued from previous page)

```
{
  int error, w;
  double val;

  error = GRBoptimize(model);
  if (error) return error;

  error = GRBgetintattr(model, "Status", status);
  if (error) return error;

  if ((*status == GRB_INF_OR_UNBD) || (*status == GRB_INFEASIBLE) ||
      (*status == GRB_UNBOUNDED))
  {
    printf("The model cannot be solved "
           "because it is infeasible or unbounded\n");
    return 0;
  }
  if (*status != GRB_OPTIMAL)
  {
    printf("Optimization was stopped with status %i\n", *status);
    return 0;
  }

  /* Print total slack and the number of shifts worked for each worker */
  error = GRBgetdblattrelement(model, "X", totSlackcol, &val);
  if (error) return error;

  printf("\nTotal slack required: %f\n", val);
  for (w = 0; w < nWorkers; ++w)
  {
    error = GRBgetdblattrelement(model, "X", totShiftscol(w), &val);
    if (error) return error;
    printf("%s worked %f shifts\n", Workers[w], val);
  }
  printf("\n");
  return 0;
}
```

2.1.2 C++ Examples

This section includes source code for all of the Gurobi C++ examples. The same source code can be found in the `examples/c++` directory of the Gurobi distribution.

batchmode_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

// This example reads a MIP model from a file, solves it in batch mode,
// and prints the JSON solution string.
//
// You will need a Compute Server license for this example to work.

#include <ctime>
#if defined (WIN32) || defined (WIN64) || defined(_WIN32) || defined (_WIN64)
#include <Windows.h>
#define sleep(n) Sleep(1000*n)
#else
#include <unistd.h>
#endif
#include "gurobi_c++.h"
using namespace std;

// Set-up the environment for batch mode optimization.
//
// The function configures and start an environment to be used for batch
// optimization.
void
setupbatchenv(GRBEnv* env)
{
  env->set(GRB_StringParam_LogFile,        "batchmode.log");
  env->set(GRB_StringParam_CSManager,      "http://localhost:61080");
  env->set(GRB_StringParam_UserName,       "gurobi");
  env->set(GRB_StringParam_ServerPassword, "pass");
  env->set(GRB_IntParam_CSBatchMode, 1);

  // No network communication happened up to this point. This will happen
  // now that we call the start() method.
  env->start();
}

// Print batch job error information, if any
void
printbatcherrorinfo(GRBBatch &batch)
{
  if (batch.get(GRB_IntAttr_BatchErrorCode) == 0)
    return;

  cerr << "Batch ID " << batch.get(GRB_StringAttr_BatchID)
       << ": Error code " << batch.get(GRB_IntAttr_BatchErrorCode)
       << " (" << batch.get(GRB_StringAttr_BatchErrorMessage)
       << ")" << endl;
}

// Create a batch request for given problem file
string
newbatchrequest(char* filename)
```

(continues on next page)

(continued from previous page)

```
{
  GRBEnv*   env   = NULL;
  GRBModel* model = NULL;
  GRBVar*   v     = NULL;
  string batchID;

  try {
    // Start environment, create Model object from file
    env = new GRBEnv(true);
    setupbatchenv(env);
    model = new GRBModel(*env, filename);

    // Set some parameters; switch on detailed JSON information
    model->set(GRB_DoubleParam_MIPGap, 0.01);
    model->set(GRB_IntParam_JSONSolDetail, 1);

    // Define tags for some variables in order to access their values later
    int numvars = model->get(GRB_IntAttr_NumVars);
    v = model->getVars();
    if (numvars > 10) numvars = 10;
    for (int j = 0; j < numvars; j++) {
      char vtag[64];
      sprintf(vtag, "Variable %d", j);
      v[j].set(GRB_StringAttr_VTag, string(vtag));
    }

    // submit batch request
    batchID = model->optimizeBatch();

  } catch (...) {
    // Free local resources
    delete[] v;
    delete model;
    delete env;
    // Let the exception propagate
    throw;
  }

  // Free local resources
  delete[] v;
  delete model;
  delete env;

  return batchID;
}

// Wait for the final status of the batch.
// Initially the status of a batch is "submitted"; the status will change
// once the batch has been processed (by a compute server).
void
waitforfinalstatus(string batchID)
{
```

(continues on next page)

(continued from previous page)

```
  // Wait no longer than one hour
  time_t maxwaittime = 3600;
  GRBEnv*   env   = NULL;
  GRBBatch* batch = NULL;


  try {
    // Setup and start environment, create local Batch handle object
    env = new GRBEnv(true);
    setupbatchenv(env);
    batch = new GRBBatch(*env, batchID);
    time_t starttime = time(NULL);
    int BatchStatus = batch->get(GRB_IntAttr_BatchStatus);

    while (BatchStatus == GRB_BATCH_SUBMITTED) {

      // Abort this batch if it is taking too long
      time_t curtime = time(NULL);
      if (curtime - starttime > maxwaittime) {
        batch->abort();
        break;
      }

      // Wait for two seconds
      sleep(2);

      // Update the resident attribute cache of the Batch object with the
      // latest values from the cluster manager.
      batch->update();
      BatchStatus = batch->get(GRB_IntAttr_BatchStatus);

      // If the batch failed, we try again
      if (BatchStatus == GRB_BATCH_FAILED)
        batch->retry();
    }
  } catch (...) {
    // Print information about error status of the job that
    // processed the batch
    printbatcherrorinfo(*batch);
    // Free local resources
    delete batch;
    delete env;
    // let the exception propagate
    throw;
  }

  // Free local resources
  delete batch;
  delete env;
}

void
```

(continues on next page)

(continued from previous page)

```
printfinalreport(string batchID)
{
  GRBEnv*   env   = NULL;
  GRBBatch* batch = NULL;

  try {
    // Setup and starts environment, create local Batch handle object
    env = new GRBEnv(true);
    setupbatchenv(env);
    batch = new GRBBatch(*env, batchID);

    int BatchStatus = batch->get(GRB_IntAttr_BatchStatus);
    if (BatchStatus == GRB_BATCH_CREATED)
      cout << "Batch status is 'CREATED'" << endl;
    else if (BatchStatus == GRB_BATCH_SUBMITTED)
      cout << "Batch is 'SUBMITTED" << endl;
    else if (BatchStatus == GRB_BATCH_ABORTED)
      cout << "Batch is 'ABORTED'" << endl;
    else if (BatchStatus == GRB_BATCH_FAILED)
      cout << "Batch is 'FAILED'" << endl;
    else if (BatchStatus == GRB_BATCH_COMPLETED) {
      cout << "Batch is 'COMPLETED'" << endl;
      // Pretty printing the general solution information
      cout << "JSON solution:" << batch->getJSONSolution() << endl;

      // Write the full JSON solution string to a file
      batch->writeJSONSolution("batch-sol.json.gz");
    } else {
      // Should not happen
      cout << "Batch has unknown BatchStatus" << endl;
    }
  } catch (...) {
    // Free local resources
    delete batch;
    delete env;
    // let the exception propagate
    throw;
  }

  // Free local resources
  delete batch;
  delete env;
}

// Instruct cluster manager to remove all data relating to this BatchID
void
batchdiscard(string batchID)
{
  GRBEnv*   env   = NULL;
  GRBBatch* batch = NULL;

  try {
```

(continues on next page)

(continued from previous page)

```
    // Setup and start environment, create local Batch handle object
    env = new GRBEnv(true);
    setupbatchenv(env);
    batch = new GRBBatch(*env, batchID);

    // Remove batch request from manager
    batch->discard();
  } catch (...) {
    // Free local resources even
    delete batch;
    delete env;
    // let the exception propagate
    throw;
  }

  // Free local resources
  delete batch;
  delete env;
}

// Solve a given model using batch optimization
int
main(int   argc,
     char** argv)
{
  // Ensure we have an input file
  if (argc != 2) {
    cout << "Usage: " << argv[0] << " filename" << endl;
    return 0;
  }

  try {
    // Submit new batch request
    string batchID = newbatchrequest(argv[1]);

    // Wait for final status
    waitforfinalstatus(batchID);

    // Report final status info
    printfinalreport(batchID);

    // Remove batch request from manager
    batchdiscard(batchID);

    cout << "Batch optimization OK" << endl;
  } catch (GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch (...) {
    cout << "Exception during optimization" << endl;
  }
  return 0;
```

(continues on next page)

(continued from previous page)

```
}
```

bilinear_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple bilinear model:

     maximize    x
     subject to  x + y + z <= 10
                 x * y <= 2          (bilinear inequality)
                 x * z + y * z == 1  (bilinear equality)
                 x, y, z non-negative (x integral in second version)
*/
#include <cassert>
#include "gurobi_c++.h"
using namespace std;

int
main(int   argc,
     char *argv[])
{
  try {
    GRBEnv env = GRBEnv();

    GRBModel model = GRBModel(env);

    // Create variables

    GRBVar x = model.addVar(0.0, GRB_INFINITY, 0.0, GRB_CONTINUOUS, "x");
    GRBVar y = model.addVar(0.0, GRB_INFINITY, 0.0, GRB_CONTINUOUS, "y");
    GRBVar z = model.addVar(0.0, GRB_INFINITY, 0.0, GRB_CONTINUOUS, "z");

    // Set objective

    GRBLinExpr obj = x;
    model.setObjective(obj, GRB_MAXIMIZE);

    // Add linear constraint: x + y + z <= 10

    model.addConstr(x + y + z <= 10, "c0");

    // Add bilinear inequality constraint: x * y <= 2

    model.addQConstr(x*y <= 2, "bilinear0");

    // Add bilinear equality constraint: y * z == 1

    model.addQConstr(x*z + y*z == 1, "bilinear1");
```

(continues on next page)

(continued from previous page)

```
    // Optimize model
    model.optimize();

    cout << x.get(GRB_StringAttr_VarName) << " "
         << x.get(GRB_DoubleAttr_X) << endl;
    cout << y.get(GRB_StringAttr_VarName) << " "
         << y.get(GRB_DoubleAttr_X) << endl;
    cout << z.get(GRB_StringAttr_VarName) << " "
         << z.get(GRB_DoubleAttr_X) << endl;

    // Constrain x to be integral and solve again
    x.set(GRB_CharAttr_VType, GRB_INTEGER);
    model.optimize();

    cout << x.get(GRB_StringAttr_VarName) << " "
         << x.get(GRB_DoubleAttr_X) << endl;
    cout << y.get(GRB_StringAttr_VarName) << " "
         << y.get(GRB_DoubleAttr_X) << endl;
    cout << z.get(GRB_StringAttr_VarName) << " "
         << z.get(GRB_DoubleAttr_X) << endl;

    cout << "Obj: " << model.get(GRB_DoubleAttr_ObjVal) << endl;

  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch(...) {
    cout << "Exception during optimization" << endl;
  }

  return 0;
}
```

callback_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/*
   This example reads a model from a file, sets up a callback that
   monitors optimization progress and implements a custom
   termination strategy, and outputs progress information to the
   screen and to a log file.

   The termination strategy implemented in this callback stops the
   optimization of a MIP model once at least one of the following two
   conditions have been satisfied:
     1) The optimality gap is less than 10%
     2) At least 10000 nodes have been explored, and an integer feasible
        solution has been found.
   Note that termination is normally handled through Gurobi parameters
```

(continues on next page)

(continued from previous page)

```
   (MIPGap, NodeLimit, etc.).  You should only use a callback for
   termination if the available parameters don't capture your desired
   termination criterion.
*/

#include "gurobi_c++.h"
#include <fstream>
#include <cmath>
using namespace std;

class mycallback: public GRBCallback
{
  public:
    double lastiter;
    double lastnode;
    int numvars;
    GRBVar* vars;
    ofstream* logfile;
    mycallback(int xnumvars, GRBVar* xvars, ofstream* xlogfile) {
      lastiter = lastnode = -GRB_INFINITY;
      numvars = xnumvars;
      vars = xvars;
      logfile = xlogfile;
    }
  protected:
    void callback () {
      try {
        if (where == GRB_CB_POLLING) {
          // Ignore polling callback
        } else if (where == GRB_CB_PRESOLVE) {
          // Presolve callback
          int cdels = getIntInfo(GRB_CB_PRE_COLDEL);
          int rdels = getIntInfo(GRB_CB_PRE_ROWDEL);
          if (cdels || rdels) {
            cout << cdels << " columns and " << rdels
                 << " rows are removed" << endl;
          }
        } else if (where == GRB_CB_SIMPLEX) {
          // Simplex callback
          double itcnt = getDoubleInfo(GRB_CB_SPX_ITRCNT);
          if (itcnt - lastiter >= 100) {
            lastiter = itcnt;
            double obj = getDoubleInfo(GRB_CB_SPX_OBJVAL);
            int ispert = getIntInfo(GRB_CB_SPX_ISPERT);
            double pinf = getDoubleInfo(GRB_CB_SPX_PRIMINF);
            double dinf = getDoubleInfo(GRB_CB_SPX_DUALINF);
            char ch;
            if (ispert == 0)      ch = ' ';
            else if (ispert == 1) ch = 'S';
            else                  ch = 'P';
            cout << itcnt << " " << obj << ch << " "
                 << pinf << " " << dinf << endl;
```

(continues on next page)

(continued from previous page)

```
      }
    } else if (where == GRB_CB_MIP) {
      // General MIP callback
      double nodecnt = getDoubleInfo(GRB_CB_MIP_NODCNT);
      double objbst = getDoubleInfo(GRB_CB_MIP_OBJBST);
      double objbnd = getDoubleInfo(GRB_CB_MIP_OBJBND);
      int solcnt = getIntInfo(GRB_CB_MIP_SOLCNT);
      if (nodecnt - lastnode >= 100) {
        lastnode = nodecnt;
        int actnodes = (int) getDoubleInfo(GRB_CB_MIP_NODLFT);
        int itcnt = (int) getDoubleInfo(GRB_CB_MIP_ITRCNT);
        int cutcnt = getIntInfo(GRB_CB_MIP_CUTCNT);
        cout << nodecnt << " " << actnodes << " " << itcnt
             << " " << objbst << " " << objbnd << " "
             << solcnt << " " << cutcnt << endl;
      }
      if (fabs(objbst - objbnd) < 0.1 * (1.0 + fabs(objbst))) {
        cout << "Stop early - 10% gap achieved" << endl;
        abort();
      }
      if (nodecnt >= 10000 && solcnt) {
        cout << "Stop early - 10000 nodes explored" << endl;
        abort();
      }
    } else if (where == GRB_CB_MIPSOL) {
      // MIP solution callback
      int nodecnt = (int) getDoubleInfo(GRB_CB_MIPSOL_NODCNT);
      double obj = getDoubleInfo(GRB_CB_MIPSOL_OBJ);
      int solcnt = getIntInfo(GRB_CB_MIPSOL_SOLCNT);
      double* x = getSolution(vars, numvars);
      cout << "**** New solution at node " << nodecnt
           << ", obj " << obj << ", sol " << solcnt
           << ", x[0] = " << x[0] << " ****" << endl;
      delete[] x;
    } else if (where == GRB_CB_MIPNODE) {
      // MIP node callback
      cout << "**** New node ****" << endl;
      if (getIntInfo(GRB_CB_MIPNODE_STATUS) == GRB_OPTIMAL) {
        double* x = getNodeRel(vars, numvars);
        setSolution(vars, x, numvars);
        delete[] x;
      }
    } else if (where == GRB_CB_BARRIER) {
      // Barrier callback
      int itcnt = getIntInfo(GRB_CB_BARRIER_ITRCNT);
      double primobj = getDoubleInfo(GRB_CB_BARRIER_PRIMOBJ);
      double dualobj = getDoubleInfo(GRB_CB_BARRIER_DUALOBJ);
      double priminf = getDoubleInfo(GRB_CB_BARRIER_PRIMINF);
      double dualinf = getDoubleInfo(GRB_CB_BARRIER_DUALINF);
      double cmpl = getDoubleInfo(GRB_CB_BARRIER_COMPL);
      cout << itcnt << " " << primobj << " " << dualobj << " "
           << priminf << " " << dualinf << " " << cmpl << endl;
```

(continues on next page)

(continued from previous page)

```
        } else if (where == GRB_CB_MESSAGE) {
          // Message callback
          string msg = getStringInfo(GRB_CB_MSG_STRING);
          *logfile << msg;
        }
      } catch (GRBException e) {
        cout << "Error number: " << e.getErrorCode() << endl;
        cout << e.getMessage() << endl;
      } catch (...) {
        cout << "Error during callback" << endl;
      }
    }
};

int
main(int   argc,
     char *argv[])
{
  if (argc < 2) {
    cout << "Usage: callback_c++ filename" << endl;
    return 1;
  }

  // Open log file
  ofstream logfile("cb.log");
  if (!logfile.is_open()) {
    cout << "Cannot open cb.log for callback message" << endl;
    return 1;
  }

  GRBEnv *env = 0;
  GRBVar *vars = 0;

  try {
    // Create environment
    env = new GRBEnv();

    // Read model from file
    GRBModel model = GRBModel(*env, argv[1]);

    // Turn off display and heuristics
    model.set(GRB_IntParam_OutputFlag, 0);
    model.set(GRB_DoubleParam_Heuristics, 0.0);

    // Create a callback object and associate it with the model
    int numvars = model.get(GRB_IntAttr_NumVars);
    vars = model.getVars();
    mycallback cb = mycallback(numvars, vars, &logfile);

    model.setCallback(&cb);

    // Solve model and capture solution information
```

(continues on next page)

(continued from previous page)

```
    model.optimize();

    cout << endl << "Optimization complete" << endl;
    if (model.get(GRB_IntAttr_SolCount) == 0) {
      cout << "No solution found, optimization status = "
           << model.get(GRB_IntAttr_Status) << endl;
    } else {
      cout << "Solution found, objective = "
           << model.get(GRB_DoubleAttr_ObjVal) << endl;
      for (int j = 0; j < numvars; j++) {
        GRBVar v = vars[j];
        double x = v.get(GRB_DoubleAttr_X);
        if (x != 0.0) {
          cout << v.get(GRB_StringAttr_VarName) << " " << x << endl;
        }
      }
    }

  } catch (GRBException e) {
    cout << "Error number: " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch (...) {
    cout << "Error during optimization" << endl;
  }

  // Close log file
  logfile.close();

  delete[] vars;
  delete env;

  return 0;
}
```

dense_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QP model:

     minimize    x + y + x^2 + x*y + y^2 + y*z + z^2
     subject to  x + 2 y + 3 z >= 4
                 x +   y       >= 1
                 x, y, z non-negative

   The example illustrates the use of dense matrices to store A and Q
   (and dense vectors for the other relevant data).  We don't recommend
   that you use dense matrices, but this example may be helpful if you
   already have your data in this format.
*/
```

(continues on next page)

(continued from previous page)

```
#include "gurobi_c++.h"
using namespace std;

static bool
dense_optimize(GRBEnv* env,
               int     rows,
               int     cols,
               double* c,     /* linear portion of objective function */
               double* Q,     /* quadratic portion of objective function */
               double* A,     /* constraint matrix */
               char*   sense, /* constraint senses */
               double* rhs,   /* RHS vector */
               double* lb,    /* variable lower bounds */
               double* ub,    /* variable upper bounds */
               char*   vtype, /* variable types (continuous, binary, etc.) */
               double* solution,
               double* objvalP)
{
  GRBModel model = GRBModel(*env);
  int i, j;
  bool success = false;

  /* Add variables to the model */

  GRBVar* vars = model.addVars(lb, ub, NULL, vtype, NULL, cols);

  /* Populate A matrix */

  for (i = 0; i < rows; i++) {
    GRBLinExpr lhs = 0;
    for (j = 0; j < cols; j++)
      if (A[i*cols+j] != 0)
        lhs += A[i*cols+j]*vars[j];
    model.addConstr(lhs, sense[i], rhs[i]);
  }

  GRBQuadExpr obj = 0;

  for (j = 0; j < cols; j++)
    obj += c[j]*vars[j];
  for (i = 0; i < cols; i++)
    for (j = 0; j < cols; j++)
      if (Q[i*cols+j] != 0)
        obj += Q[i*cols+j]*vars[i]*vars[j];

  model.setObjective(obj);

  model.optimize();

  model.write("dense.lp");
```

(continues on next page)

(continued from previous page)

```
  if (model.get(GRB_IntAttr_Status) == GRB_OPTIMAL) {
    *objvalP = model.get(GRB_DoubleAttr_ObjVal);
    for (i = 0; i < cols; i++)
      solution[i] = vars[i].get(GRB_DoubleAttr_X);
    success = true;
  }

  delete[] vars;

  return success;
}

int
main(int   argc,
     char *argv[])
{
  GRBEnv* env = 0;
  try {
    env = new GRBEnv();
    double c[] = {1, 1, 0};
    double  Q[3][3] = {{1, 1, 0}, {0, 1, 1}, {0, 0, 1}};
    double  A[2][3] = {{1, 2, 3}, {1, 1, 0}};
    char    sense[] = {'>', '>'};
    double  rhs[]   = {4, 1};
    double  lb[]    = {0, 0, 0};
    bool    success;
    double  objval, sol[3];

    success = dense_optimize(env, 2, 3, c, &Q[0][0], &A[0][0], sense, rhs,
                             lb, NULL, NULL, sol, &objval);

    cout << "optimal=" << success << " x: " << sol[0] << " y: " << sol[1] << " z: " <<␣
↪sol[2] << endl;

  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch(...) {
    cout << "Exception during optimization" << endl;
  }

  delete env;
  return 0;
}
```

diet_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Solve the classic diet model, showing how to add constraints
   to an existing model. */

#include "gurobi_c++.h"
using namespace std;

void printSolution(GRBModel& model, int nCategories, int nFoods,
                   GRBVar* buy, GRBVar* nutrition);

int
main(int argc,
     char *argv[])
{
  GRBEnv* env = 0;
  GRBVar* nutrition = 0;
  GRBVar* buy = 0;
  try
  {

    // Nutrition guidelines, based on
    // USDA Dietary Guidelines for Americans, 2005
    // http://www.health.gov/DietaryGuidelines/dga2005/
    const int nCategories = 4;
    string Categories[] =
      { "calories", "protein", "fat", "sodium" };
    double minNutrition[] = { 1800, 91, 0, 0 };
    double maxNutrition[] = { 2200, GRB_INFINITY, 65, 1779 };

    // Set of foods
    const int nFoods = 9;
    string Foods[] =
      { "hamburger", "chicken", "hot dog", "fries",
        "macaroni", "pizza", "salad", "milk", "ice cream" };
    double cost[] =
      { 2.49, 2.89, 1.50, 1.89, 2.09, 1.99, 2.49, 0.89, 1.59 };

    // Nutrition values for the foods
    double nutritionValues[][nCategories] = {
                      { 410, 24, 26, 730 },    // hamburger
                      { 420, 32, 10, 1190 },   // chicken
                      { 560, 20, 32, 1800 },   // hot dog
                      { 380, 4, 19, 270 },     // fries
                      { 320, 12, 10, 930 },    // macaroni
                      { 320, 15, 12, 820 },    // pizza
                      { 320, 31, 12, 1230 },   // salad
                      { 100, 8, 2.5, 125 },    // milk
                      { 330, 8, 10, 180 }      // ice cream
                    };
```

(continues on next page)

(continued from previous page)

```
    // Model
    env = new GRBEnv();
    GRBModel model = GRBModel(*env);
    model.set(GRB_StringAttr_ModelName, "diet");

    // Create decision variables for the nutrition information,
    // which we limit via bounds
    nutrition = model.addVars(minNutrition, maxNutrition, 0, 0,
                              Categories, nCategories);

    // Create decision variables for the foods to buy
    //
    // Note: For each decision variable we add the objective coefficient
    //       with the creation of the variable.
    buy = model.addVars(0, 0, cost, 0, Foods, nFoods);

    // The objective is to minimize the costs
    //
    // Note: The objective coefficients are set during the creation of
    //       the decision variables above.
    model.set(GRB_IntAttr_ModelSense, GRB_MINIMIZE);

    // Nutrition constraints
    for (int i = 0; i < nCategories; ++i)
    {
      GRBLinExpr ntot = 0;
      for (int j = 0; j < nFoods; ++j)
      {
        ntot += nutritionValues[j][i] * buy[j];
      }
      model.addConstr(ntot == nutrition[i], Categories[i]);
    }

    // Solve
    model.optimize();
    printSolution(model, nCategories, nFoods, buy, nutrition);

    cout << "\nAdding constraint: at most 6 servings of dairy" << endl;
    model.addConstr(buy[7] + buy[8] <= 6.0, "limit_dairy");

    // Solve
    model.optimize();
    printSolution(model, nCategories, nFoods, buy, nutrition);

  }
  catch (GRBException e)
  {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...)
  {
```

(continues on next page)

(continued from previous page)

```
    cout << "Exception during optimization" << endl;
  }

  delete[] nutrition;
  delete[] buy;
  delete env;
  return 0;
}

void printSolution(GRBModel& model, int nCategories, int nFoods,
                   GRBVar* buy, GRBVar* nutrition)
{
  if (model.get(GRB_IntAttr_Status) == GRB_OPTIMAL)
  {
    cout << "\nCost: " << model.get(GRB_DoubleAttr_ObjVal) << endl;
    cout << "\nBuy:" << endl;
    for (int j = 0; j < nFoods; ++j)
    {
      if (buy[j].get(GRB_DoubleAttr_X) > 0.0001)
      {
        cout << buy[j].get(GRB_StringAttr_VarName) << " " <<
        buy[j].get(GRB_DoubleAttr_X) << endl;
      }
    }
    cout << "\nNutrition:" << endl;
    for (int i = 0; i < nCategories; ++i)
    {
      cout << nutrition[i].get(GRB_StringAttr_VarName) << " " <<
      nutrition[i].get(GRB_DoubleAttr_X) << endl;
    }
  }
  else
  {
    cout << "No solution" << endl;
  }
}
```

facility_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Facility location: a company currently ships its product from 5 plants
   to 4 warehouses. It is considering closing some plants to reduce
   costs. What plant(s) should the company close, in order to minimize
   transportation and fixed costs?

   Based on an example from Frontline Systems:
   http://www.solver.com/disfacility.htm
   Used with permission.
 */
```

(continues on next page)

(continued from previous page)

```
#include "gurobi_c++.h"
#include <sstream>
using namespace std;

int
main(int argc,
     char *argv[])
{
  GRBEnv* env = 0;
  GRBVar* open = 0;
  GRBVar** transport = 0;
  int transportCt = 0;
  try
  {

    // Number of plants and warehouses
    const int nPlants = 5;
    const int nWarehouses = 4;

    // Warehouse demand in thousands of units
    double Demand[] = { 15, 18, 14, 20 };

    // Plant capacity in thousands of units
    double Capacity[] = { 20, 22, 17, 19, 18 };

    // Fixed costs for each plant
    double FixedCosts[] =
      { 12000, 15000, 17000, 13000, 16000 };

    // Transportation costs per thousand units
    double TransCosts[][nPlants] = {
                                      { 4000, 2000, 3000, 2500, 4500 },
                                      { 2500, 2600, 3400, 3000, 4000 },
                                      { 1200, 1800, 2600, 4100, 3000 },
                                      { 2200, 2600, 3100, 3700, 3200 }
                                    };

    // Model
    env = new GRBEnv();
    GRBModel model = GRBModel(*env);
    model.set(GRB_StringAttr_ModelName, "facility");

    // Plant open decision variables: open[p] == 1 if plant p is open.
    open = model.addVars(nPlants, GRB_BINARY);

    int p;
    for (p = 0; p < nPlants; ++p)
    {
      ostringstream vname;
      vname << "Open" << p;
      open[p].set(GRB_DoubleAttr_Obj, FixedCosts[p]);
```

(continues on next page)

(continued from previous page)

```
    open[p].set(GRB_StringAttr_VarName, vname.str());
  }

  // Transportation decision variables: how much to transport from
  // a plant p to a warehouse w
  transport = new GRBVar* [nWarehouses];
  int w;
  for (w = 0; w < nWarehouses; ++w)
  {
    transport[w] = model.addVars(nPlants);
    transportCt++;

    for (p = 0; p < nPlants; ++p)
    {
      ostringstream vname;
      vname << "Trans" << p << "." << w;
      transport[w][p].set(GRB_DoubleAttr_Obj, TransCosts[w][p]);
      transport[w][p].set(GRB_StringAttr_VarName, vname.str());
    }
  }

  // The objective is to minimize the total fixed and variable costs
  model.set(GRB_IntAttr_ModelSense, GRB_MINIMIZE);

  // Production constraints
  // Note that the right-hand limit sets the production to zero if
  // the plant is closed
  for (p = 0; p < nPlants; ++p)
  {
    GRBLinExpr ptot = 0;
    for (w = 0; w < nWarehouses; ++w)
    {
      ptot += transport[w][p];
    }
    ostringstream cname;
    cname << "Capacity" << p;
    model.addConstr(ptot <= Capacity[p] * open[p], cname.str());
  }

  // Demand constraints
  for (w = 0; w < nWarehouses; ++w)
  {
    GRBLinExpr dtot = 0;
    for (p = 0; p < nPlants; ++p)
    {
      dtot += transport[w][p];
    }
    ostringstream cname;
    cname << "Demand" << w;
    model.addConstr(dtot == Demand[w], cname.str());
  }
```

(continues on next page)

(continued from previous page)

```
  // Guess at the starting point: close the plant with the highest
  // fixed costs; open all others

  // First, open all plants
  for (p = 0; p < nPlants; ++p)
  {
    open[p].set(GRB_DoubleAttr_Start, 1.0);
  }

  // Now close the plant with the highest fixed cost
  cout << "Initial guess:" << endl;
  double maxFixed = -GRB_INFINITY;
  for (p = 0; p < nPlants; ++p)
  {
    if (FixedCosts[p] > maxFixed)
    {
      maxFixed = FixedCosts[p];
    }
  }
  for (p = 0; p < nPlants; ++p)
  {
    if (FixedCosts[p] == maxFixed)
    {
      open[p].set(GRB_DoubleAttr_Start, 0.0);
      cout << "Closing plant " << p << endl << endl;
      break;
    }
  }

  // Use barrier to solve root relaxation
  model.set(GRB_IntParam_Method, GRB_METHOD_BARRIER);

  // Solve
  model.optimize();

  // Print solution
  cout << "\nTOTAL COSTS: " << model.get(GRB_DoubleAttr_ObjVal) << endl;
  cout << "SOLUTION:" << endl;
  for (p = 0; p < nPlants; ++p)
  {
    if (open[p].get(GRB_DoubleAttr_X) > 0.99)
    {
      cout << "Plant " << p << " open:" << endl;
      for (w = 0; w < nWarehouses; ++w)
      {
        if (transport[w][p].get(GRB_DoubleAttr_X) > 0.0001)
        {
          cout << "  Transport " <<
          transport[w][p].get(GRB_DoubleAttr_X) <<
          " units to warehouse " << w << endl;
        }
      }
```

(continues on next page)

(continued from previous page)

```
      }
      else
      {
        cout << "Plant " << p << " closed!" << endl;
      }
    }

  }
  catch (GRBException e)
  {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...)
  {
    cout << "Exception during optimization" << endl;
  }

  delete[] open;
  for (int i = 0; i < transportCt; ++i) {
    delete[] transport[i];
  }
  delete[] transport;
  delete env;
  return 0;
}
```

feasopt_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, adds artificial
   variables to each constraint, and then minimizes the sum of the
   artificial variables.  A solution with objective zero corresponds
   to a feasible solution to the input model.
   We can also use FeasRelax feature to do it. In this example, we
   use minrelax=1, i.e. optimizing the returned model finds a solution
   that minimizes the original objective, but only from among those
   solutions that minimize the sum of the artificial variables. */

#include "gurobi_c++.h"
using namespace std;

int
main(int argc,
     char *argv[])
{
  if (argc < 2)
  {
    cout << "Usage: feasopt_c++ filename" << endl;
```

(continues on next page)

(continued from previous page)

```
  return 1;
}

GRBEnv* env = 0;
GRBConstr* c = 0;
try
{
  env = new GRBEnv();
  GRBModel feasmodel = GRBModel(*env, argv[1]);

  // Create a copy to use FeasRelax feature later */
  GRBModel feasmodel1 = GRBModel(feasmodel);

  // clear objective
  feasmodel.setObjective(GRBLinExpr(0.0));

  // add slack variables
  c = feasmodel.getConstrs();
  for (int i = 0; i < feasmodel.get(GRB_IntAttr_NumConstrs); ++i)
  {
    char sense = c[i].get(GRB_CharAttr_Sense);
    if (sense != '>')
    {
      double coef = -1.0;
      feasmodel.addVar(0.0, GRB_INFINITY, 1.0, GRB_CONTINUOUS, 1,
                       &c[i], &coef, "ArtN_" +
                       c[i].get(GRB_StringAttr_ConstrName));
    }
    if (sense != '<')
    {
      double coef = 1.0;
      feasmodel.addVar(0.0, GRB_INFINITY, 1.0, GRB_CONTINUOUS, 1,
                       &c[i], &coef, "ArtP_" +
                       c[i].get(GRB_StringAttr_ConstrName));
    }
  }

  // optimize modified model
  feasmodel.optimize();
  feasmodel.write("feasopt.lp");

  // use FeasRelax feature */
  feasmodel1.feasRelax(GRB_FEASRELAX_LINEAR, true, false, true);
  feasmodel1.write("feasopt1.lp");
  feasmodel1.optimize();
}
catch (GRBException e)
{
  cout << "Error code = " << e.getErrorCode() << endl;
  cout << e.getMessage() << endl;
}
catch (...)
```

(continues on next page)

(continued from previous page)

```
  {
    cout << "Error during optimization" << endl;
  }

  delete[] c;
  delete env;
  return 0;
}
```

fixanddive_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Implement a simple MIP heuristic.  Relax the model,
   sort variables based on fractionality, and fix the 25% of
   the fractional variables that are closest to integer variables.
   Repeat until either the relaxation is integer feasible or
   linearly infeasible. */

#include "gurobi_c++.h"
#include <algorithm>
#include <cmath>
#include <deque>
using namespace std;

bool vcomp(GRBVar*, GRBVar*);

int
main(int argc,
     char *argv[])
{
  if (argc < 2)
  {
    cout << "Usage: fixanddive_c++ filename" << endl;
    return 1;
  }

  GRBEnv* env = 0;
  GRBVar* x = 0;
  try
  {
    // Read model
    env = new GRBEnv();
    GRBModel model = GRBModel(*env, argv[1]);

    // Collect integer variables and relax them
    // Note that we use GRBVar* to copy variables
    deque<GRBVar*> intvars;
    x = model.getVars();
    for (int j = 0; j < model.get(GRB_IntAttr_NumVars); ++j)
```

(continues on next page)

(continued from previous page)

```
  {
    if (x[j].get(GRB_CharAttr_VType) != GRB_CONTINUOUS)
    {
      intvars.push_back(&x[j]);
      x[j].set(GRB_CharAttr_VType, GRB_CONTINUOUS);
    }
  }

  model.set(GRB_IntParam_OutputFlag, 0);
  model.optimize();

  // Perform multiple iterations. In each iteration, identify the first
  // quartile of integer variables that are closest to an integer value
  // in the relaxation, fix them to the nearest integer, and repeat.

  for (int iter = 0; iter < 1000; ++iter)
  {

    // create a list of fractional variables, sorted in order of
    // increasing distance from the relaxation solution to the nearest
    // integer value

    deque<GRBVar*> fractional;
    for (size_t j = 0; j < intvars.size(); ++j)
    {
      double sol = fabs(intvars[j]->get(GRB_DoubleAttr_X));
      if (fabs(sol - floor(sol + 0.5)) > 1e-5)
      {
        fractional.push_back(intvars[j]);
      }
    }

    cout << "Iteration " << iter << ", obj " <<
    model.get(GRB_DoubleAttr_ObjVal) << ", fractional " <<
    fractional.size() << endl;

    if (fractional.size() == 0)
    {
      cout << "Found feasible solution - objective " <<
      model.get(GRB_DoubleAttr_ObjVal) << endl;
      break;
    }

    // Fix the first quartile to the nearest integer value
    sort(fractional.begin(), fractional.end(), vcomp);
    int nfix = (int) fractional.size() / 4;
    nfix = (nfix > 1) ? nfix : 1;
    for (int i = 0; i < nfix; ++i)
    {
      GRBVar* v = fractional[i];
      double fixval = floor(v->get(GRB_DoubleAttr_X) + 0.5);
      v->set(GRB_DoubleAttr_LB, fixval);
```

(continues on next page)

(continued from previous page)

```
        v->set(GRB_DoubleAttr_UB, fixval);
        cout << "  Fix " << v->get(GRB_StringAttr_VarName) << " to " <<
        fixval << " ( rel " << v->get(GRB_DoubleAttr_X) << " )" <<
        endl;
      }

      model.optimize();

      // Check optimization result

      if (model.get(GRB_IntAttr_Status) != GRB_OPTIMAL)
      {
        cout << "Relaxation is infeasible" << endl;
        break;
      }
    }

  }
  catch (GRBException e)
  {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...)
  {
    cout << "Error during optimization" << endl;
  }

  delete[] x;
  delete env;
  return 0;
}


bool vcomp(GRBVar* v1,
           GRBVar* v2)
{
  double sol1 = fabs(v1->get(GRB_DoubleAttr_X));
  double sol2 = fabs(v2->get(GRB_DoubleAttr_X));
  double frac1 = fabs(sol1 - floor(sol1 + 0.5));
  double frac2 = fabs(sol2 - floor(sol2 + 0.5));
  return (frac1 < frac2);
}
```

gc_pwl_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC

 This example formulates and solves the following simple model
 with PWL constraints:

  maximize
        sum c[j] * x[j]
  subject to
        sum A[i,j] * x[j] <= 0,  for i = 0, ..., m-1
        sum y[j] <= 3
        y[j] = pwl(x[j]),        for j = 0, ..., n-1
        x[j] free, y[j] >= 0,    for j = 0, ..., n-1
  where pwl(x) = 0,     if x  = 0
               = 1+|x|, if x != 0

  Note
   1. sum pwl(x[j]) <= b is to bound x vector and also to favor sparse x vector.
      Here b = 3 means that at most two x[j] can be nonzero and if two, then
      sum x[j] <= 1
   2. pwl(x) jumps from 1 to 0 and from 0 to 1, if x moves from negative 0 to 0,
      then to positive 0, so we need three points at x = 0. x has infinite bounds
      on both sides, the piece defined with two points (-1, 2) and (0, 1) can
      extend x to -infinite. Overall we can use five points (-1, 2), (0, 1),
      (0, 0), (0, 1) and (1, 2) to define y = pwl(x)
*/

#include "gurobi_c++.h"
#include <sstream>
using namespace std;

int
main(int argc,
     char *argv[])
{
  int n = 5;
  int m = 5;
  double c[] = { 0.5, 0.8, 0.5, 0.1, -1 };
  double A[][5] = { {0, 0, 0, 1, -1},
                    {0, 0, 1, 1, -1},
                    {1, 1, 0, 0, -1},
                    {1, 0, 1, 0, -1},
                    {1, 0, 0, 1, -1} };
  int npts = 5;
  double xpts[] = {-1, 0, 0, 0, 1};
  double ypts[] = {2, 1, 0, 1, 2};

  GRBEnv* env = 0;
  GRBVar* x = 0;
  GRBVar* y = 0;

  try {
```

(continues on next page)

(continued from previous page)

```
    // Env and model
    env = new GRBEnv();
    GRBModel model = GRBModel(*env);
    model.set(GRB_StringAttr_ModelName, "gc_pwl_c++");

    // Add variables, set bounds and obj coefficients
    x = model.addVars(n);
    for (int i = 0; i < n; i++) {
      x[i].set(GRB_DoubleAttr_LB, -GRB_INFINITY);
      x[i].set(GRB_DoubleAttr_Obj, c[i]);
    }

    y = model.addVars(n);

    // Set objective to maximize
    model.set(GRB_IntAttr_ModelSense, GRB_MAXIMIZE);

    // Add linear constraints
    for (int i = 0; i < m; i++) {
      GRBLinExpr le = 0;
      for (int j = 0; j < n; j++) {
        le += A[i][j] * x[j];
      }
      model.addConstr(le <= 0);
    }

    GRBLinExpr le1 = 0;
    for (int j = 0; j < n; j++) {
      le1 += y[j];
    }
    model.addConstr(le1 <= 3);

    // Add piecewise constraints
    for (int j = 0; j < n; j++) {
      model.addGenConstrPWL(x[j], y[j], npts, xpts, ypts);
    }

    // Optimize model
    model.optimize();

    for (int j = 0; j < n; j++) {
      cout << "x[" << j << "] = " << x[j].get(GRB_DoubleAttr_X) << endl;
    }

    cout << "Obj: " << model.get(GRB_DoubleAttr_ObjVal) << endl;

  }
  catch (GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...) {
```

(continues on next page)

(continued from previous page)

```
    cout << "Exception during optimization" << endl;
  }

  delete[] x;
  delete[] y;
  delete env;
  return 0;
}
```

genconstr_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* In this example we show the use of general constraints for modeling
 * some common expressions. We use as an example a SAT-problem where we
 * want to see if it is possible to satisfy at least four (or all) clauses
 * of the logical form
 *
 * L = (x0 or ~x1 or x2)  and (x1 or ~x2 or x3)  and
 *     (x2 or ~x3 or x0)  and (x3 or ~x0 or x1)  and
 *     (~x0 or ~x1 or x2) and (~x1 or ~x2 or x3) and
 *     (~x2 or ~x3 or x0) and (~x3 or ~x0 or x1)
 *
 * We do this by introducing two variables for each literal (itself and its
 * negated value), one variable for each clause, one variable indicating
 * whether we can satisfy at least four clauses, and one last variable to
 * identify the minimum of the clauses (so if it is one, we can satisfy all
 * clauses). Then we put these last two variables in the objective.
 * The objective function is therefore
 *
 * maximize Obj0 + Obj1
 *
 *  Obj0 = MIN(Clause1, ... , Clause8)
 *  Obj1 = 1 -> Clause1 + ... + Clause8 >= 4
 *
 * thus, the objective value will be two if and only if we can satisfy all
 * clauses; one if and only if at least four but not all clauses can be satisfied,
 * and zero otherwise.
 */


#include "gurobi_c++.h"
#include <sstream>
#include <iomanip>
using namespace std;

#define n         4
#define NLITERALS 4  // same as n
#define NCLAUSES  8
#define NOBJ      2
```

(continues on next page)

(continued from previous page)

```
int
main(void)
{
  GRBEnv *env = 0;

  try{
    // Example data
    //   e.g. {0, n+1, 2} means clause (x0 or ~x1 or x2)
    const int Clauses[][3] = {{  0, n+1, 2}, {  1, n+2, 3},
                              {  2, n+3, 0}, {  3, n+0, 1},
                              {n+0, n+1, 2}, {n+1, n+2, 3},
                              {n+2, n+3, 0}, {n+3, n+0, 1}};

    int i, status;

    // Create environment
    env = new GRBEnv("genconstr_c++.log");

    // Create initial model
    GRBModel model = GRBModel(*env);
    model.set(GRB_StringAttr_ModelName, "genconstr_c++");

    // Initialize decision variables and objective

    GRBVar Lit[NLITERALS];
    GRBVar NotLit[NLITERALS];
    for (i = 0; i < NLITERALS; i++) {
      ostringstream vname;
      vname << "X" << i;
      Lit[i]    = model.addVar(0.0, 1.0, 0.0, GRB_BINARY, vname.str());

      vname.str("");
      vname << "notX" << i;
      NotLit[i] = model.addVar(0.0, 1.0, 0.0, GRB_BINARY, vname.str());
    }

    GRBVar Cla[NCLAUSES];
    for (i = 0; i < NCLAUSES; i++) {
      ostringstream vname;
      vname << "Clause" << i;
      Cla[i] = model.addVar(0.0, 1.0, 0.0, GRB_BINARY, vname.str());
    }

    GRBVar Obj[NOBJ];
    for (i = 0; i < NOBJ; i++) {
      ostringstream vname;
      vname << "Obj" << i;
      Obj[i] = model.addVar(0.0, 1.0, 1.0, GRB_BINARY, vname.str());
    }

    // Link Xi and notXi
```

(continues on next page)

(continued from previous page)

```
  GRBLinExpr lhs;
  for (i = 0; i < NLITERALS; i++) {
    ostringstream cname;
    cname << "CNSTR_X" << i;
    lhs = 0;
    lhs += Lit[i];
    lhs += NotLit[i];
    model.addConstr(lhs == 1.0, cname.str());
  }

  // Link clauses and literals
  GRBVar clause[3];
  for (i = 0; i < NCLAUSES; i++) {
    for (int j = 0; j < 3; j++) {
      if (Clauses[i][j] >= n) clause[j] = NotLit[Clauses[i][j]-n];
      else                    clause[j] = Lit[Clauses[i][j]];
    }
    ostringstream cname;
    cname << "CNSTR_Clause" << i;
    model.addGenConstrOr(Cla[i], clause, 3, cname.str());
  }

  // Link objs with clauses
  model.addGenConstrMin(Obj[0], Cla, NCLAUSES,
                        GRB_INFINITY, "CNSTR_Obj0");
  lhs = 0;
  for (i = 0; i < NCLAUSES; i++) {
    lhs += Cla[i];
  }
  model.addGenConstrIndicator(Obj[1], 1, lhs >= 4.0, "CNSTR_Obj1");

  // Set global objective sense
  model.set(GRB_IntAttr_ModelSense, GRB_MAXIMIZE);

  // Save problem
  model.write("genconstr_c++.mps");
  model.write("genconstr_c++.lp");

  // Optimize
  model.optimize();

  // Status checking
  status = model.get(GRB_IntAttr_Status);

  if (status == GRB_INF_OR_UNBD ||
      status == GRB_INFEASIBLE  ||
      status == GRB_UNBOUNDED     ) {
    cout << "The model cannot be solved " <<
            "because it is infeasible or unbounded" << endl;
    return 1;
  }
  if (status != GRB_OPTIMAL) {
```

(continues on next page)

(continued from previous page)

```
      cout << "Optimization was stopped with status " << status << endl;
      return 1;
    }

    // Print result
    double objval = model.get(GRB_DoubleAttr_ObjVal);

    if (objval > 1.9)
      cout << "Logical expression is satisfiable" << endl;
    else if (objval > 0.9)
      cout << "At least four clauses can be satisfied" << endl;
    else
      cout << "Not even three clauses can be satisfied" << endl;

  } catch (GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...) {
    cout << "Exception during optimization" << endl;
  }

  // Free environment
  delete env;

  return 0;
}
```

nlconstr_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple nonlinear model
   using the nonlinear constraint API:

     minimize    x - y
     subject to  sin(x) * x + x^2 * y  <= 1
                 y = cos(x) (<=> cos(x) - y = 0)
                -1 <= x <= 2
                 0 <= y <= 2

   The nonlinear constraint is set via addNLConstr() using an expression tree.
   Then we retrieve the tree with getNLConstrLHS() and verify it, delete it
   with remove(), replace it with a simple linear constraint, and re-optimize.
*/

#include "gurobi_c++.h"
#include <cmath>
using namespace std;
```

(continues on next page)

(continued from previous page)

```
int
main(int   argc,
     char *argv[])
{
  try {

    /* Create environment and model */
    GRBEnv env = GRBEnv("nlconstr.log");
    GRBModel model = GRBModel(env);

    /* Create variables: x in [-1, 2], y in [0, 2] */
    GRBVar x = model.addVar(-1.0, 2.0, 1.0, GRB_CONTINUOUS, "x");
    GRBVar y = model.addVar(0.0, 2.0, -1.0, GRB_CONTINUOUS, "y");

    /* Expression tree for sin(x) * x + x^2 * y (10 nodes)
     *
     *   node 0: PLUS       (root)
     *   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
     *   node 2: SIN        (child of 1)
     *   node 3: VARIABLE x (child of 2)
     *   node 4: VARIABLE x (child of 1)
     *   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
     *   node 6: POW        (child of 5)
     *   node 7: VARIABLE x (child of 6)
     *   node 8: CONSTANT 2 (child of 6)
     *   node 9: VARIABLE y (child of 5)
     */
    int    nnodes_in1 = 10;
    int    opcode1[10] = {GRB_OPCODE_PLUS,
                          GRB_OPCODE_MULTIPLY,
                          GRB_OPCODE_SIN,
                          GRB_OPCODE_VARIABLE,
                          GRB_OPCODE_VARIABLE,
                          GRB_OPCODE_MULTIPLY,
                          GRB_OPCODE_POW,
                          GRB_OPCODE_VARIABLE,
                          GRB_OPCODE_CONSTANT,
                          GRB_OPCODE_VARIABLE};
    double data1[10]   = {-1.0, -1.0, -1.0,
                          (double) x.index(),
                          (double) x.index(),
                          -1.0, -1.0,
                          (double) x.index(),
                          2.0,
                          (double) y.index()};
    int    parent1[10] = {-1, 0, 1, 2, 1, 0, 5, 6, 6, 5};

    /* Expression tree for cos(x) - y = 0 (4 nodes)
     *
     *   node 0: MINUS      (root)
     *   node 1: COS        (child of 0)
     *   node 2: VARIABLE x (child of 1)
```

(continues on next page)

(continued from previous page)

```
     *   node 3: VARIABLE y (child of 0)
     */
    int    nnodes_in2 = 4;
    int    opcode2[4] = {GRB_OPCODE_MINUS,      /* 0: root         */
                         GRB_OPCODE_COS,        /* 1: cos(...)     */
                         GRB_OPCODE_VARIABLE,   /* 2: x            */
                         GRB_OPCODE_VARIABLE};  /* 3: y            */
    double data2[4]   = {-1.0, -1.0,
                         (double) x.index(),
                         (double) y.index()};
    int    parent2[4] = {-1, 0, 1, 0};

    /* Add nonlinear constraint: sin(x)*x + x^2*y <= 1 */
    GRBNLConstr nlc1 = model.addNLConstr(nnodes_in1, opcode1, data1, parent1,
                                         GRB_LESS_EQUAL, 1.0,
                                         "NonlinearConstraint1");

    /* Add nonlinear constraint: cos(x) - y = 0 */
    GRBNLConstr nlc2 = model.addNLConstr(nnodes_in2, opcode2, data2, parent2,
                                         GRB_EQUAL, 0.0,
                                         "NonlinearConstraint2");

    /* Optimize model */
    model.optimize();

    int status = model.get(GRB_IntAttr_Status);
    cout << "\nFirst solve (nonlinear constraints)" << endl;
    if (status == GRB_OPTIMAL) {
      cout << "Optimal objective: " << model.get(GRB_DoubleAttr_ObjVal) << endl;
      cout << "  x = " << x.get(GRB_DoubleAttr_X)
           << ", y = " << y.get(GRB_DoubleAttr_X) << endl;
    } else if (status == GRB_INF_OR_UNBD) {
      cout << "Model is infeasible or unbounded" << endl;
    } else {
      cout << "Optimization was stopped early" << endl;
    }

    /* Retrieve number of nodes (first pass with NULLs) */
    int nnodes_out = -1;
    model.getNLConstrLHS(nlc1, &nnodes_out, NULL, NULL, NULL);
    cout << "\nRetrieved NL constraint with " << nnodes_out << " nodes" << endl;

    /* Retrieve full tree (second pass) */
    int*    opcode_out = new int[nnodes_out];
    double* data_out   = new double[nnodes_out];
    int*    parent_out = new int[nnodes_out];

    model.getNLConstrLHS(nlc1, &nnodes_out, opcode_out, data_out, parent_out);

    /* Verify tree matches what we added */
    for (int i = 0; i < nnodes_out; i++) {
      if (opcode_out[i] != opcode1[i] || parent_out[i] != parent1[i] || data_out[i] !=␣
```

(continues on next page)

(continued from previous page)

```
↪data1[i]) {
        cout << "ERROR: tree mismatch at node " << i << endl;
      }
    }

    delete[] opcode_out;
    delete[] data_out;
    delete[] parent_out;

    /* Delete nonlinear constraints */
    model.remove(nlc1);
    model.remove(nlc2);
    model.update();
    cout << "Deleted nonlinear constraints" << endl;

    /* Add a simple linear constraint instead: x + y >= 1 */
    model.addConstr(x + y >= 1.0, "LinearConstraint");

    /* Re-optimize */
    model.optimize();

    status = model.get(GRB_IntAttr_Status);
    cout << "\nSecond solve (linear constraint)" << endl;
    if (status == GRB_OPTIMAL) {
      cout << "Optimal objective: " << model.get(GRB_DoubleAttr_ObjVal) << endl;
      cout << "  x = " << x.get(GRB_DoubleAttr_X)
           << ", y = " << y.get(GRB_DoubleAttr_X) << endl;
    } else if (status == GRB_INF_OR_UNBD) {
      cout << "Model is infeasible or unbounded" << endl;
    } else {
      cout << "Optimization was stopped early" << endl;
    }

  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch(...) {
    cout << "Exception during optimization" << endl;
  }

  return 0;
}
```

nlobj_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple
   nonlinear model using the nonlinear objective API:

     minimize    sin(x) * x + x^2 * y
     subject to  x + y  >= 1
                -1 <= x <= 2
                 0 <= y <= 2

   The nonlinear objective is set via setNLObj() using an
   expression tree. Then we retrieve the tree with getNLObj() and
   verify it, delete it with delNLObj(), replace it with a simple
   linear objective, and re-optimize.
*/

#include "gurobi_c++.h"
using namespace std;

int
main(int   argc,
     char *argv[])
{

  try {

    /*  Create an environment */
    GRBEnv env = GRBEnv("nlobj.log");

    /*  Create an empty model */
    GRBModel model = GRBModel(env);

    /*  Create variables */
    GRBVar x = model.addVar(-1.0, 2.0, 0.0, GRB_CONTINUOUS, "x");
    GRBVar y = model.addVar(0.0, 2.0, 0.0, GRB_CONTINUOUS, "y");

    /*  Add constraint : x + y >= 1 */
    model.addConstr(x + y >= 1, "c0");

    /* Build the nonlinear objective: sin(x) * x + x^2 * y
     *
     * Expression tree (7 nodes):
     *
     *   node 0: PLUS       (root)
     *   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
     *   node 2: SIN        (child of 1)
     *   node 3: VARIABLE x (child of 2)
     *   node 4: VARIABLE x (child of 1)
     *   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
     *   node 6: POW        (child of 5)
     *   node 7: VARIABLE x (child of 6)
```

(continues on next page)

(continued from previous page)

```
 *   node 8: CONSTANT 2 (child of 6)
 *   node 9: VARIABLE y (child of 5)
 */

int    nnodes     = 10;
int    opcode[10] = { GRB_OPCODE_PLUS,     /*  0: root */
                      GRB_OPCODE_MULTIPLY, /*  1: sin(x)*x */
                      GRB_OPCODE_SIN,      /*  2: sin(...) */
                      GRB_OPCODE_VARIABLE, /*  3: x */
                      GRB_OPCODE_VARIABLE, /*  4: x */
                      GRB_OPCODE_MULTIPLY, /*  5: x^2 * y */
                      GRB_OPCODE_POW,      /*  6: x^2 */
                      GRB_OPCODE_VARIABLE, /*  7: x */
                      GRB_OPCODE_CONSTANT, /*  8: 2.0 */
                      GRB_OPCODE_VARIABLE }; /*  9: y */
double data[10]   = { -1.0,
                      -1.0,
                      -1.0,
                      (double)x.index(),
                      (double)x.index(),
                      -1.0,
                      -1.0,
                      (double)x.index(),
                      2.0,
                      (double)y.index() };
int    parent[10] = { -1, 0, 1, 2, 1, 0, 5, 6, 6, 5 };

/*  Set nonlinear objective (minimize by default) */
model.setNLObj(nnodes, opcode, data, parent);

/*  Optimize model */
model.optimize();

int status = model.get(GRB_IntAttr_Status);
if (status == GRB_OPTIMAL) {
  cout << "First solve (nonlinear objective):" << endl;
  cout << "  x = " << x.get(GRB_DoubleAttr_X) << endl;
  cout << "  y = " << y.get(GRB_DoubleAttr_X) << endl;
  cout
    << "  Obj = "
    << model.get(GRB_DoubleAttr_ObjVal)
    << endl;
}

/*  Retrieve the nonlinear objective and verify the number of
nodes */
int nnodes_out = -1 ;
model.getNLObj(&nnodes_out, NULL, NULL, NULL);
cout
  << "\nRetrieved NL objective with "
  << nnodes_out
  << " nodes"
```

(continues on next page)

(continued from previous page)

```
      << endl;

    /*  Delete the nonlinear objective */
    model.delNLObj();
    cout << "Deleted nonlinear objective" << endl;

    /*  Set a simple linear objective instead : minimize x + y */
    model.setObjective(x + y);

    /*  Re-optimize */
    model.optimize();

    status = model.get(GRB_IntAttr_Status);
    if (status == GRB_OPTIMAL) {
      cout << "\nSecond solve (linear objective):" << endl;
      cout << "  x = " << x.get(GRB_DoubleAttr_X) << endl;
      cout << "  y = " << y.get(GRB_DoubleAttr_X) << endl;
      cout
        << "  Obj = "
        << model.get(GRB_DoubleAttr_ObjVal)
        << endl;
    }

  } catch (GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch (...) {
    cout << "Exception during optimization" << endl;
  }

  return 0;
}
```

lp_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads an LP model from a file and solves it.
   If the model is infeasible or unbounded, the example turns off
   presolve and solves the model again. If the model is infeasible,
   the example computes an Irreducible Inconsistent Subsystem (IIS),
   and writes it to a file */

#include "gurobi_c++.h"
using namespace std;

int
main(int   argc,
     char *argv[])
{
```

(continues on next page)

(continued from previous page)

```
  if (argc < 2) {
    cout << "Usage: lp_c++ filename" << endl;
    return 1;
  }

  try {
    GRBEnv env = GRBEnv();
    GRBModel model = GRBModel(env, argv[1]);

    model.optimize();

    int optimstatus = model.get(GRB_IntAttr_Status);

    if (optimstatus == GRB_INF_OR_UNBD) {
      model.set(GRB_IntParam_Presolve, 0);
      model.optimize();
      optimstatus = model.get(GRB_IntAttr_Status);
    }

    if (optimstatus == GRB_OPTIMAL) {
      double objval = model.get(GRB_DoubleAttr_ObjVal);
      cout << "Optimal objective: " << objval << endl;
    } else if (optimstatus == GRB_INFEASIBLE) {
      cout << "Model is infeasible" << endl;

      // compute and write out IIS

      model.computeIIS();
      model.write("model.ilp");
    } else if (optimstatus == GRB_UNBOUNDED) {
      cout << "Model is unbounded" << endl;
    } else {
      cout << "Optimization was stopped with status = "
           << optimstatus << endl;
    }

  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch (...) {
    cout << "Error during optimization" << endl;
  }

  return 0;
}
```

lpmethod_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Solve a model with different values of the Method parameter;
   show which value gives the shortest solve time. */

#include "gurobi_c++.h"
using namespace std;

int
main(int   argc,
     char *argv[])
{

  if (argc < 2)
  {
    cout << "Usage: lpmethod_c++ filename" << endl;
    return 1;
  }

  try {
    // Read model
    GRBEnv env = GRBEnv();
    GRBModel m = GRBModel(env, argv[1]);

    // Solve the model with different values of Method
    int    bestMethod = -1;
    double bestTime = m.get(GRB_DoubleParam_TimeLimit);
    for (int i = 0; i <= 2; ++i) {
      m.reset();
      m.set(GRB_IntParam_Method, i);
      m.optimize();
      if (m.get(GRB_IntAttr_Status) == GRB_OPTIMAL) {
        bestTime = m.get(GRB_DoubleAttr_Runtime);
        bestMethod = i;
        // Reduce the TimeLimit parameter to save time
        // with other methods
        m.set(GRB_DoubleParam_TimeLimit, bestTime);
      }
    }

    // Report which method was fastest
    if (bestMethod == -1) {
      cout << "Unable to solve this model" << endl;
    } else {
      cout << "Solved in " << bestTime
        << " seconds with Method: " << bestMethod << endl;
    }
  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch(...) {
```

(continues on next page)

(continued from previous page)

```
    cout << "Exception during optimization" << endl;
  }

  return 0;
}
```

lpmod_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads an LP model from a file and solves it.
   If the model can be solved, then it finds the smallest positive variable,
   sets its upper bound to zero, and resolves the model two ways:
   first with an advanced start, then without an advanced start
   (i.e. 'from scratch'). */

#include "gurobi_c++.h"
using namespace std;

int
main(int argc,
     char *argv[])
{
  if (argc < 2)
  {
    cout << "Usage: lpmod_c++ filename" << endl;
    return 1;
  }

  GRBEnv* env = 0;
  GRBVar* v = 0;
  try
  {
    // Read model and determine whether it is an LP
    env = new GRBEnv();
    GRBModel model = GRBModel(*env, argv[1]);
    if (model.get(GRB_IntAttr_IsMIP) != 0)
    {
      cout << "The model is not a linear program" << endl;
      return 1;
    }

    model.optimize();

    int status = model.get(GRB_IntAttr_Status);

    if ((status == GRB_INF_OR_UNBD) || (status == GRB_INFEASIBLE) ||
        (status == GRB_UNBOUNDED))
    {
      cout << "The model cannot be solved because it is "
```

(continues on next page)

(continued from previous page)

```
    << "infeasible or unbounded" << endl;
    return 1;
  }

  if (status != GRB_OPTIMAL)
  {
    cout << "Optimization was stopped with status " << status << endl;
    return 0;
  }

  // Find the smallest variable value
  double minVal = GRB_INFINITY;
  int minVar = 0;
  v = model.getVars();
  for (int j = 0; j < model.get(GRB_IntAttr_NumVars); ++j)
  {
    double sol = v[j].get(GRB_DoubleAttr_X);
    if ((sol > 0.0001) && (sol < minVal) &&
        (v[j].get(GRB_DoubleAttr_LB) == 0.0))
    {
      minVal = sol;
      minVar = j;
    }
  }

  cout << "\n*** Setting " << v[minVar].get(GRB_StringAttr_VarName)
  << " from " << minVal << " to zero ***" << endl << endl;
  v[minVar].set(GRB_DoubleAttr_UB, 0.0);

  // Solve from this starting point
  model.optimize();

  // Save iteration & time info
  double warmCount = model.get(GRB_DoubleAttr_IterCount);
  double warmTime = model.get(GRB_DoubleAttr_Runtime);

  // Reset the model and resolve
  cout << "\n*** Resetting and solving "
  << "without an advanced start ***\n" << endl;
  model.reset();
  model.optimize();

  // Save iteration & time info
  double coldCount = model.get(GRB_DoubleAttr_IterCount);
  double coldTime = model.get(GRB_DoubleAttr_Runtime);

  cout << "\n*** Warm start: " << warmCount << " iterations, " <<
  warmTime << " seconds" << endl;
  cout << "*** Cold start: " << coldCount << " iterations, " <<
  coldTime << " seconds" << endl;

}
```

(continues on next page)

(continued from previous page)

```
  catch (GRBException e)
  {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...)
  {
    cout << "Error during optimization" << endl;
  }

  delete[] v;
  delete env;
  return 0;
}
```

mip1_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple MIP model:

     maximize    x +   y + 2 z
     subject to  x + 2 y + 3 z <= 4
                 x +   y       >= 1
                 x, y, z binary
*/

#include "gurobi_c++.h"
using namespace std;

int
main(int   argc,
     char *argv[])
{
  try {

    // Create an environment
    GRBEnv env = GRBEnv(true);
    env.set("LogFile", "mip1.log");
    env.start();

    // Create an empty model
    GRBModel model = GRBModel(env);

    // Create variables
    GRBVar x = model.addVar(0.0, 1.0, 0.0, GRB_BINARY, "x");
    GRBVar y = model.addVar(0.0, 1.0, 0.0, GRB_BINARY, "y");
    GRBVar z = model.addVar(0.0, 1.0, 0.0, GRB_BINARY, "z");

    // Set objective: maximize x + y + 2 z
```

(continues on next page)

(continued from previous page)

```
    model.setObjective(x + y + 2 * z, GRB_MAXIMIZE);

    // Add constraint: x + 2 y + 3 z <= 4
    model.addConstr(x + 2 * y + 3 * z <= 4, "c0");

    // Add constraint: x + y >= 1
    model.addConstr(x + y >= 1, "c1");

    // Optimize model
    model.optimize();

    cout << x.get(GRB_StringAttr_VarName) << " "
         << x.get(GRB_DoubleAttr_X) << endl;
    cout << y.get(GRB_StringAttr_VarName) << " "
         << y.get(GRB_DoubleAttr_X) << endl;
    cout << z.get(GRB_StringAttr_VarName) << " "
         << z.get(GRB_DoubleAttr_X) << endl;

    cout << "Obj: " << model.get(GRB_DoubleAttr_ObjVal) << endl;

  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch(...) {
    cout << "Exception during optimization" << endl;
  }

  return 0;
}
```

mip2_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, solves it and
   prints the objective values from all feasible solutions
   generated while solving the MIP. Then it creates the fixed
   model and solves that model. */

#include "gurobi_c++.h"
#include <cmath>
using namespace std;

int
main(int   argc,
     char *argv[])
{
  if (argc < 2) {
    cout << "Usage: mip2_c++ filename" << endl;
    return 1;
```

(continues on next page)

(continued from previous page)

```
}

GRBEnv *env = 0;
GRBVar *fvars = 0;
try {
  env = new GRBEnv();
  GRBModel model = GRBModel(*env, argv[1]);

  if (model.get(GRB_IntAttr_IsMIP) == 0) {
    throw GRBException("Model is not a MIP");
  }

  model.optimize();

  int optimstatus = model.get(GRB_IntAttr_Status);

  cout << "Optimization complete" << endl;
  double objval = 0;
  if (optimstatus == GRB_OPTIMAL) {
    objval = model.get(GRB_DoubleAttr_ObjVal);
    cout << "Optimal objective: " << objval << endl;
  } else if (optimstatus == GRB_INF_OR_UNBD) {
    cout << "Model is infeasible or unbounded" << endl;
    return 0;
  } else if (optimstatus == GRB_INFEASIBLE) {
    cout << "Model is infeasible" << endl;
    return 0;
  } else if (optimstatus == GRB_UNBOUNDED) {
    cout << "Model is unbounded" << endl;
    return 0;
  } else {
    cout << "Optimization was stopped with status = "
         << optimstatus << endl;
    return 0;
  }

  /* Iterate over the solutions and compute the objectives */

  cout << endl;
  for ( int k = 0; k < model.get(GRB_IntAttr_SolCount); ++k ) {
    model.set(GRB_IntParam_SolutionNumber, k);
    double objn = model.get(GRB_DoubleAttr_PoolNObjVal);

    cout << "Solution " << k << " has objective: " << objn << endl;
  }
  cout << endl;

  /* Create a fixed model, turn off presolve and solve */

  GRBModel fixed = model.fixedModel();

  fixed.set(GRB_IntParam_Presolve, 0);
```

(continues on next page)

(continued from previous page)

```
    fixed.optimize();

    int foptimstatus = fixed.get(GRB_IntAttr_Status);

    if (foptimstatus != GRB_OPTIMAL) {
      cerr << "Error: fixed model isn't optimal" << endl;
      return 0;
    }

    double fobjval = fixed.get(GRB_DoubleAttr_ObjVal);

    if (fabs(fobjval - objval) > 1.0e-6 * (1.0 + fabs(objval))) {
      cerr << "Error: objective values are different" << endl;
      return 0;
    }

    int numvars = model.get(GRB_IntAttr_NumVars);

    /* Print values of nonzero variables */
    fvars = fixed.getVars();
    for (int j = 0; j < numvars; j++) {
      GRBVar v = fvars[j];
      if (v.get(GRB_DoubleAttr_X) != 0.0) {
        cout << v.get(GRB_StringAttr_VarName) << " "
             << v.get(GRB_DoubleAttr_X) << endl;
      }
    }

  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch (...) {
    cout << "Error during optimization" << endl;
  }

  delete[] fvars;
  delete env;
  return 0;
}
```

multiobj_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Want to cover four different sets but subject to a common budget of
 * elements allowed to be used. However, the sets have different priorities to
 * be covered; and we tackle this by using multi-objective optimization. */

#include "gurobi_c++.h"
```

(continues on next page)

(continued from previous page)

```
#include <sstream>
#include <iomanip>
using namespace std;

int
main(void)
{
  GRBEnv *env  = 0;
  GRBVar *Elem = 0;
  int e, i, status, nSolutions;

  try{
    // Sample data
    const int groundSetSize = 20;
    const int nSubsets      = 4;
    const int Budget        = 12;
    double Set[][20] =
    { { 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0 },
      { 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1 },
      { 0, 0, 0, 1, 1, 0, 1, 1, 0, 0, 0, 0, 0, 1, 1, 0, 1, 1, 0, 0 },
      { 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0 } };
    int    SetObjPriority[] = {3, 2, 2, 1};
    double SetObjWeight[]   = {1.0, 0.25, 1.25, 1.0};

    // Create environment
    env = new GRBEnv("multiobj_c++.log");

    // Create initial model
    GRBModel model = GRBModel(*env);
    model.set(GRB_StringAttr_ModelName, "multiobj_c++");

    // Initialize decision variables for ground set:
    // x[e] == 1 if element e is chosen for the covering.
    Elem = model.addVars(groundSetSize, GRB_BINARY);
    for (e = 0; e < groundSetSize; e++) {
      ostringstream vname;
      vname << "El" << e;
      Elem[e].set(GRB_StringAttr_VarName, vname.str());
    }

    // Constraint: limit total number of elements to be picked to be at most
    // Budget
    GRBLinExpr lhs;
    lhs = 0;
    for (e = 0; e < groundSetSize; e++) {
      lhs += Elem[e];
    }
    model.addConstr(lhs <= Budget, "Budget");

    // Set global sense for ALL objectives
    model.set(GRB_IntAttr_ModelSense, GRB_MAXIMIZE);
```

(continues on next page)

(continued from previous page)

```
    // Limit how many solutions to collect
    model.set(GRB_IntParam_PoolSolutions, 100);

    // Set and configure i-th objective
    for (i = 0; i < nSubsets; i++) {
      GRBLinExpr objn = 0;
      for (e = 0; e < groundSetSize; e++)
        objn += Set[i][e]*Elem[e];
      ostringstream vname;
      vname << "Set" << i;

      model.setObjectiveN(objn, i, SetObjPriority[i], SetObjWeight[i],
                          1.0 + i, 0.01, vname.str());
    }

    // Save problem
    model.write("multiobj_c++.lp");

    // Optimize
    model.optimize();

    // Status checking
    status = model.get(GRB_IntAttr_Status);

    if (status == GRB_INF_OR_UNBD ||
        status == GRB_INFEASIBLE  ||
        status == GRB_UNBOUNDED     ) {
      cout << "The model cannot be solved " <<
              "because it is infeasible or unbounded" << endl;
      return 1;
    }
    if (status != GRB_OPTIMAL) {
      cout << "Optimization was stopped with status " << status << endl;
      return 1;
    }

    // Print best selected set
    cout << "Selected elements in best solution:" << endl << "\t";
    for (e = 0; e < groundSetSize; e++) {
      if (Elem[e].get(GRB_DoubleAttr_X) < .9) continue;
      cout << " El" << e;
    }
    cout << endl;

    // Print number of solutions stored
    nSolutions = model.get(GRB_IntAttr_SolCount);
    cout << "Number of solutions found: " << nSolutions << endl;

    // Print objective values of solutions
    if (nSolutions > 10) nSolutions = 10;
    cout << "Objective values for first " << nSolutions;
    cout << " solutions:" << endl;
```

(continues on next page)

(continued from previous page)

```
    for (i = 0; i < nSubsets; i++) {
      model.set(GRB_IntParam_ObjNumber, i);

      cout << "\tSet" << i;
      for (e = 0; e < nSolutions; e++) {
        cout << " ";
        model.set(GRB_IntParam_SolutionNumber, e);
        double val = model.get(GRB_DoubleAttr_ObjNVal);
        cout << std::setw(6) << val;
      }
      cout << endl;
    }

  }
  catch (GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...) {
    cout << "Exception during optimization" << endl;
  }

  // Free environment/vars
  delete[] Elem;
  delete env;
  return 0;
}
```

multiscenario_c++.cpp

```
// Copyright 2026, Gurobi Optimization, LLC

// Facility location: a company currently ships its product from 5 plants
// to 4 warehouses. It is considering closing some plants to reduce
// costs. What plant(s) should the company close, in order to minimize
// transportation and fixed costs?
//
// Since the plant fixed costs and the warehouse demands are uncertain, a
// scenario approach is chosen.
//
// Note that this example is similar to the facility_c++.cpp example. Here
// we added scenarios in order to illustrate the multi-scenario feature.
//
// Based on an example from Frontline Systems:
// http://www.solver.com/disfacility.htm
// Used with permission.

#include "gurobi_c++.h"
#include <sstream>
#include <iomanip>
```

(continues on next page)

(continued from previous page)

```
using namespace std;

int
main(int   argc,
     char *argv[])
{
  GRBEnv     *env          = 0;
  GRBVar     *open         = 0;
  GRBVar    **transport    = 0;
  GRBConstr  *demandConstr = 0;

  int transportCt = 0;

  try {
    // Number of plants and warehouses
    const int nPlants = 5;
    const int nWarehouses = 4;

    // Warehouse demand in thousands of units
    double Demand[] = { 15, 18, 14, 20 };

    // Plant capacity in thousands of units
    double Capacity[] = { 20, 22, 17, 19, 18 };

    // Fixed costs for each plant
    double FixedCosts[] =
      { 12000, 15000, 17000, 13000, 16000 };

    // Transportation costs per thousand units
    double TransCosts[][nPlants] = {
      { 4000, 2000, 3000, 2500, 4500 },
      { 2500, 2600, 3400, 3000, 4000 },
      { 1200, 1800, 2600, 4100, 3000 },
      { 2200, 2600, 3100, 3700, 3200 }
    };

    double maxFixed = -GRB_INFINITY;
    double minFixed = GRB_INFINITY;

    int p;
    for (p = 0; p < nPlants; p++) {
      if (FixedCosts[p] > maxFixed)
        maxFixed = FixedCosts[p];

      if (FixedCosts[p] < minFixed)
        minFixed = FixedCosts[p];
    }

    // Model
    env = new GRBEnv();
    GRBModel model = GRBModel(*env);
    model.set(GRB_StringAttr_ModelName, "multiscenario");
```

(continues on next page)

(continued from previous page)

```
  // Plant open decision variables: open[p] == 1 if plant p is open.
  open = model.addVars(nPlants, GRB_BINARY);

  for (p = 0; p < nPlants; p++) {
    ostringstream vname;
    vname << "Open" << p;
    open[p].set(GRB_DoubleAttr_Obj, FixedCosts[p]);
    open[p].set(GRB_StringAttr_VarName, vname.str());
  }

  // Transportation decision variables: how much to transport from
  // a plant p to a warehouse w
  transport = new GRBVar* [nWarehouses];
  int w;
  for (w = 0; w < nWarehouses; w++) {
    transport[w] = model.addVars(nPlants);
    transportCt++;

    for (p = 0; p < nPlants; p++) {
      ostringstream vname;
      vname << "Trans" << p << "." << w;
      transport[w][p].set(GRB_DoubleAttr_Obj, TransCosts[w][p]);
      transport[w][p].set(GRB_StringAttr_VarName, vname.str());
    }
  }

  // The objective is to minimize the total fixed and variable costs
  model.set(GRB_IntAttr_ModelSense, GRB_MINIMIZE);

  // Production constraints
  // Note that the right-hand limit sets the production to zero if
  // the plant is closed
  for (p = 0; p < nPlants; p++) {
    GRBLinExpr ptot = 0;
    for (w = 0; w < nWarehouses; w++) {
      ptot += transport[w][p];
    }
    ostringstream cname;
    cname << "Capacity" << p;
    model.addConstr(ptot <= Capacity[p] * open[p], cname.str());
  }

  // Demand constraints
  demandConstr = new GRBConstr[nWarehouses];
  for (w = 0; w < nWarehouses; w++) {
    GRBLinExpr dtot = 0;
    for (p = 0; p < nPlants; p++)
      dtot += transport[w][p];

    ostringstream cname;
    cname << "Demand" << w;
```

(continues on next page)

(continued from previous page)

```
    demandConstr[w] = model.addConstr(dtot == Demand[w], cname.str());
  }

  // We constructed the base model, now we add 7 scenarios
  //
  // Scenario 0: Represents the base model, hence, no manipulations.
  // Scenario 1: Manipulate the warehouses demands slightly (constraint right
  //             hand sides).
  // Scenario 2: Double the warehouses demands (constraint right hand sides).
  // Scenario 3: Manipulate the plant fixed costs (objective coefficients).
  // Scenario 4: Manipulate the warehouses demands and fixed costs.
  // Scenario 5: Force the plant with the largest fixed cost to stay open
  //             (variable bounds).
  // Scenario 6: Force the plant with the smallest fixed cost to be closed
  //             (variable bounds).

  model.set(GRB_IntAttr_NumScenarios, 7);

  // Scenario 0: Base model, hence, nothing to do except giving the
  //             scenario a name
  model.set(GRB_IntParam_ScenarioNumber, 0);
  model.set(GRB_StringAttr_ScenNName, "Base model");

  // Scenario 1: Increase the warehouse demands by 10%
  model.set(GRB_IntParam_ScenarioNumber, 1);
  model.set(GRB_StringAttr_ScenNName, "Increased warehouse demands");

  for (w = 0; w < nWarehouses; w++) {
    demandConstr[w].set(GRB_DoubleAttr_ScenNRHS, Demand[w] * 1.1);
  }

  // Scenario 2: Double the warehouse demands
  model.set(GRB_IntParam_ScenarioNumber, 2);
  model.set(GRB_StringAttr_ScenNName, "Double the warehouse demands");

  for (w = 0; w < nWarehouses; w++) {
    demandConstr[w].set(GRB_DoubleAttr_ScenNRHS, Demand[w] * 2.0);
  }

  // Scenario 3: Decrease the plant fixed costs by 5%
  model.set(GRB_IntParam_ScenarioNumber, 3);
  model.set(GRB_StringAttr_ScenNName, "Decreased plant fixed costs");

  for (p = 0; p < nPlants; p++) {
    open[p].set(GRB_DoubleAttr_ScenNObj, FixedCosts[p] * 0.95);
  }

  // Scenario 4: Combine scenario 1 and scenario 3 */
  model.set(GRB_IntParam_ScenarioNumber, 4);
  model.set(GRB_StringAttr_ScenNName, "Increased warehouse demands and decreased plant␣
↪fixed costs");
```

(continues on next page)

(continued from previous page)

```
    for (w = 0; w < nWarehouses; w++) {
      demandConstr[w].set(GRB_DoubleAttr_ScenNRHS, Demand[w] * 1.1);
    }
    for (p = 0; p < nPlants; p++) {
      open[p].set(GRB_DoubleAttr_ScenNObj, FixedCosts[p] * 0.95);
    }

    // Scenario 5: Force the plant with the largest fixed cost to stay
    //             open
    model.set(GRB_IntParam_ScenarioNumber, 5);
    model.set(GRB_StringAttr_ScenNName, "Force plant with largest fixed cost to stay open
↪");

    for (p = 0; p < nPlants; p++) {
      if (FixedCosts[p] == maxFixed) {
        open[p].set(GRB_DoubleAttr_ScenNLB, 1.0);
        break;
      }
    }

    // Scenario 6: Force the plant with the smallest fixed cost to be
    //             closed
    model.set(GRB_IntParam_ScenarioNumber, 6);
    model.set(GRB_StringAttr_ScenNName, "Force plant with smallest fixed cost to be␣
↪closed");

    for (p = 0; p < nPlants; p++) {
      if (FixedCosts[p] == minFixed) {
        open[p].set(GRB_DoubleAttr_ScenNUB, 0.0);
        break;
      }
    }

    // Guess at the starting point: close the plant with the highest
    // fixed costs; open all others

    // First, open all plants
    for (p = 0; p < nPlants; p++)
      open[p].set(GRB_DoubleAttr_Start, 1.0);

    // Now close the plant with the highest fixed cost
    cout << "Initial guess:" << endl;
    for (p = 0; p < nPlants; p++) {
      if (FixedCosts[p] == maxFixed) {
        open[p].set(GRB_DoubleAttr_Start, 0.0);
        cout << "Closing plant " << p << endl << endl;
        break;
      }
    }

    // Use barrier to solve root relaxation
    model.set(GRB_IntParam_Method, GRB_METHOD_BARRIER);
```

(continues on next page)

(continued from previous page)

```
  // Solve multi-scenario model
  model.optimize();

  int nScenarios = model.get(GRB_IntAttr_NumScenarios);

  // Print solution for each */
  for (int s = 0; s < nScenarios; s++) {
    int modelSense = GRB_MINIMIZE;

    // Set the scenario number to query the information for this scenario
    model.set(GRB_IntParam_ScenarioNumber, s);

    // collect result for the scenario
    double scenNObjBound = model.get(GRB_DoubleAttr_ScenNObjBound);
    double scenNObjVal = model.get(GRB_DoubleAttr_ScenNObjVal);

    cout << endl << endl << "------ Scenario " << s
         << " (" << model.get(GRB_StringAttr_ScenNName) << ")" << endl;

    // Check if we found a feasible solution for this scenario
    if (modelSense * scenNObjVal >= GRB_INFINITY)
      if (modelSense * scenNObjBound >= GRB_INFINITY)
        // Scenario was proven to be infeasible
        cout << endl << "INFEASIBLE" << endl;
      else
        // We did not find any feasible solution - should not happen in
        // this case, because we did not set any limit (like a time
        // limit) on the optimization process
        cout << endl << "NO SOLUTION" << endl;
    else {
      cout << endl << "TOTAL COSTS: " << scenNObjVal << endl;
      cout << "SOLUTION:" << endl;
      for (p = 0; p < nPlants; p++) {
        double scenNX = open[p].get(GRB_DoubleAttr_ScenNX);

        if (scenNX > 0.5) {
          cout << "Plant " << p << " open" << endl;
          for (w = 0; w < nWarehouses; w++) {
            scenNX = transport[w][p].get(GRB_DoubleAttr_ScenNX);

            if (scenNX > 0.0001)
              cout << "  Transport " << scenNX
                   << " units to warehouse " << w << endl;
          }
        } else
          cout << "Plant " << p << " closed!" << endl;
      }
    }
  }

  // Print a summary table: for each scenario we add a single summary
```

(continues on next page)

(continued from previous page)

```
    // line
    cout << endl << endl << "Summary: Closed plants depending on scenario" << endl <<␣
↪endl;
    cout << setw(8) << " " << " | " << setw(17) << "Plant" << setw(14) << "|" << endl;

    cout << setw(8) << "Scenario" << " |";
    for (p = 0; p < nPlants; p++)
      cout << " " << setw(5) << p;
    cout << " | " << setw(6) << "Costs" << "  Name" << endl;

    for (int s = 0; s < nScenarios; s++) {
      int modelSense = GRB_MINIMIZE;

      // Set the scenario number to query the information for this scenario
      model.set(GRB_IntParam_ScenarioNumber, s);

      // Collect result for the scenario
      double scenNObjBound = model.get(GRB_DoubleAttr_ScenNObjBound);
      double scenNObjVal = model.get(GRB_DoubleAttr_ScenNObjVal);

      cout << left << setw(8) << s << right << " |";

      // Check if we found a feasible solution for this scenario
      if (modelSense * scenNObjVal >= GRB_INFINITY) {
        if (modelSense * scenNObjBound >= GRB_INFINITY)
          // Scenario was proven to be infeasible
          cout << " " << left << setw(30) << "infeasible" << right;
        else
          // We did not find any feasible solution - should not happen in
          // this case, because we did not set any limit (like a time
          // limit) on the optimization process
          cout << " " << left << setw(30) << "no solution found" << right;

        cout << "| " << setw(6) << "-"
             << "  " << model.get(GRB_StringAttr_ScenNName)
             << endl;
      } else {
        for (p = 0; p < nPlants; p++) {
          double scenNX = open[p].get(GRB_DoubleAttr_ScenNX);
          if (scenNX  > 0.5)
            cout << setw(6) << " ";
          else
            cout << " " << setw(5) << "x";
        }

        cout << " | " << setw(6) << scenNObjVal
             << "  " << model.get(GRB_StringAttr_ScenNName)
             << endl;
      }
    }
  }
  catch (GRBException e) {
```

(continues on next page)

(continued from previous page)

```
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...) {
    cout << "Exception during optimization" << endl;
  }

  delete[] open;
  for (int i = 0; i < transportCt; ++i) {
    delete[] transport[i];
  }
  delete[] transport;
  delete[] demandConstr;
  delete env;
  return 0;
}
```

params_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Use parameters that are associated with a model.

   A MIP is solved for a few seconds with different sets of parameters.
   The one with the smallest MIP gap is selected, and the optimization
   is resumed until the optimal solution is found.
*/

#include "gurobi_c++.h"
using namespace std;

int
main(int argc,
     char *argv[])
{
  if (argc < 2)
  {
    cout << "Usage: params_c++ filename" << endl;
    return 1;
  }

  GRBEnv* env = 0;
  GRBModel *bestModel = 0, *m = 0;
  try
  {
    // Read model and verify that it is a MIP
    env = new GRBEnv();
    m = new GRBModel(*env, argv[1]);
    if (m->get(GRB_IntAttr_IsMIP) == 0)
    {
```

(continues on next page)

(continued from previous page)

```
      cout << "The model is not an integer program" << endl;
      return 1;
    }

    // Set a 2 second time limit
    m->set(GRB_DoubleParam_TimeLimit, 2);

    // Now solve the model with different values of MIPFocus
    bestModel = new GRBModel(*m);
    bestModel->optimize();
    for (int i = 1; i <= 3; ++i)
    {
      m->reset();
      m->set(GRB_IntParam_MIPFocus, i);
      m->optimize();
      if (bestModel->get(GRB_DoubleAttr_MIPGap) >
                  m->get(GRB_DoubleAttr_MIPGap))
      {
        swap(bestModel, m);
      }
    }

    // Finally, delete the extra model, reset the time limit and
    // continue to solve the best model to optimality
    delete m;
    m = 0;
    bestModel->set(GRB_DoubleParam_TimeLimit, GRB_INFINITY);
    bestModel->optimize();
    cout << "Solved with MIPFocus: " <<
    bestModel->get(GRB_IntParam_MIPFocus) << endl;

  }
  catch (GRBException e)
  {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...)
  {
    cout << "Error during optimization" << endl;
  }

  delete bestModel;
  delete m;
  delete env;
  return 0;
}
```

piecewise_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example considers the following separable, convex problem:

     minimize    f(x) - y + g(z)
     subject to  x + 2 y + 3 z <= 4
                 x +   y       >= 1
                 x,    y,    z <= 1

   where f(u) = exp(-u) and g(u) = 2 u^2 - 4 u, for all real u. It
   formulates and solves a simpler LP model by approximating f and
   g with piecewise-linear functions. Then it transforms the model
   into a MIP by negating the approximation for f, which corresponds
   to a non-convex piecewise-linear function, and solves it again.
*/

#include "gurobi_c++.h"
#include <cmath>
using namespace std;

double f(double u) { return exp(-u); }
double g(double u) { return 2 * u * u - 4 * u; }

int
main(int   argc,
     char *argv[])
{
  double *ptu = NULL;
  double *ptf = NULL;
  double *ptg = NULL;

  try {

    // Create environment

    GRBEnv env = GRBEnv();

    // Create a new model

    GRBModel model = GRBModel(env);

    // Create variables

    double lb = 0.0, ub = 1.0;

    GRBVar x = model.addVar(lb, ub, 0.0, GRB_CONTINUOUS, "x");
    GRBVar y = model.addVar(lb, ub, 0.0, GRB_CONTINUOUS, "y");
    GRBVar z = model.addVar(lb, ub, 0.0, GRB_CONTINUOUS, "z");

    // Set objective for y
```

(continues on next page)

(continued from previous page)

```
  model.setObjective(-y);

  // Add piecewise-linear objective functions for x and z

  int npts = 101;
  ptu = new double[npts];
  ptf = new double[npts];
  ptg = new double[npts];

  for (int i = 0; i < npts; i++) {
    ptu[i] = lb + (ub - lb) * i / (npts - 1);
    ptf[i] = f(ptu[i]);
    ptg[i] = g(ptu[i]);
  }

  model.setPWLObj(x, npts, ptu, ptf);
  model.setPWLObj(z, npts, ptu, ptg);

  // Add constraint: x + 2 y + 3 z <= 4

  model.addConstr(x + 2 * y + 3 * z <= 4, "c0");

  // Add constraint: x + y >= 1

  model.addConstr(x + y >= 1, "c1");

  // Optimize model as an LP

  model.optimize();

  cout << "IsMIP: " << model.get(GRB_IntAttr_IsMIP) << endl;

  cout << x.get(GRB_StringAttr_VarName) << " "
       << x.get(GRB_DoubleAttr_X) << endl;
  cout << y.get(GRB_StringAttr_VarName) << " "
       << y.get(GRB_DoubleAttr_X) << endl;
  cout << z.get(GRB_StringAttr_VarName) << " "
       << z.get(GRB_DoubleAttr_X) << endl;

  cout << "Obj: " << model.get(GRB_DoubleAttr_ObjVal) << endl;

  cout << endl;

  // Negate piecewise-linear objective function for x

  for (int i = 0; i < npts; i++) {
    ptf[i] = -ptf[i];
  }

  model.setPWLObj(x, npts, ptu, ptf);

  // Optimize model as a MIP
```

(continues on next page)

(continued from previous page)

```
    model.optimize();

    cout << "IsMIP: " << model.get(GRB_IntAttr_IsMIP) << endl;

    cout << x.get(GRB_StringAttr_VarName) << " "
         << x.get(GRB_DoubleAttr_X) << endl;
    cout << y.get(GRB_StringAttr_VarName) << " "
         << y.get(GRB_DoubleAttr_X) << endl;
    cout << z.get(GRB_StringAttr_VarName) << " "
         << z.get(GRB_DoubleAttr_X) << endl;

    cout << "Obj: " << model.get(GRB_DoubleAttr_ObjVal) << endl;

  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch(...) {
    cout << "Exception during optimization" << endl;
  }

  delete[] ptu;
  delete[] ptf;
  delete[] ptg;

  return 0;
}
```

poolsearch_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* We find alternative epsilon-optimal solutions to a given knapsack
 * problem by using PoolSearchMode */

#include "gurobi_c++.h"
#include <sstream>
#include <iomanip>
using namespace std;


int main(void)
{
  GRBEnv *env  = 0;
  GRBVar *Elem = 0;
  int e, status, nSolutions;

  try {
    // Sample data
    const int groundSetSize = 10;
```

(continues on next page)

(continued from previous page)

```
    double objCoef[10] =
    {32, 32, 15, 15, 6, 6, 1, 1, 1, 1};
    double knapsackCoef[10] =
    {16, 16,  8,  8, 4, 4, 2, 2, 1, 1};
    double Budget = 33;

    // Create environment
    env = new GRBEnv("poolsearch_c++.log");

    // Create initial model
    GRBModel model = GRBModel(*env);
    model.set(GRB_StringAttr_ModelName, "poolsearch_c++");

    // Initialize decision variables for ground set:
    // x[e] == 1 if element e is chosen
    Elem = model.addVars(groundSetSize, GRB_BINARY);
    model.set(GRB_DoubleAttr_Obj, Elem, objCoef, groundSetSize);

    for (e = 0; e < groundSetSize; e++) {
      ostringstream vname;
      vname << "El" << e;
      Elem[e].set(GRB_StringAttr_VarName, vname.str());
    }

    // Constraint: limit total number of elements to be picked to be at most
    // Budget
    GRBLinExpr lhs;
    lhs = 0;
    for (e = 0; e < groundSetSize; e++) {
      lhs += Elem[e] * knapsackCoef[e];
    }
    model.addConstr(lhs <= Budget, "Budget");

    // set global sense for ALL objectives
    model.set(GRB_IntAttr_ModelSense, GRB_MAXIMIZE);

    // Limit how many solutions to collect
    model.set(GRB_IntParam_PoolSolutions, 1024);

    // Limit the search space by setting a gap for the worst possible solution that will␣
↪be accepted
    model.set(GRB_DoubleParam_PoolGap, 0.10);

    // do a systematic search for the k-best solutions
    model.set(GRB_IntParam_PoolSearchMode, 2);

    // save problem
    model.write("poolsearch_c++.lp");

    // Optimize
    model.optimize();
```

(continues on next page)

(continued from previous page)

```
    // Status checking
    status = model.get(GRB_IntAttr_Status);

    if (status == GRB_INF_OR_UNBD ||
        status == GRB_INFEASIBLE  ||
        status == GRB_UNBOUNDED     ) {
      cout << "The model cannot be solved " <<
              "because it is infeasible or unbounded" << endl;
      return 1;
    }
    if (status != GRB_OPTIMAL) {
      cout << "Optimization was stopped with status " << status << endl;
      return 1;
    }

    // Print best selected set
    cout << "Selected elements in best solution:" << endl << "\t";
    for (e = 0; e < groundSetSize; e++) {
      if (Elem[e].get(GRB_DoubleAttr_X) < .9) continue;
      cout << " El" << e;
    }
    cout << endl;

    // Print number of solutions stored
    nSolutions = model.get(GRB_IntAttr_SolCount);
    cout << "Number of solutions found: " << nSolutions << endl;

    // Print objective values of solutions
    for (e = 0; e < nSolutions; e++) {
      model.set(GRB_IntParam_SolutionNumber, e);
      cout << model.get(GRB_DoubleAttr_PoolNObjVal) << " ";
      if (e%15 == 14) cout << endl;
    }
    cout << endl;

    // print fourth best set if available
    if (nSolutions >= 4) {
      model.set(GRB_IntParam_SolutionNumber, 3);

      cout << "Selected elements in fourth best solution:" << endl << "\t";
      for (e = 0; e < groundSetSize; e++) {
        if (Elem[e].get(GRB_DoubleAttr_PoolNX) < .9) continue;
        cout << " El" << e;
      }
      cout << endl;
    }
  }
  catch (GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...) {
```

(continues on next page)

(continued from previous page)

```
    cout << "Exception during optimization" << endl;
  }

  // Free environment/vars
  delete[] Elem;
  delete env;
  return 0;
}
```

qcp_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QCP model:

     maximize    x
     subject to  x + y + z = 1
                 x^2 + y^2 <= z^2 (second-order cone)
                 x^2 <= yz        (rotated second-order cone)
                 x, y, z non-negative
*/

#include "gurobi_c++.h"
using namespace std;

int
main(int   argc,
     char *argv[])
{
  try {
    GRBEnv env = GRBEnv();

    GRBModel model = GRBModel(env);

    // Create variables

    GRBVar x = model.addVar(0.0, GRB_INFINITY, 0.0, GRB_CONTINUOUS, "x");
    GRBVar y = model.addVar(0.0, GRB_INFINITY, 0.0, GRB_CONTINUOUS, "y");
    GRBVar z = model.addVar(0.0, GRB_INFINITY, 0.0, GRB_CONTINUOUS, "z");

    // Set objective

    GRBLinExpr obj = x;
    model.setObjective(obj, GRB_MAXIMIZE);

    // Add linear constraint: x + y + z = 1

    model.addConstr(x + y + z == 1, "c0");

    // Add second-order cone: x^2 + y^2 <= z^2
```

(continues on next page)

(continued from previous page)

```
    model.addQConstr(x*x + y*y <= z*z, "qc0");

    // Add rotated cone: x^2 <= yz

    model.addQConstr(x*x <= y*z, "qc1");

    // Optimize model

    model.optimize();

    cout << x.get(GRB_StringAttr_VarName) << " "
         << x.get(GRB_DoubleAttr_X) << endl;
    cout << y.get(GRB_StringAttr_VarName) << " "
         << y.get(GRB_DoubleAttr_X) << endl;
    cout << z.get(GRB_StringAttr_VarName) << " "
         << z.get(GRB_DoubleAttr_X) << endl;

    cout << "Obj: " << model.get(GRB_DoubleAttr_ObjVal) << endl;

  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch(...) {
    cout << "Exception during optimization" << endl;
  }

  return 0;
}
```

qp_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QP model:

     minimize    x^2 + x*y + y^2 + y*z + z^2 + 2 x
     subject to  x + 2 y + 3 z >= 4
                 x +   y       >= 1
                 x, y, z non-negative

   It solves it once as a continuous model, and once as an integer model.
*/

#include "gurobi_c++.h"
using namespace std;

int
main(int   argc,
     char *argv[])
```

(continues on next page)

(continued from previous page)

```
{
  try {
    GRBEnv env = GRBEnv();

    GRBModel model = GRBModel(env);

    // Create variables

    GRBVar x = model.addVar(0.0, 1.0, 0.0, GRB_CONTINUOUS, "x");
    GRBVar y = model.addVar(0.0, 1.0, 0.0, GRB_CONTINUOUS, "y");
    GRBVar z = model.addVar(0.0, 1.0, 0.0, GRB_CONTINUOUS, "z");

    // Set objective

    GRBQuadExpr obj = x*x + x*y + y*y + y*z + z*z + 2*x;
    model.setObjective(obj);

    // Add constraint: x + 2 y + 3 z >= 4

    model.addConstr(x + 2 * y + 3 * z >= 4, "c0");

    // Add constraint: x + y >= 1

    model.addConstr(x + y >= 1, "c1");

    // Optimize model

    model.optimize();

    cout << x.get(GRB_StringAttr_VarName) << " "
         << x.get(GRB_DoubleAttr_X) << endl;
    cout << y.get(GRB_StringAttr_VarName) << " "
         << y.get(GRB_DoubleAttr_X) << endl;
    cout << z.get(GRB_StringAttr_VarName) << " "
         << z.get(GRB_DoubleAttr_X) << endl;

    cout << "Obj: " << model.get(GRB_DoubleAttr_ObjVal) << endl;

    // Change variable types to integer

    x.set(GRB_CharAttr_VType, GRB_INTEGER);
    y.set(GRB_CharAttr_VType, GRB_INTEGER);
    z.set(GRB_CharAttr_VType, GRB_INTEGER);

    // Optimize model

    model.optimize();

    cout << x.get(GRB_StringAttr_VarName) << " "
         << x.get(GRB_DoubleAttr_X) << endl;
    cout << y.get(GRB_StringAttr_VarName) << " "
         << y.get(GRB_DoubleAttr_X) << endl;
```

(continues on next page)

(continued from previous page)

```
    cout << z.get(GRB_StringAttr_VarName) << " "
         << z.get(GRB_DoubleAttr_X) << endl;

    cout << "Obj: " << model.get(GRB_DoubleAttr_ObjVal) << endl;

  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch(...) {
    cout << "Exception during optimization" << endl;
  }

  return 0;
}
```

sensitivity_c++.cpp

```
// Copyright 2026, Gurobi Optimization, LLC

// A simple sensitivity analysis example which reads a MIP model from a
// file and solves it. Then uses the scenario feature to analyze the impact
// w.r.t. the objective function of each binary variable if it is set to
// 1-X, where X is its value in the optimal solution.
//
// Usage:
//     sensitivity_c++ <model filename>

#include "gurobi_c++.h"
using namespace std;

// Maximum number of scenarios to be considered
#define MAXSCENARIOS 100

int
main(int   argc,
     char *argv[])
{
  if (argc < 2) {
    cout << "Usage: sensitivity_c++ filename" << endl;
    return 1;
  }

  GRBVar *vars  = NULL;
  double *origX = NULL;

  try {

    // Create environment
    GRBEnv env = GRBEnv();
```

(continues on next page)

(continued from previous page)

```
  // Read model
  GRBModel model = GRBModel(env, argv[1]);

  int scenarios;

  if (model.get(GRB_IntAttr_IsMIP) == 0) {
    cout << "Model is not a MIP" << endl;
    return 1;
  }

  // Solve model
  model.optimize();

  if (model.get(GRB_IntAttr_Status) != GRB_OPTIMAL) {
    cout << "Optimization ended with status "
         << model.get(GRB_IntAttr_Status) << endl;
    return 1;
  }

  // Store the optimal solution
  double origObjVal = model.get(GRB_DoubleAttr_ObjVal);
  vars = model.getVars();
  int numVars = model.get(GRB_IntAttr_NumVars);
  origX = model.get(GRB_DoubleAttr_X, vars, numVars);

  scenarios = 0;

  // Count number of unfixed, binary variables in model. For each we
  // create a scenario.
  for (int i = 0; i < numVars; i++) {
    GRBVar v     = vars[i];
    char   vType = v.get(GRB_CharAttr_VType);

    if (v.get(GRB_DoubleAttr_LB) == 0.0               &&
        v.get(GRB_DoubleAttr_UB) == 1.0               &&
        (vType == GRB_BINARY || vType == GRB_INTEGER)   ) {
      scenarios++;

      if (scenarios >= MAXSCENARIOS)
        break;
    }
  }

  cout << "###  construct multi-scenario model with "
       << scenarios << " scenarios" << endl;

  // Set the number of scenarios in the model */
  model.set(GRB_IntAttr_NumScenarios, scenarios);

  scenarios = 0;

  // Create a (single) scenario model by iterating through unfixed binary
```

(continues on next page)

(continued from previous page)

```
  // variables in the model and create for each of these variables a
  // scenario by fixing the variable to 1-X, where X is its value in the
  // computed optimal solution
  for (int i = 0; i < numVars; i++) {
    GRBVar v     = vars[i];
    char   vType = v.get(GRB_CharAttr_VType);

    if (v.get(GRB_DoubleAttr_LB) == 0.0               &&
        v.get(GRB_DoubleAttr_UB) == 1-0               &&
        (vType == GRB_BINARY || vType == GRB_INTEGER) &&
        scenarios < MAXSCENARIOS                        ) {

      // Set ScenarioNumber parameter to select the corresponding
      // scenario for adjustments
      model.set(GRB_IntParam_ScenarioNumber, scenarios);

      // Set variable to 1-X, where X is its value in the optimal solution */
      if (origX[i] < 0.5)
        v.set(GRB_DoubleAttr_ScenNLB, 1.0);
      else
        v.set(GRB_DoubleAttr_ScenNUB, 0.0);

      scenarios++;
    } else {
      // Add MIP start for all other variables using the optimal solution
      // of the base model
      v.set(GRB_DoubleAttr_Start, origX[i]);
    }
  }

  // Solve multi-scenario model
  model.optimize();

  // In case we solved the scenario model to optimality capture the
  // sensitivity information
  if (model.get(GRB_IntAttr_Status) == GRB_OPTIMAL) {

    // get the model sense (minimization or maximization)
    int modelSense = model.get(GRB_IntAttr_ModelSense);

    scenarios = 0;

    for (int i = 0; i < numVars; i++) {
      GRBVar v     = vars[i];
      char   vType = v.get(GRB_CharAttr_VType);

      if (v.get(GRB_DoubleAttr_LB) == 0.0               &&
          v.get(GRB_DoubleAttr_UB) == 1-0               &&
          (vType == GRB_BINARY || vType == GRB_INTEGER)   ) {

        // Set scenario parameter to collect the objective value of the
        // corresponding scenario
```

(continues on next page)

(continued from previous page)

```
          model.set(GRB_IntParam_ScenarioNumber, scenarios);

          // Collect objective value and bound for the scenario
          double scenarioObjVal = model.get(GRB_DoubleAttr_ScenNObjVal);
          double scenarioObjBound = model.get(GRB_DoubleAttr_ScenNObjBound);

          cout << "Objective sensitivity for variable "
               << v.get(GRB_StringAttr_VarName)
               << " is ";

          // Check if we found a feasible solution for this scenario
          if (modelSense * scenarioObjVal >= GRB_INFINITY) {
            // Check if the scenario is infeasible
            if (modelSense * scenarioObjBound >= GRB_INFINITY)
              cout << "infeasible"  << endl;
            else
              cout << "unknown (no solution available)"  << endl;
          } else {
            // Scenario is feasible and a solution is available
            cout << modelSense * (scenarioObjVal - origObjVal) << endl;
          }

          scenarios++;

          if (scenarios >= MAXSCENARIOS)
            break;
        }
      }
    }
  } catch (GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch (...) {
    cout << "Error during optimization" << endl;
  }

  delete[] vars;
  delete[] origX;

  return 0;
}
```

sos_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example creates a very simple Special Ordered Set (SOS) model.
   The model consists of 3 continuous variables, no linear constraints,
   and a pair of SOS constraints of type 1. */

#include "gurobi_c++.h"
using namespace std;

int
main(int   argc,
     char *argv[])
{
  GRBEnv *env = 0;
  GRBVar *x = 0;
  try {
    env = new GRBEnv();

    GRBModel model = GRBModel(*env);

    // Create variables

    double ub[]    = {1, 1, 2};
    double obj[]   = {-2, -1, -1};
    string names[] = {"x0", "x1", "x2"};

    x = model.addVars(NULL, ub, obj, NULL, names, 3);

    // Add first SOS1: x0=0 or x1=0

    GRBVar sosv1[]  = {x[0], x[1]};
    double soswt1[] = {1, 2};

    model.addSOS(sosv1, soswt1, 2, GRB_SOS_TYPE1);

    // Add second SOS1: x0=0 or x2=0 */

    GRBVar sosv2[]  = {x[0], x[2]};
    double soswt2[] = {1, 2};

    model.addSOS(sosv2, soswt2, 2, GRB_SOS_TYPE1);

    // Optimize model

    model.optimize();

    for (int i = 0; i < 3; i++)
      cout << x[i].get(GRB_StringAttr_VarName) << " "
           << x[i].get(GRB_DoubleAttr_X) << endl;

    cout << "Obj: " << model.get(GRB_DoubleAttr_ObjVal) << endl;
```

(continues on next page)

(continued from previous page)

```
  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch(...) {
    cout << "Exception during optimization" << endl;
  }

  delete[] x;
  delete env;
  return 0;
}
```

sudoku_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */
/*
  Sudoku example.

  The Sudoku board is a 9x9 grid, which is further divided into a 3x3 grid
  of 3x3 grids.  Each cell in the grid must take a value from 0 to 9.
  No two grid cells in the same row, column, or 3x3 subgrid may take the
  same value.

  In the MIP formulation, binary variables x[i,j,v] indicate whether
  cell <i,j> takes value 'v'.  The constraints are as follows:
    1. Each cell must take exactly one value (sum_v x[i,j,v] = 1)
    2. Each value is used exactly once per row (sum_i x[i,j,v] = 1)
    3. Each value is used exactly once per column (sum_j x[i,j,v] = 1)
    4. Each value is used exactly once per 3x3 subgrid (sum_grid x[i,j,v] = 1)

  Input datasets for this example can be found in examples/data/sudoku*.
*/

#include "gurobi_c++.h"
#include <sstream>
using namespace std;

#define sd 3
#define n (sd*sd)

string itos(int i) {stringstream s; s << i; return s.str(); }

int
main(int   argc,
     char *argv[])
{
  try {
    GRBEnv env = GRBEnv();
    GRBModel model = GRBModel(env);
```

(continues on next page)

(continued from previous page)

```
GRBVar vars[n][n][n];
int i, j, v;

// Create 3-D array of model variables

for (i = 0; i < n; i++) {
  for (j = 0; j < n; j++) {
    for (v = 0; v < n; v++) {
      string s = "G_" + itos(i) + "_" + itos(j) + "_" + itos(v);
      vars[i][j][v] = model.addVar(0.0, 1.0, 0.0, GRB_BINARY, s);
    }
  }
}

// Add constraints

// Each cell must take one value

for (i = 0; i < n; i++) {
  for (j = 0; j < n; j++) {
    GRBLinExpr expr = 0;
    for (v = 0; v < n; v++)
      expr += vars[i][j][v];
    string s = "V_" + itos(i) + "_" + itos(j);
    model.addConstr(expr, GRB_EQUAL, 1.0, s);
  }
}

// Each value appears once per row

for (i = 0; i < n; i++) {
  for (v = 0; v < n; v++) {
    GRBLinExpr expr = 0;
    for (j = 0; j < n; j++)
      expr += vars[i][j][v];
    string s = "R_" + itos(i) + "_" + itos(v);
    model.addConstr(expr == 1.0, s);
  }
}

// Each value appears once per column

for (j = 0; j < n; j++) {
  for (v = 0; v < n; v++) {
    GRBLinExpr expr = 0;
    for (i = 0; i < n; i++)
      expr += vars[i][j][v];
    string s = "C_" + itos(j) + "_" + itos(v);
    model.addConstr(expr == 1.0, s);
  }
}
```

(continues on next page)

(continued from previous page)

```
  // Each value appears once per sub-grid

  for (v = 0; v < n; v++) {
    for (int i0 = 0; i0 < sd; i0++) {
      for (int j0 = 0; j0 < sd; j0++) {
        GRBLinExpr expr = 0;
        for (int i1 = 0; i1 < sd; i1++) {
          for (int j1 = 0; j1 < sd; j1++) {
            expr += vars[i0*sd+i1][j0*sd+j1][v];
          }
        }

        string s = "Sub_" + itos(v) + "_" + itos(i0) + "_" + itos(j0);
        model.addConstr(expr == 1.0, s);
      }
    }
  }

  // Fix variables associated with pre-specified cells

  char input[10];
  for (i = 0; i < n; i++) {
    cin >> input;
    for (j = 0; j < n; j++) {
      int val = (int) input[j] - 48 - 1; // 0-based

      if (val >= 0)
        vars[i][j][val].set(GRB_DoubleAttr_LB, 1.0);
    }
  }

  // Optimize model

  model.optimize();

  // Write model to file

  model.write("sudoku.lp");

  cout << endl;
  for (i = 0; i < n; i++) {
    for (j = 0; j < n; j++) {
      for (v = 0; v < n; v++) {
        if (vars[i][j][v].get(GRB_DoubleAttr_X) > 0.5)
          cout << v+1;
      }
    }
    cout << endl;
  }
  cout << endl;
} catch(GRBException e) {
```

(continues on next page)

(continued from previous page)

```
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch (...) {
    cout << "Error during optimization" << endl;
  }

  return 0;
}
```

tsp_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Solve a traveling salesman problem on a randomly generated set of
   points using lazy constraints.   The base MIP model only includes
   'degree-2' constraints, requiring each node to have exactly
   two incident edges.  Solutions to this model may contain subtours -
   tours that don't visit every node.  The lazy constraint callback
   adds new constraints to cut them off. */

#include "gurobi_c++.h"
#include <cassert>
#include <cstdlib>
#include <cmath>
#include <sstream>
using namespace std;

string itos(int i) {stringstream s; s << i; return s.str(); }
double distance(double* x, double* y, int i, int j);
void findsubtour(int n, double** sol, int* tourlenP, int* tour);

// Subtour elimination callback.  Whenever a feasible solution is found,
// find the smallest subtour, and add a subtour elimination constraint
// if the tour doesn't visit every node.

class subtourelim: public GRBCallback
{
  public:
    GRBVar** vars;
    int n;
    subtourelim(GRBVar** xvars, int xn) {
      vars = xvars;
      n    = xn;
    }
  protected:
    void callback() {
      try {
        if (where == GRB_CB_MIPSOL) {
          // Found an integer feasible solution - does it visit every node?
          double **x = new double*[n];
```

(continues on next page)

(continued from previous page)

```
          int *tour = new int[n];
          int i, j, len;
          for (i = 0; i < n; i++)
            x[i] = getSolution(vars[i], n);

          findsubtour(n, x, &len, tour);

          if (len < n) {
            // Add subtour elimination constraint
            GRBLinExpr expr = 0;
            for (i = 0; i < len; i++)
              for (j = i+1; j < len; j++)
                expr += vars[tour[i]][tour[j]];
            addLazy(expr <= len-1);
          }

          for (i = 0; i < n; i++)
            delete[] x[i];
          delete[] x;
          delete[] tour;
        }
      } catch (GRBException e) {
        cout << "Error number: " << e.getErrorCode() << endl;
        cout << e.getMessage() << endl;
      } catch (...) {
        cout << "Error during callback" << endl;
      }
    }
};

// Given an integer-feasible solution 'sol', find the smallest
// sub-tour.  Result is returned in 'tour', and length is
// returned in 'tourlenP'.

void
findsubtour(int      n,
            double** sol,
            int*     tourlenP,
            int*     tour)
{
  bool* seen = new bool[n];
  int bestind, bestlen;
  int i, node, len, start;

  for (i = 0; i < n; i++)
    seen[i] = false;

  start = 0;
  bestlen = n+1;
  bestind = -1;
  node = 0;
  while (start < n) {
```

(continues on next page)

(continued from previous page)

```
    for (node = 0; node < n; node++)
      if (!seen[node])
        break;
    if (node == n)
      break;
    for (len = 0; len < n; len++) {
      tour[start+len] = node;
      seen[node] = true;
      for (i = 0; i < n; i++) {
        if (sol[node][i] > 0.5 && !seen[i]) {
          node = i;
          break;
        }
      }
      if (i == n) {
        len++;
        if (len < bestlen) {
          bestlen = len;
          bestind = start;
        }
        start += len;
        break;
      }
    }
  }

  for (i = 0; i < bestlen; i++)
    tour[i] = tour[bestind+i];
  *tourlenP = bestlen;

  delete[] seen;
}

// Euclidean distance between points 'i' and 'j'.

double
distance(double* x,
         double* y,
         int     i,
         int     j)
{
  double dx = x[i]-x[j];
  double dy = y[i]-y[j];

  return sqrt(dx*dx+dy*dy);
}

int
main(int   argc,
     char *argv[])
{
  if (argc < 2) {
```

(continues on next page)

(continued from previous page)

```
  cout << "Usage: tsp_c++ size" << endl;
  return 1;
}

int n = atoi(argv[1]);
double* x = new double[n];
double* y = new double[n];

int i;
for (i = 0; i < n; i++) {
  x[i] = ((double) rand())/RAND_MAX;
  y[i] = ((double) rand())/RAND_MAX;
}

GRBEnv *env = NULL;
GRBVar **vars = NULL;

vars = new GRBVar*[n];
for (i = 0; i < n; i++)
  vars[i] = new GRBVar[n];

try {
  int j;

  env = new GRBEnv();
  GRBModel model = GRBModel(*env);

  // Must set LazyConstraints parameter when using lazy constraints

  model.set(GRB_IntParam_LazyConstraints, 1);

  // Create binary decision variables

  for (i = 0; i < n; i++) {
    for (j = 0; j <= i; j++) {
      vars[i][j] = model.addVar(0.0, 1.0, distance(x, y, i, j),
                                GRB_BINARY, "x_"+itos(i)+"_"+itos(j));
      vars[j][i] = vars[i][j];
    }
  }

  // Degree-2 constraints

  for (i = 0; i < n; i++) {
    GRBLinExpr expr = 0;
    for (j = 0; j < n; j++)
      expr += vars[i][j];
    model.addConstr(expr == 2, "deg2_"+itos(i));
  }

  // Forbid edge from node back to itself
```

(continues on next page)

(continued from previous page)

```
    for (i = 0; i < n; i++)
      vars[i][i].set(GRB_DoubleAttr_UB, 0);

    // Set callback function

    subtourelim cb = subtourelim(vars, n);
    model.setCallback(&cb);

    // Optimize model

    model.optimize();

    // Extract solution

    if (model.get(GRB_IntAttr_SolCount) > 0) {
      double **sol = new double*[n];
      for (i = 0; i < n; i++)
        sol[i] = model.get(GRB_DoubleAttr_X, vars[i], n);

      int* tour = new int[n];
      int len;

      findsubtour(n, sol, &len, tour);
      assert(len == n);

      cout << "Tour: ";
      for (i = 0; i < len; i++)
        cout << tour[i] << " ";
      cout << endl;

      for (i = 0; i < n; i++)
        delete[] sol[i];
      delete[] sol;
      delete[] tour;
    }

  } catch (GRBException e) {
    cout << "Error number: " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch (...) {
    cout << "Error during optimization" << endl;
  }

  for (i = 0; i < n; i++)
    delete[] vars[i];
  delete[] vars;
  delete[] x;
  delete[] y;
  delete env;
  return 0;
}
```

tune_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a model from a file and tunes it.
   It then writes the best parameter settings to a file
   and solves the model using these parameters. */

#include "gurobi_c++.h"
#include <cmath>
using namespace std;

int
main(int   argc,
     char *argv[])
{
  if (argc < 2) {
    cout << "Usage: tune_c++ filename" << endl;
    return 1;
  }

  GRBEnv *env = 0;
  try {
    env = new GRBEnv();

    // Read model from file

    GRBModel model = GRBModel(*env, argv[1]);

    // Set a time limit for the model

    model.set(GRB_DoubleParam_TimeLimit, 5);

    // Set a time limit for the whole tuning run
    // Note that both time limits are chosen to have a quick demonstration.
    // In general, a total tune time limit should be set such that the
    // tuning tool can test several hundreds of parameter setting

    model.set(GRB_DoubleParam_TuneTimeLimit, 60);

    // Set the TuneResults parameter to 2
    //
    // The first parameter setting is the result for the first solved
    // setting. The second entry the parameter setting of the best
    // parameter setting.

    model.set(GRB_IntParam_TuneResults, 2);

    // Tune the model

    model.tune();

    // Get the number of tuning results
```

(continues on next page)

(continued from previous page)

```
    int resultcount = model.get(GRB_IntAttr_TuneResultCount);

    if (resultcount >= 2) {

      // Load the tuned parameters into the model's environment
      //
      // Note, the first parameter setting is associated to the first solved
      // setting and the second parameter setting to best tune result.

      model.getTuneResult(1);

      // Write tuned parameters to a file

      model.write("tune.prm");

      // Solve the model using the tuned parameters

      model.optimize();
    }
  } catch(GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  } catch (...) {
    cout << "Error during tuning" << endl;
  }

  delete env;
  return 0;
}
```

workforce1_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, use IIS to find a set of
   conflicting constraints. Note that there may be additional conflicts
   besides what is reported via IIS. */

#include "gurobi_c++.h"
#include <sstream>
using namespace std;

int
main(int argc,
     char *argv[])
{
  GRBEnv* env = 0;
  GRBConstr* c = 0;
```

(continues on next page)

(continued from previous page)

```
GRBVar** x = 0;
int xCt = 0;
try
{

  // Sample data
  const int nShifts = 14;
  const int nWorkers = 7;

  // Sets of days and workers
  string Shifts[] =
    { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
      "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
      "Sun14" };
  string Workers[] =
    { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

  // Number of workers required for each shift
  double shiftRequirements[] =
    { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

  // Amount each worker is paid to work one shift
  double pay[] = { 10, 12, 10, 8, 8, 9, 11 };

  // Worker availability: 0 if the worker is unavailable for a shift
  double availability[][nShifts] =
    { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
      { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
      { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
      { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
      { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
      { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
      { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

  // Model
  env = new GRBEnv();
  GRBModel model = GRBModel(*env);
  model.set(GRB_StringAttr_ModelName, "assignment");

  // Assignment variables: x[w][s] == 1 if worker w is assigned
  // to shift s. Since an assignment model always produces integer
  // solutions, we use continuous variables and solve as an LP.
  x = new GRBVar*[nWorkers];
  for (int w = 0; w < nWorkers; ++w)
  {
    x[w] = model.addVars(nShifts);
    xCt++;
    for (int s = 0; s < nShifts; ++s)
    {
      ostringstream vname;
      vname << Workers[w] << "." << Shifts[s];
      x[w][s].set(GRB_DoubleAttr_UB, availability[w][s]);
```

(continues on next page)

(continued from previous page)

```
      x[w][s].set(GRB_DoubleAttr_Obj, pay[w]);
      x[w][s].set(GRB_StringAttr_VarName, vname.str());
    }
  }

  // The objective is to minimize the total pay costs
  model.set(GRB_IntAttr_ModelSense, GRB_MINIMIZE);

  // Constraint: assign exactly shiftRequirements[s] workers
  // to each shift s
  for (int s = 0; s < nShifts; ++s)
  {
    GRBLinExpr lhs = 0;
    for (int w = 0; w < nWorkers; ++w)
    {
      lhs += x[w][s];
    }
    model.addConstr(lhs == shiftRequirements[s], Shifts[s]);
  }

  // Optimize
  model.optimize();
  int status = model.get(GRB_IntAttr_Status);
  if (status == GRB_UNBOUNDED)
  {
    cout << "The model cannot be solved "
    << "because it is unbounded" << endl;
    return 1;
  }
  if (status == GRB_OPTIMAL)
  {
    cout << "The optimal objective is " <<
    model.get(GRB_DoubleAttr_ObjVal) << endl;
    return 0;
  }
  if ((status != GRB_INF_OR_UNBD) && (status != GRB_INFEASIBLE))
  {
    cout << "Optimization was stopped with status " << status << endl;
    return 1;
  }

  // do IIS
  cout << "The model is infeasible; computing IIS" << endl;
  model.computeIIS();
  cout << "\nThe following constraint(s) "
  << "cannot be satisfied:" << endl;
  c = model.getConstrs();
  for (int i = 0; i < model.get(GRB_IntAttr_NumConstrs); ++i)
  {
    if (c[i].get(GRB_IntAttr_IISConstr) == 1)
    {
      cout << c[i].get(GRB_StringAttr_ConstrName) << endl;
```

(continues on next page)

(continued from previous page)

```
      }
    }

  }
  catch (GRBException e)
  {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...)
  {
    cout << "Exception during optimization" << endl;
  }

  delete[] c;
  for (int i = 0; i < xCt; ++i) {
    delete[] x[i];
  }
  delete[] x;
  delete env;
  return 0;
}
```

workforce2_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, use IIS iteratively to
   find all conflicting constraints. */

#include "gurobi_c++.h"
#include <sstream>
#include <deque>
using namespace std;

int
main(int argc,
     char *argv[])
{
  GRBEnv* env = 0;
  GRBConstr* c = 0;
  GRBVar** x = 0;
  int xCt = 0;
  try
  {

    // Sample data
    const int nShifts = 14;
    const int nWorkers = 7;
```

(continues on next page)

(continued from previous page)

```
// Sets of days and workers
string Shifts[] =
  { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
    "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
    "Sun14" };
string Workers[] =
  { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

// Number of workers required for each shift
double shiftRequirements[] =
  { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

// Amount each worker is paid to work one shift
double pay[] = { 10, 12, 10, 8, 8, 9, 11 };

// Worker availability: 0 if the worker is unavailable for a shift
double availability[][nShifts] =
  { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
    { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
    { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
    { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
    { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

// Model
env = new GRBEnv();
GRBModel model = GRBModel(*env);
model.set(GRB_StringAttr_ModelName, "assignment");

// Assignment variables: x[w][s] == 1 if worker w is assigned
// to shift s. Since an assignment model always produces integer
// solutions, we use continuous variables and solve as an LP.
x = new GRBVar*[nWorkers];
for (int w = 0; w < nWorkers; ++w)
{
  x[w] = model.addVars(nShifts);
  xCt++;
  for (int s = 0; s < nShifts; ++s)
  {
    ostringstream vname;
    vname << Workers[w] << "." << Shifts[s];
    x[w][s].set(GRB_DoubleAttr_UB, availability[w][s]);
    x[w][s].set(GRB_DoubleAttr_Obj, pay[w]);
    x[w][s].set(GRB_StringAttr_VarName, vname.str());
  }
}

// The objective is to minimize the total pay costs
model.set(GRB_IntAttr_ModelSense, GRB_MINIMIZE);
```

(continues on next page)

(continued from previous page)

```
  // Constraint: assign exactly shiftRequirements[s] workers
  // to each shift s
  for (int s = 0; s < nShifts; ++s)
  {
    GRBLinExpr lhs = 0;
    for (int w = 0; w < nWorkers; ++w)
    {
      lhs += x[w][s];
    }
    model.addConstr(lhs == shiftRequirements[s], Shifts[s]);
  }

  // Optimize
  model.optimize();
  int status = model.get(GRB_IntAttr_Status);
  if (status == GRB_UNBOUNDED)
  {
    cout << "The model cannot be solved "
    << "because it is unbounded" << endl;
    return 1;
  }
  if (status == GRB_OPTIMAL)
  {
    cout << "The optimal objective is " <<
    model.get(GRB_DoubleAttr_ObjVal) << endl;
    return 0;
  }
  if ((status != GRB_INF_OR_UNBD) && (status != GRB_INFEASIBLE))
  {
    cout << "Optimization was stopped with status " << status << endl;
    return 1;
  }

  // do IIS
  cout << "The model is infeasible; computing IIS" << endl;
  deque<string> removed;

  // Loop until we reduce to a model that can be solved
  while (1)
  {
    model.computeIIS();
    cout << "\nThe following constraint cannot be satisfied:" << endl;
    c = model.getConstrs();
    for (int i = 0; i < model.get(GRB_IntAttr_NumConstrs); ++i)
    {
      if (c[i].get(GRB_IntAttr_IISConstr) == 1)
      {
        cout << c[i].get(GRB_StringAttr_ConstrName) << endl;
        // Remove a single constraint from the model
        removed.push_back(c[i].get(GRB_StringAttr_ConstrName));
        model.remove(c[i]);
        break;
```

(continues on next page)

(continued from previous page)

```
      }
    }
    delete[] c;
    c = 0;

    cout << endl;
    model.optimize();
    status = model.get(GRB_IntAttr_Status);

    if (status == GRB_UNBOUNDED)
    {
      cout << "The model cannot be solved because it is unbounded" << endl;
      return 0;
    }
    if (status == GRB_OPTIMAL)
    {
      break;
    }
    if ((status != GRB_INF_OR_UNBD) && (status != GRB_INFEASIBLE))
    {
      cout << "Optimization was stopped with status " << status << endl;
      return 1;
    }
  }
  cout << "\nThe following constraints were removed "
  << "to get a feasible LP:" << endl;

  for (deque<string>::iterator r = removed.begin();
       r != removed.end();
       ++r)
  {
    cout << *r << " ";
  }
  cout << endl;

}
catch (GRBException e)
{
  cout << "Error code = " << e.getErrorCode() << endl;
  cout << e.getMessage() << endl;
}
catch (...)
{
  cout << "Exception during optimization" << endl;
}

delete[] c;
for (int i = 0; i < xCt; ++i) {
  delete[] x[i];
}
delete[] x;
delete env;
```

(continues on next page)

(continued from previous page)

```
  return 0;
}
```

workforce3_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, relax the model
   to determine which constraints cannot be satisfied, and how much
   they need to be relaxed. */

#include "gurobi_c++.h"
#include <sstream>
using namespace std;

int
main(int argc,
     char *argv[])
{
  GRBEnv* env = 0;
  GRBConstr* c = 0;
  GRBVar** x = 0;
  GRBVar* vars = 0;
  int xCt = 0;
  try
  {

    // Sample data
    const int nShifts = 14;
    const int nWorkers = 7;

    // Sets of days and workers
    string Shifts[] =
      { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
        "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
        "Sun14" };
    string Workers[] =
      { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

    // Number of workers required for each shift
    double shiftRequirements[] =
      { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

    // Amount each worker is paid to work one shift
    double pay[] = { 10, 12, 10, 8, 8, 9, 11 };

    // Worker availability: 0 if the worker is unavailable for a shift
    double availability[][nShifts] =
      { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
```

(continues on next page)

(continued from previous page)

```
      { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
      { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
      { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
      { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
      { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
      { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

  // Model
  env = new GRBEnv();
  GRBModel model = GRBModel(*env);
  model.set(GRB_StringAttr_ModelName, "assignment");

  // Assignment variables: x[w][s] == 1 if worker w is assigned
  // to shift s. Since an assignment model always produces integer
  // solutions, we use continuous variables and solve as an LP.
  x = new GRBVar*[nWorkers];
  for (int w = 0; w < nWorkers; ++w)
  {
    x[w] = model.addVars(nShifts);
    xCt++;
    for (int s = 0; s < nShifts; ++s)
    {
      ostringstream vname;
      vname << Workers[w] << "." << Shifts[s];
      x[w][s].set(GRB_DoubleAttr_UB, availability[w][s]);
      x[w][s].set(GRB_DoubleAttr_Obj, pay[w]);
      x[w][s].set(GRB_StringAttr_VarName, vname.str());
    }
  }

  // The objective is to minimize the total pay costs
  model.set(GRB_IntAttr_ModelSense, GRB_MINIMIZE);

  // Constraint: assign exactly shiftRequirements[s] workers
  // to each shift s
  for (int s = 0; s < nShifts; ++s)
  {
    GRBLinExpr lhs = 0;
    for (int w = 0; w < nWorkers; ++w)
    {
      lhs += x[w][s];
    }
    model.addConstr(lhs == shiftRequirements[s], Shifts[s]);
  }

  // Optimize
  model.optimize();
  int status = model.get(GRB_IntAttr_Status);
  if (status == GRB_UNBOUNDED)
  {
    cout << "The model cannot be solved "
    << "because it is unbounded" << endl;
```

(continues on next page)

(continued from previous page)

```
    return 1;
  }
  if (status == GRB_OPTIMAL)
  {
    cout << "The optimal objective is " <<
    model.get(GRB_DoubleAttr_ObjVal) << endl;
    return 0;
  }
  if ((status != GRB_INF_OR_UNBD) && (status != GRB_INFEASIBLE))
  {
    cout << "Optimization was stopped with status " << status << endl;
    return 1;
  }

  // Relax the constraints to make the model feasible
  cout << "The model is infeasible; relaxing the constraints" << endl;
  int orignumvars = model.get(GRB_IntAttr_NumVars);
  model.feasRelax(0, false, false, true);
  model.optimize();
  status = model.get(GRB_IntAttr_Status);
  if ((status == GRB_INF_OR_UNBD) || (status == GRB_INFEASIBLE) ||
      (status == GRB_UNBOUNDED))
  {
    cout << "The relaxed model cannot be solved " <<
    "because it is infeasible or unbounded" << endl;
    return 1;
  }
  if (status != GRB_OPTIMAL)
  {
    cout << "Optimization was stopped with status " << status << endl;
    return 1;
  }

  cout << "\nSlack values:" << endl;
  vars = model.getVars();
  for (int i = orignumvars; i < model.get(GRB_IntAttr_NumVars); ++i)
  {
    GRBVar sv = vars[i];
    if (sv.get(GRB_DoubleAttr_X) > 1e-6)
    {
      cout << sv.get(GRB_StringAttr_VarName) << " = " <<
      sv.get(GRB_DoubleAttr_X) << endl;
    }
  }

}
catch (GRBException e)
{
  cout << "Error code = " << e.getErrorCode() << endl;
  cout << e.getMessage() << endl;
}
catch (...)
```

(continues on next page)

(continued from previous page)

```
  {
    cout << "Exception during optimization" << endl;
  }

  delete[] c;
  for (int i = 0; i < xCt; ++i) {
    delete[] x[i];
  }
  delete[] x;
  delete[] vars;
  delete env;
  return 0;
}
```

workforce4_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
 * particular day. We use Pareto optimization to solve the model:
 * first, we minimize the linear sum of the slacks. Then, we constrain
 * the sum of the slacks, and we minimize a quadratic objective that
 * tries to balance the workload among the workers. */

#include "gurobi_c++.h"
#include <sstream>
using namespace std;

int solveAndPrint(GRBModel& model, GRBVar& totSlack,
                  int nWorkers, string* Workers,
                  GRBVar* totShifts);

int
main(int   argc,
     char *argv[])
{
  GRBEnv* env = 0;
  GRBVar** x = 0;
  GRBVar* slacks = 0;
  GRBVar* totShifts = 0;
  GRBVar* diffShifts = 0;
  int xCt = 0;

  try
  {
    // Sample data
    const int nShifts = 14;
    const int nWorkers = 7;

    // Sets of days and workers
```

(continues on next page)

(continued from previous page)

```
string Shifts[] =
  { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
    "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
    "Sun14" };
string Workers[] =
  { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

// Number of workers required for each shift
double shiftRequirements[] =
  { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

// Worker availability: 0 if the worker is unavailable for a shift
double availability[][nShifts] =
  { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
    { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
    { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
    { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
    { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

// Model
env = new GRBEnv();
GRBModel model = GRBModel(*env);
model.set(GRB_StringAttr_ModelName, "assignment");

// Assignment variables: x[w][s] == 1 if worker w is assigned
// to shift s. This is no longer a pure assignment model, so we must
// use binary variables.
x = new GRBVar*[nWorkers];
int s, w;

for (w = 0; w < nWorkers; ++w) {
  x[w] = model.addVars(nShifts);
  xCt++;

  for (s = 0; s < nShifts; ++s) {
    ostringstream vname;

    vname << Workers[w] << "." << Shifts[s];
    x[w][s].set(GRB_DoubleAttr_UB, availability[w][s]);
    x[w][s].set(GRB_CharAttr_VType, GRB_BINARY);
    x[w][s].set(GRB_StringAttr_VarName, vname.str());
  }
}

// Slack variables for each shift constraint so that the shifts can
// be satisfied
slacks = model.addVars(nShifts);
for (s = 0; s < nShifts; ++s) {
  ostringstream vname;
```

(continues on next page)

(continued from previous page)

```
    vname << Shifts[s] << "Slack";
    slacks[s].set(GRB_StringAttr_VarName, vname.str());
  }

  // Variable to represent the total slack
  GRBVar totSlack = model.addVar(0, GRB_INFINITY, 0, GRB_CONTINUOUS,
                                 "totSlack");

  // Variables to count the total shifts worked by each worker
  totShifts = model.addVars(nWorkers);
  for (w = 0; w < nWorkers; ++w) {
    ostringstream vname;

    vname << Workers[w] << "TotShifts";
    totShifts[w].set(GRB_StringAttr_VarName, vname.str());
  }

  GRBLinExpr lhs;

  // Constraint: assign exactly shiftRequirements[s] workers
  // to each shift s
  for (s = 0; s < nShifts; ++s) {
    lhs = 0;
    lhs += slacks[s];

    for (w = 0; w < nWorkers; ++w) {
      lhs += x[w][s];
    }

    model.addConstr(lhs == shiftRequirements[s], Shifts[s]);
  }

  // Constraint: set totSlack equal to the total slack
  lhs = 0;
  for (s = 0; s < nShifts; ++s)
  {
    lhs += slacks[s];
  }
  model.addConstr(lhs == totSlack, "totSlack");

  // Constraint: compute the total number of shifts for each worker
  for (w = 0; w < nWorkers; ++w) {
    lhs = 0;
    for (s = 0; s < nShifts; ++s) {
      lhs += x[w][s];
    }
    ostringstream vname;
    vname << "totShifts" << Workers[w];
    model.addConstr(lhs == totShifts[w], vname.str());
  }

  // Objective: minimize the total slack
```

(continues on next page)

(continued from previous page)

```
GRBLinExpr obj = 0;
obj += totSlack;
model.setObjective(obj);

// Optimize
int status = solveAndPrint(model, totSlack, nWorkers, Workers, totShifts);
if (status != GRB_OPTIMAL)
  return 1;

// Constrain the slack by setting its upper and lower bounds
totSlack.set(GRB_DoubleAttr_UB, totSlack.get(GRB_DoubleAttr_X));
totSlack.set(GRB_DoubleAttr_LB, totSlack.get(GRB_DoubleAttr_X));

// Variable to count the average number of shifts worked
GRBVar avgShifts =
  model.addVar(0, GRB_INFINITY, 0, GRB_CONTINUOUS, "avgShifts");

// Variables to count the difference from average for each worker;
// note that these variables can take negative values.
diffShifts = model.addVars(nWorkers);
for (w = 0; w < nWorkers; ++w) {
  ostringstream vname;
  vname << Workers[w] << "Diff";
  diffShifts[w].set(GRB_StringAttr_VarName, vname.str());
  diffShifts[w].set(GRB_DoubleAttr_LB, -GRB_INFINITY);
}

// Constraint: compute the average number of shifts worked
lhs = 0;
for (w = 0; w < nWorkers; ++w) {
  lhs += totShifts[w];
}
model.addConstr(lhs == nWorkers * avgShifts, "avgShifts");

// Constraint: compute the difference from the average number of shifts
for (w = 0; w < nWorkers; ++w) {
  lhs = 0;
  lhs += totShifts[w];
  lhs -= avgShifts;
  ostringstream vname;
  vname << Workers[w] << "Diff";
  model.addConstr(lhs == diffShifts[w], vname.str());
}

// Objective: minimize the sum of the square of the difference from the
// average number of shifts worked
GRBQuadExpr qobj;
for (w = 0; w < nWorkers; ++w) {
  qobj += diffShifts[w] * diffShifts[w];
}
model.setObjective(qobj);
```

(continues on next page)

(continued from previous page)

```
    // Optimize
    status = solveAndPrint(model, totSlack, nWorkers, Workers, totShifts);
    if (status != GRB_OPTIMAL)
      return 1;
  }
  catch (GRBException e) {
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...) {
    cout << "Exception during optimization" << endl;
  }

  for (int i = 0; i < xCt; ++i) {
    delete[] x[i];
  }
  delete[] x;
  delete[] slacks;
  delete[] totShifts;
  delete[] diffShifts;
  delete env;

  return 0;
}

int solveAndPrint(GRBModel& model,
                  GRBVar&   totSlack,
                  int       nWorkers,
                  string*   Workers,
                  GRBVar*   totShifts)
{
  model.optimize();
  int status = model.get(GRB_IntAttr_Status);

  if ((status == GRB_INF_OR_UNBD) ||
      (status == GRB_INFEASIBLE)  ||
      (status == GRB_UNBOUNDED)     ) {
    cout << "The model cannot be solved " <<
    "because it is infeasible or unbounded" << endl;
    return status;
  }
  if (status != GRB_OPTIMAL) {
    cout << "Optimization was stopped with status " << status << endl;
    return status;
  }

  // Print total slack and the number of shifts worked for each worker
  cout << endl << "Total slack required: " <<
    totSlack.get(GRB_DoubleAttr_X) << endl;
  for (int w = 0; w < nWorkers; ++w) {
    cout << Workers[w] << " worked " <<
    totShifts[w].get(GRB_DoubleAttr_X) << " shifts" << endl;
```

(continues on next page)

(continued from previous page)

```
  }
  cout << endl;

  return status;
}
```

workforce5_c++.cpp

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. We use multi-objective optimization to solve the model.
   The highest-priority objective minimizes the sum of the slacks
   (i.e., the total number of uncovered shifts). The secondary objective
   minimizes the difference between the maximum and minimum number of
   shifts worked among all workers.  The second optimization is allowed
   to degrade the first objective by up to the smaller value of 10% and 2 */

#include "gurobi_c++.h"
#include <sstream>
using namespace std;

int solveAndPrint(GRBModel& model, GRBVar& totSlack,
                  int nWorkers, string* Workers,
                  GRBVar* totShifts);

int
main(int   argc,
     char *argv[])
{
  GRBEnv  *env       = 0;
  GRBVar **x         = 0;
  GRBVar  *slacks    = 0;
  GRBVar  *totShifts = 0;
  int      xCt       = 0;
  int      s, w;

  try {
    // Sample data
    const int nShifts = 14;
    const int nWorkers = 8;

    // Sets of days and workers
    string Shifts[] =
    { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
      "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
      "Sun14" };
    string Workers[] =
    { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu", "Tobi" };
```

(continues on next page)

(continued from previous page)

```
  // Number of workers required for each shift
  double shiftRequirements[] =
  { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

  // Worker availability: 0 if the worker is unavailable for a shift
  double availability[][14] =
  { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
    { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
    { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
    { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
    { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
    { 0, 1, 1, 1, 0, 1, 1, 0, 1, 1, 1, 0, 1, 1 },
    { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

  // Create environment
  env = new GRBEnv("workforce5_c++.log");

  // Create initial model
  GRBModel model = GRBModel(*env);
  model.set(GRB_StringAttr_ModelName, "workforce5_c++");

  // Initialize assignment decision variables:
  //  x[w][s] == 1 if worker w is assigned to shift s.
  // This is no longer a pure assignment model, so we must
  // use binary variables.
  x = new GRBVar*[nWorkers];
  for (w = 0; w < nWorkers; w++) {
    x[w] = model.addVars(nShifts, GRB_BINARY);
    xCt++;
    for (s = 0; s < nShifts; s++) {
      ostringstream vname;

      vname << Workers[w] << "." << Shifts[s];
      x[w][s].set(GRB_DoubleAttr_UB, availability[w][s]);
      x[w][s].set(GRB_StringAttr_VarName, vname.str());
    }
  }

  // Initialize slack decision variables
  slacks = model.addVars(nShifts);
  for (s = 0; s < nShifts; s++) {
    ostringstream vname;

    vname << Shifts[s] << "Slack";
    slacks[s].set(GRB_StringAttr_VarName, vname.str());
  }

  // Variable to represent the total slack
  GRBVar totSlack = model.addVar(0, GRB_INFINITY, 0, GRB_CONTINUOUS,
                                 "totSlack");
```

(continues on next page)

(continued from previous page)

```
  // Initialize variables to count the total shifts worked by each worker
  totShifts = model.addVars(nWorkers);
  for (w = 0; w < nWorkers; w++) {
    ostringstream vname;

    vname << Workers[w] << "TotShifts";
    totShifts[w].set(GRB_StringAttr_VarName, vname.str());
  }

  GRBLinExpr lhs;

  // Constraint: assign exactly shiftRequirements[s] workers
  // to each shift s, plus the slack
  for (s = 0; s < nShifts; s++) {
    lhs = 0;
    lhs += slacks[s];
    for (w = 0; w < nWorkers; w++) {
      lhs += x[w][s];
    }
    model.addConstr(lhs == shiftRequirements[s], Shifts[s]);
  }

  // Constraint: set totSlack column equal to the total slack
  lhs = 0;
  for (s = 0; s < nShifts; s++) {
    lhs += slacks[s];
  }
  model.addConstr(lhs == totSlack, "totSlack");

  // Constraint: compute the total number of shifts for each worker
  for (w = 0; w < nWorkers; w++) {
    lhs = 0;

    for (s = 0; s < nShifts; s++) {
      lhs += x[w][s];
    }

    ostringstream vname;
    vname << "totShifts" << Workers[w];
    model.addConstr(lhs == totShifts[w], vname.str());
  }

  // Constraint: set minShift/maxShift variable to less <=/>= to the
  // number of shifts among all workers
  GRBVar minShift = model.addVar(0, GRB_INFINITY, 0, GRB_CONTINUOUS,
                                 "minShift");
  GRBVar maxShift = model.addVar(0, GRB_INFINITY, 0, GRB_CONTINUOUS,
                                 "maxShift");
  model.addGenConstrMin(minShift, totShifts, nWorkers, GRB_INFINITY, "minShift");
  model.addGenConstrMax(maxShift, totShifts, nWorkers, -GRB_INFINITY, "maxShift");

  // Set global sense for ALL objectives
```

(continues on next page)

(continued from previous page)

```
    model.set(GRB_IntAttr_ModelSense, GRB_MINIMIZE);

    // Set primary objective
    model.setObjectiveN(totSlack, 0, 2, 1.0, 2.0, 0.1, "TotalSlack");

    // Set secondary objective
    model.setObjectiveN(maxShift - minShift, 1, 1, 1.0, 0, 0, "Fairness");

    // Save problem
    model.write("workforce5_c++.lp");

    // Optimize
    int status = solveAndPrint(model, totSlack, nWorkers, Workers, totShifts);

    // Delete local variables
    if (status != GRB_OPTIMAL)
      return 1;
  }
  catch (GRBException e){
    cout << "Error code = " << e.getErrorCode() << endl;
    cout << e.getMessage() << endl;
  }
  catch (...) {
    cout << "Exception during optimization" << endl;
  }

  for (s = 0; s < xCt; s++)
    delete[] x[s];
  delete[] x;
  delete[] slacks;
  delete[] totShifts;
  delete env;
  return 0;
}

int solveAndPrint(GRBModel& model,
                  GRBVar&   totSlack,
                  int       nWorkers,
                  string*   Workers,
                  GRBVar*   totShifts)
{
  model.optimize();
  int status = model.get(GRB_IntAttr_Status);

  if ((status == GRB_INF_OR_UNBD) ||
      (status == GRB_INFEASIBLE)  ||
      (status == GRB_UNBOUNDED)     ) {
    cout << "The model cannot be solved " <<
    "because it is infeasible or unbounded" << endl;
    return status;
  }
  if (status != GRB_OPTIMAL) {
```

(continues on next page)

(continued from previous page)

```
    cout << "Optimization was stopped with status " << status << endl;
    return status;
  }

  // Print total slack and the number of shifts worked for each worker
  cout << endl << "Total slack required: " <<
    totSlack.get(GRB_DoubleAttr_X) << endl;
  for (int w = 0; w < nWorkers; ++w) {
    cout << Workers[w] << " worked " <<
    totShifts[w].get(GRB_DoubleAttr_X) << " shifts" << endl;
  }
  cout << endl;

  return status;
}
```

2.1.3 C# Examples

This section includes source code for all of the Gurobi C# examples. The same source code can be found in the `examples/c#` directory of the Gurobi distribution.

batchmode_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, solves it in batch mode,
   and prints the JSON solution string.

   You will need a Compute Server license for this example to work. */

using System;
using Gurobi;

class batchmode_cs
{
  /// <summary>Set-up the environment for batch mode optimization.
  /// </summary>
  /// <remarks>
  /// The function creates an empty environment, sets all neccessary
  /// parameters, and returns the ready-to-be-started Env object to
  /// caller.
  /// </remarks>
  static void setupbatchenv(ref GRBEnv env)
  {
    env.CSBatchMode    = 1;
    env.CSManager      = "http://localhost:61080";
    env.LogFile        = "batchmode.log";
    env.ServerPassword = "pass";
    env.UserName       = "gurobi";
```

(continues on next page)

(continued from previous page)

```
  // No network communication happened up to this point. This will happen
  // now that we call start().
  env.Start();
}

///<summary>Print batch job error information, if any</summary>
static void printbatcherrorinfo(ref GRBBatch batch)
{
  if (batch.BatchErrorCode == 0)
    return;
  Console.WriteLine("Batch ID: " + batch.BatchID + ", Error code: " +
                    batch.BatchErrorCode + "(" +
                    batch.BatchErrorMessage + ")");
}

///<summary>Create a batch request for given problem file</summary>
static string newbatchrequest(string filename)
{
  string batchID= "";
  // Create an empty environment
  GRBEnv env = new GRBEnv(true);

  // set environment and build model
  setupbatchenv(ref env);
  GRBModel model = new GRBModel(env, filename);

  try {

    // Set some parameters
    model.Set(GRB.DoubleParam.MIPGap, 0.01);
    model.Set(GRB.IntParam.JSONSolDetail, 1);

    // Define tags for some variables to access their values later
    int count = 0;
    foreach (GRBVar v in model.GetVars()) {
      v.VTag = "Variable" + count;
      count += 1;
      if (count >= 10) break;
    }

    // Submit batch request
    batchID = model.OptimizeBatch();

  } finally {
    // Dispose of model and env
    model.Dispose();
    env.Dispose();
  }
  return batchID;
}

///<summary>Wait for the final status of the batch. Initially the
```

(continues on next page)

(continued from previous page)

```
/// status of a batch is <see cref="GRB.BatchStatus.SUBMITTED"/>;
/// the status will change once the batch has been processed
/// (by a compute server).</summary>
static void waitforfinalstatus(string batchID)
{
  // Wait no longer than one hour
  double maxwaittime = 3600;
  DateTime start = DateTime.Now;

  // Setup and start environment, create local Batch handle object
  GRBEnv env = new GRBEnv(true);
  setupbatchenv(ref env);
  GRBBatch batch = new GRBBatch(env, batchID);
  try {

    while (batch.BatchStatus == GRB.BatchStatus.SUBMITTED) {
      // Abort this batch if it is taking too long
      TimeSpan interval = DateTime.Now - start;
      if (interval.TotalSeconds > maxwaittime) {
        batch.Abort();
        break;
      }
      // Wait for two seconds
      System.Threading.Thread.Sleep(2000);

      // Update the resident attribute cache of the Batch object
      // with the latest values from the cluster manager.
      batch.Update();

      // If the batch failed, we retry it
      if (batch.BatchStatus == GRB.BatchStatus.FAILED) {
        batch.Retry();
        System.Threading.Thread.Sleep(2000);
        batch.Update();
      }
    }
  } finally {
    // Print information about error status of the job
    // that processed the batch
    printbatcherrorinfo(ref batch);
    batch.Dispose();
    env.Dispose();
  }
}

///<summary>Final Report for Batch Request</summary>
static void printfinalreport(string batchID)
{
  // Setup and start environment, create local Batch handle object
  GRBEnv env = new GRBEnv(true);
  setupbatchenv(ref env);
  GRBBatch batch = new GRBBatch(env, batchID);
```

(continues on next page)

(continued from previous page)

```
  switch(batch.BatchStatus) {
    case GRB.BatchStatus.CREATED:
      Console.WriteLine("Batch status is 'CREATED'\n");
      break;
    case GRB.BatchStatus.SUBMITTED:
      Console.WriteLine("Batch is 'SUBMITTED\n");
      break;
    case GRB.BatchStatus.ABORTED:
      Console.WriteLine("Batch is 'ABORTED'\n");
      break;
    case GRB.BatchStatus.FAILED:
      Console.WriteLine("Batch is 'FAILED'\n");
      break;
    case GRB.BatchStatus.COMPLETED:
      Console.WriteLine("Batch is 'COMPLETED'\n");
      // Get JSON solution as string
      Console.WriteLine("JSON solution:" + batch.GetJSONSolution());

      // Write the full JSON solution string to a file
      batch.WriteJSONSolution("batch-sol.json.gz");
      break;
    default:
      // Should not happen
      Console.WriteLine("Unknown BatchStatus" + batch.BatchStatus);
      Environment.Exit(1);
      break;
  }
  // Cleanup
  batch.Dispose();
  env.Dispose();
}

///<summary>Instruct the cluster manager to discard all data relating
/// to this BatchID</summary>
static void batchdiscard(string batchID)
{
  // Setup and start environment, create local Batch handle object
  GRBEnv env = new GRBEnv(true);
  setupbatchenv(ref env);
  GRBBatch batch = new GRBBatch(env, batchID);

  // Remove batch request from manager
  batch.Discard();

  // Cleanup
  batch.Dispose();
  env.Dispose();
}

///<summary>Solve a given model using batch optimization</summary>
static void Main(string[] args)
```

(continues on next page)

(continued from previous page)

```
  {
    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: batchmode_cs filename");
      return;
    }

    try {
      // Submit new batch request
      string batchID = newbatchrequest(args[0]);

      // Wait for final status
      waitforfinalstatus(batchID);

      // Report final status info
      printfinalreport(batchID);

      // Remove batch request from manager
      batchdiscard(batchID);

      Console.WriteLine("Batch optimization OK");
    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " +
          e.Message);
    }
  }
}
```

bilinear_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple bilinear model:

     maximize    x
     subject to  x + y + z <= 10
                 x * y <= 2          (bilinear inequality)
                 x * z + y * z == 1  (bilinear equality)
                 x, y, z non-negative (x integral in second version)
*/

using System;
using Gurobi;

class bilinear_cs
{
  static void Main()
  {
    try {
      GRBEnv    env   = new GRBEnv("bilinear.log");
      GRBModel  model = new GRBModel(env);
```

(continues on next page)

(continued from previous page)

```
    // Create variables

    GRBVar x = model.AddVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "x");
    GRBVar y = model.AddVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "y");
    GRBVar z = model.AddVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "z");

    // Set objective

    GRBLinExpr obj = x;
    model.SetObjective(obj, GRB.MAXIMIZE);

    // Add linear constraint: x + y + z <= 10

    model.AddConstr(x + y + z <= 10, "c0");

    // Add bilinear inequality: x * y <= 2

    model.AddQConstr(x*y <= 2, "bilinear0");

    // Add bilinear equality: x * z + y * z == 1

    model.AddQConstr(x*z + y*z == 1, "bilinear1");

    // Optimize model

    model.Optimize();

    Console.WriteLine(x.VarName + " " + x.X);
    Console.WriteLine(y.VarName + " " + y.X);
    Console.WriteLine(z.VarName + " " + z.X);

    Console.WriteLine("Obj: " + model.ObjVal + " " + obj.Value);

    x.Set(GRB.CharAttr.VType, GRB.INTEGER);
    model.Optimize();

    Console.WriteLine(x.VarName + " " + x.X);
    Console.WriteLine(y.VarName + " " + y.X);
    Console.WriteLine(z.VarName + " " + z.X);

    Console.WriteLine("Obj: " + model.ObjVal + " " + obj.Value);

    // Dispose of model and env

    model.Dispose();
    env.Dispose();

  } catch (GRBException e) {
    Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
  }
}
```

(continues on next page)

(continued from previous page)

```
}
```

callback_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/*
   This example reads a model from a file, sets up a callback that
   monitors optimization progress and implements a custom
   termination strategy, and outputs progress information to the
   screen and to a log file.

   The termination strategy implemented in this callback stops the
   optimization of a MIP model once at least one of the following two
   conditions have been satisfied:
     1) The optimality gap is less than 10%
     2) At least 10000 nodes have been explored, and an integer feasible
        solution has been found.
   Note that termination is normally handled through Gurobi parameters
   (MIPGap, NodeLimit, etc.).  You should only use a callback for
   termination if the available parameters don't capture your desired
   termination criterion.
*/

using System;
using System.IO;
using Gurobi;

class callback_cs : GRBCallback
{
  private double       lastiter;
  private double       lastnode;
  private GRBVar[]     vars;
  private StreamWriter logfile;

  public callback_cs(GRBVar[] xvars, StreamWriter xlogfile)
  {
    lastiter = lastnode = -GRB.INFINITY;
    vars = xvars;
    logfile = xlogfile;
  }

  protected override void Callback()
  {
    try {
      if (where == GRB.Callback.POLLING) {
        // Ignore polling callback
      } else if (where == GRB.Callback.PRESOLVE) {
        // Presolve callback
        int cdels = GetIntInfo(GRB.Callback.PRE_COLDEL);
```

(continues on next page)

(continued from previous page)

```
        int rdels = GetIntInfo(GRB.Callback.PRE_ROWDEL);
        if (cdels != 0 || rdels != 0) {
          Console.WriteLine(cdels + " columns and " + rdels
              + " rows are removed");
        }
      } else if (where == GRB.Callback.SIMPLEX) {
        // Simplex callback
        double itcnt = GetDoubleInfo(GRB.Callback.SPX_ITRCNT);
        if (itcnt - lastiter >= 100) {
          lastiter = itcnt;
          double obj    = GetDoubleInfo(GRB.Callback.SPX_OBJVAL);
          int    ispert = GetIntInfo(GRB.Callback.SPX_ISPERT);
          double pinf   = GetDoubleInfo(GRB.Callback.SPX_PRIMINF);
          double dinf   = GetDoubleInfo(GRB.Callback.SPX_DUALINF);
          char ch;
          if (ispert == 0)      ch = ' ';
          else if (ispert == 1) ch = 'S';
          else                  ch = 'P';
          Console.WriteLine(itcnt + " " + obj + ch + " "
              + pinf + " " + dinf);
        }
      } else if (where == GRB.Callback.MIP) {
        // General MIP callback
        double nodecnt = GetDoubleInfo(GRB.Callback.MIP_NODCNT);
        double objbst  = GetDoubleInfo(GRB.Callback.MIP_OBJBST);
        double objbnd  = GetDoubleInfo(GRB.Callback.MIP_OBJBND);
        int    solcnt  = GetIntInfo(GRB.Callback.MIP_SOLCNT);
        if (nodecnt - lastnode >= 100) {
          lastnode = nodecnt;
          int actnodes = (int) GetDoubleInfo(GRB.Callback.MIP_NODLFT);
          int itcnt    = (int) GetDoubleInfo(GRB.Callback.MIP_ITRCNT);
          int cutcnt   = GetIntInfo(GRB.Callback.MIP_CUTCNT);
          Console.WriteLine(nodecnt + " " + actnodes + " "
              + itcnt + " " + objbst + " " + objbnd + " "
              + solcnt + " " + cutcnt);
        }
        if (Math.Abs(objbst - objbnd) < 0.1 * (1.0 + Math.Abs(objbst))) {
          Console.WriteLine("Stop early - 10% gap achieved");
          Abort();
        }
        if (nodecnt >= 10000 && solcnt > 0) {
          Console.WriteLine("Stop early - 10000 nodes explored");
          Abort();
        }
      } else if (where == GRB.Callback.MIPSOL) {
        // MIP solution callback
        int      nodecnt = (int) GetDoubleInfo(GRB.Callback.MIPSOL_NODCNT);
        double   obj     = GetDoubleInfo(GRB.Callback.MIPSOL_OBJ);
        int      solcnt  = GetIntInfo(GRB.Callback.MIPSOL_SOLCNT);
        double[] x       = GetSolution(vars);
        Console.WriteLine("**** New solution at node " + nodecnt
            + ", obj " + obj + ", sol " + solcnt
```

(continues on next page)

(continued from previous page)

```
            + ", x[0] = " + x[0] + " ****");
      } else if (where == GRB.Callback.MIPNODE) {
        // MIP node callback
        Console.WriteLine("**** New node ****");
        if (GetIntInfo(GRB.Callback.MIPNODE_STATUS) == GRB.Status.OPTIMAL) {
          double[] x = GetNodeRel(vars);
          SetSolution(vars, x);
        }
      } else if (where == GRB.Callback.BARRIER) {
        // Barrier callback
        int    itcnt   = GetIntInfo(GRB.Callback.BARRIER_ITRCNT);
        double primobj = GetDoubleInfo(GRB.Callback.BARRIER_PRIMOBJ);
        double dualobj = GetDoubleInfo(GRB.Callback.BARRIER_DUALOBJ);
        double priminf = GetDoubleInfo(GRB.Callback.BARRIER_PRIMINF);
        double dualinf = GetDoubleInfo(GRB.Callback.BARRIER_DUALINF);
        double cmpl    = GetDoubleInfo(GRB.Callback.BARRIER_COMPL);
        Console.WriteLine(itcnt + " " + primobj + " " + dualobj + " "
            + priminf + " " + dualinf + " " + cmpl);
      } else if (where == GRB.Callback.MESSAGE) {
        // Message callback
        string msg = GetStringInfo(GRB.Callback.MSG_STRING);
        if (msg != null) logfile.Write(msg);
      }
    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode);
      Console.WriteLine(e.Message);
      Console.WriteLine(e.StackTrace);
    } catch (Exception e) {
      Console.WriteLine("Error during callback");
      Console.WriteLine(e.StackTrace);
    }
  }

  static void Main(string[] args)
  {
    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: callback_cs filename");
      return;
    }

    StreamWriter logfile = null;

    try {
      // Create environment
      GRBEnv env = new GRBEnv();

      // Read model from file
      GRBModel model = new GRBModel(env, args[0]);

      // Turn off display and heuristics
      model.Parameters.OutputFlag = 0;
      model.Parameters.Heuristics = 0.0;
```

(continues on next page)

(continued from previous page)

```
      // Open log file
      logfile = new StreamWriter("cb.log");

      // Create a callback object and associate it with the model
      GRBVar[]    vars = model.GetVars();
      callback_cs cb   = new callback_cs(vars, logfile);

      model.SetCallback(cb);

      // Solve model and capture solution information
      model.Optimize();

      Console.WriteLine("");
      Console.WriteLine("Optimization complete");
      if (model.SolCount == 0) {
        Console.WriteLine("No solution found, optimization status = "
            + model.Status);
      } else {
        Console.WriteLine("Solution found, objective = " + model.ObjVal);

        string[] vnames = model.Get(GRB.StringAttr.VarName, vars);
        double[] x      = model.Get(GRB.DoubleAttr.X, vars);

        for (int j = 0; j < vars.Length; j++) {
          if (x[j] != 0.0) Console.WriteLine(vnames[j] + " " + x[j]);
        }
      }

      // Dispose of model and environment
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode);
      Console.WriteLine(e.Message);
      Console.WriteLine(e.StackTrace);
    } catch (Exception e) {
      Console.WriteLine("Error during optimization");
      Console.WriteLine(e.Message);
      Console.WriteLine(e.StackTrace);
    } finally {
      // Close log file
      if (logfile != null) logfile.Close();
    }
  }
}
```

dense_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QP model:

     minimize    x + y + x^2 + x*y + y^2 + y*z + z^2
     subject to  x + 2 y + 3 z >= 4
                 x +   y       >= 1
                 x, y, z non-negative

   The example illustrates the use of dense matrices to store A and Q
   (and dense vectors for the other relevant data).  We don't recommend
   that you use dense matrices, but this example may be helpful if you
   already have your data in this format.
*/

using System;
using Gurobi;

class dense_cs {

  protected static bool
    dense_optimize(GRBEnv    env,
                   int       rows,
                   int       cols,
                   double[]  c,      // linear portion of objective function
                   double[,] Q,      // quadratic portion of objective function
                   double[,] A,      // constraint matrix
                   char[]    sense,  // constraint senses
                   double[]  rhs,    // RHS vector
                   double[]  lb,     // variable lower bounds
                   double[]  ub,     // variable upper bounds
                   char[]    vtype,  // variable types (continuous, binary, etc.)
                   double[]  solution) {

    bool success = false;

    try {
      GRBModel model = new GRBModel(env);

      // Add variables to the model

      GRBVar[] vars = model.AddVars(lb, ub, null, vtype, null);

      // Populate A matrix

      for (int i = 0; i < rows; i++) {
        GRBLinExpr expr = new GRBLinExpr();
        for (int j = 0; j < cols; j++)
          if (A[i,j] != 0)
            expr.AddTerm(A[i,j], vars[j]); // Note: '+=' would be much slower
        model.AddConstr(expr, sense[i], rhs[i], "");
```

(continues on next page)

(continued from previous page)

```
    }

    // Populate objective

    GRBQuadExpr obj = new GRBQuadExpr();
    if (Q != null) {
      for (int i = 0; i < cols; i++)
        for (int j = 0; j < cols; j++)
          if (Q[i,j] != 0)
            obj.AddTerm(Q[i,j], vars[i], vars[j]); // Note: '+=' would be much slower
      for (int j = 0; j < cols; j++)
        if (c[j] != 0)
          obj.AddTerm(c[j], vars[j]); // Note: '+=' would be much slower
      model.SetObjective(obj);
    }

    // Solve model

    model.Optimize();

    // Extract solution

    if (model.Status == GRB.Status.OPTIMAL) {
      success = true;

      for (int j = 0; j < cols; j++)
        solution[j] = vars[j].X;
    }

    model.Dispose();

  } catch (GRBException e) {
    Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
  }

  return success;
}

public static void Main(String[] args) {
  try {
    GRBEnv env = new GRBEnv();

    double[] c = new double[] {1, 1, 0};
    double[,] Q = new double[,] {{1, 1, 0}, {0, 1, 1}, {0, 0, 1}};
    double[,] A = new double[,] {{1, 2, 3}, {1, 1, 0}};
    char[] sense = new char[] {'>', '>'};
    double[] rhs = new double[] {4, 1};
    double[] lb = new double[] {0, 0, 0};
    bool success;
    double[] sol = new double[3];

    success = dense_optimize(env, 2, 3, c, Q, A, sense, rhs,
```

(continues on next page)

(continued from previous page)

```
                                lb, null, null, sol);

      if (success) {
        Console.WriteLine("x: " + sol[0] + ", y: " + sol[1] + ", z: " + sol[2]);
      }

      // Dispose of environment
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

diet_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Solve the classic diet model, showing how to add constraints
   to an existing model. */

using System;
using Gurobi;

class diet_cs
{
  static void Main()
  {
    try {

      // Nutrition guidelines, based on
      // USDA Dietary Guidelines for Americans, 2005
      // http://www.health.gov/DietaryGuidelines/dga2005/
      string[] Categories =
          new string[] { "calories", "protein", "fat", "sodium" };
      int nCategories = Categories.Length;
      double[] minNutrition = new double[] { 1800, 91, 0, 0 };
      double[] maxNutrition = new double[] { 2200, GRB.INFINITY, 65, 1779 };

      // Set of foods
      string[] Foods =
          new string[] { "hamburger", "chicken", "hot dog", "fries",
              "macaroni", "pizza", "salad", "milk", "ice cream" };
      int nFoods = Foods.Length;
      double[] cost =
          new double[] { 2.49, 2.89, 1.50, 1.89, 2.09, 1.99, 2.49, 0.89,
              1.59 };

      // Nutrition values for the foods
```

(continues on next page)

(continued from previous page)

```
    double[,] nutritionValues = new double[,] {
        { 410, 24, 26, 730 },   // hamburger
        { 420, 32, 10, 1190 },  // chicken
        { 560, 20, 32, 1800 },  // hot dog
        { 380, 4, 19, 270 },    // fries
        { 320, 12, 10, 930 },   // macaroni
        { 320, 15, 12, 820 },   // pizza
        { 320, 31, 12, 1230 },  // salad
        { 100, 8, 2.5, 125 },   // milk
        { 330, 8, 10, 180 }     // ice cream
        };

    // Model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env);

    model.ModelName = "diet";

    // Create decision variables for the nutrition information,
    // which we limit via bounds
    GRBVar[] nutrition = new GRBVar[nCategories];
    for (int i = 0; i < nCategories; ++i) {
      nutrition[i] =
          model.AddVar(minNutrition[i], maxNutrition[i], 0, GRB.CONTINUOUS,
                       Categories[i]);
    }

    // Create decision variables for the foods to buy
    //
    // Note: For each decision variable we add the objective coefficient
    //       with the creation of the variable.
    GRBVar[] buy = new GRBVar[nFoods];
    for (int j = 0; j < nFoods; ++j) {
      buy[j] =
          model.AddVar(0, GRB.INFINITY, cost[j], GRB.CONTINUOUS, Foods[j]);
    }

    // The objective is to minimize the costs
    //
    // Note: The objective coefficients are set during the creation of
    //       the decision variables above.
    model.ModelSense = GRB.MINIMIZE;

    // Nutrition constraints
    for (int i = 0; i < nCategories; ++i) {
      GRBLinExpr ntot = 0.0;
      for (int j = 0; j < nFoods; ++j)
        ntot.AddTerm(nutritionValues[j,i], buy[j]);
      model.AddConstr(ntot == nutrition[i], Categories[i]);
    }

    // Solve
```

(continues on next page)

(continued from previous page)

```
      model.Optimize();
      PrintSolution(model, buy, nutrition);

      Console.WriteLine("\nAdding constraint: at most 6 servings of dairy");
      model.AddConstr(buy[7] + buy[8] <= 6.0, "limit_dairy");

      // Solve
      model.Optimize();
      PrintSolution(model, buy, nutrition);

      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " +
          e.Message);
    }
  }

  private static void PrintSolution(GRBModel model, GRBVar[] buy,
                                    GRBVar[] nutrition) {
    if (model.Status == GRB.Status.OPTIMAL) {
      Console.WriteLine("\nCost: " + model.ObjVal);
      Console.WriteLine("\nBuy:");
      for (int j = 0; j < buy.Length; ++j) {
        if (buy[j].X > 0.0001) {
          Console.WriteLine(buy[j].VarName + " " + buy[j].X);
        }
      }
      Console.WriteLine("\nNutrition:");
      for (int i = 0; i < nutrition.Length; ++i) {
        Console.WriteLine(nutrition[i].VarName + " " + nutrition[i].X);
      }
    } else {
      Console.WriteLine("No solution");
    }
  }
}
```

facility_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Facility location: a company currently ships its product from 5 plants
   to 4 warehouses. It is considering closing some plants to reduce
   costs. What plant(s) should the company close, in order to minimize
   transportation and fixed costs?

   Based on an example from Frontline Systems:
```

(continues on next page)

(continued from previous page)

```
   http://www.solver.com/disfacility.htm
   Used with permission.
 */

using System;
using Gurobi;

class facility_cs
{
  static void Main()
  {
    try {

      // Warehouse demand in thousands of units
      double[] Demand = new double[] { 15, 18, 14, 20 };

      // Plant capacity in thousands of units
      double[] Capacity = new double[] { 20, 22, 17, 19, 18 };

      // Fixed costs for each plant
      double[] FixedCosts =
          new double[] { 12000, 15000, 17000, 13000, 16000 };

      // Transportation costs per thousand units
      double[,] TransCosts =
          new double[,] { { 4000, 2000, 3000, 2500, 4500 },
              { 2500, 2600, 3400, 3000, 4000 },
              { 1200, 1800, 2600, 4100, 3000 },
              { 2200, 2600, 3100, 3700, 3200 } };

      // Number of plants and warehouses
      int nPlants = Capacity.Length;
      int nWarehouses = Demand.Length;

      // Model
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env);

      model.ModelName = "facility";

      // Plant open decision variables: open[p] == 1 if plant p is open.
      GRBVar[] open = new GRBVar[nPlants];
      for (int p = 0; p < nPlants; ++p) {
        open[p] = model.AddVar(0, 1, FixedCosts[p], GRB.BINARY, "Open" + p);
      }

      // Transportation decision variables: how much to transport from
      // a plant p to a warehouse w
      GRBVar[,] transport = new GRBVar[nWarehouses,nPlants];
      for (int w = 0; w < nWarehouses; ++w) {
        for (int p = 0; p < nPlants; ++p) {
          transport[w,p] =
```

(continues on next page)

(continued from previous page)

```
            model.AddVar(0, GRB.INFINITY, TransCosts[w,p], GRB.CONTINUOUS,
                         "Trans" + p + "." + w);
        }
      }

      // The objective is to minimize the total fixed and variable costs
      model.ModelSense = GRB.MINIMIZE;

      // Production constraints
      // Note that the right-hand limit sets the production to zero if
      // the plant is closed
      for (int p = 0; p < nPlants; ++p) {
        GRBLinExpr ptot = 0.0;
        for (int w = 0; w < nWarehouses; ++w)
          ptot.AddTerm(1.0, transport[w,p]);
        model.AddConstr(ptot <= Capacity[p] * open[p], "Capacity" + p);
      }

      // Demand constraints
      for (int w = 0; w < nWarehouses; ++w) {
        GRBLinExpr dtot = 0.0;
        for (int p = 0; p < nPlants; ++p)
          dtot.AddTerm(1.0, transport[w,p]);
        model.AddConstr(dtot == Demand[w], "Demand" + w);
      }

      // Guess at the starting point: close the plant with the highest
      // fixed costs; open all others

      // First, open all plants
      for (int p = 0; p < nPlants; ++p) {
        open[p].Start = 1.0;
      }

      // Now close the plant with the highest fixed cost
      Console.WriteLine("Initial guess:");
      double maxFixed = -GRB.INFINITY;
      for (int p = 0; p < nPlants; ++p) {
        if (FixedCosts[p] > maxFixed) {
          maxFixed = FixedCosts[p];
        }
      }
      for (int p = 0; p < nPlants; ++p) {
        if (FixedCosts[p] == maxFixed) {
          open[p].Start = 0.0;
          Console.WriteLine("Closing plant " + p + "\n");
          break;
        }
      }

      // Use barrier to solve root relaxation
      model.Parameters.Method = GRB.METHOD_BARRIER;
```

(continues on next page)

(continued from previous page)

```
      // Solve
      model.Optimize();

      // Print solution
      Console.WriteLine("\nTOTAL COSTS: " + model.ObjVal);
      Console.WriteLine("SOLUTION:");
      for (int p = 0; p < nPlants; ++p) {
        if (open[p].X > 0.99) {
          Console.WriteLine("Plant " + p + " open:");
          for (int w = 0; w < nWarehouses; ++w) {
            if (transport[w,p].X > 0.0001) {
              Console.WriteLine("  Transport " +
                  transport[w,p].X + " units to warehouse " + w);
            }
          }
        } else {
          Console.WriteLine("Plant " + p + " closed!");
        }
      }

      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

feasopt_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, adds artificial
   variables to each constraint, and then minimizes the sum of the
   artificial variables.  A solution with objective zero corresponds
   to a feasible solution to the input model.
   We can also use FeasRelax feature to do it. In this example, we
   use minrelax=1, i.e. optimizing the returned model finds a solution
   that minimizes the original objective, but only from among those
   solutions that minimize the sum of the artificial variables. */

using Gurobi;
using System;

class feasopt_cs
{
  static void Main(string[] args)
```

(continues on next page)

(continued from previous page)

```
{
  if (args.Length < 1) {
    Console.Out.WriteLine("Usage: feasopt_cs filename");
    return;
  }

  try {
    GRBEnv env = new GRBEnv();
    GRBModel feasmodel = new GRBModel(env, args[0]);

    // Create a copy to use FeasRelax feature later */
    GRBModel feasmodel1 = new GRBModel(feasmodel);

    // Clear objective
    feasmodel.SetObjective(new GRBLinExpr());

    // Add slack variables
    GRBConstr[] c = feasmodel.GetConstrs();
    for (int i = 0; i < c.Length; ++i) {
      char sense = c[i].Sense;
      if (sense != '>') {
        GRBConstr[] constrs = new GRBConstr[] { c[i] };
        double[] coeffs = new double[] { -1 };
        feasmodel.AddVar(0.0, GRB.INFINITY, 1.0, GRB.CONTINUOUS, constrs,
                         coeffs, "ArtN_" + c[i].ConstrName);
      }
      if (sense != '<') {
        GRBConstr[] constrs = new GRBConstr[] { c[i] };
        double[] coeffs = new double[] { 1 };
        feasmodel.AddVar(0.0, GRB.INFINITY, 1.0, GRB.CONTINUOUS, constrs,
                         coeffs, "ArtP_" +
                             c[i].ConstrName);
      }
    }

    // Optimize modified model
    feasmodel.Optimize();
    feasmodel.Write("feasopt.lp");

    // Use FeasRelax feature */
    feasmodel1.FeasRelax(GRB.FEASRELAX_LINEAR, true, false, true);
    feasmodel1.Write("feasopt1.lp");
    feasmodel1.Optimize();

    // Dispose of model and env
    feasmodel1.Dispose();
    feasmodel.Dispose();
    env.Dispose();

  } catch (GRBException e) {
    Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
  }
```

(continues on next page)

(continued from previous page)

```
  }
}
```

fixanddive_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Implement a simple MIP heuristic.  Relax the model,
   sort variables based on fractionality, and fix the 25% of
   the fractional variables that are closest to integer variables.
   Repeat until either the relaxation is integer feasible or
   linearly infeasible. */

using System;
using System.Collections.Generic;
using Gurobi;

class fixanddive_cs
{
  // Comparison class used to sort variable list based on relaxation
  // fractionality

  class FractionalCompare : IComparer<GRBVar>
  {
    public int Compare(GRBVar v1, GRBVar v2)
    {
      try {
        double sol1 = Math.Abs(v1.X);
        double sol2 = Math.Abs(v2.X);
        double frac1 = Math.Abs(sol1 - Math.Floor(sol1 + 0.5));
        double frac2 = Math.Abs(sol2 - Math.Floor(sol2 + 0.5));
        if (frac1 < frac2) {
          return -1;
        } else if (frac1 > frac2) {
          return 1;
        } else {
          return 0;
        }
      } catch (GRBException e) {
        Console.WriteLine("Error code: " + e.ErrorCode + ". " +
            e.Message);
      }
      return 0;
    }
  }

  static void Main(string[] args)
  {
    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: fixanddive_cs filename");
```

(continues on next page)

(continued from previous page)

```
    return;
  }

  try {
    // Read model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env, args[0]);

    // Collect integer variables and relax them
    List<GRBVar> intvars = new List<GRBVar>();
    foreach (GRBVar v in model.GetVars()) {
      if (v.VType != GRB.CONTINUOUS) {
        intvars.Add(v);
        v.VType = GRB.CONTINUOUS;
      }
    }

    model.Parameters.OutputFlag = 0;
    model.Optimize();

    // Perform multiple iterations. In each iteration, identify the first
    // quartile of integer variables that are closest to an integer value
    // in the relaxation, fix them to the nearest integer, and repeat.

    for (int iter = 0; iter < 1000; ++iter) {

      // create a list of fractional variables, sorted in order of
      // increasing distance from the relaxation solution to the nearest
      // integer value

      List<GRBVar> fractional = new List<GRBVar>();
      foreach (GRBVar v in intvars) {
        double sol = Math.Abs(v.X);
        if (Math.Abs(sol - Math.Floor(sol + 0.5)) > 1e-5) {
          fractional.Add(v);
        }
      }

      Console.WriteLine("Iteration " + iter + ", obj " +
          model.ObjVal + ", fractional " + fractional.Count);

      if (fractional.Count == 0) {
        Console.WriteLine("Found feasible solution - objective " +
            model.ObjVal);
        break;
      }

      // Fix the first quartile to the nearest integer value

      fractional.Sort(new FractionalCompare());
      int nfix = Math.Max(fractional.Count / 4, 1);
      for (int i = 0; i < nfix; ++i) {
```

(continues on next page)

(continued from previous page)

```
          GRBVar v = fractional[i];
          double fixval = Math.Floor(v.X + 0.5);
          v.LB = fixval;
          v.UB = fixval;
          Console.WriteLine("  Fix " + v.VarName +
              " to " + fixval + " ( rel " + v.X + " )");
        }

        model.Optimize();

        // Check optimization result

        if (model.Status != GRB.Status.OPTIMAL) {
          Console.WriteLine("Relaxation is infeasible");
          break;
        }
      }

      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " +
          e.Message);
    }
  }
}
```

gc_pwl_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC

 This example formulates and solves the following simple model
 with PWL constraints:

  maximize
        sum c[j] * x[j]
  subject to
        sum A[i,j] * x[j] <= 0,  for i = 0, ..., m-1
        sum y[j] <= 3
        y[j] = pwl(x[j]),        for j = 0, ..., n-1
        x[j] free, y[j] >= 0,    for j = 0, ..., n-1
  where pwl(x) = 0,     if x  = 0
                 = 1+|x|, if x != 0

  Note
   1. sum pwl(x[j]) <= b is to bound x vector and also to favor sparse x vector.
      Here b = 3 means that at most two x[j] can be nonzero and if two, then
      sum x[j] <= 1
```

(continues on next page)

(continued from previous page)

```
   2. pwl(x) jumps from 1 to 0 and from 0 to 1, if x moves from negative 0 to 0,
      then to positive 0, so we need three points at x = 0. x has infinite bounds
      on both sides, the piece defined with two points (-1, 2) and (0, 1) can
      extend x to -infinite. Overall we can use five points (-1, 2), (0, 1),
      (0, 0), (0, 1) and (1, 2) to define y = pwl(x)
*/

using System;
using Gurobi;

public class gc_pwl_cs {

  public static void Main() {
    try {
      int n = 5;
      int m = 5;
      double[] c = new double[] { 0.5, 0.8, 0.5, 0.1, -1 };
      double[,] A = new double[,] { {0, 0, 0, 1, -1},
                                    {0, 0, 1, 1, -1},
                                    {1, 1, 0, 0, -1},
                                    {1, 0, 1, 0, -1},
                                    {1, 0, 0, 1, -1} };
      double[] xpts = new double[] {-1, 0, 0, 0, 1};
      double[] ypts = new double[] {2, 1, 0, 1, 2};

      // Env and model
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env);
      model.ModelName = "gc_pwl_cs";

      // Add variables, set bounds and obj coefficients
      GRBVar[] x = model.AddVars(n, GRB.CONTINUOUS);
      for (int i = 0; i < n; i++) {
        x[i].LB = -GRB.INFINITY;
        x[i].Obj = c[i];
      }

      GRBVar[] y = model.AddVars(n, GRB.CONTINUOUS);

      // Set objective to maximize
      model.ModelSense = GRB.MAXIMIZE;

      // Add linear constraints
      for (int i = 0; i < m; i++) {
        GRBLinExpr le = 0.0;
        for (int j = 0; j < n; j++) {
          le.AddTerm(A[i,j], x[j]);
        }
        model.AddConstr(le, GRB.LESS_EQUAL, 0, "cx" + i);
      }

      GRBLinExpr le1 = 0.0;
```

(continues on next page)

(continued from previous page)

```
      for (int j = 0; j < n; j++) {
        le1.AddTerm(1.0, y[j]);
      }
      model.AddConstr(le1, GRB.LESS_EQUAL, 3, "cy");

      // Add piecewise constraints
      for (int j = 0; j < n; j++) {
        model.AddGenConstrPWL(x[j], y[j], xpts, ypts, "pwl" + j);
      }

      // Optimize model
      model.Optimize();

      for (int j = 0; j < n; j++) {
        Console.WriteLine("x[" + j + "] = " + x[j].X);
      }
      Console.WriteLine("Obj: " + model.ObjVal);

      // Dispose of model and environment
      model.Dispose();
      env.Dispose();
    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

genconstr_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* In this example we show the use of general constraints for modeling
   some common expressions. We use as an example a SAT-problem where we
   want to see if it is possible to satisfy at least four (or all) clauses
   of the logical form

   L = (x0 or ~x1 or x2)  and (x1 or ~x2 or x3)  and
       (x2 or ~x3 or x0)  and (x3 or ~x0 or x1)  and
       (~x0 or ~x1 or x2) and (~x1 or ~x2 or x3) and
       (~x2 or ~x3 or x0) and (~x3 or ~x0 or x1)

   We do this by introducing two variables for each literal (itself and its
   negated value), one variable for each clause, one variable indicating
   whether we can satisfy at least four clauses, and one last variable to
   identify the minimum of the clauses (so if it is one, we can satisfy all
   clauses). Then we put these last two variables in the objective.
   The objective function is therefore

   maximize Obj0 + Obj1
```

(continues on next page)

(continued from previous page)

```
    Obj0 = MIN(Clause1, ... , Clause8)
    Obj1 = 1 -> Clause1 + ... + Clause8 >= 4

   thus, the objective value will be two if and only if we can satisfy all
   clauses; one if and only if at least four but not all clauses can be satisfied,
   and zero otherwise.
 */

using System;
using Gurobi;

class genconstr_cs {

  public const int n = 4;
  public const int NLITERALS = 4;  // same as n
  public const int NCLAUSES = 8;
  public const int NOBJ = 2;

  static void Main() {

    try {
      // Example data:
      //   e.g. {0, n+1, 2} means clause (x0 or ~x1 or x2)
      int[,] Clauses = new int[,]
                       {{  0, n+1, 2}, {  1, n+2, 3},
                        {  2, n+3, 0}, {  3, n+0, 1},
                        {n+0, n+1, 2}, {n+1, n+2, 3},
                        {n+2, n+3, 0}, {n+3, n+0, 1}};

      int i, status;

      // Create environment
      GRBEnv env = new GRBEnv("genconstr_cs.log");

      // Create initial model
      GRBModel model = new GRBModel(env);
      model.ModelName = "genconstr_cs";

      // Initialize decision variables and objective

      GRBVar[] Lit     = new GRBVar[NLITERALS];
      GRBVar[] NotLit  = new GRBVar[NLITERALS];
      for (i = 0; i < NLITERALS; i++) {
        Lit[i]    = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, string.Format("X{0}", i));
        NotLit[i] = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, string.Format("notX{0}", i));
      }

      GRBVar[] Cla = new GRBVar[NCLAUSES];
      for (i = 0; i < NCLAUSES; i++) {
        Cla[i] = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, string.Format("Clause{0}", i));
      }
```

(continues on next page)

(continued from previous page)

```
      GRBVar[] Obj = new GRBVar[NOBJ];
      for (i = 0; i < NOBJ; i++) {
        Obj[i] = model.AddVar(0.0, 1.0, 1.0, GRB.BINARY, string.Format("Obj{0}", i));
      }

      // Link Xi and notXi
      GRBLinExpr lhs;
      for (i = 0; i < NLITERALS; i++) {
        lhs = new GRBLinExpr();
        lhs.AddTerm(1.0, Lit[i]);
        lhs.AddTerm(1.0, NotLit[i]);
        model.AddConstr(lhs, GRB.EQUAL, 1.0, string.Format("CNSTR_X{0}", i));
      }

      // Link clauses and literals
      for (i = 0; i < NCLAUSES; i++) {
        GRBVar[] clause = new GRBVar[3];
        for (int j = 0; j < 3; j++) {
          if (Clauses[i,j] >= n) clause[j] = NotLit[Clauses[i,j]-n];
          else                   clause[j] = Lit[Clauses[i,j]];
        }
        model.AddGenConstrOr(Cla[i], clause, string.Format("CNSTR_Clause{0}", i));
      }

      // Link objs with clauses
      model.AddGenConstrMin(Obj[0], Cla, GRB.INFINITY, "CNSTR_Obj0");
      lhs = new GRBLinExpr();
      for (i = 0; i < NCLAUSES; i++) {
        lhs.AddTerm(1.0, Cla[i]);
      }
      model.AddGenConstrIndicator(Obj[1], 1, lhs, GRB.GREATER_EQUAL, 4.0, "CNSTR_Obj1");

      // Set global objective sense
      model.ModelSense = GRB.MAXIMIZE;

      // Save problem
      model.Write("genconstr_cs.mps");
      model.Write("genconstr_cs.lp");

      // Optimize
      model.Optimize();

      // Status checking
      status = model.Status;

      if (status == GRB.Status.INF_OR_UNBD ||
          status == GRB.Status.INFEASIBLE  ||
          status == GRB.Status.UNBOUNDED     ) {
        Console.WriteLine("The model cannot be solved " +
              "because it is infeasible or unbounded");
        return;
      }
```

(continues on next page)

(continued from previous page)

```
      if (status != GRB.Status.OPTIMAL) {
        Console.WriteLine("Optimization was stopped with status {0}", status);
        return;
      }

      // Print result
      double objval = model.ObjVal;

      if (objval > 1.9)
        Console.WriteLine("Logical expression is satisfiable");
      else if (objval > 0.9)
        Console.WriteLine("At least four clauses can be satisfied");
      else
        Console.WriteLine("Not even three clauses can be satisfied");

      // Dispose of model and environment
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: {0}. {1}", e.ErrorCode, e.Message);
    }
  }
}
```

nlconstr_cs.cs

```
// Copyright 2026, Gurobi Optimization, LLC

// This example formulates and solves the following simple nonlinear model
// using the nonlinear API:
//
//   minimize    x - y
//   subject to  sin(x) * x + x^2 * y  <= 1
//               y = cos(x) (<=> cos(x) - y = 0)
//              -1 <= x <= 2
//               0 <= y <= 2
//
// The example is split into two functions that show two ways to build the
// nonlinear constraints with the new NL API:
//
// - nlconstrNLAPI(): uses the nonlinear expression API. The left-hand sides
//   of the constraints are built as GRBNLExpr objects with the overloaded
//   operators, the nonlinear functions hosted on GRBNLExpr, and the Pow()
//   helper, and passed directly to AddNLConstr().
//
// - nlconstrNLAPIAdv(): uses the advanced expression-tree variant of
//   AddNLConstr(), where the left-hand side of each constraint is described
//   with arrays of opcodes, data, and parent pointers.
//
```

(continues on next page)

(continued from previous page)

```
// In both cases we retrieve a nonlinear constraint with GetNLConstrLHS(),
// delete it with Remove(), replace it with a simple linear constraint, and
// re-optimize.

using System;
using Gurobi;
using static Gurobi.GRBNLExpr;

class nlconstr_cs
{

  /// <summary>
  /// Run both ways of building nonlinear constraints: the nonlinear
  /// expression API and the advanced expression-tree API.
  /// </summary>
  static void Main()
  {
    try {
      // First, the nonlinear expression API
      nlconstrNLAPI();

      // Then, the advanced expression-tree API
      nlconstrNLAPIAdv();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }

  /// <summary>
  /// Formulate the model with the nonlinear expression API, passing
  /// GRBNLExpr left-hand sides to AddNLConstr().
  /// </summary>
  static void nlconstrNLAPI()
  {
    // Create environment
    GRBEnv env = new GRBEnv("nlconstr.log");

    // Create empty model
    GRBModel model = new GRBModel(env);

    // Create variables
    GRBVar x = model.AddVar(-1.0, 2.0, 1.0, GRB.CONTINUOUS, "x");
    GRBVar y = model.AddVar( 0.0, 2.0, -1.0, GRB.CONTINUOUS, "y");

    // Add nonlinear constraint: sin(x)*x + x^2*y <= 1.
    // The left-hand side is built as a GRBNLExpr:
    //   GRBNLExpr.Sin(x)      -> sin(x)
    //   GRBNLExpr.Pow(x, 2.0) -> x^2 (a SQUARE node)
    GRBNLConstr nlc1 = model.AddNLConstr(
        Sin(x) * x + Pow(x, 2.0) * y <= 1.0,
        "NonlinearConstraint1");
```

(continues on next page)

(continued from previous page)

```
  // Add nonlinear constraint: cos(x) - y = 0
  GRBNLConstr nlc2 = model.AddNLConstr(Cos(x) - y == 0.0,
                                       "NonlinearConstraint2");

  // Optimize model
  model.Optimize();

  Console.WriteLine("\nFirst solve (nonlinear constraints)");
  if (model.Status == GRB.Status.OPTIMAL) {
    Console.WriteLine("Optimal objective: {0:E4}", model.ObjVal);
    Console.WriteLine("  x={0:F6}, y={1:F6}", x.X, y.X);
  } else if (model.Status == GRB.Status.INF_OR_UNBD) {
    Console.WriteLine("Model is infeasible or unbounded");
  } else {
    Console.WriteLine("Optimization was stopped early");
  }

  // Retrieve the first nonlinear constraint as a GRBNLExpr and print it
  GRBNLExpr lhs = model.GetNLConstrLHS(nlc1);
  Console.WriteLine("\nRetrieved NL constraint: \"" + lhs + "\"");

  // Delete the nonlinear constraints
  model.Remove(nlc1);
  model.Remove(nlc2);
  model.Update();
  Console.WriteLine("Deleted nonlinear constraints");

  // Add a simple linear constraint instead: x + y >= 1
  model.AddConstr(x + y, GRB.GREATER_EQUAL, 1.0, "LinearConstraint");

  // Re-optimize
  model.Optimize();

  Console.WriteLine("\nSecond solve (linear constraint)");
  if (model.Status == GRB.Status.OPTIMAL) {
    Console.WriteLine("Optimal objective: {0:E4}", model.ObjVal);
    Console.WriteLine("  x={0:F6}, y={1:F6}", x.X, y.X);
  } else if (model.Status == GRB.Status.INF_OR_UNBD) {
    Console.WriteLine("Model is infeasible or unbounded");
  } else {
    Console.WriteLine("Optimization was stopped early");
  }

  // Dispose of model and env
  model.Dispose();
  env.Dispose();
}

/// <summary>
/// Formulate the model with the advanced expression-tree variant of
/// AddNLConstr(), where the left-hand side of each constraint is
```

(continues on next page)

(continued from previous page)

```
  /// described with arrays of opcodes, data, and parent pointers.
  /// </summary>
  static void nlconstrNLAPIAdv()
  {
    // Create environment
    GRBEnv env = new GRBEnv("nlconstr.log");

    // Create empty model
    GRBModel model = new GRBModel(env);

    // Create variables
    GRBVar x = model.AddVar(-1.0, 2.0, 1.0, GRB.CONTINUOUS, "x");
    GRBVar y = model.AddVar( 0.0, 2.0, -1.0, GRB.CONTINUOUS, "y");

    // Expression tree for sin(x) * x + x^2 * y (10 nodes)
    //
    //   node 0: PLUS       (root)
    //   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
    //   node 2: SIN        (child of 1)
    //   node 3: VARIABLE x (child of 2)
    //   node 4: VARIABLE x (child of 1)
    //   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
    //   node 6: POW        (child of 5)
    //   node 7: VARIABLE x (child of 6)
    //   node 8: CONSTANT 2 (child of 6)
    //   node 9: VARIABLE y (child of 5)
    int[] opcode1 = new int[] {
      GRB.OPCODE_PLUS,
      GRB.OPCODE_MULTIPLY,
      GRB.OPCODE_SIN,
      GRB.OPCODE_VARIABLE,
      GRB.OPCODE_VARIABLE,
      GRB.OPCODE_MULTIPLY,
      GRB.OPCODE_POW,
      GRB.OPCODE_VARIABLE,
      GRB.OPCODE_CONSTANT,
      GRB.OPCODE_VARIABLE
    };
    double[] data1 = new double[] {
      -1.0, -1.0, -1.0,
       x.Index,
       x.Index,
      -1.0, -1.0,
       x.Index,
       2.0,
       y.Index
    };
    int[] parent1 = new int[] {-1, 0, 1, 2, 1, 0, 5, 6, 6, 5};

    // Expression tree for cos(x) - y = 0 (4 nodes)
    //
    //   node 0: MINUS      (root)
```

(continues on next page)

(continued from previous page)

```
    //   node 1: COS        (child of 0)
    //   node 2: VARIABLE x (child of 1)
    //   node 3: VARIABLE y (child of 0)
    int[] opcode2 = new int[] {
      GRB.OPCODE_MINUS,
      GRB.OPCODE_COS,
      GRB.OPCODE_VARIABLE,
      GRB.OPCODE_VARIABLE
    };
    double[] data2 = new double[] {
      -1.0, -1.0,
       x.Index,
       y.Index
    };
    int[] parent2 = new int[] {-1, 0, 1, 0};

    // Add nonlinear constraint: sin(x)*x + x^2*y <= 1
    GRBNLConstr nlc1 = model.AddNLConstr(opcode1, data1, parent1,
                                         GRB.LESS_EQUAL, 1.0,
                                         "NonlinearConstraint1");

    // Add nonlinear constraint: cos(x) - y = 0
    GRBNLConstr nlc2 = model.AddNLConstr(opcode2, data2, parent2,
                                         GRB.EQUAL, 0.0,
                                         "NonlinearConstraint2");

    // Optimize model
    model.Optimize();

    Console.WriteLine("\nFirst solve (nonlinear constraints)");
    if (model.Status == GRB.Status.OPTIMAL) {
      Console.WriteLine("Optimal objective: {0:E4}", model.ObjVal);
      Console.WriteLine("  x={0:F6}, y={1:F6}", x.X, y.X);
    } else if (model.Status == GRB.Status.INF_OR_UNBD) {
      Console.WriteLine("Model is infeasible or unbounded");
    } else {
      Console.WriteLine("Optimization was stopped early");
    }

    // Retrieve the first nonlinear constraint and print the number of nodes
    int nnodes;
    model.GetNLConstrLHS(nlc1, out nnodes, null, null, null);
    Console.WriteLine("\nRetrieved NL constraint with " + nnodes + " nodes");

    // Delete the nonlinear constraints
    model.Remove(nlc1);
    model.Remove(nlc2);
    model.Update();
    Console.WriteLine("Deleted nonlinear constraints");

    // Add a simple linear constraint instead: x + y >= 1
    model.AddConstr(x + y, GRB.GREATER_EQUAL, 1.0, "LinearConstraint");
```

(continues on next page)

(continued from previous page)

```
    // Re-optimize
    model.Optimize();

    Console.WriteLine("\nSecond solve (linear constraint)");
    if (model.Status == GRB.Status.OPTIMAL) {
      Console.WriteLine("Optimal objective: {0:E4}", model.ObjVal);
      Console.WriteLine("  x={0:F6}, y={1:F6}", x.X, y.X);
    } else if (model.Status == GRB.Status.INF_OR_UNBD) {
      Console.WriteLine("Model is infeasible or unbounded");
    } else {
      Console.WriteLine("Optimization was stopped early");
    }

    // Dispose of model and env
    model.Dispose();
    env.Dispose();
  }
}
```

nlobj_cs.cs

```
// Copyright 2026, Gurobi Optimization, LLC

// This example formulates and solves the following simple nonlinear model
// using the nonlinear objective API:
//
//      minimize    sin(x) * x + x^2 * y
//      subject to  x + y  >= 1
//                 -1 <= x <= 2
//                  0 <= y <= 2
//
// The example is split into two functions that show two ways to build a
// nonlinear objective with the new NL API:
//
// - nlobjNLAPI(): uses the nonlinear expression API. The nonlinear
//   objective is built as a GRBNLExpr object with the overloaded
//   operators, the nonlinear functions hosted on GRBNLExpr, and the Pow()
//   helper, and passed directly to SetNLObj().
//
// - nlobjNLAPIAdv(): uses the advanced expression-tree variant of
//   SetNLObj(), where the nonlinear expression is described
//   with arrays of opcodes, data, and parent pointers.
//
// In both cases we retrieve the nonlinear objective with GetNLObj(),
// delete it with DelNLObj(), replace it with a simple linear objective, and
// re-optimize.

using System;
using Gurobi;
```

(continues on next page)

(continued from previous page)

```
using static Gurobi.GRBNLExpr;

class nlobj_cs
{
  /// <summary>
  /// Run both ways of building nonlinear objectives: the nonlinear
  /// expression API and the advanced expression-tree API.
  /// </summary>
  static void Main()
  {
    try {
      // First, the nonlinear expression API
      nlobjNLAPI();

      // Then, the advanced expression-tree API
      nlobjNLAPIAdv();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }

  /// <summary>
  /// Formulate the nonlinear objective with the nonlinear expression API,
  /// passing a GRBNLExpr object to SetNLObj().
  /// </summary>
  static void nlobjNLAPI()
  {
    // Create environment
    GRBEnv env = new GRBEnv("nlobj.log");

    // Create empty model
    GRBModel model = new GRBModel(env);

    // Create variables
    GRBVar x = model.AddVar(-1.0, 2.0, 0.0, GRB.CONTINUOUS, "x");
    GRBVar y = model.AddVar( 0.0, 2.0, 0.0, GRB.CONTINUOUS, "y");

    // Add constraint: x + y >= 1
    model.AddConstr(x + y, GRB.GREATER_EQUAL, 1.0, "c0");

    // Add nonlinear objective: sin(x)*x + x^2*y <= 1.
    // The nonlinear expression is built as a GRBNLExpr:
    //   GRBNLExpr.Sin(x)      -> sin(x)
    //   GRBNLExpr.Pow(x, 2.0) -> x^2 (a SQUARE node)
    model.SetNLObj(Sin(x) * x + Pow(x, 2.0) * y);

    // Optimize model
    model.Optimize();

    Console.WriteLine("\nFirst solve (nonlinear objective)");
    if (model.Status == GRB.Status.OPTIMAL) {
```

(continues on next page)

(continued from previous page)

```
    Console.WriteLine("Optimal objective: {0:E4}", model.ObjVal);
    Console.WriteLine("  x={0:F6}, y={1:F6}", x.X, y.X);
  } else {
    Console.WriteLine("Optimization did not produce an optimal solution");
  }

  // Retrieve the nonlinear objective and print the number of nodes
  GRBNLExpr nlobj = model.GetNLObj();
  Console.WriteLine("\nRetrieved NL objective: \"" + nlobj + "\"");

  // Delete the nonlinear objective
  model.DelNLObj();
  Console.WriteLine("Deleted nonlinear objective");

  // Set a simple linear objective instead: minimize x + y
  model.SetObjective(x + y, GRB.MINIMIZE);

  // Re-optimize
  model.Optimize();

  Console.WriteLine("\nSecond solve (linear objective)");
  if (model.Status == GRB.Status.OPTIMAL) {
    Console.WriteLine("Optimal objective: {0:E4}", model.ObjVal);
    Console.WriteLine("  x={0:F6}, y={1:F6}", x.X, y.X);
  } else {
    Console.WriteLine("Optimization did not produce an optimal solution");
  }

  // Dispose of model and env
  model.Dispose();
  env.Dispose();
}

/// <summary>
/// Formulate the nonlinear objective with the advanced expression-tree
/// variant of SetNLObj(), where the nonlinear expression is
/// described with arrays of opcodes, data, and parent pointers.
/// </summary>
static void nlobjNLAPIAdv()
{
  // Create environment
  GRBEnv env = new GRBEnv("nlobj.log");

  // Create empty model
  GRBModel model = new GRBModel(env);

  // Create variables
  GRBVar x = model.AddVar(-1.0, 2.0, 0.0, GRB.CONTINUOUS, "x");
  GRBVar y = model.AddVar( 0.0, 2.0, 0.0, GRB.CONTINUOUS, "y");

  // Add constraint: x + y >= 1
  model.AddConstr(x + y, GRB.GREATER_EQUAL, 1.0, "c0");
```

(continues on next page)

(continued from previous page)

```
// Expression tree for sin(x) * x + x^2 * y (10 nodes)
//
//   node 0: PLUS       (root)
//   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
//   node 2: SIN        (child of 1)
//   node 3: VARIABLE x (child of 2)
//   node 4: VARIABLE x (child of 1)
//   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
//   node 6: POW        (child of 5)
//   node 7: VARIABLE x (child of 6)
//   node 8: CONSTANT 2 (child of 6)
//   node 9: VARIABLE y (child of 5)
int[] opcode = new int[] {
  GRB.OPCODE_PLUS,
  GRB.OPCODE_MULTIPLY,
  GRB.OPCODE_SIN,
  GRB.OPCODE_VARIABLE,
  GRB.OPCODE_VARIABLE,
  GRB.OPCODE_MULTIPLY,
  GRB.OPCODE_POW,
  GRB.OPCODE_VARIABLE,
  GRB.OPCODE_CONSTANT,
  GRB.OPCODE_VARIABLE
};
double[] data = new double[] {
  -1.0, -1.0, -1.0,
    x.Index,
    x.Index,
  -1.0, -1.0,
    x.Index,
    2.0,
    y.Index
};
int[] parent = new int[] {-1, 0, 1, 2, 1, 0, 5, 6, 6, 5};

// Set nonlinear objective
model.SetNLObj(opcode, data, parent);

// Optimize model
model.Optimize();

Console.WriteLine("\nFirst solve (nonlinear objective)");
if (model.Status == GRB.Status.OPTIMAL) {
  Console.WriteLine("Optimal objective: {0:E4}", model.ObjVal);
  Console.WriteLine("  x={0:F6}, y={1:F6}", x.X, y.X);
} else {
  Console.WriteLine("Optimization did not produce an optimal solution");
}

// Retrieve the nonlinear objective and print the number of nodes
int nnodes;
```

(continues on next page)

(continued from previous page)

```
    model.GetNLObj(out nnodes, null, null, null);
    Console.WriteLine("\nRetrieved NL objective with " + nnodes + " nodes");

    // Delete the nonlinear objective
    model.DelNLObj();
    Console.WriteLine("Deleted nonlinear objective");

    // Set a simple linear objective instead: minimize x + y
    model.SetObjective(x + y, GRB.MINIMIZE);

    // Re-optimize
    model.Optimize();

    Console.WriteLine("\nSecond solve (linear objective)");
    if (model.Status == GRB.Status.OPTIMAL) {
      Console.WriteLine("Optimal objective: {0:E4}", model.ObjVal);
      Console.WriteLine("  x={0:F6}, y={1:F6}", x.X, y.X);
    } else {
      Console.WriteLine("Optimization did not produce an optimal solution");
    }

    // Dispose of model and env
    model.Dispose();
    env.Dispose();
  }
}
```

lp_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads an LP model from a file and solves it.
   If the model is infeasible or unbounded, the example turns off
   presolve and solves the model again. If the model is infeasible,
   the example computes an Irreducible Inconsistent Subsystem (IIS),
   and writes it to a file. */

using System;
using Gurobi;

class lp_cs
{
  static void Main(string[] args)
  {
    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: lp_cs filename");
      return;
    }

    try {
```

(continues on next page)

(continued from previous page)

```
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env, args[0]);

      model.Optimize();

      int optimstatus = model.Status;

      if (optimstatus == GRB.Status.INF_OR_UNBD) {
        model.Parameters.Presolve = 0;
        model.Optimize();
        optimstatus = model.Status;
      }

      if (optimstatus == GRB.Status.OPTIMAL) {
        double objval = model.ObjVal;
        Console.WriteLine("Optimal objective: " + objval);
      } else if (optimstatus == GRB.Status.INFEASIBLE) {
        Console.WriteLine("Model is infeasible");

        // compute and write out IIS

        model.ComputeIIS();
        model.Write("model.ilp");
      } else if (optimstatus == GRB.Status.UNBOUNDED) {
        Console.WriteLine("Model is unbounded");
      } else {
        Console.WriteLine("Optimization was stopped with status = "
                          + optimstatus);
      }

      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

lpmethod_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Solve a model with different values of the Method parameter;
   show which value gives the shortest solve time. */

using System;
using Gurobi;
```

(continues on next page)

(continued from previous page)

```
class lpmethod_cs
{
  static void Main(string[] args)
  {
    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: lpmethod_cs filename");
      return;
    }

    try {
      // Read model
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env, args[0]);

      // Solve the model with different values of Method
      int bestMethod = -1;
      double bestTime = model.Parameters.TimeLimit;
      for (int i = 0; i <= 2; ++i)
      {
        model.Reset();
        model.Parameters.Method = i;
        model.Optimize();
        if (model.Status == GRB.Status.OPTIMAL)
        {
          bestTime = model.Runtime;
          bestMethod = i;
          // Reduce the TimeLimit parameter to save time
          // with other methods
          model.Parameters.TimeLimit = bestTime;
        }
      }

      // Report which method was fastest
      if (bestMethod == -1) {
        Console.WriteLine("Unable to solve this model");
      } else {
        Console.WriteLine("Solved in " + bestTime
          + " seconds with Method: " + bestMethod);
      }

      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

lpmod_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads an LP model from a file and solves it.
   If the model can be solved, then it finds the smallest positive variable,
   sets its upper bound to zero, and resolves the model two ways:
   first with an advanced start, then without an advanced start
   (i.e. 'from scratch'). */

using System;
using Gurobi;

class lpmod_cs
{
  static void Main(string[] args)
  {
    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: lpmod_cs filename");
      return;
    }

    try {
      // Read model and determine whether it is an LP
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env, args[0]);
      if (model.IsMIP != 0) {
        Console.WriteLine("The model is not a linear program");
        Environment.Exit(1);
      }

      model.Optimize();

      int status = model.Status;

      if ((status == GRB.Status.INF_OR_UNBD) ||
          (status == GRB.Status.INFEASIBLE) ||
          (status == GRB.Status.UNBOUNDED)) {
        Console.WriteLine("The model cannot be solved because it is "
            + "infeasible or unbounded");
        Environment.Exit(1);
      }

      if (status != GRB.Status.OPTIMAL) {
        Console.WriteLine("Optimization was stopped with status " + status);
        Environment.Exit(0);
      }

      // Find the smallest variable value
      double minVal = GRB.INFINITY;
      GRBVar minVar = null;
      foreach (GRBVar v in model.GetVars()) {
        double sol = v.X;
```

(continues on next page)

(continued from previous page)

```
        if ((sol > 0.0001) && (sol < minVal) && (v.LB == 0.0)) {
          minVal = sol;
          minVar = v;
        }
      }

      Console.WriteLine("\n*** Setting " +
          minVar.VarName + " from " + minVal +
          " to zero ***\n");
      minVar.UB = 0.0;

      // Solve from this starting point
      model.Optimize();

      // Save iteration & time info
      double warmCount = model.IterCount;
      double warmTime = model.Runtime;

      // Reset the model and resolve
      Console.WriteLine("\n*** Resetting and solving "
          + "without an advanced start ***\n");
      model.Reset();
      model.Optimize();

      double coldCount = model.IterCount;
      double coldTime = model.Runtime;

      Console.WriteLine("\n*** Warm start: " + warmCount + " iterations, " +
          warmTime + " seconds");
      Console.WriteLine("*** Cold start: " + coldCount + " iterations, " +
          coldTime + " seconds");

      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " +
          e.Message);
    }
  }
}
```

mip1_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple MIP model:

     maximize    x +   y + 2 z
     subject to  x + 2 y + 3 z <= 4
                 x +   y       >= 1
                 x, y, z binary
*/

using System;
using Gurobi;

class mip1_cs
{
  static void Main()
  {
    try {

      // Create an empty environment, set options and start
      GRBEnv env = new GRBEnv(true);
      env.Set("LogFile", "mip1.log");
      env.Start();

      // Create empty model
      GRBModel model = new GRBModel(env);

      // Create variables
      GRBVar x = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, "x");
      GRBVar y = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, "y");
      GRBVar z = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, "z");

      // Set objective: maximize x + y + 2 z
      model.SetObjective(x + y + 2 * z, GRB.MAXIMIZE);

      // Add constraint: x + 2 y + 3 z <= 4
      model.AddConstr(x + 2 * y + 3 * z <= 4.0, "c0");

      // Add constraint: x + y >= 1
      model.AddConstr(x + y >= 1.0, "c1");

      // Optimize model
      model.Optimize();

      Console.WriteLine(x.VarName + " " + x.X);
      Console.WriteLine(y.VarName + " " + y.X);
      Console.WriteLine(z.VarName + " " + z.X);

      Console.WriteLine("Obj: " + model.ObjVal);

      // Dispose of model and env
```

(continues on next page)

(continued from previous page)

```
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

mip2_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, solves it and
   prints the objective values from all feasible solutions
   generated while solving the MIP. Then it creates the fixed
   model and solves that model. */

using System;
using Gurobi;

class mip2_cs
{
  static void Main(string[] args)
  {
    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: mip2_cs filename");
      return;
    }

    try {
      GRBEnv    env   = new GRBEnv();
      GRBModel  model = new GRBModel(env, args[0]);
      if (model.IsMIP == 0) {
        Console.WriteLine("Model is not a MIP");
        return;
      }

      model.Optimize();

      int optimstatus = model.Status;
      double objval = 0;
      if (optimstatus == GRB.Status.OPTIMAL) {
        objval = model.ObjVal;
        Console.WriteLine("Optimal objective: " + objval);
      } else if (optimstatus == GRB.Status.INF_OR_UNBD) {
        Console.WriteLine("Model is infeasible or unbounded");
        return;
      } else if (optimstatus == GRB.Status.INFEASIBLE) {
        Console.WriteLine("Model is infeasible");
```

(continues on next page)

(continued from previous page)

```
      return;
    } else if (optimstatus == GRB.Status.UNBOUNDED) {
      Console.WriteLine("Model is unbounded");
      return;
    } else {
      Console.WriteLine("Optimization was stopped with status = "
                        + optimstatus);
      return;
    }

    /* Iterate over the solutions and compute the objectives */

    Console.WriteLine();
    for (int k = 0; k < model.SolCount; ++k) {
      model.Parameters.SolutionNumber = k;
      double objn = model.PoolNObjVal;

      Console.WriteLine("Solution " + k + " has objective: " + objn);
    }
    Console.WriteLine();

    /* Create a fixed model, turn off presolve and solve */

    GRBModel fixedmodel = model.FixedModel();

    fixedmodel.Parameters.Presolve = 0;

    fixedmodel.Optimize();

    int foptimstatus = fixedmodel.Status;

    if (foptimstatus != GRB.Status.OPTIMAL) {
      Console.WriteLine("Error: fixed model isn't optimal");
      return;
    }

    double fobjval = fixedmodel.ObjVal;

    if (Math.Abs(fobjval - objval) > 1.0e-6 * (1.0 + Math.Abs(objval))) {
      Console.WriteLine("Error: objective values are different");
      return;
    }

    GRBVar[] fvars  = fixedmodel.GetVars();
    double[] x      = fixedmodel.Get(GRB.DoubleAttr.X, fvars);
    string[] vnames = fixedmodel.Get(GRB.StringAttr.VarName, fvars);

    for (int j = 0; j < fvars.Length; j++) {
      if (x[j] != 0.0) Console.WriteLine(vnames[j] + " " + x[j]);
    }

    // Dispose of models and env
```

(continues on next page)

(continued from previous page)

```
      fixedmodel.Dispose();
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

multiobj_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Want to cover four different sets but subject to a common budget of
   elements allowed to be used. However, the sets have different priorities to
   be covered; and we tackle this by using multi-objective optimization. */

using System;
using Gurobi;

class multiobj_cs {
  static void Main() {

    try {
      // Sample data
      int groundSetSize = 20;
      int nSubsets      = 4;
      int Budget        = 12;
      double[,] Set = new double[,]
      { { 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0 },
        { 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1 },
        { 0, 0, 0, 1, 1, 0, 1, 1, 0, 0, 0, 0, 0, 1, 1, 0, 1, 1, 0, 0 },
        { 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0 } };
      int[]    SetObjPriority = new int[] {3, 2, 2, 1};
      double[] SetObjWeight   = new double[] {1.0, 0.25, 1.25, 1.0};
      int e, i, status, nSolutions;

      // Create environment
      GRBEnv env = new GRBEnv("multiobj_cs.log");

      // Create initial model
      GRBModel model = new GRBModel(env);
      model.ModelName = "multiobj_cs";

      // Initialize decision variables for ground set:
      // x[e] == 1 if element e is chosen for the covering.
      GRBVar[] Elem = model.AddVars(groundSetSize, GRB.BINARY);
      for (e = 0; e < groundSetSize; e++) {
        string vname = string.Format("El{0}", e);
```

(continues on next page)

(continued from previous page)

```
    Elem[e].VarName = vname;
  }

  // Constraint: limit total number of elements to be picked to be at most
  // Budget
  GRBLinExpr lhs = new GRBLinExpr();
  for (e = 0; e < groundSetSize; e++) {
    lhs.AddTerm(1.0, Elem[e]);
  }
  model.AddConstr(lhs, GRB.LESS_EQUAL, Budget, "Budget");

  // Set global sense for ALL objectives
  model.ModelSense = GRB.MAXIMIZE;

  // Limit how many solutions to collect
  model.Parameters.PoolSolutions = 100;

  // Set and configure i-th objective
  for (i = 0; i < nSubsets; i++) {
    string vname = string.Format("Set{0}", i);
    GRBLinExpr objn = new GRBLinExpr();
    for (e = 0; e < groundSetSize; e++) {
      objn.AddTerm(Set[i,e], Elem[e]);
    }

    model.SetObjectiveN(objn, i, SetObjPriority[i], SetObjWeight[i],
                        1.0 + i, 0.01, vname);
  }

  // Save problem
  model.Write("multiobj_cs.lp");

  // Optimize
  model.Optimize();

  // Status checking
  status = model.Status;

  if (status == GRB.Status.INF_OR_UNBD ||
      status == GRB.Status.INFEASIBLE  ||
      status == GRB.Status.UNBOUNDED     ) {
    Console.WriteLine("The model cannot be solved " +
              "because it is infeasible or unbounded");
    return;
  }
  if (status != GRB.Status.OPTIMAL) {
    Console.WriteLine("Optimization was stopped with status {0}", status);
    return;
  }

  // Print best selected set
  Console.WriteLine("Selected elements in best solution:");
```

(continues on next page)

(continued from previous page)

```
      Console.Write("\t");
      for (e = 0; e < groundSetSize; e++) {
        if (Elem[e].X < .9) continue;
        Console.Write("El{0} ", e);
      }
      Console.WriteLine();

      // Print number of solutions stored
      nSolutions = model.SolCount;
      Console.WriteLine("Number of solutions found: {0}", nSolutions);

      // Print objective values of solutions
      if (nSolutions > 10) nSolutions = 10;
      Console.WriteLine("Objective values for first {0} solutions:", nSolutions);
      for (i = 0; i < nSubsets; i++) {
        model.Parameters.ObjNumber = i;

        Console.Write("\tSet" + i);
        for (e = 0; e < nSolutions; e++) {
          model.Parameters.SolutionNumber = e;
          Console.Write("{0,8}", model.ObjNVal);
        }
        Console.WriteLine();
      }
      model.Dispose();
      env.Dispose();
    } catch (GRBException e) {
      Console.WriteLine("Error code = {0}", e);
      Console.WriteLine(e.Message);
    }
  }
}
```

multiscenario_cs.cs

```
// Copyright 2026, Gurobi Optimization, LLC

// Facility location: a company currently ships its product from 5 plants
// to 4 warehouses. It is considering closing some plants to reduce
// costs. What plant(s) should the company close, in order to minimize
// transportation and fixed costs?
//
// Since the plant fixed costs and the warehouse demands are uncertain, a
// scenario approach is chosen.
//
// Note that this example is similar to the facility_cs.cs example. Here we
// added scenarios in order to illustrate the multi-scenario feature.
//
// Based on an example from Frontline Systems:
// http://www.solver.com/disfacility.htm
```

(continues on next page)

(continued from previous page)

```
// Used with permission.

using System;
using Gurobi;

class multiscenario_cs
{
  static void Main()
  {
    try {

      // Warehouse demand in thousands of units
      double[] Demand = new double[] { 15, 18, 14, 20 };

      // Plant capacity in thousands of units
      double[] Capacity = new double[] { 20, 22, 17, 19, 18 };

      // Fixed costs for each plant
      double[] FixedCosts =
        new double[] { 12000, 15000, 17000, 13000, 16000 };

      // Transportation costs per thousand units
      double[,] TransCosts =
        new double[,] { { 4000, 2000, 3000, 2500, 4500 },
                        { 2500, 2600, 3400, 3000, 4000 },
                        { 1200, 1800, 2600, 4100, 3000 },
                        { 2200, 2600, 3100, 3700, 3200 } };

      // Number of plants and warehouses
      int nPlants = Capacity.Length;
      int nWarehouses = Demand.Length;

      double maxFixed = -GRB.INFINITY;
      double minFixed = GRB.INFINITY;
      for (int p = 0; p < nPlants; ++p) {
        if (FixedCosts[p] > maxFixed)
          maxFixed = FixedCosts[p];

        if (FixedCosts[p] < minFixed)
          minFixed = FixedCosts[p];
      }

      // Model
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env);

      model.ModelName = "multiscenario";

      // Plant open decision variables: open[p] == 1 if plant p is open.
      GRBVar[] open = new GRBVar[nPlants];
      for (int p = 0; p < nPlants; ++p) {
        open[p] = model.AddVar(0, 1, FixedCosts[p], GRB.BINARY, "Open" + p);
```

(continues on next page)

(continued from previous page)

```
    }

    // Transportation decision variables: how much to transport from
    // a plant p to a warehouse w
    GRBVar[,] transport = new GRBVar[nWarehouses,nPlants];
    for (int w = 0; w < nWarehouses; ++w) {
      for (int p = 0; p < nPlants; ++p) {
        transport[w,p] = model.AddVar(0, GRB.INFINITY, TransCosts[w,p],
                                      GRB.CONTINUOUS, "Trans" + p + "." + w);
      }
    }

    // The objective is to minimize the total fixed and variable costs
    model.ModelSense = GRB.MINIMIZE;

    // Production constraints
    // Note that the right-hand limit sets the production to zero if
    // the plant is closed
    for (int p = 0; p < nPlants; ++p) {
      GRBLinExpr ptot = 0.0;
      for (int w = 0; w < nWarehouses; ++w)
        ptot.AddTerm(1.0, transport[w,p]);
      model.AddConstr(ptot <= Capacity[p] * open[p], "Capacity" + p);
    }

    // Demand constraints
    GRBConstr[] demandConstr = new GRBConstr[nWarehouses];
    for (int w = 0; w < nWarehouses; ++w) {
      GRBLinExpr dtot = 0.0;
      for (int p = 0; p < nPlants; ++p)
        dtot.AddTerm(1.0, transport[w,p]);
      demandConstr[w] = model.AddConstr(dtot == Demand[w], "Demand" + w);
    }

    // We constructed the base model, now we add 7 scenarios
    //
    // Scenario 0: Represents the base model, hence, no manipulations.
    // Scenario 1: Manipulate the warehouses demands slightly (constraint right
    //             hand sides).
    // Scenario 2: Double the warehouses demands (constraint right hand sides).
    // Scenario 3: Manipulate the plant fixed costs (objective coefficients).
    // Scenario 4: Manipulate the warehouses demands and fixed costs.
    // Scenario 5: Force the plant with the largest fixed cost to stay open
    //             (variable bounds).
    // Scenario 6: Force the plant with the smallest fixed cost to be closed
    //             (variable bounds).

    model.NumScenarios = 7;

    // Scenario 0: Base model, hence, nothing to do except giving the
    //             scenario a name
    model.Parameters.ScenarioNumber = 0;
```

(continues on next page)

(continued from previous page)

```
    model.ScenNName = "Base model";

    // Scenario 1: Increase the warehouse demands by 10%
    model.Parameters.ScenarioNumber = 1;
    model.ScenNName = "Increased warehouse demands";

    for (int w = 0; w < nWarehouses; w++) {
      demandConstr[w].ScenNRHS = Demand[w] * 1.1;
    }

    // Scenario 2: Double the warehouse demands
    model.Parameters.ScenarioNumber = 2;
    model.ScenNName = "Double the warehouse demands";

    for (int w = 0; w < nWarehouses; w++) {
      demandConstr[w].ScenNRHS = Demand[w] * 2.0;
    }

    // Scenario 3: Decrease the plant fixed costs by 5%
    model.Parameters.ScenarioNumber = 3;
    model.ScenNName = "Decreased plant fixed costs";

    for (int p = 0; p < nPlants; p++) {
      open[p].ScenNObj = FixedCosts[p] * 0.95;
    }

    // Scenario 4: Combine scenario 1 and scenario 3 */
    model.Parameters.ScenarioNumber = 4;
    model.ScenNName = "Increased warehouse demands and decreased plant fixed costs";

    for (int w = 0; w < nWarehouses; w++) {
      demandConstr[w].ScenNRHS = Demand[w] * 1.1;
    }
    for (int p = 0; p < nPlants; p++) {
      open[p].ScenNObj = FixedCosts[p] * 0.95;
    }

    // Scenario 5: Force the plant with the largest fixed cost to stay
    //             open
    model.Parameters.ScenarioNumber = 5;
    model.ScenNName = "Force plant with largest fixed cost to stay open";

    for (int p = 0; p < nPlants; p++) {
      if (FixedCosts[p] == maxFixed) {
        open[p].ScenNLB = 1.0;
        break;
      }
    }

    // Scenario 6: Force the plant with the smallest fixed cost to be
    //             closed
    model.Parameters.ScenarioNumber = 6;
```

(continues on next page)

(continued from previous page)

```
    model.ScenNName = "Force plant with smallest fixed cost to be closed";

    for (int p = 0; p < nPlants; p++) {
      if (FixedCosts[p] == minFixed) {
        open[p].ScenNUB = 0.0;
        break;
      }
    }

    // Guess at the starting point: close the plant with the highest
    // fixed costs; open all others

    // First, open all plants
    for (int p = 0; p < nPlants; ++p) {
      open[p].Start = 1.0;
    }

    // Now close the plant with the highest fixed cost
    Console.WriteLine("Initial guess:");
    for (int p = 0; p < nPlants; ++p) {
      if (FixedCosts[p] == maxFixed) {
        open[p].Start = 0.0;
        Console.WriteLine("Closing plant " + p + "\n");
        break;
      }
    }

    // Use barrier to solve root relaxation
    model.Parameters.Method = GRB.METHOD_BARRIER;

    // Solve multi-scenario model
    model.Optimize();

    int nScenarios = model.NumScenarios;

    for (int s = 0; s < nScenarios; s++) {
      int modelSense = GRB.MINIMIZE;

      // Set the scenario number to query the information for this scenario
      model.Parameters.ScenarioNumber = s;

      // collect result for the scenario
      double scenNObjBound = model.ScenNObjBound;
      double scenNObjVal = model.ScenNObjVal;

      Console.WriteLine("\n\n------ Scenario " + s
                        + " (" +  model.ScenNName + ")");

      // Check if we found a feasible solution for this scenario
      if (modelSense * scenNObjVal >= GRB.INFINITY)
        if (modelSense * scenNObjBound >= GRB.INFINITY)
          // Scenario was proven to be infeasible
```

(continues on next page)

(continued from previous page)

```
          Console.WriteLine("\nINFEASIBLE");
        else
          // We did not find any feasible solution - should not happen in
          // this case, because we did not set any limit (like a time
          // limit) on the optimization process
          Console.WriteLine("\nNO SOLUTION");
      else {
        Console.WriteLine("\nTOTAL COSTS: " + scenNObjVal);
        Console.WriteLine("SOLUTION:");
        for (int p = 0; p < nPlants; p++) {
          double scenNX = open[p].ScenNX;

          if (scenNX > 0.5) {
            Console.WriteLine("Plant " + p + " open");
            for (int w = 0; w < nWarehouses; w++) {
              scenNX = transport[w,p].ScenNX;

              if (scenNX > 0.0001)
                Console.WriteLine("  Transport " + scenNX
                                  + " units to warehouse " + w);
            }
          } else
            Console.WriteLine("Plant " + p + " closed!");
        }
      }
    }

    // Print a summary table: for each scenario we add a single summary
    // line
    Console.WriteLine("\n\nSummary: Closed plants depending on scenario\n");
    Console.WriteLine("{0,8} | {1,17} {2,13}", "", "Plant", "|");

    Console.Write("{0,8} |", "Scenario");
    for (int p = 0; p < nPlants; p++)
      Console.Write("{0,6}", p);
    Console.WriteLine(" | {0,6}  Name", "Costs");

    for (int s = 0; s < nScenarios; s++) {
      int modelSense = GRB.MINIMIZE;

      // Set the scenario number to query the information for this scenario
      model.Parameters.ScenarioNumber = s;

      // Collect result for the scenario
      double scenNObjBound = model.ScenNObjBound;
      double scenNObjVal = model.ScenNObjVal;

      Console.Write("{0,-8} |", s);

      // Check if we found a feasible solution for this scenario
      if (modelSense * scenNObjVal >= GRB.INFINITY) {
        if (modelSense * scenNObjBound >= GRB.INFINITY)
```

(continues on next page)

(continued from previous page)

```
            // Scenario was proven to be infeasible
            Console.WriteLine(" {0,-30}| {1,6}  " + model.ScenNName,
                              "infeasible", "-");
          else
            // We did not find any feasible solution - should not happen in
            // this case, because we did not set any limit (like a time
            // limit) on the optimization process
            Console.WriteLine(" {0,-30}| {1,6}  " + model.ScenNName,
                              "no solution found", "-");
        } else {
          for (int p = 0; p < nPlants; p++) {
            double scenNX = open[p].ScenNX;
            if (scenNX  > 0.5)
              Console.Write("{0,6}", " ");
            else
              Console.Write("{0,6}", "x");
          }

          Console.WriteLine(" | {0,6}  "+ model.ScenNName, scenNObjVal);
        }
      }

      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

params_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Use parameters that are associated with a model.

   A MIP is solved for a few seconds with different sets of parameters.
   The one with the smallest MIP gap is selected, and the optimization
   is resumed until the optimal solution is found.
*/

using System;
using Gurobi;

class params_cs
{
  static void Main(string[] args)
  {
```

(continues on next page)

(continued from previous page)

```
    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: params_cs filename");
      return;
    }

    try {
      // Read model and verify that it is a MIP
      GRBEnv env = new GRBEnv();
      GRBModel m = new GRBModel(env, args[0]);
      if (m.IsMIP == 0) {
        Console.WriteLine("The model is not an integer program");
        Environment.Exit(1);
      }

      // Set a 2 second time limit
      m.Parameters.TimeLimit = 2.0;

      // Now solve the model with different values of MIPFocus
      GRBModel bestModel = new GRBModel(m);
      bestModel.Optimize();
      for (int i = 1; i <= 3; ++i) {
        m.Reset();
        m.Parameters.MIPFocus = i;
        m.Optimize();
        if (bestModel.MIPGap > m.MIPGap) {
          GRBModel swap = bestModel;
          bestModel = m;
          m = swap;
        }
      }

      // Finally, delete the extra model, reset the time limit and
      // continue to solve the best model to optimality
      m.Dispose();
      bestModel.Parameters.TimeLimit = GRB.INFINITY;
      bestModel.Optimize();
      Console.WriteLine("Solved with MIPFocus: " +
                        bestModel.Parameters.MIPFocus);

      // Clean up bestModel and environment
      bestModel.Dispose();
      env.Dispose();
    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " +
          e.Message);
    }
  }
}
```

piecewise_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example considers the following separable, convex problem:

     minimize    f(x) - y + g(z)
     subject to  x + 2 y + 3 z <= 4
                 x +   y       >= 1
                 x,    y,    z <= 1

   where f(u) = exp(-u) and g(u) = 2 u^2 - 4 u, for all real u. It
   formulates and solves a simpler LP model by approximating f and
   g with piecewise-linear functions. Then it transforms the model
   into a MIP by negating the approximation for f, which corresponds
   to a non-convex piecewise-linear function, and solves it again.
*/

using System;
using Gurobi;

class piecewise_cs
{

  private static double f(double u) { return Math.Exp(-u); }
  private static double g(double u) { return 2 * u * u - 4 * u; }

  static void Main()
  {
    try {

      // Create environment

      GRBEnv env = new GRBEnv();

      // Create a new model

      GRBModel model = new GRBModel(env);

      // Create variables

      double lb = 0.0, ub = 1.0;

      GRBVar x = model.AddVar(lb, ub, 0.0, GRB.CONTINUOUS, "x");
      GRBVar y = model.AddVar(lb, ub, 0.0, GRB.CONTINUOUS, "y");
      GRBVar z = model.AddVar(lb, ub, 0.0, GRB.CONTINUOUS, "z");

      // Set objective for y

      model.SetObjective(-y);

      // Add piecewise-linear objective functions for x and z
```

(continues on next page)

(continued from previous page)

```
int npts = 101;
double[] ptu = new double[npts];
double[] ptf = new double[npts];
double[] ptg = new double[npts];

for (int i = 0; i < npts; i++) {
  ptu[i] = lb + (ub - lb) * i / (npts - 1);
  ptf[i] = f(ptu[i]);
  ptg[i] = g(ptu[i]);
}

model.SetPWLObj(x, ptu, ptf);
model.SetPWLObj(z, ptu, ptg);

// Add constraint: x + 2 y + 3 z <= 4

model.AddConstr(x + 2 * y + 3 * z <= 4.0, "c0");

// Add constraint: x + y >= 1

model.AddConstr(x + y >= 1.0, "c1");

// Optimize model as an LP

model.Optimize();

Console.WriteLine("IsMIP: " + model.IsMIP);

Console.WriteLine(x.VarName + " " + x.X);
Console.WriteLine(y.VarName + " " + y.X);
Console.WriteLine(z.VarName + " " + z.X);

Console.WriteLine("Obj: " + model.ObjVal);

Console.WriteLine();

// Negate piecewise-linear objective function for x

for (int i = 0; i < npts; i++) {
  ptf[i] = -ptf[i];
}

model.SetPWLObj(x, ptu, ptf);

// Optimize model as a MIP

model.Optimize();

Console.WriteLine("IsMIP: " + model.IsMIP);

Console.WriteLine(x.VarName + " " + x.X);
Console.WriteLine(y.VarName + " " + y.X);
```

(continues on next page)

(continued from previous page)

```
      Console.WriteLine(z.VarName + " " + z.X);

      Console.WriteLine("Obj: " + model.ObjVal);

      // Dispose of model and environment

      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

poolsearch_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* We find alternative epsilon-optimal solutions to a given knapsack
   problem by using PoolSearchMode */

using System;
using Gurobi;

class poolsearch_cs {

  static void Main() {

    try{
      // Sample data
      int groundSetSize = 10;
      double[] objCoef = new double[] {32, 32, 15, 15, 6, 6, 1, 1, 1, 1};
      double[] knapsackCoef = new double[] {16, 16,  8,  8, 4, 4, 2, 2, 1, 1};
      double Budget = 33;
      int e, status, nSolutions;

      // Create environment
      GRBEnv env = new GRBEnv("poolsearch_cs.log");

      // Create initial model
      GRBModel model = new GRBModel(env);
      model.ModelName = "poolsearch_cs";

      // Initialize decision variables for ground set:
      // x[e] == 1 if element e is chosen
      GRBVar[] Elem = model.AddVars(groundSetSize, GRB.BINARY);
      model.Set(GRB.DoubleAttr.Obj, Elem, objCoef);

      for (e = 0; e < groundSetSize; e++) {
```

(continues on next page)

(continued from previous page)

```
      Elem[e].VarName = string.Format("El{0}", e);
    }

    // Constraint: limit total number of elements to be picked to be at most
    // Budget
    GRBLinExpr lhs = new GRBLinExpr();
    for (e = 0; e < groundSetSize; e++) {
      lhs.AddTerm(knapsackCoef[e], Elem[e]);
    }
    model.AddConstr(lhs, GRB.LESS_EQUAL, Budget, "Budget");

    // set global sense for ALL objectives
    model.ModelSense = GRB.MAXIMIZE;

    // Limit how many solutions to collect
    model.Parameters.PoolSolutions = 1024;

    // Limit the search space by setting a gap for the worst possible solution that␣
↪will be accepted
    model.Parameters.PoolGap = 0.10;

    // do a systematic search for the k-best solutions
    model.Parameters.PoolSearchMode = 2;

    // save problem
    model.Write("poolsearch_cs.lp");

    // Optimize
    model.Optimize();

    // Status checking
    status = model.Status;

    if (status == GRB.Status.INF_OR_UNBD ||
        status == GRB.Status.INFEASIBLE  ||
        status == GRB.Status.UNBOUNDED     ) {
      Console.WriteLine("The model cannot be solved " +
             "because it is infeasible or unbounded");
      return;
    }
    if (status != GRB.Status.OPTIMAL) {
      Console.WriteLine("Optimization was stopped with status {0}", status);
      return;
    }

    // Print best selected set
    Console.WriteLine("Selected elements in best solution:");
    Console.Write("\t");
    for (e = 0; e < groundSetSize; e++) {
      if (Elem[e].X < .9) continue;
      Console.Write("El{0} ", e);
    }
```

(continues on next page)

(continued from previous page)

```
      Console.WriteLine();

      // Print number of solutions stored
      nSolutions = model.SolCount;
      Console.WriteLine("Number of solutions found: {0}", nSolutions);

      // Print objective values of solutions
      for (e = 0; e < nSolutions; e++) {
        model.Parameters.SolutionNumber = e;
        Console.Write("{0} ", model.PoolNObjVal);
        if (e%15 == 14) Console.WriteLine();
      }
      Console.WriteLine();

      // Print fourth best set if available
      if (nSolutions >= 4) {
        model.Parameters.SolutionNumber = 3;

        Console.WriteLine("Selected elements in fourth best solution:");
        Console.Write("\t");
        for (e = 0; e < groundSetSize; e++) {
          if (Elem[e].PoolNX < .9) continue;
          Console.Write("El{0} ", e);
        }
        Console.WriteLine();
      }

      model.Dispose();
      env.Dispose();
    } catch (GRBException e) {
      Console.WriteLine("Error code: {0}. {1}", e.ErrorCode, e.Message);
    }
  }

}
```

qcp_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QCP model:

     maximize    x
     subject to  x + y + z = 1
                 x^2 + y^2 <= z^2 (second-order cone)
                 x^2 <= yz        (rotated second-order cone)
                 x, y, z non-negative
*/

using System;
```

(continues on next page)

(continued from previous page)

```
using Gurobi;

class qcp_cs
{
  static void Main()
  {
    try {
      GRBEnv    env   = new GRBEnv("qcp.log");
      GRBModel  model = new GRBModel(env);

      // Create variables

      GRBVar x = model.AddVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "x");
      GRBVar y = model.AddVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "y");
      GRBVar z = model.AddVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "z");

      // Set objective

      GRBLinExpr obj = x;
      model.SetObjective(obj, GRB.MAXIMIZE);

      // Add linear constraint: x + y + z = 1

      model.AddConstr(x + y + z == 1.0, "c0");

      // Add second-order cone: x^2 + y^2 <= z^2

      model.AddQConstr(x*x + y*y <= z*z, "qc0");

      // Add rotated cone: x^2 <= yz

      model.AddQConstr(x*x <= y*z, "qc1");

      // Optimize model

      model.Optimize();

      Console.WriteLine(x.VarName + " " + x.X);
      Console.WriteLine(y.VarName + " " + y.X);
      Console.WriteLine(z.VarName + " " + z.X);

      Console.WriteLine("Obj: " + model.ObjVal + " " + obj.Value);

      // Dispose of model and env

      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
```

(continues on next page)

(continued from previous page)

```
}
```

qp_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QP model:

     minimize    x^2 + x*y + y^2 + y*z + z^2 + 2 x
     subject to  x + 2 y + 3 z >= 4
                 x +   y       >= 1
                 x, y, z non-negative

   It solves it once as a continuous model, and once as an integer model.
*/

using System;
using Gurobi;

class qp_cs
{
  static void Main()
  {
    try {
      GRBEnv    env   = new GRBEnv("qp.log");
      GRBModel  model = new GRBModel(env);

      // Create variables

      GRBVar x = model.AddVar(0.0, 1.0, 0.0, GRB.CONTINUOUS, "x");
      GRBVar y = model.AddVar(0.0, 1.0, 0.0, GRB.CONTINUOUS, "y");
      GRBVar z = model.AddVar(0.0, 1.0, 0.0, GRB.CONTINUOUS, "z");

      // Set objective

      GRBQuadExpr obj = x*x + x*y + y*y + y*z + z*z + 2*x;
      model.SetObjective(obj);

      // Add constraint: x + 2 y + 3 z >= 4

      model.AddConstr(x + 2 * y + 3 * z >= 4.0, "c0");

      // Add constraint: x + y >= 1

      model.AddConstr(x + y >= 1.0, "c1");

      // Optimize model

      model.Optimize();
```

(continues on next page)

(continued from previous page)

```
      Console.WriteLine(x.VarName + " " + x.X);
      Console.WriteLine(y.VarName + " " + y.X);
      Console.WriteLine(z.VarName + " " + z.X);

      Console.WriteLine("Obj: " + model.ObjVal + " " + obj.Value);


      // Change variable types to integer

      x.VType = GRB.INTEGER;
      y.VType = GRB.INTEGER;
      z.VType = GRB.INTEGER;

      // Optimize model

      model.Optimize();

      Console.WriteLine(x.VarName + " " + x.X);
      Console.WriteLine(y.VarName + " " + y.X);
      Console.WriteLine(z.VarName + " " + z.X);

      Console.WriteLine("Obj: " + model.ObjVal + " " + obj.Value);

      // Dispose of model and env

      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

sensitivity_cs.cs

```
// Copyright 2026, Gurobi Optimization, LLC

// A simple sensitivity analysis example which reads a MIP model from a
// file and solves it. Then uses the scenario feature to analyze the impact
// w.r.t. the objective function of each binary variable if it is set to
// 1-X, where X is its value in the optimal solution.
//
// Usage:
//     sensitivity_cs <model filename>

using System;
using Gurobi;

class sensitivity_cs
```

(continues on next page)

(continued from previous page)

```
{
  // Maximum number of scenarios to be considered
  public const int MAXSCENARIOS = 100;

  static void Main(string[] args)
  {
    const int maxscenarios = sensitivity_cs.MAXSCENARIOS;

    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: sensitivity_cs filename");
      return;
    }

    try {

      // Create environment
      GRBEnv env = new GRBEnv();

      // Read model
      GRBModel model = new GRBModel(env, args[0]);

      int scenarios;

      if (model.IsMIP == 0) {
        Console.WriteLine("Model is not a MIP");
        return;
      }

      // Solve model
      model.Optimize();

      if (model.Status != GRB.Status.OPTIMAL) {
        Console.WriteLine("Optimization ended with status " + model.Status);
        return;
      }

      // Store the optimal solution
      double   origObjVal = model.ObjVal;
      GRBVar[] vars       = model.GetVars();
      double[] origX      = model.Get(GRB.DoubleAttr.X, vars);

      scenarios = 0;

      // Count number of unfixed, binary variables in model. For each we
      // create a scenario.
      for (int i = 0; i < vars.Length; i++) {
        GRBVar v     = vars[i];
        char   vType = v.VType;

        if (v.LB == 0.0 && v.UB == 1.0                    &&
            (vType == GRB.BINARY || vType == GRB.INTEGER)   ) {
          scenarios++;
```

(continues on next page)

(continued from previous page)

```
      if (scenarios >= maxscenarios)
        break;
    }
  }

  Console.WriteLine("###  construct multi-scenario model with "
                    + scenarios + " scenarios");

  // Set the number of scenarios in the model */
  model.NumScenarios = scenarios;

  scenarios = 0;

  // Create a (single) scenario model by iterating through unfixed
  // binary variables in the model and create for each of these
  // variables a scenario by fixing the variable to 1-X, where X is its
  // value in the computed optimal solution
  for (int i = 0; i < vars.Length; i++) {
    GRBVar v     = vars[i];
    char   vType = v.VType;

    if (v.LB == 0.0 && v.UB == 1.0                    &&
        (vType == GRB.BINARY || vType == GRB.INTEGER) &&
        scenarios < maxscenarios                        ) {

      // Set ScenarioNumber parameter to select the corresponding
      // scenario for adjustments
      model.Parameters.ScenarioNumber = scenarios;

      // Set variable to 1-X, where X is its value in the optimal solution */
      if (origX[i] < 0.5)
        v.ScenNLB = 1.0;
      else
        v.ScenNUB = 0.0;

      scenarios++;
    } else {
      // Add MIP start for all other variables using the optimal solution
      // of the base model
      v.Start = origX[i];
    }
  }

  // Solve multi-scenario model
  model.Optimize();

  // In case we solved the scenario model to optimality capture the
  // sensitivity information
  if (model.Status == GRB.Status.OPTIMAL) {

    // get the model sense (minimization or maximization)
```

(continues on next page)

(continued from previous page)

```
        int modelSense = model.ModelSense;

        scenarios = 0;

        for (int i = 0; i < vars.Length; i++) {
          GRBVar v     = vars[i];
          char   vType = v.VType;

          if (v.LB == 0.0 && v.UB == 1.0                    &&
              (vType == GRB.BINARY || vType == GRB.INTEGER)   ) {

            // Set scenario parameter to collect the objective value of the
            // corresponding scenario
            model.Parameters.ScenarioNumber = scenarios;

            double scenarioObjVal = model.ScenNObjVal;
            double scenarioObjBound = model.ScenNObjBound;

            Console.Write("Objective sensitivity for variable "
                          + v.VarName + " is ");

            // Check if we found a feasible solution for this scenario
            if (modelSense * scenarioObjVal >= GRB.INFINITY) {
              // Check if the scenario is infeasible
              if (modelSense * scenarioObjBound >= GRB.INFINITY)
                Console.WriteLine("infeasible");
              else
                Console.WriteLine("unknown (no solution available)");
            } else {
              // Scenario is feasible and a solution is available
              Console.WriteLine(modelSense * (scenarioObjVal - origObjVal));
            }

            scenarios++;

            if (scenarios >= maxscenarios)
              break;
          }
        }
      }

      // Dispose of model and environment
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode);
      Console.WriteLine(e.Message);
      Console.WriteLine(e.StackTrace);
    }
  }
}
```

sos_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example creates a very simple Special Ordered Set (SOS) model.
   The model consists of 3 continuous variables, no linear constraints,
   and a pair of SOS constraints of type 1. */

using System;
using Gurobi;

class sos_cs
{
  static void Main()
  {
    try {
      GRBEnv env = new GRBEnv();

      GRBModel model = new GRBModel(env);

      // Create variables

      double[] ub    = {1, 1, 2};
      double[] obj   = {-2, -1, -1};
      string[] names = {"x0", "x1", "x2"};

      GRBVar[] x = model.AddVars(null, ub, obj, null, names);

      // Add first SOS1: x0=0 or x1=0

      GRBVar[] sosv1  = {x[0], x[1]};
      double[] soswt1 = {1, 2};

      model.AddSOS(sosv1, soswt1, GRB.SOS_TYPE1);

      // Add second SOS1: x0=0 or x2=0

      GRBVar[] sosv2  = {x[0], x[2]};
      double[] soswt2 = {1, 2};

      model.AddSOS(sosv2, soswt2, GRB.SOS_TYPE1);

      // Optimize model

      model.Optimize();

      for (int i = 0; i < 3; i++)
        Console.WriteLine(x[i].VarName + " " + x[i].X);

      // Dispose of model and env
      model.Dispose();
      env.Dispose();
```

(continues on next page)

(continued from previous page)

```
    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

sudoku_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/*
  Sudoku example.

  The Sudoku board is a 9x9 grid, which is further divided into a 3x3 grid
  of 3x3 grids.  Each cell in the grid must take a value from 0 to 9.
  No two grid cells in the same row, column, or 3x3 subgrid may take the
  same value.

  In the MIP formulation, binary variables x[i,j,v] indicate whether
  cell <i,j> takes value 'v'.  The constraints are as follows:
    1. Each cell must take exactly one value (sum_v x[i,j,v] = 1)
    2. Each value is used exactly once per row (sum_i x[i,j,v] = 1)
    3. Each value is used exactly once per column (sum_j x[i,j,v] = 1)
    4. Each value is used exactly once per 3x3 subgrid (sum_grid x[i,j,v] = 1)

  Input datasets for this example can be found in examples/data/sudoku*.
*/

using System;
using System.IO;
using Gurobi;

class sudoku_cs
{
  static void Main(string[] args)
  {
    int n = 9;
    int s = 3;

    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: sudoku_cs filename");
      return;
    }

    try {
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env);

      // Create 3-D array of model variables
```

(continues on next page)

(continued from previous page)

```
    GRBVar[,,] vars = new GRBVar[n,n,n];

    for (int i = 0; i < n; i++) {
      for (int j = 0; j < n; j++) {
        for (int v = 0; v < n; v++) {
          string st = "G_" + i.ToString() + "_" + j.ToString()
                            + "_" + v.ToString();
          vars[i,j,v] = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, st);
        }
      }
    }

    // Add constraints

    GRBLinExpr expr;

    // Each cell must take one value

    for (int i = 0; i < n; i++) {
      for (int j = 0; j < n; j++) {
        expr = 0.0;
        for (int v = 0; v < n; v++)
          expr.AddTerm(1.0, vars[i,j,v]);
        string st = "V_" + i.ToString() + "_" + j.ToString();
        model.AddConstr(expr == 1.0, st);
      }
    }

    // Each value appears once per row

    for (int i = 0; i < n; i++) {
      for (int v = 0; v < n; v++) {
        expr = 0.0;
        for (int j = 0; j < n; j++)
          expr.AddTerm(1.0, vars[i,j,v]);
        string st = "R_" + i.ToString() + "_" + v.ToString();
        model.AddConstr(expr == 1.0, st);
      }
    }

    // Each value appears once per column

    for (int j = 0; j < n; j++) {
      for (int v = 0; v < n; v++) {
        expr = 0.0;
        for (int i = 0; i < n; i++)
          expr.AddTerm(1.0, vars[i,j,v]);
        string st = "C_" + j.ToString() + "_" + v.ToString();
        model.AddConstr(expr == 1.0, st);
      }
    }
```

(continues on next page)

(continued from previous page)

```
    // Each value appears once per sub-grid

    for (int v = 0; v < n; v++) {
      for (int i0 = 0; i0 < s; i0++) {
        for (int j0 = 0; j0 < s; j0++) {
          expr = 0.0;
          for (int i1 = 0; i1 < s; i1++) {
            for (int j1 = 0; j1 < s; j1++) {
              expr.AddTerm(1.0, vars[i0*s+i1,j0*s+j1,v]);
            }
          }
          string st = "Sub_" + v.ToString() + "_" + i0.ToString()
                            + "_" + j0.ToString();
          model.AddConstr(expr == 1.0, st);
        }
      }
    }

    // Fix variables associated with pre-specified cells

    StreamReader sr = File.OpenText(args[0]);

    for (int i = 0; i < n; i++) {
      string input = sr.ReadLine();
      for (int j = 0; j < n; j++) {
        int val = (int) input[j] - 48 - 1; // 0-based

        if (val >= 0)
          vars[i,j,val].LB = 1.0;
      }
    }

    // Optimize model

    model.Optimize();

    // Write model to file
    model.Write("sudoku.lp");

    double[,,] x = model.Get(GRB.DoubleAttr.X, vars);

    Console.WriteLine();
    for (int i = 0; i < n; i++) {
      for (int j = 0; j < n; j++) {
        for (int v = 0; v < n; v++) {
          if (x[i,j,v] > 0.5) {
            Console.Write(v+1);
          }
        }
      }
      Console.WriteLine();
    }
```

(continues on next page)

(continued from previous page)

```
      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

tsp_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

// Solve a traveling salesman problem on a randomly generated set of
// points using lazy constraints.   The base MIP model only includes
// 'degree-2' constraints, requiring each node to have exactly
// two incident edges.  Solutions to this model may contain subtours -
// tours that don't visit every node.  The lazy constraint callback
// adds new constraints to cut them off.

using System;
using Gurobi;

class tsp_cs : GRBCallback {
  private GRBVar[,] vars;

  public tsp_cs(GRBVar[,] xvars) {
    vars = xvars;
  }

  // Subtour elimination callback.  Whenever a feasible solution is found,
  // find the smallest subtour, and add a subtour elimination
  // constraint if the tour doesn't visit every node.

  protected override void Callback() {
    try {
      if (where == GRB.Callback.MIPSOL) {
        // Found an integer feasible solution - does it visit every node?

        int n = vars.GetLength(0);
        int[] tour = findsubtour(GetSolution(vars));

        if (tour.Length < n) {
          // Add subtour elimination constraint
          GRBLinExpr expr = 0;
          for (int i = 0; i < tour.Length; i++)
            for (int j = i+1; j < tour.Length; j++)
              expr.AddTerm(1.0, vars[tour[i], tour[j]]);
```

(continues on next page)

(continued from previous page)

```
          AddLazy(expr <= tour.Length-1);
        }
      }
    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
      Console.WriteLine(e.StackTrace);
    }
  }

  // Given an integer-feasible solution 'sol', return the smallest
  // sub-tour (as a list of node indices).

  protected static int[] findsubtour(double[,] sol)
  {
    int n = sol.GetLength(0);
    bool[] seen = new bool[n];
    int[] tour = new int[n];
    int bestind, bestlen;
    int i, node, len, start;

    for (i = 0; i < n; i++)
      seen[i] = false;

    start = 0;
    bestlen = n+1;
    bestind = -1;
    node = 0;
    while (start < n) {
      for (node = 0; node < n; node++)
        if (!seen[node])
          break;
      if (node == n)
        break;
      for (len = 0; len < n; len++) {
        tour[start+len] = node;
        seen[node] = true;
        for (i = 0; i < n; i++) {
          if (sol[node, i] > 0.5 && !seen[i]) {
            node = i;
            break;
          }
        }
        if (i == n) {
          len++;
          if (len < bestlen) {
            bestlen = len;
            bestind = start;
          }
          start += len;
          break;
        }
      }
```

(continues on next page)

(continued from previous page)

```
  }

  for (i = 0; i < bestlen; i++)
    tour[i] = tour[bestind+i];
  System.Array.Resize(ref tour, bestlen);

  return tour;
}

// Euclidean distance between points 'i' and 'j'

protected static double distance(double[] x,
                                 double[] y,
                                 int      i,
                                 int      j) {
  double dx = x[i]-x[j];
  double dy = y[i]-y[j];
  return Math.Sqrt(dx*dx+dy*dy);
}

public static void Main(String[] args) {

  if (args.Length < 1) {
    Console.WriteLine("Usage: tsp_cs nnodes");
    return;
  }

  int n = Convert.ToInt32(args[0]);

  try {
    GRBEnv   env   = new GRBEnv();
    GRBModel model = new GRBModel(env);

    // Must set LazyConstraints parameter when using lazy constraints

    model.Parameters.LazyConstraints = 1;

    double[] x = new double[n];
    double[] y = new double[n];

    Random r = new Random();
    for (int i = 0; i < n; i++) {
      x[i] = r.NextDouble();
      y[i] = r.NextDouble();
    }

    // Create variables

    GRBVar[,] vars = new GRBVar[n, n];

    for (int i = 0; i < n; i++) {
      for (int j = 0; j <= i; j++) {
```

(continues on next page)

(continued from previous page)

```
          vars[i, j] = model.AddVar(0.0, 1.0, distance(x, y, i, j),
                                    GRB.BINARY, "x"+i+"_"+j);
          vars[j, i] = vars[i, j];
        }
      }

      // Degree-2 constraints

      for (int i = 0; i < n; i++) {
        GRBLinExpr expr = 0;
        for (int j = 0; j < n; j++)
          expr.AddTerm(1.0, vars[i, j]);
        model.AddConstr(expr == 2.0, "deg2_"+i);
      }

      // Forbid edge from node back to itself

      for (int i = 0; i < n; i++)
        vars[i, i].UB = 0.0;

      model.SetCallback(new tsp_cs(vars));
      model.Optimize();

      if (model.SolCount > 0) {
        int[] tour = findsubtour(model.Get(GRB.DoubleAttr.X, vars));

        Console.Write("Tour: ");
        for (int i = 0; i < tour.Length; i++)
          Console.Write(tour[i] + " ");
        Console.WriteLine();
      }

      // Dispose of model and environment
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
      Console.WriteLine(e.StackTrace);
    }
  }
}
```

tune_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a model from a file and tunes it.
   It then writes the best parameter settings to a file
   and solves the model using these parameters. */

using System;
using Gurobi;

class tune_cs
{
  static void Main(string[] args)
  {
    if (args.Length < 1) {
      Console.Out.WriteLine("Usage: tune_cs filename");
      return;
    }

    try {
      GRBEnv env = new GRBEnv();

      // Read model from file
      GRBModel model = new GRBModel(env, args[0]);

      // Set a time limit for the model
      model.Parameters.TimeLimit = 5;

      // Set a time limit for the whol tuning run
      // Note that both time limits are chosen to have a quick demonstration.
      // In general, a total tune time limit should be set such that the
      // tuning tool can test several hundreds of parameter setting
      model.Parameters.TuneTimeLimit = 60;

      // Set the TuneResults parameter to 2
      //
      // The first parameter setting is the result for the first solved
      // setting. The second entry the parameter setting of the best
      // parameter setting.
      model.Parameters.TuneResults = 2;

      // Tune the model
      model.Tune();

      // Get the number of tuning results
      int resultcount = model.TuneResultCount;

      if (resultcount >= 2) {

        // Load the tuned parameters into the model's environment
        //
        // Note, the first parameter setting is associated to the first
```

(continues on next page)

(continued from previous page)

```
        // solved setting and the second parameter setting to best tune
        // result.
        model.GetTuneResult(1);

        // Write the tuned parameters to a file
        model.Write("tune.prm");

        // Solve the model using the tuned parameters
        model.Optimize();
      }

      // Dispose of model and environment
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " + e.Message);
    }
  }
}
```

workforce1_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, use IIS to find a set of
   conflicting constraints. Note that there may be additional conflicts
   besides what is reported via IIS. */

using System;
using Gurobi;

class workforce1_cs
{
  static void Main()
  {
    try {

      // Sample data
      // Sets of days and workers
      string[] Shifts =
          new string[] { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
              "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
              "Sun14" };
      string[] Workers =
          new string[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

      int nShifts = Shifts.Length;
      int nWorkers = Workers.Length;
```

(continues on next page)

(continued from previous page)

```
// Number of workers required for each shift
double[] shiftRequirements =
    new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

// Amount each worker is paid to work one shift
double[] pay = new double[] { 10, 12, 10, 8, 8, 9, 11 };

// Worker availability: 0 if the worker is unavailable for a shift
double[,] availability =
    new double[,] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
        { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
        { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
        { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
        { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
        { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
        { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

// Model
GRBEnv env = new GRBEnv();
GRBModel model = new GRBModel(env);

model.ModelName = "assignment";

// Assignment variables: x[w][s] == 1 if worker w is assigned
// to shift s. Since an assignment model always produces integer
// solutions, we use continuous variables and solve as an LP.
GRBVar[,] x = new GRBVar[nWorkers,nShifts];
for (int w = 0; w < nWorkers; ++w) {
  for (int s = 0; s < nShifts; ++s) {
    x[w,s] =
        model.AddVar(0, availability[w,s], pay[w], GRB.CONTINUOUS,
                     Workers[w] + "." + Shifts[s]);
  }
}

// The objective is to minimize the total pay costs
model.ModelSense = GRB.MINIMIZE;

// Constraint: assign exactly shiftRequirements[s] workers
// to each shift s
for (int s = 0; s < nShifts; ++s) {
  GRBLinExpr lhs = 0.0;
  for (int w = 0; w < nWorkers; ++w)
    lhs.AddTerm(1.0, x[w, s]);
  model.AddConstr(lhs == shiftRequirements[s], Shifts[s]);
}

// Optimize
model.Optimize();
int status = model.Status;
if (status == GRB.Status.UNBOUNDED) {
```

(continues on next page)

(continued from previous page)

```
        Console.WriteLine("The model cannot be solved "
            + "because it is unbounded");
        return;
      }
      if (status == GRB.Status.OPTIMAL) {
        Console.WriteLine("The optimal objective is " + model.ObjVal);
        return;
      }
      if ((status != GRB.Status.INF_OR_UNBD) &&
          (status != GRB.Status.INFEASIBLE)) {
        Console.WriteLine("Optimization was stopped with status " + status);
        return;
      }

      // Do IIS
      Console.WriteLine("The model is infeasible; computing IIS");
      model.ComputeIIS();
      Console.WriteLine("\nThe following constraint(s) "
          + "cannot be satisfied:");
      foreach (GRBConstr c in model.GetConstrs()) {
        if (c.IISConstr == 1) {
          Console.WriteLine(c.ConstrName);
        }
      }

      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " +
          e.Message);
    }
  }
}
```

workforce2_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, use IIS iteratively to
   find all conflicting constraints. */

using System;
using System.Collections.Generic;
using Gurobi;

class workforce2_cs
{
```

(continues on next page)

(continued from previous page)

```
static void Main()
{
  try {

    // Sample data
    // Sets of days and workers
    string[] Shifts =
        new string[] { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
            "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
            "Sun14" };
    string[] Workers =
        new string[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

    int nShifts = Shifts.Length;
    int nWorkers = Workers.Length;

    // Number of workers required for each shift
    double[] shiftRequirements =
        new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

    // Amount each worker is paid to work one shift
    double[] pay = new double[] { 10, 12, 10, 8, 8, 9, 11 };

    // Worker availability: 0 if the worker is unavailable for a shift
    double[,] availability =
        new double[,] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
            { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
            { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
            { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
            { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
            { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
            { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

    // Model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env);

    model.ModelName = "assignment";

    // Assignment variables: x[w][s] == 1 if worker w is assigned
    // to shift s. Since an assignment model always produces integer
    // solutions, we use continuous variables and solve as an LP.
    GRBVar[,] x = new GRBVar[nWorkers,nShifts];
    for (int w = 0; w < nWorkers; ++w) {
      for (int s = 0; s < nShifts; ++s) {
        x[w,s] =
            model.AddVar(0, availability[w,s], pay[w], GRB.CONTINUOUS,
                         Workers[w] + "." + Shifts[s]);
      }
    }

    // The objective is to minimize the total pay costs
```

(continues on next page)

(continued from previous page)

```
    model.ModelSense = GRB.MINIMIZE;

    // Constraint: assign exactly shiftRequirements[s] workers
    // to each shift s
    for (int s = 0; s < nShifts; ++s) {
      GRBLinExpr lhs = 0.0;
      for (int w = 0; w < nWorkers; ++w)
        lhs.AddTerm(1.0, x[w, s]);
      model.AddConstr(lhs == shiftRequirements[s], Shifts[s]);
    }

    // Optimize
    model.Optimize();
    int status = model.Status;
    if (status == GRB.Status.UNBOUNDED) {
      Console.WriteLine("The model cannot be solved "
          + "because it is unbounded");
      return;
    }
    if (status == GRB.Status.OPTIMAL) {
      Console.WriteLine("The optimal objective is " + model.ObjVal);
      return;
    }
    if ((status != GRB.Status.INF_OR_UNBD) &&
        (status != GRB.Status.INFEASIBLE)) {
      Console.WriteLine("Optimization was stopped with status " + status);
      return;
    }

    // Do IIS
    Console.WriteLine("The model is infeasible; computing IIS");
    LinkedList<string> removed = new LinkedList<string>();

    // Loop until we reduce to a model that can be solved
    while (true) {
      model.ComputeIIS();
      Console.WriteLine("\nThe following constraint cannot be satisfied:");
      foreach (GRBConstr c in model.GetConstrs()) {
        if (c.IISConstr == 1) {
          Console.WriteLine(c.ConstrName);
          // Remove a single constraint from the model
          removed.AddFirst(c.ConstrName);
          model.Remove(c);
          break;
        }
      }

      Console.WriteLine();
      model.Optimize();
      status = model.Status;

      if (status == GRB.Status.UNBOUNDED) {
```

(continues on next page)

(continued from previous page)

```
          Console.WriteLine("The model cannot be solved "
              + "because it is unbounded");
          return;
        }
        if (status == GRB.Status.OPTIMAL) {
          break;
        }
        if ((status != GRB.Status.INF_OR_UNBD) &&
            (status != GRB.Status.INFEASIBLE)) {
          Console.WriteLine("Optimization was stopped with status " +
              status);
          return;
        }
      }

      Console.WriteLine("\nThe following constraints were removed "
          + "to get a feasible LP:");
      foreach (string s in removed) {
        Console.Write(s + " ");
      }
      Console.WriteLine();

      // Dispose of model and env
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " +
          e.Message);
    }
  }
}
```

workforce3_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, relax the model
   to determine which constraints cannot be satisfied, and how much
   they need to be relaxed. */

using System;
using Gurobi;

class workforce3_cs
{
  static void Main()
  {
    try {
```

(continues on next page)

(continued from previous page)

```
// Sample data
// Sets of days and workers
string[] Shifts =
    new string[] { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
        "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
        "Sun14" };
string[] Workers =
    new string[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

int nShifts = Shifts.Length;
int nWorkers = Workers.Length;

// Number of workers required for each shift
double[] shiftRequirements =
    new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

// Amount each worker is paid to work one shift
double[] pay = new double[] { 10, 12, 10, 8, 8, 9, 11 };

// Worker availability: 0 if the worker is unavailable for a shift
double[,] availability =
    new double[,] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
        { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
        { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
        { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
        { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
        { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
        { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

// Model
GRBEnv env = new GRBEnv();
GRBModel model = new GRBModel(env);

model.ModelName = "assignment";

// Assignment variables: x[w][s] == 1 if worker w is assigned
// to shift s. Since an assignment model always produces integer
// solutions, we use continuous variables and solve as an LP.
GRBVar[,] x = new GRBVar[nWorkers,nShifts];
for (int w = 0; w < nWorkers; ++w) {
  for (int s = 0; s < nShifts; ++s) {
    x[w,s] =
        model.AddVar(0, availability[w,s], pay[w], GRB.CONTINUOUS,
                     Workers[w] + "." + Shifts[s]);
  }
}

// The objective is to minimize the total pay costs
model.ModelSense = GRB.MINIMIZE;

// Constraint: assign exactly shiftRequirements[s] workers
```

(continues on next page)

(continued from previous page)

```
    // to each shift s
    for (int s = 0; s < nShifts; ++s) {
      GRBLinExpr lhs = 0.0;
      for (int w = 0; w < nWorkers; ++w) {
        lhs.AddTerm(1.0, x[w,s]);
      }
      model.AddConstr(lhs == shiftRequirements[s], Shifts[s]);
    }

    // Optimize
    model.Optimize();
    int status = model.Status;
    if (status == GRB.Status.UNBOUNDED) {
      Console.WriteLine("The model cannot be solved "
          + "because it is unbounded");
      return;
    }
    if (status == GRB.Status.OPTIMAL) {
      Console.WriteLine("The optimal objective is " + model.ObjVal);
      return;
    }
    if ((status != GRB.Status.INF_OR_UNBD) &&
        (status != GRB.Status.INFEASIBLE)) {
      Console.WriteLine("Optimization was stopped with status " + status);
      return;
    }

    // Relax the constraints to make the model feasible
    Console.WriteLine("The model is infeasible; relaxing the constraints");
    int orignumvars = model.NumVars;
    model.FeasRelax(0, false, false, true);
    model.Optimize();
    status = model.Status;
    if ((status == GRB.Status.INF_OR_UNBD) ||
        (status == GRB.Status.INFEASIBLE) ||
        (status == GRB.Status.UNBOUNDED)) {
      Console.WriteLine("The relaxed model cannot be solved "
          + "because it is infeasible or unbounded");
      return;
    }
    if (status != GRB.Status.OPTIMAL) {
      Console.WriteLine("Optimization was stopped with status " + status);
      return;
    }

    Console.WriteLine("\nSlack values:");
    GRBVar[] vars = model.GetVars();
    for (int i = orignumvars; i < model.NumVars; ++i) {
      GRBVar sv = vars[i];
      if (sv.X > 1e-6) {
        Console.WriteLine(sv.VarName + " = " + sv.X);
      }
```

(continues on next page)

(continued from previous page)

```
      }

      // Dispose of model and environment
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: " + e.ErrorCode + ". " +
          e.Message);
    }
  }
}
```

workforce4_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. We use Pareto optimization to solve the model:
   first, we minimize the linear sum of the slacks. Then, we constrain
   the sum of the slacks, and we minimize a quadratic objective that
   tries to balance the workload among the workers. */

using System;
using Gurobi;

class workforce4_cs
{
  static void Main()
  {
    try {

      // Sample data
      // Sets of days and workers
      string[] Shifts =
          new string[] { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
              "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
              "Sun14" };
      string[] Workers =
          new string[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

      int nShifts = Shifts.Length;
      int nWorkers = Workers.Length;

      // Number of workers required for each shift
      double[] shiftRequirements =
          new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

      // Worker availability: 0 if the worker is unavailable for a shift
      double[,] availability =
```

(continues on next page)

(continued from previous page)

```
        new double[,] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
            { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
            { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
            { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
            { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
            { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
            { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

    // Model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env);

    model.ModelName = "assignment";

    // Assignment variables: x[w][s] == 1 if worker w is assigned
    // to shift s. This is no longer a pure assignment model, so we must
    // use binary variables.
    GRBVar[,] x = new GRBVar[nWorkers, nShifts];
    for (int w = 0; w < nWorkers; ++w) {
      for (int s = 0; s < nShifts; ++s) {
        x[w,s] =
            model.AddVar(0, availability[w,s], 0, GRB.BINARY,
                         Workers[w] + "." + Shifts[s]);
      }
    }

    // Slack variables for each shift constraint so that the shifts can
    // be satisfied
    GRBVar[] slacks = new GRBVar[nShifts];
    for (int s = 0; s < nShifts; ++s) {
      slacks[s] =
        model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                     Shifts[s] + "Slack");
    }

    // Variable to represent the total slack
    GRBVar totSlack = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                   "totSlack");

    // Variables to count the total shifts worked by each worker
    GRBVar[] totShifts = new GRBVar[nWorkers];
    for (int w = 0; w < nWorkers; ++w) {
      totShifts[w] = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                  Workers[w] + "TotShifts");
    }

    GRBLinExpr lhs;

    // Constraint: assign exactly shiftRequirements[s] workers
    // to each shift s, plus the slack
    for (int s = 0; s < nShifts; ++s) {
      lhs = new GRBLinExpr();
```

(continues on next page)

(continued from previous page)

```
      lhs.AddTerm(1.0, slacks[s]);
      for (int w = 0; w < nWorkers; ++w) {
        lhs.AddTerm(1.0, x[w, s]);
      }
      model.AddConstr(lhs == shiftRequirements[s], Shifts[s]);
    }

    // Constraint: set totSlack equal to the total slack
    lhs = new GRBLinExpr();
    for (int s = 0; s < nShifts; ++s) {
      lhs.AddTerm(1.0, slacks[s]);
    }
    model.AddConstr(lhs == totSlack, "totSlack");

    // Constraint: compute the total number of shifts for each worker
    for (int w = 0; w < nWorkers; ++w) {
      lhs = new GRBLinExpr();
      for (int s = 0; s < nShifts; ++s) {
        lhs.AddTerm(1.0, x[w, s]);
      }
      model.AddConstr(lhs == totShifts[w], "totShifts" + Workers[w]);
    }

    // Objective: minimize the total slack
    model.SetObjective(1.0*totSlack);

    // Optimize
    int status = solveAndPrint(model, totSlack, nWorkers, Workers, totShifts);
    if (status != GRB.Status.OPTIMAL) {
      return;
    }

    // Constrain the slack by setting its upper and lower bounds
    totSlack.UB = totSlack.X;
    totSlack.LB = totSlack.X;

    // Variable to count the average number of shifts worked
    GRBVar avgShifts =
      model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS, "avgShifts");

    // Variables to count the difference from average for each worker;
    // note that these variables can take negative values.
    GRBVar[] diffShifts = new GRBVar[nWorkers];
    for (int w = 0; w < nWorkers; ++w) {
      diffShifts[w] = model.AddVar(-GRB.INFINITY, GRB.INFINITY, 0,
                                   GRB.CONTINUOUS, Workers[w] + "Diff");
    }

    // Constraint: compute the average number of shifts worked
    lhs = new GRBLinExpr();
    for (int w = 0; w < nWorkers; ++w) {
      lhs.AddTerm(1.0, totShifts[w]);
```

(continues on next page)

(continued from previous page)

```
    }
    model.AddConstr(lhs == nWorkers * avgShifts, "avgShifts");

    // Constraint: compute the difference from the average number of shifts
    for (int w = 0; w < nWorkers; ++w) {
      model.AddConstr(totShifts[w] - avgShifts == diffShifts[w],
                      Workers[w] + "Diff");
    }

    // Objective: minimize the sum of the square of the difference from the
    // average number of shifts worked
    GRBQuadExpr qobj = new GRBQuadExpr();
    for (int w = 0; w < nWorkers; ++w) {
      qobj.AddTerm(1.0, diffShifts[w], diffShifts[w]);
    }
    model.SetObjective(qobj);

    // Optimize
    status = solveAndPrint(model, totSlack, nWorkers, Workers, totShifts);
    if (status != GRB.Status.OPTIMAL) {
      return;
    }

    // Dispose of model and env
    model.Dispose();
    env.Dispose();

  } catch (GRBException e) {
    Console.WriteLine("Error code: " + e.ErrorCode + ". " +
        e.Message);
  }
}

private static int solveAndPrint(GRBModel model, GRBVar totSlack,
                                 int nWorkers, String[] Workers,
                                 GRBVar[] totShifts)
{
  model.Optimize();
  int status = model.Status;
  if ((status == GRB.Status.INF_OR_UNBD) ||
      (status == GRB.Status.INFEASIBLE) ||
      (status == GRB.Status.UNBOUNDED)) {
    Console.WriteLine("The model cannot be solved "
        + "because it is infeasible or unbounded");
    return status;
  }
  if (status != GRB.Status.OPTIMAL) {
    Console.WriteLine("Optimization was stopped with status " + status);
    return status;
  }

  // Print total slack and the number of shifts worked for each worker
```

(continues on next page)

(continued from previous page)

```
    Console.WriteLine("\nTotal slack required: " + totSlack.X);
    for (int w = 0; w < nWorkers; ++w) {
      Console.WriteLine(Workers[w] + " worked " +
                        totShifts[w].X + " shifts");
    }
    Console.WriteLine("\n");
    return status;
  }
}
```

workforce5_cs.cs

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. We use multi-objective optimization to solve the model.
   The highest-priority objective minimizes the sum of the slacks
   (i.e., the total number of uncovered shifts). The secondary objective
   minimizes the difference between the maximum and minimum number of
   shifts worked among all workers.  The second optimization is allowed
   to degrade the first objective by up to the smaller value of 10% and 2 */

using System;
using Gurobi;

class workforce5_cs
{
  static void Main()
  {
    try {

      // Sample data
      // Sets of days and workers
      string[] Shifts =
          new string[]  { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
              "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
              "Sun14" };
      string[] Workers =
          new string[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu", "Tobi" };

      int nShifts = Shifts.Length;
      int nWorkers = Workers.Length;

      // Number of workers required for each shift
      double[] shiftRequirements =
          new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

      // Worker availability: 0 if the worker is unavailable for a shift
      double[,] availability =
          new double[,] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
```

(continues on next page)

(continued from previous page)

```
            { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
            { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
            { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
            { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
            { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
            { 0, 1, 1, 1, 0, 1, 1, 0, 1, 1, 1, 0, 1, 1 },
            { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

      // Create environment
      GRBEnv env = new GRBEnv();

      // Create initial model
      GRBModel model = new GRBModel(env);
      model.ModelName = "workforce5_cs";

      // Initialize assignment decision variables:
      // x[w][s] == 1 if worker w is assigned to shift s.
      // This is no longer a pure assignment model, so we must
      // use binary variables.
      GRBVar[,] x = new GRBVar[nWorkers, nShifts];
      for (int w = 0; w < nWorkers; ++w) {
        for (int s = 0; s < nShifts; ++s) {
          x[w,s] =
              model.AddVar(0, availability[w,s], 0, GRB.BINARY,
                           string.Format("{0}.{1}", Workers[w], Shifts[s]));
        }
      }

      // Slack variables for each shift constraint so that the shifts can
      // be satisfied
      GRBVar[] slacks = new GRBVar[nShifts];
      for (int s = 0; s < nShifts; ++s) {
        slacks[s] =
            model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                         string.Format("{0}Slack", Shifts[s]));
      }

      // Variable to represent the total slack
      GRBVar totSlack = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                     "totSlack");

      // Variables to count the total shifts worked by each worker
      GRBVar[] totShifts = new GRBVar[nWorkers];
      for (int w = 0; w < nWorkers; ++w) {
        totShifts[w] = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                    string.Format("{0}TotShifts", Workers[w]));
      }

      GRBLinExpr lhs;

      // Constraint: assign exactly shiftRequirements[s] workers
      // to each shift s, plus the slack
```

(continues on next page)

(continued from previous page)

```
      for (int s = 0; s < nShifts; ++s) {
        lhs = new GRBLinExpr();
        lhs.AddTerm(1.0, slacks[s]);
        for (int w = 0; w < nWorkers; ++w) {
          lhs.AddTerm(1.0, x[w,s]);
        }
        model.AddConstr(lhs, GRB.EQUAL, shiftRequirements[s], Shifts[s]);
      }

      // Constraint: set totSlack equal to the total slack
      lhs = new GRBLinExpr();
      lhs.AddTerm(-1.0, totSlack);
      for (int s = 0; s < nShifts; ++s) {
        lhs.AddTerm(1.0, slacks[s]);
      }
      model.AddConstr(lhs, GRB.EQUAL, 0, "totSlack");

      // Constraint: compute the total number of shifts for each worker
      for (int w = 0; w < nWorkers; ++w) {
        lhs = new GRBLinExpr();
        lhs.AddTerm(-1.0, totShifts[w]);
        for (int s = 0; s < nShifts; ++s) {
          lhs.AddTerm(1.0, x[w,s]);
        }
        model.AddConstr(lhs, GRB.EQUAL, 0, string.Format("totShifts{0}", Workers[w]));
      }

      // Constraint: set minShift/maxShift variable to less <=/>= to the
      // number of shifts among all workers
      GRBVar minShift = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                     "minShift");
      GRBVar maxShift = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                     "maxShift");
      model.AddGenConstrMin(minShift, totShifts, GRB.INFINITY, "minShift");
      model.AddGenConstrMax(maxShift, totShifts, -GRB.INFINITY, "maxShift");

      // Set global sense for ALL objectives
      model.ModelSense = GRB.MINIMIZE;

      // Set primary objective
      model.SetObjectiveN(totSlack, 0, 2, 1.0, 2.0, 0.1, "TotalSlack");

      // Set secondary objective
      model.SetObjectiveN(maxShift - minShift, 1, 1, 1.0, 0, 0, "Fairness");

      // Save problem
      model.Write("workforce5_cs.lp");

      // Optimize
      int status = solveAndPrint(model, totSlack, nWorkers, Workers, totShifts);

      if (status != GRB.Status.OPTIMAL)
```

(continues on next page)

(continued from previous page)

```
        return;

      // Dispose of model and environment
      model.Dispose();
      env.Dispose();

    } catch (GRBException e) {
      Console.WriteLine("Error code: {0}. {1}", e.ErrorCode, e.Message);
    }
  }

  private static int solveAndPrint(GRBModel model, GRBVar totSlack,
                                   int nWorkers, String[] Workers,
                                   GRBVar[] totShifts)
  {

    model.Optimize();
    int status = model.Status;
    if (status == GRB.Status.INF_OR_UNBD ||
        status == GRB.Status.INFEASIBLE  ||
        status == GRB.Status.UNBOUNDED     ) {
      Console.WriteLine("The model cannot be solved "
          + "because it is infeasible or unbounded");
      return status;
    }
    if (status != GRB.Status.OPTIMAL ) {
      Console.WriteLine("Optimization was stopped with status {0}", status);
      return status;
    }

    // Print total slack and the number of shifts worked for each worker
    Console.WriteLine("\nTotal slack required: {0}", totSlack.X);
    for (int w = 0; w < nWorkers; ++w) {
      Console.WriteLine("{0} worked {1} shifts", Workers[w], totShifts[w].X);
    }
    Console.WriteLine("\n");
    return status;
  }

}
```

2.1.4 Java Examples

This section includes source code for all of the Gurobi Java examples. The same source code can be found in the `examples/java` directory of the Gurobi distribution.

Batchmode.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a model from a file, solves it in batch mode
 * and prints the JSON solution string. */

import com.gurobi.gurobi.*;

public class Batchmode {

  // Set-up a batch-mode environment
  private static GRBEnv setupbatchconnection() throws GRBException {
    GRBEnv env = new GRBEnv(true);
    env.set(GRB.IntParam.CSBatchMode,       1);
    env.set(GRB.StringParam.LogFile,        "batchmode.log");
    env.set(GRB.StringParam.CSManager,      "http://localhost:61080");
    env.set(GRB.StringParam.UserName,       "gurobi");
    env.set(GRB.StringParam.ServerPassword, "pass");
    env.start();
    return env;
  }

  // Display batch-error if any
  private static void batcherrorinfo(GRBBatch batch) throws GRBException {
    // Get last error code
    int error = batch.get(GRB.IntAttr.BatchErrorCode);
    if (error == 0) return;

    // Query last error message
    String errMsg = batch.get(GRB.StringAttr.BatchErrorMessage);

    // Query batchID
    String batchID = batch.get(GRB.StringAttr.BatchID);

    System.out.println("Batch ID " + batchID + "Error Code " +
                       error + "(" + errMsg + ")");
  }

  // Create a batch request from the given problem file
  private static String newbatchrequest(String filename) throws GRBException {
    // Setup a batch connection
    GRBEnv env = setupbatchconnection();

    // Read a model
    GRBModel model = new GRBModel(env, filename);
```

(continues on next page)

(continued from previous page)

```
    // Set some parameters
    model.set(GRB.DoubleParam.MIPGap,     0.01);
    model.set(GRB.IntParam.JSONSolDetail, 1);

    // Set-up some tags, we need tags to be able to query results
    int count = 0;
    for (GRBVar v: model.getVars()) {
      v.set(GRB.StringAttr.VTag, "UniqueVariableIdentifier" + count);
      count += 1;
      if (count >= 10) break;
    }

    // Batch-mode optimization
    String batchid = model.optimizeBatch();

    // no need to keep the model around
    model.dispose();

    // no need to keep environment
    env.dispose();

    return batchid;
  }

  // Wait for final status
  private static void waitforfinalstatus(String batchid) throws Exception {
    // Setup a batch connection
    GRBEnv env = setupbatchconnection();

    // Create Batch-object
    GRBBatch batch = new GRBBatch(env, batchid);

    try {
      // Query status, and wait for completed
      int status = batch.get(GRB.IntAttr.BatchStatus);
      long timestart = System.currentTimeMillis();

      while(status == GRB.BatchStatus.SUBMITTED) {

        // Abort if taking too long
        long curtime = System.currentTimeMillis();
        if (curtime - timestart > 3600 * 1000) {
          // Request to abort the batch
          batch.abort();
          break;
        }

        // Do not bombard the server
        Thread.sleep(2000);

        // Update local attributes
        batch.update();
```

(continues on next page)

(continued from previous page)

```
      // Query current status
      status = batch.get(GRB.IntAttr.BatchStatus);

      // Deal with failed status
      if (status == GRB.BatchStatus.FAILED ||
          status == GRB.BatchStatus.ABORTED  ) {
        // Retry the batch job
        batch.retry();
      }
    }

  } catch (Exception e) {
    // Display batch-error if any
    batcherrorinfo(batch);
    throw e;
  } finally {
    // Dispose resources
    batch.dispose();
    env.dispose();
  }
}

// Final report on batch request
private static void finalreport(String batchid) throws GRBException {

  // Setup a batch connection
  GRBEnv env = setupbatchconnection();

  // Create batch object
  GRBBatch batch = new GRBBatch(env, batchid);

  try {
    int status = batch.get(GRB.IntAttr.BatchStatus);
    // Display depending on batch status
    switch(status) {
      case GRB.BatchStatus.CREATED:
        System.out.println("Batch is 'CREATED'");
        System.out.println("maybe batch-creation process was killed?");
        break;
      case GRB.BatchStatus.SUBMITTED:
        System.out.println("Batch is 'SUBMITTED'");
        System.out.println("Some other user re-submitted this Batch object?");
        break;
      case GRB.BatchStatus.ABORTED:
        System.out.println("Batch is 'ABORTED'");
        break;
      case GRB.BatchStatus.FAILED:
        System.out.println("Batch is 'FAILED'");
        break;
      case GRB.BatchStatus.COMPLETED:
```

(continues on next page)

(continued from previous page)

```
          // print JSON solution into string
          System.out.println("JSON solution:" + batch.getJSONSolution());

          // save solution into a file
          batch.writeJSONSolution("batch-sol.json.gz");
          break;
        default:
          System.out.println("This should not happen, probably points to a user-memory␣
↪corruption problem");
          System.exit(1);
          break;

      }
    } catch (GRBException e) {
      // Display batch-error if any
      batcherrorinfo(batch);
      throw e;
    } finally {
      // Dispose resources
      batch.dispose();
      env.dispose();
    }
  }

  // Discard batch data from the Cluster Manager
  private static void discardbatch(String batchid) throws GRBException {
    // Setup a batch connection
    GRBEnv env = setupbatchconnection();

    // Create batch object
    GRBBatch batch = new GRBBatch(env, batchid);

    try {
      // Request to erase input and output data related to this batch
      batch.discard();
    } catch (GRBException e) {
      // Display batch-error if any
      batcherrorinfo(batch);
      throw e;
    } finally {
      // Dispose resources
      batch.dispose();
      env.dispose();
    }

  }

  // Main public function
  public static void main(String[] args) {

    // Ensure enough parameters
    if (args.length < 1) {
```

(continues on next page)

(continued from previous page)

```
      System.out.println("Usage: java Batch filename");
      System.exit(1);
    }

    try {

      // Create a new batch request
      String batchid = newbatchrequest(args[0]);

      // Wait for final status
      waitforfinalstatus(batchid);

      // Query final status, and if completed, print JSON solution
      finalreport(batchid);

      // once the user is done, discard all remote information
      discardbatch(batchid);

      // Signal success
      System.out.println("OK");
    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". "
          + e.getMessage());
    } catch (Exception e) {
      System.out.println("Error");
    }
  }
}
```

Bilinear.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple bilinear model:

     maximize    x
     subject to  x + y + z <= 10
                 x * y <= 2          (bilinear inequality)
                 x * z + y * z == 1  (bilinear equality)
                 x, y, z non-negative (x integral in second version)
*/

import com.gurobi.gurobi.*;

public class Bilinear {
  public static void main(String[] args) {
    try {
      GRBEnv    env   = new GRBEnv("bilinear.log");
      GRBModel  model = new GRBModel(env);
```

(continues on next page)

(continued from previous page)

```
    // Create variables

    GRBVar x = model.addVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "x");
    GRBVar y = model.addVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "y");
    GRBVar z = model.addVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "z");

    // Set objective

    GRBLinExpr obj = new GRBLinExpr();
    obj.addTerm(1.0, x);
    model.setObjective(obj, GRB.MAXIMIZE);

    // Add linear constraint: x + y + z <= 10

    GRBLinExpr expr = new GRBLinExpr();
    expr.addTerm(1.0, x); expr.addTerm(1.0, y); expr.addTerm(1.0, z);
    model.addConstr(expr, GRB.LESS_EQUAL, 10.0, "c0");

    // Add bilinear inequality: x * y <= 2

    GRBQuadExpr qexpr = new GRBQuadExpr();
    qexpr.addTerm(1.0, x, y);
    model.addQConstr(qexpr, GRB.LESS_EQUAL, 2.0, "bilinear0");

    // Add bilinear equality: x * z + y * z == 1

    qexpr = new GRBQuadExpr();
    qexpr.addTerm(1.0, x, z);
    qexpr.addTerm(1.0, y, z);
    model.addQConstr(qexpr, GRB.EQUAL, 1.0, "bilinear1");

    // Optimize model

    model.optimize();

    System.out.println(x.get(GRB.StringAttr.VarName)
                       + " " +x.get(GRB.DoubleAttr.X));
    System.out.println(y.get(GRB.StringAttr.VarName)
                       + " " +y.get(GRB.DoubleAttr.X));
    System.out.println(z.get(GRB.StringAttr.VarName)
                       + " " +z.get(GRB.DoubleAttr.X));

    System.out.println("Obj: " + model.get(GRB.DoubleAttr.ObjVal) + " " +
                       obj.getValue());
    System.out.println();

    // Constrain x to be integral and solve again

    x.set(GRB.CharAttr.VType, GRB.INTEGER);
    model.optimize();

    System.out.println(x.get(GRB.StringAttr.VarName)
```

(continues on next page)

(continued from previous page)

```
                        + " " +x.get(GRB.DoubleAttr.X));
      System.out.println(y.get(GRB.StringAttr.VarName)
                        + " " +y.get(GRB.DoubleAttr.X));
      System.out.println(z.get(GRB.StringAttr.VarName)
                        + " " +z.get(GRB.DoubleAttr.X));

      System.out.println("Obj: " + model.get(GRB.DoubleAttr.ObjVal) + " " +
                         obj.getValue());
      System.out.println();

      // Dispose of model and environment

      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Callback.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/*
   This example reads a model from a file, sets up a callback that
   monitors optimization progress and implements a custom
   termination strategy, and outputs progress information to the
   screen and to a log file.

   The termination strategy implemented in this callback stops the
   optimization of a MIP model once at least one of the following two
   conditions have been satisfied:
     1) The optimality gap is less than 10%
     2) At least 10000 nodes have been explored, and an integer feasible
        solution has been found.
   Note that termination is normally handled through Gurobi parameters
   (MIPGap, NodeLimit, etc.).  You should only use a callback for
   termination if the available parameters don't capture your desired
   termination criterion.
*/

import com.gurobi.gurobi.*;
import java.io.FileWriter;
import java.io.IOException;

public class Callback extends GRBCallback {
  private double     lastiter;
```

(continues on next page)

(continued from previous page)

```
private double     lastnode;
private GRBVar[]   vars;
private FileWriter logfile;

public Callback(GRBVar[] xvars, FileWriter xlogfile) {
  lastiter = lastnode = -GRB.INFINITY;
  vars = xvars;
  logfile = xlogfile;
}

protected void callback() {
  try {
    if (where == GRB.CB_POLLING) {
      // Ignore polling callback
    } else if (where == GRB.CB_PRESOLVE) {
      // Presolve callback
      int cdels = getIntInfo(GRB.CB_PRE_COLDEL);
      int rdels = getIntInfo(GRB.CB_PRE_ROWDEL);
      if (cdels != 0 || rdels != 0) {
        System.out.println(cdels + " columns and " + rdels
            + " rows are removed");
      }
    } else if (where == GRB.CB_SIMPLEX) {
      // Simplex callback
      double itcnt = getDoubleInfo(GRB.CB_SPX_ITRCNT);
      if (itcnt - lastiter >= 100) {
        lastiter = itcnt;
        double obj    = getDoubleInfo(GRB.CB_SPX_OBJVAL);
        int    ispert = getIntInfo(GRB.CB_SPX_ISPERT);
        double pinf   = getDoubleInfo(GRB.CB_SPX_PRIMINF);
        double dinf   = getDoubleInfo(GRB.CB_SPX_DUALINF);
        char ch;
        if (ispert == 0)      ch = ' ';
        else if (ispert == 1) ch = 'S';
        else                  ch = 'P';
        System.out.println(itcnt + " " + obj + ch + " "
            + pinf + " " + dinf);
      }
    } else if (where == GRB.CB_MIP) {
      // General MIP callback
      double nodecnt = getDoubleInfo(GRB.CB_MIP_NODCNT);
      double objbst  = getDoubleInfo(GRB.CB_MIP_OBJBST);
      double objbnd  = getDoubleInfo(GRB.CB_MIP_OBJBND);
      int    solcnt  = getIntInfo(GRB.CB_MIP_SOLCNT);
      if (nodecnt - lastnode >= 100) {
        lastnode = nodecnt;
        int actnodes = (int) getDoubleInfo(GRB.CB_MIP_NODLFT);
        int itcnt    = (int) getDoubleInfo(GRB.CB_MIP_ITRCNT);
        int cutcnt   = getIntInfo(GRB.CB_MIP_CUTCNT);
        System.out.println(nodecnt + " " + actnodes + " "
            + itcnt + " " + objbst + " " + objbnd + " "
            + solcnt + " " + cutcnt);
```

(continues on next page)

(continued from previous page)

```
        }
        if (Math.abs(objbst - objbnd) < 0.1 * (1.0 + Math.abs(objbst))) {
          System.out.println("Stop early - 10% gap achieved");
          abort();
        }
        if (nodecnt >= 10000 && solcnt > 0) {
          System.out.println("Stop early - 10000 nodes explored");
          abort();
        }
      } else if (where == GRB.CB_MIPSOL) {
        // MIP solution callback
        int      nodecnt = (int) getDoubleInfo(GRB.CB_MIPSOL_NODCNT);
        double   obj     = getDoubleInfo(GRB.CB_MIPSOL_OBJ);
        int      solcnt  = getIntInfo(GRB.CB_MIPSOL_SOLCNT);
        double[] x       = getSolution(vars);
        System.out.println("**** New solution at node " + nodecnt
            + ", obj " + obj + ", sol " + solcnt
            + ", x[0] = " + x[0] + " ****");
      } else if (where == GRB.CB_MIPNODE) {
        // MIP node callback
        System.out.println("**** New node ****");
        if (getIntInfo(GRB.CB_MIPNODE_STATUS) == GRB.OPTIMAL) {
          double[] x = getNodeRel(vars);
          setSolution(vars, x);
        }
      } else if (where == GRB.CB_BARRIER) {
        // Barrier callback
        int    itcnt   = getIntInfo(GRB.CB_BARRIER_ITRCNT);
        double primobj = getDoubleInfo(GRB.CB_BARRIER_PRIMOBJ);
        double dualobj = getDoubleInfo(GRB.CB_BARRIER_DUALOBJ);
        double priminf = getDoubleInfo(GRB.CB_BARRIER_PRIMINF);
        double dualinf = getDoubleInfo(GRB.CB_BARRIER_DUALINF);
        double cmpl    = getDoubleInfo(GRB.CB_BARRIER_COMPL);
        System.out.println(itcnt + " " + primobj + " " + dualobj + " "
            + priminf + " " + dualinf + " " + cmpl);
      } else if (where == GRB.CB_MESSAGE) {
        // Message callback
        String msg = getStringInfo(GRB.CB_MSG_STRING);
        if (msg != null) logfile.write(msg);
      }
    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode());
      System.out.println(e.getMessage());
      e.printStackTrace();
    } catch (Exception e) {
      System.out.println("Error during callback");
      e.printStackTrace();
    }
  }

  public static void main(String[] args) {
```

(continues on next page)

(continued from previous page)

```
  if (args.length < 1) {
    System.out.println("Usage: java Callback filename");
    System.exit(1);
  }

  FileWriter logfile = null;

  try {
    // Create environment
    GRBEnv env = new GRBEnv();

    // Read model from file
    GRBModel model = new GRBModel(env, args[0]);

    // Turn off display and heuristics
    model.set(GRB.IntParam.OutputFlag, 0);
    model.set(GRB.DoubleParam.Heuristics, 0.0);

    // Open log file
    logfile = new FileWriter("cb.log");

    // Create a callback object and associate it with the model
    GRBVar[] vars = model.getVars();
    Callback cb   = new Callback(vars, logfile);

    model.setCallback(cb);

    // Solve model and capture solution information
    model.optimize();

    System.out.println("");
    System.out.println("Optimization complete");
    if (model.get(GRB.IntAttr.SolCount) == 0) {
      System.out.println("No solution found, optimization status = "
          + model.get(GRB.IntAttr.Status));
    } else {
      System.out.println("Solution found, objective = "
          + model.get(GRB.DoubleAttr.ObjVal));

      String[] vnames = model.get(GRB.StringAttr.VarName, vars);
      double[] x      = model.get(GRB.DoubleAttr.X, vars);

      for (int j = 0; j < vars.length; j++) {
        if (x[j] != 0.0) System.out.println(vnames[j] + " " + x[j]);
      }
    }

    // Dispose of model and environment
    model.dispose();
    env.dispose();

  } catch (GRBException e) {
```

(continues on next page)

(continued from previous page)

```
      System.out.println("Error code: " + e.getErrorCode());
      System.out.println(e.getMessage());
      e.printStackTrace();
    } catch (Exception e) {
      System.out.println("Error during optimization");
      e.printStackTrace();
    } finally {
      // Close log file
      if (logfile != null) {
        try { logfile.close(); } catch (IOException e) {}
      }
    }
  }
}
```

Dense.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QP model:

     minimize    x + y + x^2 + x*y + y^2 + y*z + z^2
     subject to  x + 2 y + 3 z >= 4
                 x +   y       >= 1
                 x, y, z non-negative

   The example illustrates the use of dense matrices to store A and Q
   (and dense vectors for the other relevant data).  We don't recommend
   that you use dense matrices, but this example may be helpful if you
   already have your data in this format.
*/

import com.gurobi.gurobi.*;

public class Dense {

  protected static boolean
    dense_optimize(GRBEnv     env,
                   int        rows,
                   int        cols,
                   double[]   c,      // linear portion of objective function
                   double[][] Q,      // quadratic portion of objective function
                   double[][] A,      // constraint matrix
                   char[]     sense,  // constraint senses
                   double[]   rhs,    // RHS vector
                   double[]   lb,     // variable lower bounds
                   double[]   ub,     // variable upper bounds
                   char[]     vtype,  // variable types (continuous, binary, etc.)
                   double[]   solution) {
```

(continues on next page)

(continued from previous page)

```
    boolean success = false;

    try {
      GRBModel model = new GRBModel(env);

      // Add variables to the model

      GRBVar[] vars = model.addVars(lb, ub, null, vtype, null);

      // Populate A matrix

      for (int i = 0; i < rows; i++) {
        GRBLinExpr expr = new GRBLinExpr();
        for (int j = 0; j < cols; j++)
          if (A[i][j] != 0)
            expr.addTerm(A[i][j], vars[j]);
        model.addConstr(expr, sense[i], rhs[i], "");
      }

      // Populate objective

      GRBQuadExpr obj = new GRBQuadExpr();
      if (Q != null) {
        for (int i = 0; i < cols; i++)
          for (int j = 0; j < cols; j++)
            if (Q[i][j] != 0)
              obj.addTerm(Q[i][j], vars[i], vars[j]);
        for (int j = 0; j < cols; j++)
          if (c[j] != 0)
            obj.addTerm(c[j], vars[j]);
        model.setObjective(obj);
      }

      // Solve model

      model.optimize();

      // Extract solution

      if (model.get(GRB.IntAttr.Status) == GRB.Status.OPTIMAL) {
        success = true;

        for (int j = 0; j < cols; j++)
          solution[j] = vars[j].get(GRB.DoubleAttr.X);
      }

      model.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
      e.printStackTrace();
```

(continues on next page)

(continued from previous page)

```
    }

    return success;
  }

  public static void main(String[] args) {
    try {
      GRBEnv env = new GRBEnv();

      double c[] = new double[] {1, 1, 0};
      double Q[][] = new double[][] {{1, 1, 0}, {0, 1, 1}, {0, 0, 1}};
      double A[][] = new double[][] {{1, 2, 3}, {1, 1, 0}};
      char sense[] = new char[] {'>', '>'};
      double rhs[] = new double[] {4, 1};
      double lb[] = new double[] {0, 0, 0};
      boolean success;
      double sol[] = new double[3];


      success = dense_optimize(env, 2, 3, c, Q, A, sense, rhs,
                               lb, null, null, sol);

      if (success) {
        System.out.println("x: " + sol[0] + ", y: " + sol[1] + ", z: " + sol[2]);
      }

      // Dispose of environment
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
      e.printStackTrace();
    }
  }
}
```

Diet.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Solve the classic diet model, showing how to add constraints
   to an existing model. */

import com.gurobi.gurobi.*;

public class Diet {

  public static void main(String[] args) {
    try {
```

(continues on next page)

(continued from previous page)

```
    // Nutrition guidelines, based on
    // USDA Dietary Guidelines for Americans, 2005
    // http://www.health.gov/DietaryGuidelines/dga2005/
    String Categories[] =
        new String[] { "calories", "protein", "fat", "sodium" };
    int nCategories = Categories.length;
    double minNutrition[] = new double[] { 1800, 91, 0, 0 };
    double maxNutrition[] = new double[] { 2200, GRB.INFINITY, 65, 1779 };

    // Set of foods
    String Foods[] =
        new String[] { "hamburger", "chicken", "hot dog", "fries",
            "macaroni", "pizza", "salad", "milk", "ice cream" };
    int nFoods = Foods.length;
    double cost[] =
        new double[] { 2.49, 2.89, 1.50, 1.89, 2.09, 1.99, 2.49, 0.89,
            1.59 };

    // Nutrition values for the foods
    double nutritionValues[][] = new double[][] {
        { 410, 24, 26, 730 },   // hamburger
        { 420, 32, 10, 1190 },  // chicken
        { 560, 20, 32, 1800 },  // hot dog
        { 380, 4, 19, 270 },    // fries
        { 320, 12, 10, 930 },   // macaroni
        { 320, 15, 12, 820 },   // pizza
        { 320, 31, 12, 1230 },  // salad
        { 100, 8, 2.5, 125 },   // milk
        { 330, 8, 10, 180 }     // ice cream
        };

    // Model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env);
    model.set(GRB.StringAttr.ModelName, "diet");

    // Create decision variables for the nutrition information,
    // which we limit via bounds
    GRBVar[] nutrition = new GRBVar[nCategories];
    for (int i = 0; i < nCategories; ++i) {
      nutrition[i] =
          model.addVar(minNutrition[i], maxNutrition[i], 0, GRB.CONTINUOUS,
                       Categories[i]);
    }

    // Create decision variables for the foods to buy
    //
    // Note: For each decision variable we add the objective coefficient
    //       with the creation of the variable.
    GRBVar[] buy = new GRBVar[nFoods];
    for (int j = 0; j < nFoods; ++j) {
```

(continues on next page)

(continued from previous page)

```
      buy[j] =
          model.addVar(0, GRB.INFINITY, cost[j], GRB.CONTINUOUS, Foods[j]);
    }

    // The objective is to minimize the costs
    //
    // Note: The objective coefficients are set during the creation of
    //       the decision variables above.
    model.set(GRB.IntAttr.ModelSense, GRB.MINIMIZE);

    // Nutrition constraints
    for (int i = 0; i < nCategories; ++i) {
      GRBLinExpr ntot = new GRBLinExpr();
      for (int j = 0; j < nFoods; ++j) {
        ntot.addTerm(nutritionValues[j][i], buy[j]);
      }
      model.addConstr(ntot, GRB.EQUAL, nutrition[i], Categories[i]);
    }

    // Solve
    model.optimize();
    printSolution(model, buy, nutrition);
    System.out.println("JSON solution:" + model.getJSONSolution());

    System.out.println("\nAdding constraint: at most 6 servings of dairy");
    GRBLinExpr lhs = new GRBLinExpr();
    lhs.addTerm(1.0, buy[7]);
    lhs.addTerm(1.0, buy[8]);
    model.addConstr(lhs, GRB.LESS_EQUAL, 6.0, "limit_dairy");

    // Solve
    model.optimize();
    printSolution(model, buy, nutrition);
    System.out.println("JSON solution:" + model.getJSONSolution());

    // Dispose of model and environment
    model.dispose();
    env.dispose();

  } catch (GRBException e) {
    System.out.println("Error code: " + e.getErrorCode() + ". " +
        e.getMessage());
  }
}

private static void printSolution(GRBModel model, GRBVar[] buy,
                                  GRBVar[] nutrition) throws GRBException {
  if (model.get(GRB.IntAttr.Status) == GRB.Status.OPTIMAL) {
    System.out.println("\nCost: " + model.get(GRB.DoubleAttr.ObjVal));
    System.out.println("\nBuy:");
    for (int j = 0; j < buy.length; ++j) {
      if (buy[j].get(GRB.DoubleAttr.X) > 0.0001) {
```

(continues on next page)

(continued from previous page)

```
          System.out.println(buy[j].get(GRB.StringAttr.VarName) + " " +
              buy[j].get(GRB.DoubleAttr.X));
        }
      }
      System.out.println("\nNutrition:");
      for (int i = 0; i < nutrition.length; ++i) {
        System.out.println(nutrition[i].get(GRB.StringAttr.VarName) + " " +
            nutrition[i].get(GRB.DoubleAttr.X));
      }
    } else {
      System.out.println("No solution");
    }
  }
}
```

Facility.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Facility location: a company currently ships its product from 5 plants
   to 4 warehouses. It is considering closing some plants to reduce
   costs. What plant(s) should the company close, in order to minimize
   transportation and fixed costs?

   Based on an example from Frontline Systems:
   http://www.solver.com/disfacility.htm
   Used with permission.
 */

import com.gurobi.gurobi.*;

public class Facility {

  public static void main(String[] args) {
    try {

      // Warehouse demand in thousands of units
      double Demand[] = new double[] { 15, 18, 14, 20 };

      // Plant capacity in thousands of units
      double Capacity[] = new double[] { 20, 22, 17, 19, 18 };

      // Fixed costs for each plant
      double FixedCosts[] =
          new double[] { 12000, 15000, 17000, 13000, 16000 };

      // Transportation costs per thousand units
      double TransCosts[][] =
          new double[][] { { 4000, 2000, 3000, 2500, 4500 },
              { 2500, 2600, 3400, 3000, 4000 },
```

(continues on next page)

(continued from previous page)

```
            { 1200, 1800, 2600, 4100, 3000 },
            { 2200, 2600, 3100, 3700, 3200 } };

    // Number of plants and warehouses
    int nPlants = Capacity.length;
    int nWarehouses = Demand.length;

    // Model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env);
    model.set(GRB.StringAttr.ModelName, "facility");

    // Plant open decision variables: open[p] == 1 if plant p is open.
    GRBVar[] open = new GRBVar[nPlants];
    for (int p = 0; p < nPlants; ++p) {
      open[p] = model.addVar(0, 1, FixedCosts[p], GRB.BINARY, "Open" + p);
    }

    // Transportation decision variables: how much to transport from
    // a plant p to a warehouse w
    GRBVar[][] transport = new GRBVar[nWarehouses][nPlants];
    for (int w = 0; w < nWarehouses; ++w) {
      for (int p = 0; p < nPlants; ++p) {
        transport[w][p] =
            model.addVar(0, GRB.INFINITY, TransCosts[w][p], GRB.CONTINUOUS,
                         "Trans" + p + "." + w);
      }
    }

    // The objective is to minimize the total fixed and variable costs
    model.set(GRB.IntAttr.ModelSense, GRB.MINIMIZE);

    // Production constraints
    // Note that the right-hand limit sets the production to zero if
    // the plant is closed
    for (int p = 0; p < nPlants; ++p) {
      GRBLinExpr ptot = new GRBLinExpr();
      for (int w = 0; w < nWarehouses; ++w) {
        ptot.addTerm(1.0, transport[w][p]);
      }
      GRBLinExpr limit = new GRBLinExpr();
      limit.addTerm(Capacity[p], open[p]);
      model.addConstr(ptot, GRB.LESS_EQUAL, limit, "Capacity" + p);
    }

    // Demand constraints
    for (int w = 0; w < nWarehouses; ++w) {
      GRBLinExpr dtot = new GRBLinExpr();
      for (int p = 0; p < nPlants; ++p) {
        dtot.addTerm(1.0, transport[w][p]);
      }
      model.addConstr(dtot, GRB.EQUAL, Demand[w], "Demand" + w);
```

(continues on next page)

(continued from previous page)

```
    }

    // Guess at the starting point: close the plant with the highest
    // fixed costs; open all others

    // First, open all plants
    for (int p = 0; p < nPlants; ++p) {
      open[p].set(GRB.DoubleAttr.Start, 1.0);
    }

    // Now close the plant with the highest fixed cost
    System.out.println("Initial guess:");
    double maxFixed = -GRB.INFINITY;
    for (int p = 0; p < nPlants; ++p) {
      if (FixedCosts[p] > maxFixed) {
        maxFixed = FixedCosts[p];
      }
    }
    for (int p = 0; p < nPlants; ++p) {
      if (FixedCosts[p] == maxFixed) {
        open[p].set(GRB.DoubleAttr.Start, 0.0);
        System.out.println("Closing plant " + p + "\n");
        break;
      }
    }

    // Use barrier to solve root relaxation
    model.set(GRB.IntParam.Method, GRB.METHOD_BARRIER);

    // Solve
    model.optimize();

    // Print solution
    System.out.println("\nTOTAL COSTS: " + model.get(GRB.DoubleAttr.ObjVal));
    System.out.println("SOLUTION:");
    for (int p = 0; p < nPlants; ++p) {
      if (open[p].get(GRB.DoubleAttr.X) > 0.99) {
        System.out.println("Plant " + p + " open:");
        for (int w = 0; w < nWarehouses; ++w) {
          if (transport[w][p].get(GRB.DoubleAttr.X) > 0.0001) {
            System.out.println("  Transport " +
                transport[w][p].get(GRB.DoubleAttr.X) +
                " units to warehouse " + w);
          }
        }
      } else {
        System.out.println("Plant " + p + " closed!");
      }
    }

    // Dispose of model and environment
    model.dispose();
```

(continues on next page)

(continued from previous page)

```
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Feasopt.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, adds artificial
   variables to each constraint, and then minimizes the sum of the
   artificial variables.  A solution with objective zero corresponds
   to a feasible solution to the input model.
   We can also use FeasRelax feature to do it. In this example, we
   use minrelax=1, i.e. optimizing the returned model finds a solution
   that minimizes the original objective, but only from among those
   solutions that minimize the sum of the artificial variables. */

import com.gurobi.gurobi.*;

public class Feasopt {
  public static void main(String[] args) {

    if (args.length < 1) {
      System.out.println("Usage: java Feasopt filename");
      System.exit(1);
    }

    try {
      GRBEnv env = new GRBEnv();
      GRBModel feasmodel = new GRBModel(env, args[0]);

      // Create a copy to use FeasRelax feature later */
      GRBModel feasmodel1 = new GRBModel(feasmodel);

      // Clear objective
      feasmodel.setObjective(new GRBLinExpr());

      // Add slack variables
      GRBConstr[] c = feasmodel.getConstrs();
      for (int i = 0; i < c.length; ++i) {
        char sense = c[i].get(GRB.CharAttr.Sense);
        if (sense != '>') {
          GRBConstr[] constrs = new GRBConstr[] { c[i] };
          double[] coeffs = new double[] { -1 };
          feasmodel.addVar(0.0, GRB.INFINITY, 1.0, GRB.CONTINUOUS, constrs,
```

(continues on next page)

(continued from previous page)

```
                            coeffs, "ArtN_" +
                                c[i].get(GRB.StringAttr.ConstrName));
        }
        if (sense != '<') {
          GRBConstr[] constrs = new GRBConstr[] { c[i] };
          double[] coeffs = new double[] { 1 };
          feasmodel.addVar(0.0, GRB.INFINITY, 1.0, GRB.CONTINUOUS, constrs,
                            coeffs, "ArtP_" +
                                c[i].get(GRB.StringAttr.ConstrName));
        }
      }

      // Optimize modified model
      feasmodel.optimize();
      feasmodel.write("feasopt.lp");

      // use FeasRelax feature */
      feasmodel1.feasRelax(GRB.FEASRELAX_LINEAR, true, false, true);
      feasmodel1.write("feasopt1.lp");
      feasmodel1.optimize();

      // Dispose of model and environment
      feasmodel1.dispose();
      feasmodel.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Fixanddive.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Implement a simple MIP heuristic.  Relax the model,
 sort variables based on fractionality, and fix the 25% of
 the fractional variables that are closest to integer variables.
 Repeat until either the relaxation is integer feasible or
 linearly infeasible. */

import com.gurobi.gurobi.*;
import java.util.*;

public class Fixanddive {
  public static void main(String[] args) {

    // Comparison class used to sort variable list based on relaxation
```

(continues on next page)

(continued from previous page)

```
  // fractionality

  class FractionalCompare implements Comparator<GRBVar> {
    public int compare(GRBVar v1, GRBVar v2) {
      try {
        double sol1 = Math.abs(v1.get(GRB.DoubleAttr.X));
        double sol2 = Math.abs(v2.get(GRB.DoubleAttr.X));
        double frac1 = Math.abs(sol1 - Math.floor(sol1 + 0.5));
        double frac2 = Math.abs(sol2 - Math.floor(sol2 + 0.5));
        if (frac1 < frac2) {
          return -1;
        } else if (frac1 == frac2) {
          return 0;
        } else {
          return 1;
        }
      } catch (GRBException e) {
        System.out.println("Error code: " + e.getErrorCode() + ". " +
            e.getMessage());
      }
      return 0;
    }
  }

  if (args.length < 1) {
    System.out.println("Usage: java Fixanddive filename");
    System.exit(1);
  }

  try {
    // Read model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env, args[0]);

    // Collect integer variables and relax them
    ArrayList<GRBVar> intvars = new ArrayList<GRBVar>();
    for (GRBVar v : model.getVars()) {
      if (v.get(GRB.CharAttr.VType) != GRB.CONTINUOUS) {
        intvars.add(v);
        v.set(GRB.CharAttr.VType, GRB.CONTINUOUS);
      }
    }

    model.set(GRB.IntParam.OutputFlag, 0);
    model.optimize();

    // Perform multiple iterations. In each iteration, identify the first
    // quartile of integer variables that are closest to an integer value
    // in the relaxation, fix them to the nearest integer, and repeat.

    for (int iter = 0; iter < 1000; ++iter) {
```

(continues on next page)

(continued from previous page)

```
      // create a list of fractional variables, sorted in order of
      // increasing distance from the relaxation solution to the nearest
      // integer value

      ArrayList<GRBVar> fractional = new ArrayList<GRBVar>();
      for (GRBVar v : intvars) {
        double sol = Math.abs(v.get(GRB.DoubleAttr.X));
        if (Math.abs(sol - Math.floor(sol + 0.5)) > 1e-5) {
          fractional.add(v);
        }
      }

      System.out.println("Iteration " + iter + ", obj " +
          model.get(GRB.DoubleAttr.ObjVal) + ", fractional " +
          fractional.size());

      if (fractional.size() == 0) {
        System.out.println("Found feasible solution - objective " +
            model.get(GRB.DoubleAttr.ObjVal));
        break;
      }

      // Fix the first quartile to the nearest integer value

      Collections.sort(fractional, new FractionalCompare());
      int nfix = Math.max(fractional.size() / 4, 1);
      for (int i = 0; i < nfix; ++i) {
        GRBVar v = fractional.get(i);
        double fixval = Math.floor(v.get(GRB.DoubleAttr.X) + 0.5);
        v.set(GRB.DoubleAttr.LB, fixval);
        v.set(GRB.DoubleAttr.UB, fixval);
        System.out.println("  Fix " + v.get(GRB.StringAttr.VarName) +
            " to " + fixval + " ( rel " + v.get(GRB.DoubleAttr.X) + " )");
      }

      model.optimize();

      // Check optimization result

      if (model.get(GRB.IntAttr.Status) != GRB.Status.OPTIMAL) {
        System.out.println("Relaxation is infeasible");
        break;
      }
    }

    // Dispose of model and environment
    model.dispose();
    env.dispose();

  } catch (GRBException e) {
    System.out.println("Error code: " + e.getErrorCode() + ". " +
        e.getMessage());
```

(continues on next page)

(continued from previous page)

```
    }
  }

}
```

GCPWL.java

```
/* Copyright 2026, Gurobi Optimization, LLC

 This example formulates and solves the following simple model
 with PWL constraints:

  maximize
        sum c[j] * x[j]
  subject to
        sum A[i,j] * x[j] <= 0,  for i = 0, ..., m-1
        sum y[j] <= 3
        y[j] = pwl(x[j]),        for j = 0, ..., n-1
        x[j] free, y[j] >= 0,    for j = 0, ..., n-1
  where pwl(x) = 0,     if x  = 0
               = 1+|x|, if x != 0

  Note
   1. sum pwl(x[j]) <= b is to bound x vector and also to favor sparse x vector.
      Here b = 3 means that at most two x[j] can be nonzero and if two, then
      sum x[j] <= 1
   2. pwl(x) jumps from 1 to 0 and from 0 to 1, if x moves from negative 0 to 0,
      then to positive 0, so we need three points at x = 0. x has infinite bounds
      on both sides, the piece defined with two points (-1, 2) and (0, 1) can
      extend x to -infinite. Overall we can use five points (-1, 2), (0, 1),
      (0, 0), (0, 1) and (1, 2) to define y = pwl(x)
*/

import com.gurobi.gurobi.*;
import java.util.*;

public class GCPWL {

  public static void main(String[] args) {
    try {
      int n = 5;
      int m = 5;
      double c[] = { 0.5, 0.8, 0.5, 0.1, -1 };
      double A[][] = { {0, 0, 0, 1, -1},
                       {0, 0, 1, 1, -1},
                       {1, 1, 0, 0, -1},
                       {1, 0, 1, 0, -1},
                       {1, 0, 0, 1, -1} };
      double xpts[] = {-1, 0, 0, 0, 1};
      double ypts[] = {2, 1, 0, 1, 2};
```

(continues on next page)

(continued from previous page)

```
    // Env and model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env);
    model.set(GRB.StringAttr.ModelName, "GCPWL");

    // Add variables, set bounds and obj coefficients
    GRBVar[] x = model.addVars(n, GRB.CONTINUOUS);
    for (int i = 0; i < n; i++) {
      x[i].set(GRB.DoubleAttr.LB, -GRB.INFINITY);
      x[i].set(GRB.DoubleAttr.Obj, c[i]);
    }

    GRBVar[] y = model.addVars(n, GRB.CONTINUOUS);

    // Set objective to maximize
    model.set(GRB.IntAttr.ModelSense, GRB.MAXIMIZE);

    // Add linear constraints
    for (int i = 0; i < m; i++) {
      GRBLinExpr le = new GRBLinExpr();
      for (int j = 0; j < n; j++) {
        le.addTerm(A[i][j], x[j]);
      }
      model.addConstr(le, GRB.LESS_EQUAL, 0, "cx" + i);
    }

    GRBLinExpr le1 = new GRBLinExpr();
    for (int j = 0; j < n; j++) {
      le1.addTerm(1.0, y[j]);
    }
    model.addConstr(le1, GRB.LESS_EQUAL, 3, "cy");

    // Add piecewise constraints
    for (int j = 0; j < n; j++) {
      model.addGenConstrPWL(x[j], y[j], xpts, ypts, "pwl" + j);
    }

    // Optimize model
    model.optimize();

    for (int j = 0; j < n; j++) {
      System.out.println("x[" + j + "] = " + x[j].get(GRB.DoubleAttr.X));
    }
    System.out.println("Obj: " + model.get(GRB.DoubleAttr.ObjVal));

    // Dispose of model and environment
    model.dispose();
    env.dispose();
  } catch (GRBException e) {
    System.out.println("Error code: " + e.getErrorCode() + ". " +
        e.getMessage());
```

(continues on next page)

(continued from previous page)

```
    }
  }
}
```

Genconstr.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* In this example we show the use of general constraints for modeling
   some common expressions. We use as an example a SAT-problem where we
   want to see if it is possible to satisfy at least four (or all) clauses
   of the logical form

   L = (x0 or ~x1 or x2)  and (x1 or ~x2 or x3)  and
       (x2 or ~x3 or x0)  and (x3 or ~x0 or x1)  and
       (~x0 or ~x1 or x2) and (~x1 or ~x2 or x3) and
       (~x2 or ~x3 or x0) and (~x3 or ~x0 or x1)

   We do this by introducing two variables for each literal (itself and its
   negated value), one variable for each clause, one variable indicating
   whether we can satisfy at least four clauses, and one last variable to
   identify the minimum of the clauses (so if it is one, we can satisfy all
   clauses). Then we put these last two variables in the objective.
   The objective function is therefore

   maximize Obj0 + Obj1

    Obj0 = MIN(Clause1, ... , Clause8)
    Obj1 = 1 -> Clause1 + ... + Clause8 >= 4

   thus, the objective value will be two if and only if we can satisfy all
   clauses; one if and only if at least four but not all clauses can be satisfied,
   and zero otherwise.
 */


import com.gurobi.gurobi.*;

public class Genconstr {

  public static final int n = 4;
  public static final int NLITERALS = 4;  // same as n
  public static final int NCLAUSES = 8;
  public static final int NOBJ = 2;

  public static void main(String[] args) {

    try {
      // Example data:
      //   e.g. {0, n+1, 2} means clause (x0 or ~x1 or x2)
```

(continues on next page)

(continued from previous page)

```
    int Clauses[][] = new int[][]
                      {{  0, n+1, 2}, {  1, n+2, 3},
                       {  2, n+3, 0}, {  3, n+0, 1},
                       {n+0, n+1, 2}, {n+1, n+2, 3},
                       {n+2, n+3, 0}, {n+3, n+0, 1}};

    int i, status, nSolutions;

    // Create environment
    GRBEnv env = new GRBEnv("Genconstr.log");

    // Create initial model
    GRBModel model = new GRBModel(env);
    model.set(GRB.StringAttr.ModelName, "Genconstr");

    // Initialize decision variables and objective

    GRBVar[] Lit    = new GRBVar[NLITERALS];
    GRBVar[] NotLit = new GRBVar[NLITERALS];
    for (i = 0; i < NLITERALS; i++) {
      Lit[i]    = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, "X" + String.valueOf(i));
      NotLit[i] = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, "notX" + String.valueOf(i));
    }

    GRBVar[] Cla = new GRBVar[NCLAUSES];
    for (i = 0; i < NCLAUSES; i++) {
      Cla[i] = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, "Clause" + String.valueOf(i));
    }

    GRBVar[] Obj = new GRBVar[NOBJ];
    for (i = 0; i < NOBJ; i++) {
      Obj[i] = model.addVar(0.0, 1.0, 1.0, GRB.BINARY, "Obj" + String.valueOf(i));
    }

    // Link Xi and notXi
    GRBLinExpr lhs;
    for (i = 0; i < NLITERALS; i++) {
      lhs = new GRBLinExpr();
      lhs.addTerm(1.0, Lit[i]);
      lhs.addTerm(1.0, NotLit[i]);
      model.addConstr(lhs, GRB.EQUAL, 1.0, "CNSTR_X" + String.valueOf(i));
    }

    // Link clauses and literals
    for (i = 0; i < NCLAUSES; i++) {
      GRBVar[] clause = new GRBVar[3];
      for (int j = 0; j < 3; j++) {
        if (Clauses[i][j] >= n) clause[j] = NotLit[Clauses[i][j]-n];
        else                    clause[j] = Lit[Clauses[i][j]];
      }
      model.addGenConstrOr(Cla[i], clause, "CNSTR_Clause" + String.valueOf(i));
    }
```

(continues on next page)

(continued from previous page)

```
    // Link objs with clauses
    model.addGenConstrMin(Obj[0], Cla, GRB.INFINITY, "CNSTR_Obj0");
    lhs = new GRBLinExpr();
    for (i = 0; i < NCLAUSES; i++) {
      lhs.addTerm(1.0, Cla[i]);
    }
    model.addGenConstrIndicator(Obj[1], 1, lhs, GRB.GREATER_EQUAL, 4.0, "CNSTR_Obj1");

    // Set global objective sense
    model.set(GRB.IntAttr.ModelSense, GRB.MAXIMIZE);

    // Save problem
    model.write("Genconstr.mps");
    model.write("Genconstr.lp");

    // Optimize
    model.optimize();

    // Status checking
    status = model.get(GRB.IntAttr.Status);

    if (status == GRB.INF_OR_UNBD ||
        status == GRB.INFEASIBLE  ||
        status == GRB.UNBOUNDED     ) {
      System.out.println("The model cannot be solved " +
             "because it is infeasible or unbounded");
      System.exit(1);
    }
    if (status != GRB.OPTIMAL) {
      System.out.println("Optimization was stopped with status " + status);
      System.exit(1);
    }

    // Print result
    double objval = model.get(GRB.DoubleAttr.ObjVal);

    if (objval > 1.9)
      System.out.println("Logical expression is satisfiable");
    else if (objval > 0.9)
      System.out.println("At least four clauses can be satisfied");
    else
      System.out.println("Not even three clauses can be satisfied");

    // Dispose of model and environment
    model.dispose();
    env.dispose();

  } catch (GRBException e) {
    System.out.println("Error code: " + e.getErrorCode() + ". " +
        e.getMessage());
  }
```

(continues on next page)

(continued from previous page)

```
  }
}
```

Lp.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads an LP model from a file and solves it.
   If the model is infeasible or unbounded, the example turns off
   presolve and solves the model again. If the model is infeasible,
   the example computes an Irreducible Inconsistent Subsystem (IIS),
   and writes it to a file */

import com.gurobi.gurobi.*;

public class Lp {
  public static void main(String[] args) {

    if (args.length < 1) {
      System.out.println("Usage: java Lp filename");
      System.exit(1);
    }

    try {
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env, args[0]);

      model.optimize();

      int optimstatus = model.get(GRB.IntAttr.Status);

      if (optimstatus == GRB.Status.INF_OR_UNBD) {
        model.set(GRB.IntParam.Presolve, 0);
        model.optimize();
        optimstatus = model.get(GRB.IntAttr.Status);
      }

      if (optimstatus == GRB.Status.OPTIMAL) {
        double objval = model.get(GRB.DoubleAttr.ObjVal);
        System.out.println("Optimal objective: " + objval);
      } else if (optimstatus == GRB.Status.INFEASIBLE) {
        System.out.println("Model is infeasible");

        // Compute and write out IIS
        model.computeIIS();
        model.write("model.ilp");
      } else if (optimstatus == GRB.Status.UNBOUNDED) {
        System.out.println("Model is unbounded");
      } else {
        System.out.println("Optimization was stopped with status = "
```

(continues on next page)

(continued from previous page)

```
                            + optimstatus);
      }

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Lpmethod.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Solve a model with different values of the Method parameter;
   show which value gives the shortest solve time. */

import com.gurobi.gurobi.*;

public class Lpmethod {

  public static void main(String[] args) {

    if (args.length < 1) {
      System.out.println("Usage: java Lpmethod filename");
      System.exit(1);
    }

    try {
      // Read model
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env, args[0]);

      // Solve the model with different values of Method
      int bestMethod = -1;
      double bestTime = model.get(GRB.DoubleParam.TimeLimit);
      for (int i = 0; i <= 2; ++i) {
        model.reset();
        model.set(GRB.IntParam.Method, i);
        model.optimize();
        if (model.get(GRB.IntAttr.Status) == GRB.Status.OPTIMAL) {
          bestTime = model.get(GRB.DoubleAttr.Runtime);
          bestMethod = i;
          // Reduce the TimeLimit parameter to save time
          // with other methods
          model.set(GRB.DoubleParam.TimeLimit, bestTime);
```

(continues on next page)

(continued from previous page)

```
        }
      }

      // Report which method was fastest
      if (bestMethod == -1) {
        System.out.println("Unable to solve this model");
      } else {
        System.out.println("Solved in " + bestTime
            + " seconds with Method: " + bestMethod);
      }

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". "
          + e.getMessage());
    }
  }
}
```

Lpmod.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads an LP model from a file and solves it.
   If the model can be solved, then it finds the smallest positive variable,
   sets its upper bound to zero, and resolves the model two ways:
   first with an advanced start, then without an advanced start
   (i.e. 'from scratch'). */

import com.gurobi.gurobi.*;

public class Lpmod {
  public static void main(String[] args) {

    if (args.length < 1) {
      System.out.println("Usage: java Lpmod filename");
      System.exit(1);
    }

    try {
      // Read model and determine whether it is an LP
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env, args[0]);
      if (model.get(GRB.IntAttr.IsMIP) != 0) {
        System.out.println("The model is not a linear program");
        System.exit(1);
      }
```

(continues on next page)

(continued from previous page)

```
    model.optimize();

    int status = model.get(GRB.IntAttr.Status);

    if (status == GRB.Status.INF_OR_UNBD ||
        status == GRB.Status.INFEASIBLE  ||
        status == GRB.Status.UNBOUNDED     ) {
      System.out.println("The model cannot be solved because it is "
          + "infeasible or unbounded");
      System.exit(1);
    }

    if (status != GRB.Status.OPTIMAL) {
      System.out.println("Optimization was stopped with status " + status);
      System.exit(0);
    }

    // Find the smallest variable value
    double minVal = GRB.INFINITY;
    GRBVar minVar = null;
    for (GRBVar v : model.getVars()) {
      double sol = v.get(GRB.DoubleAttr.X);
      if ((sol > 0.0001) && (sol < minVal) &&
          (v.get(GRB.DoubleAttr.LB) == 0.0)) {
        minVal = sol;
        minVar = v;
      }
    }

    System.out.println("\n*** Setting " +
        minVar.get(GRB.StringAttr.VarName) + " from " + minVal +
        " to zero ***\n");
    minVar.set(GRB.DoubleAttr.UB, 0.0);

    // Solve from this starting point
    model.optimize();

    // Save iteration & time info
    double warmCount = model.get(GRB.DoubleAttr.IterCount);
    double warmTime = model.get(GRB.DoubleAttr.Runtime);

    // Reset the model and resolve
    System.out.println("\n*** Resetting and solving "
        + "without an advanced start ***\n");
    model.reset();
    model.optimize();

    double coldCount = model.get(GRB.DoubleAttr.IterCount);
    double coldTime = model.get(GRB.DoubleAttr.Runtime);

    System.out.println("\n*** Warm start: " + warmCount + " iterations, " +
```

(continues on next page)

(continued from previous page)

```
          warmTime + " seconds");
      System.out.println("*** Cold start: " + coldCount + " iterations, " +
          coldTime + " seconds");

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Mip1.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple MIP model:

     maximize    x +   y + 2 z
     subject to  x + 2 y + 3 z <= 4
                 x +   y       >= 1
                 x, y, z binary
*/

import com.gurobi.gurobi.*;

public class Mip1 {
  public static void main(String[] args) {
    try {

      // Create empty environment, set options, and start
      GRBEnv env = new GRBEnv(true);
      env.set("logFile", "mip1.log");
      env.start();

      // Create empty model
      GRBModel model = new GRBModel(env);

      // Create variables
      GRBVar x = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, "x");
      GRBVar y = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, "y");
      GRBVar z = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, "z");

      // Set objective: maximize x + y + 2 z
      GRBLinExpr expr = new GRBLinExpr();
      expr.addTerm(1.0, x); expr.addTerm(1.0, y); expr.addTerm(2.0, z);
      model.setObjective(expr, GRB.MAXIMIZE);
```

(continues on next page)

(continued from previous page)

```
      // Add constraint: x + 2 y + 3 z <= 4
      expr = new GRBLinExpr();
      expr.addTerm(1.0, x); expr.addTerm(2.0, y); expr.addTerm(3.0, z);
      model.addConstr(expr, GRB.LESS_EQUAL, 4.0, "c0");

      // Add constraint: x + y >= 1
      expr = new GRBLinExpr();
      expr.addTerm(1.0, x); expr.addTerm(1.0, y);
      model.addConstr(expr, GRB.GREATER_EQUAL, 1.0, "c1");

      // Optimize model
      model.optimize();

      System.out.println(x.get(GRB.StringAttr.VarName)
                         + " " +x.get(GRB.DoubleAttr.X));
      System.out.println(y.get(GRB.StringAttr.VarName)
                         + " " +y.get(GRB.DoubleAttr.X));
      System.out.println(z.get(GRB.StringAttr.VarName)
                         + " " +z.get(GRB.DoubleAttr.X));

      System.out.println("Obj: " + model.get(GRB.DoubleAttr.ObjVal));

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
                         e.getMessage());
    }
  }
}
```

Mip2.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a MIP model from a file, solves it and
   prints the objective values from all feasible solutions
   generated while solving the MIP. Then it creates the fixed
   model and solves that model. */

import com.gurobi.gurobi.*;

public class Mip2 {
  public static void main(String[] args) {

    if (args.length < 1) {
      System.out.println("Usage: java Mip2 filename");
```

(continues on next page)

(continued from previous page)

```
    System.exit(1);
  }

  try {
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env, args[0]);
    if (model.get(GRB.IntAttr.IsMIP) == 0) {
      System.out.println("Model is not a MIP");
      System.exit(1);
    }

    model.optimize();

    int optimstatus = model.get(GRB.IntAttr.Status);
    double objval = 0;
    if (optimstatus == GRB.Status.OPTIMAL) {
      objval = model.get(GRB.DoubleAttr.ObjVal);
      System.out.println("Optimal objective: " + objval);
    } else if (optimstatus == GRB.Status.INF_OR_UNBD) {
      System.out.println("Model is infeasible or unbounded");
      return;
    } else if (optimstatus == GRB.Status.INFEASIBLE) {
      System.out.println("Model is infeasible");
      return;
    } else if (optimstatus == GRB.Status.UNBOUNDED) {
      System.out.println("Model is unbounded");
      return;
    } else {
      System.out.println("Optimization was stopped with status = "
          + optimstatus);
      return;
    }

    /* Iterate over the solutions and compute the objectives */

    System.out.println();
    for (int k = 0; k < model.get(GRB.IntAttr.SolCount); ++k) {
      model.set(GRB.IntParam.SolutionNumber, k);
      double objn = model.get(GRB.DoubleAttr.PoolNObjVal);

      System.out.println("Solution " + k + " has objective: " + objn);
    }
    System.out.println();

    /* Create a fixed model, turn off presolve and solve */

    GRBModel fixed = model.fixedModel();

    fixed.set(GRB.IntParam.Presolve, 0);

    fixed.optimize();
```

(continues on next page)

(continued from previous page)

```
      int foptimstatus = fixed.get(GRB.IntAttr.Status);

      if (foptimstatus != GRB.Status.OPTIMAL) {
        System.err.println("Error: fixed model isn't optimal");
        return;
      }

      double fobjval = fixed.get(GRB.DoubleAttr.ObjVal);

      if (Math.abs(fobjval - objval) > 1.0e-6 * (1.0 + Math.abs(objval))) {
        System.err.println("Error: objective values are different");
        return;
      }

      GRBVar[] fvars  = fixed.getVars();
      double[] x      = fixed.get(GRB.DoubleAttr.X, fvars);
      String[] vnames = fixed.get(GRB.StringAttr.VarName, fvars);

      for (int j = 0; j < fvars.length; j++) {
        if (x[j] != 0.0) {
          System.out.println(vnames[j] + " " + x[j]);
        }
      }

      // Dispose of models and environment
      fixed.dispose();
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". "
          + e.getMessage());
    }
  }
}
```

Multiobj.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Want to cover four different sets but subject to a common budget of
   elements allowed to be used. However, the sets have different priorities to
   be covered; and we tackle this by using multi-objective optimization. */

import com.gurobi.gurobi.*;

public class Multiobj {
  public static void main(String[] args) {

    try {
```

(continues on next page)

(continued from previous page)

```
    // Sample data
    int groundSetSize = 20;
    int nSubsets      = 4;
    int Budget        = 12;
    double Set[][] = new double[][]
    { { 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0 },
      { 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1 },
      { 0, 0, 0, 1, 1, 0, 1, 1, 0, 0, 0, 0, 0, 1, 1, 0, 1, 1, 0, 0 },
      { 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0 } };
    int    SetObjPriority[] = new int[] {3, 2, 2, 1};
    double SetObjWeight[]   = new double[] {1.0, 0.25, 1.25, 1.0};
    int e, i, status, nSolutions;

    // Create environment
    GRBEnv env = new GRBEnv("Multiobj.log");

    // Create initial model
    GRBModel model = new GRBModel(env);
    model.set(GRB.StringAttr.ModelName, "Multiobj");

    // Initialize decision variables for ground set:
    // x[e] == 1 if element e is chosen for the covering.
    GRBVar[] Elem = model.addVars(groundSetSize, GRB.BINARY);
    for (e = 0; e < groundSetSize; e++) {
      String vname = "El" + String.valueOf(e);
      Elem[e].set(GRB.StringAttr.VarName, vname);
    }

    // Constraint: limit total number of elements to be picked to be at most
    // Budget
    GRBLinExpr lhs = new GRBLinExpr();
    for (e = 0; e < groundSetSize; e++) {
      lhs.addTerm(1.0, Elem[e]);
    }
    model.addConstr(lhs, GRB.LESS_EQUAL, Budget, "Budget");

    // Set global sense for ALL objectives
    model.set(GRB.IntAttr.ModelSense, GRB.MAXIMIZE);

    // Limit how many solutions to collect
    model.set(GRB.IntParam.PoolSolutions, 100);

    // Set and configure i-th objective
    for (i = 0; i < nSubsets; i++) {
      GRBLinExpr objn = new GRBLinExpr();
      String vname = "Set" + String.valueOf(i);

      for (e = 0; e < groundSetSize; e++)
        objn.addTerm(Set[i][e], Elem[e]);

      model.setObjectiveN(objn, i, SetObjPriority[i], SetObjWeight[i],
                          1.0 + i, 0.01, vname);
```

(continues on next page)

(continued from previous page)

```
    }

    // Save problem
    model.write("Multiobj.lp");

    // Optimize
    model.optimize();

    // Status checking
    status = model.get(GRB.IntAttr.Status);

    if (status == GRB.INF_OR_UNBD ||
        status == GRB.INFEASIBLE  ||
        status == GRB.UNBOUNDED     ) {
      System.out.println("The model cannot be solved " +
                         "because it is infeasible or unbounded");
      System.exit(1);
    }
    if (status != GRB.OPTIMAL) {
      System.out.println("Optimization was stopped with status " + status);
      System.exit(1);
    }

    // Print best selected set
    System.out.println("Selected elements in best solution:");
    System.out.println("\t");
    for (e = 0; e < groundSetSize; e++) {
      if (Elem[e].get(GRB.DoubleAttr.X) < .9) continue;
      System.out.print(" El" + e);
    }
    System.out.println();

    // Print number of solutions stored
    nSolutions = model.get(GRB.IntAttr.SolCount);
    System.out.println("Number of solutions found: " + nSolutions);

    // Print objective values of solutions
    if (nSolutions > 10) nSolutions = 10;
    System.out.println("Objective values for first " + nSolutions);
    System.out.println(" solutions:");
    for (i = 0; i < nSubsets; i++) {
      model.set(GRB.IntParam.ObjNumber, i);

      System.out.print("\tSet" + i);
      for (e = 0; e < nSolutions; e++) {
        System.out.print(" ");
        model.set(GRB.IntParam.SolutionNumber, e);
        double val = model.get(GRB.DoubleAttr.ObjNVal);
        System.out.print("      " + val);
      }
      System.out.println();
    }
```

(continues on next page)

(continued from previous page)

```
      model.dispose();
      env.dispose();
    } catch (GRBException e) {
      System.out.println("Error code = " + e.getErrorCode());
      System.out.println(e.getMessage());
    }
  }
}
```

Multiscenario.java

```
// Copyright 2026, Gurobi Optimization, LLC

// Facility location: a company currently ships its product from 5 plants
// to 4 warehouses. It is considering closing some plants to reduce
// costs. What plant(s) should the company close, in order to minimize
// transportation and fixed costs?
//
// Since the plant fixed costs and the warehouse demands are uncertain, a
// scenario approach is chosen.
//
// Note that this example is similar to the Facility.java example. Here we
// added scenarios in order to illustrate the multi-scenario feature.
//
// Based on an example from Frontline Systems:
// http://www.solver.com/disfacility.htm
// Used with permission.

import com.gurobi.gurobi.*;

public class Multiscenario {

  public static void main(String[] args) {
    try {

      // Warehouse demand in thousands of units
      double Demand[] = new double[] { 15, 18, 14, 20 };

      // Plant capacity in thousands of units
      double Capacity[] = new double[] { 20, 22, 17, 19, 18 };

      // Fixed costs for each plant
      double FixedCosts[] =
        new double[] { 12000, 15000, 17000, 13000, 16000 };

      // Transportation costs per thousand units
      double TransCosts[][] =
        new double[][] { { 4000, 2000, 3000, 2500, 4500 },
                         { 2500, 2600, 3400, 3000, 4000 },
                         { 1200, 1800, 2600, 4100, 3000 },
```

(continues on next page)

(continued from previous page)

```
                        { 2200, 2600, 3100, 3700, 3200 } };

    // Number of plants and warehouses
    int nPlants = Capacity.length;
    int nWarehouses = Demand.length;

    double maxFixed = -GRB.INFINITY;
    double minFixed = GRB.INFINITY;
    for (int p = 0; p < nPlants; ++p) {
      if (FixedCosts[p] > maxFixed)
        maxFixed = FixedCosts[p];

      if (FixedCosts[p] < minFixed)
        minFixed = FixedCosts[p];
    }

    // Model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env);
    model.set(GRB.StringAttr.ModelName, "multiscenario");

    // Plant open decision variables: open[p] == 1 if plant p is open.
    GRBVar[] open = new GRBVar[nPlants];
    for (int p = 0; p < nPlants; ++p) {
      open[p] = model.addVar(0, 1, FixedCosts[p], GRB.BINARY, "Open" + p);
    }

    // Transportation decision variables: how much to transport from
    // a plant p to a warehouse w
    GRBVar[][] transport = new GRBVar[nWarehouses][nPlants];
    for (int w = 0; w < nWarehouses; ++w) {
      for (int p = 0; p < nPlants; ++p) {
        transport[w][p] = model.addVar(0, GRB.INFINITY, TransCosts[w][p],
                                       GRB.CONTINUOUS, "Trans" + p + "." + w);
      }
    }

    // The objective is to minimize the total fixed and variable costs
    model.set(GRB.IntAttr.ModelSense, GRB.MINIMIZE);

    // Production constraints
    // Note that the right-hand limit sets the production to zero if
    // the plant is closed
    for (int p = 0; p < nPlants; ++p) {
      GRBLinExpr ptot = new GRBLinExpr();
      for (int w = 0; w < nWarehouses; ++w) {
        ptot.addTerm(1.0, transport[w][p]);
      }
      GRBLinExpr limit = new GRBLinExpr();
      limit.addTerm(Capacity[p], open[p]);
      model.addConstr(ptot, GRB.LESS_EQUAL, limit, "Capacity" + p);
    }
```

(continues on next page)

(continued from previous page)

```
    // Demand constraints
    GRBConstr[] demandConstr = new GRBConstr[nWarehouses];
    for (int w = 0; w < nWarehouses; ++w) {
      GRBLinExpr dtot = new GRBLinExpr();
      for (int p = 0; p < nPlants; ++p) {
        dtot.addTerm(1.0, transport[w][p]);
      }
      demandConstr[w] = model.addConstr(dtot, GRB.EQUAL, Demand[w], "Demand" + w);
    }

    // We constructed the base model, now we add 7 scenarios
    //
    // Scenario 0: Represents the base model, hence, no manipulations.
    // Scenario 1: Manipulate the warehouses demands slightly (constraint right
    //             hand sides).
    // Scenario 2: Double the warehouses demands (constraint right hand sides).
    // Scenario 3: Manipulate the plant fixed costs (objective coefficients).
    // Scenario 4: Manipulate the warehouses demands and fixed costs.
    // Scenario 5: Force the plant with the largest fixed cost to stay open
    //             (variable bounds).
    // Scenario 6: Force the plant with the smallest fixed cost to be closed
    //             (variable bounds).

    model.set(GRB.IntAttr.NumScenarios, 7);

    // Scenario 0: Base model, hence, nothing to do except giving the
    //             scenario a name
    model.set(GRB.IntParam.ScenarioNumber, 0);
    model.set(GRB.StringAttr.ScenNName, "Base model");

    // Scenario 1: Increase the warehouse demands by 10%
    model.set(GRB.IntParam.ScenarioNumber, 1);
    model.set(GRB.StringAttr.ScenNName, "Increased warehouse demands");

    for (int w = 0; w < nWarehouses; w++) {
      demandConstr[w].set(GRB.DoubleAttr.ScenNRHS, Demand[w] * 1.1);
    }

    // Scenario 2: Double the warehouse demands
    model.set(GRB.IntParam.ScenarioNumber, 2);
    model.set(GRB.StringAttr.ScenNName, "Double the warehouse demands");

    for (int w = 0; w < nWarehouses; w++) {
      demandConstr[w].set(GRB.DoubleAttr.ScenNRHS, Demand[w] * 2.0);
    }

    // Scenario 3: Decrease the plant fixed costs by 5%
    model.set(GRB.IntParam.ScenarioNumber, 3);
    model.set(GRB.StringAttr.ScenNName, "Decreased plant fixed costs");

    for (int p = 0; p < nPlants; p++) {
```

(continues on next page)

(continued from previous page)

```
      open[p].set(GRB.DoubleAttr.ScenNObj, FixedCosts[p] * 0.95);
    }

    // Scenario 4: Combine scenario 1 and scenario 3 */
    model.set(GRB.IntParam.ScenarioNumber, 4);
    model.set(GRB.StringAttr.ScenNName, "Increased warehouse demands and decreased␣
↪plant fixed costs");

    for (int w = 0; w < nWarehouses; w++) {
      demandConstr[w].set(GRB.DoubleAttr.ScenNRHS, Demand[w] * 1.1);
    }
    for (int p = 0; p < nPlants; p++) {
      open[p].set(GRB.DoubleAttr.ScenNObj, FixedCosts[p] * 0.95);
    }

    // Scenario 5: Force the plant with the largest fixed cost to stay
    //             open
    model.set(GRB.IntParam.ScenarioNumber, 5);
    model.set(GRB.StringAttr.ScenNName, "Force plant with largest fixed cost to stay␣
↪open");

    for (int p = 0; p < nPlants; p++) {
      if (FixedCosts[p] == maxFixed) {
        open[p].set(GRB.DoubleAttr.ScenNLB, 1.0);
        break;
      }
    }

    // Scenario 6: Force the plant with the smallest fixed cost to be
    //             closed
    model.set(GRB.IntParam.ScenarioNumber, 6);
    model.set(GRB.StringAttr.ScenNName, "Force plant with smallest fixed cost to be␣
↪closed");

    for (int p = 0; p < nPlants; p++) {
      if (FixedCosts[p] == minFixed) {
        open[p].set(GRB.DoubleAttr.ScenNUB, 0.0);
        break;
      }
    }

    // Guess at the starting point: close the plant with the highest
    // fixed costs; open all others

    // First, open all plants
    for (int p = 0; p < nPlants; ++p) {
      open[p].set(GRB.DoubleAttr.Start, 1.0);
    }

    // Now close the plant with the highest fixed cost
    System.out.println("Initial guess:");
    for (int p = 0; p < nPlants; ++p) {
```

(continues on next page)

(continued from previous page)

```
        if (FixedCosts[p] == maxFixed) {
          open[p].set(GRB.DoubleAttr.Start, 0.0);
          System.out.println("Closing plant " + p + "\n");
          break;
        }
      }

      // Use barrier to solve root relaxation
      model.set(GRB.IntParam.Method, GRB.METHOD_BARRIER);

      // Solve multi-scenario model
      model.optimize();

      int nScenarios = model.get(GRB.IntAttr.NumScenarios);

      // Print solution for each */
      for (int s = 0; s < nScenarios; s++) {
        int modelSense = GRB.MINIMIZE;

        // Set the scenario number to query the information for this scenario
        model.set(GRB.IntParam.ScenarioNumber, s);

        // collect result for the scenario
        double scenNObjBound = model.get(GRB.DoubleAttr.ScenNObjBound);
        double scenNObjVal = model.get(GRB.DoubleAttr.ScenNObjVal);

        System.out.println("\n\n------ Scenario " + s +
                           " (" +  model.get(GRB.StringAttr.ScenNName) + ")");

        // Check if we found a feasible solution for this scenario
        if (modelSense * scenNObjVal >= GRB.INFINITY)
          if (modelSense * scenNObjBound >= GRB.INFINITY)
            // Scenario was proven to be infeasible
            System.out.println("\nINFEASIBLE");
          else
            // We did not find any feasible solution - should not happen in
            // this case, because we did not set any limit (like a time
            // limit) on the optimization process
            System.out.println("\nNO SOLUTION");
        else {
          System.out.println("\nTOTAL COSTS: " + scenNObjVal);
          System.out.println("SOLUTION:");
          for (int p = 0; p < nPlants; p++) {
            double scenNX = open[p].get(GRB.DoubleAttr.ScenNX);

            if (scenNX > 0.5) {
              System.out.println("Plant " + p + " open");
              for (int w = 0; w < nWarehouses; w++) {
                scenNX = transport[w][p].get(GRB.DoubleAttr.ScenNX);

                if (scenNX > 0.0001)
                  System.out.println("  Transport " + scenNX +
```

(continues on next page)

(continued from previous page)

```
                                    " units to warehouse " + w);
              }
            } else
              System.out.println("Plant " + p + " closed!");
          }
        }
      }

      // Print a summary table: for each scenario we add a single summary
      // line
      System.out.println("\n\nSummary: Closed plants depending on scenario\n");
      System.out.format("%8s | %17s %13s\n", "", "Plant", "|");

      System.out.format("%8s |", "Scenario");
      for (int p = 0; p < nPlants; p++)
        System.out.format(" %5d", p);
      System.out.format(" | %6s  %s\n", "Costs", "Name");

      for (int s = 0; s < nScenarios; s++) {
        int modelSense = GRB.MINIMIZE;

        // Set the scenario number to query the information for this scenario
        model.set(GRB.IntParam.ScenarioNumber, s);

        // Collect result for the scenario
        double scenNObjBound = model.get(GRB.DoubleAttr.ScenNObjBound);
        double scenNObjVal = model.get(GRB.DoubleAttr.ScenNObjVal);

        System.out.format("%-8d |", s);

        // Check if we found a feasible solution for this scenario
        if (modelSense * scenNObjVal >= GRB.INFINITY) {
          if (modelSense * scenNObjBound >= GRB.INFINITY)
            // Scenario was proven to be infeasible
            System.out.format(" %-30s| %6s  %s\n",
                              "infeasible", "-", model.get(GRB.StringAttr.ScenNName));
          else
            // We did not find any feasible solution - should not happen in
            // this case, because we did not set any limit (like a time
            // limit) on the optimization process
            System.out.format(" %-30s| %6s  %s\n",
                              "no solution found", "-", model.get(GRB.StringAttr.
↪ScenNName));
        } else {
          for (int p = 0; p < nPlants; p++) {
            double scenNX = open[p].get(GRB.DoubleAttr.ScenNX);
            if (scenNX  > 0.5)
              System.out.format("%6s", " ");
            else
              System.out.format("%6s", "x");
          }
```

(continues on next page)

(continued from previous page)

```
          System.out.format(" | %6g  %s\n", scenNObjVal, model.get(GRB.StringAttr.
↪ScenNName));
        }
      }

      // Dispose of model and environment
      model.dispose();
      env.dispose();
    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
                         e.getMessage());
    }
  }
}
```

NLConstr.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple nonlinear model
   using the nonlinear constraint API:

     minimize    x - y
     subject to  sin(x) * x + x^2 * y  <= 1
                 y = cos(x) (<=> cos(x) - y = 0)
                -1 <= x <= 2
                 0 <= y <= 2

   The nonlinear constraint is set via addNLConstr() using an expression tree.
   Then we retrieve the tree with getNLConstrLHS() and verify it, delete it with
   remove(), replace it with a simple linear constraint, and re-optimize.
*/

import com.gurobi.gurobi.*;

public class NLConstr {

  public static void main(String[] args) {
    try {
      // Create environment
      GRBEnv env = new GRBEnv("nlconstr.log");

      // Create empty model
      GRBModel model = new GRBModel(env);

      // Create variables
      GRBVar x = model.addVar(-1.0, 2.0, 1.0, GRB.CONTINUOUS, "x");
      GRBVar y = model.addVar( 0.0, 2.0, -1.0, GRB.CONTINUOUS, "y");

      /* Expression tree for sin(x) * x + x^2 * y (10 nodes)
```

(continues on next page)

(continued from previous page)

```
     *
     *   node 0: PLUS       (root)
     *   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
     *   node 2: SIN        (child of 1)
     *   node 3: VARIABLE x (child of 2)
     *   node 4: VARIABLE x (child of 1)
     *   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
     *   node 6: POW        (child of 5)
     *   node 7: VARIABLE x (child of 6)
     *   node 8: CONSTANT 2 (child of 6)
     *   node 9: VARIABLE y (child of 5)
     */

    int[] opcode1 = new int[] {
      GRB.OPCODE_PLUS,      // 0: root
      GRB.OPCODE_MULTIPLY,  // 1: sin(x)*x
      GRB.OPCODE_SIN,       // 2: sin(...)
      GRB.OPCODE_VARIABLE,  // 3: x
      GRB.OPCODE_VARIABLE,  // 4: x
      GRB.OPCODE_MULTIPLY,  // 5: x^2 * y
      GRB.OPCODE_POW,       // 6: x^2
      GRB.OPCODE_VARIABLE,  // 7: x
      GRB.OPCODE_CONSTANT,  // 8: 2.0
      GRB.OPCODE_VARIABLE   // 9: y
    };
    double[] data1 = new double[] {
      -1.0, -1.0, -1.0,
       x.index(),  // x index
       x.index(),  // x index
      -1.0, -1.0,
       x.index(),  // x index
       2.0,
       y.index()   // y index
    };
    int[] parent1 = new int[] {-1, 0, 1, 2, 1, 0, 5, 6, 6, 5};

    /* Expression tree for cos(x) - y = 0 (4 nodes)
     *
     *   node 0: MINUS      (root)
     *   node 1: COS        (child of 0)
     *   node 2: VARIABLE x (child of 1)
     *   node 3: VARIABLE y (child of 0)
     */

    int[] opcode2 = new int[] {
      GRB.OPCODE_MINUS,     // 0: root
      GRB.OPCODE_COS,       // 1: cos(...)
      GRB.OPCODE_VARIABLE,  // 2: x
      GRB.OPCODE_VARIABLE,  // 3: y
    };
    double[] data2 = new double[] {
      -1.0, -1.0,
```

(continues on next page)

(continued from previous page)

```
        x.index(),  // x index
        y.index()   // y index
    };
    int[] parent2 = new int[] {-1, 0, 1, 0};

    // Add nonlinear constraint: sin(x) * x + x^2 * y <= 1
    GRBNLConstr nlc1 = model.addNLConstr(opcode1, data1, parent1,
                                         GRB.LESS_EQUAL, 1.0,
                                         "NonlinearConstraint1");

    // Add nonlinear constraint: cos(x) - y = 0
    GRBNLConstr nlc2 = model.addNLConstr(opcode2, data2, parent2,
                                         GRB.EQUAL, 0.0,
                                         "NonlinearConstraint2");

    // Optimize model
    model.optimize();

    System.out.println("\nFirst solve (nonlinear constraints)");
    if (model.get(GRB.IntAttr.Status) == GRB.OPTIMAL) {
      System.out.printf("Optimal objective: %.4e%n",
                        model.get(GRB.DoubleAttr.ObjVal));
      System.out.printf("  x=%.6f, y=%.6f%n",
                        x.get(GRB.DoubleAttr.X),
                        y.get(GRB.DoubleAttr.X));
    } else if (model.get(GRB.IntAttr.Status) == GRB.INF_OR_UNBD) {
      System.out.println("Model is infeasible or unbounded");
    } else {
      System.out.println("Optimization was stopped early");
    }

    // Retrieve the nonlinear constraint and print the number of nodes
    int[] nnodes = new int[1];
    model.getNLConstrLHS(nlc1, nnodes, null, null, null);
    System.out.println("\nRetrieved NL constraint with " + nnodes[0] +
                       " nodes");

    // Delete nonlinear constraints
    model.remove(nlc1);
    model.remove(nlc2);
    model.update();
    System.out.println("Deleted nonlinear constraints");

    // Add a simple linear constraint instead: x + y >= 1
    GRBLinExpr expr = new GRBLinExpr();
    expr.addTerm(1.0, x);
    expr.addTerm(1.0, y);
    model.addConstr(expr, GRB.GREATER_EQUAL, 1.0, "LinearConstraint");

    // Re-optimize
    model.optimize();
```

(continues on next page)

(continued from previous page)

```
      System.out.println("\nSecond solve (linear constraint)");
      if (model.get(GRB.IntAttr.Status) == GRB.OPTIMAL) {
        System.out.printf("Optimal objective: %.4e%n",
                          model.get(GRB.DoubleAttr.ObjVal));
        System.out.printf("  x=%.6f, y=%.6f%n",
                          x.get(GRB.DoubleAttr.X),
                          y.get(GRB.DoubleAttr.X));
      } else if (model.get(GRB.IntAttr.Status) == GRB.INF_OR_UNBD) {
        System.out.println("Model is infeasible or unbounded");
      } else {
        System.out.println("Optimization was stopped early");
      }

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
                         e.getMessage());
    }
  }
}
```

NLObj.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple nonlinear model
   using the nonlinear objective API:

     minimize    sin(x) * x + x^2 * y
     subject to  x + y  >= 1
                -1 <= x <= 2
                 0 <= y <= 2

   The nonlinear objective is set via setNLObj() using an expression tree.
   Then we retrieve the tree with getNLObj() and verify it, delete it with
   delNLObj(), replace it with a simple linear objective, and re-optimize.
*/

import com.gurobi.gurobi.*;

public class NLObj {

  public static void main(String[] args) {
    try {
      // Create environment
      GRBEnv env = new GRBEnv("nlobj.log");
```

(continues on next page)

(continued from previous page)

```
      // Create empty model
      GRBModel model = new GRBModel(env);

      // Create variables
      GRBVar x = model.addVar(-1.0, 2.0, 0.0, GRB.CONTINUOUS, "x");
      GRBVar y = model.addVar( 0.0, 2.0, 0.0, GRB.CONTINUOUS, "y");

      // Add constraint: x + y >= 1
      GRBLinExpr expr = new GRBLinExpr();
      expr.addTerm(1.0, x);
      expr.addTerm(1.0, y);
      model.addConstr(expr, GRB.GREATER_EQUAL, 1.0, "c0");

      /* Expression tree for sin(x) * x + x^2 * y (10 nodes)
       *
       *   node 0: PLUS       (root)
       *   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
       *   node 2: SIN        (child of 1)
       *   node 3: VARIABLE x (child of 2)
       *   node 4: VARIABLE x (child of 1)
       *   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
       *   node 6: POW        (child of 5)
       *   node 7: VARIABLE x (child of 6)
       *   node 8: CONSTANT 2 (child of 6)
       *   node 9: VARIABLE y (child of 5)
       */

      int[] opcode = new int[] {
        GRB.OPCODE_PLUS,      // 0: root
        GRB.OPCODE_MULTIPLY,  // 1: sin(x)*x
        GRB.OPCODE_SIN,       // 2: sin(...)
        GRB.OPCODE_VARIABLE,  // 3: x
        GRB.OPCODE_VARIABLE,  // 4: x
        GRB.OPCODE_MULTIPLY,  // 5: x^2 * y
        GRB.OPCODE_POW,       // 6: x^2
        GRB.OPCODE_VARIABLE,  // 7: x
        GRB.OPCODE_CONSTANT,  // 8: 2.0
        GRB.OPCODE_VARIABLE   // 9: y
      };
      double[] data = new double[] {
        -1.0, -1.0, -1.0,
         x.index(),  // x index
         x.index(),  // x index
        -1.0, -1.0,
         x.index(),  // x index
         2.0,
         y.index()   // y index
      };
      int[] parent = new int[] {-1, 0, 1, 2, 1, 0, 5, 6, 6, 5};

      // Set nonlinear objective
      model.setNLObj(opcode, data, parent);
```

(continues on next page)

(continued from previous page)

```
    // Optimize model
    model.optimize();

    System.out.println("\nFirst solve (nonlinear objective)");
    if (model.get(GRB.IntAttr.Status) == GRB.OPTIMAL) {
      System.out.printf("Optimal objective: %.4e%n",
                        model.get(GRB.DoubleAttr.ObjVal));
      System.out.printf("  x=%.6f, y=%.6f%n",
                        x.get(GRB.DoubleAttr.X),
                        y.get(GRB.DoubleAttr.X));
    } else {
      System.out.println("Optimization did not produce an optimal solution");
    }

    // Retrieve the nonlinear objective and print the number of nodes
    int[] nnodes = new int[1];
    model.getNLObj(nnodes, null, null, null);
    System.out.println("\nRetrieved NL objective with " + nnodes[0] + " nodes");

    // Delete the nonlinear objective
    model.delNLObj();
    System.out.println("Deleted nonlinear objective");

    // Set a simple linear objective instead: minimize x + y
    GRBLinExpr linobj = new GRBLinExpr();
    linobj.addTerm(1.0, x);
    linobj.addTerm(1.0, y);
    model.setObjective(linobj, GRB.MINIMIZE);

    // Re-optimize
    model.optimize();

    System.out.println("\nSecond solve (linear objective)");
    if (model.get(GRB.IntAttr.Status) == GRB.OPTIMAL) {
      System.out.printf("Optimal objective: %.4e%n",
                        model.get(GRB.DoubleAttr.ObjVal));
      System.out.printf("  x=%.6f, y=%.6f%n",
                        x.get(GRB.DoubleAttr.X),
                        y.get(GRB.DoubleAttr.X));
    } else {
      System.out.println("Optimization did not produce an optimal solution");
    }

    // Dispose of model and environment
    model.dispose();
    env.dispose();

  } catch (GRBException e) {
    System.out.println("Error code: " + e.getErrorCode() + ". " +
                       e.getMessage());
  }
```

(continues on next page)

(continued from previous page)

```
  }
}
```

Params.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Use parameters that are associated with a model.

   A MIP is solved for a few seconds with different sets of parameters.
   The one with the smallest MIP gap is selected, and the optimization
   is resumed until the optimal solution is found.
*/

import com.gurobi.gurobi.*;

public class Params {

  public static void main(String[] args) {

    if (args.length < 1) {
      System.out.println("Usage: java Params filename");
      System.exit(1);
    }

    try {
      // Read model and verify that it is a MIP
      GRBEnv env = new GRBEnv();
      GRBModel m = new GRBModel(env, args[0]);
      if (m.get(GRB.IntAttr.IsMIP) == 0) {
        System.out.println("The model is not an integer program");
        System.exit(1);
      }

      // Set a 2 second time limit
      m.set(GRB.DoubleParam.TimeLimit, 2);

      // Now solve the model with different values of MIPFocus
      GRBModel bestModel = new GRBModel(m);
      bestModel.optimize();
      for (int i = 1; i <= 3; ++i) {
        m.reset();
        m.set(GRB.IntParam.MIPFocus, i);
        m.optimize();
        if (bestModel.get(GRB.DoubleAttr.MIPGap) >
                    m.get(GRB.DoubleAttr.MIPGap)) {
          GRBModel swap = bestModel;
          bestModel = m;
          m = swap;
        }
```

(continues on next page)

(continued from previous page)

```
      }

      // Delete the extra model, reset the time limit and
      // continue to solve the best model to optimality
      m.dispose();
      bestModel.set(GRB.DoubleParam.TimeLimit, GRB.INFINITY);
      bestModel.optimize();
      System.out.println("Solved with MIPFocus: " +
          bestModel.get(GRB.IntParam.MIPFocus));

      // Dispose of bestModel and env
      bestModel.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Piecewise.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example considers the following separable, convex problem:

     minimize    f(x) - y + g(z)
     subject to  x + 2 y + 3 z <= 4
                 x +   y       >= 1
                 x,    y,    z <= 1

   where f(u) = exp(-u) and g(u) = 2 u^2 - 4 u, for all real u. It
   formulates and solves a simpler LP model by approximating f and
   g with piecewise-linear functions. Then it transforms the model
   into a MIP by negating the approximation for f, which corresponds
   to a non-convex piecewise-linear function, and solves it again.
*/

import com.gurobi.gurobi.*;

public class Piecewise {

  private static double f(double u) { return Math.exp(-u); }
  private static double g(double u) { return 2 * u * u - 4 * u; }

  public static void main(String[] args) {
    try {

      // Create environment
```

(continues on next page)

(continued from previous page)

```
    GRBEnv env = new GRBEnv();

    // Create a new model

    GRBModel model = new GRBModel(env);

    // Create variables

    double lb = 0.0, ub = 1.0;

    GRBVar x = model.addVar(lb, ub, 0.0, GRB.CONTINUOUS, "x");
    GRBVar y = model.addVar(lb, ub, 0.0, GRB.CONTINUOUS, "y");
    GRBVar z = model.addVar(lb, ub, 0.0, GRB.CONTINUOUS, "z");

    // Set objective for y

    GRBLinExpr obj = new GRBLinExpr();
    obj.addTerm(-1.0, y);
    model.setObjective(obj);

    // Add piecewise-linear objective functions for x and z

    int npts = 101;
    double[] ptu = new double[npts];
    double[] ptf = new double[npts];
    double[] ptg = new double[npts];

    for (int i = 0; i < npts; i++) {
      ptu[i] = lb + (ub - lb) * i / (npts - 1);
      ptf[i] = f(ptu[i]);
      ptg[i] = g(ptu[i]);
    }

    model.setPWLObj(x, ptu, ptf);
    model.setPWLObj(z, ptu, ptg);

    // Add constraint: x + 2 y + 3 z <= 4

    GRBLinExpr expr = new GRBLinExpr();
    expr.addTerm(1.0, x); expr.addTerm(2.0, y); expr.addTerm(3.0, z);
    model.addConstr(expr, GRB.LESS_EQUAL, 4.0, "c0");

    // Add constraint: x + y >= 1

    expr = new GRBLinExpr();
    expr.addTerm(1.0, x); expr.addTerm(1.0, y);
    model.addConstr(expr, GRB.GREATER_EQUAL, 1.0, "c1");

    // Optimize model as an LP

    model.optimize();
```

(continues on next page)

(continued from previous page)

```
      System.out.println("IsMIP: " + model.get(GRB.IntAttr.IsMIP));

      System.out.println(x.get(GRB.StringAttr.VarName)
                         + " " +x.get(GRB.DoubleAttr.X));
      System.out.println(y.get(GRB.StringAttr.VarName)
                         + " " +y.get(GRB.DoubleAttr.X));
      System.out.println(z.get(GRB.StringAttr.VarName)
                         + " " +z.get(GRB.DoubleAttr.X));

      System.out.println("Obj: " + model.get(GRB.DoubleAttr.ObjVal));

      System.out.println();

      // Negate piecewise-linear objective function for x

      for (int i = 0; i < npts; i++) {
        ptf[i] = -ptf[i];
      }

      model.setPWLObj(x, ptu, ptf);

      // Optimize model as a MIP

      model.optimize();

      System.out.println("IsMIP: " + model.get(GRB.IntAttr.IsMIP));

      System.out.println(x.get(GRB.StringAttr.VarName)
                         + " " +x.get(GRB.DoubleAttr.X));
      System.out.println(y.get(GRB.StringAttr.VarName)
                         + " " +y.get(GRB.DoubleAttr.X));
      System.out.println(z.get(GRB.StringAttr.VarName)
                         + " " +z.get(GRB.DoubleAttr.X));

      System.out.println("Obj: " + model.get(GRB.DoubleAttr.ObjVal));

      // Dispose of model and environment

      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Poolsearch.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* We find alternative epsilon-optimal solutions to a given knapsack
   problem by using PoolSearchMode */

import com.gurobi.gurobi.*;

public class Poolsearch {

  public static void main(String[] args) {

    try{
      // Sample data
      int groundSetSize = 10;
      double objCoef[] = new double[] {32, 32, 15, 15, 6, 6, 1, 1, 1, 1};
      double knapsackCoef[] = new double[] {16, 16,  8,  8, 4, 4, 2, 2, 1, 1};
      double Budget = 33;
      int e, status, nSolutions;

      // Create environment
      GRBEnv env = new GRBEnv("Poolsearch.log");

      // Create initial model
      GRBModel model = new GRBModel(env);
      model.set(GRB.StringAttr.ModelName, "Poolsearch");

      // Initialize decision variables for ground set:
      // x[e] == 1 if element e is chosen
      GRBVar[] Elem = model.addVars(groundSetSize, GRB.BINARY);
      model.set(GRB.DoubleAttr.Obj, Elem, objCoef);

      for (e = 0; e < groundSetSize; e++) {
        Elem[e].set(GRB.StringAttr.VarName, "El" + String.valueOf(e));
      }

      // Constraint: limit total number of elements to be picked to be at most
      // Budget
      GRBLinExpr lhs = new GRBLinExpr();
      for (e = 0; e < groundSetSize; e++) {
        lhs.addTerm(knapsackCoef[e], Elem[e]);
      }
      model.addConstr(lhs, GRB.LESS_EQUAL, Budget, "Budget");

      // set global sense for ALL objectives
      model.set(GRB.IntAttr.ModelSense, GRB.MAXIMIZE);

      // Limit how many solutions to collect
      model.set(GRB.IntParam.PoolSolutions, 1024);

      // Limit the search space by setting a gap for the worst possible solution that␣
↪will be accepted
```

(continues on next page)

(continued from previous page)

```
    model.set(GRB.DoubleParam.PoolGap, 0.10);

    // do a systematic search for the k-best solutions
    model.set(GRB.IntParam.PoolSearchMode, 2);

    // save problem
    model.write("Poolsearch.lp");

    // Optimize
    model.optimize();

    // Status checking
    status = model.get(GRB.IntAttr.Status);

    if (status == GRB.INF_OR_UNBD ||
        status == GRB.INFEASIBLE  ||
        status == GRB.UNBOUNDED     ) {
      System.out.println("The model cannot be solved " +
             "because it is infeasible or unbounded");
      System.exit(1);
    }
    if (status != GRB.OPTIMAL) {
      System.out.println("Optimization was stopped with status " + status);
      System.exit(1);
    }

    // Print best selected set
    System.out.println("Selected elements in best solution:");
    System.out.print("\t");
    for (e = 0; e < groundSetSize; e++) {
      if (Elem[e].get(GRB.DoubleAttr.X) < .9) continue;
      System.out.print(" El" + e);
    }
    System.out.println();

    // Print number of solutions stored
    nSolutions = model.get(GRB.IntAttr.SolCount);
    System.out.println("Number of solutions found: " + nSolutions);

    // Print objective values of solutions
    for (e = 0; e < nSolutions; e++) {
      model.set(GRB.IntParam.SolutionNumber, e);
      System.out.print(model.get(GRB.DoubleAttr.PoolNObjVal) +  " ");
      if (e%15 == 14) System.out.println();
    }
    System.out.println();

    // print fourth best set if available
    if (nSolutions >= 4) {
      model.set(GRB.IntParam.SolutionNumber, 3);

      System.out.println("Selected elements in fourth best solution:");
```

(continues on next page)

(continued from previous page)

```
        System.out.print("\t");
        for (e = 0; e < groundSetSize; e++) {
          if (Elem[e].get(GRB.DoubleAttr.PoolNX) < .9) continue;
          System.out.print(" El" + e);
        }
        System.out.println();
      }

      model.dispose();
      env.dispose();
    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }

}
```

Qcp.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QCP model:

     maximize    x
     subject to  x + y + z = 1
                 x^2 + y^2 <= z^2 (second-order cone)
                 x^2 <= yz        (rotated second-order cone)
                 x, y, z non-negative
*/

import com.gurobi.gurobi.*;

public class Qcp {
  public static void main(String[] args) {
    try {
      GRBEnv    env   = new GRBEnv("qcp.log");
      GRBModel  model = new GRBModel(env);

      // Create variables

      GRBVar x = model.addVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "x");
      GRBVar y = model.addVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "y");
      GRBVar z = model.addVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "z");

      // Set objective

      GRBLinExpr obj = new GRBLinExpr();
      obj.addTerm(1.0, x);
      model.setObjective(obj, GRB.MAXIMIZE);
```

(continues on next page)

(continued from previous page)

```
      // Add linear constraint: x + y + z = 1

      GRBLinExpr expr = new GRBLinExpr();
      expr.addTerm(1.0, x); expr.addTerm(1.0, y); expr.addTerm(1.0, z);
      model.addConstr(expr, GRB.EQUAL, 1.0, "c0");

      // Add second-order cone: x^2 + y^2 <= z^2

      GRBQuadExpr qexpr = new GRBQuadExpr();
      qexpr.addTerm(1.0, x, x);
      qexpr.addTerm(1.0, y, y);
      qexpr.addTerm(-1.0, z, z);
      model.addQConstr(qexpr, GRB.LESS_EQUAL, 0.0, "qc0");

      // Add rotated cone: x^2 <= yz

      qexpr = new GRBQuadExpr();
      qexpr.addTerm(1.0, x, x);
      qexpr.addTerm(-1.0, y, z);
      model.addQConstr(qexpr, GRB.LESS_EQUAL, 0.0, "qc1");

      // Optimize model

      model.optimize();

      System.out.println(x.get(GRB.StringAttr.VarName)
                         + " " +x.get(GRB.DoubleAttr.X));
      System.out.println(y.get(GRB.StringAttr.VarName)
                         + " " +y.get(GRB.DoubleAttr.X));
      System.out.println(z.get(GRB.StringAttr.VarName)
                         + " " +z.get(GRB.DoubleAttr.X));

      System.out.println("Obj: " + model.get(GRB.DoubleAttr.ObjVal) + " " +
                         obj.getValue());
      System.out.println();

      // Dispose of model and environment

      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Qp.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example formulates and solves the following simple QP model:

     minimize    x^2 + x*y + y^2 + y*z + z^2 + 2 x
     subject to  x + 2 y + 3 z >= 4
                 x +   y       >= 1
                 x, y, z non-negative

   It solves it once as a continuous model, and once as an integer model.
*/

import com.gurobi.gurobi.*;

public class Qp {
  public static void main(String[] args) {
    try {
      GRBEnv    env   = new GRBEnv("qp.log");
      GRBModel  model = new GRBModel(env);

      // Create variables

      GRBVar x = model.addVar(0.0, 1.0, 0.0, GRB.CONTINUOUS, "x");
      GRBVar y = model.addVar(0.0, 1.0, 0.0, GRB.CONTINUOUS, "y");
      GRBVar z = model.addVar(0.0, 1.0, 0.0, GRB.CONTINUOUS, "z");

      // Set objective

      GRBQuadExpr obj = new GRBQuadExpr();
      obj.addTerm(1.0, x, x);
      obj.addTerm(1.0, x, y);
      obj.addTerm(1.0, y, y);
      obj.addTerm(1.0, y, z);
      obj.addTerm(1.0, z, z);
      obj.addTerm(2.0, x);
      model.setObjective(obj);

      // Add constraint: x + 2 y + 3 z >= 4

      GRBLinExpr expr = new GRBLinExpr();
      expr.addTerm(1.0, x); expr.addTerm(2.0, y); expr.addTerm(3.0, z);
      model.addConstr(expr, GRB.GREATER_EQUAL, 4.0, "c0");

      // Add constraint: x + y >= 1

      expr = new GRBLinExpr();
      expr.addTerm(1.0, x); expr.addTerm(1.0, y);
      model.addConstr(expr, GRB.GREATER_EQUAL, 1.0, "c1");

      // Optimize model
```

(continues on next page)

(continued from previous page)

```
      model.optimize();

      System.out.println(x.get(GRB.StringAttr.VarName)
                         + " " +x.get(GRB.DoubleAttr.X));
      System.out.println(y.get(GRB.StringAttr.VarName)
                         + " " +y.get(GRB.DoubleAttr.X));
      System.out.println(z.get(GRB.StringAttr.VarName)
                         + " " +z.get(GRB.DoubleAttr.X));

      System.out.println("Obj: " + model.get(GRB.DoubleAttr.ObjVal) + " " +
                         obj.getValue());
      System.out.println();


      // Change variable types to integer

      x.set(GRB.CharAttr.VType, GRB.INTEGER);
      y.set(GRB.CharAttr.VType, GRB.INTEGER);
      z.set(GRB.CharAttr.VType, GRB.INTEGER);

      // Optimize again

      model.optimize();

      System.out.println(x.get(GRB.StringAttr.VarName)
                         + " " +x.get(GRB.DoubleAttr.X));
      System.out.println(y.get(GRB.StringAttr.VarName)
                         + " " +y.get(GRB.DoubleAttr.X));
      System.out.println(z.get(GRB.StringAttr.VarName)
                         + " " +z.get(GRB.DoubleAttr.X));

      System.out.println("Obj: " + model.get(GRB.DoubleAttr.ObjVal) + " " +
                         obj.getValue());

      // Dispose of model and environment

      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Sensitivity.java

```
// Copyright 2026, Gurobi Optimization, LLC

// A simple sensitivity analysis example which reads a MIP model from a
// file and solves it. Then uses the scenario feature to analyze the impact
// w.r.t. the objective function of each binary variable if it is set to
// 1-X, where X is its value in the optimal solution.
//
// Usage:
//     java Sensitivity <model filename>

import com.gurobi.gurobi.*;

public class Sensitivity {

    // Maximum number of scenarios to be considered
    private static final int MAXSCENARIOS = 100;

    public static void main(String[] args) {

    if (args.length < 1) {
      System.out.println("Usage: java Sensitivity filename");
      System.exit(1);
    }

    try {

      // Create environment
      GRBEnv env = new GRBEnv();

      // Read model
      GRBModel model = new GRBModel(env, args[0]);

      int scenarios;

      if (model.get(GRB.IntAttr.IsMIP) == 0) {
        System.out.println("Model is not a MIP");
        System.exit(1);
      }

      // Solve model
      model.optimize();

      if (model.get(GRB.IntAttr.Status) != GRB.OPTIMAL) {
        System.out.println("Optimization ended with status "
                           + model.get(GRB.IntAttr.Status));
        System.exit(1);
      }

      // Store the optimal solution
      double   origObjVal = model.get(GRB.DoubleAttr.ObjVal);
      GRBVar[] vars       = model.getVars();
```

(continues on next page)

(continued from previous page)

```
    double[] origX      = model.get(GRB.DoubleAttr.X, vars);

    scenarios = 0;

    // Count number of unfixed, binary variables in model. For each we
    // create a scenario.
    for (int i = 0; i < vars.length; i++) {
      GRBVar v     = vars[i];
      char   vType = v.get(GRB.CharAttr.VType);

      if (v.get(GRB.DoubleAttr.LB) == 0                 &&
          v.get(GRB.DoubleAttr.UB) == 1                 &&
          (vType == GRB.BINARY || vType == GRB.INTEGER)   ) {

        scenarios++;

        if (scenarios >= MAXSCENARIOS)
          break;
      }
    }

    System.out.println("###  construct multi-scenario model with "
                       + scenarios + " scenarios");

    // Set the number of scenarios in the model */
    model.set(GRB.IntAttr.NumScenarios, scenarios);

    scenarios = 0;

    // Create a (single) scenario model by iterating through unfixed
    // binary variables in the model and create for each of these
    // variables a scenario by fixing the variable to 1-X, where X is its
    // value in the computed optimal solution
    for (int i = 0; i < vars.length; i++) {
      GRBVar v     = vars[i];
      char   vType = v.get(GRB.CharAttr.VType);

      if (v.get(GRB.DoubleAttr.LB) == 0                 &&
          v.get(GRB.DoubleAttr.UB) == 1                 &&
          (vType == GRB.BINARY || vType == GRB.INTEGER) &&
          scenarios < MAXSCENARIOS                        ) {

        // Set ScenarioNumber parameter to select the corresponding
        // scenario for adjustments
        model.set(GRB.IntParam.ScenarioNumber, scenarios);

        // Set variable to 1-X, where X is its value in the optimal solution */
        if (origX[i] < 0.5)
          v.set(GRB.DoubleAttr.ScenNLB, 1.0);
        else
          v.set(GRB.DoubleAttr.ScenNUB, 0.0);
```

(continues on next page)

(continued from previous page)

```
        scenarios++;
      } else {
        // Add MIP start for all other variables using the optimal
        // solution of the base model
        v.set(GRB.DoubleAttr.Start, origX[i]);
      }
    }

    // Solve multi-scenario model
    model.optimize();

    // In case we solved the scenario model to optimality capture the
    // sensitivity information
    if (model.get(GRB.IntAttr.Status) == GRB.OPTIMAL) {

      // get the model sense (minimization or maximization)
      int modelSense = model.get(GRB.IntAttr.ModelSense);

      scenarios = 0;

      for (int i = 0; i < vars.length; i++) {
        GRBVar v     = vars[i];
        char   vType = v.get(GRB.CharAttr.VType);

        if (v.get(GRB.DoubleAttr.LB) == 0                 &&
            v.get(GRB.DoubleAttr.UB) == 1                 &&
            (vType == GRB.BINARY || vType == GRB.INTEGER)   ) {

          // Set scenario parameter to collect the objective value of the
          // corresponding scenario
          model.set(GRB.IntParam.ScenarioNumber, scenarios);

          // Collect objective value and bound for the scenario
          double scenarioObjVal = model.get(GRB.DoubleAttr.ScenNObjVal);
          double scenarioObjBound = model.get(GRB.DoubleAttr.ScenNObjBound);

          System.out.print("Objective sensitivity for variable "
                           + v.get(GRB.StringAttr.VarName) + " is ");

          // Check if we found a feasible solution for this scenario
          if (modelSense * scenarioObjVal >= GRB.INFINITY) {
            // Check if the scenario is infeasible
            if (modelSense * scenarioObjBound >= GRB.INFINITY)
              System.out.println("infeasible");
            else
              System.out.println("unknown (no solution available)");
          } else {
            // Scenario is feasible and a solution is available
            System.out.println("" + modelSense * (scenarioObjVal - origObjVal));
          }

          scenarios++;
```

(continues on next page)

(continued from previous page)

```
            if (scenarios >= MAXSCENARIOS)
              break;
          }
        }
      }

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode());
      System.out.println(e.getMessage());
      e.printStackTrace();
    }
  }
}
```

Sos.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example creates a very simple Special Ordered Set (SOS) model.
   The model consists of 3 continuous variables, no linear constraints,
   and a pair of SOS constraints of type 1. */

import com.gurobi.gurobi.*;

public class Sos {
  public static void main(String[] args) {
    try {
      GRBEnv env = new GRBEnv();

      GRBModel model = new GRBModel(env);

      // Create variables

      double ub[]    = {1, 1, 2};
      double obj[]   = {-2, -1, -1};
      String names[] = {"x0", "x1", "x2"};

      GRBVar[] x = model.addVars(null, ub, obj, null, names);

      // Add first SOS1: x0=0 or x1=0

      GRBVar sosv1[]  = {x[0], x[1]};
      double soswt1[] = {1, 2};

      model.addSOS(sosv1, soswt1, GRB.SOS_TYPE1);
```

(continues on next page)

(continued from previous page)

```
      // Add second SOS1: x0=0 or x2=0

      GRBVar sosv2[]  = {x[0], x[2]};
      double soswt2[] = {1, 2};

      model.addSOS(sosv2, soswt2, GRB.SOS_TYPE1);

      // Optimize model

      model.optimize();

      for (int i = 0; i < 3; i++)
        System.out.println(x[i].get(GRB.StringAttr.VarName) + " "
                           + x[i].get(GRB.DoubleAttr.X));

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Sudoku.java

```
/* Copyright 2026, Gurobi Optimization, LLC */
/*
  Sudoku example.

  The Sudoku board is a 9x9 grid, which is further divided into a 3x3 grid
  of 3x3 grids.  Each cell in the grid must take a value from 0 to 9.
  No two grid cells in the same row, column, or 3x3 subgrid may take the
  same value.

  In the MIP formulation, binary variables x[i,j,v] indicate whether
  cell <i,j> takes value 'v'.  The constraints are as follows:
    1. Each cell must take exactly one value (sum_v x[i,j,v] = 1)
    2. Each value is used exactly once per row (sum_i x[i,j,v] = 1)
    3. Each value is used exactly once per column (sum_j x[i,j,v] = 1)
    4. Each value is used exactly once per 3x3 subgrid (sum_grid x[i,j,v] = 1)

  Input datasets for this example can be found in examples/data/sudoku*.
*/

import com.gurobi.gurobi.*;
import java.io.*;
```

(continues on next page)

(continued from previous page)

```
public class Sudoku {
  public static void main(String[] args) {
    int n = 9;
    int s = 3;

    if (args.length < 1) {
      System.out.println("Usage: java Sudoku filename");
      System.exit(1);
    }

    try {
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env);

      // Create 3-D array of model variables

      GRBVar[][][] vars = new GRBVar[n][n][n];

      for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
          for (int v = 0; v < n; v++) {
            String st = "G_" + String.valueOf(i) + "_" + String.valueOf(j)
                              + "_" + String.valueOf(v);
            vars[i][j][v] = model.addVar(0.0, 1.0, 0.0, GRB.BINARY, st);
          }
        }
      }

      // Add constraints

      GRBLinExpr expr;

      // Each cell must take one value

      for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
          expr = new GRBLinExpr();
          expr.addTerms(null, vars[i][j]);
          String st = "V_" + String.valueOf(i) + "_" + String.valueOf(j);
          model.addConstr(expr, GRB.EQUAL, 1.0, st);
        }
      }

      // Each value appears once per row

      for (int i = 0; i < n; i++) {
        for (int v = 0; v < n; v++) {
          expr = new GRBLinExpr();
          for (int j = 0; j < n; j++)
            expr.addTerm(1.0, vars[i][j][v]);
          String st = "R_" + String.valueOf(i) + "_" + String.valueOf(v);
```

(continues on next page)

(continued from previous page)

```
        model.addConstr(expr, GRB.EQUAL, 1.0, st);
      }
    }

    // Each value appears once per column

    for (int j = 0; j < n; j++) {
      for (int v = 0; v < n; v++) {
        expr = new GRBLinExpr();
        for (int i = 0; i < n; i++)
          expr.addTerm(1.0, vars[i][j][v]);
        String st = "C_" + String.valueOf(j) + "_" + String.valueOf(v);
        model.addConstr(expr, GRB.EQUAL, 1.0, st);
      }
    }

    // Each value appears once per sub-grid

    for (int v = 0; v < n; v++) {
      for (int i0 = 0; i0 < s; i0++) {
        for (int j0 = 0; j0 < s; j0++) {
          expr = new GRBLinExpr();
          for (int i1 = 0; i1 < s; i1++) {
            for (int j1 = 0; j1 < s; j1++) {
              expr.addTerm(1.0, vars[i0*s+i1][j0*s+j1][v]);
            }
          }
          String st = "Sub_" + String.valueOf(v) + "_" + String.valueOf(i0)
                            + "_" + String.valueOf(j0);
          model.addConstr(expr, GRB.EQUAL, 1.0, st);
        }
      }
    }

    // Fix variables associated with pre-specified cells

    File file = new File(args[0]);

    try (BufferedReader br = new BufferedReader(new FileReader(file))) {
      for (int i = 0; i < n; i++) {
          String line = br.readLine();
          for (int j = 0; j < n; j++) {
            char c = line.charAt(j);
            if (Character.isDigit(c)) {
              vars[i][j][Character.getNumericValue(c)-1].set(GRB.DoubleAttr.LB, 1.0);
            }
          }
      }
    }


    // Optimize model
```

(continues on next page)

(continued from previous page)

```
      model.optimize();

      // Write model to file
      model.write("sudoku.lp");

      double[][][] x = model.get(GRB.DoubleAttr.X, vars);

      System.out.println();
      for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
          for (int v = 0; v < n; v++) {
            if (x[i][j][v] > 0.5) {
              System.out.print(v+1);
            }
          }
        }
        System.out.println();
      }

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    } catch (IOException e) {
      System.out.println("IO Error");
    }
  }
}
```

Tsp.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

// Solve a traveling salesman problem on a randomly generated set of
// points using lazy constraints.   The base MIP model only includes
// 'degree-2' constraints, requiring each node to have exactly
// two incident edges.  Solutions to this model may contain subtours -
// tours that don't visit every node.  The lazy constraint callback
// adds new constraints to cut them off.

import com.gurobi.gurobi.*;

public class Tsp extends GRBCallback {
  private GRBVar[][] vars;

  public Tsp(GRBVar[][] xvars) {
```

(continues on next page)

(continued from previous page)

```
  vars = xvars;
}

// Subtour elimination callback.  Whenever a feasible solution is found,
// find the subtour that contains node 0, and add a subtour elimination
// constraint if the tour doesn't visit every node.

protected void callback() {
  try {
    if (where == GRB.CB_MIPSOL) {
      // Found an integer feasible solution - does it visit every node?
      int n = vars.length;
      int[] tour = findsubtour(getSolution(vars));

      if (tour.length < n) {
        // Add subtour elimination constraint
        GRBLinExpr expr = new GRBLinExpr();
        for (int i = 0; i < tour.length; i++)
          for (int j = i+1; j < tour.length; j++)
            expr.addTerm(1.0, vars[tour[i]][tour[j]]);
        addLazy(expr, GRB.LESS_EQUAL, tour.length-1);
      }
    }
  } catch (GRBException e) {
    System.out.println("Error code: " + e.getErrorCode() + ". " +
        e.getMessage());
    e.printStackTrace();
  }
}

// Given an integer-feasible solution 'sol', return the smallest
// sub-tour (as a list of node indices).

protected static int[] findsubtour(double[][] sol)
{
  int n = sol.length;
  boolean[] seen = new boolean[n];
  int[] tour = new int[n];
  int bestind, bestlen;
  int i, node, len, start;

  for (i = 0; i < n; i++)
    seen[i] = false;

  start = 0;
  bestlen = n+1;
  bestind = -1;
  node = 0;
  while (start < n) {
    for (node = 0; node < n; node++)
      if (!seen[node])
        break;
```

(continues on next page)

(continued from previous page)

```
    if (node == n)
      break;
    for (len = 0; len < n; len++) {
      tour[start+len] = node;
      seen[node] = true;
      for (i = 0; i < n; i++) {
        if (sol[node][i] > 0.5 && !seen[i]) {
          node = i;
          break;
        }
      }
      if (i == n) {
        len++;
        if (len < bestlen) {
          bestlen = len;
          bestind = start;
        }
        start += len;
        break;
      }
    }
  }

  int result[] = new int[bestlen];
  for (i = 0; i < bestlen; i++)
    result[i] = tour[bestind+i];
  return result;
}

// Euclidean distance between points 'i' and 'j'

protected static double distance(double[] x,
                                 double[] y,
                                 int      i,
                                 int      j) {
  double dx = x[i]-x[j];
  double dy = y[i]-y[j];
  return Math.sqrt(dx*dx+dy*dy);
}

public static void main(String[] args) {

  if (args.length < 1) {
    System.out.println("Usage: java Tsp ncities");
    System.exit(1);
  }

  int n = Integer.parseInt(args[0]);

  try {
    GRBEnv   env   = new GRBEnv();
    GRBModel model = new GRBModel(env);
```

(continues on next page)

(continued from previous page)

```
    // Must set LazyConstraints parameter when using lazy constraints

    model.set(GRB.IntParam.LazyConstraints, 1);

    double[] x = new double[n];
    double[] y = new double[n];

    for (int i = 0; i < n; i++) {
      x[i] = Math.random();
      y[i] = Math.random();
    }

    // Create variables

    GRBVar[][] vars = new GRBVar[n][n];

    for (int i = 0; i < n; i++)
      for (int j = 0; j <= i; j++) {
        vars[i][j] = model.addVar(0.0, 1.0, distance(x, y, i, j),
                                  GRB.BINARY,
                                "x"+String.valueOf(i)+"_"+String.valueOf(j));
        vars[j][i] = vars[i][j];
      }

    // Degree-2 constraints

    for (int i = 0; i < n; i++) {
      GRBLinExpr expr = new GRBLinExpr();
      for (int j = 0; j < n; j++)
        expr.addTerm(1.0, vars[i][j]);
      model.addConstr(expr, GRB.EQUAL, 2.0, "deg2_"+String.valueOf(i));
    }

    // Forbid edge from node back to itself

    for (int i = 0; i < n; i++)
      vars[i][i].set(GRB.DoubleAttr.UB, 0.0);

    model.setCallback(new Tsp(vars));
    model.optimize();

    if (model.get(GRB.IntAttr.SolCount) > 0) {
      int[] tour = findsubtour(model.get(GRB.DoubleAttr.X, vars));
      assert tour.length == n;

      System.out.print("Tour: ");
      for (int i = 0; i < tour.length; i++)
        System.out.print(String.valueOf(tour[i]) + " ");
      System.out.println();
    }
```

(continues on next page)

(continued from previous page)

```
      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
      e.printStackTrace();
    }
  }
}
```

Tune.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* This example reads a model from a file and tunes it.
   It then writes the best parameter settings to a file
   and solves the model using these parameters. */

import com.gurobi.gurobi.*;

public class Tune {
  public static void main(String[] args) {

    if (args.length < 1) {
      System.out.println("Usage: java Tune filename");
      System.exit(1);
    }

    try {
      GRBEnv env = new GRBEnv();

      // Read model from file
      GRBModel model = new GRBModel(env, args[0]);

      // Set a time limit for the model
      model.set(GRB.DoubleParam.TimeLimit, 5);

      // Set a time limit for the whole tuning run
      // Note that both time limits are chosen to have a quick demonstration.
      // In general, a total tune time limit should be set such that the
      // tuning tool can test several hundreds of parameter setting
      model.set(GRB.DoubleParam.TuneTimeLimit, 60);

      // Set the TuneResults parameter to 2
      //
      // The first parameter setting is the result for the first solved
      // setting. The second entry the parameter setting of the best
      // parameter setting.
```

(continues on next page)

(continued from previous page)

```
      model.set(GRB.IntParam.TuneResults, 2);

      // Tune the model
      model.tune();

      // Get the number of tuning results
      int resultcount = model.get(GRB.IntAttr.TuneResultCount);

      if (resultcount >= 2) {

        // Load the tuned parameters into the model's environment
        //
        // Note, the first parameter setting is associated to the first
        // solved setting and the second parameter setting to best tune
        // result.
        model.getTuneResult(1);

        // Write the tuned parameters to a file
        model.write("tune.prm");

        // Solve the model using the tuned parameters
        model.optimize();
      }

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". "
          + e.getMessage());
    }
  }
}
```

Workforce1.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, use IIS to find a set of
   conflicting constraints. Note that there may be additional conflicts
   besides what is reported via IIS. */

import com.gurobi.gurobi.*;

public class Workforce1 {

  public static void main(String[] args) {
    try {
```

(continues on next page)

(continued from previous page)

```
    // Sample data
    // Sets of days and workers
    String Shifts[] =
        new String[] { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
            "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
            "Sun14" };
    String Workers[] =
        new String[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

    int nShifts = Shifts.length;
    int nWorkers = Workers.length;

    // Number of workers required for each shift
    double shiftRequirements[] =
        new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

    // Amount each worker is paid to work one shift
    double pay[] = new double[] { 10, 12, 10, 8, 8, 9, 11 };

    // Worker availability: 0 if the worker is unavailable for a shift
    double availability[][] =
        new double[][] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
            { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
            { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
            { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
            { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
            { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
            { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

    // Model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env);
    model.set(GRB.StringAttr.ModelName, "assignment");

    // Assignment variables: x[w][s] == 1 if worker w is assigned
    // to shift s. Since an assignment model always produces integer
    // solutions, we use continuous variables and solve as an LP.
    GRBVar[][] x = new GRBVar[nWorkers][nShifts];
    for (int w = 0; w < nWorkers; ++w) {
      for (int s = 0; s < nShifts; ++s) {
        x[w][s] =
            model.addVar(0, availability[w][s], pay[w], GRB.CONTINUOUS,
                         Workers[w] + "." + Shifts[s]);
      }
    }

    // The objective is to minimize the total pay costs
    model.set(GRB.IntAttr.ModelSense, GRB.MINIMIZE);

    // Constraint: assign exactly shiftRequirements[s] workers
    // to each shift s
```

(continues on next page)

(continued from previous page)

```
      for (int s = 0; s < nShifts; ++s) {
        GRBLinExpr lhs = new GRBLinExpr();
        for (int w = 0; w < nWorkers; ++w) {
          lhs.addTerm(1.0, x[w][s]);
        }
        model.addConstr(lhs, GRB.EQUAL, shiftRequirements[s], Shifts[s]);
      }

      // Optimize
      model.optimize();
      int status = model.get(GRB.IntAttr.Status);
      if (status == GRB.Status.UNBOUNDED) {
        System.out.println("The model cannot be solved "
            + "because it is unbounded");
        return;
      }
      if (status == GRB.Status.OPTIMAL) {
        System.out.println("The optimal objective is " +
            model.get(GRB.DoubleAttr.ObjVal));
        return;
      }
      if (status != GRB.Status.INF_OR_UNBD &&
          status != GRB.Status.INFEASIBLE    ){
        System.out.println("Optimization was stopped with status " + status);
        return;
      }

      // Compute IIS
      System.out.println("The model is infeasible; computing IIS");
      model.computeIIS();
      System.out.println("\nThe following constraint(s) "
          + "cannot be satisfied:");
      for (GRBConstr c : model.getConstrs()) {
        if (c.get(GRB.IntAttr.IISConstr) == 1) {
          System.out.println(c.get(GRB.StringAttr.ConstrName));
        }
      }

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Workforce2.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, use IIS iteratively to
   find all conflicting constraints. */

import com.gurobi.gurobi.*;
import java.util.*;

public class Workforce2 {

  public static void main(String[] args) {
    try {

      // Sample data
      // Sets of days and workers
      String Shifts[] =
          new String[] { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
              "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
              "Sun14" };
      String Workers[] =
          new String[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

      int nShifts = Shifts.length;
      int nWorkers = Workers.length;

      // Number of workers required for each shift
      double shiftRequirements[] =
          new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

      // Amount each worker is paid to work one shift
      double pay[] = new double[] { 10, 12, 10, 8, 8, 9, 11 };

      // Worker availability: 0 if the worker is unavailable for a shift
      double availability[][] =
          new double[][] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
              { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
              { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
              { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
              { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
              { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
              { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

      // Model
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env);
      model.set(GRB.StringAttr.ModelName, "assignment");

      // Assignment variables: x[w][s] == 1 if worker w is assigned
      // to shift s. Since an assignment model always produces integer
      // solutions, we use continuous variables and solve as an LP.
```

(continues on next page)

(continued from previous page)

```
    GRBVar[][] x = new GRBVar[nWorkers][nShifts];
    for (int w = 0; w < nWorkers; ++w) {
      for (int s = 0; s < nShifts; ++s) {
        x[w][s] =
            model.addVar(0, availability[w][s], pay[w], GRB.CONTINUOUS,
                         Workers[w] + "." + Shifts[s]);
      }
    }

    // The objective is to minimize the total pay costs
    model.set(GRB.IntAttr.ModelSense, GRB.MINIMIZE);

    // Constraint: assign exactly shiftRequirements[s] workers
    // to each shift s
    for (int s = 0; s < nShifts; ++s) {
      GRBLinExpr lhs = new GRBLinExpr();
      for (int w = 0; w < nWorkers; ++w) {
        lhs.addTerm(1.0, x[w][s]);
      }
      model.addConstr(lhs, GRB.EQUAL, shiftRequirements[s], Shifts[s]);
    }

    // Optimize
    model.optimize();
    int status = model.get(GRB.IntAttr.Status);
    if (status == GRB.Status.UNBOUNDED) {
      System.out.println("The model cannot be solved "
          + "because it is unbounded");
      return;
    }
    if (status == GRB.Status.OPTIMAL) {
      System.out.println("The optimal objective is " +
          model.get(GRB.DoubleAttr.ObjVal));
      return;
    }
    if (status != GRB.Status.INF_OR_UNBD &&
        status != GRB.Status.INFEASIBLE    ) {
      System.out.println("Optimization was stopped with status " + status);
      return;
    }

    // Do IIS
    System.out.println("The model is infeasible; computing IIS");
    LinkedList<String> removed = new LinkedList<String>();

    // Loop until we reduce to a model that can be solved
    while (true) {
      model.computeIIS();
      System.out.println("\nThe following constraint cannot be satisfied:");
      for (GRBConstr c : model.getConstrs()) {
        if (c.get(GRB.IntAttr.IISConstr) == 1) {
          System.out.println(c.get(GRB.StringAttr.ConstrName));
```

(continues on next page)

(continued from previous page)

```
            // Remove a single constraint from the model
            removed.add(c.get(GRB.StringAttr.ConstrName));
            model.remove(c);
            break;
          }
        }

        System.out.println();
        model.optimize();
        status = model.get(GRB.IntAttr.Status);

        if (status == GRB.Status.UNBOUNDED) {
          System.out.println("The model cannot be solved "
              + "because it is unbounded");
          return;
        }
        if (status == GRB.Status.OPTIMAL) {
          break;
        }
        if (status != GRB.Status.INF_OR_UNBD &&
            status != GRB.Status.INFEASIBLE    ) {
          System.out.println("Optimization was stopped with status " +
              status);
          return;
        }
      }

      System.out.println("\nThe following constraints were removed "
          + "to get a feasible LP:");
      for (String s : removed) {
        System.out.print(s + " ");
      }
      System.out.println();

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Workforce3.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. If the problem cannot be solved, relax the model
   to determine which constraints cannot be satisfied, and how much
   they need to be relaxed. */

import com.gurobi.gurobi.*;

public class Workforce3 {

  public static void main(String[] args) {
    try {

      // Sample data
      // Sets of days and workers
      String Shifts[] =
          new String[] { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
              "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
              "Sun14" };
      String Workers[] =
          new String[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

      int nShifts = Shifts.length;
      int nWorkers = Workers.length;

      // Number of workers required for each shift
      double shiftRequirements[] =
          new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

      // Amount each worker is paid to work one shift
      double pay[] = new double[] { 10, 12, 10, 8, 8, 9, 11 };

      // Worker availability: 0 if the worker is unavailable for a shift
      double availability[][] =
          new double[][] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
              { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
              { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
              { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
              { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
              { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
              { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

      // Model
      GRBEnv env = new GRBEnv();
      GRBModel model = new GRBModel(env);
      model.set(GRB.StringAttr.ModelName, "assignment");

      // Assignment variables: x[w][s] == 1 if worker w is assigned
      // to shift s. Since an assignment model always produces integer
      // solutions, we use continuous variables and solve as an LP.
```

(continues on next page)

(continued from previous page)

```
    GRBVar[][] x = new GRBVar[nWorkers][nShifts];
    for (int w = 0; w < nWorkers; ++w) {
      for (int s = 0; s < nShifts; ++s) {
        x[w][s] =
            model.addVar(0, availability[w][s], pay[w], GRB.CONTINUOUS,
                         Workers[w] + "." + Shifts[s]);
      }
    }

    // The objective is to minimize the total pay costs
    model.set(GRB.IntAttr.ModelSense, GRB.MINIMIZE);

    // Constraint: assign exactly shiftRequirements[s] workers
    // to each shift s
    for (int s = 0; s < nShifts; ++s) {
      GRBLinExpr lhs = new GRBLinExpr();
      for (int w = 0; w < nWorkers; ++w) {
        lhs.addTerm(1.0, x[w][s]);
      }
      model.addConstr(lhs, GRB.EQUAL, shiftRequirements[s], Shifts[s]);
    }

    // Optimize
    model.optimize();
    int status = model.get(GRB.IntAttr.Status);
    if (status == GRB.UNBOUNDED) {
      System.out.println("The model cannot be solved "
          + "because it is unbounded");
      return;
    }
    if (status == GRB.OPTIMAL) {
      System.out.println("The optimal objective is " +
          model.get(GRB.DoubleAttr.ObjVal));
      return;
    }
    if (status != GRB.INF_OR_UNBD &&
        status != GRB.INFEASIBLE    ) {
      System.out.println("Optimization was stopped with status " + status);
      return;
    }

    // Relax the constraints to make the model feasible
    System.out.println("The model is infeasible; relaxing the constraints");
    int orignumvars = model.get(GRB.IntAttr.NumVars);
    model.feasRelax(0, false, false, true);
    model.optimize();
    status = model.get(GRB.IntAttr.Status);
    if (status == GRB.INF_OR_UNBD ||
        status == GRB.INFEASIBLE  ||
        status == GRB.UNBOUNDED     ) {
      System.out.println("The relaxed model cannot be solved "
          + "because it is infeasible or unbounded");
```

(continues on next page)

(continued from previous page)

```
        return;
      }
      if (status != GRB.OPTIMAL) {
        System.out.println("Optimization was stopped with status " + status);
        return;
      }

      System.out.println("\nSlack values:");
      GRBVar[] vars = model.getVars();
      for (int i = orignumvars; i < model.get(GRB.IntAttr.NumVars); ++i) {
        GRBVar sv = vars[i];
        if (sv.get(GRB.DoubleAttr.X) > 1e-6) {
          System.out.println(sv.get(GRB.StringAttr.VarName) + " = " +
              sv.get(GRB.DoubleAttr.X));
        }
      }

      // Dispose of model and environment
      model.dispose();
      env.dispose();

    } catch (GRBException e) {
      System.out.println("Error code: " + e.getErrorCode() + ". " +
          e.getMessage());
    }
  }
}
```

Workforce4.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. We use Pareto optimization to solve the model:
   first, we minimize the linear sum of the slacks. Then, we constrain
   the sum of the slacks, and we minimize a quadratic objective that
   tries to balance the workload among the workers. */

import com.gurobi.gurobi.*;

public class Workforce4 {

  public static void main(String[] args) {
    try {

      // Sample data
      // Sets of days and workers
      String Shifts[] =
          new String[] { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
              "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
```

(continues on next page)

(continued from previous page)

```
        "Sun14" };
    String Workers[] =
        new String[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu" };

    int nShifts = Shifts.length;
    int nWorkers = Workers.length;

    // Number of workers required for each shift
    double shiftRequirements[] =
        new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

    // Worker availability: 0 if the worker is unavailable for a shift
    double availability[][] =
        new double[][] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
            { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
            { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
            { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
            { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
            { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
            { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

    // Model
    GRBEnv env = new GRBEnv();
    GRBModel model = new GRBModel(env);
    model.set(GRB.StringAttr.ModelName, "assignment");

    // Assignment variables: x[w][s] == 1 if worker w is assigned
    // to shift s. This is no longer a pure assignment model, so we must
    // use binary variables.
    GRBVar[][] x = new GRBVar[nWorkers][nShifts];
    for (int w = 0; w < nWorkers; ++w) {
      for (int s = 0; s < nShifts; ++s) {
        x[w][s] =
            model.addVar(0, availability[w][s], 0, GRB.BINARY,
                         Workers[w] + "." + Shifts[s]);
      }
    }

    // Slack variables for each shift constraint so that the shifts can
    // be satisfied
    GRBVar[] slacks = new GRBVar[nShifts];
    for (int s = 0; s < nShifts; ++s) {
      slacks[s] =
          model.addVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                       Shifts[s] + "Slack");
    }

    // Variable to represent the total slack
    GRBVar totSlack = model.addVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                   "totSlack");

    // Variables to count the total shifts worked by each worker
```

(continues on next page)

(continued from previous page)

```
    GRBVar[] totShifts = new GRBVar[nWorkers];
    for (int w = 0; w < nWorkers; ++w) {
      totShifts[w] = model.addVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                  Workers[w] + "TotShifts");
    }

    GRBLinExpr lhs;

    // Constraint: assign exactly shiftRequirements[s] workers
    // to each shift s, plus the slack
    for (int s = 0; s < nShifts; ++s) {
      lhs = new GRBLinExpr();
      lhs.addTerm(1.0, slacks[s]);
      for (int w = 0; w < nWorkers; ++w) {
        lhs.addTerm(1.0, x[w][s]);
      }
      model.addConstr(lhs, GRB.EQUAL, shiftRequirements[s], Shifts[s]);
    }

    // Constraint: set totSlack equal to the total slack
    lhs = new GRBLinExpr();
    lhs.addTerm(-1.0, totSlack);
    for (int s = 0; s < nShifts; ++s) {
      lhs.addTerm(1.0, slacks[s]);
    }
    model.addConstr(lhs, GRB.EQUAL, 0, "totSlack");

    // Constraint: compute the total number of shifts for each worker
    for (int w = 0; w < nWorkers; ++w) {
      lhs = new GRBLinExpr();
      lhs.addTerm(-1.0, totShifts[w]);
      for (int s = 0; s < nShifts; ++s) {
        lhs.addTerm(1.0, x[w][s]);
      }
      model.addConstr(lhs, GRB.EQUAL, 0, "totShifts" + Workers[w]);
    }

    // Objective: minimize the total slack
    GRBLinExpr obj = new GRBLinExpr();
    obj.addTerm(1.0, totSlack);
    model.setObjective(obj);

    // Optimize
    int status =
      solveAndPrint(model, totSlack, nWorkers, Workers, totShifts);
    if (status != GRB.Status.OPTIMAL ) {
      return;
    }

    // Constrain the slack by setting its upper and lower bounds
    totSlack.set(GRB.DoubleAttr.UB, totSlack.get(GRB.DoubleAttr.X));
    totSlack.set(GRB.DoubleAttr.LB, totSlack.get(GRB.DoubleAttr.X));
```

(continues on next page)

(continued from previous page)

```
    // Variable to count the average number of shifts worked
    GRBVar avgShifts =
      model.addVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS, "avgShifts");

    // Variables to count the difference from average for each worker;
    // note that these variables can take negative values.
    GRBVar[] diffShifts = new GRBVar[nWorkers];
    for (int w = 0; w < nWorkers; ++w) {
      diffShifts[w] = model.addVar(-GRB.INFINITY, GRB.INFINITY, 0,
                                   GRB.CONTINUOUS, Workers[w] + "Diff");
    }

    // Constraint: compute the average number of shifts worked
    lhs = new GRBLinExpr();
    lhs.addTerm(-nWorkers, avgShifts);
    for (int w = 0; w < nWorkers; ++w) {
      lhs.addTerm(1.0, totShifts[w]);
    }
    model.addConstr(lhs, GRB.EQUAL, 0, "avgShifts");

    // Constraint: compute the difference from the average number of shifts
    for (int w = 0; w < nWorkers; ++w) {
      lhs = new GRBLinExpr();
      lhs.addTerm(-1, diffShifts[w]);
      lhs.addTerm(-1, avgShifts);
      lhs.addTerm( 1, totShifts[w]);
      model.addConstr(lhs, GRB.EQUAL, 0, Workers[w] + "Diff");
    }

    // Objective: minimize the sum of the square of the difference from the
    // average number of shifts worked
    GRBQuadExpr qobj = new GRBQuadExpr();
    for (int w = 0; w < nWorkers; ++w) {
      qobj.addTerm(1.0, diffShifts[w], diffShifts[w]);
    }
    model.setObjective(qobj);

    // Optimize
    status =
      solveAndPrint(model, totSlack, nWorkers, Workers, totShifts);
    if (status != GRB.Status.OPTIMAL ) {
      return;
    }

    // Dispose of model and environment
    model.dispose();
    env.dispose();

  } catch (GRBException e) {
    System.out.println("Error code: " + e.getErrorCode() + ". " +
        e.getMessage());
```

(continues on next page)

(continued from previous page)

```
    }
  }

  private static int solveAndPrint(GRBModel model, GRBVar totSlack,
                                   int nWorkers, String[] Workers,
                                   GRBVar[] totShifts) throws GRBException {

    model.optimize();
    int status = model.get(GRB.IntAttr.Status);
    if (status == GRB.Status.INF_OR_UNBD ||
        status == GRB.Status.INFEASIBLE  ||
        status == GRB.Status.UNBOUNDED     ) {
      System.out.println("The model cannot be solved "
          + "because it is infeasible or unbounded");
      return status;
    }
    if (status != GRB.Status.OPTIMAL ) {
      System.out.println("Optimization was stopped with status " + status);
      return status;
    }

    // Print total slack and the number of shifts worked for each worker
    System.out.println("\nTotal slack required: " +
                       totSlack.get(GRB.DoubleAttr.X));
    for (int w = 0; w < nWorkers; ++w) {
      System.out.println(Workers[w] + " worked " +
                         totShifts[w].get(GRB.DoubleAttr.X) + " shifts");
    }
    System.out.println("\n");
    return status;
  }

}
```

Workforce5.java

```
/* Copyright 2026, Gurobi Optimization, LLC */

/* Assign workers to shifts; each worker may or may not be available on a
   particular day. We use multi-objective optimization to solve the model.
   The highest-priority objective minimizes the sum of the slacks
   (i.e., the total number of uncovered shifts). The secondary objective
   minimizes the difference between the maximum and minimum number of
   shifts worked among all workers.  The second optimization is allowed
   to degrade the first objective by up to the smaller value of 10% and 2 */

import com.gurobi.gurobi.*;

public class Workforce5 {
```

(continues on next page)

(continued from previous page)

```
  public static void main(String[] args) {

    try {

      // Sample data
      // Sets of days and workers
      String Shifts[] =
          new String[]  { "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6",
              "Sun7", "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13",
              "Sun14" };
      String Workers[] =
          new String[] { "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu", "Tobi" };

      int nShifts = Shifts.length;
      int nWorkers = Workers.length;

      // Number of workers required for each shift
      double shiftRequirements[] =
          new double[] { 3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 };

      // Worker availability: 0 if the worker is unavailable for a shift
      double availability[][] =
          new double[][] { { 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 },
              { 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 },
              { 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 },
              { 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 },
              { 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 },
              { 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 },
              { 0, 1, 1, 1, 0, 1, 1, 0, 1, 1, 1, 0, 1, 1 },
              { 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 } };

      // Create environment
      GRBEnv env = new GRBEnv();

      // Create initial model
      GRBModel model = new GRBModel(env);
      model.set(GRB.StringAttr.ModelName, "Workforce5");

      // Initialize assignment decision variables:
      // x[w][s] == 1 if worker w is assigned to shift s.
      // This is no longer a pure assignment model, so we must
      // use binary variables.
      GRBVar[][] x = new GRBVar[nWorkers][nShifts];
      for (int w = 0; w < nWorkers; ++w) {
        for (int s = 0; s < nShifts; ++s) {
          x[w][s] =
              model.addVar(0, availability[w][s], 0, GRB.BINARY,
                           Workers[w] + "." + Shifts[s]);
        }
      }

      // Slack variables for each shift constraint so that the shifts can
```

(continues on next page)

(continued from previous page)

```
    // be satisfied
    GRBVar[] slacks = new GRBVar[nShifts];
    for (int s = 0; s < nShifts; ++s) {
      slacks[s] =
          model.addVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                       Shifts[s] + "Slack");
    }

    // Variable to represent the total slack
    GRBVar totSlack = model.addVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                   "totSlack");

    // Variables to count the total shifts worked by each worker
    GRBVar[] totShifts = new GRBVar[nWorkers];
    for (int w = 0; w < nWorkers; ++w) {
      totShifts[w] = model.addVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                  Workers[w] + "TotShifts");
    }

    GRBLinExpr lhs;

    // Constraint: assign exactly shiftRequirements[s] workers
    // to each shift s, plus the slack
    for (int s = 0; s < nShifts; ++s) {
      lhs = new GRBLinExpr();
      lhs.addTerm(1.0, slacks[s]);
      for (int w = 0; w < nWorkers; ++w) {
        lhs.addTerm(1.0, x[w][s]);
      }
      model.addConstr(lhs, GRB.EQUAL, shiftRequirements[s], Shifts[s]);
    }

    // Constraint: set totSlack equal to the total slack
    lhs = new GRBLinExpr();
    lhs.addTerm(-1.0, totSlack);
    for (int s = 0; s < nShifts; ++s) {
      lhs.addTerm(1.0, slacks[s]);
    }
    model.addConstr(lhs, GRB.EQUAL, 0, "totSlack");

    // Constraint: compute the total number of shifts for each worker
    for (int w = 0; w < nWorkers; ++w) {
      lhs = new GRBLinExpr();
      lhs.addTerm(-1.0, totShifts[w]);
      for (int s = 0; s < nShifts; ++s) {
        lhs.addTerm(1.0, x[w][s]);
      }
      model.addConstr(lhs, GRB.EQUAL, 0, "totShifts" + Workers[w]);
    }

    // Constraint: set minShift/maxShift variable to less <=/>= to the
    // number of shifts among all workers
```

(continues on next page)

(continued from previous page)

```
    GRBVar minShift = model.addVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                   "minShift");
    GRBVar maxShift = model.addVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
                                   "maxShift");
    model.addGenConstrMin(minShift, totShifts, GRB.INFINITY, "minShift");
    model.addGenConstrMax(maxShift, totShifts, -GRB.INFINITY, "maxShift");

    // Set global sense for ALL objectives
    model.set(GRB.IntAttr.ModelSense, GRB.MINIMIZE);

    // Set primary objective
    GRBLinExpr obj0 = new GRBLinExpr();
    obj0.addTerm(1.0, totSlack);
    model.setObjectiveN(obj0, 0, 2, 1.0, 2.0, 0.1, "TotalSlack");

    // Set secondary objective
    GRBLinExpr obj1 = new GRBLinExpr();
    obj1.addTerm(1.0, maxShift);
    obj1.addTerm(-1.0, minShift);
    model.setObjectiveN(obj1, 1, 1, 1.0, 0.0, 0.0, "Fairness");

    // Save problem
    model.write("Workforce5.lp");

    // Optimize
    int status = solveAndPrint(model, totSlack, nWorkers, Workers, totShifts);

    if (status != GRB.OPTIMAL)
      return;

    // Dispose of model and environment
    model.dispose();
    env.dispose();

  } catch (GRBException e) {
    System.out.println("Error code: " + e.getErrorCode() + ". " +
        e.getMessage());
  }
}

private static int solveAndPrint(GRBModel model, GRBVar totSlack,
                                 int nWorkers, String[] Workers,
                                 GRBVar[] totShifts) throws GRBException {

  model.optimize();
  int status = model.get(GRB.IntAttr.Status);
  if (status == GRB.Status.INF_OR_UNBD ||
      status == GRB.Status.INFEASIBLE  ||
      status == GRB.Status.UNBOUNDED     ) {
    System.out.println("The model cannot be solved "
        + "because it is infeasible or unbounded");
    return status;
```

(continues on next page)

(continued from previous page)

```
    }
    if (status != GRB.Status.OPTIMAL ) {
      System.out.println("Optimization was stopped with status " + status);
      return status;
    }

    // Print total slack and the number of shifts worked for each worker
    System.out.println("\nTotal slack required: " +
                       totSlack.get(GRB.DoubleAttr.X));
    for (int w = 0; w < nWorkers; ++w) {
      System.out.println(Workers[w] + " worked " +
                         totShifts[w].get(GRB.DoubleAttr.X) + " shifts");
    }
    System.out.println("\n");
    return status;
  }

}
```

2.1.5 Python Examples

This section includes source code for all of the Gurobi Python examples. The same source code can be found in the `examples/python` directory of the Gurobi distribution.

acopf_4buses.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# A Power Flow Problem is illustrated on a 4 bus (node) network using an AC (Alternating␣
↪Current) represention
#
#
# Zij = Impedance between i and j                          P_i      = Active Power␣
↪Injected into bus i
# Yij = Admittance between i and j  (Yij = 1/Zij)          Q_i      = Reactive Power␣
↪Injeced into bus i
# Yij = Gij + j Bij    (j = sqrt(-1))                      V_i      = Voltage Magnitude␣
↪at bus i
#                                                        Theta_i  = Voltage Angle at␣
↪bus i
#
# Real (P) and Reactive (Q) Power balance equations must be met on all buses
#
# P_i = V_i \sum_{j=1}^{N} V_j (G_{ij} \cos(\theta_i - \theta_j) + B_{ij} \sin(\theta_i -
↪ \theta_j))
#
# Q_i = V_i \sum_{j=1}^{N} V_j (G_{ij} \sin(\theta_i - \theta_j) - B_{ij} \cos(\theta_i -
↪ \theta_j))
```

(continues on next page)

(continued from previous page)

```
#
#
#   (1)---(2)    Bus 1: Swing Bus. Fixed Voltage Magnitude and Angle. Variable P and Q.
#    |     |     Bus 2: Load Bus.  Fixed P and Q. Variable Voltage Magnitude and Angle.
#    |     |     Bus 3. Generation bus. Fixed Voltage Magnitude and P. Variable Voltage␣
↪Angle and Q.
#   (4)---(3)    Bus 4. Load Bus.  Fixed P and Q. Variable Voltage and Angle.
#
#  Objective: minimize overall reactive power on buses 1 and 3
import numpy as np
import gurobipy as gp
from gurobipy import GRB
from gurobipy import nlfunc

# Number of Buses (Nodes)
N = 4

# Conductance/susceptance components
G = np.array(
    [
        [1.7647, -0.5882, 0.0, -1.1765],
        [-0.5882, 1.5611, -0.3846, -0.5882],
        [0.0, -0.3846, 1.5611, -1.1765],
        [-1.1765, -0.5882, -1.1765, 2.9412],
    ]
)
B = np.array(
    [
        [-7.0588, 2.3529, 0.0, 4.7059],
        [2.3529, -6.629, 1.9231, 2.3529],
        [0.0, 1.9231, -6.629, 4.7059],
        [4.7059, 2.3529, 4.7059, -11.7647],
    ]
)

# Assign bounds where fixings are needed
v_lb = np.array([1.0, 0.0, 1.0, 0.0])
v_ub = np.array([1.0, 1.5, 1.0, 1.5])
P_lb = np.array([-3.0, -0.3, 0.3, -0.2])
P_ub = np.array([3.0, -0.3, 0.3, -0.2])
Q_lb = np.array([-3.0, -0.2, -3.0, -0.15])
Q_ub = np.array([3.0, -0.2, 3.0, -0.15])
theta_lb = np.array([0.0, -np.pi / 2, -np.pi / 2, -np.pi / 2])
theta_ub = np.array([0.0, np.pi / 2, np.pi / 2, np.pi / 2])

with gp.Env() as env, gp.Model("OptimalPowerFlow", env=env) as model:
    P = model.addMVar(N, name="P", lb=P_lb, ub=P_ub)  # Real power for buses
    Q = model.addMVar(N, name="Q", lb=Q_lb, ub=Q_ub)  # Reactive for buses
    v = model.addMVar(N, name="v", lb=v_lb, ub=v_ub)  # Voltage magnitude at buses

    # Voltage angle at buses. The MVar is reshaped to a column vector to
    # simplify the outer subtraction used in power balance constraints.
```

(continues on next page)

(continued from previous page)

```
    theta = model.addMVar(N, name="theta", lb=theta_lb, ub=theta_ub).reshape((N, 1))

    # Minimize Reactive Power at buses 1 and 3
    model.setObjective(Q[[0, 2]].sum(), GRB.MINIMIZE)

    # Real power balance
    constr_P = model.addGenConstrNL(
        P,
        v * ((G * nlfunc.cos(theta - theta.T) + B * nlfunc.sin(theta - theta.T)) @ v),
        name="constr_P",
    )

    # Reactive power balance
    constr_Q = model.addGenConstrNL(
        Q,
        v * ((G * nlfunc.sin(theta - theta.T) - B * nlfunc.cos(theta - theta.T)) @ v),
        name="constr_Q",
    )

    model.optimize()

    # Print output table if pandas is installed
    try:
        import pandas as pd

        df = pd.DataFrame(
            {
                "Bus": range(1, N + 1),
                "Voltage": v.X,
                "Angle": theta.reshape(N).X * 180 / np.pi,
                "Real Power": P.X,
                "Reactive Power": Q.X,
            }
        )

        print(df)
    except ImportError:
        pass
```

batchmode.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example reads a MIP model from a file, solves it in batch mode,
# and prints the JSON solution string.
#
# You will need a Compute Server license for this example to work.
```

(continues on next page)

(continued from previous page)

```
import sys
import time
import json
import gurobipy as gp
from gurobipy import GRB


# Set up the environment for batch mode optimization.
#
# The function creates an empty environment, sets all necessary parameters,
# and returns the ready-to-be-started Env object to caller.   It is the
# caller's responsibility to dispose of this environment when it's no
# longer needed.
def setupbatchenv():
    env = gp.Env(empty=True)
    env.setParam("LogFile", "batchmode.log")
    env.setParam("CSManager", "http://localhost:61080")
    env.setParam("UserName", "gurobi")
    env.setParam("ServerPassword", "pass")
    env.setParam("CSBatchMode", 1)

    # No network communication happened up to this point.  This will happen
    # once the caller invokes the start() method of the returned Env object.

    return env


# Print batch job error information, if any
def printbatcherrorinfo(batch):
    if batch is None or batch.BatchErrorCode == 0:
        return

    print(
        f"Batch ID {batch.BatchID}: Error code {batch.BatchErrorCode} ({batch.
↪BatchErrorMessage})"
    )


# Create a batch request for given problem file
def newbatchrequest(filename):
    # Start environment, create Model object from file
    #
    # By using the context handlers for env and model, it is ensured that
    # model.dispose() and env.dispose() are called automatically
    with setupbatchenv().start() as env, gp.read(filename, env=env) as model:
        # Set some parameters
        model.Params.MIPGap = 0.01
        model.Params.JSONSolDetail = 1

        # Define tags for some variables in order to access their values later
        for count, v in enumerate(model.getVars()):
            v.VTag = f"Variable{count}"
```

(continues on next page)

(continued from previous page)

```
            if count >= 10:
                break

        # Submit batch request
        batchID = model.optimizeBatch()

    return batchID


# Wait for the final status of the batch.
# Initially the status of a batch is "submitted"; the status will change
# once the batch has been processed (by a compute server).
def waitforfinalstatus(batchID):
    # Wait no longer than one hour
    maxwaittime = 3600

    # Setup and start environment, create local Batch handle object
    with setupbatchenv().start() as env, gp.Batch(batchID, env) as batch:
        starttime = time.time()
        while batch.BatchStatus == GRB.BATCH_SUBMITTED:
            # Abort this batch if it is taking too long
            curtime = time.time()
            if curtime - starttime > maxwaittime:
                batch.abort()
                break

            # Wait for two seconds
            time.sleep(2)

            # Update the resident attribute cache of the Batch object with the
            # latest values from the cluster manager.
            batch.update()

            # If the batch failed, we retry it
            if batch.BatchStatus == GRB.BATCH_FAILED:
                batch.retry()

        # Print information about error status of the job that processed the batch
        printbatcherrorinfo(batch)


def printfinalreport(batchID):
    # Setup and start environment, create local Batch handle object
    with setupbatchenv().start() as env, gp.Batch(batchID, env) as batch:
        if batch.BatchStatus == GRB.BATCH_CREATED:
            print("Batch status is 'CREATED'")
        elif batch.BatchStatus == GRB.BATCH_SUBMITTED:
            print("Batch is 'SUBMITTED")
        elif batch.BatchStatus == GRB.BATCH_ABORTED:
            print("Batch is 'ABORTED'")
        elif batch.BatchStatus == GRB.BATCH_FAILED:
            print("Batch is 'FAILED'")
```

(continues on next page)

(continued from previous page)

```
        elif batch.BatchStatus == GRB.BATCH_COMPLETED:
            print("Batch is 'COMPLETED'")
            print("JSON solution:")
            # Get JSON solution as string, create dict from it
            sol = json.loads(batch.getJSONSolution())

            # Pretty printing the general solution information
            print(json.dumps(sol["SolutionInfo"], indent=4))

            # Write the full JSON solution string to a file
            batch.writeJSONSolution("batch-sol.json.gz")
        else:
            # Should not happen
            print("Batch has unknown BatchStatus")

        printbatcherrorinfo(batch)


# Instruct the cluster manager to discard all data relating to this BatchID
def batchdiscard(batchID):
    # Setup and start environment, create local Batch handle object
    with setupbatchenv().start() as env, gp.Batch(batchID, env) as batch:
        # Remove batch request from manager
        batch.discard()


# Solve a given model using batch optimization
if __name__ == "__main__":
    # Ensure we have an input file
    if len(sys.argv) < 2:
        print(f"Usage: {sys.argv[0]} filename")
        sys.exit(0)

    # Submit new batch request
    batchID = newbatchrequest(sys.argv[1])

    # Wait for final status
    waitforfinalstatus(batchID)

    # Report final status info
    printfinalreport(batchID)

    # Remove batch request from manager
    batchdiscard(batchID)

    print("Batch optimization OK")
```

bilinear.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example formulates and solves the following simple bilinear model:
#  maximize    x
#  subject to  x + y + z <= 10
#              x * y <= 2         (bilinear inequality)
#              x * z + y * z = 1  (bilinear equality)
#              x, y, z non-negative (x integral in second version)

import gurobipy as gp
from gurobipy import GRB

# Create a new model
m = gp.Model("bilinear")

# Create variables
x = m.addVar(name="x")
y = m.addVar(name="y")
z = m.addVar(name="z")

# Set objective: maximize x
m.setObjective(1.0 * x, GRB.MAXIMIZE)

# Add linear constraint: x + y + z <= 10
m.addConstr(x + y + z <= 10, "c0")

# Add bilinear inequality constraint: x * y <= 2
m.addConstr(x * y <= 2, "bilinear0")

# Add bilinear equality constraint: x * z + y * z == 1
m.addConstr(x * z + y * z == 1, "bilinear1")

# Optimize model
m.optimize()

m.printAttr("x")

# Constrain 'x' to be integral and solve again
x.VType = GRB.INTEGER
m.optimize()

m.printAttr("x")
```

callback.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

#   This example reads a model from a file, sets up a callback that
#   monitors optimization progress and implements a custom
#   termination strategy, and outputs progress information to the
#   screen and to a log file.
#
#   The termination strategy implemented in this callback stops the
#   optimization of a MIP model once at least one of the following two
#   conditions have been satisfied:
#     1) The optimality gap is less than 10%
#     2) At least 10000 nodes have been explored, and an integer feasible
#        solution has been found.
#   Note that termination is normally handled through Gurobi parameters
#   (MIPGap, NodeLimit, etc.).  You should only use a callback for
#   termination if the available parameters don't capture your desired
#   termination criterion.

import sys
from functools import partial

import gurobipy as gp
from gurobipy import GRB


class CallbackData:
    def __init__(self, modelvars):
        self.modelvars = modelvars
        self.lastiter = -GRB.INFINITY
        self.lastnode = -GRB.INFINITY


def mycallback(model, where, *, cbdata, logfile):
    """
    Callback function. 'model' and 'where' arguments are passed by gurobipy
    when the callback is invoked. The other arguments must be provided via
    functools.partial:
      1) 'cbdata' is an instance of CallbackData, which holds the model
         variables and tracks state information across calls to the callback.
      2) 'logfile' is a writeable file handle.
    """

    if where == GRB.Callback.POLLING:
        # Ignore polling callback
        pass
    elif where == GRB.Callback.PRESOLVE:
        # Presolve callback
        cdels = model.cbGet(GRB.Callback.PRE_COLDEL)
        rdels = model.cbGet(GRB.Callback.PRE_ROWDEL)
```

(continues on next page)

(continued from previous page)

```
        if cdels or rdels:
            print(f"{cdels} columns and {rdels} rows are removed")
    elif where == GRB.Callback.SIMPLEX:
        # Simplex callback
        itcnt = model.cbGet(GRB.Callback.SPX_ITRCNT)
        if itcnt - cbdata.lastiter >= 100:
            cbdata.lastiter = itcnt
            obj = model.cbGet(GRB.Callback.SPX_OBJVAL)
            ispert = model.cbGet(GRB.Callback.SPX_ISPERT)
            pinf = model.cbGet(GRB.Callback.SPX_PRIMINF)
            dinf = model.cbGet(GRB.Callback.SPX_DUALINF)
            if ispert == 0:
                ch = " "
            elif ispert == 1:
                ch = "S"
            else:
                ch = "P"
            print(f"{int(itcnt)} {obj:g}{ch} {pinf:g} {dinf:g}")
    elif where == GRB.Callback.MIP:
        # General MIP callback
        nodecnt = model.cbGet(GRB.Callback.MIP_NODCNT)
        objbst = model.cbGet(GRB.Callback.MIP_OBJBST)
        objbnd = model.cbGet(GRB.Callback.MIP_OBJBND)
        solcnt = model.cbGet(GRB.Callback.MIP_SOLCNT)
        if nodecnt - cbdata.lastnode >= 100:
            cbdata.lastnode = nodecnt
            actnodes = model.cbGet(GRB.Callback.MIP_NODLFT)
            itcnt = model.cbGet(GRB.Callback.MIP_ITRCNT)
            cutcnt = model.cbGet(GRB.Callback.MIP_CUTCNT)
            print(
                f"{nodecnt:.0f} {actnodes:.0f} {itcnt:.0f} {objbst:g} "
                f"{objbnd:g} {solcnt} {cutcnt}"
            )
        if abs(objbst - objbnd) < 0.1 * (1.0 + abs(objbst)):
            print("Stop early - 10% gap achieved")
            model.terminate()
        if nodecnt >= 10000 and solcnt:
            print("Stop early - 10000 nodes explored")
            model.terminate()
    elif where == GRB.Callback.MIPSOL:
        # MIP solution callback
        nodecnt = model.cbGet(GRB.Callback.MIPSOL_NODCNT)
        obj = model.cbGet(GRB.Callback.MIPSOL_OBJ)
        solcnt = model.cbGet(GRB.Callback.MIPSOL_SOLCNT)
        x = model.cbGetSolution(cbdata.modelvars)
        print(
            f"**** New solution at node {nodecnt:.0f}, obj {obj:g}, "
            f"sol {solcnt:.0f}, x[0] = {x[0]:g} ****"
        )
    elif where == GRB.Callback.MIPNODE:
        # MIP node callback
        print("**** New node ****")
```

(continues on next page)

(continued from previous page)

```
        if model.cbGet(GRB.Callback.MIPNODE_STATUS) == GRB.OPTIMAL:
            x = model.cbGetNodeRel(cbdata.modelvars)
            model.cbSetSolution(cbdata.modelvars, x)
    elif where == GRB.Callback.BARRIER:
        # Barrier callback
        itcnt = model.cbGet(GRB.Callback.BARRIER_ITRCNT)
        primobj = model.cbGet(GRB.Callback.BARRIER_PRIMOBJ)
        dualobj = model.cbGet(GRB.Callback.BARRIER_DUALOBJ)
        priminf = model.cbGet(GRB.Callback.BARRIER_PRIMINF)
        dualinf = model.cbGet(GRB.Callback.BARRIER_DUALINF)
        cmpl = model.cbGet(GRB.Callback.BARRIER_COMPL)
        print(f"{itcnt:.0f} {primobj:g} {dualobj:g} {priminf:g} {dualinf:g} {cmpl:g}")
    elif where == GRB.Callback.MESSAGE:
        # Message callback
        msg = model.cbGet(GRB.Callback.MSG_STRING)
        logfile.write(msg)


# Parse arguments
if len(sys.argv) < 2:
    print("Usage: callback.py filename")
    sys.exit(0)
model_file = sys.argv[1]

# This context block manages several resources to ensure they are properly
# closed at the end of the program:
#   1) A Gurobi environment, with console output and heuristics disabled.
#   2) A Gurobi model, read from a file provided by the user.
#   3) A Python file handle which the callback will write to.

with gp.Env(params={"OutputFlag": 0, "Heuristics": 0}) as env, gp.read(
    model_file, env=env
) as model, open("cb.log", "w") as logfile:

    # Set up callback function with required arguments
    callback_data = CallbackData(model.getVars())
    callback_func = partial(mycallback, cbdata=callback_data, logfile=logfile)

    # Solve model and print solution information
    model.optimize(callback_func)

    print("")
    print("Optimization complete")
    if model.SolCount == 0:
        print(f"No solution found, optimization status = {model.Status}")
    else:
        print(f"Solution found, objective = {model.ObjVal:g}")
        for v in model.getVars():
            if v.X != 0.0:
                print(f"{v.VarName} {v.X:g}")
```

dense.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example formulates and solves the following simple QP model:
#
#    minimize    x + y + x^2 + x*y + y^2 + y*z + z^2
#    subject to  x + 2 y + 3 z >= 4
#                x +   y       >= 1
#                x, y, z non-negative
#
# The example illustrates the use of dense matrices to store A and Q
# (and dense vectors for the other relevant data).  We don't recommend
# that you use dense matrices, but this example may be helpful if you
# already have your data in this format.

import sys
import gurobipy as gp
from gurobipy import GRB


def dense_optimize(rows, cols, c, Q, A, sense, rhs, lb, ub, vtype, solution):
    model = gp.Model()

    # Add variables to model
    vars = []
    for j in range(cols):
        vars.append(model.addVar(lb=lb[j], ub=ub[j], vtype=vtype[j]))

    # Populate A matrix
    for i in range(rows):
        expr = gp.LinExpr()
        for j in range(cols):
            if A[i][j] != 0:
                expr += A[i][j] * vars[j]
        model.addLConstr(expr, sense[i], rhs[i])

    # Populate objective
    obj = gp.QuadExpr()
    for i in range(cols):
        for j in range(cols):
            if Q[i][j] != 0:
                obj += Q[i][j] * vars[i] * vars[j]
    for j in range(cols):
        if c[j] != 0:
            obj += c[j] * vars[j]
    model.setObjective(obj)

    # Solve
    model.optimize()
```

(continues on next page)

(continued from previous page)

```
    # Write model to a file
    model.write("dense.lp")

    if model.status == GRB.OPTIMAL:
        x = model.getAttr("X", vars)
        for i in range(cols):
            solution[i] = x[i]
        return True
    else:
        return False


# Put model data into dense matrices

c = [1, 1, 0]
Q = [[1, 1, 0], [0, 1, 1], [0, 0, 1]]
A = [[1, 2, 3], [1, 1, 0]]
sense = [GRB.GREATER_EQUAL, GRB.GREATER_EQUAL]
rhs = [4, 1]
lb = [0, 0, 0]
ub = [GRB.INFINITY, GRB.INFINITY, GRB.INFINITY]
vtype = [GRB.CONTINUOUS, GRB.CONTINUOUS, GRB.CONTINUOUS]
sol = [0] * 3

# Optimize

success = dense_optimize(2, 3, c, Q, A, sense, rhs, lb, ub, vtype, sol)

if success:
    print(f"x: {sol[0]:g}, y: {sol[1]:g}, z: {sol[2]:g}")
```

diet.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Solve the classic diet model, showing how to add constraints
# to an existing model.

import gurobipy as gp
from gurobipy import GRB

# Nutrition guidelines, based on
# USDA Dietary Guidelines for Americans, 2005
# http://www.health.gov/DietaryGuidelines/dga2005/

categories, minNutrition, maxNutrition = gp.multidict(
    {
        "calories": [1800, 2200],
```

(continues on next page)

(continued from previous page)

```
        "protein": [91, GRB.INFINITY],
        "fat": [0, 65],
        "sodium": [0, 1779],
    }
)

foods, cost = gp.multidict(
    {
        "hamburger": 2.49,
        "chicken": 2.89,
        "hot dog": 1.50,
        "fries": 1.89,
        "macaroni": 2.09,
        "pizza": 1.99,
        "salad": 2.49,
        "milk": 0.89,
        "ice cream": 1.59,
    }
)

# Nutrition values for the foods
nutritionValues = {
    ("hamburger", "calories"): 410,
    ("hamburger", "protein"): 24,
    ("hamburger", "fat"): 26,
    ("hamburger", "sodium"): 730,
    ("chicken", "calories"): 420,
    ("chicken", "protein"): 32,
    ("chicken", "fat"): 10,
    ("chicken", "sodium"): 1190,
    ("hot dog", "calories"): 560,
    ("hot dog", "protein"): 20,
    ("hot dog", "fat"): 32,
    ("hot dog", "sodium"): 1800,
    ("fries", "calories"): 380,
    ("fries", "protein"): 4,
    ("fries", "fat"): 19,
    ("fries", "sodium"): 270,
    ("macaroni", "calories"): 320,
    ("macaroni", "protein"): 12,
    ("macaroni", "fat"): 10,
    ("macaroni", "sodium"): 930,
    ("pizza", "calories"): 320,
    ("pizza", "protein"): 15,
    ("pizza", "fat"): 12,
    ("pizza", "sodium"): 820,
    ("salad", "calories"): 320,
    ("salad", "protein"): 31,
    ("salad", "fat"): 12,
    ("salad", "sodium"): 1230,
    ("milk", "calories"): 100,
    ("milk", "protein"): 8,
```

(continues on next page)

(continued from previous page)

```
    ("milk", "fat"): 2.5,
    ("milk", "sodium"): 125,
    ("ice cream", "calories"): 330,
    ("ice cream", "protein"): 8,
    ("ice cream", "fat"): 10,
    ("ice cream", "sodium"): 180,
}

# Model
m = gp.Model("diet")

# Create decision variables for the foods to buy
buy = m.addVars(foods, name="buy")

# You could use Python looping constructs and m.addVar() to create
# these decision variables instead.  The following would be equivalent
#
# buy = {}
# for f in foods:
#   buy[f] = m.addVar(name=f)

# The objective is to minimize the costs
m.setObjective(buy.prod(cost), GRB.MINIMIZE)

# Using looping constructs, the preceding statement would be:
#
# m.setObjective(sum(buy[f]*cost[f] for f in foods), GRB.MINIMIZE)

# Nutrition constraints
m.addConstrs(
    (
        gp.quicksum(nutritionValues[f, c] * buy[f] for f in foods)
        == [minNutrition[c], maxNutrition[c]]
        for c in categories
    ),
    "_",
)

# Using looping constructs, the preceding statement would be:
#
# for c in categories:
#  m.addRange(sum(nutritionValues[f, c] * buy[f] for f in foods),
#             minNutrition[c], maxNutrition[c], c)


def printSolution():
    if m.status == GRB.OPTIMAL:
        print(f"\nCost: {m.ObjVal:g}")
        print("\nBuy:")
        for f in foods:
            if buy[f].X > 0.0001:
                print(f"{f} {buy[f].X:g}")
```

(continues on next page)

(continued from previous page)

```
    else:
        print("No solution")


# Solve
m.optimize()
printSolution()

print("\nAdding constraint: at most 6 servings of dairy")
m.addConstr(buy.sum(["milk", "ice cream"]) <= 6, "limit_dairy")

# Solve
m.optimize()
printSolution()
```

diet2.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Separate the model (dietmodel.py) from the data file (diet2.py), so
# that the model can be solved with different data files.
#
# Nutrition guidelines, based on
# USDA Dietary Guidelines for Americans, 2005
# http://www.health.gov/DietaryGuidelines/dga2005/

import dietmodel
import gurobipy as gp
from gurobipy import GRB

categories, minNutrition, maxNutrition = gp.multidict(
    {
        "calories": [1800, 2200],
        "protein": [91, GRB.INFINITY],
        "fat": [0, 65],
        "sodium": [0, 1779],
    }
)

foods, cost = gp.multidict(
    {
        "hamburger": 2.49,
        "chicken": 2.89,
        "hot dog": 1.50,
        "fries": 1.89,
        "macaroni": 2.09,
        "pizza": 1.99,
        "salad": 2.49,
```

(continues on next page)

(continued from previous page)

```
        "milk": 0.89,
        "ice cream": 1.59,
    }
)

# Nutrition values for the foods
nutritionValues = {
    ("hamburger", "calories"): 410,
    ("hamburger", "protein"): 24,
    ("hamburger", "fat"): 26,
    ("hamburger", "sodium"): 730,
    ("chicken", "calories"): 420,
    ("chicken", "protein"): 32,
    ("chicken", "fat"): 10,
    ("chicken", "sodium"): 1190,
    ("hot dog", "calories"): 560,
    ("hot dog", "protein"): 20,
    ("hot dog", "fat"): 32,
    ("hot dog", "sodium"): 1800,
    ("fries", "calories"): 380,
    ("fries", "protein"): 4,
    ("fries", "fat"): 19,
    ("fries", "sodium"): 270,
    ("macaroni", "calories"): 320,
    ("macaroni", "protein"): 12,
    ("macaroni", "fat"): 10,
    ("macaroni", "sodium"): 930,
    ("pizza", "calories"): 320,
    ("pizza", "protein"): 15,
    ("pizza", "fat"): 12,
    ("pizza", "sodium"): 820,
    ("salad", "calories"): 320,
    ("salad", "protein"): 31,
    ("salad", "fat"): 12,
    ("salad", "sodium"): 1230,
    ("milk", "calories"): 100,
    ("milk", "protein"): 8,
    ("milk", "fat"): 2.5,
    ("milk", "sodium"): 125,
    ("ice cream", "calories"): 330,
    ("ice cream", "protein"): 8,
    ("ice cream", "fat"): 10,
    ("ice cream", "sodium"): 180,
}

dietmodel.solve(categories, minNutrition, maxNutrition, foods, cost, nutritionValues)
```

diet3.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Use a SQLite database with the diet model (dietmodel.py).  The database
# (diet.db) can be recreated using the included SQL script (diet.sql).
#
# Note that this example reads an external data file (..\data\diet.db).
# As a result, it must be run from the Gurobi examples/python directory.

import os
import sqlite3
import dietmodel
import gurobipy as gp

con = sqlite3.connect(os.path.join("..", "data", "diet.db"))
cur = con.cursor()

cur.execute("select category,minnutrition,maxnutrition from categories")
result = cur.fetchall()
categories, minNutrition, maxNutrition = gp.multidict(
    (cat, [minv, maxv]) for cat, minv, maxv in result
)

cur.execute("select food,cost from foods")
result = cur.fetchall()
foods, cost = gp.multidict(result)

cur.execute("select food,category,value from nutrition")
result = cur.fetchall()
nutritionValues = dict(((f, c), v) for f, c, v in result)

con.close()

dietmodel.solve(categories, minNutrition, maxNutrition, foods, cost, nutritionValues)
```

diet4.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Read diet model data from an Excel spreadsheet (diet.xlsx).
# Pass the imported data into the diet model (dietmodel.py).
#
# Note that this example reads an external data file (..\data\diet.xlsx).
# As a result, it must be run from the Gurobi examples/python directory.
#
# This example uses Python package 'openpyxl', which isn't included
```

(continues on next page)

(continued from previous page)

```
# in most Python distributions.  You can install it with
# 'pip install openpyxl'.

import os
import openpyxl
import dietmodel

# Open 'diet.xlsx'
book = openpyxl.load_workbook(os.path.join("..", "data", "diet.xlsx"))

# Read min/max nutrition info from 'Categories' sheet
sheet = book["Categories"]
categories = []
minNutrition = {}
maxNutrition = {}
for row in sheet.iter_rows():
    category = row[0].value
    if category != "Categories":
        categories.append(category)
        minNutrition[category] = row[1].value
        maxNutrition[category] = row[2].value

# Read food costs from 'Foods' sheet
sheet = book["Foods"]
foods = []
cost = {}
for row in sheet.iter_rows():
    food = row[0].value
    if food != "Foods":
        foods.append(food)
        cost[food] = row[1].value

# Read food nutrition info from 'Nutrition' sheet
sheet = book["Nutrition"]
nutritionValues = {}
for row in sheet.iter_rows():
    if row[0].value == None:  # column labels - categories
        cats = [v.value for v in row]
    else:  # nutrition values
        food = row[0].value
        for col in range(1, len(row)):
            nutritionValues[food, cats[col]] = row[col].value


dietmodel.solve(categories, minNutrition, maxNutrition, foods, cost, nutritionValues)
```

dietmodel.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Solve the classic diet model.  This file implements
# a function that formulates and solves the model,
# but it contains no model data.  The data is
# passed in by the calling program.  Run example 'diet2.py',
# 'diet3.py', or 'diet4.py' to invoke this function.

import gurobipy as gp
from gurobipy import GRB


def solve(categories, minNutrition, maxNutrition, foods, cost, nutritionValues):
    # Model
    m = gp.Model("diet")

    # Create decision variables for the foods to buy
    buy = m.addVars(foods, name="buy")

    # The objective is to minimize the costs
    m.setObjective(buy.prod(cost), GRB.MINIMIZE)

    # Nutrition constraints
    m.addConstrs(
        (
            gp.quicksum(nutritionValues[f, c] * buy[f] for f in foods)
            == [minNutrition[c], maxNutrition[c]]
            for c in categories
        ),
        "_",
    )

    def printSolution():
        if m.status == GRB.OPTIMAL:
            print("\nCost: %g" % m.ObjVal)
            print("\nBuy:")
            for f in foods:
                if buy[f].X > 0.0001:
                    print(f"{f} {buy[f].X:g}")
        else:
            print("No solution")

    # Solve
    m.optimize()
    printSolution()

    print("\nAdding constraint: at most 6 servings of dairy")
    m.addConstr(buy.sum(["milk", "ice cream"]) <= 6, "limit_dairy")
```

(continues on next page)

(continued from previous page)

```
    # Solve
    m.optimize()
    printSolution()
```

facility.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Facility location: a company currently ships its product from 5 plants
# to 4 warehouses. It is considering closing some plants to reduce
# costs. What plant(s) should the company close, in order to minimize
# transportation and fixed costs?
#
# Note that this example uses lists instead of dictionaries.  Since
# it does not work with sparse data, lists are a reasonable option.
#
# Based on an example from Frontline Systems:
#   http://www.solver.com/disfacility.htm
# Used with permission.

import gurobipy as gp
from gurobipy import GRB

# Warehouse demand in thousands of units
demand = [15, 18, 14, 20]

# Plant capacity in thousands of units
capacity = [20, 22, 17, 19, 18]

# Fixed costs for each plant
fixedCosts = [12000, 15000, 17000, 13000, 16000]

# Transportation costs per thousand units
transCosts = [
    [4000, 2000, 3000, 2500, 4500],
    [2500, 2600, 3400, 3000, 4000],
    [1200, 1800, 2600, 4100, 3000],
    [2200, 2600, 3100, 3700, 3200],
]

# Range of plants and warehouses
plants = range(len(capacity))
warehouses = range(len(demand))

# Model
m = gp.Model("facility")

# Plant open decision variables: open[p] == 1 if plant p is open.
```

(continues on next page)

(continued from previous page)

```
open = m.addVars(plants, vtype=GRB.BINARY, obj=fixedCosts, name="open")

# Transportation decision variables: transport[w,p] captures the
# optimal quantity to transport to warehouse w from plant p
transport = m.addVars(warehouses, plants, obj=transCosts, name="trans")

# You could use Python looping constructs and m.addVar() to create
# these decision variables instead.  The following would be equivalent
# to the preceding two statements...
#
# open = []
# for p in plants:
#     open.append(m.addVar(vtype=GRB.BINARY,
#                          obj=fixedCosts[p],
#                          name="open[%d]" % p))
#
# transport = []
# for w in warehouses:
#     transport.append([])
#     for p in plants:
#         transport[w].append(m.addVar(obj=transCosts[w][p],
#                                      name="trans[%d,%d]" % (w, p)))

# The objective is to minimize the total fixed and variable costs
m.ModelSense = GRB.MINIMIZE

# Production constraints
# Note that the right-hand limit sets the production to zero if the plant
# is closed
m.addConstrs(
    (transport.sum("*", p) <= capacity[p] * open[p] for p in plants), "Capacity"
)

# Using Python looping constructs, the preceding would be...
#
# for p in plants:
#     m.addConstr(sum(transport[w][p] for w in warehouses)
#                 <= capacity[p] * open[p], "Capacity[%d]" % p)

# Demand constraints
m.addConstrs((transport.sum(w, "*") == demand[w] for w in warehouses), "Demand")

# ... and the preceding would be ...
# for w in warehouses:
#     m.addConstr(sum(transport[w][p] for p in plants) == demand[w],
#                 "Demand[%d]" % w)

# Save model
m.write("facilityPY.lp")

# Guess at the starting point: close the plant with the highest fixed costs;
# open all others
```

(continues on next page)

(continued from previous page)

```
# First open all plants
for p in plants:
    open[p].Start = 1.0

# Now close the plant with the highest fixed cost
print("Initial guess:")
maxFixed = max(fixedCosts)
for p in plants:
    if fixedCosts[p] == maxFixed:
        open[p].Start = 0.0
        print(f"Closing plant {p}")
        break
print("")

# Use barrier to solve root relaxation
m.Params.Method = 2

# Solve
m.optimize()

# Print solution
print(f"\nTOTAL COSTS: {m.ObjVal:g}")
print("SOLUTION:")
for p in plants:
    if open[p].X > 0.99:
        print(f"Plant {p} open")
        for w in warehouses:
            if transport[w, p].X > 0:
                print(f"  Transport {transport[w, p].X:g} units to warehouse {w}")
    else:
        print(f"Plant {p} closed!")
```

feasopt.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example reads a MIP model from a file, adds artificial
# variables to each constraint, and then minimizes the sum of the
# artificial variables.  A solution with objective zero corresponds
# to a feasible solution to the input model.
#
# We can also use FeasRelax feature to do it. In this example, we
# use minrelax=1, i.e. optimizing the returned model finds a solution
# that minimizes the original objective, but only from among those
# solutions that minimize the sum of the artificial variables.

import sys
```

(continues on next page)

(continued from previous page)

```
import gurobipy as gp

if len(sys.argv) < 2:
    print("Usage: feasopt.py filename")
    sys.exit(0)

feasmodel = gp.read(sys.argv[1])

# create a copy to use FeasRelax feature later

feasmodel1 = feasmodel.copy()

# clear objective

feasmodel.setObjective(0.0)

# add slack variables

for c in feasmodel.getConstrs():
    sense = c.Sense
    if sense != ">":
        feasmodel.addVar(
            obj=1.0, name=f"ArtN_{c.ConstrName}", column=gp.Column([-1], [c])
        )
    if sense != "<":
        feasmodel.addVar(
            obj=1.0, name=f"ArtP_{c.ConstrName}", column=gp.Column([1], [c])
        )

# optimize modified model

feasmodel.optimize()

feasmodel.write("feasopt.lp")

# use FeasRelax feature

feasmodel1.feasRelaxS(0, True, False, True)

feasmodel1.write("feasopt1.lp")

feasmodel1.optimize()
```

fixanddive.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Implement a simple MIP heuristic.  Relax the model,
# sort variables based on fractionality, and fix the 25% of
# the fractional variables that are closest to integer variables.
# Repeat until either the relaxation is integer feasible or
# linearly infeasible.

import sys
import gurobipy as gp
from gurobipy import GRB

# Key function used to sort variables based on relaxation fractionality


def sortkey(v1):
    sol = v1.X
    return abs(sol - int(sol + 0.5))


if len(sys.argv) < 2:
    print("Usage: fixanddive.py filename")
    sys.exit(0)

# Read model

model = gp.read(sys.argv[1])

# Collect integer variables and relax them
intvars = []
for v in model.getVars():
    if v.VType != GRB.CONTINUOUS:
        intvars += [v]
        v.VType = GRB.CONTINUOUS

model.Params.OutputFlag = 0

model.optimize()


# Perform multiple iterations.  In each iteration, identify the first
# quartile of integer variables that are closest to an integer value in the
# relaxation, fix them to the nearest integer, and repeat.

for iter in range(1000):
    # create a list of fractional variables, sorted in order of increasing
    # distance from the relaxation solution to the nearest integer value

    fractional = []
```

(continues on next page)

(continued from previous page)

```
    for v in intvars:
        sol = v.X
        if abs(sol - int(sol + 0.5)) > 1e-5:
            fractional += [v]

    fractional.sort(key=sortkey)

    print(f"Iteration {iter}, obj {model.ObjVal:g}, fractional {len(fractional)}")

    if len(fractional) == 0:
        print(f"Found feasible solution - objective {model.ObjVal:g}")
        break

    # Fix the first quartile to the nearest integer value
    nfix = max(int(len(fractional) / 4), 1)
    for i in range(nfix):
        v = fractional[i]
        fixval = int(v.X + 0.5)
        v.LB = fixval
        v.UB = fixval
        print(f"  Fix {v.VarName} to {fixval:g} (rel {v.X:g})")

    model.optimize()

    # Check optimization result

    if model.Status != GRB.OPTIMAL:
        print("Relaxation is infeasible")
        break
```

gc_pwl.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example formulates and solves the following simple model
# with PWL constraints:
#
#  maximize
#        sum c[j] * x[j]
#  subject to
#        sum A[i,j] * x[j] <= 0,  for i = 0, ..., m-1
#        sum y[j] <= 3
#        y[j] = pwl(x[j]),        for j = 0, ..., n-1
#        x[j] free, y[j] >= 0,    for j = 0, ..., n-1
#  where pwl(x) = 0,     if x  = 0
#               = 1+|x|, if x != 0
#
#  Note
```

(continues on next page)

(continued from previous page)

```
#   1. sum pwl(x[j]) <= b is to bound x vector and also to favor sparse x vector.
#      Here b = 3 means that at most two x[j] can be nonzero and if two, then
#      sum x[j] <= 1
#   2. pwl(x) jumps from 1 to 0 and from 0 to 1, if x moves from negative 0 to 0,
#      then to positive 0, so we need three points at x = 0. x has infinite bounds
#      on both sides, the piece defined with two points (-1, 2) and (0, 1) can
#      extend x to -infinite. Overall we can use five points (-1, 2), (0, 1),
#      (0, 0), (0, 1) and (1, 2) to define y = pwl(x)
#

import gurobipy as gp
from gurobipy import GRB

try:
    n = 5
    m = 5
    c = [0.5, 0.8, 0.5, 0.1, -1]
    A = [
        [0, 0, 0, 1, -1],
        [0, 0, 1, 1, -1],
        [1, 1, 0, 0, -1],
        [1, 0, 1, 0, -1],
        [1, 0, 0, 1, -1],
    ]

    # Create a new model
    model = gp.Model("gc_pwl")

    # Create variables
    x = model.addVars(n, lb=-GRB.INFINITY, name="x")
    y = model.addVars(n, name="y")

    # Set objective
    model.setObjective(gp.quicksum(c[j] * x[j] for j in range(n)), GRB.MAXIMIZE)

    # Add Constraints
    for i in range(m):
        model.addConstr(gp.quicksum(A[i][j] * x[j] for j in range(n)) <= 0)

    model.addConstr(y.sum() <= 3)

    for j in range(n):
        model.addGenConstrPWL(x[j], y[j], [-1, 0, 0, 0, 1], [2, 1, 0, 1, 2])

    # Optimize model
    model.optimize()

    for j in range(n):
        print(f"{x[j].VarName} = {x[j].X:g}")

    print(f"Obj: {model.ObjVal:g}")
```

(continues on next page)

(continued from previous page)

```
except gp.GurobiError as e:
    print(f"Error code {e.errno}: {e}")

except AttributeError:
    print("Encountered an attribute error")
```

genconstr.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# In this example we show the use of general constraints for modeling
# some common expressions. We use as an example a SAT-problem where we
# want to see if it is possible to satisfy at least four (or all) clauses
# of the logical form
#
# L = (x0 or ~x1 or x2)  and (x1 or ~x2 or x3)  and
#     (x2 or ~x3 or x0)  and (x3 or ~x0 or x1)  and
#     (~x0 or ~x1 or x2) and (~x1 or ~x2 or x3) and
#     (~x2 or ~x3 or x0) and (~x3 or ~x0 or x1)
#
# We do this by introducing two variables for each literal (itself and its
# negated value), one variable for each clause, one variable indicating
# whether we can satisfy at least four clauses, and one last variable to
# identify the minimum of the clauses (so if it is one, we can satisfy all
# clauses). Then we put these last two variables in the objective.
# The objective function is therefore
#
# maximize Obj0 + Obj1
#
#  Obj0 = MIN(Clause1, ... , Clause8)
#  Obj1 = 1 -> Clause1 + ... + Clause8 >= 4
#
# thus, the objective value will be two if and only if we can satisfy all
# clauses; one if and only if at least four but not all clauses can be satisfied,
# and zero otherwise.

import gurobipy as gp
from gurobipy import GRB
import sys

try:
    NLITERALS = 4

    n = NLITERALS

    # Example data:
    #   e.g. {0, n+1, 2} means clause (x0 or ~x1 or x2)
    Clauses = [
```

(continues on next page)

(continued from previous page)

```
        [0, n + 1, 2],
        [1, n + 2, 3],
        [2, n + 3, 0],
        [3, n + 0, 1],
        [n + 0, n + 1, 2],
        [n + 1, n + 2, 3],
        [n + 2, n + 3, 0],
        [n + 3, n + 0, 1],
    ]

    # Create a new model
    model = gp.Model("Genconstr")

    # initialize decision variables and objective
    Lit = model.addVars(NLITERALS, vtype=GRB.BINARY, name="X")
    NotLit = model.addVars(NLITERALS, vtype=GRB.BINARY, name="NotX")

    Cla = model.addVars(len(Clauses), vtype=GRB.BINARY, name="Clause")

    Obj0 = model.addVar(vtype=GRB.BINARY, name="Obj0")
    Obj1 = model.addVar(vtype=GRB.BINARY, name="Obj1")

    # Link Xi and notXi
    model.addConstrs(
        (Lit[i] + NotLit[i] == 1.0 for i in range(NLITERALS)), name="CNSTR_X"
    )

    # Link clauses and literals
    for i, c in enumerate(Clauses):
        clause = []
        for l in c:
            if l >= n:
                clause.append(NotLit[l - n])
            else:
                clause.append(Lit[l])
        model.addConstr(Cla[i] == gp.or_(clause), "CNSTR_Clause" + str(i))

    # Link objs with clauses
    model.addConstr(Obj0 == gp.min_(Cla.values()), name="CNSTR_Obj0")
    model.addConstr((Obj1 == 1) >> (Cla.sum() >= 4.0), name="CNSTR_Obj1")

    # Set optimization objective
    model.setObjective(Obj0 + Obj1, GRB.MAXIMIZE)

    # Save problem
    model.write("genconstr.mps")
    model.write("genconstr.lp")

    # Optimize
    model.optimize()

    # Status checking
```

(continues on next page)

(continued from previous page)

```
    status = model.getAttr(GRB.Attr.Status)

    if status in (GRB.INF_OR_UNBD, GRB.INFEASIBLE, GRB.UNBOUNDED):
        print("The model cannot be solved because it is infeasible or unbounded")
        sys.exit(1)

    if status != GRB.OPTIMAL:
        print("Optimization was stopped with status ", status)
        sys.exit(1)

    # Print result
    objval = model.getAttr(GRB.Attr.ObjVal)

    if objval > 1.9:
        print("Logical expression is satisfiable")
    elif objval > 0.9:
        print("At least four clauses can be satisfied")
    else:
        print("Not even three clauses can be satisfied")

except gp.GurobiError as e:
    print(f"Error code {e.errno}: {e}")

except AttributeError:
    print("Encountered an attribute error")
```

heurcb.py

```
#!/usr/bin/env python3.11

# Copyright 2025, Gurobi Optimization, LLC

# This example uses a callback to implement a simple rounding heuristic.
# It reads a MIP model from a file, sets up the callback, turns off
# the standard heuristics, and then applies the callback heuristic
# at every opportunity.

import sys
import math
import gurobipy as gp
from gurobipy import GRB


# Define callback function


def mycallback(model, where):
    if where == GRB.Callback.MIPNODE:
        if model.cbGet(GRB.Callback.MIPNODE_STATUS) == GRB.OPTIMAL:
            integers = []
```

(continues on next page)

(continued from previous page)

```
            fixval = []
            for v in model.getVars():
                if v.vtype != GRB.CONTINUOUS:
                    x = model.cbGetNodeRel(v)
                    integers += [v]
                    fixval += [math.ceil(x - 1e-5)]  # Round all int vars up
            model.cbSetSolution(integers, fixval)


if len(sys.argv) < 2:
    print("Usage: heurcb.py filename")
    sys.exit(0)

# Read and solve model

model = gp.read(sys.argv[1])

# Turn off Gurobi heuristics

model.setParam("Heuristics", 0)

# Solve model

model.optimize(mycallback)
```

lp.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example reads an LP model from a file and solves it.
# If the model is infeasible or unbounded, the example turns off
# presolve and solves the model again. If the model is infeasible,
# the example computes an Irreducible Inconsistent Subsystem (IIS),
# and writes it to a file

import sys
import gurobipy as gp
from gurobipy import GRB

if len(sys.argv) < 2:
    print("Usage: lp.py filename")
    sys.exit(0)

# Read and solve model

model = gp.read(sys.argv[1])
model.optimize()
```

(continues on next page)

(continued from previous page)

```
if model.Status == GRB.INF_OR_UNBD:
    # Turn presolve off to determine whether model is infeasible
    # or unbounded
    model.setParam(GRB.Param.Presolve, 0)
    model.optimize()

if model.Status == GRB.OPTIMAL:
    print(f"Optimal objective: {model.ObjVal:g}")
    model.write("model.sol")
    sys.exit(0)
elif model.Status != GRB.INFEASIBLE:
    print(f"Optimization was stopped with status {model.Status}")
    sys.exit(0)


# Model is infeasible - compute an Irreducible Inconsistent Subsystem (IIS)

print("")
print("Model is infeasible")
model.computeIIS()
model.write("model.ilp")
print("IIS written to file 'model.ilp'")
```

lpmethod.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Solve a model with different values of the Method parameter;
# show which value gives the shortest solve time.

import sys
import gurobipy as gp
from gurobipy import GRB

if len(sys.argv) < 2:
    print("Usage: lpmethod.py filename")
    sys.exit(0)

# Read model
m = gp.read(sys.argv[1])

# Solve the model with different values of Method
bestTime = m.Params.TimeLimit
bestMethod = -1
for i in range(3):
    m.reset()
    m.Params.Method = i
    m.optimize()
```

(continues on next page)

(continued from previous page)

```
    if m.Status == GRB.OPTIMAL:
        bestTime = m.Runtime
        bestMethod = i
        # Reduce the TimeLimit parameter to save time with other methods
        m.Params.TimeLimit = bestTime

# Report which method was fastest
if bestMethod == -1:
    print("Unable to solve this model")
else:
    print(f"Solved in {bestTime:g} seconds with Method {bestMethod}")
```

lpmod.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example reads an LP model from a file and solves it.
# If the model can be solved, then it finds the smallest positive variable,
# sets its upper bound to zero, and resolves the model two ways:
# first with an advanced start, then without an advanced start
# (i.e. 'from scratch').

import sys
import gurobipy as gp
from gurobipy import GRB

if len(sys.argv) < 2:
    print("Usage: lpmod.py filename")
    sys.exit(0)

# Read model and determine whether it is an LP

model = gp.read(sys.argv[1])
if model.IsMIP == 1:
    print("The model is not a linear program")
    sys.exit(1)

model.optimize()

status = model.Status

if status == GRB.INF_OR_UNBD or status == GRB.INFEASIBLE or status == GRB.UNBOUNDED:
    print("The model cannot be solved because it is infeasible or unbounded")
    sys.exit(1)

if status != GRB.OPTIMAL:
    print(f"Optimization was stopped with status {status}")
    sys.exit(0)
```

(continues on next page)

(continued from previous page)

```
# Find the smallest variable value
minVal = GRB.INFINITY
for v in model.getVars():
    if v.X > 0.0001 and v.X < minVal and v.LB == 0.0:
        minVal = v.X
        minVar = v

print(f"\n*** Setting {minVar.VarName} from {minVal:g} to zero ***\n")
minVar.UB = 0.0

# Solve from this starting point
model.optimize()

# Save iteration & time info
warmCount = model.IterCount
warmTime = model.Runtime

# Reset the model and resolve
print("\n*** Resetting and solving without an advanced start ***\n")
model.reset()
model.optimize()

coldCount = model.IterCount
coldTime = model.Runtime

print("")
print(f"*** Warm start: {warmCount:g} iterations, {warmTime:g} seconds")
print(f"*** Cold start: {coldCount:g} iterations, {coldTime:g} seconds")
```

matrix1.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example formulates and solves the following simple MIP model
# using the matrix API:
#  maximize
#        x +   y + 2 z
#  subject to
#        x + 2 y + 3 z <= 4
#        x +   y       >= 1
#        x, y, z binary

import gurobipy as gp
from gurobipy import GRB
import numpy as np
import scipy.sparse as sp
```

(continues on next page)

(continued from previous page)

```
try:
    # Create a new model
    m = gp.Model("matrix1")

    # Create variables
    x = m.addMVar(shape=3, vtype=GRB.BINARY, name="x")

    # Set objective
    obj = np.array([1.0, 1.0, 2.0])
    m.setObjective(obj @ x, GRB.MAXIMIZE)

    # Build (sparse) constraint matrix
    val = np.array([1.0, 2.0, 3.0, -1.0, -1.0])
    row = np.array([0, 0, 0, 1, 1])
    col = np.array([0, 1, 2, 0, 1])

    A = sp.csr_matrix((val, (row, col)), shape=(2, 3))

    # Build rhs vector
    rhs = np.array([4.0, -1.0])

    # Add constraints
    m.addConstr(A @ x <= rhs, name="c")

    # Optimize model
    m.optimize()

    print(x.X)
    print(f"Obj: {m.ObjVal:g}")

except gp.GurobiError as e:
    print(f"Error code {e.errno}: {e}")

except AttributeError:
    print("Encountered an attribute error")
```

matrix2.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example uses the matrix friendly API to formulate the n-queens
# problem; it maximizes the number queens placed on an n x n
# chessboard without threatening each other.
#
# This example demonstrates slicing on MVar objects.

import numpy as np
import gurobipy as gp
```

(continues on next page)

(continued from previous page)

```
from gurobipy import GRB

n = 8

m = gp.Model("nqueens")

# n-by-n binary variables; x[i, j] decides whether a queen is placed at
# position (i, j)
x = m.addMVar((n, n), vtype=GRB.BINARY, name="x")

# Maximize the number of placed queens
m.setObjective(x.sum(), GRB.MAXIMIZE)

# At most one queen per row; this adds n linear constraints
m.addConstr(x.sum(axis=1) <= 1, name="row")

# At most one queen per column; this adds n linear constraints
m.addConstr(x.sum(axis=0) <= 1, name="col")

for i in range(-n + 1, n):
    # At most one queen on diagonal i
    m.addConstr(x.diagonal(i).sum() <= 1, name=f"diag{i:d}")

    # At most one queen on anti-diagonal i
    m.addConstr(x[:, ::-1].diagonal(i).sum() <= 1, name=f"adiag{i:d}")

# Solve the problem
m.optimize()

print(x.X)
print(f"Queens placed: {m.ObjVal:.0f}")
```

mip1.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example formulates and solves the following simple MIP model:
#  maximize
#        x +   y + 2 z
#  subject to
#        x + 2 y + 3 z <= 4
#        x +   y       >= 1
#        x, y, z binary

import gurobipy as gp
from gurobipy import GRB

try:
```

(continues on next page)

(continued from previous page)

```
    # Create a new model
    m = gp.Model("mip1")

    # Create variables
    x = m.addVar(vtype=GRB.BINARY, name="x")
    y = m.addVar(vtype=GRB.BINARY, name="y")
    z = m.addVar(vtype=GRB.BINARY, name="z")

    # Set objective
    m.setObjective(x + y + 2 * z, GRB.MAXIMIZE)

    # Add constraint: x + 2 y + 3 z <= 4
    m.addConstr(x + 2 * y + 3 * z <= 4, "c0")

    # Add constraint: x + y >= 1
    m.addConstr(x + y >= 1, "c1")

    # Optimize model
    m.optimize()

    for v in m.getVars():
        print(f"{v.VarName} {v.X:g}")

    print(f"Obj: {m.ObjVal:g}")

except gp.GurobiError as e:
    print(f"Error code {e.errno}: {e}")

except AttributeError:
    print("Encountered an attribute error")
```

mip1_remote.py

```
import gurobipy as gp
from gurobipy import GRB

# Variation of mip1.py, with a focus on remote services
#
# When remote resources are tied to the optimization process, such as a token
# server, compute server, or Instant Cloud, extra care should be taken to
# ensure that such resources are released once they are no longer needed.
# Technically, such resources are managed by a gurobipy.Env object
# ("environment").  This example shows best practices for acquiring and
# releasing such shared resources via Env objects.
#
# See also https://docs.gurobi.com/projects/optimizer/en/current/reference/misc/emptyenv.
↪html#configuration-parameters


def populate_and_solve(m):
```

(continues on next page)

(continued from previous page)

```
    # This function formulates and solves the following MIP model (see mip1.py):
    #  maximize
    #        x +   y + 2 z
    #  subject to
    #        x + 2 y + 3 z <= 4
    #        x +   y       >= 1
    #        x, y, z binary

    # Create variables
    x = m.addVar(vtype=GRB.BINARY, name="x")
    y = m.addVar(vtype=GRB.BINARY, name="y")
    z = m.addVar(vtype=GRB.BINARY, name="z")

    # Set objective
    m.setObjective(x + y + 2 * z, GRB.MAXIMIZE)

    # Add constraint: x + 2 y + 3 z <= 4
    m.addConstr(x + 2 * y + 3 * z <= 4, "c0")

    # Add constraint: x + y >= 1
    m.addConstr(x + y >= 1, "c1")

    # Optimize model
    m.optimize()

    for v in m.getVars():
        print(f"{v.VarName} {v.X:g}")

    print(f"Obj: {m.ObjVal:g}")


# Put any connection parameters for Gurobi Compute Server, Gurobi Cluster
# Manager or Gurobi Token server here, unless they are set already
# through the license file.

connection_params = {
    # For Compute Server you need at least this
    #       "ComputeServer": "<server name>",
    #       "UserName": "<user name>",
    #       "ServerPassword": "<password>",
    # For Cluster Manager you need at least this
    #       "CSManager": "<manager name>",
    #       "CSAPIAccessID": "<access ID>",
    #       "CSAPISecret": "<secret>",
    # For Instant cloud you need at least this
    #       "CloudAccessID": "<access id>",
    #       "CloudSecretKey": "<secret>",
}

with gp.Env(params=connection_params) as env:
    # 'env' is now set up according to the connection parameters.
    # The environment is disposed of automatically through the context manager
```

(continues on next page)

(continued from previous page)

```
    # upon leaving this block.
    with gp.Model(env=env) as model:
        # 'model' is now an instance tied to the enclosing Env object 'env'.
        # The model is disposed of automatically through the context manager
        # upon leaving this block.
        try:
            populate_and_solve(model)
        except:
            # Add appropriate error handling here.
            raise
```

mip2.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example reads a MIP model from a file, solves it and prints
# the objective values from all feasible solutions generated while
# solving the MIP. Then it creates the associated fixed model and
# solves that model.

import sys
import gurobipy as gp
from gurobipy import GRB

if len(sys.argv) < 2:
    print("Usage: mip2.py filename")
    sys.exit(0)

# Read and solve model

model = gp.read(sys.argv[1])

if model.IsMIP == 0:
    print("Model is not a MIP")
    sys.exit(0)

model.optimize()

if model.Status == GRB.OPTIMAL:
    print(f"Optimal objective: {model.ObjVal:g}")
elif model.Status == GRB.INF_OR_UNBD:
    print("Model is infeasible or unbounded")
    sys.exit(0)
elif model.Status == GRB.INFEASIBLE:
    print("Model is infeasible")
    sys.exit(0)
elif model.Status == GRB.UNBOUNDED:
    print("Model is unbounded")
```

(continues on next page)

(continued from previous page)

```
    sys.exit(0)
else:
    print(f"Optimization ended with status {model.Status}")
    sys.exit(0)

# Iterate over the solutions and compute the objectives
model.Params.OutputFlag = 0
print("")
for k in range(model.SolCount):
    model.Params.SolutionNumber = k
    print(f"Solution {k} has objective {model.PoolNObjVal:g}")
print("")
model.Params.OutputFlag = 1

fixed = model.fixed()
fixed.Params.Presolve = 0
fixed.optimize()

if fixed.Status != GRB.OPTIMAL:
    print("Error: fixed model isn't optimal")
    sys.exit(1)

diff = model.ObjVal - fixed.ObjVal

if abs(diff) > 1e-6 * (1.0 + abs(model.ObjVal)):
    print("Error: objective values are different")
    sys.exit(1)

# Print values of nonzero variables
for v in fixed.getVars():
    if v.X != 0:
        print(f"{v.VarName} {v.X:g}")
```

multiobj.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Want to cover four different sets but subject to a common budget of
# elements allowed to be used. However, the sets have different priorities to
# be covered; and we tackle this by using multi-objective optimization.

import gurobipy as gp
from gurobipy import GRB
import sys

try:
    # Sample data
    Groundset = range(20)
```

(continues on next page)

(continued from previous page)

```
    Subsets = range(4)
    Budget = 12
    Set = [
        [1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0],
        [0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1],
        [0, 0, 0, 1, 1, 0, 1, 1, 0, 0, 0, 0, 0, 1, 1, 0, 1, 1, 0, 0],
        [0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0],
    ]
    SetObjPriority = [3, 2, 2, 1]
    SetObjWeight = [1.0, 0.25, 1.25, 1.0]

    # Create initial model
    model = gp.Model("multiobj")

    # Initialize decision variables for ground set:
    # x[e] == 1 if element e is chosen for the covering.
    Elem = model.addVars(Groundset, vtype=GRB.BINARY, name="El")

    # Constraint: limit total number of elements to be picked to be at most
    # Budget
    model.addConstr(Elem.sum() <= Budget, name="Budget")

    # Set global sense for ALL objectives
    model.ModelSense = GRB.MAXIMIZE

    # Limit how many solutions to collect
    model.setParam(GRB.Param.PoolSolutions, 100)

    # Set and configure i-th objective
    for i in Subsets:
        objn = sum(Elem[k] * Set[i][k] for k in range(len(Elem)))
        model.setObjectiveN(
            objn, i, SetObjPriority[i], SetObjWeight[i], 1.0 + i, 0.01, "Set" + str(i)
        )

    # Save problem
    model.write("multiobj.lp")

    # Optimize
    model.optimize()

    model.setParam(GRB.Param.OutputFlag, 0)

    # Status checking
    status = model.Status
    if status in (GRB.INF_OR_UNBD, GRB.INFEASIBLE, GRB.UNBOUNDED):
        print("The model cannot be solved because it is infeasible or unbounded")
        sys.exit(1)

    if status != GRB.OPTIMAL:
        print(f"Optimization was stopped with status {status}")
        sys.exit(1)
```

(continues on next page)

(continued from previous page)

```
    # Print best selected set
    print("Selected elements in best solution:")
    selected = [e for e in Groundset if Elem[e].X > 0.9]
    print(" ".join(f"El{e}" for e in selected))

    # Print number of solutions stored
    nSolutions = model.SolCount
    print(f"Number of solutions found: {nSolutions}")

    # Print objective values of solutions
    if nSolutions > 10:
        nSolutions = 10
    print(f"Objective values for first {nSolutions} solutions:")
    for i in Subsets:
        model.setParam(GRB.Param.ObjNumber, i)
        objvals = []
        for e in range(nSolutions):
            model.setParam(GRB.Param.SolutionNumber, e)
            objvals.append(model.ObjNVal)

        print(f"\tSet{i}" + "".join(f" {objval:6g}" for objval in objvals[:3]))

except gp.GurobiError as e:
    print(f"Error code {e.errno}: {e}")

except AttributeError as e:
    print(f"Encountered an attribute error: {e}")
```

multiscenario.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Facility location: a company currently ships its product from 5 plants to
# 4 warehouses. It is considering closing some plants to reduce costs. What
# plant(s) should the company close, in order to minimize transportation
# and fixed costs?
#
# Since the plant fixed costs and the warehouse demands are uncertain, a
# scenario approach is chosen.
#
# Note that this example is similar to the facility.py example. Here we
# added scenarios in order to illustrate the multi-scenario feature.
#
# Note that this example uses lists instead of dictionaries.  Since
# it does not work with sparse data, lists are a reasonable option.
#
# Based on an example from Frontline Systems:
```

(continues on next page)

(continued from previous page)

```
#   http://www.solver.com/disfacility.htm
# Used with permission.

import gurobipy as gp
from gurobipy import GRB

# Warehouse demand in thousands of units
demand = [15, 18, 14, 20]

# Plant capacity in thousands of units
capacity = [20, 22, 17, 19, 18]

# Fixed costs for each plant
fixedCosts = [12000, 15000, 17000, 13000, 16000]
maxFixed = max(fixedCosts)
minFixed = min(fixedCosts)

# Transportation costs per thousand units
transCosts = [
    [4000, 2000, 3000, 2500, 4500],
    [2500, 2600, 3400, 3000, 4000],
    [1200, 1800, 2600, 4100, 3000],
    [2200, 2600, 3100, 3700, 3200],
]

# Range of plants and warehouses
plants = range(len(capacity))
warehouses = range(len(demand))

# Model
m = gp.Model("multiscenario")

# Plant open decision variables: open[p] == 1 if plant p is open.
open = m.addVars(plants, vtype=GRB.BINARY, obj=fixedCosts, name="open")

# Transportation decision variables: transport[w,p] captures the
# optimal quantity to transport to warehouse w from plant p
transport = m.addVars(warehouses, plants, obj=transCosts, name="trans")

# You could use Python looping constructs and m.addVar() to create
# these decision variables instead.  The following would be equivalent
# to the preceding two statements...
#
# open = []
# for p in plants:
#     open.append(m.addVar(vtype=GRB.BINARY,
#                          obj=fixedCosts[p],
#                          name="open[%d]" % p))
#
# transport = []
# for w in warehouses:
#     transport.append([])
```

(continues on next page)

(continued from previous page)

```
#     for p in plants:
#         transport[w].append(m.addVar(obj=transCosts[w][p],
#                                      name="trans[%d,%d]" % (w, p)))

# The objective is to minimize the total fixed and variable costs
m.ModelSense = GRB.MINIMIZE

# Production constraints
# Note that the right-hand limit sets the production to zero if the plant
# is closed
m.addConstrs(
    (transport.sum("*", p) <= capacity[p] * open[p] for p in plants), "Capacity"
)

# Using Python looping constructs, the preceding would be...
#
# for p in plants:
#     m.addConstr(sum(transport[w][p] for w in warehouses)
#                 <= capacity[p] * open[p], "Capacity[%d]" % p)

# Demand constraints
demandConstr = m.addConstrs(
    (transport.sum(w, "*") == demand[w] for w in warehouses), "Demand"
)

# ... and the preceding would be ...
# for w in warehouses:
#     m.addConstr(sum(transport[w][p] for p in plants) == demand[w],
#                 "Demand[%d]" % w)

# We constructed the base model, now we add 7 scenarios
#
# Scenario 0: Represents the base model, hence, no manipulations.
# Scenario 1: Manipulate the warehouses demands slightly (constraint right
#             hand sides).
# Scenario 2: Double the warehouses demands (constraint right hand sides).
# Scenario 3: Manipulate the plant fixed costs (objective coefficients).
# Scenario 4: Manipulate the warehouses demands and fixed costs.
# Scenario 5: Force the plant with the largest fixed cost to stay open
#             (variable bounds).
# Scenario 6: Force the plant with the smallest fixed cost to be closed
#             (variable bounds).

m.NumScenarios = 7

# Scenario 0: Base model, hence, nothing to do except giving the scenario a
#             name
m.Params.ScenarioNumber = 0
m.ScenNName = "Base model"

# Scenario 1: Increase the warehouse demands by 10%
m.Params.ScenarioNumber = 1
```

(continues on next page)

(continued from previous page)

```
m.ScenNName = "Increased warehouse demands"
for w in warehouses:
    demandConstr[w].ScenNRhs = demand[w] * 1.1

# Scenario 2: Double the warehouse demands
m.Params.ScenarioNumber = 2
m.ScenNName = "Double the warehouse demands"
for w in warehouses:
    demandConstr[w].ScenNRhs = demand[w] * 2.0

# Scenario 3: Decrease the plant fixed costs by 5%
m.Params.ScenarioNumber = 3
m.ScenNName = "Decreased plant fixed costs"
for p in plants:
    open[p].ScenNObj = fixedCosts[p] * 0.95

# Scenario 4: Combine scenario 1 and scenario 3
m.Params.ScenarioNumber = 4
m.ScenNName = "Increased warehouse demands and decreased plant fixed costs"
for w in warehouses:
    demandConstr[w].ScenNRhs = demand[w] * 1.1
for p in plants:
    open[p].ScenNObj = fixedCosts[p] * 0.95

# Scenario 5: Force the plant with the largest fixed cost to stay open
m.Params.ScenarioNumber = 5
m.ScenNName = "Force plant with largest fixed cost to stay open"
open[fixedCosts.index(maxFixed)].ScenNLB = 1.0

# Scenario 6: Force the plant with the smallest fixed cost to be closed
m.Params.ScenarioNumber = 6
m.ScenNName = "Force plant with smallest fixed cost to be closed"
open[fixedCosts.index(minFixed)].ScenNUB = 0.0

# Save model
m.write("multiscenario.lp")

# Guess at the starting point: close the plant with the highest fixed costs;
# open all others

# First open all plants
for p in plants:
    open[p].Start = 1.0

# Now close the plant with the highest fixed cost
p = fixedCosts.index(maxFixed)
open[p].Start = 0.0
print(f"Initial guess: Closing plant {p}\n")

# Use barrier to solve root relaxation
m.Params.Method = 2
```

(continues on next page)

(continued from previous page)

```
# Solve multi-scenario model
m.optimize()

# Print solution for each scenario
for s in range(m.NumScenarios):
    # Set the scenario number to query the information for this scenario
    m.Params.ScenarioNumber = s

    print(f"\n\n------ Scenario {s} ({m.ScenNName})")

    # Check if we found a feasible solution for this scenario
    if m.ModelSense * m.ScenNObjVal >= GRB.INFINITY:
        if m.ModelSense * m.ScenNObjBound >= GRB.INFINITY:
            # Scenario was proven to be infeasible
            print("\nINFEASIBLE")
        else:
            # We did not find any feasible solution - should not happen in
            # this case, because we did not set any limit (like a time
            # limit) on the optimization process
            print("\nNO SOLUTION")
    else:
        print(f"\nTOTAL COSTS: {m.ScenNObjVal:g}")
        print("SOLUTION:")
        for p in plants:
            if open[p].ScenNX > 0.5:
                print(f"Plant {p} open")
                for w in warehouses:
                    if transport[w, p].ScenNX > 0:
                        print(
                            f"  Transport {transport[w, p].ScenNX:g} units to warehouse
↪{w}"
                        )
            else:
                print(f"Plant {p} closed!")

# Print a summary table: for each scenario we add a single summary line
print("\n\nSummary: Closed plants depending on scenario\n")
print(f"{'':8} | {'Plant':>17} {'|':>13}")

tableStr = [f"{'Scenario':8} |"]
tableStr += [f"{p:>5}" for p in plants]
tableStr += [f"| {'Costs':>6}  Name"]
print(" ".join(tableStr))

for s in range(m.NumScenarios):
    # Set the scenario number to query the information for this scenario
    m.Params.ScenarioNumber = s

    tableStr = f"{s:<8} |"

    # Check if we found a feasible solution for this scenario
    if m.ModelSense * m.ScenNObjVal >= GRB.INFINITY:
```

(continues on next page)

(continued from previous page)

```
        if m.ModelSense * m.ScenNObjBound >= GRB.INFINITY:
            # Scenario was proven to be infeasible
            print(tableStr, f"{'infeasible':<30}| {'-':>6}  {m.ScenNName:<}")
        else:
            # We did not find any feasible solution - should not happen in
            # this case, because we did not set any limit (like a time
            # limit) on the optimization process
            print(tableStr, f"{'no solution found':<30}| {'-':>6}  {m.ScenNName:<}")
    else:
        for p in plants:
            if open[p].ScenNX > 0.5:
                tableStr += f" {' ':>5}"
            else:
                tableStr += f" {'x':>5}"

        print(tableStr, f"| {m.ScenNObjVal:6g}  {m.ScenNName:<}")
```

netflow.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Solve a multi-commodity flow problem.  Two products ('Pencils' and 'Pens')
# are produced in 2 cities ('Detroit' and 'Denver') and must be sent to
# warehouses in 3 cities ('Boston', 'New York', and 'Seattle') to
# satisfy supply/demand ('inflow[h,i]').
#
# Flows on the transportation network must respect arc capacity constraints
# ('capacity[i,j]'). The objective is to minimize the sum of the arc
# transportation costs ('cost[i,j]').

import gurobipy as gp
from gurobipy import GRB

# Base data
commodities = ["Pencils", "Pens"]
nodes = ["Detroit", "Denver", "Boston", "New York", "Seattle"]

arcs, capacity = gp.multidict(
    {
        ("Detroit", "Boston"): 100,
        ("Detroit", "New York"): 80,
        ("Detroit", "Seattle"): 120,
        ("Denver", "Boston"): 120,
        ("Denver", "New York"): 120,
        ("Denver", "Seattle"): 120,
    }
)
```

(continues on next page)

(continued from previous page)

```
# Cost for triplets commodity-source-destination
cost = {
    ("Pencils", "Detroit", "Boston"): 10,
    ("Pencils", "Detroit", "New York"): 20,
    ("Pencils", "Detroit", "Seattle"): 60,
    ("Pencils", "Denver", "Boston"): 40,
    ("Pencils", "Denver", "New York"): 40,
    ("Pencils", "Denver", "Seattle"): 30,
    ("Pens", "Detroit", "Boston"): 20,
    ("Pens", "Detroit", "New York"): 20,
    ("Pens", "Detroit", "Seattle"): 80,
    ("Pens", "Denver", "Boston"): 60,
    ("Pens", "Denver", "New York"): 70,
    ("Pens", "Denver", "Seattle"): 30,
}

# Supply (> 0) and demand (< 0) for pairs of commodity-city
inflow = {
    ("Pencils", "Detroit"): 50,
    ("Pencils", "Denver"): 60,
    ("Pencils", "Boston"): -50,
    ("Pencils", "New York"): -50,
    ("Pencils", "Seattle"): -10,
    ("Pens", "Detroit"): 60,
    ("Pens", "Denver"): 40,
    ("Pens", "Boston"): -40,
    ("Pens", "New York"): -30,
    ("Pens", "Seattle"): -30,
}

# Create optimization model
m = gp.Model("netflow")

# Create variables
flow = m.addVars(commodities, arcs, obj=cost, name="flow")

# Arc-capacity constraints
m.addConstrs((flow.sum("*", i, j) <= capacity[i, j] for i, j in arcs), "cap")

# Equivalent version using Python looping
# for i, j in arcs:
#   m.addConstr(sum(flow[h, i, j] for h in commodities) <= capacity[i, j],
#               "cap[%s, %s]" % (i, j))


# Flow-conservation constraints
m.addConstrs(
    (
        flow.sum(h, "*", j) + inflow[h, j] == flow.sum(h, j, "*")
        for h in commodities
        for j in nodes
    ),
```

(continues on next page)

(continued from previous page)

```
    "node",
)

# Alternate version:
# m.addConstrs(
#   (gp.quicksum(flow[h, i, j] for i, j in arcs.select('*', j)) + inflow[h, j] ==
#     gp.quicksum(flow[h, j, k] for j, k in arcs.select(j, '*'))
#     for h in commodities for j in nodes), "node")

# Compute optimal solution
m.optimize()

# Print solution
if m.Status == GRB.OPTIMAL:
    solution = m.getAttr("X", flow)
    for h in commodities:
        print(f"\nOptimal flows for {h}:")
        for i, j in arcs:
            if solution[h, i, j] > 0:
                print(f"{i} -> {j}: {solution[h, i, j]:g}")
```

nlconstr.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example formulates and solves the following simple nonlinear model
# using the nonlinear API:
#
#   minimize    x - y
#   subject to  sin(x) * x + x^2 * y  <= 1
#               y = cos(x) (<=> cos(x) - y = 0)
#              -1 <= x <= 2
#               0 <= y <= 2
#
# The example uses the nonlinear expression API. The left-hand sides
# of the constraints are built as NLExpr objects with the overloaded
# operators, the nonlinear functions hosted in gurobipy.nlfunc, and the
# ** operator, and passed directly to addConstr().
#
# We retrieve a nonlinear constraint with getNLConstrLHS() together with
# its sense and rhs attribute and print it.

import gurobipy as gp
from gurobipy import GRB
from gurobipy.nlfunc import sin, cos

# Create new model
model = gp.Model("nlconstr")
```

(continues on next page)

(continued from previous page)

```
# Create variables
x = model.addVar(lb=-1.0, ub=2.0, obj=1.0, vtype=GRB.CONTINUOUS, name="x")
y = model.addVar(lb=0.0, ub=2.0, obj=-1.0, vtype=GRB.CONTINUOUS, name="y")

# Add nonlinear constraint: sin(x)*x + x^2*y <= 1.
nlc1 = model.addConstr(sin(x) * x + x**2 * y <= 1.0, "NonlinearConstraint1")

# Add nonlinear constraint: cos(x) - y = 0
nlc2 = model.addConstr(cos(x) - y == 0.0, "NonlinearConstraint2")

# Optimize model
model.optimize()

print("\nSolving model with nonlinear constraints")
if model.Status == GRB.OPTIMAL:
    print(f"Optimal objective: {model.ObjVal}")
    print(f"  x={x.X}, y={y.X}")
elif model.Status == GRB.INF_OR_UNBD:
    print("Model is infeasible or unbounded")
else:
    print("Optimization was stopped early")

# Retrieve the first nonlinear constraint as an NLExpr and print it
lhs = model.getNLConstrLHS(nlc1)
print(f'\nRetrieved NL constraint: "{lhs} {nlc1.NLCSense}= {nlc1.NLCRHS}"')
```

nlobj.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example formulates and solves the following simple nonlinear model
# using the nonlinear objective API:
#
#      minimize    sin(x) * x + x^2 * y
#      subject to  x + y  >= 1
#                 -1 <= x <= 2
#                  0 <= y <= 2
#
# The example uses the nonlinear expression API. The nonlinear
# expression in the objective is built as NLExpr object with the overloaded
# operators, the nonlinear functions hosted in gurobipy.nlfunc, and the
# ** operator.
#
# We retrieve the nonlinear objective with getObjective() and print it.

import gurobipy as gp
from gurobipy import GRB
```

(continues on next page)

(continued from previous page)

```
from gurobipy.nlfunc import sin, cos

# Create new model
model = gp.Model("nlobj")

# Create variables
x = model.addVar(lb=-1.0, ub=2.0, obj=0.0, vtype=GRB.CONTINUOUS, name="x")
y = model.addVar(lb=0.0, ub=2.0, obj=0.0, vtype=GRB.CONTINUOUS, name="y")

# Add constraint: x + y >= 1
model.addConstr(x + y >= 1.0, "c0")

# Add nonlinear objective: sin(x)*x + x^2*y
model.setObjective(sin(x) * x + x**2 * y)

# Optimize model
model.optimize()

print("\nSolving model with nonlinear objective")
if model.Status == GRB.OPTIMAL:
    print(f"Optimal objective: {model.ObjVal}")
    print(f"  x={x.X}, y={y.X}")
else:
    print("Optimization did not produce an optimal solution")

# Retrieve the nonlinear objective as an NLExpr and print it
nlobj = model.getObjective()
print(f'\nRetrieved NL objective: "{nlobj}"')
```

params.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Use parameters that are associated with a model.
#
# A MIP is solved for a few seconds with different sets of parameters.
# The one with the smallest MIP gap is selected, and the optimization
# is resumed until the optimal solution is found.

import sys
import gurobipy as gp

if len(sys.argv) < 2:
    print("Usage: params.py filename")
    sys.exit(0)


# Read model and verify that it is a MIP
```

(continues on next page)

(continued from previous page)

```
m = gp.read(sys.argv[1])
if m.IsMIP == 0:
    print("The model is not an integer program")
    sys.exit(1)

# Set a 2 second time limit
m.Params.TimeLimit = 2

# Now solve the model with different values of MIPFocus
bestModel = m.copy()
bestModel.optimize()
for i in range(1, 4):
    m.reset()
    m.Params.MIPFocus = i
    m.optimize()
    if bestModel.MIPGap > m.MIPGap:
        bestModel, m = m, bestModel  # swap models

# Finally, delete the extra model, reset the time limit and
# continue to solve the best model to optimality
del m
bestModel.Params.TimeLimit = float("inf")
bestModel.optimize()
print(f"Solved with MIPFocus: {bestModel.Params.MIPFocus}")
```

piecewise.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example considers the following separable, convex problem:
#
#   minimize    f(x) - y + g(z)
#   subject to  x + 2 y + 3 z <= 4
#               x +   y       >= 1
#               x,    y,    z <= 1
#
# where f(u) = exp(-u) and g(u) = 2 u^2 - 4 u, for all real u. It
# formulates and solves a simpler LP model by approximating f and
# g with piecewise-linear functions. Then it transforms the model
# into a MIP by negating the approximation for f, which corresponds
# to a non-convex piecewise-linear function, and solves it again.

import gurobipy as gp
from math import exp


def f(u):
    return exp(-u)
```

(continues on next page)

(continued from previous page)

```
def g(u):
    return 2 * u * u - 4 * u


try:
    # Create a new model

    m = gp.Model()

    # Create variables

    lb = 0.0
    ub = 1.0

    x = m.addVar(lb, ub, name="x")
    y = m.addVar(lb, ub, name="y")
    z = m.addVar(lb, ub, name="z")

    # Set objective for y

    m.setObjective(-y)

    # Add piecewise-linear objective functions for x and z

    npts = 101
    ptu = []
    ptf = []
    ptg = []

    for i in range(npts):
        ptu.append(lb + (ub - lb) * i / (npts - 1))
        ptf.append(f(ptu[i]))
        ptg.append(g(ptu[i]))

    m.setPWLObj(x, ptu, ptf)
    m.setPWLObj(z, ptu, ptg)

    # Add constraint: x + 2 y + 3 z <= 4

    m.addConstr(x + 2 * y + 3 * z <= 4, "c0")

    # Add constraint: x + y >= 1

    m.addConstr(x + y >= 1, "c1")

    # Optimize model as an LP

    m.optimize()

    print(f"IsMIP: {m.IsMIP}")
```

(continues on next page)

(continued from previous page)

```
    for v in m.getVars():
        print(f"{v.VarName} {v.X:g}")
    print(f"Obj: {m.ObjVal:g}")
    print("")

    # Negate piecewise-linear objective function for x

    for i in range(npts):
        ptf[i] = -ptf[i]

    m.setPWLObj(x, ptu, ptf)

    # Optimize model as a MIP

    m.optimize()

    print(f"IsMIP: {m.IsMIP}")
    for v in m.getVars():
        print(f"{v.VarName} {v.X:g}")
    print(f"Obj: {m.ObjVal:g}")

except gp.GurobiError as e:
    print(f"Error code {e.errno}: {e}")

except AttributeError:
    print("Encountered an attribute error")
```

poolsearch.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# We find alternative epsilon-optimal solutions to a given knapsack
# problem by using PoolSearchMode

import gurobipy as gp
from gurobipy import GRB
import sys

try:
    # Sample data
    Groundset = range(10)
    objCoef = [32, 32, 15, 15, 6, 6, 1, 1, 1, 1]
    knapsackCoef = [16, 16, 8, 8, 4, 4, 2, 2, 1, 1]
    Budget = 33

    # Create initial model
    model = gp.Model("poolsearch")
```

(continues on next page)

(continued from previous page)

```
    # Create dicts for tupledict.prod() function
    objCoefDict = dict(zip(Groundset, objCoef))
    knapsackCoefDict = dict(zip(Groundset, knapsackCoef))

    # Initialize decision variables for ground set:
    # x[e] == 1 if element e is chosen
    Elem = model.addVars(Groundset, vtype=GRB.BINARY, name="El")

    # Set objective function
    model.ModelSense = GRB.MAXIMIZE
    model.setObjective(Elem.prod(objCoefDict))

    # Constraint: limit total number of elements to be picked to be at most
    # Budget
    model.addConstr(Elem.prod(knapsackCoefDict) <= Budget, name="Budget")

    # Limit how many solutions to collect
    model.setParam(GRB.Param.PoolSolutions, 1024)
    # Limit the search space by setting a gap for the worst possible solution
    # that will be accepted
    model.setParam(GRB.Param.PoolGap, 0.10)
    # do a systematic search for the k-best solutions
    model.setParam(GRB.Param.PoolSearchMode, 2)

    # save problem
    model.write("poolsearch.lp")

    # Optimize
    model.optimize()

    model.setParam(GRB.Param.OutputFlag, 0)

    # Status checking
    status = model.Status
    if status in (GRB.INF_OR_UNBD, GRB.INFEASIBLE, GRB.UNBOUNDED):
        print("The model cannot be solved because it is infeasible or unbounded")
        sys.exit(1)

    if status != GRB.OPTIMAL:
        print(f"Optimization was stopped with status {status}")
        sys.exit(1)

    # Print best selected set
    print("Selected elements in best solution:")
    print("\t", end="")
    for e in Groundset:
        if Elem[e].X > 0.9:
            print(f" El{e}", end="")
    print("")

    # Print number of solutions stored
    nSolutions = model.SolCount
```

(continues on next page)

(continued from previous page)

```
    print(f"Number of solutions found: {nSolutions}")

    # Print objective values of solutions
    for e in range(nSolutions):
        model.setParam(GRB.Param.SolutionNumber, e)
        print(f"{model.PoolNObjVal:g} ", end="")
        if e % 15 == 14:
            print("")
    print("")

    # print fourth best set if available
    if nSolutions >= 4:
        model.setParam(GRB.Param.SolutionNumber, 3)

        print("Selected elements in fourth best solution:")
        print("\t", end="")
        for e in Groundset:
            if Elem[e].PoolNX > 0.9:
                print(f" El{e}", end="")
        print("")

except gp.GurobiError as e:
    print(f"Gurobi error {e.errno}: {e.message}")

except AttributeError as e:
    print(f"Encountered an attribute error: {e}")
```

portfolio.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Portfolio selection: given a sum of money to invest, one must decide how to
# spend it amongst a portfolio of financial securities.  Our approach is due
# to Markowitz (1959) and looks to minimize the risk associated with the
# investment while realizing a target expected return.  By varying the target,
# one can compute an 'efficient frontier', which defines the optimal portfolio
# for a given expected return.
#
# Note that this example reads historical return data from a comma-separated
# file (../data/portfolio.csv).  As a result, it must be run from the Gurobi
# examples/python directory.
#
# This example requires the pandas (>= 0.20.3), NumPy, and Matplotlib
# Python packages, which are part of the SciPy ecosystem for
# mathematics, science, and engineering (http://scipy.org).  These
# packages aren't included in all Python distributions, but are
# included by default with Anaconda Python.
```

(continues on next page)

(continued from previous page)

```
import gurobipy as gp
from gurobipy import GRB
from math import sqrt
import pandas as pd
import numpy as np
import matplotlib

matplotlib.use("Agg")
import matplotlib.pyplot as plt

# Import (normalized) historical return data using pandas
data = pd.read_csv("../data/portfolio.csv", index_col=0)
stocks = data.columns

# Calculate basic summary statistics for individual stocks
stock_volatility = data.std()
stock_return = data.mean()

# Turn off all logging and create an empty model
with gp.Env(params={"OutputFlag": 0}) as env, gp.Model("portfolio", env=env) as m:

    # Add a variable for each stock
    vars = pd.Series(m.addVars(stocks), index=stocks)

    # Objective is to minimize risk (squared).  This is modeled using the
    # covariance matrix, which measures the historical correlation between stocks.
    sigma = data.cov()
    portfolio_risk = sigma.dot(vars).dot(vars)
    m.setObjective(portfolio_risk, GRB.MINIMIZE)

    # Fix budget with a constraint
    m.addConstr(vars.sum() == 1, "budget")

    # Optimize model to find the minimum risk portfolio
    m.optimize()

    # Create an expression representing the expected return for the portfolio
    portfolio_return = stock_return.dot(vars)

    # Display minimum risk portfolio
    print("Minimum Risk Portfolio:\n")
    for v in vars:
        if v.X > 0:
            print(f"\t{v.VarName}\t: {v.X:g}")
    minrisk_volatility = sqrt(portfolio_risk.getValue())
    print(f"\nVolatility      = {minrisk_volatility:g}")
    minrisk_return = portfolio_return.getValue()
    print(f"Expected Return = {minrisk_return:g}")

    # Add (redundant) target return constraint
    target = m.addConstr(portfolio_return == minrisk_return, "target")
```

(continues on next page)

(continued from previous page)

```
    # Solve for efficient frontier by varying target return
    frontier = pd.Series(dtype=np.float64)
    for r in np.linspace(stock_return.min(), stock_return.max(), 100):
        target.rhs = r
        m.optimize()
        frontier.loc[sqrt(portfolio_risk.getValue())] = r

# Plot volatility versus expected return for individual stocks
ax = plt.gca()
ax.scatter(x=stock_volatility, y=stock_return, color="Blue", label="Individual Stocks")
for stock in stocks:
    ax.annotate(stock, (stock_volatility[stock], stock_return[stock]))

# Plot volatility versus expected return for minimum risk portfolio
ax.scatter(x=minrisk_volatility, y=minrisk_return, color="DarkGreen")
ax.annotate(
    "Minimum\nRisk\nPortfolio",
    (minrisk_volatility, minrisk_return),
    horizontalalignment="right",
)

# Plot efficient frontier
frontier.plot(color="DarkGreen", label="Efficient Frontier", ax=ax)

# Format and display the final plot
ax.axis((0.005, 0.06, -0.02, 0.025))
ax.set_xlabel("Volatility (standard deviation)")
ax.set_ylabel("Expected Return")
ax.legend()
ax.grid()
plt.savefig("portfolio.png")
print("Plotted efficient frontier to 'portfolio.png'")
```

qcp.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example formulates and solves the following simple QCP model:
#  maximize    x
#  subject to  x + y + z = 1
#              x^2 + y^2 <= z^2 (second-order cone)
#              x^2 <= yz        (rotated second-order cone)
#              x, y, z non-negative

import gurobipy as gp
from gurobipy import GRB

# Create a new model
```

(continues on next page)

(continued from previous page)

```
m = gp.Model("qcp")

# Create variables
x = m.addVar(name="x")
y = m.addVar(name="y")
z = m.addVar(name="z")

# Set objective: x
obj = 1.0 * x
m.setObjective(obj, GRB.MAXIMIZE)

# Add constraint: x + y + z = 1
m.addConstr(x + y + z == 1, "c0")

# Add second-order cone: x^2 + y^2 <= z^2
m.addConstr(x**2 + y**2 <= z**2, "qc0")

# Add rotated cone: x^2 <= yz
m.addConstr(x**2 <= y * z, "qc1")

m.optimize()

for v in m.getVars():
    print(f"{v.VarName} {v.X:g}")

print(f"Obj: {m.ObjVal:g}")
```

qp.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example formulates and solves the following simple QP model:
#  minimize
#      x^2 + x*y + y^2 + y*z + z^2 + 2 x
#  subject to
#      x + 2 y + 3 z >= 4
#      x +   y       >= 1
#      x, y, z non-negative
#
# It solves it once as a continuous model, and once as an integer model.

import gurobipy as gp
from gurobipy import GRB

# Create a new model
m = gp.Model("qp")

# Create variables
```

(continues on next page)

(continued from previous page)

```
x = m.addVar(ub=1.0, name="x")
y = m.addVar(ub=1.0, name="y")
z = m.addVar(ub=1.0, name="z")

# Set objective: x^2 + x*y + y^2 + y*z + z^2 + 2 x
obj = x**2 + x * y + y**2 + y * z + z**2 + 2 * x
m.setObjective(obj)

# Add constraint: x + 2 y + 3 z >= 4
m.addConstr(x + 2 * y + 3 * z >= 4, "c0")

# Add constraint: x + y >= 1
m.addConstr(x + y >= 1, "c1")

m.optimize()

for v in m.getVars():
    print(f"{v.VarName} {v.X:g}")

print(f"Obj: {m.ObjVal:g}")

x.VType = GRB.INTEGER
y.VType = GRB.INTEGER
z.VType = GRB.INTEGER

m.optimize()

for v in m.getVars():
    print(f"{v.VarName} {v.X:g}")

print(f"Obj: {m.ObjVal:g}")
```

sensitivity.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# A simple sensitivity analysis example which reads a MIP model from a file
# and solves it. Then uses the scenario feature to analyze the impact
# w.r.t. the objective function of each binary variable if it is set to
# 1-X, where X is its value in the optimal solution.
#
# Usage:
#     sensitivity.py <model filename>
#

import sys
import gurobipy as gp
from gurobipy import GRB
```

(continues on next page)

(continued from previous page)

```
# Maximum number of scenarios to be considered
maxScenarios = 100

if len(sys.argv) < 2:
    print("Usage: sensitivity.py filename")
    sys.exit(0)

# Read model
model = gp.read(sys.argv[1])

if model.IsMIP == 0:
    print("Model is not a MIP")
    sys.exit(0)

# Solve model
model.optimize()

if model.Status != GRB.OPTIMAL:
    print(f"Optimization ended with status {model.Status}")
    sys.exit(0)

# Store the optimal solution
origObjVal = model.ObjVal
for v in model.getVars():
    v._origX = v.X


scenarios = 0

# Count number of unfixed, binary variables in model. For each we create a
# scenario.
for v in model.getVars():
    if v.LB == 0.0 and v.UB == 1.0 and v.VType in (GRB.BINARY, GRB.INTEGER):
        scenarios += 1

        if scenarios >= maxScenarios:
            break


# Set the number of scenarios in the model
model.NumScenarios = scenarios
scenarios = 0

print(f"###  construct multi-scenario model with {scenarios} scenarios")

# Create a (single) scenario model by iterating through unfixed binary
# variables in the model and create for each of these variables a scenario
# by fixing the variable to 1-X, where X is its value in the computed
# optimal solution
for v in model.getVars():
    if (
```

(continues on next page)

(continued from previous page)

```
        v.LB == 0.0
        and v.UB == 1.0
        and v.VType in (GRB.BINARY, GRB.INTEGER)
        and scenarios < maxScenarios
    ):
        # Set ScenarioNumber parameter to select the corresponding scenario
        # for adjustments
        model.Params.ScenarioNumber = scenarios

        # Set variable to 1-X, where X is its value in the optimal solution
        if v._origX < 0.5:
            v.ScenNLB = 1.0
        else:
            v.ScenNUB = 0.0

        scenarios += 1

    else:
        # Add MIP start for all other variables using the optimal solution
        # of the base model
        v.Start = v._origX


# Solve multi-scenario model
model.optimize()


# In case we solved the scenario model to optimality capture the
# sensitivity information
if model.Status == GRB.OPTIMAL:
    modelSense = model.ModelSense
    scenarios = 0

    # Capture sensitivity information from each scenario
    for v in model.getVars():
        if v.LB == 0.0 and v.UB == 1.0 and v.VType in (GRB.BINARY, GRB.INTEGER):
            # Set scenario parameter to collect the objective value of the
            # corresponding scenario
            model.Params.ScenarioNumber = scenarios

            # Collect objective value and bound for the scenario
            scenarioObjVal = model.ScenNObjVal
            scenarioObjBound = model.ScenNObjBound

            # Check if we found a feasible solution for this scenario
            if modelSense * scenarioObjVal >= GRB.INFINITY:
                # Check if the scenario is infeasible
                if modelSense * scenarioObjBound >= GRB.INFINITY:
                    print(
                        f"Objective sensitivity for variable {v.VarName} is infeasible"
                    )
                else:
```

(continues on next page)

(continued from previous page)

```
                    print(
                        f"Objective sensitivity for variable {v.VarName} is unknown (no␣
↪solution available)"
                    )
            else:
                # Scenario is feasible and a solution is available
                print(
                    f"Objective sensitivity for variable {v.VarName} is {modelSense *␣
↪(scenarioObjVal - origObjVal):g}"
                )

            scenarios += 1

            if scenarios >= maxScenarios:
                break
```

sos.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# This example creates a very simple Special Ordered Set (SOS) model.
# The model consists of 3 continuous variables, no linear constraints,
# and a pair of SOS constraints of type 1.

import gurobipy as gp
from gurobipy import GRB

try:
    # Create a new model

    model = gp.Model("sos")

    # Create variables

    x0 = model.addVar(ub=1.0, name="x0")
    x1 = model.addVar(ub=1.0, name="x1")
    x2 = model.addVar(ub=2.0, name="x2")

    # Set objective
    model.setObjective(2 * x0 + x1 + x2, GRB.MAXIMIZE)

    # Add first SOS: x0 = 0 or x1 = 0
    model.addSOS(GRB.SOS_TYPE1, [x0, x1], [1, 2])

    # Add second SOS: x0 = 0 or x2 = 0
    model.addSOS(GRB.SOS_TYPE1, [x0, x2], [1, 2])

    model.optimize()
```

(continues on next page)

(continued from previous page)

```
    for v in model.getVars():
        print(f"{v.VarName} {v.X:g}")

    print(f"Obj: {model.ObjVal:g}")

except gp.GurobiError as e:
    print(f"Error code {e.errno}: {e}")

except AttributeError:
    print("Encountered an attribute error")
```

sudoku.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Sudoku example.

# The Sudoku board is a 9x9 grid, which is further divided into a 3x3 grid
# of 3x3 grids.  Each cell in the grid must take a value from 0 to 9.
# No two grid cells in the same row, column, or 3x3 subgrid may take the
# same value.
#
# In the MIP formulation, binary variables x[i,j,v] indicate whether
# cell <i,j> takes value 'v'.  The constraints are as follows:
#   1. Each cell must take exactly one value (sum_v x[i,j,v] = 1)
#   2. Each value is used exactly once per row (sum_i x[i,j,v] = 1)
#   3. Each value is used exactly once per column (sum_j x[i,j,v] = 1)
#   4. Each value is used exactly once per 3x3 subgrid (sum_grid x[i,j,v] = 1)
#
# Input datasets for this example can be found in examples/data/sudoku*.

import sys
import math
import gurobipy as gp
from gurobipy import GRB

if len(sys.argv) < 2:
    print("Usage: sudoku.py filename")
    sys.exit(0)

with open(sys.argv[1]) as f:
    grid = f.read().split()

n = len(grid[0])
s = int(math.sqrt(n))
```

(continues on next page)

(continued from previous page)

```
# Create our 3-D array of model variables

model = gp.Model("sudoku")

vars = model.addVars(n, n, n, vtype=GRB.BINARY, name="G")


# Fix variables associated with cells whose values are pre-specified

for i in range(n):
    for j in range(n):
        if grid[i][j] != ".":
            v = int(grid[i][j]) - 1
            vars[i, j, v].LB = 1

# Each cell must take one value

model.addConstrs(
    (vars.sum(i, j, "*") == 1 for i in range(n) for j in range(n)), name="V"
)

# Each value appears once per row

model.addConstrs(
    (vars.sum(i, "*", v) == 1 for i in range(n) for v in range(n)), name="R"
)

# Each value appears once per column

model.addConstrs(
    (vars.sum("*", j, v) == 1 for j in range(n) for v in range(n)), name="C"
)


# Each value appears once per subgrid

model.addConstrs(
    (
        gp.quicksum(
            vars[i, j, v]
            for i in range(i0 * s, (i0 + 1) * s)
            for j in range(j0 * s, (j0 + 1) * s)
        )
        == 1
        for v in range(n)
        for i0 in range(s)
        for j0 in range(s)
    ),
    name="Sub",
)

model.optimize()
```

(continues on next page)

(continued from previous page)

```
model.write("sudoku.lp")

print("")
print("Solution:")
print("")

# Retrieve optimization result

solution = model.getAttr("X", vars)

for i in range(n):
    sol = ""
    for j in range(n):
        for v in range(n):
            if solution[i, j, v] > 0.5:
                sol += str(v + 1)
    print(sol)
```

tsp.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Solve a traveling salesman problem on a randomly generated set of points
# using lazy constraints.  The base MIP model only includes 'degree-2'
# constraints, requiring each node to have exactly two incident edges.
# Solutions to this model may contain subtours - tours that don't visit every
# city.  The lazy constraint callback adds new constraints to cut them off.

import sys
import logging
import math
import random
from collections import defaultdict
from itertools import combinations

import gurobipy as gp
from gurobipy import GRB


def shortest_subtour(edges):
    """Given a list of edges, return the shortest subtour (as a list of nodes)
    found by following those edges. It is assumed there is exactly one 'in'
    edge and one 'out' edge for every node represented in the edge list."""

    # Create a mapping from each node to its neighbours
    node_neighbors = defaultdict(list)
    for i, j in edges:
```

(continues on next page)

(continued from previous page)

```
        node_neighbors[i].append(j)
    assert all(len(neighbors) == 2 for neighbors in node_neighbors.values())

    # Follow edges to find cycles. Each time a new cycle is found, keep track
    # of the shortest cycle found so far and restart from an unvisited node.
    unvisited = set(node_neighbors)
    shortest = None
    while unvisited:
        cycle = []
        neighbors = list(unvisited)
        while neighbors:
            current = neighbors.pop()
            cycle.append(current)
            unvisited.remove(current)
            neighbors = [j for j in node_neighbors[current] if j in unvisited]
        if shortest is None or len(cycle) < len(shortest):
            shortest = cycle

    assert shortest is not None
    return shortest


class TSPCallback:
    """Callback class implementing lazy constraints for the TSP.  At MIPSOL
    callbacks, solutions are checked for subtours and subtour elimination
    constraints are added if needed."""

    def __init__(self, nodes, x):
        self.nodes = nodes
        self.x = x

    def __call__(self, model, where):
        """Callback entry point: call lazy constraints routine when new
        solutions are found. Stop the optimization if there is an exception in
        user code."""
        if where == GRB.Callback.MIPSOL:
            try:
                self.eliminate_subtours(model)
            except Exception:
                logging.exception("Exception occurred in MIPSOL callback")
                model.terminate()

    def eliminate_subtours(self, model):
        """Extract the current solution, check for subtours, and formulate lazy
        constraints to cut off the current solution if subtours are found.
        Assumes we are at MIPSOL."""
        values = model.cbGetSolution(self.x)
        edges = [(i, j) for (i, j), v in values.items() if v > 0.5]
        tour = shortest_subtour(edges)
        if len(tour) < len(self.nodes):
            # add subtour elimination constraint for every pair of cities in tour
            model.cbLazy(
```

(continues on next page)

(continued from previous page)

```
                gp.quicksum(self.x[i, j] for i, j in combinations(tour, 2))
                <= len(tour) - 1
            )


def solve_tsp(nodes, distances):
    """
    Solve a dense symmetric TSP using the following base formulation:

    min  sum_ij d_ij x_ij
    s.t. sum_j x_ij == 2   forall i in V
         x_ij binary       forall (i,j) in E

    and subtours eliminated using lazy constraints.
    """

    with gp.Env() as env, gp.Model(env=env) as m:
        # Create variables, and add symmetric keys to the resulting dictionary
        # 'x', such that (i, j) and (j, i) refer to the same variable.
        x = m.addVars(distances.keys(), obj=distances, vtype=GRB.BINARY, name="e")
        x.update({(j, i): v for (i, j), v in x.items()})

        # Create degree 2 constraints
        for i in nodes:
            m.addConstr(gp.quicksum(x[i, j] for j in nodes if i != j) == 2)

        # Optimize model using lazy constraints to eliminate subtours
        m.Params.LazyConstraints = 1
        cb = TSPCallback(nodes, x)
        m.optimize(cb)

        # Extract the solution as a tour
        edges = [(i, j) for (i, j), v in x.items() if v.X > 0.5]
        tour = shortest_subtour(edges)
        assert set(tour) == set(nodes)

        return tour, m.ObjVal


if __name__ == "__main__":
    # Parse arguments
    if len(sys.argv) < 2:
        print("Usage: tsp.py npoints <seed>")
        sys.exit(0)
    npoints = int(sys.argv[1])
    seed = int(sys.argv[2]) if len(sys.argv) > 2 else 1

    # Create n random points in 2D
    random.seed(seed)
    nodes = list(range(npoints))
    points = [(random.randint(0, 100), random.randint(0, 100)) for i in nodes]
```

(continues on next page)

(continued from previous page)

```
    # Dictionary of Euclidean distance between each pair of points
    distances = {
        (i, j): math.sqrt(sum((points[i][k] - points[j][k]) ** 2 for k in range(2)))
        for i, j in combinations(nodes, 2)
    }

    tour, cost = solve_tsp(nodes, distances)

    print("")
    print(f"Optimal tour: {tour}")
    print(f"Optimal cost: {cost:g}")
    print("")
```

tune.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

#  This example reads a model from a file and tunes it.
#  It then writes the best parameter settings to a file
#  and solves the model using these parameters.

import sys
import gurobipy as gp

if len(sys.argv) < 2:
    print("Usage: tune.py filename")
    sys.exit(0)

# Read the model
model = gp.read(sys.argv[1])

# Set a time limit for the model
model.Params.TimeLimit = 5

# Set a time limit for the whole tuning run
# Note that both time limits are chosen to have a quick demonstration.
# In general, a total tune time limit should be set such that the
# tuning tool can test several hundreds of parameter setting
model.Params.TuneTimeLimit = 60

# Set the TuneResults parameter to 2
#
# The first parameter setting is the result for the first solved
# setting. The second entry the parameter setting of the best parameter
# setting.
model.Params.TuneResults = 2

# Tune the model
```

(continues on next page)

(continued from previous page)

```
model.tune()

if model.TuneResultCount >= 2:
    # Load the best tuned parameters into the model
    #
    # Note, the first parameter setting is associated to the first solved
    # setting and the second parameter setting to best tune result.
    model.getTuneResult(1)

    # Write tuned parameters to a file
    model.write("tune.prm")

    # Solve the model using the tuned parameters
    model.optimize()
```

workforce1.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Assign workers to shifts; each worker may or may not be available on a
# particular day. If the problem cannot be solved, use IIS to find a set of
# conflicting constraints. Note that there may be additional conflicts besides
# what is reported via IIS.

import gurobipy as gp
from gurobipy import GRB
import sys

# Number of workers required for each shift
shifts, shiftRequirements = gp.multidict(
    {
        "Mon1": 3,
        "Tue2": 2,
        "Wed3": 4,
        "Thu4": 4,
        "Fri5": 5,
        "Sat6": 6,
        "Sun7": 5,
        "Mon8": 2,
        "Tue9": 2,
        "Wed10": 3,
        "Thu11": 4,
        "Fri12": 6,
        "Sat13": 7,
        "Sun14": 5,
    }
)
```

(continues on next page)

(continued from previous page)

```
# Amount each worker is paid to work one shift
workers, pay = gp.multidict(
    {
        "Amy": 10,
        "Bob": 12,
        "Cathy": 10,
        "Dan": 8,
        "Ed": 8,
        "Fred": 9,
        "Gu": 11,
    }
)

# Worker availability
availability = gp.tuplelist(
    [
        ("Amy", "Tue2"),
        ("Amy", "Wed3"),
        ("Amy", "Fri5"),
        ("Amy", "Sun7"),
        ("Amy", "Tue9"),
        ("Amy", "Wed10"),
        ("Amy", "Thu11"),
        ("Amy", "Fri12"),
        ("Amy", "Sat13"),
        ("Amy", "Sun14"),
        ("Bob", "Mon1"),
        ("Bob", "Tue2"),
        ("Bob", "Fri5"),
        ("Bob", "Sat6"),
        ("Bob", "Mon8"),
        ("Bob", "Thu11"),
        ("Bob", "Sat13"),
        ("Cathy", "Wed3"),
        ("Cathy", "Thu4"),
        ("Cathy", "Fri5"),
        ("Cathy", "Sun7"),
        ("Cathy", "Mon8"),
        ("Cathy", "Tue9"),
        ("Cathy", "Wed10"),
        ("Cathy", "Thu11"),
        ("Cathy", "Fri12"),
        ("Cathy", "Sat13"),
        ("Cathy", "Sun14"),
        ("Dan", "Tue2"),
        ("Dan", "Wed3"),
        ("Dan", "Fri5"),
        ("Dan", "Sat6"),
        ("Dan", "Mon8"),
        ("Dan", "Tue9"),
        ("Dan", "Wed10"),
        ("Dan", "Thu11"),
```

(continues on next page)

(continued from previous page)

```
        ("Dan", "Fri12"),
        ("Dan", "Sat13"),
        ("Dan", "Sun14"),
        ("Ed", "Mon1"),
        ("Ed", "Tue2"),
        ("Ed", "Wed3"),
        ("Ed", "Thu4"),
        ("Ed", "Fri5"),
        ("Ed", "Sun7"),
        ("Ed", "Mon8"),
        ("Ed", "Tue9"),
        ("Ed", "Thu11"),
        ("Ed", "Sat13"),
        ("Ed", "Sun14"),
        ("Fred", "Mon1"),
        ("Fred", "Tue2"),
        ("Fred", "Wed3"),
        ("Fred", "Sat6"),
        ("Fred", "Mon8"),
        ("Fred", "Tue9"),
        ("Fred", "Fri12"),
        ("Fred", "Sat13"),
        ("Fred", "Sun14"),
        ("Gu", "Mon1"),
        ("Gu", "Tue2"),
        ("Gu", "Wed3"),
        ("Gu", "Fri5"),
        ("Gu", "Sat6"),
        ("Gu", "Sun7"),
        ("Gu", "Mon8"),
        ("Gu", "Tue9"),
        ("Gu", "Wed10"),
        ("Gu", "Thu11"),
        ("Gu", "Fri12"),
        ("Gu", "Sat13"),
        ("Gu", "Sun14"),
    ]
)

# Model
m = gp.Model("assignment")

# Assignment variables: x[w,s] == 1 if worker w is assigned to shift s.
# Since an assignment model always produces integer solutions, we use
# continuous variables and solve as an LP.
x = m.addVars(availability, ub=1, name="x")

# The objective is to minimize the total pay costs
m.setObjective(gp.quicksum(pay[w] * x[w, s] for w, s in availability), GRB.MINIMIZE)

# Constraints: assign exactly shiftRequirements[s] workers to each shift s
reqCts = m.addConstrs((x.sum("*", s) == shiftRequirements[s] for s in shifts), "_")
```

(continues on next page)

(continued from previous page)

```
# Using Python looping constructs, the preceding statement would be...
#
# reqCts = {}
# for s in shifts:
#   reqCts[s] = m.addConstr(
#         gp.quicksum(x[w,s] for w,s in availability.select('*', s)) ==
#         shiftRequirements[s], s)

# Save model
m.write("workforce1.lp")

# Optimize
m.optimize()
status = m.Status
if status == GRB.UNBOUNDED:
    print("The model cannot be solved because it is unbounded")
    sys.exit(0)
if status == GRB.OPTIMAL:
    print(f"The optimal objective is {m.ObjVal:g}")
    sys.exit(0)
if status != GRB.INF_OR_UNBD and status != GRB.INFEASIBLE:
    print(f"Optimization was stopped with status {status}")
    sys.exit(0)

# do IIS
print("The model is infeasible; computing IIS")
m.computeIIS()
if m.IISMinimal:
    print("IIS is minimal\n")
else:
    print("IIS is not minimal\n")
print("\nThe following constraint(s) cannot be satisfied:")
for c in m.getConstrs():
    if c.IISConstr:
        print(c.ConstrName)
```

workforce2.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Assign workers to shifts; each worker may or may not be available on a
# particular day. If the problem cannot be solved, use IIS iteratively to
# find all conflicting constraints.

import gurobipy as gp
from gurobipy import GRB
import sys
```

(continues on next page)

(continued from previous page)

```
# Number of workers required for each shift
shifts, shiftRequirements = gp.multidict(
    {
        "Mon1": 3,
        "Tue2": 2,
        "Wed3": 4,
        "Thu4": 4,
        "Fri5": 5,
        "Sat6": 6,
        "Sun7": 5,
        "Mon8": 2,
        "Tue9": 2,
        "Wed10": 3,
        "Thu11": 4,
        "Fri12": 6,
        "Sat13": 7,
        "Sun14": 5,
    }
)

# Amount each worker is paid to work one shift
workers, pay = gp.multidict(
    {
        "Amy": 10,
        "Bob": 12,
        "Cathy": 10,
        "Dan": 8,
        "Ed": 8,
        "Fred": 9,
        "Gu": 11,
    }
)

# Worker availability
availability = gp.tuplelist(
    [
        ("Amy", "Tue2"),
        ("Amy", "Wed3"),
        ("Amy", "Fri5"),
        ("Amy", "Sun7"),
        ("Amy", "Tue9"),
        ("Amy", "Wed10"),
        ("Amy", "Thu11"),
        ("Amy", "Fri12"),
        ("Amy", "Sat13"),
        ("Amy", "Sun14"),
        ("Bob", "Mon1"),
        ("Bob", "Tue2"),
        ("Bob", "Fri5"),
        ("Bob", "Sat6"),
        ("Bob", "Mon8"),
```

(continues on next page)

(continued from previous page)

```
        ("Bob", "Thu11"),
        ("Bob", "Sat13"),
        ("Cathy", "Wed3"),
        ("Cathy", "Thu4"),
        ("Cathy", "Fri5"),
        ("Cathy", "Sun7"),
        ("Cathy", "Mon8"),
        ("Cathy", "Tue9"),
        ("Cathy", "Wed10"),
        ("Cathy", "Thu11"),
        ("Cathy", "Fri12"),
        ("Cathy", "Sat13"),
        ("Cathy", "Sun14"),
        ("Dan", "Tue2"),
        ("Dan", "Wed3"),
        ("Dan", "Fri5"),
        ("Dan", "Sat6"),
        ("Dan", "Mon8"),
        ("Dan", "Tue9"),
        ("Dan", "Wed10"),
        ("Dan", "Thu11"),
        ("Dan", "Fri12"),
        ("Dan", "Sat13"),
        ("Dan", "Sun14"),
        ("Ed", "Mon1"),
        ("Ed", "Tue2"),
        ("Ed", "Wed3"),
        ("Ed", "Thu4"),
        ("Ed", "Fri5"),
        ("Ed", "Sun7"),
        ("Ed", "Mon8"),
        ("Ed", "Tue9"),
        ("Ed", "Thu11"),
        ("Ed", "Sat13"),
        ("Ed", "Sun14"),
        ("Fred", "Mon1"),
        ("Fred", "Tue2"),
        ("Fred", "Wed3"),
        ("Fred", "Sat6"),
        ("Fred", "Mon8"),
        ("Fred", "Tue9"),
        ("Fred", "Fri12"),
        ("Fred", "Sat13"),
        ("Fred", "Sun14"),
        ("Gu", "Mon1"),
        ("Gu", "Tue2"),
        ("Gu", "Wed3"),
        ("Gu", "Fri5"),
        ("Gu", "Sat6"),
        ("Gu", "Sun7"),
        ("Gu", "Mon8"),
        ("Gu", "Tue9"),
```

(continues on next page)

(continued from previous page)

```
        ("Gu", "Wed10"),
        ("Gu", "Thu11"),
        ("Gu", "Fri12"),
        ("Gu", "Sat13"),
        ("Gu", "Sun14"),
    ]
)

# Model
m = gp.Model("assignment")

# Assignment variables: x[w,s] == 1 if worker w is assigned to shift s.
# Since an assignment model always produces integer solutions, we use
# continuous variables and solve as an LP.
x = m.addVars(availability, ub=1, name="x")

# The objective is to minimize the total pay costs
m.setObjective(gp.quicksum(pay[w] * x[w, s] for w, s in availability), GRB.MINIMIZE)

# Constraint: assign exactly shiftRequirements[s] workers to each shift s
reqCts = m.addConstrs((x.sum("*", s) == shiftRequirements[s] for s in shifts), "_")

# Optimize
m.optimize()
status = m.Status
if status == GRB.UNBOUNDED:
    print("The model cannot be solved because it is unbounded")
    sys.exit(0)
if status == GRB.OPTIMAL:
    print(f"The optimal objective is {m.ObjVal:g}")
    sys.exit(0)
if status != GRB.INF_OR_UNBD and status != GRB.INFEASIBLE:
    print(f"Optimization was stopped with status {status}")
    sys.exit(0)

# do IIS
print("The model is infeasible; computing IIS")
removed = []

# Loop until we reduce to a model that can be solved
while True:
    m.computeIIS()
    print("\nThe following constraint cannot be satisfied:")
    for c in m.getConstrs():
        if c.IISConstr:
            print(c.ConstrName)
            # Remove a single constraint from the model
            removed.append(str(c.ConstrName))
            m.remove(c)
            break
    print("")
```

(continues on next page)

(continued from previous page)

```
    m.optimize()
    status = m.Status

    if status == GRB.UNBOUNDED:
        print("The model cannot be solved because it is unbounded")
        sys.exit(0)
    if status == GRB.OPTIMAL:
        break
    if status != GRB.INF_OR_UNBD and status != GRB.INFEASIBLE:
        print(f"Optimization was stopped with status {status}")
        sys.exit(0)

print("\nThe following constraints were removed to get a feasible LP:")
print(removed)
```

workforce3.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Assign workers to shifts; each worker may or may not be available on a
# particular day. If the problem cannot be solved, relax the model
# to determine which constraints cannot be satisfied, and how much
# they need to be relaxed.

import gurobipy as gp
from gurobipy import GRB
import sys

# Number of workers required for each shift
shifts, shiftRequirements = gp.multidict(
    {
        "Mon1": 3,
        "Tue2": 2,
        "Wed3": 4,
        "Thu4": 4,
        "Fri5": 5,
        "Sat6": 6,
        "Sun7": 5,
        "Mon8": 2,
        "Tue9": 2,
        "Wed10": 3,
        "Thu11": 4,
        "Fri12": 6,
        "Sat13": 7,
        "Sun14": 5,
    }
)
```

(continues on next page)

(continued from previous page)

```
# Amount each worker is paid to work one shift
workers, pay = gp.multidict(
    {"Amy": 10, "Bob": 12, "Cathy": 10, "Dan": 8, "Ed": 8, "Fred": 9, "Gu": 11}
)

# Worker availability
availability = gp.tuplelist(
    [
        ("Amy", "Tue2"),
        ("Amy", "Wed3"),
        ("Amy", "Fri5"),
        ("Amy", "Sun7"),
        ("Amy", "Tue9"),
        ("Amy", "Wed10"),
        ("Amy", "Thu11"),
        ("Amy", "Fri12"),
        ("Amy", "Sat13"),
        ("Amy", "Sun14"),
        ("Bob", "Mon1"),
        ("Bob", "Tue2"),
        ("Bob", "Fri5"),
        ("Bob", "Sat6"),
        ("Bob", "Mon8"),
        ("Bob", "Thu11"),
        ("Bob", "Sat13"),
        ("Cathy", "Wed3"),
        ("Cathy", "Thu4"),
        ("Cathy", "Fri5"),
        ("Cathy", "Sun7"),
        ("Cathy", "Mon8"),
        ("Cathy", "Tue9"),
        ("Cathy", "Wed10"),
        ("Cathy", "Thu11"),
        ("Cathy", "Fri12"),
        ("Cathy", "Sat13"),
        ("Cathy", "Sun14"),
        ("Dan", "Tue2"),
        ("Dan", "Wed3"),
        ("Dan", "Fri5"),
        ("Dan", "Sat6"),
        ("Dan", "Mon8"),
        ("Dan", "Tue9"),
        ("Dan", "Wed10"),
        ("Dan", "Thu11"),
        ("Dan", "Fri12"),
        ("Dan", "Sat13"),
        ("Dan", "Sun14"),
        ("Ed", "Mon1"),
        ("Ed", "Tue2"),
        ("Ed", "Wed3"),
        ("Ed", "Thu4"),
        ("Ed", "Fri5"),
```

(continues on next page)

(continued from previous page)

```
        ("Ed", "Sun7"),
        ("Ed", "Mon8"),
        ("Ed", "Tue9"),
        ("Ed", "Thu11"),
        ("Ed", "Sat13"),
        ("Ed", "Sun14"),
        ("Fred", "Mon1"),
        ("Fred", "Tue2"),
        ("Fred", "Wed3"),
        ("Fred", "Sat6"),
        ("Fred", "Mon8"),
        ("Fred", "Tue9"),
        ("Fred", "Fri12"),
        ("Fred", "Sat13"),
        ("Fred", "Sun14"),
        ("Gu", "Mon1"),
        ("Gu", "Tue2"),
        ("Gu", "Wed3"),
        ("Gu", "Fri5"),
        ("Gu", "Sat6"),
        ("Gu", "Sun7"),
        ("Gu", "Mon8"),
        ("Gu", "Tue9"),
        ("Gu", "Wed10"),
        ("Gu", "Thu11"),
        ("Gu", "Fri12"),
        ("Gu", "Sat13"),
        ("Gu", "Sun14"),
    ]
)

# Model
m = gp.Model("assignment")

# Assignment variables: x[w,s] == 1 if worker w is assigned to shift s.
# Since an assignment model always produces integer solutions, we use
# continuous variables and solve as an LP.
x = m.addVars(availability, ub=1, name="x")

# The objective is to minimize the total pay costs
m.setObjective(gp.quicksum(pay[w] * x[w, s] for w, s in availability), GRB.MINIMIZE)

# Constraint: assign exactly shiftRequirements[s] workers to each shift s
reqCts = m.addConstrs((x.sum("*", s) == shiftRequirements[s] for s in shifts), "_")

# Optimize
m.optimize()
status = m.Status
if status == GRB.UNBOUNDED:
    print("The model cannot be solved because it is unbounded")
    sys.exit(0)
if status == GRB.OPTIMAL:
```

(continues on next page)

(continued from previous page)

```
    print(f"The optimal objective is {m.ObjVal:g}")
    sys.exit(0)
if status != GRB.INF_OR_UNBD and status != GRB.INFEASIBLE:
    print(f"Optimization was stopped with status {status}")
    sys.exit(0)

# Relax the constraints to make the model feasible
print("The model is infeasible; relaxing the constraints")
orignumvars = m.NumVars
m.feasRelaxS(0, False, False, True)
m.optimize()
status = m.Status
if status in (GRB.INF_OR_UNBD, GRB.INFEASIBLE, GRB.UNBOUNDED):
    print("The relaxed model cannot be solved \
           because it is infeasible or unbounded")
    sys.exit(1)

if status != GRB.OPTIMAL:
    print(f"Optimization was stopped with status {status}")
    sys.exit(1)

print("\nSlack values:")
slacks = m.getVars()[orignumvars:]
for sv in slacks:
    if sv.X > 1e-6:
        print(f"{sv.VarName} = {sv.X:g}")
```

workforce4.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Assign workers to shifts; each worker may or may not be available on a
# particular day. We use lexicographic optimization to solve the model:
# first, we minimize the linear sum of the slacks. Then, we constrain
# the sum of the slacks, and we minimize a quadratic objective that
# tries to balance the workload among the workers.

import gurobipy as gp
from gurobipy import GRB
import sys

# Number of workers required for each shift
shifts, shiftRequirements = gp.multidict(
    {
        "Mon1": 3,
        "Tue2": 2,
        "Wed3": 4,
        "Thu4": 4,
```

(continues on next page)

(continued from previous page)

```
        "Fri5": 5,
        "Sat6": 6,
        "Sun7": 5,
        "Mon8": 2,
        "Tue9": 2,
        "Wed10": 3,
        "Thu11": 4,
        "Fri12": 6,
        "Sat13": 7,
        "Sun14": 5,
    }
)

# Amount each worker is paid to work one shift
workers, pay = gp.multidict(
    {
        "Amy": 10,
        "Bob": 12,
        "Cathy": 10,
        "Dan": 8,
        "Ed": 8,
        "Fred": 9,
        "Gu": 11,
    }
)

# Worker availability
availability = gp.tuplelist(
    [
        ("Amy", "Tue2"),
        ("Amy", "Wed3"),
        ("Amy", "Fri5"),
        ("Amy", "Sun7"),
        ("Amy", "Tue9"),
        ("Amy", "Wed10"),
        ("Amy", "Thu11"),
        ("Amy", "Fri12"),
        ("Amy", "Sat13"),
        ("Amy", "Sun14"),
        ("Bob", "Mon1"),
        ("Bob", "Tue2"),
        ("Bob", "Fri5"),
        ("Bob", "Sat6"),
        ("Bob", "Mon8"),
        ("Bob", "Thu11"),
        ("Bob", "Sat13"),
        ("Cathy", "Wed3"),
        ("Cathy", "Thu4"),
        ("Cathy", "Fri5"),
        ("Cathy", "Sun7"),
        ("Cathy", "Mon8"),
        ("Cathy", "Tue9"),
```

(continues on next page)

(continued from previous page)

```
        ("Cathy", "Wed10"),
        ("Cathy", "Thu11"),
        ("Cathy", "Fri12"),
        ("Cathy", "Sat13"),
        ("Cathy", "Sun14"),
        ("Dan", "Tue2"),
        ("Dan", "Wed3"),
        ("Dan", "Fri5"),
        ("Dan", "Sat6"),
        ("Dan", "Mon8"),
        ("Dan", "Tue9"),
        ("Dan", "Wed10"),
        ("Dan", "Thu11"),
        ("Dan", "Fri12"),
        ("Dan", "Sat13"),
        ("Dan", "Sun14"),
        ("Ed", "Mon1"),
        ("Ed", "Tue2"),
        ("Ed", "Wed3"),
        ("Ed", "Thu4"),
        ("Ed", "Fri5"),
        ("Ed", "Sun7"),
        ("Ed", "Mon8"),
        ("Ed", "Tue9"),
        ("Ed", "Thu11"),
        ("Ed", "Sat13"),
        ("Ed", "Sun14"),
        ("Fred", "Mon1"),
        ("Fred", "Tue2"),
        ("Fred", "Wed3"),
        ("Fred", "Sat6"),
        ("Fred", "Mon8"),
        ("Fred", "Tue9"),
        ("Fred", "Fri12"),
        ("Fred", "Sat13"),
        ("Fred", "Sun14"),
        ("Gu", "Mon1"),
        ("Gu", "Tue2"),
        ("Gu", "Wed3"),
        ("Gu", "Fri5"),
        ("Gu", "Sat6"),
        ("Gu", "Sun7"),
        ("Gu", "Mon8"),
        ("Gu", "Tue9"),
        ("Gu", "Wed10"),
        ("Gu", "Thu11"),
        ("Gu", "Fri12"),
        ("Gu", "Sat13"),
        ("Gu", "Sun14"),
    ]
)
```

(continues on next page)

(continued from previous page)

```
# Model
m = gp.Model("assignment")

# Assignment variables: x[w,s] == 1 if worker w is assigned to shift s.
# This is no longer a pure assignment model, so we must use binary variables.
x = m.addVars(availability, vtype=GRB.BINARY, name="x")

# Slack variables for each shift constraint so that the shifts can
# be satisfied
slacks = m.addVars(shifts, name="Slack")

# Variable to represent the total slack
totSlack = m.addVar(name="totSlack")

# Variables to count the total shifts worked by each worker
totShifts = m.addVars(workers, name="TotShifts")

# Constraint: assign exactly shiftRequirements[s] workers to each shift s,
# plus the slack
reqCts = m.addConstrs(
    (slacks[s] + x.sum("*", s) == shiftRequirements[s] for s in shifts), "_"
)

# Constraint: set totSlack equal to the total slack
m.addConstr(totSlack == slacks.sum(), "totSlack")

# Constraint: compute the total number of shifts for each worker
m.addConstrs((totShifts[w] == x.sum(w, "*") for w in workers), "totShifts")

# Objective: minimize the total slack
# Note that this replaces the previous 'pay' objective coefficients
m.setObjective(totSlack)


# Optimize
def solveAndPrint():
    m.optimize()
    status = m.status
    if status in (GRB.INF_OR_UNBD, GRB.INFEASIBLE, GRB.UNBOUNDED):
        print("The model cannot be solved because it is infeasible or \
               unbounded")
        sys.exit(1)

    if status != GRB.OPTIMAL:
        print(f"Optimization was stopped with status {status}")
        sys.exit(0)

    # Print total slack and the number of shifts worked for each worker
    print("")
    print(f"Total slack required: {totSlack.X:g}")
    for w in workers:
        print(f"{w} worked {totShifts[w].X:g} shifts")
```

(continues on next page)

(continued from previous page)

```
    print("")


solveAndPrint()

# Constrain the slack by setting its upper and lower bounds
totSlack.UB = totSlack.X
totSlack.LB = totSlack.X

# Variable to count the average number of shifts worked
avgShifts = m.addVar(name="avgShifts")

# Variables to count the difference from average for each worker;
# note that these variables can take negative values.
diffShifts = m.addVars(workers, lb=-GRB.INFINITY, name="Diff")

# Constraint: compute the average number of shifts worked
m.addConstr(len(workers) * avgShifts == totShifts.sum(), "avgShifts")

# Constraint: compute the difference from the average number of shifts
m.addConstrs((diffShifts[w] == totShifts[w] - avgShifts for w in workers), "Diff")

# Objective: minimize the sum of the square of the difference from the
# average number of shifts worked
m.setObjective(gp.quicksum(diffShifts[w] * diffShifts[w] for w in workers))

# Optimize
solveAndPrint()
```

workforce5.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Assign workers to shifts; each worker may or may not be available on a
# particular day. We use multi-objective optimization to solve the model.
# The highest-priority objective minimizes the sum of the slacks
# (i.e., the total number of uncovered shifts). The secondary objective
# minimizes the difference between the maximum and minimum number of
# shifts worked among all workers.  The second optimization is allowed
# to degrade the first objective by up to the smaller value of 10% and 2 */

import gurobipy as gp
from gurobipy import GRB
import sys

# Sample data
# Sets of days and workers
Shifts = [
```

(continues on next page)

(continued from previous page)

```
    "Mon1",
    "Tue2",
    "Wed3",
    "Thu4",
    "Fri5",
    "Sat6",
    "Sun7",
    "Mon8",
    "Tue9",
    "Wed10",
    "Thu11",
    "Fri12",
    "Sat13",
    "Sun14",
]

Workers = ["Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu", "Tobi"]

# Number of workers required for each shift
S = [3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5]
shiftRequirements = {s: S[i] for i, s in enumerate(Shifts)}

# Worker availability: 0 if the worker is unavailable for a shift
A = [
    [0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1],
    [1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0],
    [0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1],
    [0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1],
    [1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1],
    [1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1],
    [0, 1, 1, 1, 0, 1, 1, 0, 1, 1, 1, 0, 1, 1],
    [1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1],
]

availability = {
    (w, s): A[j][i] for i, s in enumerate(Shifts) for j, w in enumerate(Workers)
}

try:
    # Create model with a context manager. Upon exit from this block,
    # model.dispose is called automatically, and memory consumed by the model
    # is released.
    #
    # The model is created in the default environment, which will be created
    # automatically upon model construction.  For safe release of resources
    # tied to the default environment, disposeDefaultEnv is called below.
    with gp.Model("workforce5") as model:
        # Initialize assignment decision variables:
        # x[w][s] == 1 if worker w is assigned to shift s.
        # This is no longer a pure assignment model, so we must
        # use binary variables.
        x = model.addVars(
```

(continues on next page)

(continued from previous page)

```
        availability.keys(), ub=availability, vtype=GRB.BINARY, name="x"
    )

    # Slack variables for each shift constraint so that the shifts can
    # be satisfied
    slacks = model.addVars(Shifts, name="Slack")

    # Variable to represent the total slack
    totSlack = model.addVar(name="totSlack")

    # Variables to count the total shifts worked by each worker
    totShifts = model.addVars(Workers, name="TotShifts")

    # Constraint: assign exactly shiftRequirements[s] workers
    # to each shift s, plus the slack
    model.addConstrs(
        (x.sum("*", s) + slacks[s] == shiftRequirements[s] for s in Shifts),
        name="shiftRequirement",
    )

    # Constraint: set totSlack equal to the total slack
    model.addConstr(totSlack == slacks.sum(), name="totSlack")

    # Constraint: compute the total number of shifts for each worker
    model.addConstrs(
        (totShifts[w] == x.sum(w, "*") for w in Workers), name="totShifts"
    )

    # Constraint: set minShift/maxShift variable to less/greater than the
    # number of shifts among all workers
    minShift = model.addVar(name="minShift")
    maxShift = model.addVar(name="maxShift")
    model.addGenConstrMin(minShift, totShifts.values(), name="minShift")
    model.addGenConstrMax(maxShift, totShifts.values(), name="maxShift")

    # Set global sense for ALL objectives
    model.ModelSense = GRB.MINIMIZE

    # Set up primary objective
    model.setObjectiveN(
        totSlack, index=0, priority=2, abstol=2.0, reltol=0.1, name="TotalSlack"
    )

    # Set up secondary objective
    model.setObjectiveN(maxShift - minShift, index=1, priority=1, name="Fairness")

    # Save problem
    model.write("workforce5.lp")

    # Optimize
    model.optimize()
```

(continues on next page)

(continued from previous page)

```
        status = model.Status

        if status in (GRB.INF_OR_UNBD, GRB.INFEASIBLE, GRB.UNBOUNDED):
            print("Model cannot be solved because it is infeasible or unbounded")
            sys.exit(0)

        if status != GRB.OPTIMAL:
            print(f"Optimization was stopped with status {status}")
            sys.exit(0)

        # Print total slack and the number of shifts worked for each worker
        print("")
        print(f"Total slack required: {totSlack.X}")
        for w in Workers:
            print(f"{w} worked {totShifts[w].X} shifts")
        print("")

except gp.GurobiError as e:
    print(f"Error code {e.errno}: {e}")
except AttributeError as e:
    print(f"Encountered an attribute error: {e}")
finally:
    # Safely release memory and/or server side resources consumed by
    # the default environment.
    gp.disposeDefaultEnv()
```

workforce_batchmode.py

```
#!/usr/bin/env python3

# Copyright 2026, Gurobi Optimization, LLC

# Assign workers to shifts; each worker may or may not be available on a
# particular day.  The optimization problem is solved as a batch, and
# the schedule constructed only from the meta data available in the solution
# JSON.
#
# NOTE: You'll need a license file configured to use a Cluster Manager
#       for this example to run.

import time
import json
import sys
import gurobipy as gp
from gurobipy import GRB
from collections import OrderedDict, defaultdict

# For later pretty printing names for the shifts
shiftname = OrderedDict(
    [
```

(continues on next page)

(continued from previous page)

```
        ("Mon1", "Monday 8:00"),
        ("Mon8", "Monday 14:00"),
        ("Tue2", "Tuesday 8:00"),
        ("Tue9", "Tuesday 14:00"),
        ("Wed3", "Wednesday 8:00"),
        ("Wed10", "Wednesday 14:00"),
        ("Thu4", "Thursday 8:00"),
        ("Thu11", "Thursday 14:00"),
        ("Fri5", "Friday 8:00"),
        ("Fri12", "Friday 14:00"),
        ("Sat6", "Saturday 8:00"),
        ("Sat13", "Saturday 14:00"),
        ("Sun7", "Sunday 9:00"),
        ("Sun14", "Sunday 12:00"),
    ]
)


# Build the assignment problem in a Model, and submit it for batch optimization
#
# Required input: A Cluster Manager environment setup for batch optimization
def submit_assigment_problem(env):
    # Number of workers required for each shift
    shifts, shiftRequirements = gp.multidict(
        {
            "Mon1": 3,
            "Tue2": 2,
            "Wed3": 4,
            "Thu4": 4,
            "Fri5": 5,
            "Sat6": 5,
            "Sun7": 3,
            "Mon8": 2,
            "Tue9": 2,
            "Wed10": 3,
            "Thu11": 4,
            "Fri12": 5,
            "Sat13": 7,
            "Sun14": 5,
        }
    )

    # Amount each worker is paid to work one shift
    workers, pay = gp.multidict(
        {
            "Amy": 10,
            "Bob": 12,
            "Cathy": 10,
            "Dan": 8,
            "Ed": 8,
            "Fred": 9,
            "Gu": 11,
```

(continues on next page)

(continued from previous page)

```
        }
    )

    # Worker availability
    availability = gp.tuplelist(
        [
            ("Amy", "Tue2"),
            ("Amy", "Wed3"),
            ("Amy", "Thu4"),
            ("Amy", "Sun7"),
            ("Amy", "Tue9"),
            ("Amy", "Wed10"),
            ("Amy", "Thu11"),
            ("Amy", "Fri12"),
            ("Amy", "Sat13"),
            ("Amy", "Sun14"),
            ("Bob", "Mon1"),
            ("Bob", "Tue2"),
            ("Bob", "Fri5"),
            ("Bob", "Sat6"),
            ("Bob", "Mon8"),
            ("Bob", "Thu11"),
            ("Bob", "Sat13"),
            ("Cathy", "Wed3"),
            ("Cathy", "Thu4"),
            ("Cathy", "Fri5"),
            ("Cathy", "Sun7"),
            ("Cathy", "Mon8"),
            ("Cathy", "Tue9"),
            ("Cathy", "Wed10"),
            ("Cathy", "Thu11"),
            ("Cathy", "Fri12"),
            ("Cathy", "Sat13"),
            ("Cathy", "Sun14"),
            ("Dan", "Tue2"),
            ("Dan", "Thu4"),
            ("Dan", "Fri5"),
            ("Dan", "Sat6"),
            ("Dan", "Mon8"),
            ("Dan", "Tue9"),
            ("Dan", "Wed10"),
            ("Dan", "Thu11"),
            ("Dan", "Fri12"),
            ("Dan", "Sat13"),
            ("Dan", "Sun14"),
            ("Ed", "Mon1"),
            ("Ed", "Tue2"),
            ("Ed", "Wed3"),
            ("Ed", "Thu4"),
            ("Ed", "Fri5"),
            ("Ed", "Sat6"),
            ("Ed", "Mon8"),
```

(continues on next page)

(continued from previous page)

```
            ("Ed", "Tue9"),
            ("Ed", "Thu11"),
            ("Ed", "Sat13"),
            ("Ed", "Sun14"),
            ("Fred", "Mon1"),
            ("Fred", "Tue2"),
            ("Fred", "Wed3"),
            ("Fred", "Sat6"),
            ("Fred", "Mon8"),
            ("Fred", "Tue9"),
            ("Fred", "Fri12"),
            ("Fred", "Sat13"),
            ("Fred", "Sun14"),
            ("Gu", "Mon1"),
            ("Gu", "Tue2"),
            ("Gu", "Wed3"),
            ("Gu", "Fri5"),
            ("Gu", "Sat6"),
            ("Gu", "Sun7"),
            ("Gu", "Mon8"),
            ("Gu", "Tue9"),
            ("Gu", "Wed10"),
            ("Gu", "Thu11"),
            ("Gu", "Fri12"),
            ("Gu", "Sat13"),
            ("Gu", "Sun14"),
        ]
    )

    # Start environment, get model in this environment
    with gp.Model("assignment", env=env) as m:
        # Assignment variables: x[w,s] == 1 if worker w is assigned to shift s.
        # Since an assignment model always produces integer solutions, we use
        # continuous variables and solve as an LP.
        x = m.addVars(availability, ub=1, name="x")

        # Set tags encoding the assignments for later retrieval of the schedule.
        # Each tag is a JSON string of the format
        #   {
        #     "Worker": "<Name of the worker>",
        #     "Shift":  "String representation of the shift"
        #   }
        #
        for k, v in x.items():
            name, timeslot = k
            d = {"Worker": name, "Shift": shiftname[timeslot]}
            v.VTag = json.dumps(d)

        # The objective is to minimize the total pay costs
        m.setObjective(
            gp.quicksum(pay[w] * x[w, s] for w, s in availability), GRB.MINIMIZE
        )
```

(continues on next page)

(continued from previous page)

```
        # Constraints: assign exactly shiftRequirements[s] workers to each shift
        reqCts = m.addConstrs(
            (x.sum("*", s) == shiftRequirements[s] for s in shifts), "_"
        )

        # Submit this model for batch optimization to the cluster manager
        # and return its batch ID for later querying the solution
        batchID = m.optimizeBatch()

    return batchID


# Wait for the final status of the batch.
# Initially the status of a batch is "submitted"; the status will change
# once the batch has been processed (by a compute server).
def waitforfinalbatchstatus(batch):
    # Wait no longer than ten seconds
    maxwaittime = 10

    starttime = time.time()
    while batch.BatchStatus == GRB.BATCH_SUBMITTED:
        # Abort this batch if it is taking too long
        curtime = time.time()
        if curtime - starttime > maxwaittime:
            batch.abort()
            break

        # Wait for one second
        time.sleep(1)

        # Update the resident attribute cache of the Batch object with the
        # latest values from the cluster manager.
        batch.update()


# Print the schedule according to the solution in the given dict
def print_shift_schedule(soldict):
    schedule = defaultdict(list)

    # Iterate over the variables that take a non-zero value (i.e.,
    # an assignment), and collect them per day
    for v in soldict["Vars"]:
        # There is only one VTag, the JSON dict of an assignment we passed
        # in as the VTag
        assignment = json.loads(v["VTag"][0])
        schedule[assignment["Shift"]].append(assignment["Worker"])

    # Print the schedule
    for k in shiftname.values():
        day, time = k.split()
        workers = ", ".join(schedule[k])
```

(continues on next page)

(continued from previous page)

```
        print(f" - {day:10} {time:>5}: {workers}")


if __name__ == "__main__":
    # Create Cluster Manager environment in batch mode.
    env = gp.Env(empty=True)
    env.setParam("CSBatchMode", 1)

    # env is a context manager; upon leaving, Env.dispose() is called
    with env.start():
        # Submit the assignment problem to the cluster manager, get batch ID
        batchID = submit_assigment_problem(env)

        # Create a batch object, wait for batch to complete, query solution JSON
        with gp.Batch(batchID, env) as batch:
            waitforfinalbatchstatus(batch)

            if batch.BatchStatus != GRB.BATCH_COMPLETED:
                print("Batch request couldn't be completed")
                sys.exit(0)

            jsonsol = batch.getJSONSolution()

    # Dump JSON solution string into a dict
    soldict = json.loads(jsonsol)

    # Has the assignment problem been solved as expected?
    if soldict["SolutionInfo"]["Status"] != GRB.OPTIMAL:
        # Shouldn't happen...
        print("Assignment problem could  not be solved to optimality")
        sys.exit(0)

    # Print shift schedule from solution JSON
    print_shift_schedule(soldict)
```

2.1.6 MATLAB Examples

This section includes source code for all of the Gurobi MATLAB examples. The same source code can be found in the `examples/matlab` directory of the Gurobi distribution.

bilinear.m

```
function bilinear
% This example formulates and solves the following simple bilinear model:
%  maximize    x
%  subject to  x + y + z <= 10
%              x * y <= 2         (bilinear inequality)
%              x * z + y * z = 1  (bilinear equality)
%              x, y, z non-negative (x integral in second version)
```

(continues on next page)

(continued from previous page)

```
% Copyright 2026, Gurobi Optimization, LLC

% Linear constraint matrix
m.A = sparse([1, 1, 1]);
m.sense = '<';
m.rhs = 10;

% Variable names
m.varnames = {'x', 'y', 'z'};

% Objective function max 1.0 * x
m.obj = [1; 0; 0];
m.modelsense = 'max';

% Bilinear inequality constraint: x * y <= 2
m.quadcon(1).Qrow = 1;
m.quadcon(1).Qcol = 2;
m.quadcon(1).Qval = 1.0;
m.quadcon(1).q = sparse(3,1);
m.quadcon(1).rhs = 2.0;
m.quadcon(1).sense = '<';
m.quadcon(1).name = 'bilinear0';

% Bilinear equality constraint: x * z + y * z == 1
m.quadcon(2).Qrow = [1, 2];
m.quadcon(2).Qcol = [3, 3];
m.quadcon(2).Qval = [1.0, 1.0];
m.quadcon(2).q = sparse(3,1);
m.quadcon(2).rhs = 1.0;
m.quadcon(2).sense = '=';
m.quadcon(2).name = 'bilinear1';

% Solve bilinear model, display solution.
result = gurobi(m);
disp(result.x);

% Constrain 'x' to be integral and solve again
m.vtype = 'ICC';
result = gurobi(m);
disp(result.x);
end
```

diet.m

```
function diet()
% Copyright 2026, Gurobi Optimization, LLC
%
% Solve the classic diet model

% Nutrition guidelines, based on
% USDA Dietary Guidelines for Americans, 2005
% http://www.health.gov/DietaryGuidelines/dga2005/

ncategories = 4;
categories = {'calories'; 'protein'; 'fat'; 'sodium'};
%             minNutrition maxNutrition
categorynutrition = [ 1800 2200;   % calories
                        91   inf;    % protein
                        0    65;     % fat
                        0    1779];  % sodium

nfoods = 9;
foods = {'hamburger';
         'chicken';
         'hot dog';
         'fries';
         'macaroni';
         'pizza';
         'salad';
         'milk';
         'ice cream'};

foodcost = [2.49;  % hamburger
            2.89;  % chicken
            1.50;  % hot dog
            1.89;  % fries
            2.09;  % macaroni
            1.99;  % pizza
            2.49;  % salad
            0.89;  % milk
            1.59]; % ice cream

                  % calories protein fat sodium
nutritionValues = [ 410      24      26  730;   % hamburger
                    420      32      10  1190;  % chicken
                    560      20      32  1800;  % hot dog
                    380      4       19  270;   % fries
                    320      12      10  930;   % macaroni
                    320      15      12  820;   % pizza
                    320      31      12  1230;  % salad
                    100      8       2.5 125;   % milk
                    330      8       10  180];  % ice cream
nutritionValues = sparse(nutritionValues);
model.modelName = 'diet';
```

(continues on next page)

(continued from previous page)

```
% The variables are layed out as [ buy; nutrition]
model.obj   = [ foodcost;         zeros(ncategories, 1)];
model.lb    = [ zeros(nfoods, 1); categorynutrition(:, 1)];
model.ub    = [  inf(nfoods, 1);  categorynutrition(:, 2)];
model.A     = [ nutritionValues' -speye(ncategories)];
model.rhs   = zeros(ncategories, 1);
model.sense = repmat('=', ncategories, 1);


function printSolution(result)
    if strcmp(result.status, 'OPTIMAL')
        buy       = result.x(1:nfoods);
        nutrition = result.x(nfoods+1:nfoods+ncategories);
        fprintf('\nCost: %f\n', result.objval);
        fprintf('\nBuy:\n')
        for f=1:nfoods
            if buy(f) > 0.0001
                fprintf('%10s %g\n', foods{f}, buy(f));
            end
        end
        fprintf('\nNutrition:\n')
        for c=1:ncategories
            fprintf('%10s %g\n', categories{c}, nutrition(c));
        end
    else
        fprintf('No solution\n');
    end
end

% Solve
results = gurobi(model);
printSolution(results);

fprintf('\nAdding constraint at most 6 servings of dairy\n')
milk = find(strcmp('milk', foods));
icecream = find(strcmp('ice cream', foods));
model.A(end+1,:) = sparse([1; 1], [milk; icecream], 1, ...
        1, nfoods + ncategories);
model.rhs(end+1) = 6;
model.sense(end+1) = '<';

% Solve
results = gurobi(model);
printSolution(results)

end
```

facility.m

```
function facility()

% Copyright 2026, Gurobi Optimization, LLC
%
% Facility location: a company currently ships its product from 5 plants
% to 4 warehouses. It is considering closing some plants to reduce
% costs. What plant(s) should the company close, in order to minimize
% transportation and fixed costs?
%
% Note that this example uses lists instead of dictionaries.  Since
% it does not work with sparse data, lists are a reasonable option.
%
% Based on an example from Frontline Systems:
%   http://www.solver.com/disfacility.htm
% Used with permission.

% define primitive data
nPlants     = 5;
nWarehouses = 4;
% Warehouse demand in thousands of units
Demand      = [15; 18; 14; 20];
% Plant capacity in thousands of units
Capacity    = [20; 22; 17; 19; 18];
% Fixed costs for each plant
FixedCosts  = [12000; 15000; 17000; 13000; 16000];
% Transportation costs per thousand units
TransCosts  = [
    4000; 2000; 3000; 2500; 4500;
    2500; 2600; 3400; 3000; 4000;
    1200; 1800; 2600; 4100; 3000;
    2200; 2600; 3100; 3700; 3200];

% Index helper function
flowidx = @(w, p) nPlants * w + p;

% Build model
model.modelname = 'facility';
model.modelsense = 'min';

% Set data for variables
ncol = nPlants + nPlants * nWarehouses;
model.lb    = zeros(ncol, 1);
model.ub    = [ones(nPlants, 1); inf(nPlants * nWarehouses, 1)];
model.obj   = [FixedCosts; TransCosts];
model.vtype = [repmat('B', nPlants, 1); repmat('C', nPlants * nWarehouses, 1)];

for p = 1:nPlants
    model.varnames{p} = sprintf('Open%d', p);
end

for w = 1:nWarehouses
```

(continues on next page)

(continued from previous page)

```
    for p = 1:nPlants
        v = flowidx(w, p);
        model.varnames{v} = sprintf('Trans%d,%d', w, p);
    end
end

% Set data for constraints and matrix
nrow = nPlants + nWarehouses;
model.A     = sparse(nrow, ncol);
model.rhs   = [zeros(nPlants, 1); Demand];
model.sense = [repmat('<', nPlants, 1); repmat('=', nWarehouses, 1)];

% Production constraints
for p = 1:nPlants
    for w = 1:nWarehouses
        model.A(p, p) = -Capacity(p);
        model.A(p, flowidx(w, p)) = 1.0;
    end
    model.constrnames{p} = sprintf('Capacity%d', p);
end

% Demand constraints
for w = 1:nWarehouses
    for p = 1:nPlants
        model.A(nPlants+w, flowidx(w, p)) = 1.0;
    end
    model.constrnames{nPlants+w} = sprintf('Demand%d', w);
end

% Save model
gurobi_write(model,'facility_m.lp');

% Guess at the starting point: close the plant with the highest fixed
% costs; open all others first open all plants
model.start = [ones(nPlants, 1); inf(nPlants * nWarehouses, 1)];
[~, idx] = max(FixedCosts);
model.start(idx) = 0;

% Set parameters
params.method = 2;

% Optimize
res = gurobi(model, params);

% Print solution
if strcmp(res.status, 'OPTIMAL')
    fprintf('\nTotal Costs: %g\n', res.objval);
    fprintf('solution:\n');
    for p = 1:nPlants
        if res.x(p) > 0.99
            fprintf('Plant %d open:\n', p);
        end
```

(continues on next page)

(continued from previous page)

```
        for w = 1:nWarehouses
            if res.x(flowidx(w, p)) > 0.0001
                fprintf('  Transport %g units to warehouse %d\n', res.x(flowidx(w, p)),␣
↪w);
            end
        end
    end
else
    fprintf('\n No solution\n');
end

end
```

feasopt.m

```
function feasopt(filename)
%
% Copyright 2026, Gurobi Optimization, LLC
%
% This example reads a MIP model from a file, adds artificial
% variables to each constraint, and then minimizes the sum of the
% artificial variables.  A solution with objective zero corresponds
% to a feasible solution to the input model.
% We can also use FeasRelax feature to do it. In this example, we
% use minrelax=1, i.e. optimizing the returned model finds a solution
% that minimizes the original objective, but only from among those
% solutions that minimize the sum of the artificial variables.

% Read model
fprintf('Reading model %s\n', filename);
model = gurobi_read(filename);

params.logfile = 'feasopt.log';
result1 = gurobi(model, params);

[rows, cols] = size(model.A);

% Create penalties, only linear constraints are allowed to be relaxed
penalties.rhs = ones(rows, 1);

result = gurobi_feasrelax(model, 0, true, penalties, params);
gurobi_write(result.model, 'feasopt1.lp');

% clear objective
model.obj = zeros(cols, 1);

nvar = cols;
for c = 1:rows
    if model.sense(c) ~= '>'
        nvar = nvar + 1;
```

(continues on next page)

(continued from previous page)

```
        model.A(c, nvar) = -1;
        model.obj(nvar) = 1;
        model.vtype(nvar) = 'C';
        model.varnames(nvar) = strcat('ArtN_', model.constrnames(c));
        model.lb(nvar) = 0;
        model.ub(nvar) = inf;
    end
    if model.sense(c) ~= '<'
        nvar = nvar + 1;
        model.A(c, nvar) = 1;
        model.obj(nvar) = 1;
        model.vtype(nvar) = 'C';
        model.varnames(nvar) = strcat('ArtP_', model.constrnames(c));
        model.lb(nvar) = 0;
        model.ub(nvar) = inf;
    end
end

gurobi_write(model, 'feasopt2.lp');
result2 = gurobi(model, params);

end
```

fixanddive.m

```
function fixanddive(filename)
%
% Copyright 2026, Gurobi Optimization, LLC
%
% Implement a simple MIP heuristic.  Relax the model,
% sort variables based on fractionality, and fix the 25% of
% the fractional variables that are closest to integer variables.
% Repeat until either the relaxation is integer feasible or
% linearly infeasible.

% Read model
fprintf('Reading model %s\n', filename);

model = gurobi_read(filename);
cols = size(model.A, 2);
ivars = find(model.vtype ~= 'C');

if length(ivars) <= 0
    fprintf('All variables of the model are continuous, nothing to do\n');
    return;
end

% save vtype and set all variables to continuous
vtype = model.vtype;
model.vtype = repmat('C', cols, 1);
```

(continues on next page)

(continued from previous page)

```
params.OutputFlag = 0;

result = gurobi(model, params);

% Perform multiple iterations. In each iteration, identify the first
% quartile of integer variables that are closest to an integer value
% in the relaxation, fix them to the nearest integer, and repeat.

frac = zeros(cols, 1);
for iter = 1:1000
    % See if status is optimal
    if ~strcmp(result.status, 'OPTIMAL')
        fprintf('Model status is %s\n', result.status);
        fprintf('Can not keep fixing variables\n');
        break;
    end
    % collect fractionality of integer variables
    fracs = 0;
    for j = 1:cols
        if vtype(j) == 'C'
            frac(j) = 1; % indicating not integer variable
        else
            t = result.x(j);
            t = t - floor(t);
            if t > 0.5
                t = t - 0.5;
            end
            if t > 1e-5
                frac(j) = t;
                fracs = fracs + 1;
            else
                frac(j) = 1; % indicating not fractional
            end
        end
    end

    fprintf('Iteration %d, obj %g, fractional %d\n', iter, result.objval, fracs);

    if fracs == 0
        fprintf('Found feasible solution - objective %g\n', result.objval);
        break;
    end

    % sort variables based on fractionality
    [~, I] = sort(frac);

    % fix the first quartile to the nearest integer value
    nfix = max(fracs/4, 1);
    for i = 1:nfix
        j = I(i);
        t = floor(result.x(j) + 0.5);
```

(continues on next page)

(continued from previous page)

```
        model.lb(j) = t;
        model.ub(j) = t;
    end

    % use warm start basis and reoptimize
    model.vbasis = result.vbasis;
    model.cbasis = result.cbasis;
    result = gurobi(model, params);
end
```

gc_pwl.m

```
function gc_pwl
% Copyright 2026, Gurobi Optimization, LLC
%
% This example formulates and solves the following simple model
% with PWL constraints:
%
%  maximize
%        sum c(j) * x(j)
%  subject to
%        sum A(i,j) * x(j) <= 0,  for i = 1, ..., m
%        sum y(j) <= 3
%        y(j) = pwl(x(j)),        for j = 1, ..., n
%        x(j) free, y(j) >= 0,    for j = 1, ..., n
%
%  where pwl(x) = 0,     if x  = 0
%               = 1+|x|, if x != 0
%
%  Note
%   1. sum pwl(x(j)) <= b is to bound x vector and also to favor sparse x vector.
%      Here b = 3 means that at most two x(j) can be nonzero and if two, then
%      sum x(j) <= 1
%   2. pwl(x) jumps from 1 to 0 and from 0 to 1, if x moves from negative 0 to 0,
%      then to positive 0, so we need three points at x = 0. x has infinite bounds
%      on both sides, the piece defined with two points (-1, 2) and (0, 1) can
%      extend x to -infinite. Overall we can use five points (-1, 2), (0, 1),
%      (0, 0), (0, 1) and (1, 2) to define y = pwl(x)

n = 5;

% A x <= 0
A1 = [
    0, 0, 0, 1, -1;
    0, 0, 1, 1, -1;
    1, 1, 0, 0, -1;
    1, 0, 1, 0, -1;
    1, 0, 0, 1, -1;
    ];
```

(continues on next page)

(continued from previous page)

```
% sum y(j) <= 3
A2 = [1, 1, 1, 1, 1];

% Constraint matrix altogether
model.A = sparse(blkdiag(A1, A2));

% Right-hand-side coefficient vector
model.rhs = [zeros(n,1); 3];

% Objective function (x coefficients arbitrarily chosen)
model.obj = [0.5, 0.8, 0.5, 0.1, -1, zeros(1, n)];

% It's a maximization model
model.modelsense = 'max';

% Lower bounds for x and y
model.lb = [-inf*ones(n,1); zeros(n,1)];

% PWL constraints
for k = 1:n
    model.genconpwl(k).xvar = k;
    model.genconpwl(k).yvar = n + k;
    model.genconpwl(k).xpts = [-1, 0, 0, 0, 1];
    model.genconpwl(k).ypts = [2, 1, 0, 1, 2];
end

result = gurobi(model);

for k = 1:n
    fprintf('x(%d) = %g\n', k, result.x(k));
end

fprintf('Objective value: %g\n', result.objval);
end
```

genconstr.m

```
function genconstr()

% Copyright 2026, Gurobi Optimization, LLC
%
% In this example we show the use of general constraints for modeling
% some common expressions. We use as an example a SAT-problem where we
% want to see if it is possible to satisfy at least four (or all) clauses
% of the logical form
%
% L = (x1 or ~x2 or x3)  and (x2 or ~x3 or x4)  and
%     (x3 or ~x4 or x1)  and (x4 or ~x1 or x2)  and
%     (~x1 or ~x2 or x3) and (~x2 or ~x3 or x4) and
%     (~x3 or ~x4 or x1) and (~x4 or ~x1 or x2)
```

(continues on next page)

(continued from previous page)

```
%
% We do this by introducing two variables for each literal (itself and its
% negated value), one variable for each clause, one variable indicating
% whether we can satisfy at least four clauses, and one last variable to
% identify the minimum of the clauses (so if it is one, we can satisfy all
% clauses). Then we put these last two variables in the objective.
% The objective function is therefore
%
% maximize Obj1 + Obj2
%
%  Obj1 = MIN(Clause2, ... , Clause8)
%  Obj2 = 2 -> Clause2 + ... + Clause8 >= 4
%
% thus, the objective value will be two if and only if we can satisfy all
% clauses; one if and only if at least four but not all clauses can be satisfied,
% and zero otherwise.
%


% define primitive data
n         = 4;
nLiterals = 4;
nClauses  = 8;
nObj      = 2;
nVars     = 2 * nLiterals + nClauses + nObj;
Clauses = [
      1, n+2, 3;   2, n+3, 4;
      3, n+4, 1;   4, n+1, 2;
    n+1, n+2, 3; n+2, n+3, 4;
    n+3, n+4, 1; n+4, n+1, 2
    ];

% Create model
model.modelname  = 'genconstr';
model.modelsense = 'max';

% Set-up data for variables and constraints
model.vtype = repmat('B', nVars, 1);
model.ub    = ones(nVars, 1);
model.obj   = [zeros(2*nLiterals + nClauses, 1); ones(nObj, 1)];
model.A     = sparse(nLiterals, nVars);
model.rhs   = ones(nLiterals, 1);
model.sense = repmat('=', nLiterals, 1);

for j = 1:nLiterals
    model.varnames{j} = sprintf('X%d', j);
    model.varnames{nLiterals+j} = sprintf('notX%d', j);
end
for j = 1:nClauses
    model.varnames{2*nLiterals+j} = sprintf('Clause%d', j);
end
for j = 1:nObj
```

(continues on next page)

(continued from previous page)

```
    model.varnames{2*nLiterals+nClauses+j} = sprintf('Obj%d', j);
end

% Link Xi and notXi
for i = 1:nLiterals
    model.A(i, i) = 1;
    model.A(i, nLiterals+i) = 1;
    model.constrnames{i} = sprintf('CNSTR_X%d', i);
end

% Link clauses and literals
for i = 1:nClauses
    model.genconor(i).resvar = 2 * nLiterals + i;
    model.genconor(i).vars = Clauses(i:i,1:3);
    model.genconor(i).name = sprintf('CNSTR_Clause%d', i);
end

% Link objs with clauses
model.genconmin.resvar = 2 * nLiterals + nClauses + 1;
for i = 1:nClauses
    model.genconmin.vars(i) = 2 * nLiterals + i;
end
model.genconmin.name = 'CNSTR_Obj1';

model.genconind.binvar = 2 * nLiterals + nClauses + 2;
model.genconind.binval = 1;
model.genconind.a      = [zeros(2*nLiterals,1); ones(nClauses,1); zeros(nObj,1)];
model.genconind.sense  = '>';
model.genconind.rhs    = 4;
model.genconind.name   = 'CNSTR_Obj2';

% Save model
gurobi_write(model, 'genconstr_m.lp');

% Optimize
params.logfile = 'genconstr.log';
result = gurobi(model, params);

% Check optimization status
if strcmp(result.status, 'OPTIMAL')
    if result.objval > 1.9
        fprintf('Logical expression is satisfiable\n');
    else
        if result.objval > 0.9
            fprintf('At least four clauses are satisfiable\n');
        else
            fprintf('At most three clauses may be satisfiable\n');
        end
    end
else
    fprintf('Optimization failed\n');
end
```

intlinprog.m

```
function [x,fval,exitflag,output] = intlinprog(f,intcon,A,b,Aeq,beq,lb,ub,x0,options)
% Copyright 2026, Gurobi Optimization, LLC
%
%INTLINPROG A mixed integer programming (MIP) example using the
%   Gurobi MATLAB interface
%
%   This example is based on the intlinprog interface defined in the
%   MATLAB Optimization Toolbox. The Optimization Toolbox
%   is a registered trademark of The Math Works, Inc.
%
%   x = INTLINPROG(f,intcon,A,b) solves the MIP problem:
%
%     minimize     f'*x
%     subject to    A*x <= b,
%                     x(j) integer, where j is in the vector
%                                   intcon of integer constraints.
%
%   For large problems, you can pass A as a sparse matrix and b as a
%   sparse vector.
%
%   x = INTLINPROG(f,intcon,A,b,Aeq,beq) solves the MIP problem:
%
%     minimize     f'*x
%     subject to    A*x <= b,
%                 Aeq*x == beq,
%                     x(j) integer, where j is in the vector
%                                   intcon of integer constraints.
%
%   For large problems, you can pass Aeq as a sparse matrix and beq as a
%   sparse vector. You can set A=[] and b=[] if no inequalities exist.
%
%   x = INTLINPROG(f,intcon,A,b,Aeq,beq,lb,ub) solves the MIP problem:
%
%     minimize     f'*x
%     subject to    A*x <= b,
%                 Aeq*x == beq,
%           lb <=     x <= ub,
%                     x(j) integer, where j is in the vector
%                                   intcon of integer constraints.
%
%   You can set lb(j) = -inf, if x(j) has no lower bound, and ub(j) = inf,
%   if x(j) has no upper bound. You can set Aeq=[] and beq=[] if no
%   equalities exist.
%
%   x = INTLINPROG(f,intcon,A,b,Aeq,beq,lb,ub,X0) solves the problem above
%   with MIP start set to X0.
%
%   You can set lb=[] or ub=[] if no bounds exist.
%
%   x = INTLINPROG(f,intcon,A,b,Aeq,beq,lb,ub,x0,OPTIONS) solves the
%   problem above given the specified OPTIONS. Only a subset of possible
```

(continues on next page)

(continued from previous page)

```
%   options have any effect:
%
%     OPTIONS.Display               'off' or 'none' disables output,
%     OPTIONS.MaxTime               time limit in seconds,
%     OPTIONS.MaxFeasiblePoints     MIP feasible solution limit,
%     OPTIONS.RelativeGapTolerance  relative MIP optimality gap,
%     OPTIONS.AbsoluteGapTolerance  absolute MIP optimality gap.
%
%   x = INTLINPROG(PROBLEM) solves PROBLEM, which is a structure that must
%   have solver name 'intlinprog' in PROBLEM.solver. You can also specify
%   any of the input arguments above using fields PROBLEM.f, PROBLEM.A, ...
%
%   [x,fval] = INTLINPROG(f,intcon,A,b) returns the objective value at the
%   solution. That is, fval = f'*x.
%
%   [x,fval,exitflag] = INTLINPROG(f,intcon,A,b) returns an exitflag
%   containing the status of the optimization. The values for exitflag and
%   the corresponding status codes are:
%
%      2  stopped prematurely, integer feasible point found
%      1  converged to a solution
%      0  stopped prematurely, no integer feasible point found
%     -2  no feasible point found
%     -3  problem is unbounded
%
%   [x,fval,exitflag,OUTPUT] = INTLINPROG(f,intcon,A,b) returns information
%   about the optimization. OUTPUT is a structure with the following fields:
%
%     OUTPUT.message          Gurobi status code
%     OUTPUT.relativegap      relative MIP optimality gap
%     OUTPUT.absolutegap      absolute MIP optimality gap
%     OUTPUT.numnodes         number of branch-and-cut nodes explored
%     OUTPUT.constrviolation  maximum violation for constraints and bounds
%

% Initialize missing arguments
if nargin == 1
    if isa(f,'struct') && isfield(f,'solver') && strcmpi(f.solver,'intlinprog')
        [f,intcon,A,b,Aeq,beq,lb,ub,x0,options] = probstruct2args(f);
    else
        error('PROBLEM should be a structure with valid fields');
    end
elseif nargin < 4 || nargin > 10
    error('INTLINPROG: the number of input arguments is wrong');
elseif nargin < 10
    options = struct();
    if nargin == 9
        if isa(x0,'struct') || isa(x0,'optim.options.SolverOptions')
            options = x0; % x0 was omitted and options were passed instead
            x0 = [];
        end
    else
```

(continues on next page)

(continued from previous page)

```
        x0 = [];
        if nargin < 8
            ub = [];
            if nargin < 7
                lb = [];
                if nargin < 6
                    beq = [];
                    if nargin < 5
                        Aeq = [];
                    end
                end
            end
        end
    end
end

%build Gurobi model
model.obj = f;
model.A = [sparse(A); sparse(Aeq)]; % A must be sparse
n = size(model.A, 2);
model.vtype = repmat('C', n, 1);
model.vtype(intcon) = 'I';
model.sense = [repmat('<',size(A,1),1); repmat('=',size(Aeq,1),1)];
model.rhs = full([b(:); beq(:)]); % rhs must be dense
if ~isempty(x0)
    model.start = x0;
end
if ~isempty(lb)
    model.lb = lb;
else
    model.lb = -inf(n,1); % default lb for MATLAB is -inf
end
if ~isempty(ub)
    model.ub = ub;
end

% Extract relevant Gurobi parameters from (subset of) options
params = struct();

if isfield(options,'Display') || isa(options,'optim.options.SolverOptions')
    if any(strcmp(options.Display,{'off','none'}))
        params.OutputFlag = 0;
    end
end

if isfield(options,'MaxTime') || isa(options,'optim.options.SolverOptions')
    params.TimeLimit = options.MaxTime;
end

if isfield(options,'MaxFeasiblePoints') ...
        || isa(options,'optim.options.SolverOptions')
    params.SolutionLimit = options.MaxFeasiblePoints;
```

(continues on next page)

(continued from previous page)

```
end

if isfield(options,'RelativeGapTolerance') ...
        || isa(options,'optim.options.SolverOptions')
    params.MIPGap = options.RelativeGapTolerance;
end

if isfield(options,'AbsoluteGapTolerance') ...
        || isa(options,'optim.options.SolverOptions')
    params.MIPGapAbs = options.AbsoluteGapTolerance;
end

% Solve model with Gurobi
result = gurobi(model, params);

% Resolve model if status is INF_OR_UNBD
if strcmp(result.status,'INF_OR_UNBD')
    params.DualReductions = 0;
    warning('Infeasible or unbounded, resolve without dual reductions to determine...');
    result = gurobi(model,params);
end

% Collect results
x = [];
output.message = result.status;
output.relativegap = [];
output.absolutegap = [];
output.numnodes = result.nodecount;
output.constrviolation = [];

if isfield(result,'x')
    x = result.x;
    if nargout > 3
        slack = model.A*x-model.rhs;
        violA = slack(1:size(A,1));
        violAeq = norm(slack((size(A,1)+1):end),inf);
        viollb = model.lb(:)-x;
        violub = 0;
        if isfield(model,'ub')
            violub = x-model.ub(:);
        end
        output.constrviolation = max([0; violA; violAeq; viollb; violub]);
    end
end

fval = [];

if isfield(result,'objval')
    fval = result.objval;
    if nargout > 3 && numel(intcon) > 0
        U = fval;
        L = result.objbound;
```

(continues on next page)

(continued from previous page)

```
        output.relativegap = 100*(U-L)/(abs(U)+1);
        output.absolutegap = U-L;
    end
end

if strcmp(result.status, 'OPTIMAL')
    exitflag = 1;
elseif strcmp(result.status, 'INFEASIBLE') ...
        || strcmp(result.status, 'CUTOFF')
    exitflag = -2;
elseif strcmp(result.status, 'UNBOUNDED')
    exitflag = -3;
elseif isfield(result, 'x')
    exitflag = 2;
else
    exitflag = 0;
end

% Local Functions ==========================================================

function [f,intcon,A,b,Aeq,beq,lb,ub,x0,options] = probstruct2args(s)
%PROBSTRUCT2ARGS Get problem structure fields ([] is returned when missing)

f = getstructfield(s,'f');
intcon = getstructfield(s,'intcon');
A = getstructfield(s,'Aineq');
b = getstructfield(s,'bineq');
Aeq = getstructfield(s,'Aeq');
beq = getstructfield(s,'beq');
lb = getstructfield(s,'lb');
ub = getstructfield(s,'ub');
x0 = getstructfield(s,'x0');
options = getstructfield(s,'options');

function f = getstructfield(s,field)
%GETSTRUCTFIELD Get structure field ([] is returned when missing)

if isfield(s,field)
    f = getfield(s,field);
else
    f = [];
end
```

linprog.m

```
function [x,fval,exitflag,output,lambda] = linprog(f,A,b,Aeq,beq,lb,ub,x0,options)
%Copyright 2026, Gurobi Optimization, LLC
%
%LINPROG A linear programming example using the Gurobi MATLAB interface
%
%   This example is based on the linprog interface defined in the
%   MATLAB Optimization Toolbox. The Optimization Toolbox
%   is a registered trademark of The Math Works, Inc.
%
%   x = LINPROG(f,A,b) solves the linear programming problem:
%
%     minimize     f'*x
%     subject to    A*x <= b.
%
%   For large problems, you can pass A as a sparse matrix and b as a
%   sparse vector.
%
%   x = LINPROG(f,A,b,Aeq,beq) solves the problem:
%
%     minimize     f'*x
%     subject to    A*x <= b,
%                 Aeq*x == beq.
%
%   For large problems, you can pass Aeq as a sparse matrix and beq as a
%   sparse vector. You can set A=[] and b=[] if no inequalities exist.
%
%   x = LINPROG(f,A,b,Aeq,beq,lb,ub) solves the problem:
%
%     minimize     f'*x
%     subject to    A*x <= b,
%                 Aeq*x == beq,
%           lb <=     x <= ub.
%
%   You can set lb(j) = -inf, if x(j) has no lower bound, and ub(j) = inf,
%   if x(j) has no upper bound. You can set Aeq=[] and beq=[] if no
%   equalities exist.
%
%   x = LINPROG(f,A,b,Aeq,beq,lb,ub,OPTIONS) solves the problem above
%   given the specified OPTIONS. Only a subset of possible options have
%   any effect:
%
%     OPTIONS.Display  'off' or 'none' disables output,
%     OPTIONS.MaxTime  time limit in seconds.
%
%   You can set lb=[] or ub=[] if no bounds exist.
%
%   x = LINPROG(PROBLEM) solves PROBLEM, which is a structure that must
%   have solver name 'linprog' in PROBLEM.solver. You can also specify
%   any of the input arguments above using fields PROBLEM.f, PROBLEM.A, ...
%
%   [x,fval] = LINPROG(f,A,b) returns the objective value at the solution.
```

(continues on next page)

(continued from previous page)

```
%   That is, fval = f'*x.
%
%   [x,fval,exitflag] = LINPROG(f,A,b) returns an exitflag containing the
%   status of the optimization. The values for exitflag and the
%   corresponding status codes are:
%
%      1  converged to a solution (OPTIMAL),
%      0  maximum number of iterations reached (ITERATION_LIMIT),
%     -2  no feasible point found (INFEASIBLE, NUMERIC, ...),
%     -3  problem is unbounded (UNBOUNDED).
%
%   [x,fval,exitflag,OUTPUT] = LINPROG(f,A,b) returns information about
%   the optimization. OUTPUT is a structure with the following fields:
%
%     OUTPUT.message          Gurobi status code
%     OUTPUT.constrviolation  maximum violation for constraints and bounds
%
%   [x,fval,exitflag,OUTPUT,LAMBDA] = LINPROG(f,A,b) returns the
%   Lagrangian multipliers at the solution. LAMBDA is a structure with
%   the following fields:
%
%     LAMBDA.lower    multipliers corresponding to x >= lb
%     LAMBDA.upper    multipliers corresponding to x <= ub
%     LAMBDA.ineqlin  multipliers corresponding to A*x <= b
%     LAMBDA.eqlin    multipliers corresponding to Aeq*x == beq
%

% Initialize missing arguments
if nargin == 1
    if isa(f,'struct') && isfield(f,'solver') && strcmpi(f.solver,'linprog')
        [f,A,b,Aeq,beq,lb,ub,x0,options] = probstruct2args(f);
    else
        error('PROBLEM should be a structure with valid fields');
    end
elseif nargin < 3 || nargin > 9
    error('LINPROG: the number of input arguments is wrong');
elseif nargin < 9
    options = struct();
    if nargin == 8
        if isa(x0,'struct') || isa(x0,'optim.options.SolverOptions')
            options = x0; % x0 was omitted and options were passed instead
            x0 = [];
        end
    else
        x0 = [];
        if nargin < 7
            ub = [];
            if nargin < 6
                lb = [];
                if nargin < 5
                    beq = [];
                    if nargin < 4
```

(continues on next page)

(continued from previous page)

```
                        Aeq = [];
                    end
                end
            end
        end
    end
end

% Warn user if x0 argument is ignored
if ~isempty(x0)
    warning('LINPROG will ignore non-empty starting point X0');
end

% Build Gurobi model
model.obj = f;
model.A = [sparse(A); sparse(Aeq)]; % A must be sparse
model.sense = [repmat('<',size(A,1),1); repmat('=',size(Aeq,1),1)];
model.rhs = full([b(:); beq(:)]); % rhs must be dense
if ~isempty(lb)
    model.lb = lb;
else
    model.lb = -inf(size(model.A,2),1); % default lb for MATLAB is -inf
end
if ~isempty(ub)
    model.ub = ub;
end

% Extract relevant Gurobi parameters from (subset of) options
params = struct();

if isfield(options,'Display') || isa(options,'optim.options.SolverOptions')
    if any(strcmp(options.Display,{'off','none'}))
        params.OutputFlag = 0;
    end
end

if isfield(options,'MaxTime') || isa(options,'optim.options.SolverOptions')
    params.TimeLimit = options.MaxTime;
end

% Solve model with Gurobi
result = gurobi(model,params);

% Resolve model if status is INF_OR_UNBD
if strcmp(result.status,'INF_OR_UNBD')
    params.DualReductions = 0;
    warning('Infeasible or unbounded, resolve without dual reductions to determine...');
    result = gurobi(model,params);
end

% Collect results
x = [];
```

(continues on next page)

(continued from previous page)

```
output.message = result.status;
output.constrviolation = [];

if isfield(result,'x')
    x = result.x;
    if nargout > 3
        slack = model.A*x-model.rhs;
        violA = slack(1:size(A,1));
        violAeq = norm(slack((size(A,1)+1):end),inf);
        viollb = model.lb(:)-x;
        violub = 0;
        if isfield(model,'ub')
            violub = x-model.ub(:);
        end
        output.constrviolation = max([0; violA; violAeq; viollb; violub]);
    end
end

fval = [];

if isfield(result,'objval')
    fval = result.objval;
end

if strcmp(result.status,'OPTIMAL')
    exitflag = 1; % converged to a solution
elseif strcmp(result.status,'UNBOUNDED')
    exitflag = -3; % problem is unbounded
elseif strcmp(result.status,'ITERATION_LIMIT')
    exitflag = 0; % maximum number of iterations reached
else
    exitflag = -2; % no feasible point found
end

lambda.lower = [];
lambda.upper = [];
lambda.ineqlin = [];
lambda.eqlin = [];

if nargout > 4
    if isfield(result,'rc')
        lambda.lower = max(0,result.rc);
        lambda.upper = -min(0,result.rc);
    end
    if isfield(result,'pi')
        if ~isempty(A)
            lambda.ineqlin = -result.pi(1:size(A,1));
        end
        if ~isempty(Aeq)
            lambda.eqlin = -result.pi((size(A,1)+1):end);
        end
    end
```

(continues on next page)

(continued from previous page)

```
end

if isempty(lambda.lower) && isempty(lambda.upper) && ...
        isempty(lambda.ineqlin) && isempty(lambda.eqlin)
    lambda = [];
end

% Local Functions ==========================================================

function [f,A,b,Aeq,beq,lb,ub,x0,options] = probstruct2args(s)
%PROBSTRUCT2ARGS Get problem structure fields ([] is returned when missing)

f = getstructfield(s,'f');
A = getstructfield(s,'Aineq');
b = getstructfield(s,'bineq');
Aeq = getstructfield(s,'Aeq');
beq = getstructfield(s,'beq');
lb = getstructfield(s,'lb');
ub = getstructfield(s,'ub');
x0 = getstructfield(s,'x0');
options = getstructfield(s,'options');

function f = getstructfield(s,field)
%GETSTRUCTFIELD Get structure field ([] is returned when missing)

if isfield(s,field)
    f = getfield(s,field);
else
    f = [];
end
```

lp.m

```
function lp()
% Copyright 2026, Gurobi Optimization, LLC
%
% This example formulates and solves the following simple LP model:
% maximize
%       x + 2 y + 3 z
% subject to
%       x +   y        <= 1
%             y +   z  <= 1
%

model.A = sparse([1 1 0; 0 1 1]);
model.obj = [1 2 3];
model.modelsense = 'Max';
model.rhs = [1 1];
model.sense = [ '<' '<'];
```

(continues on next page)

(continued from previous page)

```
result = gurobi(model);

disp(result.objval);
disp(result.x);

% Alterantive representation of A - as sparse triplet matrix
i = [1; 1; 2; 2];
j = [1; 2; 2; 3];
x = [1; 1; 1; 1];
model.A = sparse(i, j, x, 2, 3);

% Set some parameters
params.method = 2;
params.timelimit = 100;

result = gurobi(model, params);

disp(result.objval);
disp(result.x)
end
```

lp2.m

```
function lp2()
% Copyright 2026, Gurobi Optimization, LLC
%
% Formulate a simple linear program, solve it, and then solve it
% again using the optimal basis.

model.A = sparse([1 3 4; 8 2 3]);
model.obj = [1 2 3];
model.rhs = [4 7];
model.sense = ['>' '>'];

% First solve requires a few simplex iterations
result = gurobi(model)

% Second solve - start from an optimal basis, so no iterations
model.vbasis = result.vbasis;
model.cbasis = result.cbasis;
result = gurobi(model)
end
```

lpmethod.m

```
function lpmethod(filename)
% Copyright 2026, Gurobi Optimization, LLC
%
% Solve a model with different values of the Method parameter;
% show which value gives the shortest solve time.

% Read model
fprintf('Reading model %s\n', filename);
model = gurobi_read(filename);

bestTime = inf;
bestMethod = -1;

for i = 0:4
    params.method = i;
    res = gurobi(model, params);
    if strcmp(res.status, 'OPTIMAL')
        bestMethod = i;
        bestTime = res.runtime;
        params.TimeLimit = bestTime;
    end
end

% Report which method was fastest
if bestMethod == -1
    fprintf('Unable to solve this model\n');
else
    fprintf('Solved in %g seconds with Method %d\n', bestTime, bestMethod);
end
```

lpmod.m

```
function lpmod(filename)

% Copyright 2026, Gurobi Optimization, LLC
%
% This example reads an LP model from a file and solves it.
% If the model can be solved, then it finds the smallest positive variable,
% sets its upper bound to zero, and resolves the model two ways:
% first with an advanced start, then without an advanced start
% (i.e. 'from scratch').

% Read model
fprintf('Reading model %s\n', filename);

model = gurobi_read(filename);

if (isfield(model, 'multiobj')  && ~isempty(model.multiobj))  || ...
   (isfield(model, 'sos')       && ~isempty(model.sos))       || ...
```

(continues on next page)

(continued from previous page)

```
   (isfield(model, 'pwlobj')    && ~isempty(model.pwlobj))    || ...
   (isfield(model, 'quadcon')   && ~isempty(model.quadcon))   || ...
   (isfield(model, 'genconstr') && ~isempty(model.genconstr)) || ...
    isfield(model, 'Q')
    fprintf('The model is not a linear program, quit\n');
    return;
end

ivars = find(model.vtype ~= 'C');
ints = length(ivars);

if ints > 0
    fprintf('problem is a MIP, quit\n');
    return;
end

result = gurobi(model);
if ~strcmp(result.status, 'OPTIMAL')
    fprintf('This model cannot be solved because its optimization status is %s\n',␣
↪result.status);
    return;
end

cols = size(model.A,2);

% create lb if they do not exists, and set them to default values
if ~isfield(model, 'lb') || isempty(model.lb)
    model.lb = zeros(cols, 1);
end

% Find the smallest variable value
minVal = inf;
minVar = -1;
for j = 1:cols
    if result.x(j) > 0.0001 && result.x(j) < minVal && model.lb(j) == 0.0
        minVal = result.x(j);
        minVar = j;
    end
end

fprintf('\n*** Setting %s from %d to zero ***\n', model.varnames{minVar}, minVar);
model.ub(minVar) = 0;

model.vbasis = result.vbasis;
model.cbasis = result.cbasis;

% Solve from this starting point
result = gurobi(model);

% Save iteration & time info
warmCount = result.itercount;
warmTime = result.runtime;
```

(continues on next page)

(continued from previous page)

```
% Remove warm start basis and resolve
model = rmfield(model, 'vbasis');
model = rmfield(model, 'cbasis');
result = gurobi(model);

coldCount = result.itercount;
coldTime = result.runtime;

fprintf('\n');
fprintf('*** Warm start: %g iterations, %g seconds\n', warmCount, warmTime);
fprintf('*** Cold start: %g iterations, %g seconds\n', coldCount, coldTime);
```

mip1.m

```
function mip1()
% Copyright 2026, Gurobi Optimization, LLC
% This example formulates and solves the following simple MIP model:
%  maximize
%        x +   y + 2 z
%  subject to
%        x + 2 y + 3 z <= 4
%        x +   y       >= 1
%        x, y, z binary

names = {'x'; 'y'; 'z'};

model.A = sparse([1 2 3; 1 1 0]);
model.obj = [1 1 2];
model.rhs = [4; 1];
model.sense = '<>';
model.vtype = 'B';
model.modelsense = 'max';
model.varnames = names;

gurobi_write(model, 'mip1.lp');

params.outputflag = 0;

result = gurobi(model, params);

disp(result);

for v=1:length(names)
    fprintf('%s %d\n', names{v}, result.x(v));
end

fprintf('Obj: %e\n', result.objval);
end
```

mip2.m

```
function mip2(filename)

% Copyright 2026, Gurobi Optimization, LLC
%
% This example reads a MIP model from a file, solves it and prints
% the objective values from all feasible solutions generated while
% solving the MIP. Then it creates the associated fixed model and
% solves that model.

% Read model
fprintf('Reading model %s\n', filename);

model = gurobi_read(filename);

cols = size(model.A, 2);

ivars = find(model.vtype ~= 'C');
ints = length(ivars);

if ints <= 0
    fprintf('All variables of the model are continuous, nothing to do\n');
    return;
end

% Optimize
params.poolsolutions = 20;
result = gurobi(model, params);

% Capture solution information
if ~strcmp(result.status, 'OPTIMAL')
    fprintf('This model cannot be solved because its optimization status is %s\n', ...
        result.status);
    return;
end

% Iterate over the solutions
if isfield(result, 'pool') && ~isempty(result.pool)
    solcount = length(result.pool);
    for k = 1:solcount
        fprintf('Solution %d has objective %g\n', k, result.pool(k).objval);
    end
else
    fprintf('Solution 1 has objective %g\n', result.objval);
end

% Convert to fixed model
for j = 1:cols
    if model.vtype(j) ~= 'C'
        t = floor(result.x(j) + 0.5);
        model.lb(j) = t;
        model.ub(j) = t;
```

(continues on next page)

(continued from previous page)

```
    end
end

% Solve the fixed model
result2 = gurobi(model, params);
if ~strcmp(result.status, 'OPTIMAL')
    fprintf('Error: fixed model is not optimal\n');
    return;
end
if abs(result.objval - result2.objval) > 1e-6 * (1 + abs(result.objval))
    fprintf('Error: Objective values differ\n');
end

% Print values of non-zero variables
for j = 1:cols
    if abs(result2.x(j)) > 1e-6
        fprintf('%s %g\n', model.varnames{j}, result2.x(j));
    end
end
```

multiobj.m

```
function multiobj()

% Copyright 2026, Gurobi Optimization, LLC
%
% Want to cover four different sets but subject to a common budget of
% elements allowed to be used. However, the sets have different priorities to
% be covered; and we tackle this by using multi-objective optimization.

% define primitive data
groundSetSize     = 20;
nSubSets          = 4;
Budget            = 12;
Set               = [
    1 1 1 1 1 1 1 1 1 1 0 0 0 0 0 0 0 0 0 0;
    0 0 0 0 0 1 1 1 1 1 0 0 0 0 0 1 1 1 1 1;
    0 0 0 1 1 0 1 1 0 0 0 0 0 1 1 0 1 1 0 0;
    0 0 0 1 1 1 0 0 0 1 1 1 0 0 0 1 1 1 0 0
    ];
SetObjPriority    = [3; 2; 2; 1];
SetObjWeight      = [1.0; 0.25; 1.25; 1.0];

% Initialize model
model.modelsense  = 'max';
model.modelname   = 'multiobj';

% Set variables and constraints
model.vtype       = repmat('B', groundSetSize, 1);
model.lb          = zeros(groundSetSize, 1);
```

(continues on next page)

(continued from previous page)

```
model.ub          = ones(groundSetSize, 1);
model.A           = sparse(1, groundSetSize);
model.rhs         = Budget;
model.sense       = '<';
model.constrnames = {'Budget'};

for j = 1:groundSetSize
    model.varnames{j} = sprintf('El%d', j);
    model.A(1, j)     = 1;
end

% Set multi-objectives
for m = 1:nSubSets
    model.multiobj(m).objn     = Set(m, :);
    model.multiobj(m).priority = SetObjPriority(m);
    model.multiobj(m).weight   = SetObjWeight(m);
    model.multiobj(m).abstol   = m;
    model.multiobj(m).reltol   = 0.01;
    model.multiobj(m).name     = sprintf('Set%d', m);
    model.multiobj(m).con      = 0.0;
end

% Save model
gurobi_write(model,'multiobj_m.lp')

% Set parameters
params.PoolSolutions = 100;

% Optimize
result = gurobi(model, params);

% Capture solution information
if ~strcmp(result.status, 'OPTIMAL')
    fprintf('Optimization finished with status %d, quit now\n', result.status);
    return;
end

% Print best solution
fprintf('Selected elements in best solution:\n');
for j = 1:groundSetSize
    if result.x(j) >= 0.9
        fprintf('%s ', model.varnames{j});
    end
end
fprintf('\n');

% Print all solution objectives and best furth solution
if isfield(result, 'pool') && ~isempty(result.pool)
    solcount = length(result.pool);
    fprintf('Number of solutions found: %d\n', solcount);
    fprintf('Objective values for first %d solutions:\n', solcount);
    for m = 1:nSubSets
```

(continues on next page)

(continued from previous page)

```
        fprintf('  %s:', model.multiobj(m).name);
        for k = 1:solcount
            fprintf('  %3g', result.pool(k).objval(m));
        end
        fprintf('\n');
    end
    fprintf('\n');
else
    fprintf('Number of solutions found: 1\n');
    fprintf('Solution 1 has objective values:');
    for k = 1:nSubSets
        fprintf('  %g', result.objval(k));
    end
    fprintf('\n');
end
```

nlconstr.m

```
function nlconstr()
% Copyright 2026, Gurobi Optimization, LLC
%
% This example formulates and solves the following simple nonlinear model
% using the nonlinear constraint API:
%
%  minimize
%      x - y
%  subject to
%      sin(x) * x + x^2 * y <= 1
%      y = cos(x)  (<=> cos(x) - y = 0)
%      -1 <= x <= 2
%       0 <= y <= 2
%
% The nonlinear constraints are set through the model.nlcon field, a struct
% array holding the expression tree of each constraint together with its
% sense and right-hand side.

model.varnames = {'x', 'y'};

% Set linear objective: x - y
model.obj = [1, -1];

% Bounds: -1 <= x <= 2, 0 <= y <= 2
model.lb = [-1; 0];
model.ub = [ 2; 2];

% There are no linear constraints, but the model still needs a constraint
% matrix with one column per variable
model.A = sparse(0, 2);

% Add nonlinear constraint: sin(x) * x + x^2 * y <= 1
```

(continues on next page)

(continued from previous page)

```
%
% The left-hand side is given as an expression tree with 10 nodes. Every node
% has an opcode, a data value, and the index of its parent node. Nodes are
% 1-based, and the root node is marked by a parent of 0. The data value of a
% VARIABLE node is the 1-based index of that variable, the data value of a
% CONSTANT node is the constant itself, and all other nodes use -1.
%
%   node  1: PLUS        (root)
%   node  2: MULTIPLY    (child of 1)  ->  sin(x) * x
%   node  3: SIN         (child of 2)
%   node  4: VARIABLE x  (child of 3)
%   node  5: VARIABLE x  (child of 2)
%   node  6: MULTIPLY    (child of 1)  ->  x^2 * y
%   node  7: POW         (child of 6)
%   node  8: VARIABLE x  (child of 7)
%   node  9: CONSTANT 2  (child of 7)
%   node 10: VARIABLE y  (child of 6)
model.nlcon(1).opcode = [ ...
    GRB.OPCODE_PLUS, ...      %  1: root
    GRB.OPCODE_MULTIPLY, ...  %  2: sin(x) * x
    GRB.OPCODE_SIN, ...       %  3: sin(...)
    GRB.OPCODE_VARIABLE, ...  %  4: x
    GRB.OPCODE_VARIABLE, ...  %  5: x
    GRB.OPCODE_MULTIPLY, ...  %  6: x^2 * y
    GRB.OPCODE_POW, ...       %  7: x^2
    GRB.OPCODE_VARIABLE, ...  %  8: x
    GRB.OPCODE_CONSTANT, ...  %  9: 2
    GRB.OPCODE_VARIABLE, ...  % 10: y
];
model.nlcon(1).data   = [-1, -1, -1, 1, 1, -1, -1, 1, 2, 2];
model.nlcon(1).parent = [ 0,  1,  2, 3, 2,  1,  6, 7, 7, 6];
model.nlcon(1).sense  = '<';
model.nlcon(1).rhs    = 1;
model.nlcon(1).name   = 'NonlinearConstraint1';

% Add nonlinear constraint: cos(x) - y = 0
%
% Only a constant right-hand side is allowed, so y = cos(x) is stated by
% moving y to the left-hand side. The expression tree has 4 nodes:
%
%   node 1: MINUS        (root)
%   node 2: COS          (child of 1)
%   node 3: VARIABLE x   (child of 2)
%   node 4: VARIABLE y   (child of 1)
model.nlcon(2).opcode = [ ...
    GRB.OPCODE_MINUS, ...     % 1: root
    GRB.OPCODE_COS, ...       % 2: cos(...)
    GRB.OPCODE_VARIABLE, ...  % 3: x
    GRB.OPCODE_VARIABLE, ...  % 4: y
];
model.nlcon(2).data   = [-1, -1, 1, 2];
model.nlcon(2).parent = [ 0,  1, 2, 1];
```

(continues on next page)

(continued from previous page)

```
model.nlcon(2).sense  = '=';
model.nlcon(2).rhs    = 0;
model.nlcon(2).name   = 'NonlinearConstraint2';

% Optimize
params.logfile = 'nlconstr.log';
result = gurobi(model, params);

if strcmp(result.status, 'OPTIMAL')
    for j = 1:2
        fprintf('%s %e\n', model.varnames{j}, result.x(j));
    end
    fprintf('Obj: %e\n', result.objval);
else
    fprintf('Optimization did not produce an optimal solution\n');
end
end
```

nlobj.m

```
function nlobj()
% Copyright 2026, Gurobi Optimization, LLC
%
% This example formulates and solves the following simple nonlinear model
% using the nonlinear objective API:
%
%  minimize
%      sin(x) * x + x^2 * y
%  subject to
%      x + y >= 1
%      -1 <= x <= 2
%       0 <= y <= 2
%
% The nonlinear objective is set through the model.nlobj field, which holds
% the expression tree of the objective function.

model.varnames = {'x', 'y'};

% Bounds: -1 <= x <= 2, 0 <= y <= 2
model.lb = [-1; 0];
model.ub = [ 2; 2];

% Add constraint: x + y >= 1
model.A     = sparse([1 1]);
model.rhs   = 1;
model.sense = '>';

% Set nonlinear objective: sin(x) * x + x^2 * y
%
% The objective is given as an expression tree with 10 nodes. Every node has
```

(continues on next page)

(continued from previous page)

```
% an opcode, a data value, and the index of its parent node. Nodes are
% 1-based, and the root node is marked by a parent of 0. The data value of a
% VARIABLE node is the 1-based index of that variable, the data value of a
% CONSTANT node is the constant itself, and all other nodes use -1.
%
%   node  1: PLUS        (root)
%   node  2: MULTIPLY    (child of 1)  ->  sin(x) * x
%   node  3: SIN         (child of 2)
%   node  4: VARIABLE x  (child of 3)
%   node  5: VARIABLE x  (child of 2)
%   node  6: MULTIPLY    (child of 1)  ->  x^2 * y
%   node  7: POW         (child of 6)
%   node  8: VARIABLE x  (child of 7)
%   node  9: CONSTANT 2  (child of 7)
%   node 10: VARIABLE y  (child of 6)
model.nlobj.opcode = [ ...
    GRB.OPCODE_PLUS, ...      %  1: root
    GRB.OPCODE_MULTIPLY, ...  %  2: sin(x) * x
    GRB.OPCODE_SIN, ...       %  3: sin(...)
    GRB.OPCODE_VARIABLE, ...  %  4: x
    GRB.OPCODE_VARIABLE, ...  %  5: x
    GRB.OPCODE_MULTIPLY, ...  %  6: x^2 * y
    GRB.OPCODE_POW, ...       %  7: x^2
    GRB.OPCODE_VARIABLE, ...  %  8: x
    GRB.OPCODE_CONSTANT, ...  %  9: 2
    GRB.OPCODE_VARIABLE, ...  % 10: y
];
model.nlobj.data   = [-1, -1, -1, 1, 1, -1, -1, 1, 2, 2];
model.nlobj.parent = [ 0,  1,  2, 3, 2,  1,  6, 7, 7, 6];

% Optimize
params.logfile = 'nlobj.log';
result = gurobi(model, params);

if strcmp(result.status, 'OPTIMAL')
    for j = 1:2
        fprintf('%s %e\n', model.varnames{j}, result.x(j));
    end
    fprintf('Obj: %e\n', result.objval);
else
    fprintf('Optimization did not produce an optimal solution\n');
end
end
```

opttoolbox_lp.m

```
function opttoolbox_lp()
% Copyright 2026, Gurobi Optimization, LLC
%
% This example uses Matlab 2017b problem based modeling feature, which
% requires Optimization Toolbox, to formulate and solve the following
% simple LP model, the same model as for lp.m
%
% maximize
%       x + 2 y + 3 z
% subject to
%       x +   y        <= 1
%             y +   z  <= 1
%
% To use Gurobi with this example, linprog.m must be in the current
% directory or added to Matlab path

x = optimvar('x', 'LowerBound',0);
y = optimvar('y', 'LowerBound',0);
z = optimvar('z', 'LowerBound',0);

prob = optimproblem('ObjectiveSense','maximize');

prob.Objective = x + 2 * y + 3 * z;

prob.Constraints.cons1 = x + y <= 1;
prob.Constraints.cons2 = y + z <= 1;

options = optimoptions('linprog');

% For Matlab R2017b use the following
% sol = solve(prob, options)

% Syntax for R2018a and later
sol = solve(prob, 'Options', options);
end
```

opttoolbox_mip1.m

```
function opttoolbox_mip1()
% Copyright 2026, Gurobi Optimization, LLC
%
% This example uses Matlab 2017b problem based modeling feature, which
% requires Optimization Toolbox, to formulate and solve the following
% simple MIP model, the same model as for mip1.m
%
%  maximize
%        x +   y + 2 z
%  subject to
%        x + 2 y + 3 z <= 4
```

(continues on next page)

(continued from previous page)

```
%        x +   y       >= 1
%  x, y, z binary
%
% To use Gurobi with this example, intlinprog.m must be in the current
% directory or added to Matlab path

x = optimvar('x', 'Type','integer','LowerBound',0,'UpperBound',1);
y = optimvar('y', 'Type','integer','LowerBound',0,'UpperBound',1);
z = optimvar('z', 'Type','integer','LowerBound',0,'UpperBound',1);

prob = optimproblem('ObjectiveSense','maximize');

prob.Objective = x + y + 2 * z;

prob.Constraints.cons1 = x + 2 * y + 3 * z <= 4;
prob.Constraints.cons2 = x + y >= 1;

options = optimoptions('intlinprog');

% For Matlab R2017b use the following
% sol = solve(prob, options)

% Syntax for R2018a and later
sol = solve(prob, 'Options', options);

end
```

params.m

```
function params(filename)
% Copyright 2026, Gurobi Optimization, LLC
%
% Use parameters that are associated with a model.
%
% A MIP is solved for a few seconds with different sets of parameters.
% The one with the smallest MIP gap is selected, and the optimization
% is resumed until the optimal solution is found.

% Read model
fprintf('Reading model %s\n', filename);

model = gurobi_read(filename);

ivars = find(model.vtype ~= 'C');

if length(ivars) <= 0
    fprintf('All variables of the model are continuous, nothing to do\n');
    return;
end
```

(continues on next page)

(continued from previous page)

```
% Set a 2 second time limit
params.TimeLimit = 2;

% Now solve the model with different values of MIPFocus

params.MIPFocus = 0;
result          = gurobi(model, params);
bestgap         = result.mipgap;
bestparams      = params;
for i = 1:3
    params.MIPFocus = i;
    result          = gurobi(model, params);
    if result.mipgap < bestgap
        bestparams = params;
        bestgap    = result.mipgap;
    end
end

% Finally, reset the time limit and Re-solve model to optimality
bestparams.TimeLimit = Inf;
result = gurobi(model, bestparams);
fprintf('Solution status: %s, objective value %g\n', ...
    result.status, result.objval);
end
```

piecewise.m

```
function piecewise()
% Copyright 2026, Gurobi Optimization, LLC
%
% This example considers the following separable, convex problem:
%
%   minimize    f(x) - y + g(z)
%   subject to  x + 2 y + 3 z <= 4
%               x +   y       >= 1
%               x,    y,    z <= 1
%
% where f(u) = exp(-u) and g(u) = 2 u^2 - 4 u, for all real u. It
% formulates and solves a simpler LP model by approximating f and
% g with piecewise-linear functions. Then it transforms the model
% into a MIP by negating the approximation for f, which corresponds
% to a non-convex piecewise-linear function, and solves it again.

names = {'x'; 'y'; 'z'};

model.A = sparse([1 2 3; 1 1 0]);
model.obj = [0; -1; 0];
model.rhs = [4; 1];
model.sense = '<>';
model.vtype = 'C';
```

(continues on next page)

(continued from previous page)

```
model.lb = [0; 0; 0];
model.ub = [1; 1; 1];
model.varnames = names;

% Compute f and g on 101 points in [0,1]
u = linspace(0.0, 1.0, 101);
f = exp(-u);
g = 2*u.^2 - 4*u;

% Set piecewise-linear objective f(x)
model.pwlobj(1).var = 1;
model.pwlobj(1).x   = u;
model.pwlobj(1).y   = f;

% Set piecewise-linear objective g(z)
model.pwlobj(2).var   = 3;
model.pwlobj(2).x     = u;
model.pwlobj(2).y     = g;

% Optimize model as LP
result = gurobi(model);

disp(result);

for v=1:length(names)
    fprintf('%s %d\n', names{v}, result.x(v));
end

fprintf('Obj: %e\n', result.objval);

% Negate piecewise-linear objective function for x
f = -f;
model.pwlobj(1).y = f;

gurobi_write(model, 'pwl.lp')

% Optimize model as a MIP
result = gurobi(model);

disp(result);

for v=1:length(names)
    fprintf('%s %d\n', names{v}, result.x(v));
end

fprintf('Obj: %e\n', result.objval);
end
```

poolsearch.m

```
function poolsearch()

% Copyright 2026, Gurobi Optimization, LLC
%
% We find alternative epsilon-optimal solutions to a given knapsack
% problem by using PoolSearchMode

% define primitive data
groundSetSize = 10;
objCoef       = [32; 32; 15; 15; 6; 6; 1; 1; 1; 1];
knapsackCoef  = [16, 16,  8,  8, 4, 4, 2, 2, 1, 1];
Budget        = 33;

% Initialize model
model.modelsense  = 'max';
model.modelname   = 'poolsearch';

% Set variables
model.obj         = objCoef;
model.vtype       = repmat('B', groundSetSize, 1);
model.lb          = zeros(groundSetSize, 1);
model.ub          = ones(groundSetSize, 1);
for j = 1:groundSetSize
    model.varnames{j} = sprintf('El%d', j);
end

% Build constraint matrix
model.A           = sparse(knapsackCoef);
model.rhs         = Budget;
model.sense       = '<';
model.constrnames = {'Budget'};

% Set poolsearch parameters
params.PoolSolutions  = 1024;
params.PoolGap        = 0.10;
params.PoolSearchMode = 2;

% Save problem
gurobi_write(model, 'poolsearch_m.lp');

% Optimize
result = gurobi(model, params);

% Capture solution information
if ~strcmp(result.status, 'OPTIMAL')
    fprintf('Optimization finished with status %s, quit now\n', result.status);
    return;
end

% Print best solution
fprintf('Selected elements in best solution:\n');
```

(continues on next page)

(continued from previous page)

```
for j = 1:groundSetSize
    if result.x(j) >= 0.9
        fprintf('%s ', model.varnames{j});
    end
end
fprintf('\n');

% Print all solution objectives and best furth solution
if isfield(result, 'pool') && ~isempty(result.pool)
    solcount = length(result.pool);
    fprintf('Number of solutions found: %d\n', solcount);
    fprintf('Objective values for all %d solutions:\n', solcount);
    for k = 1:solcount
        fprintf('%g ', result.pool(k).objval);
    end
    fprintf('\n');
    if solcount >= 4
        fprintf('Selected elements in fourth best solution:\n');
        for k = 1:groundSetSize
            if result.pool(4).poolnx(k) >= 0.9
                fprintf(' %s', model.varnames{k});
            end
        end
        fprintf('\n');
    end
else
    fprintf('Number of solutions found: 1\n');
    fprintf('Solution 1 has objective: %g \n', result.objval);
end
```

qcp.m

```
function qcp()
% Copyright 2026, Gurobi Optimization, LLC
%
% This example formulates and solves the following simple QCP model:
%  maximize
%      x
%  subject to
%      x + y + z = 1
%      x^2 + y^2 <= z^2 (second-order cone)
%      x^2 <= yz        (rotated second-order cone)
%      x, y, z non-negative

names = {'x', 'y', 'z'};
model.varnames = names;

% Set objective: x
model.obj = [ 1 0 0 ];
model.modelsense = 'max';
```

(continues on next page)

(continued from previous page)

```
% Add constraint: x + y + z = 1
model.A   = sparse([1 1 1]);
model.rhs = 1;
model.sense = '=';

% Add second-order cone: x^2 + y^2 <= z^2 using a sparse matrix
model.quadcon(1).Qc = sparse([
    1 0  0;
    0 1  0;
    0 0 -1]);
model.quadcon(1).q  = zeros(3,1);
model.quadcon(1).rhs = 0.0;
model.quadcon(1).name = 'std_cone';

% Add rotated cone: x^2 <= yz using sparse triplet representation
% Equivalent sparse matrix data:
%model.quadcon(2).Qc = sparse([
%    1 0  0;
%    0 0 -1;
%    0 0  0]);
model.quadcon(2).Qrow = [1, 2]
model.quadcon(2).Qcol = [1, 3]
model.quadcon(2).Qval = [1, -1]
% All-zero sparse 3-by-1 vector
model.quadcon(2).q  = sparse(3,1);
model.quadcon(2).rhs = 0.0;
model.quadcon(2).name = 'rot_cone';

gurobi_write(model, 'qcp.lp');

result = gurobi(model);

for j=1:3
    fprintf('%s %e\n', names{j}, result.x(j))
end

fprintf('Obj: %e\n', result.objval);
end
```

qp.m

```
function qp()
% Copyright 2026, Gurobi Optimization, LLC
%
% This example formulates and solves the following simple QP model:
%  minimize
%      x^2 + x*y + y^2 + y*z + z^2 + 2 x
%  subject to
%      x + 2 y + 3 z >= 4
```

(continues on next page)

(continued from previous page)

```
%      x +   y       >= 1
%      x, y, z non-negative
%
% It solves it once as a continuous model, and once as an integer
% model.

names = {'x', 'y', 'z'};
model.varnames = names;
model.Q = sparse([1 0.5 0; 0.5 1 0.5; 0 0.5 1]);
model.A = sparse([1 2 3; 1 1 0]);
model.obj = [2 0 0];
model.rhs = [4 1];
model.sense = '>';

gurobi_write(model, 'qp.lp');

results = gurobi(model);

for v=1:length(names)
    fprintf('%s %e\n', names{v}, results.x(v));
end

fprintf('Obj: %e\n', results.objval);

model.vtype = 'B';

results  = gurobi(model);

for v=1:length(names)
    fprintf('%s %e\n', names{v}, results.x(v));
end

fprintf('Obj: %e\n', results.objval);

end
```

sensitivity.m

```
function sensitivity(filename)
% Copyright 2026, Gurobi Optimization, LLC
%
% A simple sensitivity analysis example which reads a MIP model
% from a file and solves it. Then each binary variable is set
% to 1-X, where X is its value in the optimal solution, and
% the impact on the objective function value is reported.

% Read model
fprintf('Reading model %s\n', filename);

model = gurobi_read(filename);
```

(continues on next page)

(continued from previous page)

```
cols = size(model.A, 2);

ivars = find(model.vtype ~= 'C');
if length(ivars) <= 0
    fprintf('All variables of the model are continuous, nothing to do\n');
    return;
end

% Optimize
result = gurobi(model);

% Capture solution information
if result.status ~= 'OPTIMAL'
    fprintf('Model status is %d, quit now\n', result.status);
end

origx = result.x;
origobjval = result.objval;

params.OutputFlag = 0;

% Iterate through unfixed binary variables in the model
for j = 1:cols
    if model.vtype(j) ~= 'B' && model.vtype(j) ~= 'I'
        continue;
    end
    if model.vtype(j) == 'I'
        if model.lb(j) ~= 0.0 || model.ub(j) ~= 1.0
            continue;
        end
    else
        if model.lb(j) > 0.0 || model.ub(j) < 1.0
            continue;
        end
    end

    % Update MIP start for all variables
    model.start = origx;

    % Set variable to 1-X, where X is its value in optimal solution
    if origx(j) < 0.5
        model.start(j) = 1;
        model.lb(j) = 1;
    else
        model.start(j) = 0;
        model.ub(j) = 0;
    end

    % Optimize
    result = gurobi(model, params);

    % Display result
```

(continues on next page)

(continued from previous page)

```
    if ~strcmp(result.status, 'OPTIMAL')
        gap = inf;
    else
        gap = result.objval - origobjval;
    end
    fprintf('Objective sensitivity for variable %s is %g\n', ...
        model.varnames{j}, gap);

    % Restore original bounds
    model.lb(j) = 0;
    model.ub(j) = 1;
end
```

sos.m

```
function sos()
% Copyright 2026, Gurobi Optimization, LLC
%
% This example creates a very simple Special Ordered Set (SOS)
% model. The model consists of 3 continuous variables, no linear
% constraints, and a pair of SOS constraints of type 1.

model.ub = [1 1 2];
model.obj = [2 1 1];
model.modelsense = 'Max';
model.A = sparse(1,3);
model.rhs = 0;
model.sense = '=';

% Add first SOS: x1 = 0 or x2 = 0
model.sos(1).type   = 1;
model.sos(1).index  = [1 2];
model.sos(1).weight = [1 2];

% Add second SOS: x1 = 0 or x3 = 0
model.sos(2).type   = 1;
model.sos(2).index  = [1 3];
model.sos(2).weight = [1 2];

% Write model to file
gurobi_write(model, 'sos.lp');

result = gurobi(model);

for i=1:3
    fprintf('x%d %e\n', i, result.x(i))
end

fprintf('Obj: %e\n', result.objval);
end
```

sudoku.m

```
function sudoku(filename)

%  Copyright 2026, Gurobi Optimization, LLC */
%
% Sudoku example.
%
% The Sudoku board is a 9x9 grid, which is further divided into a 3x3 grid
% of 3x3 grids.  Each cell in the grid must take a value from 0 to 9.
% No two grid cells in the same row, column, or 3x3 subgrid may take the
% same value.
%
% In the MIP formulation, binary variables x[i,j,v] indicate whether
% cell <i,j> takes value 'v'.  The constraints are as follows:
%   1. Each cell must take exactly one value (sum_v x[i,j,v] = 1)
%   2. Each value is used exactly once per row (sum_i x[i,j,v] = 1)
%   3. Each value is used exactly once per column (sum_j x[i,j,v] = 1)
%   4. Each value is used exactly once per 3x3 subgrid (sum_grid x[i,j,v] = 1)
%
% Input datasets for this example can be found in examples/data/sudoku*.
%

SUBDIM = 3;
DIM    = SUBDIM*SUBDIM;

fileID = fopen(filename);
if fileID == -1
    fprintf('Could not read file %s, quit\n', filename);
    return;
end

board = repmat(-1, DIM, DIM);
for i = 1:DIM
    s = fgets(fileID, 100);
    if length(s) <= DIM
        fprintf('Error: not enough board positions specified, quit\n');
        return;
    end
    for j = 1:DIM
        if s(j) ~= '.'
            board(i, j) = str2double(s(j));
            if board(i,j) < 1 || board(i,j) > DIM
                fprintf('Error: Unexpected character in Input line %d, quit\n', i);
                return;
            end
        end
    end
end

% Map X(i,j,k) into an index variable in the model
nVars = DIM * DIM * DIM;
```

(continues on next page)

(continued from previous page)

```
% Build model
model.vtype    = repmat('B', nVars, 1);
model.lb       = zeros(nVars, 1);
model.ub       = ones(nVars, 1);

for i = 1:DIM
    for j = 1:DIM
        for v = 1:DIM
            var = (i-1)*DIM*DIM + (j-1)*DIM + v;
            model.varnames{var} = sprintf('x[%d,%d,%d]', i, j, v);
        end
    end
end

% Create constraints:
nRows = 4 * DIM * DIM;
model.A = sparse(nRows, nVars);
model.rhs = ones(nRows, 1);
model.sense = repmat('=', nRows, 1);

Row = 1;

% Each cell gets a value */
for i = 1:DIM
    for j = 1:DIM
        for v = 1:DIM
            if board(i,j) == v
                model.lb((i-1)*DIM*DIM + (j-1)*DIM + v) = 1;
            end
            model.A(Row, (i-1)*DIM*DIM + (j-1)*DIM + v) = 1;
        end
        Row = Row + 1;
    end
end

% Each value must appear once in each row
for v = 1:DIM
    for j = 1:DIM
        for i = 1:DIM
            model.A(Row, (i-1)*DIM*DIM + (j-1)*DIM + v) = 1;
        end
        Row = Row + 1;
    end
end

% Each value must appear once in each column
for v = 1:DIM
    for i = 1:DIM
        for j = 1:DIM
            model.A(Row, (i-1)*DIM*DIM + (j-1)*DIM + v) = 1;
        end
```

(continues on next page)

(continued from previous page)

```
        Row = Row + 1;
    end
end

% Each value must appear once in each subgrid
for v = 1:DIM
    for ig = 0: SUBDIM-1
        for jg = 0: SUBDIM-1
            for i = ig*SUBDIM+1:(ig+1)*SUBDIM
                for j = jg*SUBDIM+1:(jg+1)*SUBDIM
                    model.A(Row, (i-1)*DIM*DIM + (j-1)*DIM + v) = 1;
                end
            end
            Row = Row + 1;
        end
    end
end

% Save model
gurobi_write(model, 'sudoku_m.lp');

% Optimize model
params.logfile = 'sudoku_m.log';
result = gurobi(model, params);

if strcmp(result.status, 'OPTIMAL')
    fprintf('Solution:\n');
    for i = 1:DIM
        for j = 1:DIM
            for v = 1:DIM
                var = (i-1)*DIM*DIM + (j-1)*DIM + v;
                if result.x(var) > 0.99
                    fprintf('%d', v);
                end
            end
        end
        fprintf('\n');
    end
else
    fprintf('Problem was infeasible\n')
end
```

workforce1.m

```
function workforce1()

% Copyright 2026, Gurobi Optimization, LLC
%
% Assign workers to shifts; each worker may or may not be available on a
% particular day. If the problem cannot be solved, use IIS to find a set of
% conflicting constraints. Note that there may be additional conflicts
% besides what is reported via IIS.

% define data
nShifts  = 14;
nWorkers =  7;
nVars    = nShifts * nWorkers;

Shifts  = {'Mon1'; 'Tue2'; 'Wed3'; 'Thu4'; 'Fri5'; 'Sat6'; 'Sun7';
    'Mon8'; 'Tue9'; 'Wed10'; 'Thu11'; 'Fri12'; 'Sat13'; 'Sun14'};
Workers = {'Amy'; 'Bob'; 'Cathy'; 'Dan'; 'Ed'; 'Fred'; 'Gu'};

pay     = [10; 12; 10; 8; 8; 9; 11];

shiftRequirements = [3; 2; 4; 4; 5; 6; 5; 2; 2; 3; 4; 6; 7; 5];

availability = [
    0 1 1 0 1 0 1 0 1 1 1 1 1 1;
    1 1 0 0 1 1 0 1 0 0 1 0 1 0;
    0 0 1 1 1 0 1 1 1 1 1 1 1 1;
    0 1 1 0 1 1 0 1 1 1 1 1 1 1;
    1 1 1 1 1 0 1 1 1 0 1 0 1 1;
    1 1 1 0 0 1 0 1 1 0 0 1 1 1;
    1 1 1 0 1 1 1 1 1 1 1 1 1 1
    ];

% Build model
model.modelname  = 'workforce1';
model.modelsense = 'min';

% Initialize assignment decision variables:
%    x[w][s] == 1 if worker w is assigned
%    to shift s. Since an assignment model always produces integer
%    solutions, we use continuous variables and solve as an LP.
model.ub    = ones(nVars, 1);
model.obj   = zeros(nVars, 1);

for w = 1:nWorkers
    for s = 1:nShifts
        model.varnames{s+(w-1)*nShifts} = sprintf('%s.%s', Workers{w}, Shifts{s});
        model.obj(s+(w-1)*nShifts) = pay(w);
        if availability(w, s) == 0
            model.ub(s+(w-1)*nShifts) = 0;
        end
    end
```

(continues on next page)

(continued from previous page)

```
end

% Set-up shift-requirements constraints
model.sense = repmat('=', nShifts, 1);
model.rhs   = shiftRequirements;
model.constrnames = Shifts;
model.A = sparse(nShifts, nVars);
for s = 1:nShifts
    for w = 1:nWorkers
        model.A(s, s+(w-1)*nShifts) = 1;
    end
end

% Save model
gurobi_write(model,'workforce1_m.lp');

% Optimize
params.logfile = 'workforce1_m.log';
result = gurobi(model, params);

% Display results
if strcmp(result.status, 'OPTIMAL')
    % The code may enter here if you change some of the data... otherwise
    % this will never be executed.
    fprintf('The optimal objective is %g\n', result.objval);
    fprintf('Schedule:\n');
    for s = 1:nShifts
        fprintf('\t%s:', Shifts{s});
        for w = 1:nWorkers
            if result.x(s+(w-1)*nShifts) > 0.9
                fprintf('%s ', Workers{w});
            end
        end
        fprintf('\n');
    end
else
    if strcmp(result.status, 'INFEASIBLE')
        fprintf('Problem is infeasible.... computing IIS\n');
        iis = gurobi_iis(model, params);
        if iis.minimal
            fprintf('IIS is minimal\n');
        else
            fprintf('IIS is not minimal\n');
        end

        if any(iis.Arows)
            fprintf('Rows in IIS: ');
            disp(strjoin(model.constrnames(iis.Arows)));
        end
        if any(iis.lb)
            fprintf('LB in IIS: ');
            disp(strjoin(model.varnames(iis.lb)));
```

(continues on next page)

(continued from previous page)

```
        end
        if any(iis.ub)
            fprintf('UB in IIS: ');
            disp(strjoin(model.varnames(iis.ub)));
        end
    else
        % Just to handle user interruptions or other problems
        fprintf('Unexpected status %s\n',result.status);
    end
end
```

workforce2.m

```
function workforce2()

% Copyright 2026, Gurobi Optimization, LLC
%
% Assign workers to shifts; each worker may or may not be available on a
% particular day. If the problem cannot be solved, use IIS iteratively to
% find all conflicting constraints.

% define data
nShifts  = 14;
nWorkers =  7;
nVars    = nShifts * nWorkers;

Shifts  = {'Mon1'; 'Tue2'; 'Wed3'; 'Thu4'; 'Fri5'; 'Sat6'; 'Sun7';
    'Mon8'; 'Tue9'; 'Wed10'; 'Thu11'; 'Fri12'; 'Sat13'; 'Sun14'};
Workers = {'Amy'; 'Bob'; 'Cathy'; 'Dan'; 'Ed'; 'Fred'; 'Gu'};

pay     = [10; 12; 10; 8; 8; 9; 11];

shiftRequirements = [3; 2; 4; 4; 5; 6; 5; 2; 2; 3; 4; 6; 7; 5];

availability = [
    0 1 1 0 1 0 1 0 1 1 1 1 1 1;
    1 1 0 0 1 1 0 1 0 0 1 0 1 0;
    0 0 1 1 1 0 1 1 1 1 1 1 1 1;
    0 1 1 0 1 1 0 1 1 1 1 1 1 1;
    1 1 1 1 1 0 1 1 1 0 1 0 1 1;
    1 1 1 0 0 1 0 1 1 0 0 1 1 1;
    1 1 1 0 1 1 1 1 1 1 1 1 1 1
    ];


% Build model
model.modelname  = 'workforce2';
model.modelsense = 'min';

% Initialize assignment decision variables:
```

(continues on next page)

(continued from previous page)

```
%    x[w][s] == 1 if worker w is assigned
%    to shift s. Since an assignment model always produces integer
%    solutions, we use continuous variables and solve as an LP.
model.ub    = ones(nVars, 1);
model.obj   = zeros(nVars, 1);

for w = 1:nWorkers
    for s = 1:nShifts
        model.varnames{s+(w-1)*nShifts} = sprintf('%s.%s', Workers{w}, Shifts{s});
        model.obj(s+(w-1)*nShifts) = pay(w);
        if availability(w, s) == 0
            model.ub(s+(w-1)*nShifts) = 0;
        end
    end
end

% Set-up shift-requirements constraints
model.sense = repmat('=', nShifts, 1);
model.rhs   = shiftRequirements;
model.constrnames = Shifts;
model.A = sparse(nShifts, nVars);
for s = 1:nShifts
    for w = 1:nWorkers
        model.A(s, s+(w-1)*nShifts) = 1;
    end
end

% Save model
gurobi_write(model, 'workforce2_m.lp');

% Optimize
params.logfile = 'workforce2_m.log';
result = gurobi(model, params);

% If infeasible, remove IIS rows until it becomes feasible
numremoved = 0;
if strcmp(result.status, 'INFEASIBLE')
    numremoved = 0;
    while strcmp(result.status, 'INFEASIBLE')
        iis = gurobi_iis(model, params);
        keep = find(~iis.Arows);
        fprintf('Removing rows: ');
        disp(model.constrnames{iis.Arows})
        model.A = model.A(keep, :);
        model.sense = model.sense(keep, :);
        model.rhs   = model.rhs(keep, :);
        model.constrnames = model.constrnames(keep,:);
        numremoved = numremoved + 1;
        result = gurobi(model, params);
    end
end
```

(continues on next page)

(continued from previous page)

```
% Display results
if strcmp(result.status, 'OPTIMAL')
    if numremoved > 0
        fprintf('It becomes feasible after %d rounds of IIS row removing\n', numremoved);
    end
    printsolution(result, Shifts, Workers)
else
    % Just to handle user interruptions or other problems
    fprintf('Unexpected status %s\n',result.status)
end

end

function printsolution(result, Shifts, Workers)
% Helper function to display results
nShifts = length(Shifts);
nWorkers = length(Workers);

fprintf('The optimal objective is %g\n', result.objval);
fprintf('Schedule:\n');
for s = 1:nShifts
    fprintf('\t%s:', Shifts{s});
    for w = 1:nWorkers
        if result.x(s+(w-1)*nShifts) > 0.9
            fprintf('%s ', Workers{w});
        end
    end
    fprintf('\n');
end
end
```

workforce3.m

```
function workforce3()

% Copyright 2026, Gurobi Optimization, LLC
%
% Assign workers to shifts; each worker may or may not be available on a
% particular day. If the problem cannot be solved, relax the model
% to determine which constraints cannot be satisfied, and how much
% they need to be relaxed.

% define data
nShifts  = 14;
nWorkers =  7;
nVars    = nShifts * nWorkers;

Shifts  = {'Mon1'; 'Tue2'; 'Wed3'; 'Thu4'; 'Fri5'; 'Sat6'; 'Sun7';
    'Mon8'; 'Tue9'; 'Wed10'; 'Thu11'; 'Fri12'; 'Sat13'; 'Sun14'};
Workers = {'Amy'; 'Bob'; 'Cathy'; 'Dan'; 'Ed'; 'Fred'; 'Gu'};
```

(continues on next page)

(continued from previous page)

```
pay     = [10; 12; 10; 8; 8; 9; 11];

shiftRequirements = [3; 2; 4; 4; 5; 6; 5; 2; 2; 3; 4; 6; 7; 5];

availability = [
    0 1 1 0 1 0 1 0 1 1 1 1 1 1;
    1 1 0 0 1 1 0 1 0 0 1 0 1 0;
    0 0 1 1 1 0 1 1 1 1 1 1 1 1;
    0 1 1 0 1 1 0 1 1 1 1 1 1 1;
    1 1 1 1 1 0 1 1 1 0 1 0 1 1;
    1 1 1 0 0 1 0 1 1 0 0 1 1 1;
    1 1 1 0 1 1 1 1 1 1 1 1 1 1
    ];

% Build model
model.modelname  = 'workforce3';
model.modelsense = 'min';

% Initialize assignment decision variables:
%    x[w][s] == 1 if worker w is assigned
%    to shift s. Since an assignment model always produces integer
%    solutions, we use continuous variables and solve as an LP.
model.ub    = ones(nVars, 1);
model.obj   = zeros(nVars, 1);

for w = 1:nWorkers
    for s = 1:nShifts
        model.varnames{s+(w-1)*nShifts} = sprintf('%s.%s', Workers{w}, Shifts{s});
        model.obj(s+(w-1)*nShifts) = pay(w);
        if availability(w, s) == 0
            model.ub(s+(w-1)*nShifts) = 0;
        end
    end
end

% Set-up shift-requirements constraints
model.sense = repmat('=', nShifts, 1);
model.rhs   = shiftRequirements;
model.constrnames = Shifts;
model.A = sparse(nShifts, nVars);
for s = 1:nShifts
    for w = 1:nWorkers
        model.A(s, s+(w-1)*nShifts) = 1;
    end
end

% Save model
gurobi_write(model,'workforce3_m.lp');

% Optimize
params.logfile = 'workforce3_m.log';
```

(continues on next page)

(continued from previous page)

```
result = gurobi(model, params);

% Display results
if strcmp(result.status, 'OPTIMAL')
    % The code may enter here if you change some of the data... otherwise
    % this will never be executed.
    printsolution(result, Shifts, Workers)
else
    if strcmp(result.status, 'INFEASIBLE')
        penalties.lb  = inf(nVars, 1);
        penalties.ub  = inf(nVars, 1);
        penalties.rhs = ones(nShifts, 1);
        feasrelax     = gurobi_feasrelax(model, 0, false, penalties, params);
        result        = gurobi(feasrelax.model, params);
        if strcmp(result.status, 'OPTIMAL')
            printsolution(result, Shifts, Workers);
            fprintf('Slack value:\n');
            for j = nVars+1:length(result.x)
                if result.x(j) > 0.1
                    fprintf('\t%s, %g\n', feasrelax.model.varnames{j}, result.x(j));
                end
            end
        else
            fprintf('Unexpected status %s\n',result.status);
        end
    else
        % Just to handle user interruptions or other problems
        fprintf('Unexpected status %s\n',result.status);
    end
end

end

function printsolution(result, Shifts, Workers)
% Helper function to display results
nShifts = length(Shifts);
nWorkers = length(Workers);
fprintf('The optimal objective is %g\n', result.objval);
fprintf('Schedule:\n');
for s = 1:nShifts
    fprintf('\t%s:', Shifts{s});
    for w = 1:nWorkers
        if result.x(s+(w-1)*nShifts) > 0.9
            fprintf('%s ', Workers{w});
        end
    end
    fprintf('\n');
end
end
```

workforce4.m

```
function workforce4()

% Copyright 2026, Gurobi Optimization, LLC
%
% Assign workers to shifts; each worker may or may not be available on a
% particular day.  We use Pareto optimization to solve the model:
% first, we minimize the linear sum of the slacks. Then, we constrain
% the sum of the slacks, and we minimize a quadratic objective that
% tries to balance the workload among the workers.

% define data
nShifts  = 14;
nWorkers =  7;
nVars    = (nShifts + 1) * (nWorkers + 1) + nWorkers + 1;
avgShiftIdx = (nShifts+1)*(nWorkers+1);
totalSlackIdx = nVars;

Shifts  = {'Mon1'; 'Tue2'; 'Wed3'; 'Thu4'; 'Fri5'; 'Sat6'; 'Sun7';
    'Mon8'; 'Tue9'; 'Wed10'; 'Thu11'; 'Fri12'; 'Sat13'; 'Sun14'};
Workers = {'Amy'; 'Bob'; 'Cathy'; 'Dan'; 'Ed'; 'Fred'; 'Gu'};

shiftRequirements = [3; 2; 4; 4; 5; 6; 5; 2; 2; 3; 4; 6; 7; 5];

availability = [
    0 1 1 0 1 0 1 0 1 1 1 1 1 1;
    1 1 0 0 1 1 0 1 0 0 1 0 1 0;
    0 0 1 1 1 0 1 1 1 1 1 1 1 1;
    0 1 1 0 1 1 0 1 1 1 1 1 1 1;
    1 1 1 1 1 0 1 1 1 0 1 0 1 1;
    1 1 1 0 0 1 0 1 1 0 0 1 1 1;
    1 1 1 0 1 1 1 1 1 1 1 1 1 1
    ];

% Build model
model.modelname  = 'workforce4';
model.modelsense = 'min';

% Initialize assignment decision variables:
%    x[w][s] == 1 if worker w is assigned
%    to shift s. Since an assignment model always produces integer
%    solutions, we use continuous variables and solve as an LP.
model.vtype = repmat('C', nVars, 1);
model.lb    = zeros(nVars, 1);
model.ub    = ones(nVars, 1);
model.obj   = zeros(nVars, 1);

for w = 1:nWorkers
    for s = 1:nShifts
        model.varnames{s+(w-1)*nShifts} = sprintf('%s.%s', Workers{w}, Shifts{s});
        if availability(w, s) == 0
            model.ub(s+(w-1)*nShifts) = 0;
```

(continues on next page)

(continued from previous page)

```
        end
    end
end

% Initialize shift slack variables
for s = 1:nShifts
    model.varnames{s+nShifts*nWorkers} = sprintf('ShiftSlack_%s', Shifts{s});
    model.ub(s+nShifts*nWorkers) = inf;
end

% Initialize worker slack and diff variables
for w = 1:nWorkers
    model.varnames{w + nShifts * (nWorkers+1)} = sprintf('TotalShifts_%s', Workers{w});
    model.ub(w + nShifts * (nWorkers+1))       = inf;
    model.varnames{w + avgShiftIdx}            = sprintf('DiffShifts_%s', Workers{w});
    model.ub(w + avgShiftIdx)                  = inf;
    model.lb(w + avgShiftIdx)                  = -inf;
end

% Initialize average shift variable
model.ub((nShifts+1)*(nWorkers+1))       = inf;
model.varnames{(nShifts+1)*(nWorkers+1)} = 'AvgShift';

% Initialize total slack variable
model.ub(totalSlackIdx)       = inf;
model.varnames{totalSlackIdx} = 'TotalSlack';
model.obj(totalSlackIdx)      = 1;

% Set-up shift-requirements constraints with shift slack
model.sense = repmat('=', nShifts+1+nWorkers, 1);
model.rhs   = [shiftRequirements; zeros(1+nWorkers, 1)];
model.constrnames = Shifts;
model.A = sparse(nShifts+1+nWorkers, nVars);
for s = 1:nShifts
    for w = 1:nWorkers
        model.A(s, s+(w-1)*nShifts) = 1;
    end
    model.A(s, s + nShifts*nWorkers) = 1;
end

% Set TotalSlack equal to the sum of each shift slack
for s = 1:nShifts
    model.A(nShifts+1, s+nShifts*nWorkers) = -1;
end
model.A(nShifts+1, totalSlackIdx) = 1;
model.constrnames{nShifts+1} = 'TotalSlack';

% Set total number of shifts for each worker
for w = 1:nWorkers
    for s = 1:nShifts
        model.A(w + nShifts+1, s+(w-1)*nShifts) = -1;
    end
```

(continues on next page)

(continued from previous page)

```
    model.A(w + nShifts+1, w + nShifts * (nWorkers+1)) = 1;
    model.constrnames{nShifts+1+w} = sprintf('totShifts_%s', Workers{w});
end

% Save model
gurobi_write(model,'workforce4a_m.lp');

% Optimize
params.logfile = 'workforce4_m.log';
result = solveandprint(model, params, Shifts, Workers);
if ~strcmp(result.status, 'OPTIMAL')
    fprintf('Quit now\n');
    return;
end

% Constraint the slack by setting its upper and lower bounds
totalSlack = result.x(totalSlackIdx);
model.lb(totalSlackIdx) = totalSlack;
model.ub(totalSlackIdx) = totalSlack;

Rows = nShifts+1+nWorkers;
for w = 1:nWorkers
    model.A(Rows+w, w + nShifts * (nWorkers+1)) = 1;
    model.A(Rows+w, w + avgShiftIdx) = -1;
    model.A(Rows+w, avgShiftIdx) = -1;
    model.A(Rows+1+nWorkers, w + nShifts * (nWorkers+1)) = 1;
    model.rhs(Rows+w) = 0;
    model.sense(Rows+w) = '=';
    model.constrnames{Rows+w} = sprintf('DiffShifts_%s_AvgShift', Workers{w});
end
model.A(Rows+1+nWorkers, avgShiftIdx) = -nWorkers;
model.rhs(Rows+1+nWorkers) = 0;
model.sense(Rows+1+nWorkers) = '=';
model.constrnames{Rows+1+nWorkers} = 'AvgShift';

% Objective: minimize the sum of the square of the difference from the
% average number of shifts worked
model.obj = zeros(nVars, 1);
model.Q   = sparse(nVars, nVars);
for w = 1:nWorkers
    model.Q(avgShiftIdx + w, avgShiftIdx + w) = 1;
end

% model is no longer an assignment problem, enforce binary constraints
% on shift decision variables.
model.vtype(1:(nWorkers * nShifts), 1) = 'B';
model.vtype((nWorkers * nShifts + 1):nVars, 1) = 'C';

% Save modified model
gurobi_write(model,'workforce4b_m.lp');

% Optimize
```

(continues on next page)

(continued from previous page)

```
result = solveandprint(model, params, Shifts, Workers);
if ~strcmp(result.status, 'OPTIMAL')
    fprintf('Not optimal\n');
end

end

function result = solveandprint(model, params, Shifts, Workers)
% Helper function to solve and display results

nShifts = length(Shifts);
nWorkers = length(Workers);
result = gurobi(model, params);
if strcmp(result.status, 'OPTIMAL')
    fprintf('The optimal objective is %g\n', result.objval);
    fprintf('Schedule:\n');
    for s = 1:nShifts
        fprintf('\t%s:', Shifts{s});
        for w = 1:nWorkers
            if result.x(s+(w-1)*nShifts) > 0.9
                fprintf('%s ', Workers{w});
            end
        end
        fprintf('\n');
    end
    fprintf('Workload:\n');
    for w = 1:nWorkers
        fprintf('\t%s: %g\n', Workers{w}, result.x(w + nShifts * (nWorkers+1)));
    end
else
    fprintf('Optimization finished with status %s\n', result.status);
end
end
```

workforce5.m

```
function workforce5()

% Copyright 2026, Gurobi Optimization, LLC
%
% Assign workers to shifts; each worker may or may not be available on a
% particular day. We use multi-objective optimization to solve the model.
% The highest-priority objective minimizes the sum of the slacks
% (i.e., the total number of uncovered shifts). The secondary objective
% minimizes the difference between the maximum and minimum number of
% shifts worked among all workers.  The second optimization is allowed
% to degrade the first objective by up to the smaller value of 10% and 2

% define data
nShifts  = 14;
```

(continues on next page)

(continued from previous page)

```
nWorkers =  8;
nVars    = (nShifts + 1) * (nWorkers + 1) + 2;
minShiftIdx = (nShifts+1)*(nWorkers+1);
maxShiftIdx = minShiftIdx+1;
totalSlackIdx = nVars;

Shifts  = {'Mon1'; 'Tue2'; 'Wed3'; 'Thu4'; 'Fri5'; 'Sat6'; 'Sun7';
    'Mon8'; 'Tue9'; 'Wed10'; 'Thu11'; 'Fri12'; 'Sat13'; 'Sun14'};
Workers = {'Amy'; 'Bob'; 'Cathy'; 'Dan'; 'Ed'; 'Fred'; 'Gu'; 'Tobi'};

shiftRequirements = [3; 2; 4; 4; 5; 6; 5; 2; 2; 3; 4; 6; 7; 5];

availability = [
    0 1 1 0 1 0 1 0 1 1 1 1 1 1;
    1 1 0 0 1 1 0 1 0 0 1 0 1 0;
    0 0 1 1 1 0 1 1 1 1 1 1 1 1;
    0 1 1 0 1 1 0 1 1 1 1 1 1 1;
    1 1 1 1 1 0 1 1 1 0 1 0 1 1;
    1 1 1 0 0 1 0 1 1 0 0 1 1 1;
    0 1 1 1 0 1 1 0 1 1 1 0 1 1;
    1 1 1 0 1 1 1 1 1 1 1 1 1 1
    ];

% Build model
model.modelname  = 'workforce5';
model.modelsense = 'min';

% Initialize assignment decision variables:
%    x[w][s] == 1 if worker w is assigned
%    to shift s. Since an assignment model always produces integer
%    solutions, we use continuous variables and solve as an LP.
model.vtype = repmat('C', nVars, 1);
model.lb    = zeros(nVars, 1);
model.ub    = ones(nVars, 1);

for w = 1:nWorkers
    for s = 1:nShifts
        model.vtype(s+(w-1)*nShifts) = 'B';
        model.varnames{s+(w-1)*nShifts} = sprintf('%s.%s', Workers{w}, Shifts{s});
        if availability(w, s) == 0
            model.ub(s+(w-1)*nShifts) = 0;
        end
    end
end

% Initialize shift slack variables
for s = 1:nShifts
    model.varnames{s+nShifts*nWorkers} = sprintf('ShiftSlack_%s', Shifts{s});
    model.ub(s+nShifts*nWorkers) = inf;
end

% Initialize worker slack and diff variables
```

(continues on next page)

(continued from previous page)

```
for w = 1:nWorkers
    model.varnames{w + nShifts * (nWorkers+1)} = sprintf('TotalShifts_%s', Workers{w});
    model.ub(w + nShifts * (nWorkers+1))       = inf;
end

% Initialize min/max shift variables
model.ub(minShiftIdx)       = inf;
model.varnames{minShiftIdx} = 'MinShift';
model.ub(maxShiftIdx)       = inf;
model.varnames{maxShiftIdx} = 'MaxShift';

% Initialize total slack variable
model.ub(totalSlackIdx)       = inf;
model.varnames{totalSlackIdx} = 'TotalSlack';

% Set-up shift-requirements constraints with shift slack
model.sense = repmat('=', nShifts+1+nWorkers, 1);
model.rhs   = [shiftRequirements; zeros(1+nWorkers, 1)];
model.constrnames = Shifts;
model.A = sparse(nShifts+1+nWorkers, nVars);
for s = 1:nShifts
    for w = 1:nWorkers
        model.A(s, s+(w-1)*nShifts) = 1;
    end
    model.A(s, s + nShifts*nWorkers) = 1;
end

% Set TotalSlack equal to the sum of each shift slack
for s = 1:nShifts
    model.A(nShifts+1, s+nShifts*nWorkers) = -1;
end
model.A(nShifts+1, totalSlackIdx) = 1;
model.constrnames{nShifts+1} = 'TotalSlack';

% Set total number of shifts for each worker
for w = 1:nWorkers
    for s = 1:nShifts
        model.A(w + nShifts+1, s+(w-1)*nShifts) = -1;
    end
    model.A(w + nShifts+1, w + nShifts * (nWorkers+1)) = 1;
    model.constrnames{nShifts+1+w} = sprintf('totShifts_%s', Workers{w});
end

% Set minShift / maxShift general constraints
model.genconmin.resvar = minShiftIdx;
model.genconmin.name   = 'MinShift';
model.genconmax.resvar = maxShiftIdx;
model.genconmax.name   = 'MaxShift';
for w = 1:nWorkers
    model.genconmin.vars(w) = w + nShifts * (nWorkers+1);
    model.genconmax.vars(w) = w + nShifts * (nWorkers+1);
end
```

(continues on next page)

(continued from previous page)

```
% Set multiobjective
model.multiobj(1).objn                = zeros(nVars, 1);
model.multiobj(1).objn(totalSlackIdx) = 1;
model.multiobj(1).priority            = 2;
model.multiobj(1).weight              = 1;
model.multiobj(1).abstol              = 2;
model.multiobj(1).reltol              = 0.1;
model.multiobj(1).name                = 'TotalSlack';
model.multiobj(1).con                 = 0.0;
model.multiobj(2).objn                = zeros(nVars, 1);
model.multiobj(2).objn(minShiftIdx)   = -1;
model.multiobj(2).objn(maxShiftIdx)   = 1;
model.multiobj(2).priority            = 1;
model.multiobj(2).weight              = 1;
model.multiobj(2).abstol              = 0;
model.multiobj(2).reltol              = 0;
model.multiobj(2).name                = 'Fairness';
model.multiobj(2).con                 = 0.0;

% Save initial model
gurobi_write(model,'workforce5_m.lp');

% Optimize
params.logfile = 'workforce5_m.log';
result = solveandprint(model, params, Shifts, Workers);
if ~strcmp(result.status, 'OPTIMAL')
    fprintf('Not optimal\n');
end

end

function result = solveandprint(model, params, Shifts, Workers)
% Helper function to solve and display results

nShifts = length(Shifts);
nWorkers = length(Workers);
result = gurobi(model, params);
if strcmp(result.status, 'OPTIMAL')
    fprintf('The optimal objective is %g\n', result.objval);
    fprintf('Schedule:\n');
    for s = 1:nShifts
        fprintf('\t%s:', Shifts{s});
        for w = 1:nWorkers
            if result.x(s+(w-1)*nShifts) > 0.9
                fprintf('%s ', Workers{w});
            end
        end
        fprintf('\n');
    end
    fprintf('Workload:\n');
    for w = 1:nWorkers
```

(continues on next page)

(continued from previous page)

```
        fprintf('\t%s: %g\n', Workers{w}, result.x(w + nShifts * (nWorkers+1)));
    end
else
    fprintf('Optimization finished with status %s\n', result.status);
end
end
```

2.1.7 R Examples

This section includes source code for all of the Gurobi R examples. The same source code can be found in the `examples/R` directory of the Gurobi distribution.

bilinear.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example formulates and solves the following simple bilinear model:
#  maximize
#        x
#  subject to
#        x + y + z <= 10
#        x * y <= 2         (bilinear inequality)
#        x * z + y * z = 1  (bilinear equality)
#        x, y, z non-negative (x integral in second version)

library(gurobi)
library(Matrix)

model <- list()

# Linear constraint matrix
model$A <- matrix(c(1, 1, 1), nrow=1, byrow=T)
model$rhs <- c(10.0)
model$sense <- c('<')

# Variable names
model$varnames <- c('x', 'y', 'z')

# Objective function max 1.0 * x
model$obj <- c(1, 0, 0)
model$modelsense <- 'max'

# Bilinear inequality constraint: x * y <= 2
qc1 <- list()
qc1$Qc <- spMatrix(3, 3, c(1), c(2), c(1.0))
qc1$rhs <- 2.0
qc1$sense <- c('<')
qc1$name <- 'bilinear0'

# Bilinear equality constraint: x * z + y * z == 1
```

(continues on next page)

(continued from previous page)

```
qc2 <- list()
qc2$Qc <- spMatrix(3, 3, c(1, 2), c(3, 3), c(1.0, 1.0))
qc2$rhs <- 1.0
qc2$sense <- c('=')
qc2$name <- 'bilinear1'

model$quadcon <- list(qc1, qc2)

# Solve bilinear model, display solution.
result <- gurobi(model)
print(result$x)

# Constrain 'x' to be integral and solve again
model$vtype <- c('I', 'C', 'C')
result <- gurobi(model)
print(result$x)
```

diet.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Solve the classic diet model, showing how to add constraints
# to an existing model.

library(Matrix)
library(gurobi)

# display results
printSolution <- function(model, res, nCategories, nFoods) {
  if (res$status == 'OPTIMAL') {
    cat('\nCost: ',res$objval,'\nBuy:\n')
    for (j in nCategories + 1:nFoods) {
      if (res$x[j] > 1e-4) {
        cat(format(model$varnames[j],justify='left',width=10),':',
            format(res$x[j],justify='right',width=10,nsmall=2),'\n')
      }
    }
    cat('\nNutrition:\n')
    for (j in 1:nCategories) {
      cat(format(model$varnames[j],justify='left',width=10),':',
          format(res$x[j],justify='right',width=10,nsmall=2),'\n')
    }
  } else {
    cat('No solution\n')
  }
}

# define primitive data
Categories      <- c('calories', 'protein', 'fat', 'sodium')
nCategories     <- length(Categories)
```

(continues on next page)

(continued from previous page)

```
minNutrition    <- c(     1800 ,       91 ,    0 ,       0 )
maxNutrition    <- c(     2200 ,      Inf ,   65 ,    1779 )

Foods           <- c('hamburger', 'chicken', 'hot dog', 'fries', 'macaroni',
                     'pizza', 'salad', 'milk', 'ice cream')
nFoods          <- length(Foods)
cost            <- c(2.49, 2.89, 1.50, 1.89, 2.09, 1.99, 2.49, 0.89, 1.59)
nutritionValues <- c( 410, 24, 26 ,  730,
                      420, 32, 10 , 1190,
                      560, 20, 32 , 1800,
                      380,  4, 19 ,  270,
                      320, 12, 10 ,  930,
                      320, 15, 12 ,  820,
                      320, 31, 12 , 1230,
                      100,  8, 2.5,  125,
                      330,  8, 10 ,  180 )
# Build model
model     <- list()
model$A   <- spMatrix(nCategories, nCategories + nFoods,
               i = c(mapply(rep,1:4,1+nFoods)),
               j = c(1, (nCategories+1):(nCategories+nFoods),
                     2, (nCategories+1):(nCategories+nFoods),
                     3, (nCategories+1):(nCategories+nFoods),
                     4, (nCategories+1):(nCategories+nFoods) ),
               x = c(-1.0, nutritionValues[1 + nCategories*(0:(nFoods-1))],
                     -1.0, nutritionValues[2 + nCategories*(0:(nFoods-1))],
                     -1.0, nutritionValues[3 + nCategories*(0:(nFoods-1))],
                     -1.0, nutritionValues[4 + nCategories*(0:(nFoods-1))] ))
model$obj         <- c(rep(0, nCategories), cost)
model$lb          <- c(minNutrition, rep(0, nFoods))
model$ub          <- c(maxNutrition, rep(Inf, nFoods))
model$varnames    <- c(Categories, Foods)
model$rhs         <- rep(0,nCategories)
model$sense       <- rep('=',nCategories)
model$constrnames <- Categories
model$modelname   <- 'diet'
model$modelsense  <- 'min'

# Optimize
res <- gurobi(model)
printSolution(model, res, nCategories, nFoods)

# Adding constraint: at most 6 servings of dairy
# this is the matrix part of the constraint
B <- spMatrix(1, nCategories + nFoods,
              i = rep(1,2),
              j = (nCategories+c(8,9)),
              x = rep(1,2))
# append B to A
model$A           <- rbind(model$A,       B)
# extend row-related vectors
model$constrnames <- c(model$constrnames, 'limit_dairy')
```

(continues on next page)

(continued from previous page)

```
model$rhs         <- c(model$rhs,         6)
model$sense       <- c(model$sense,       '<')

# Optimize
res <- gurobi(model)
printSolution(model, res, nCategories, nFoods)

# Clear space
rm(res, model)
```

facility.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Facility location: a company currently ships its product from 5 plants
# to 4 warehouses. It is considering closing some plants to reduce
# costs. What plant(s) should the company close, in order to minimize
# transportation and fixed costs?
#
# Note that this example uses lists instead of dictionaries.  Since
# it does not work with sparse data, lists are a reasonable option.
#
# Based on an example from Frontline Systems:
#   http://www.solver.com/disfacility.htm
# Used with permission.

library(Matrix)
library(gurobi)

# define primitive data
nPlants     <- 5
nWarehouses <- 4
# Warehouse demand in thousands of units
Demand      <- c(15, 18, 14, 20)
# Plant capacity in thousands of units
Capacity    <- c(20, 22, 17, 19, 18)
# Fixed costs for each plant
FixedCosts  <- c( 12000, 15000, 17000, 13000, 16000)
# Transportation costs per thousand units
TransCosts  <- c(4000, 2000, 3000, 2500, 4500,
                 2500, 2600, 3400, 3000, 4000,
                 1200, 1800, 2600, 4100, 3000,
                 2200, 2600, 3100, 3700, 3200 )

flowidx <- function(w, p) {nPlants * (w-1) + p}

# Build model
model <- list()
model$modelname <- 'facility'
model$modelsense <- 'min'
```

(continues on next page)

(continued from previous page)

```
# initialize data for variables
model$lb       <- 0
model$ub       <- c(rep(1, nPlants),   rep(Inf, nPlants * nWarehouses))
model$vtype    <- c(rep('B', nPlants), rep('C', nPlants * nWarehouses))
model$obj      <- c(FixedCosts, TransCosts)
model$varnames <- c(paste0(rep('Open',nPlants),1:nPlants),
                    sprintf('Trans%d,%d',
                            c(mapply(rep,1:nWarehouses,nPlants)),
                            1:nPlants))

# build production constraint matrix
A1 <- spMatrix(nPlants, nPlants, i = c(1:nPlants), j = (1:nPlants), x = -Capacity)
A2 <- spMatrix(nPlants, nPlants * nWarehouses,
               i = c(mapply(rep, 1:nPlants, nWarehouses)),
               j = mapply(flowidx,1:nWarehouses,c(mapply(rep,1:nPlants,nWarehouses))),
               x = rep(1, nWarehouses * nPlants))
A3 <- spMatrix(nWarehouses, nPlants)
A4 <- spMatrix(nWarehouses, nPlants * nWarehouses,
               i = c(mapply(rep, 1:nWarehouses, nPlants)),
               j = mapply(flowidx,c(mapply(rep,1:nWarehouses,nPlants)),1:nPlants),
               x = rep(1, nPlants * nWarehouses))
model$A           <- rbind(cbind(A1, A2), cbind(A3, A4))
model$rhs         <- c(rep(0, nPlants),   Demand)
model$sense       <- c(rep('<', nPlants), rep('=', nWarehouses))
model$constrnames <- c(sprintf('Capacity%d',1:nPlants),
                       sprintf('Demand%d',1:nWarehouses))

# Save model
gurobi_write(model,'facilityR.lp')

# Guess at the starting point: close the plant with the highest fixed
# costs; open all others first open all plants
model$start <- c(rep(1,nPlants),rep(NA, nPlants * nWarehouses))

# find most expensive plant, and close it in mipstart
cat('Initial guess:\n')
worstidx <- which.max(FixedCosts)
model$start[worstidx] <- 0
cat('Closing plant',worstidx,'\n')

# set parameters
params <- list()
params$method <- 2

# Optimize
res <- gurobi(model, params)

# Print solution
if (res$status == 'OPTIMAL') {
  cat('\nTotal Costs:',res$objval,'\nsolution:\n')
  cat('Facilities:', model$varnames[which(res$x[1:nPlants]>1e-5)], '\n')
```

(continues on next page)

(continued from previous page)

```
  active <- nPlants + which(res$x[(nPlants+1):(nPlants*(nWarehouses+1))] > 1e-5)
  cat('Flows: ')
  cat(sprintf('%s=%g ',model$varnames[active], res$x[active]), '\n')
  rm(active)
} else {
  cat('No solution\n')
}

# Clear space
rm(res, model, params, A1, A2, A3, A4)
```

feasopt.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example reads a MIP model from a file, adds artificial
# variables to each constraint, and then minimizes the sum of the
# artificial variables.  A solution with objective zero corresponds
# to a feasible solution to the input model.
# We can also use FeasRelax feature to do it. In this example, we
# use minrelax=1, i.e. optimizing the returned model finds a solution
# that minimizes the original objective, but only from among those
# solutions that minimize the sum of the artificial variables.

library(Matrix)
library(gurobi)

args <- commandArgs(trailingOnly = TRUE)
if (length(args) < 1) {
  stop('Usage: Rscript feasopt.R filename\n')
}

# Set up parameters
params <- list()
params$logfile <- 'feasopt.log'

# Read model
cat('Reading model',args[1],'...')
model <- gurobi_read(args[1], params)
cat('... done\n')

# Create penalties
penalties     <- list()
penalties$lb  <- Inf
penalties$ub  <- Inf
penalties$rhs <- rep(1,length(model$rhs))

result <- gurobi_feasrelax(model, 0, TRUE, penalties, params = params)

# Display results
```

(continues on next page)

(continued from previous page)

```
if (result$feasobj > 1e-6) {
  cat('Model',args[1],'is infeasible within variable bounds\n')
} else {
  cat('Model',args[1],'is feasible\n')
}

# Clear space
rm(params, model, penalties, result)
```

fixanddive.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Implement a simple MIP heuristic.  Relax the model,
# sort variables based on fractionality, and fix the 25% of
# the fractional variables that are closest to integer variables.
# Repeat until either the relaxation is integer feasible or
# linearly infeasible.

library(Matrix)
library(gurobi)

args <- commandArgs(trailingOnly = TRUE)
if (length(args) < 1) {
  stop('Usage: Rscript fixanddive.R filename\n')
}

# Read model
cat('Reading model',args[1],'...')
model <- gurobi_read(args[1])
cat('... done\n')

# Detect set of non-continous variables
numvars    <- ncol(model$A)
intvars    <- which(model$vtype != 'C')
numintvars <- length(intvars)
if (numintvars < 1) {
  stop('All model\'s variables are continuous, nothing to do\n')
}

# create lb and ub if they do not exists, and set them to default values
if (!('lb' %in% model)) {
  model$lb <- numeric(numvars)
}
if (!('ub' %in% model)) {
  model$ub <- Inf + numeric(numvars)
}

# set all variables to continuous
ovtype                <- model$vtype
```

(continues on next page)

(continued from previous page)

```
model$vtype[1:numvars] <- 'C'

# parameters
params            <- list()
params$OutputFlag <- 0

result <- gurobi(model, params)

# Perform multiple iterations. In each iteration, identify the first
# quartile of integer variables that are closest to an integer value
# in the relaxation, fix them to the nearest integer, and repeat.
for (iter in 1:1000) {
  # See if status is optimal
  if (result$status != 'OPTIMAL') {
    cat('Model status is', result$status,'\n')
    cat('Cannot keep fixing variables\n')
    break
  }
  # collect fractionality of integer variables
  fractional  <- abs(result$x - floor(result$x+0.5))
  fractional  <- replace(fractional, fractional < 1e-5, 1)
  fractional  <- replace(fractional, ovtype == 'C', 1)
  fractional  <- replace(fractional, ovtype == 'S', 1)
  nfractional <- length(which(fractional<0.51))

  cat('Iteration:', iter, 'Obj:', result$objval,
      'Fractional:', nfractional, '\n')
  if (nfractional == 0) {
    cat('Found feasible solution - objective', result$objval, '\n')
    break
  }

  # order the set of fractional index
  select <- order(fractional, na.last = TRUE, decreasing = FALSE)

  # fix 25% of variables
  nfix <- as.integer(ceiling(nfractional  / 4))
  # cat('Will fix', nfix, 'variables, out of', numvars, '\n')
  if (nfix < 10)
    cat('Fixing ')
  else
    cat('Fixing',nfix,'variables, fractionality threshold:',fractional[select[nfix]],'\n
↪')
  for (k in 1:nfix) {
    j   <- select[k]
    val <- floor(result$x[j] + 0.5)
    model$lb[j] <- val
    model$ub[j] <- val
    if (nfix < 10)
      cat(model$varname[j],'x*=',result$x[j],'to',val,' ')
  }
  if (nfix < 10)
```

(continues on next page)

(continued from previous page)

```
    cat('\n')

  # reoptimize
  result <- gurobi(model, params)
}

# Clear space
rm(model, params, result)
```

gc_pwl.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example formulates and solves the following simple model
# with PWL constraints:
#
#  maximize
#        sum c(j) * x(j)
#  subject to
#        sum A(i,j) * x(j) <= 0,  for i = 1, ..., m
#        sum y(j) <= 3
#        y(j) = pwl(x(j)),        for j = 1, ..., n
#        x(j) free, y(j) >= 0,    for j = 1, ..., n
#
#  where pwl(x) = 0,     if x  = 0
#               = 1+|x|, if x != 0
#
#  Note
#   1. sum pwl(x(j)) <= b is to bound x vector and also to favor sparse x vector.
#      Here b = 3 means that at most two x(j) can be nonzero and if two, then
#      sum x(j) <= 1
#   2. pwl(x) jumps from 1 to 0 and from 0 to 1, if x moves from negative 0 to 0,
#      then to positive 0, so we need three points at x = 0. x has infinite bounds
#      on both sides, the piece defined with two points (-1, 2) and (0, 1) can
#      extend x to -infinite. Overall we can use five points (-1, 2), (0, 1),
#      (0, 0), (0, 1) and (1, 2) to define y = pwl(x)

library(gurobi)
library(Matrix)

n = 5

# A x <= 0
A <- rbind(c(0, 0, 0, 1, -1),
           c(0, 0, 1, 1, -1),
           c(1, 1, 0, 0, -1),
           c(1, 0, 1, 0, -1),
           c(1, 0, 0, 1, -1))

# sum y(j) <= 3
```

(continues on next page)

(continued from previous page)

```
y <- rbind(c(1, 1, 1, 1, 1))

# Initialize model
model <- list()

# Constraint matrix
model$A <- bdiag(A, y)

# Right-hand-side coefficient vector
model$rhs <- c(rep(0, n), 3)

# Objective function (x coefficients arbitrarily chosen)
model$obj <- c(0.5, 0.8, 0.5, 0.1, -1, rep(0, n))

# It's a maximization model
model$modelsense <- "max"

# Lower bounds for x and y
model$lb <- c(rep(-Inf, n), rep(0, n))

# PWL constraints
model$genconpwl <- list()
for (k in 1:n) {
    model$genconpwl[[k]]      <- list()
    model$genconpwl[[k]]$xvar <- k
    model$genconpwl[[k]]$yvar <- n + k
    model$genconpwl[[k]]$xpts <- c(-1, 0, 0, 0, 1)
    model$genconpwl[[k]]$ypts <- c(2, 1, 0, 1, 2)
}

# Solve the model and collect the results
result <- gurobi(model)

# Display solution values for x
for (k in 1:n)
    print(sprintf('x(%d) = %g', k, result$x[k]))

print(sprintf('Objective value: %g', result$objval))

# Clear space
rm(model, result)
```

genconstr.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# In this example we show the use of general constraints for modeling
# some common expressions. We use as an example a SAT-problem where we
# want to see if it is possible to satisfy at least four (or all) clauses
# of the logical form
#
# L = (x0 or ~x1 or x2)  and (x1 or ~x2 or x3)  and
#     (x2 or ~x3 or x0)  and (x3 or ~x0 or x1)  and
#     (~x0 or ~x1 or x2) and (~x1 or ~x2 or x3) and
#     (~x2 or ~x3 or x0) and (~x3 or ~x0 or x1)
#
# We do this by introducing two variables for each literal (itself and its
# negated value), one variable for each clause, one variable indicating
# whether we can satisfy at least four clauses, and one last variable to
# identify the minimum of the clauses (so if it is one, we can satisfy all
# clauses). Then we put these last two variables in the objective.
# The objective function is therefore
#
# maximize Obj0 + Obj1
#
#  Obj0 = MIN(Clause1, ... , Clause8)
#  Obj1 = 1 -> Clause1 + ... + Clause8 >= 4
#
# thus, the objective value will be two if and only if we can satisfy all
# clauses; one if and only if at least four but not all clauses can be satisfied,
# and zero otherwise.
#

library(Matrix)
library(gurobi)

# Set up parameters
params <- list()
params$logfile <- 'genconstr.log'

# define primitive data
nLiterals <- 4
nClauses  <- 8
nObj      <- 2
nVars     <- 2 * nLiterals + nClauses + nObj
Literal <- function(n) {n}
NotLit  <- function(n) {n + nLiterals}
Clause  <- function(n) {2 * nLiterals + n}
Obj     <- function(n) {2 * nLiterals + nClauses + n}

Clauses <- list(c(Literal(1), NotLit(2), Literal(3)),
                c(Literal(2), NotLit(3), Literal(4)),
                c(Literal(3), NotLit(4), Literal(1)),
                c(Literal(4), NotLit(1), Literal(2)),
                c(NotLit(1), NotLit(2), Literal(3)),
```

(continues on next page)

(continued from previous page)

```
                c(NotLit(2), NotLit(3), Literal(4)),
                c(NotLit(3), NotLit(4), Literal(1)),
                c(NotLit(4), NotLit(1), Literal(2)))


# Create model
model <- list()
model$modelname  <- 'genconstr'
model$modelsense <- 'max'

# Create objective function, variable names, and variable types
model$vtype    <- rep('B',nVars)
model$ub       <- rep(1,  nVars)
model$varnames <- c(sprintf('X%d',      seq(1,nLiterals)),
                    sprintf('notX%d',   seq(1,nLiterals)),
                    sprintf('Clause%d', seq(1,nClauses)),
                    sprintf('Obj%d',    seq(1,nObj)))
model$obj      <- c(rep(0, 2*nLiterals + nClauses), rep(1, nObj))

# Create linear constraints linking literals and not literals
model$A           <- spMatrix(nLiterals, nVars,
                      i = c(seq(1,nLiterals),
                            seq(1,nLiterals)),
                      j = c(seq(1,nLiterals),
                            seq(1+nLiterals,2*nLiterals)),
                      x = rep(1,2*nLiterals))
model$constrnames <- c(sprintf('CNSTR_X%d',seq(1,nLiterals)))
model$rhs         <- rep(1,   nLiterals)
model$sense       <- rep('=', nLiterals)

# Create OR general constraints linking clauses and literals
model$genconor <- lapply(1:nClauses,
                         function(i) list(resvar=Clause(i),
                                          vars  = Clauses[[i]],
                                          name  = sprintf('CNSTR_Clause%d',i)))

# Set up Obj1 = Min(Clause[1:nClauses])
model$genconmin <- list(list(resvar = Obj(1),
                             vars   = c(seq(Clause(1),Clause(nClauses))),
                             name   = 'CNSTR_Obj1'))


# the indicator constraint excepts the following vector types for the
# linear sum:
#
# - a dense vector, for example
#   c(rep(0, 2*nLiterals), rep(1, nClauses), rep(0,nObj))
# - a sparse vector, for example
#   sparseVector( x = rep(1,nClauses), i = (2*nLiterals+1):(2*nLiterals+nClauses),␣
↪length=nVars)
# - In case all coefficients are the same, you can pass a vector of length
#   one with the corresponding value which gets expanded to a dense vector
```

(continues on next page)

(continued from previous page)

```
#   with all values being the given one
#
# We use a sparse vector in this example
a <- sparseVector( x = rep(1,nClauses), i = (2*nLiterals+1):(2*nLiterals+nClauses),␣
↪length=nVars)

# Set up Obj2 to signal if any clause is satisfied, i.e.
# we use an indicator constraint of the form:
#     (Obj2 = 1) -> sum(Clause[1:nClauses]) >= 4
model$genconind <- list(list(binvar = Obj(2),
                             binval = 1,
                             a      = a,
                             sense  = '>',
                             rhs    = 4,
                             name   = 'CNSTR_Obj2'))

# Save model
gurobi_write(model, 'genconstr.lp', params)

# Optimize
result <- gurobi(model, params = params)

# Check optimization status
if (result$status == 'OPTIMAL') {
  if (result$objval > 1.9) {
    cat('Logical expression is satisfiable\n')
  } else if(result$objval > 0.9) {
    cat('At least four clauses are satisfiable\n')
  } else {
    cat('At most three clauses may be satisfiable\n')
  }
} else {
  cat('Optimization failed\n')
}

# Clear space
rm(model,result,params,Clauses)
```

lp.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example formulates and solves the following simple LP model:
#  maximize
#        x + 2 y + 3 z
#  subject to
#        x +   y       <= 1
#              y +   z <= 1

library(Matrix)
```

(continues on next page)

(continued from previous page)

```
library(gurobi)

model <- list()

model$A          <- matrix(c(1,1,0,0,1,1), nrow=2, byrow=T)
model$obj        <- c(1,2,3)
model$modelsense <- 'max'
model$rhs        <- c(1,1)
model$sense      <- c('<', '<')

result <- gurobi(model)

print(result$objval)
print(result$x)

# Second option for A - as a sparseMatrix (using the Matrix package)...

model$A <- spMatrix(2, 3, c(1, 1, 2, 2), c(1, 2, 2, 3), c(1, 1, 1, 1))

params <- list(Method=2, TimeLimit=100)

result <- gurobi(model, params)

print(result$objval)
print(result$x)

# Third option for A - as a sparse triplet matrix (using the slam package)...

model$A <- simple_triplet_matrix(c(1, 1, 2, 2), c(1, 2, 2, 3), c(1, 1, 1, 1))

params <- list(Method=2, TimeLimit=100)

result <- gurobi(model, params)

print(result$objval)
print(result$x)

# Clear space
rm(result, params, model)
```

lp2.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Formulate a simple linear program, solve it, and then solve it
# again using the optimal basis.

library(gurobi)

model <- list()
```

(continues on next page)

(continued from previous page)

```
model$A     <- matrix(c(1,3,4,8,2,3), nrow=2, byrow=T)
model$obj   <- c(1,2,3)
model$rhs   <- c(4,7)
model$sense <- c('>', '>')

# First solve - requires a few simplex iterations

result <- gurobi(model)

model$vbasis <- result$vbasis
model$cbasis <- result$cbasis

# Second solve - start from optimal basis, so no iterations

result <- gurobi(model)

# Clear space
rm(model, result)
```

lpmethod.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Solve a model with different values of the Method parameter;
# show which value gives the shortest solve time.

library(Matrix)
library(gurobi)

args <- commandArgs(trailingOnly = TRUE)
if (length(args) < 1) {
  stop('Usage: Rscript lpmethod.R filename\n')
}

# Read model
cat('Reading model',args[1],'...')
model <- gurobi_read(args[1])
cat('... done\n')

# Solve the model with different values of Method
params     <- list()
bestTime   <- Inf
bestMethod <- -1
for (i in 0:4) {
  params$method <- i
  res <- gurobi(model, params)
  if (res$status == 'OPTIMAL') {
    bestMethod       <- i
    bestTime         <- res$runtime
```

(continues on next page)

(continued from previous page)

```
    params$TimeLimit <- bestTime
  }
}

# Report which method was fastest
if (bestMethod == -1) {
  cat('Unable to solve this model\n')
} else {
  cat('Solved in', bestTime, 'seconds with Method:', bestMethod, '\n')
}

rm(params, model)
```

lpmod.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example reads an LP model from a file and solves it.
# If the model can be solved, then it finds the smallest positive variable,
# sets its upper bound to zero, and resultolves the model two ways:
# first with an advanced start, then without an advanced start
# (i.e. 'from scratch').

library(Matrix)
library(gurobi)

args <- commandArgs(trailingOnly = TRUE)
if (length(args) < 1) {
  stop('Usage: Rscript lpmod.R filename\n')
}

# Read model
cat('Reading model',args[1],'...')
model <- gurobi_read(args[1])
cat('... done\n')

# Determine whether it is an LP
if ('multiobj'  %in% names(model) ||
    'sos'       %in% names(model) ||
    'pwlobj'    %in% names(model) ||
    'cones'     %in% names(model) ||
    'quadcon'   %in% names(model) ||
    'genconstr' %in% names(model)   ) {
  stop('The model is not a linear program\n')
}

# Detect set of non-continuous variables
intvars    <- which(model$vtype != 'C')
numintvars <- length(intvars)
if (numintvars > 0) {
```

(continues on next page)

(continued from previous page)

```
  stop('problem is a MIP, nothing to do\n')
}

# Optimize
result <- gurobi(model)
if (result$status != 'OPTIMAL') {
  cat('This model cannot be solved because its optimization status is',
      result$status, '\n')
  stop('Stop now\n')
}

# Recover number of variables in model
numvars   <- ncol(model$A)

# Ensure bounds array is initialized
if (is.null(model$lb)) {
  model$lb <- rep(0, numvars)
}
if (is.null(model$ub)) {
  model$ub <- rep(Inf, numvars)
}

# Find smallest (non-zero) variable value with zero lower bound
x      <- replace(result$x, result$x < 1e-4, Inf)
x      <- replace(x, model$lb > 1e-6, Inf)
minVar <- which.min(x)
minVal <- x[minVar]

# Get variable name
varname <- ''
if (is.null(model$varnames)) {
  varname <- sprintf('C%d',minVar)
} else {
  varname <- model$varnames[minVar]
}

cat('\n*** Setting', varname, 'from', minVal, 'to zero ***\n\n')
model$ub[minVar] <- 0

# Set advance start basis information
model$vbasis <- result$vbasis
model$cbasis <- result$cbasis

result2   <- gurobi(model)
warmCount <- result2$itercount
warmTime  <- result2$runtime

# Reset-advance start information
model$vbasis <- NULL
model$cbasis <- NULL

result2   <- gurobi(model)
```

(continues on next page)

(continued from previous page)

```
coldCount <- result2$itercount
coldTime  <- result2$runtime

cat('\n*** Warm start:', warmCount, 'iterations,', warmTime, 'seconds\n')
cat('\n*** Cold start:', coldCount, 'iterations,', coldTime, 'seconds\n')

# Clear space
rm(model, result, result2)
```

mip.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example formulates and solves the following simple MIP model:
#  maximize
#        x +   y + 2 z
#  subject to
#        x + 2 y + 3 z <= 4
#        x +   y       >= 1
#        x, y, z binary

library(gurobi)

model <- list()

model$A          <- matrix(c(1,2,3,1,1,0), nrow=2, ncol=3, byrow=T)
model$obj        <- c(1,1,2)
model$modelsense <- 'max'
model$rhs        <- c(4,1)
model$sense      <- c('<', '>')
model$vtype      <- 'B'

params <- list(OutputFlag=0)

result <- gurobi(model, params)

print('Solution:')
print(result$objval)
print(result$x)

# Clear space
rm(model, result, params)
```

mip2.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example reads a MIP model from a file, solves it and
# prints the objective values from all feasible solutions
# generated while solving the MIP. Then it creates the fixed
# model and solves that model.

library(Matrix)
library(gurobi)

args <- commandArgs(trailingOnly = TRUE)
if (length(args) < 1) {
  stop('Usage: Rscript mip2.R filename\n')
}

# Read model
cat('Reading model',args[1],'...')
model <- gurobi_read(args[1])
cat('... done\n')

# Detect set of non-continous variables
numvars    <- dim(model$A)[[2]]
intvars    <- which(model$vtype != 'C')
numintvars <- length(intvars)
if (numintvars < 1) {
  stop('All model\'s variables are continuous, nothing to do\n')
}

# Optimize
params               <- list()
params$poolsolutions <- 20
result               <- gurobi(model, params)

# Capture solution information
if (result$status != 'OPTIMAL') {
  cat('Optimization finished with status', result$status, '\n')
  stop('Stop now\n')
}

# Iterate over the solutions
if ('pool' %in% names(result)) {
  solcount <- length(result$pool)
  for (k in 1:solcount) {
    cat('Solution', k, 'has objective:', result$pool[[k]]$objval, '\n')
  }
} else {
  solcount <- 1
  cat('Solution 1 has objective:', result$objval, '\n')
}

# Convert to fixed model
```

(continues on next page)

(continued from previous page)

```
for (j in 1:numvars) {
  if (model$vtype[j] != 'C') {
    t <- floor(result$x[j]+0.5)
    model$lb[j] <- t
    model$ub[j] <- t
  }
}

# Solve the fixed model
result2 <- gurobi(model, params)
if (result2$status != 'OPTIMAL') {
  stop('Error: fixed model isn\'t optimal\n')
}

if (abs(result$objval - result2$objval) > 1e-6 * (1 + abs(result$objval))) {
  stop('Error: Objective values differ\n')
}

# Print values of non-zero variables
for (j in 1:numvars) {
  if (abs(result2$x[j]) < 1e-6) next
  varnames <- ''
  if ('varnames' %in% names(model)) {
    varnames <- model$varnames[j]
  } else {
    varnames <- sprintf('X%d', j)
  }
  cat(format(varnames, justify='left', width=10),':',
      format(result2$x[j], justify='right', digits=2, width=10), '\n')
}

# Clear space
rm(model, params, result, result2)
```

multiobj.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Want to cover four different sets but subject to a common budget of
# elements allowed to be used. However, the sets have different priorities to
# be covered; and we tackle this by using multi-objective optimization.

library(Matrix)
library(gurobi)

# define primitive data
groundSetSize     <- 20
nSubSets          <- 4
Budget            <- 12
Set               <- list(
```

(continues on next page)

(continued from previous page)

```
    c( 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0 ),
    c( 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1 ),
    c( 0, 0, 0, 1, 1, 0, 1, 1, 0, 0, 0, 0, 0, 1, 1, 0, 1, 1, 0, 0 ),
    c( 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0 ) )
SetObjPriority    <- c(3, 2, 2, 1)
SetObjWeight      <- c(1.0, 0.25, 1.25, 1.0)

# Initialize model
model             <- list()
model$modelsense  <- 'max'
model$modelname   <- 'multiobj'

# Set variables, all of them are binary, with 0,1 bounds.
model$vtype       <- 'B'
model$lb          <- 0
model$ub          <- 1
model$varnames    <- paste(rep('El', groundSetSize), 1:groundSetSize, sep='')

# Build constraint matrix
model$A           <- spMatrix(1, groundSetSize,
                              i = rep(1,groundSetSize),
                              j = 1:groundSetSize,
                              x = rep(1,groundSetSize))
model$rhs         <- c(Budget)
model$sense       <- c('<')
model$constrnames <- c('Budget')

# Set multi-objectives
model$multiobj          <- list()
for (m in 1:nSubSets) {
  model$multiobj[[m]]          <- list()
  model$multiobj[[m]]$objn     <- Set[[m]]
  model$multiobj[[m]]$priority <- SetObjPriority[m]
  model$multiobj[[m]]$weight   <- SetObjWeight[m]
  model$multiobj[[m]]$abstol   <- m
  model$multiobj[[m]]$reltol   <- 0.01
  model$multiobj[[m]]$name     <- sprintf('Set%d', m)
  model$multiobj[[m]]$con      <- 0.0
}

# Save model
gurobi_write(model,'multiobj_R.lp')

# Set parameters
params               <- list()
params$PoolSolutions <- 100

# Optimize
result <- gurobi(model, params)

# Capture solution information
if (result$status != 'OPTIMAL') {
```

(continues on next page)

(continued from previous page)

```
  cat('Optimization finished with status', result$status, '\n')
  stop('Stop now\n')
}

# Print best solution
cat('Selected elements in best solution:\n')
for (e in 1:groundSetSize) {
  if(result$x[e] < 0.9) next
  cat(' El',e,sep='')
}
cat('\n')

# Iterate over the best 10 solutions
if ('pool' %in% names(result)) {
  solcount <- length(result$pool)
  cat('Number of solutions found:', solcount, '\n')
  if (solcount > 10) {
    solcount <- 10
  }
  cat('Objective values for first', solcount, 'solutions:\n')
  for (k in 1:solcount) {
    cat('Solution', k, 'has objective:', result$pool[[k]]$objval[1], '\n')
  }
} else {
  solcount <- 1
  cat('Number of solutions found:', solcount, '\n')
  cat('Solution 1 has objective:', result$objval, '\n')
}

# Clean up
rm(model, params, result)
```

params.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Use parameters that are associated with a model.
#
# A MIP is solved for a few seconds with different sets of parameters.
# The one with the smallest MIP gap is selected, and the optimization
# is resumed until the optimal solution is found.


library(Matrix)
library(gurobi)

args <- commandArgs(trailingOnly = TRUE)
if (length(args) < 1) {
  stop('Usage: Rscript params.R filename\n')
}
```

(continues on next page)

(continued from previous page)

```
# Read model
cat('Reading model',args[1],'...')
model <- gurobi_read(args[1])
cat('... done\n')

# Detect set of non-continuous variables
intvars    <- which(model$vtype != 'C')
numintvars <- length(intvars)
if (numintvars < 1) {
  stop('All model\'s variables are continuous, nothing to do\n')
}

# Set a 2 second time limit
params <- list()
params$TimeLimit <- 2
# Now solve the model with different values of MIPFocus
params$MIPFocus <- 0
result          <- gurobi(model, params)
bestgap         <- result$mipgap
bestparams      <- params
for (i in 1:3) {
  params$MIPFocus <- i
  result          <- gurobi(model, params)
  if (result$mipgap < bestgap) {
    bestparams <- params
    bestgap    <- result$mipgap
  }
}

# Finally, reset the time limit and Re-solve model to optimality
bestparams$TimeLimit <- Inf
result <- gurobi(model, bestparams)
cat('Solved with MIPFocus:', bestparams$MIPFocus, '\n')

# Clear space
rm(model, params, result, bestparams)
```

piecewise.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example considers the following separable, convex problem:
#
#  minimize
#        f(x) - y + g(z)
#  subject to
#        x + 2 y + 3 z   <= 4
#        x +   y         >= 1
#        x,    y,    z   <= 1
```

(continues on next page)

(continued from previous page)

```
#
# where f(u) = exp(-u) and g(u) = 2 u^2 - 4u, for all real u.  It
# formulates and solves a simpler LP model by approximating f and
# g with piecewise-linear functions.  Then it transforms the model
# into a MIP by negating the approximation for f, which gives
# a non-convex piecewise-linear function, and solves it again.

library(gurobi)

model <- list()

model$A     <- matrix(c(1,2,3,1,1,0), nrow=2, byrow=T)
model$obj   <- c(0,-1,0)
model$ub    <- c(1,1,1)
model$rhs   <- c(4,1)
model$sense <- c('<', '>')

# Uniformly spaced points in [0.0, 1.0]
u <- seq(from=0, to=1, by=0.01)

# First piecewise-linear function: f(x) = exp(-x)
pwl1     <- list()
pwl1$var <- 1
pwl1$x   <- u
pwl1$y   <- sapply(u, function(x) exp(-x))

# Second piecewise-linear function: g(z) = 2 z^2 - 4 z
pwl2     <- list()
pwl2$var <- 3
pwl2$x   <- u
pwl2$y   <- sapply(u, function(z) 2 * z * z - 4 * z)

model$pwlobj <- list(pwl1, pwl2)

result <- gurobi(model)

print(result$objval)
print(result$x)


# Negate piecewise-linear function on x, making it non-convex

model$pwlobj[[1]]$y <- sapply(u, function(x) -exp(-x))

result <- gurobi(model)
gurobi_write(model, "pwl.lp")

print(result$objval)
print(result$x)

# Clear space
rm(model, pwl1, pwl2, result)
```

poolsearch.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# We find alternative epsilon-optimal solutions to a given knapsack
# problem by using PoolSearchMode

library(Matrix)
library(gurobi)

# define primitive data
groundSetSize <- 10
objCoef       <- c(32, 32, 15, 15, 6, 6, 1, 1, 1, 1)
knapsackCoef  <- c(16, 16,  8,  8, 4, 4, 2, 2, 1, 1)
Budget        <- 33

# Initialize model
model             <- list()
model$modelsense  <- 'max'
model$modelname   <- 'poolsearch'

# Set variables
model$obj         <- objCoef
model$vtype       <- 'B'
model$lb          <- 0
model$ub          <- 1
model$varnames    <- sprintf('El%d', seq(1,groundSetSize))

# Build constraint matrix
model$A           <- spMatrix(1, groundSetSize,
                              i = rep(1,groundSetSize),
                              j = 1:groundSetSize,
                              x = knapsackCoef)
model$rhs         <- c(Budget)
model$sense       <- c('<')
model$constrnames <- c('Budget')

# Set poolsearch parameters
params                <- list()
params$PoolSolutions  <- 1024
params$PoolGap        <- 0.10
params$PoolSearchMode <- 2

# Save problem
gurobi_write(model, 'poolsearch_R.lp')

# Optimize
result <- gurobi(model, params)

# Capture solution information
if (result$status != 'OPTIMAL') {
  cat('Optimization finished with status', result$status, '\n')
  stop('Stop now\n')
```

(continues on next page)

(continued from previous page)

```
}

# Print best solution
cat('Selected elements in best solution:\n')
cat(model$varnames[which(result$x>=0.9)],'\n')

# Print all solution objectives and best furth solution
if ('pool' %in% names(result)) {
  solcount <- length(result$pool)
  cat('Number of solutions found:', solcount, '\n')
  cat('Objective values for first', solcount, 'solutions:\n')
  for (k in 1:solcount) {
    cat(result$pool[[k]]$objval,' ',sep='')
  }
  cat('\n')
  if (solcount >= 4) {
    cat('Selected elements in fourth best solution:\n')
    cat(model$varnames[which(result$pool[[4]]$poolnx >= 0.9)], '\n')
  }
} else {
  solcount <- 1
  cat('Number of solutions found:', solcount, '\n')
  cat('Solution 1 has objective:', result$objval, '\n')
}

# Clean up
rm(model, params, result)
```

qcp.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example formulates and solves the following simple QCP model:
#  maximize
#        x
#  subject to
#        x + y + z   =  1
#        x^2 + y^2 <= z^2  (second-order cone)
#        x^2 <= yz         (rotated second-order cone)
#        x, y, z non-negative

library(gurobi)
library(Matrix)

model <- list()

model$A          <- matrix(c(1,1,1), nrow=1, byrow=T)
model$modelsense <- 'max'
model$obj        <- c(1,0,0)
model$rhs        <- c(1)
```

(continues on next page)

(continued from previous page)

```
model$sense      <- c('=')

# First quadratic constraint: x^2 + y^2 - z^2 <= 0
qc1 <- list()
qc1$Qc <- spMatrix(3, 3, c(1, 2, 3), c(1, 2, 3), c(1.0, 1.0, -1.0))
qc1$rhs <- 0.0

# Second quadratic constraint: x^2 - yz <= 0
qc2 <- list()
qc2$Qc <- spMatrix(3, 3, c(1, 2), c(1, 3), c(1.0, -1.0))
qc2$rhs <- 0.0

model$quadcon <- list(qc1, qc2)

result <- gurobi(model)

print(result$objval)
print(result$x)

# Clear space
rm(model, result)
```

qp.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example formulates and solves the following simple QP model:
#  minimize
#        x^2 + x*y + y^2 + y*z + z^2 + 2 x
#  subject to
#        x + 2 y + 3z >= 4
#        x +   y      >= 1
#        x, y, z non-negative

library(gurobi)

model <- list()

model$A     <- matrix(c(1,2,3,1,1,0), nrow=2, byrow=T)
model$Q     <- matrix(c(1,0.5,0,0.5,1,0.5,0,0.5,1), nrow=3, byrow=T)
model$obj   <- c(2,0,0)
model$rhs   <- c(4,1)
model$sense <- c('>', '>')

result <- gurobi(model)

print(result$objval)
print(result$x)

model$vtype <- c('I', 'I', 'I')
```

(continues on next page)

(continued from previous page)

```
result <- gurobi(model)

print(result$objval)
print(result$x)

# Clear space
rm(model, result)
```

sensitivity.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# A simple sensitivity analysis example which reads a MIP model
# from a file and solves it. Then each binary variable is set
# to 1-X, where X is its value in the optimal solution, and
# the impact on the objective function value is reported.

library(Matrix)
library(gurobi)

args <- commandArgs(trailingOnly = TRUE)
if (length(args) < 1) {
  stop('Usage: Rscript sensitivity.R filename\n')
}

# Read model
cat('Reading model',args[1],'...')
model <- gurobi_read(args[1])
cat('... done\n')

# Detect set of non-continous variables
numvars    <- ncol(model$A)
intvars    <- which(model$vtype != 'C')
numintvars <- length(intvars)
if (numintvars < 1) {
  stop('All model\'s variables are continuous, nothing to do\n')
}
maxanalyze <- 10

# Optimize
result <- gurobi(model)

# Capture solution information
if (result$status != 'OPTIMAL') {
  cat('Optimization finished with status', result$status, '\n')
  stop('Stop now\n')
}
origx       <- result$x
origobjval  <- result$objval
```

(continues on next page)

(continued from previous page)

```
# create lb and ub if they do not exists, and set them to default values
if (!('lb' %in% names(model))) {
  model$lb <- numeric(numvars)
}
if (!('ub' %in% names(model))) {
  # This line is not needed, as we must have ub defined
  model$ub <- Inf + numeric(numvars)
}

# Disable output for subsequent solves
params            <- list()
params$OutputFlag <- 0

# We limit the sensitivity analysis to a maximum number of variables
numanalyze <- 0

# Iterate through unfixed binary variables in the model
for (j in 1:numvars) {
  if (model$vtype[j] != 'B' &&
      model$vtype[j] != 'I'   ) next
  if (model$vtype[j] == 'I') {
    if (model$lb[j] != 0.0)     next
    if (model$ub[j] != 1.0)     next
  } else {
    if (model$lb[j] > 0.0)      next
    if (model$ub[j] < 1.0)      next
  }

  # Update MIP start for all variables
  model$start <- origx

  # Set variable to 1-X, where X is its value in optimal solution
  if (origx[j] < 0.5) {
    model$start[j] <- 1
    model$lb[j]    <- 1
  } else {
    model$start[j] <- 0
    model$ub[j]    <- 0
  }

  # Optimize
  result <- gurobi(model, params)

  # Display result
  varnames <- ''
  if ('varnames' %in% names(model)) {
    varnames <- model$varnames[j]
  } else {
    varnames <- sprintf('%s%d', model$vtype[j], j)
  }
  gap <- 0
```

(continues on next page)

(continued from previous page)

```
  if (result$status != 'OPTIMAL') {
    gap <- Inf
  } else {
    gap <- result$objval - origobjval
  }
  cat('Objective sensitivity for variable', varnames, 'is', gap, '\n')

  # Restore original bounds
  model$lb[j] <- 0
  model$ub[j] <- 1

  numanalyze <- numanalyze + 1

  # Stop when we reached the maximum number of sensitivity analysis steps
  if (numanalyze >= maxanalyze) {
      cat('Limit sensitivity analysis to the first', maxanalyze, 'variables\n')
      break
  }
}

# Clear space
rm(model, params, result, origx)
```

sos.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# This example formulates and solves the following simple SOS model:
#  maximize
#        2 x + y + z
#  subject to
#        x1 = 0 or x2 = 0 (SOS1 constraint)
#        x1 = 0 or x3 = 0 (SOS1 constraint)
#        x1 <= 1, x2 <= 1, x3 <= 2

library(gurobi)

model <- list()

model$A          <- matrix(c(0,0,0), nrow=1, byrow=T)
model$obj        <- c(2,1,1)
model$modelsense <- 'max'
model$ub         <- c(1,1,2)
model$rhs        <- c(0)
model$sense      <- c('=')

# First SOS: x1 = 0 or x2 = 0
sos1 <- list()
sos1$type <- 1
sos1$index <- c(1, 2)
```

(continues on next page)

(continued from previous page)

```
sos1$weight <- c(1, 2)

# Second SOS: x1 = 0 or x3 = 0
sos2 <- list()
sos2$type <- 1
sos2$index <- c(1, 3)
sos2$weight <- c(1, 2)

model$sos <- list(sos1, sos2)

result <- gurobi(model)

print(result$objval)
print(result$x)

# Clear space
rm(model, result)
```

sudoku.R

```
#  Copyright 2026, Gurobi Optimization, LLC */
#
# Sudoku example.
#
# The Sudoku board is a 9x9 grid, which is further divided into a 3x3 grid
# of 3x3 grids.  Each cell in the grid must take a value from 0 to 9.
# No two grid cells in the same row, column, or 3x3 subgrid may take the
# same value.
#
# In the MIP formulation, binary variables x[i,j,v] indicate whether
# cell <i,j> takes value 'v'.  The constraints are as follows:
#   1. Each cell must take exactly one value (sum_v x[i,j,v] = 1)
#   2. Each value is used exactly once per row (sum_i x[i,j,v] = 1)
#   3. Each value is used exactly once per column (sum_j x[i,j,v] = 1)
#   4. Each value is used exactly once per 3x3 subgrid (sum_grid x[i,j,v] = 1)
#
# Input datasets for this example can be found in examples/data/sudoku*.
#

library(Matrix)
library(gurobi)

args <- commandArgs(trailingOnly = TRUE)
if (length(args) < 1) {
  stop('Usage: Rscript sudoku.R filename\n')
}

# Read input file
conn <- file(args[1], open='r')
if(!isOpen(conn)) {
```

(continues on next page)

(continued from previous page)

```
  cat('Could not read file',args[1],'\n')
  stop('Stop now\n')
}
linn <- readLines(conn)
close(conn)

# Ensure that all lines have the same length as the number of lines, and
# that the character set is the correct one.
# Load fixed positions in board
Dim    <- length(linn)
board  <- matrix(0, Dim, Dim, byrow = TRUE)
if (Dim != 9) {
  cat('Input file',args[1],'has',Dim,'lines instead of 9\n')
  stop('Stop now\n')
}
for (i in 1:Dim) {
  line <- strsplit(linn[[i]],split='')[[1]]
  if (length(line) != Dim) {
    cat('Input line',i,'has',length(line),'characters, expected',Dim,'\n')
    stop('Stop now\n')
  }
  for (j in 1:Dim) {
    if (line[[j]] != '.') {
      k <- as.numeric(line[[j]])
      if (k < 1 || k > Dim) {
        cat('Unexpected character in Input line',i,'character',j,'\n')
        stop('Stop now\n')
      } else {
        board[i,j] = k
      }
    }
  }
}

# Map X[i,j,k] into an index variable in the model
nVars  <- Dim * Dim * Dim
varIdx <- function(i,j,k) {i + (j-1) * Dim + (k-1) * Dim * Dim}

cat('Dataset grid:',Dim,'x',Dim,'\n')

# Set up parameters
params <- list()
params$logfile <- 'sudoku.log'

# Build model
model            <- list()
model$modelname  <- 'sudoku'
model$modelsense <- 'min'

# Create variable names, types, and bounds
model$vtype    <- 'B'
model$lb       <- rep(0,  nVars)
```

(continues on next page)

(continued from previous page)

```
model$ub       <- rep(1,  nVars)
model$varnames <- rep('', nVars)
for (i in 1:Dim) {
  for (j in 1:Dim) {
    for (k in 1:Dim) {
      if (board[i,j] == k) model$lb[varIdx(i,j,k)] = 1
      model$varnames[varIdx(i,j,k)] = paste0('X',i,j,k)
    }
  }
}

# Create (empty) constraints:
model$A           <- spMatrix(0,nVars)
model$rhs         <- c()
model$sense       <- c()
model$constrnames <- c()

# Each cell gets a value:
for (i in 1:Dim) {
  for (j in 1:Dim) {
    B <- spMatrix(1, nVars,
            i = rep(1,Dim),
            j = varIdx(i,j,1:Dim),
            x = rep(1,Dim))
    model$A           <- rbind(model$A, B)
    model$rhs         <- c(model$rhs, 1)
    model$sense       <- c(model$sense, '=')
    model$constrnames <- c(model$constrnames, paste0('OneValInCell',i,j))
  }
}

# Each value must appear once in each column
for (i in 1:Dim) {
  for (k in 1:Dim) {
    B <- spMatrix(1, nVars,
            i = rep(1,Dim),
            j = varIdx(i,1:Dim,k),
            x = rep(1,Dim))
    model$A           <- rbind(model$A, B)
    model$rhs         <- c(model$rhs, 1)
    model$sense       <- c(model$sense, '=')
    model$constrnames <- c(model$constrnames, paste0('OnceValueInRow',i,k))
  }
}

#Each value must appear once in each row
for (j in 1:Dim) {
  for (k in 1:Dim) {
    B <- spMatrix(1, nVars,
            i = rep(1,Dim),
            j = varIdx(1:Dim,j,k),
            x = rep(1,Dim))
```

(continues on next page)

(continued from previous page)

```
    model$A           <- rbind(model$A, B)
    model$rhs         <- c(model$rhs, 1)
    model$sense       <- c(model$sense, '=')
    model$constrnames <- c(model$constrnames, paste0('OnceValueInColumn',j,k))
  }
}

# Each value must appear once in each subgrid
SubDim <- 3
for (k in 1:Dim) {
  for (g1 in 1:SubDim) {
    for (g2 in 1:SubDim) {
      B <- spMatrix(1, nVars,
              i = rep(1,Dim),
              j = c(varIdx(1+(g1-1)*SubDim,(g2-1)*SubDim + 1:SubDim, k),
                    varIdx(2+(g1-1)*SubDim,(g2-1)*SubDim + 1:SubDim, k),
                    varIdx(3+(g1-1)*SubDim,(g2-1)*SubDim + 1:SubDim, k)),
              x = rep(1,Dim))
      model$A           <- rbind(model$A, B)
      model$rhs         <- c(model$rhs, 1)
      model$sense       <- c(model$sense, '=')
      model$constrnames <- c(model$constrnames,
                             paste0('OnceValueInSubGrid',g1,g2,k))
    }
  }
}

# Save model
gurobi_write(model, 'sudoku.lp', params)

# Optimize model
result <- gurobi(model, params =  params)

if (result$status == 'OPTIMAL') {
  cat('Solution:\n')
  cat('---------------------------------\n')
  for (i in 1:Dim) {
    for (j in 1:Dim) {
      if (j %% SubDim == 1) cat('| ')
      for (k in 1:Dim) {
        if (result$x[varIdx(i,j,k)] > 0.99) {
          cat(k,' ')
        }
      }
    }
    cat('|\n')
    if (i %% SubDim == 0) cat('---------------------------------\n')
  }
} else {
  cat('Problem was infeasible\n')
}
```

(continues on next page)

(continued from previous page)

```
# Clear space
rm(result, model, board, linn, params)
```

workforce1.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Assign workers to shifts; each worker may or may not be available on a
# particular day. If the problem cannot be solved, use IIS to find a set of
# conflicting constraints. Note that there may be additional conflicts
# besides what is reported via IIS.

library(Matrix)
library(gurobi)

# define data
nShifts  <- 14
nWorkers <-  7
nVars    <- nShifts * nWorkers
varIdx   <- function(w,s) {s+(w-1)*nShifts}

Shifts  <- c('Mon1', 'Tue2', 'Wed3', 'Thu4', 'Fri5', 'Sat6', 'Sun7',
             'Mon8', 'Tue9', 'Wed10', 'Thu11', 'Fri12', 'Sat13', 'Sun14')
Workers <- c( 'Amy', 'Bob', 'Cathy', 'Dan', 'Ed', 'Fred', 'Gu' )

pay     <- c(10, 12, 10, 8, 8, 9, 11 )

shiftRequirements <- c(3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 )

availability <- list( c( 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 ),
                      c( 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 ),
                      c( 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 ),
                      c( 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 ),
                      c( 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 ),
                      c( 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 ),
                      c( 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 ) )

# Set up parameters
params <- list()
params$logfile <- 'workforce1.log'

# Build model
model            <- list()
model$modelname  <- 'workforce1'
model$modelsense <- 'min'

# Initialize assignment decision variables:
#    x[w][s] == 1 if worker w is assigned
#    to shift s. Since an assignment model always produces integer
#    solutions, we use continuous variables and solve as an LP.
```

(continues on next page)

(continued from previous page)

```
model$lb       <- 0
model$ub       <- rep(1, nVars)
model$obj      <- rep(0, nVars)
model$varnames <- rep('',nVars)
for (w in 1:nWorkers) {
  for (s in 1:nShifts) {
    model$varnames[varIdx(w,s)] = paste0(Workers[w],'.',Shifts[s])
    model$obj[varIdx(w,s)]      = pay[w]
    if (availability[[w]][s] == 0) model$ub[varIdx(w,s)] = 0
  }
}

# Set up shift-requirements constraints
model$A           <- spMatrix(nShifts,nVars,
                      i = c(mapply(rep,1:nShifts,nWorkers)),
                      j = mapply(varIdx,1:nWorkers,
                                 mapply(rep,1:nShifts,nWorkers)),
                      x = rep(1,nShifts * nWorkers))
model$sense       <- rep('=',nShifts)
model$rhs         <- shiftRequirements
model$constrnames <- Shifts

# Save model
gurobi_write(model,'workforce1.lp', params)

# Optimize
result <- gurobi(model, params = params)

# Display results
if (result$status == 'OPTIMAL') {
# The code may enter here if you change some of the data... otherwise
# this will never be executed.
  cat('The optimal objective is',result$objval,'\n')
  cat('Schedule:\n')
  for (s in 1:nShifts) {
    cat('\t',Shifts[s],':')
    for (w in 1:nWorkers) {
      if (result$x[varIdx(w,s)] > 0.9) cat(Workers[w],' ')
    }
    cat('\n')
  }
} else if (result$status == 'INFEASIBLE') {
# Find ONE IIS
  cat('Problem is infeasible.... computing IIS\n')
  iis <- gurobi_iis(model, params = params)
  if (iis$minimal) cat('IIS is minimal\n')
  else             cat('IIS is not minimal\n')
  cat('Rows in IIS: ', model$constrnames[iis$Arows])
  cat('\nLB in IIS: ', model$varnames[iis$lb])
  cat('\nUB in IIS: ', model$varnames[iis$ub])
  cat('\n')
  rm(iis)
```

(continues on next page)

(continued from previous page)

```
} else {
# Just to handle user interruptions or other problems
  cat('Unexpected status',result$status,'\nEnding now\n')
}

#Clear space
rm(model, params, availability, Shifts, Workers, pay, shiftRequirements, result)
```

workforce2.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Assign workers to shifts; each worker may or may not be available on a
# particular day. If the problem cannot be solved, use IIS iteratively to
# find all conflicting constraints.

library(Matrix)
library(gurobi)

# Function to display results
printsolution <- function(result) {
  if(result$status == 'OPTIMAL') {
    cat('The optimal objective is',result$objval,'\n')
    cat('Schedule:\n')
    for (s in 1:nShifts) {
      cat('\t',Shifts[s],':')
      for (w in 1:nWorkers) {
        if (result$x[varIdx(w,s)] > 0.9) cat(Workers[w],' ')
      }
      cat('\n')
    }
  }
}

# define data
nShifts  <- 14
nWorkers <-  7
nVars    <- nShifts * nWorkers
varIdx   <- function(w,s) {s+(w-1)*nShifts}

Shifts  <- c('Mon1', 'Tue2', 'Wed3', 'Thu4', 'Fri5', 'Sat6', 'Sun7',
             'Mon8', 'Tue9', 'Wed10', 'Thu11', 'Fri12', 'Sat13', 'Sun14')
Workers <- c( 'Amy', 'Bob', 'Cathy', 'Dan', 'Ed', 'Fred', 'Gu' )

pay     <- c(10, 12, 10, 8, 8, 9, 11 )

shiftRequirements <- c(3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 )

availability <- list( c( 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 ),
                      c( 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 ),
```

(continues on next page)

(continued from previous page)

```
                    c( 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 ),
                    c( 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 ),
                    c( 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 ),
                    c( 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 ),
                    c( 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 ) )

# Set up parameters
params <- list()
params$logfile <- 'workforce2.log'

# Build model
model            <- list()
model$modelname  <- 'workforce2'
model$modelsense <- 'min'

# Initialize assignment decision variables:
#    x[w][s] == 1 if worker w is assigned
#    to shift s. Since an assignment model always produces integer
#    solutions, we use continuous variables and solve as an LP.
model$lb       <- 0
model$ub       <- rep(1, nVars)
model$obj      <- rep(0, nVars)
model$varnames <- rep('',nVars)
for (w in 1:nWorkers) {
  for (s in 1:nShifts) {
    model$varnames[varIdx(w,s)] = paste0(Workers[w],'.',Shifts[s])
    model$obj[varIdx(w,s)]      = pay[w]
    if (availability[[w]][s] == 0) model$ub[varIdx(w,s)] = 0
  }
}

# Set up shift-requirements constraints
model$A           <- spMatrix(nShifts,nVars,
                      i = c(mapply(rep,1:nShifts,nWorkers)),
                      j = mapply(varIdx,1:nWorkers,
                                 mapply(rep,1:nShifts,nWorkers)),
                      x = rep(1,nShifts * nWorkers))
model$sense       <- rep('=',nShifts)
model$rhs         <- shiftRequirements
model$constrnames <- Shifts

# Save model
gurobi_write(model,'workforce2.lp', params)

# Optimize
result <- gurobi(model, params = params)

# Display results
if (result$status == 'OPTIMAL') {
# The code may enter here if you change some of the data... otherwise
# this will never be executed.
  printsolution(result);
```

(continues on next page)

(continued from previous page)

```
} else if (result$status == 'INFEASIBLE') {
# We will loop until we reduce a model that can be solved
  numremoved <- 0
  while(result$status == 'INFEASIBLE') {
    iis              <- gurobi_iis(model, params = params)
    keep             <- (!iis$Arows)
    cat('Removing rows',model$constrnames[iis$Arows],'...\n')
    model$A          <- model$A[keep,,drop = FALSE]
    model$sense      <- model$sense[keep]
    model$rhs        <- model$rhs[keep]
    model$constrnames <- model$constrnames[keep]
    numremoved       <- numremoved + 1
    gurobi_write(model, paste0('workforce2-',numremoved,'.lp'), params)
    result           <- gurobi(model, params = params)
  }
  printsolution(result)
  rm(iis)
} else {
# Just to handle user interruptions or other problems
  cat('Unexpected status',result$status,'\nEnding now\n')
}

#Clear space
rm(model, params, availability, Shifts, Workers, pay, shiftRequirements, result)
```

workforce3.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Assign workers to shifts; each worker may or may not be available on a
# particular day. If the problem cannot be solved, relax the model
# to determine which constraints cannot be satisfied, and how much
# they need to be relaxed.

library(Matrix)
library(gurobi)

# Function to display results
printsolution <- function(result) {
  if(result$status == 'OPTIMAL') {
    cat('The optimal objective is',result$objval,'\n')
    cat('Schedule:\n')
    for (s in 1:nShifts) {
      cat('\t',Shifts[s],':')
      for (w in 1:nWorkers) {
        if (result$x[varIdx(w,s)] > 0.9) cat(Workers[w],' ')
      }
      cat('\n')
    }
  }
```

(continues on next page)

(continued from previous page)

```
}

# define data
nShifts  <- 14
nWorkers <-  7
nVars    <- nShifts * nWorkers
varIdx   <- function(w,s) {s+(w-1)*nShifts}

Shifts  <- c('Mon1', 'Tue2', 'Wed3', 'Thu4', 'Fri5', 'Sat6', 'Sun7',
             'Mon8', 'Tue9', 'Wed10', 'Thu11', 'Fri12', 'Sat13', 'Sun14')
Workers <- c( 'Amy', 'Bob', 'Cathy', 'Dan', 'Ed', 'Fred', 'Gu' )

pay     <- c(10, 12, 10, 8, 8, 9, 11 )

shiftRequirements <- c(3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 )

availability <- list( c( 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 ),
                      c( 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 ),
                      c( 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 ),
                      c( 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 ),
                      c( 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 ),
                      c( 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 ),
                      c( 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 ) )

# Set up parameters
params <- list()
params$logfile <- 'workforce3.log'

# Build model
model            <- list()
model$modelname  <- 'workforce3'
model$modelsense <- 'min'

# Initialize assignment decision variables:
#    x[w][s] == 1 if worker w is assigned
#    to shift s. Since an assignment model always produces integer
#    solutions, we use continuous variables and solve as an LP.
model$lb       <- 0
model$ub       <- rep(1, nVars)
model$obj      <- rep(0, nVars)
model$varnames <- rep('',nVars)
for (w in 1:nWorkers) {
  for (s in 1:nShifts) {
    model$varnames[varIdx(w,s)] = paste0(Workers[w],'.',Shifts[s])
    model$obj[varIdx(w,s)]      = pay[w]
    if (availability[[w]][s] == 0) model$ub[varIdx(w,s)] = 0
  }
}

# Set up shift-requirements constraints
model$A          <- spMatrix(nShifts,nVars,
                     i = c(mapply(rep,1:nShifts,nWorkers)),
```

(continues on next page)

(continued from previous page)

```
                    j = mapply(varIdx,1:nWorkers,
                               mapply(rep,1:nShifts,nWorkers)),
                    x = rep(1,nShifts * nWorkers))
model$sense       <- rep('=',nShifts)
model$rhs         <- shiftRequirements
model$constrnames <- Shifts

# Save model
gurobi_write(model,'workforce3.lp', params)

# Optimize
result <- gurobi(model, params = params)

# Display results
if (result$status == 'OPTIMAL') {
# The code may enter here if you change some of the data... otherwise
# this will never be executed.
  printsolution(result);
} else if (result$status == 'INFEASIBLE') {
# Use gurobi_feasrelax to find out which copnstraints should be relaxed
# and by how much to make the problem feasible.
  penalties     <- list()
  penalties$lb  <- Inf
  penalties$ub  <- Inf
  penalties$rhs <- rep(1,length(model$rhs))
  feasrelax     <- gurobi_feasrelax(model, 0, FALSE, penalties, params = params)
  result        <- gurobi(feasrelax$model, params = params)
  if (result$status == 'OPTIMAL') {
    printsolution(result)
    cat('Slack values:\n')
    for (j in (nVars+1):length(result$x)) {
      if(result$x[j] > 0.1)
        cat('\t',feasrelax$model$varnames[j],result$x[j],'\n')
    }
  } else {
    cat('Unexpected status',result$status,'\nEnding now\n')
  }
  rm(penalties, feasrelax)
} else {
# Just to handle user interruptions or other problems
  cat('Unexpected status',result$status,'\nEnding now\n')
}

#Clear space
rm(model, params, availability, Shifts, Workers, pay, shiftRequirements, result)
```

workforce4.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Assign workers to shifts; each worker may or may not be available on a
# particular day.  We use Pareto optimization to solve the model:
# first, we minimize the linear sum of the slacks. Then, we constrain
# the sum of the slacks, and we minimize a quadratic objective that
# tries to balance the workload among the workers.

library(Matrix)
library(gurobi)

# define data
nShifts       <- 14
nWorkers      <-  7
nVars         <- (nShifts + 1) * (nWorkers + 1) + nWorkers + 1
varIdx        <- function(w,s) {s+(w-1)*nShifts}
shiftSlackIdx <- function(s) {s+nShifts*nWorkers}
totShiftIdx   <- function(w) {w + nShifts * (nWorkers+1)}
avgShiftIdx   <- ((nShifts+1)*(nWorkers+1))
diffShiftIdx  <- function(w) {w + avgShiftIdx}
totalSlackIdx <- nVars


Shifts  <- c('Mon1', 'Tue2', 'Wed3', 'Thu4', 'Fri5', 'Sat6', 'Sun7',
             'Mon8', 'Tue9', 'Wed10', 'Thu11', 'Fri12', 'Sat13', 'Sun14')
Workers <- c( 'Amy', 'Bob', 'Cathy', 'Dan', 'Ed', 'Fred', 'Gu' )

shiftRequirements <- c(3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 )

availability <- list( c( 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 ),
                      c( 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 ),
                      c( 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 ),
                      c( 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 ),
                      c( 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 ),
                      c( 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 ),
                      c( 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 ) )

# Function to display results
solveandprint <- function(model, params) {
  result <- gurobi(model, params = params)
  if(result$status == 'OPTIMAL') {
    cat('The optimal objective is',result$objval,'\n')
    cat('Schedule:\n')
    for (s in 1:nShifts) {
      cat('\t',Shifts[s],':')
      for (w in 1:nWorkers) {
        if (result$x[varIdx(w,s)] > 0.9) cat(Workers[w],' ')
      }
      cat('\n')
    }
    cat('Workload:\n')
```

(continues on next page)

(continued from previous page)

```
    for (w in 1:nWorkers) {
      cat('\t',Workers[w],':',result$x[totShiftIdx(w)],'\n')
    }
  } else {
    cat('Optimization finished with status',result$status)
  }
  result
}

# Set up parameters
params <- list()
params$logfile <- 'workforce4.log'

# Build model
model            <- list()
model$modelname  <- 'workforce4'
model$modelsense <- 'min'

# Initialize assignment decision variables:
#    x[w][s] == 1 if worker w is assigned to shift s.
#    This is no longer a pure assignment model, so we must
#    use binary variables.
model$vtype    <- rep('C', nVars)
model$lb       <- rep(0, nVars)
model$ub       <- rep(1, nVars)
model$obj      <- rep(0, nVars)
model$varnames <- rep('',nVars)
for (w in 1:nWorkers) {
  for (s in 1:nShifts) {
    model$vtype[varIdx(w,s)]    = 'B'
    model$varnames[varIdx(w,s)] = paste0(Workers[w],'.',Shifts[s])
    if (availability[[w]][s] == 0) model$ub[varIdx(w,s)] = 0
  }
}

# Initialize shift slack variables
for (s in 1:nShifts) {
  model$varnames[shiftSlackIdx(s)] = paste0('ShiftSlack',Shifts[s])
  model$ub[shiftSlackIdx(s)] = Inf
}

# Initialize worker slack and diff variables
for (w in 1:nWorkers) {
  model$varnames[totShiftIdx(w)] = paste0('TotalShifts',Workers[w])
  model$ub[totShiftIdx(w)]       = Inf
  model$varnames[diffShiftIdx(w)]  = paste0('DiffShifts',Workers[w])
  model$ub[diffShiftIdx(w)]        = Inf
  model$lb[diffShiftIdx(w)]        = -Inf
}

#Initialize average shift variable
model$ub[avgShiftIdx]      = Inf
```

(continues on next page)

(continued from previous page)

```
model$varnames[avgShiftIdx] = 'AvgShift'

#Initialize total slack variable
model$ub[totalSlackIdx]      = Inf
model$varnames[totalSlackIdx] = 'TotalSlack'
model$obj[totalSlackIdx]     = 1

# Set up shift-requirements constraints
model$A           <- spMatrix(nShifts,nVars,
                      i = c(c(mapply(rep,1:nShifts,nWorkers)),
                            c(1:nShifts)),
                      j = c(mapply(varIdx,1:nWorkers,
                                   mapply(rep,1:nShifts,nWorkers)),
                            shiftSlackIdx(1:nShifts)),
                      x = rep(1,nShifts * (nWorkers+1)))
model$sense       <- rep('=',nShifts)
model$rhs         <- shiftRequirements
model$constrnames <- Shifts

# Set TotalSlack equal to the sum of each shift slack
B <- spMatrix(1, nVars,
        i = rep(1,nShifts+1),
        j = c(shiftSlackIdx(1:nShifts),totalSlackIdx),
        x = c(rep(1,nShifts),-1))
model$A           <- rbind(model$A, B)
model$rhs         <- c(model$rhs,0)
model$sense       <- c(model$sense,'=')
model$constrnames <- c(model$constrnames, 'TotalSlack')

# Set total number of shifts for each worker
B <- spMatrix(nWorkers, nVars,
          i = c(mapply(rep,1:nWorkers,nShifts),
                1:nWorkers),
          j = c(mapply(varIdx,c(mapply(rep,1:nWorkers,nShifts)),1:nShifts),
                totShiftIdx(1:nWorkers)),
          x = c(rep(1,nShifts*nWorkers),rep(-1,nWorkers)))
model$A           <- rbind(model$A, B)
model$rhs         <- c(model$rhs,rep(0,nWorkers))
model$sense       <- c(model$sense,rep('=',nWorkers))
model$constrnames <- c(model$constrnames, sprintf('TotalShifts%s',Workers[1:nWorkers]))

# Save initial model
gurobi_write(model,'workforce4.lp', params)

# Optimize
result <- solveandprint(model, params)
if (result$status != 'OPTIMAL') stop('Stop now\n')

# Constraint the slack by setting its upper and lower bounds
totalSlack <- result$x[totalSlackIdx]
model$lb[totalSlackIdx] = totalSlack
model$ub[totalSlackIdx] = totalSlack
```

(continues on next page)

(continued from previous page)

```
# Link average number of shifts worked and difference with average
B <- spMatrix(nWorkers+1, nVars,
        i = c(1:nWorkers,
              1:nWorkers,
              1:nWorkers,
              rep(nWorkers+1,nWorkers+1)),
        j = c(totShiftIdx(1:nWorkers),
              diffShiftIdx(1:nWorkers),
              rep(avgShiftIdx,nWorkers),
              totShiftIdx(1:nWorkers),avgShiftIdx),
        x = c(rep(1, nWorkers),
              rep(-1,nWorkers),
              rep(-1,nWorkers),
              rep(1,nWorkers),-nWorkers))
model$A           <- rbind(model$A, B)
model$rhs         <- c(model$rhs,rep(0,nWorkers+1))
model$sense       <- c(model$sense,rep('=',nWorkers+1))
model$constrnames <- c(model$constrnames,
                       sprintf('DiffShifts%s',Workers[1:nWorkers]),
                       'AvgShift')

# Objective: minimize the sum of the square of the difference from the
# average number of shifts worked
model$obj <- 0
model$Q   <- spMatrix(nVars,nVars,
                i = c(diffShiftIdx(1:nWorkers)),
                j = c(diffShiftIdx(1:nWorkers)),
                x = rep(1,nWorkers))

# Save modified model
gurobi_write(model,'workforce4b.lp', params)

# Optimize
result <- solveandprint(model, params)
if (result$status != 'OPTIMAL') stop('Stop now\n')

#Clear space
rm(model, params, availability, Shifts, Workers, shiftRequirements, result)
```

workforce5.R

```
# Copyright 2026, Gurobi Optimization, LLC
#
# Assign workers to shifts; each worker may or may not be available on a
# particular day. We use multi-objective optimization to solve the model.
# The highest-priority objective minimizes the sum of the slacks
# (i.e., the total number of uncovered shifts). The secondary objective
# minimizes the difference between the maximum and minimum number of
# shifts worked among all workers.  The second optimization is allowed
```

(continues on next page)

(continued from previous page)

```
# to degrade the first objective by up to the smaller value of 10% and 2

library('Matrix')
library('gurobi')

# define data
nShifts       <- 14
nWorkers      <-  8
nVars         <- (nShifts + 1) * (nWorkers + 1) + 2
varIdx        <- function(w,s) {s+(w-1)*nShifts}
shiftSlackIdx <- function(s) {s+nShifts*nWorkers}
totShiftIdx   <- function(w) {w + nShifts * (nWorkers+1)}
minShiftIdx   <- ((nShifts+1)*(nWorkers+1))
maxShiftIdx   <- (minShiftIdx+1)
totalSlackIdx <- nVars


Shifts  <- c('Mon1', 'Tue2', 'Wed3', 'Thu4', 'Fri5', 'Sat6', 'Sun7',
             'Mon8', 'Tue9', 'Wed10', 'Thu11', 'Fri12', 'Sat13', 'Sun14')
Workers <- c( 'Amy', 'Bob', 'Cathy', 'Dan', 'Ed', 'Fred', 'Gu', 'Tobi' )

shiftRequirements <- c(3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5 )

availability <- list( c( 0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1 ),
                      c( 1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0 ),
                      c( 0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1 ),
                      c( 0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1 ),
                      c( 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1 ),
                      c( 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1 ),
                      c( 0, 1, 1, 1, 0, 1, 1, 0, 1, 1, 1, 0, 1, 1 ),
                      c( 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1 ) )

# Function to display results
solveandprint <- function(model, params) {
  result <- gurobi(model, params = params)
  if(result$status == 'OPTIMAL') {
    cat('The optimal objective is',result$objval,'\n')
    cat('Schedule:\n')
    for (s in 1:nShifts) {
      cat('\t',Shifts[s],':')
      for (w in 1:nWorkers) {
        if (result$x[varIdx(w,s)] > 0.9) cat(Workers[w],' ')
      }
      cat('\n')
    }
    cat('Workload:\n')
    for (w in 1:nWorkers) {
      cat('\t',Workers[w],':',result$x[totShiftIdx(w)],'\n')
    }
  } else {
    cat('Optimization finished with status',result$status)
  }
```

(continues on next page)

(continued from previous page)

```
  result
}

# Set up parameters
params <- list()
params$logfile <- 'workforce5.log'

# Build model
model            <- list()
model$modelname  <- 'workforce5'
model$modelsense <- 'min'

# Initialize assignment decision variables:
#    x[w][s] == 1 if worker w is assigned to shift s.
#    This is no longer a pure assignment model, so we must
#    use binary variables.
model$vtype    <- rep('C', nVars)
model$lb       <- rep(0, nVars)
model$ub       <- rep(1, nVars)
model$varnames <- rep('',nVars)
for (w in 1:nWorkers) {
  for (s in 1:nShifts) {
    model$vtype[varIdx(w,s)]    = 'B'
    model$varnames[varIdx(w,s)] = paste0(Workers[w],'.',Shifts[s])
    if (availability[[w]][s] == 0) model$ub[varIdx(w,s)] = 0
  }
}

# Initialize shift slack variables
for (s in 1:nShifts) {
  model$varnames[shiftSlackIdx(s)] = paste0('ShiftSlack',Shifts[s])
  model$ub[shiftSlackIdx(s)] = Inf
}

# Initialize worker slack and diff variables
for (w in 1:nWorkers) {
  model$varnames[totShiftIdx(w)] = paste0('TotalShifts',Workers[w])
  model$ub[totShiftIdx(w)]       = Inf
}

#Initialize min/max shift variables
model$ub[minShiftIdx]       = Inf
model$varnames[minShiftIdx] = 'MinShift'
model$ub[maxShiftIdx]       = Inf
model$varnames[maxShiftIdx] = 'MaxShift'

#Initialize total slack variable
model$ub[totalSlackIdx]      = Inf
model$varnames[totalSlackIdx] = 'TotalSlack'

# Set up shift-requirements constraints
model$A          <- spMatrix(nShifts,nVars,
```

(continues on next page)

(continued from previous page)

```
                      i = c(c(mapply(rep,1:nShifts,nWorkers)),
                            c(1:nShifts)),
                      j = c(mapply(varIdx,1:nWorkers,
                                   mapply(rep,1:nShifts,nWorkers)),
                            shiftSlackIdx(1:nShifts)),
                      x = rep(1,nShifts * (nWorkers+1)))
model$sense       <- rep('=',nShifts)
model$rhs         <- shiftRequirements
model$constrnames <- Shifts

# Set TotalSlack equal to the sum of each shift slack
B <- spMatrix(1, nVars,
        i = rep(1,nShifts+1),
        j = c(shiftSlackIdx(1:nShifts),totalSlackIdx),
        x = c(rep(1,nShifts),-1))
model$A           <- rbind(model$A, B)
model$rhs         <- c(model$rhs,0)
model$sense       <- c(model$sense,'=')
model$constrnames <- c(model$constrnames, 'TotalSlack')

# Set total number of shifts for each worker
B <- spMatrix(nWorkers, nVars,
          i = c(mapply(rep,1:nWorkers,nShifts),
                1:nWorkers),
          j = c(mapply(varIdx,c(mapply(rep,1:nWorkers,nShifts)),1:nShifts),
                totShiftIdx(1:nWorkers)),
          x = c(rep(1,nShifts*nWorkers),rep(-1,nWorkers)))
model$A           <- rbind(model$A, B)
model$rhs         <- c(model$rhs,rep(0,nWorkers))
model$sense       <- c(model$sense,rep('=',nWorkers))
model$constrnames <- c(model$constrnames, sprintf('TotalShifts%s',Workers[1:nWorkers]))

# Set minShift / maxShift general constraints
model$genconmin <- list(list(resvar = minShiftIdx,
                             vars   = c(totShiftIdx(1:nWorkers)),
                             name   = 'MinShift'))
model$genconmax <- list(list(resvar = maxShiftIdx,
                             vars   = c(totShiftIdx(1:nWorkers)),
                             name   = 'MaxShift'))

# Set multiobjective
model$multiobj <- list(1:2)
model$multiobj[[1]]          <- list()
model$multiobj[[1]]$objn     <- c(rep(0,nVars))
model$multiobj[[1]]$objn[totalSlackIdx] = 1
model$multiobj[[1]]$priority <- 2
model$multiobj[[1]]$weight   <- 1
model$multiobj[[1]]$abstol   <- 2
model$multiobj[[1]]$reltol   <- 0.1
model$multiobj[[1]]$name     <- 'TotalSlack'
model$multiobj[[1]]$con      <- 0.0
model$multiobj[[2]]          <- list()
```

(continues on next page)

(continued from previous page)

```
model$multiobj[[2]]$objn     <- c(rep(0,nVars))
model$multiobj[[2]]$objn[minShiftIdx] = -1
model$multiobj[[2]]$objn[maxShiftIdx] =  1
model$multiobj[[2]]$priority <- 1
model$multiobj[[2]]$weight   <- 1
model$multiobj[[2]]$abstol   <- 0
model$multiobj[[2]]$reltol   <- 0
model$multiobj[[2]]$name     <- 'Fairness'
model$multiobj[[2]]$con      <- 0.0


# Save initial model
gurobi_write(model,'workforce5.lp', params)

# Optimize
result <- solveandprint(model, params)
if (result$status != 'OPTIMAL') stop('Stop now\n')

#Clear space
rm(model, params, availability, Shifts, Workers, shiftRequirements, result)
```

2.1.8 Visual Basic Examples

This section includes source code for all of the Gurobi Visual Basic examples. The same source code can be found in the `examples/vb` directory of the Gurobi distribution.

batchmode_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example reads a MIP model from a file, solves it in batch mode,
' and prints the JSON solution string.
'
'   You will need a Compute Server license for this example to work. */

Imports System
Imports Gurobi

Class batchmode_vb

    ' Set-up the environment for batch mode optimization.
    '
    ' The function creates an empty environment, sets all neccessary
    ' parameters, and returns the ready-to-be-started Env object to caller.
    ' It is the caller's responsibility to dispose of this environment when
    ' it's no longer needed.
    Private Shared Function setupbatchenv() As GRBEnv
        Dim env As GRBEnv = New GRBEnv(True)
        env.CSBatchMode = 1
        env.CSManager = "http://localhost:61080"
```

(continues on next page)

(continued from previous page)

```
        env.LogFile = "batchmode.log"
        env.ServerPassword = "pass"
        env.UserName = "gurobi"

        ' No network communication happened up to this point. This will happen
        ' once the caller invokes the start() method of the returned Env
        ' Object.

        Return env
    End Function

    ' Print batch job error information, if any
    Private Shared Sub printbatcherrorinfo(ByRef batch As GRBBatch)
        If batch.BatchErrorCode = 0 Then Return
        Console.WriteLine("Batch ID: " & batch.BatchID & ", Error code: " & batch.
↪BatchErrorCode & "(" & batch.BatchErrorMessage & ")")
    End Sub

    ' Create a batch request for given problem file
    Private Shared Function newbatchrequest(ByVal filename As String) As String
        Dim batchID As String = ""

        ' Start environment, create Model object from file
        Dim env As GRBEnv = setupbatchenv()
        env.Start()
        Dim model As GRBModel = New GRBModel(env, filename)

        Try
            ' Set some parameters
            model.[Set](GRB.DoubleParam.MIPGap, 0.01)
            model.[Set](GRB.IntParam.JSONSolDetail, 1)

            ' Define tags for some variables in order to access their values later
            Dim count As Integer = 0
            For Each v As GRBVar In model.GetVars()
                v.VTag = "Variable" & count
                count += 1
                If count >= 10 Then Exit For
            Next

            ' submit batch request
            batchID = model.OptimizeBatch()
        Finally
            model.Dispose()
            env.Dispose()
        End Try

        Return batchID
    End Function

    ' Wait for the final status of the batch.
    ' Initially the status of a batch is "submitted"; the status will change
```

(continues on next page)

(continued from previous page)

```
    ' once the batch has been processed (by a compute server).
    Private Shared Sub waitforfinalstatus(ByVal batchID As String)
        ' Wait no longer than one hour
        Dim maxwaittime As Double = 3600
        Dim start As DateTime = DateTime.Now

        ' Setup and start environment, create local Batch handle object
        Dim env As GRBEnv = setupbatchenv()
        env.Start()
        Dim batch As GRBBatch = New GRBBatch(env, batchID)

        Try

            While batch.BatchStatus = GRB.BatchStatus.SUBMITTED
                ' Abort this batch if it is taking too long
                Dim interval As TimeSpan = DateTime.Now - start
                If interval.TotalSeconds > maxwaittime Then
                    batch.Abort()
                    Exit While
                End If

                ' Wait for two seconds
                System.Threading.Thread.Sleep(2000)

                ' Update the resident attribute cache of the Batch object with the
                ' latest values from the cluster manager.
                batch.Update()

                ' If the batch failed, we retry it
                If batch.BatchStatus = GRB.BatchStatus.FAILED Then
                    batch.Retry()
                    System.Threading.Thread.Sleep(2000)
                    batch.Update()
                End If
            End While

        Finally
           ' Print information about error status of the job that
           ' processed the batch
            printbatcherrorinfo(batch)
            batch.Dispose()
            env.Dispose()
        End Try
    End Sub

    Private Shared Sub printfinalreport(ByVal batchID As String)
        ' Setup and start environment, create local Batch handle object
        Dim env As GRBEnv = setupbatchenv()
        env.Start()
        Dim batch As GRBBatch = New GRBBatch(env, batchID)

        Select Case batch.BatchStatus
```

(continues on next page)

(continued from previous page)

```
            Case GRB.BatchStatus.CREATED
                Console.WriteLine("Batch status is 'CREATED'" & vbLf)
            Case GRB.BatchStatus.SUBMITTED
                Console.WriteLine("Batch is 'SUBMITTED" & vbLf)
            Case GRB.BatchStatus.ABORTED
                Console.WriteLine("Batch is 'ABORTED'" & vbLf)
            Case GRB.BatchStatus.FAILED
                Console.WriteLine("Batch is 'FAILED'" & vbLf)
            Case GRB.BatchStatus.COMPLETED
                Console.WriteLine("Batch is 'COMPLETED'" & vbLf)
                ' Pretty printing the general solution information
                Console.WriteLine("JSON solution:" & batch.GetJSONSolution())

                ' Write the full JSON solution string to a file
                batch.WriteJSONSolution("batch-sol.json.gz")
            Case Else
                ' Should not happen
                Console.WriteLine("Unknown BatchStatus" & batch.BatchStatus)
                Environment.[Exit](1)
        End Select

        batch.Dispose()
        env.Dispose()
    End Sub

    ' Instruct cluster manager to discard all data relating to this BatchID
    Private Shared Sub batchdiscard(ByVal batchID As String)
        ' Setup and start environment, create local Batch handle object
        Dim env As GRBEnv = setupbatchenv()
        env.Start()
        Dim batch As GRBBatch = New GRBBatch(env, batchID)

        ' Remove batch request from manager
        batch.Discard()
        batch.Dispose()
        env.Dispose()
    End Sub

    ' Solve a given model using batch optimization
    Shared Sub Main(ByVal args As String())
        ' Ensure we have an input file
        If args.Length < 1 Then
            Console.Out.WriteLine("Usage: batchmode_vb filename")
            Return
        End If

        Try
            ' Submit new batch request
            Dim batchID As String = newbatchrequest(args(0))

            ' Wait for final status
            waitforfinalstatus(batchID)
```

(continues on next page)

(continued from previous page)

```
            ' Report final status info
            printfinalreport(batchID)

            ' Remove batch request from manager
            batchdiscard(batchID)

            Console.WriteLine("Batch optimization OK")
        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

bilinear_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC */

' This example formulates and solves the following simple bilinear model:
'
'     maximize    x
'     subject to  x + y + z <= 10
'                 x * y <= 2          (bilinear inequality)
'                 x * z + y * z == 1  (bilinear equality)
'                 x, y, z non-negative (x integral in second version)

Imports Gurobi

Class bilinear_vb
    Shared Sub Main()
        Try
            Dim env As New GRBEnv("bilinear.log")
            Dim model As New GRBModel(env)

            ' Create variables

            Dim x As GRBVar = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS, "x")
            Dim y As GRBVar = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS, "y")
            Dim z As GRBVar = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS, "z")

            ' Set objective
            Dim obj As GRBLinExpr = x
            model.SetObjective(obj, GRB.MAXIMIZE)

            ' Add linear constraint: x + y + z <= 10

            model.AddConstr(x + y + z <= 10, "c0")

            ' Add bilinear inequality: x * y <= 2
```

(continues on next page)

(continued from previous page)

```
            model.AddQConstr(x * y <= 2, "bilinear0")

            ' Add bilinear equality: x * z + y * z == 1

            model.AddQConstr(x * z + y * z = 1, "bilinear1")

            ' Optimize model

            model.Optimize()

            Console.WriteLine(x.VarName & " " & x.X)
            Console.WriteLine(y.VarName & " " & y.X)
            Console.WriteLine(z.VarName & " " & z.X)

            Console.WriteLine("Obj: " & model.ObjVal & " " & obj.Value)

            x.Set(GRB.CharAttr.VType, GRB.INTEGER)
            model.Optimize()

            Console.WriteLine(x.VarName & " " & x.X)
            Console.WriteLine(y.VarName & " " & y.X)
            Console.WriteLine(z.VarName & " " & z.X)

            Console.WriteLine("Obj: " & model.ObjVal & " " & obj.Value)

            ' Dispose of model and env

            model.Dispose()

            env.Dispose()
        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try

    End Sub
End Class
```

callback_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

'   This example reads a model from a file, sets up a callback that
'   monitors optimization progress and implements a custom
'   termination strategy, and outputs progress information to the
'   screen and to a log file.
'
'   The termination strategy implemented in this callback stops the
'   optimization of a MIP model once at least one of the following two
'   conditions have been satisfied:
'     1) The optimality gap is less than 10%
```

(continues on next page)

(continued from previous page)

```
'     2) At least 10000 nodes have been explored, and an integer feasible
'        solution has been found.
'   Note that termination is normally handled through Gurobi parameters
'   (MIPGap, NodeLimit, etc.).  You should only use a callback for
'   termination if the available parameters don't capture your desired
'   termination criterion.

Imports System
Imports Gurobi

Class callback_vb
    Inherits GRBCallback
    Private vars As GRBVar()
    Private lastnode As Double
    Private lastiter As Double

    Public Sub New(ByVal xvars As GRBVar())
        vars = xvars
        lastnode = lastiter = -1
    End Sub

    Protected Overloads Overrides Sub Callback()
        Try
            If where = GRB.Callback.PRESOLVE Then
                ' Presolve callback
                Dim cdels As Integer = GetIntInfo(GRB.Callback.PRE_COLDEL)
                Dim rdels As Integer = GetIntInfo(GRB.Callback.PRE_ROWDEL)
                Console.WriteLine(cdels & " columns and " & rdels & " rows are removed")
            ElseIf where = GRB.Callback.SIMPLEX Then
                ' Simplex callback
                Dim itcnt As Double = GetDoubleInfo(GRB.Callback.SPX_ITRCNT)
                If itcnt Mod - lastiter >= 100 Then
                    lastiter = itcnt
                    Dim obj As Double = GetDoubleInfo(GRB.Callback.SPX_OBJVAL)
                    Dim pinf As Double = GetDoubleInfo(GRB.Callback.SPX_PRIMINF)
                    Dim dinf As Double = GetDoubleInfo(GRB.Callback.SPX_DUALINF)
                    Dim ispert As Integer = GetIntInfo(GRB.Callback.SPX_ISPERT)
                    Dim ch As Char
                    If ispert = 0 Then
                        ch = " "c
                    ElseIf ispert = 1 Then
                        ch = "S"c
                    Else
                        ch = "P"c
                    End If
                    Console.WriteLine(itcnt & "   " & obj & ch & "   " & pinf & "   " &␣
↪dinf)
                End If
            ElseIf where = GRB.Callback.MIP Then
                ' General MIP callback
                Dim nodecnt As Double = GetDoubleInfo(GRB.Callback.MIP_NODCNT)
                If nodecnt - lastnode >= 100 Then
```

(continues on next page)

(continued from previous page)

```
                    lastnode = nodecnt
                    Dim objbst As Double = GetDoubleInfo(GRB.Callback.MIP_OBJBST)
                    Dim objbnd As Double = GetDoubleInfo(GRB.Callback.MIP_OBJBND)
                    If Math.Abs(objbst - objbnd) < 0.1 * (1.0R + Math.Abs(objbst)) Then
                        Abort()
                    End If
                    Dim actnodes As Integer = CInt(GetDoubleInfo(GRB.Callback.MIP_
↪NODLFT))
                    Dim itcnt As Integer = CInt(GetDoubleInfo(GRB.Callback.MIP_ITRCNT))
                    Dim solcnt As Integer = GetIntInfo(GRB.Callback.MIP_SOLCNT)
                    Dim cutcnt As Integer = GetIntInfo(GRB.Callback.MIP_CUTCNT)
                    Console.WriteLine(nodecnt & " " & actnodes & " " & itcnt & " " & _
                                      objbst & " " & objbnd & " " & solcnt & " " &␣
↪cutcnt)
                End If
            ElseIf where = GRB.Callback.MIPSOL Then
                ' MIP solution callback
                Dim obj As Double = GetDoubleInfo(GRB.Callback.MIPSOL_OBJ)
                Dim nodecnt As Integer = CInt(GetDoubleInfo(GRB.Callback.MIPSOL_NODCNT))
                Dim x As Double() = GetSolution(vars)
                Console.WriteLine("**** New solution at node " & nodecnt & ", obj " & _
                                  obj & ", x(0) = " & x(0) & "****")
            End If
        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
            Console.WriteLine(e.StackTrace)
        End Try
    End Sub

    Shared Sub Main(ByVal args As String())

        If args.Length < 1 Then
            Console.WriteLine("Usage: callback_vb filename")
            Return
        End If

        Try
            Dim env As New GRBEnv()
            Dim model As New GRBModel(env, args(0))

            Dim vars As GRBVar() = model.GetVars()

            ' Create a callback object and associate it with the model
            model.SetCallback(New callback_vb(vars))
            model.Optimize()

            Dim x As Double() = model.Get(GRB.DoubleAttr.X, vars)
            Dim vnames As String() = model.Get(GRB.StringAttr.VarName, vars)

            For j As Integer = 0 To vars.Length - 1
                If x(j) <> 0.0R Then
                    Console.WriteLine(vnames(j) & " " & x(j))
```

(continues on next page)

(continued from previous page)

```
                End If
            Next

            ' Dispose of model and env
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
            Console.WriteLine(e.StackTrace)
        End Try
    End Sub
End Class
```

dense_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example formulates and solves the following simple QP model:
'
'   minimize    x + y + x^2 + x*y + y^2 + y*z + z^2
'   subject to  x + 2 y + 3 z >= 4
'               x +   y       >= 1
'               x, y, z non-negative
'
' The example illustrates the use of dense matrices to store A and Q
' (and dense vectors for the other relevant data).  We don't recommend
' that you use dense matrices, but this example may be helpful if you
' already have your data in this format.

Imports Gurobi

Class dense_vb

    Protected Shared Function _
      dense_optimize(env As GRBEnv, _
                     rows As Integer, _
                     cols As Integer, _
                     c As Double(), _
                     Q As Double(,), _
                     A As Double(,), _
                     sense As Char(), _
                     rhs As Double(), _
                     lb As Double(), _
                     ub As Double(), _
                     vtype As Char(), _
                     solution As Double()) As Boolean

        Dim success As Boolean = False
```

(continues on next page)

(continued from previous page)

```
        Try
            Dim model As New GRBModel(env)

            ' Add variables to the model

            Dim vars As GRBVar() = model.AddVars(lb, ub, Nothing, vtype, Nothing)

            ' Populate A matrix

            For i As Integer = 0 To rows - 1
                Dim expr As New GRBLinExpr()
                For j As Integer = 0 To cols - 1
                    If A(i, j) <> 0 Then
                        expr.AddTerm(A(i, j), vars(j))
                    End If
                Next
                model.AddConstr(expr, sense(i), rhs(i), "")
            Next

            ' Populate objective

            Dim obj As New GRBQuadExpr()
            If Q IsNot Nothing Then
                For i As Integer = 0 To cols - 1
                    For j As Integer = 0 To cols - 1
                        If Q(i, j) <> 0 Then
                            obj.AddTerm(Q(i, j), vars(i), vars(j))
                        End If
                    Next
                Next
                For j As Integer = 0 To cols - 1
                    If c(j) <> 0 Then
                        obj.AddTerm(c(j), vars(j))
                    End If
                Next
                model.SetObjective(obj)
            End If

            ' Solve model

            model.Optimize()

            ' Extract solution

            If model.Status = GRB.Status.OPTIMAL Then
                success = True

                For j As Integer = 0 To cols - 1
                    solution(j) = vars(j).X
                Next
            End If
```

(continues on next page)

(continued from previous page)

```
            model.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try

        Return success
    End Function

    Public Shared Sub Main(args As String())
        Try
            Dim env As New GRBEnv()

            Dim c As Double() = New Double() {1, 1, 0}
            Dim Q As Double(,) = New Double(,) {{1, 1, 0}, {0, 1, 1}, {0, 0, 1}}
            Dim A As Double(,) = New Double(,) {{1, 2, 3}, {1, 1, 0}}
            Dim sense As Char() = New Char() {">"C, ">"C}
            Dim rhs As Double() = New Double() {4, 1}
            Dim lb As Double() = New Double() {0, 0, 0}
            Dim success As Boolean
            Dim sol As Double() = New Double(2) {}

            success = dense_optimize(env, 2, 3, c, Q, A, sense, rhs, lb, Nothing, _
                                     Nothing, sol)

            If success Then
                Console.WriteLine("x: " & sol(0) & ", y: " & sol(1) & ", z: " & sol(2))
            End If

            ' Dispose of environment

            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try

    End Sub
End Class
```

diet_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' Solve the classic diet model, showing how to add constraints
' to an existing model.

Imports System
Imports Gurobi

```

(continues on next page)

(continued from previous page)

```
Class diet_vb
    Shared Sub Main()
        Try

            ' Nutrition guidelines, based on
            ' USDA Dietary Guidelines for Americans, 2005
            ' http://www.health.gov/DietaryGuidelines/dga2005/
            Dim Categories As String() = New String() {"calories", "protein", "fat", _
                                                       "sodium"}
            Dim nCategories As Integer = Categories.Length
            Dim minNutrition As Double() = New Double() {1800, 91, 0, 0}
            Dim maxNutrition As Double() = New Double() {2200, GRB.INFINITY, 65, 1779}

            ' Set of foods
            Dim Foods As String() = New String() {"hamburger", "chicken", "hot dog", _
                                                  "fries", "macaroni", "pizza", _
                                                  "salad", "milk", "ice cream"}
            Dim nFoods As Integer = Foods.Length
            Dim cost As Double() = New Double() {2.49, 2.89, 1.5R, 1.89, 2.09, 1.99, _
                                                 2.49, 0.89, 1.59}

            ' Nutrition values for the foods
            ' hamburger
            ' chicken
            ' hot dog
            ' fries
            ' macaroni
            ' pizza
            ' salad
            ' milk
            ' ice cream
            Dim nutritionValues As Double(,) = New Double(,) {{410, 24, 26, 730}, _
                                                              {420, 32, 10, 1190}, _
                                                              {560, 20, 32, 1800}, _
                                                              {380, 4, 19, 270}, _
                                                              {320, 12, 10, 930}, _
                                                              {320, 15, 12, 820}, _
                                                              {320, 31, 12, 1230}, _
                                                              {100, 8, 2.5, 125}, _
                                                              {330, 8, 10, 180}}

            ' Model
            Dim env As New GRBEnv()
            Dim model As New GRBModel(env)

            model.ModelName = "diet"

            ' Create decision variables for the nutrition information,
            ' which we limit via bounds
            Dim nutrition As GRBVar() = New GRBVar(nCategories - 1) {}
            For i As Integer = 0 To nCategories - 1
                nutrition(i) = model.AddVar(minNutrition(i), maxNutrition(i), 0, _
```

(continues on next page)

(continued from previous page)

```
                                        GRB.CONTINUOUS, Categories(i))
        Next

        ' Create decision variables for the foods to buy
        '
        ' Note: For each decision variable we add the objective coefficient
        '       with the creation of the variable.
        Dim buy As GRBVar() = New GRBVar(nFoods - 1) {}
        For j As Integer = 0 To nFoods - 1
            buy(j) = model.AddVar(0, GRB.INFINITY, cost(j), GRB.CONTINUOUS, _
                                  Foods(j))
        Next

        ' The objective is to minimize the costs
        '
        ' Note: The objective coefficients are set during the creation of
        '       the decision variables above.
        model.ModelSense = GRB.MINIMIZE

        ' Nutrition constraints
        For i As Integer = 0 To nCategories - 1
            Dim ntot As GRBLinExpr = 0
            For j As Integer = 0 To nFoods - 1
                ntot.AddTerm(nutritionValues(j, i), buy(j))
            Next
            model.AddConstr(ntot = nutrition(i), Categories(i))
        Next

        ' Solve
        model.Optimize()
        PrintSolution(model, buy, nutrition)

        Console.WriteLine(vbLf & "Adding constraint: at most 6 servings of dairy")
        model.AddConstr(buy(7) + buy(8) <= 6, "limit_dairy")

        ' Solve
        model.Optimize()

        PrintSolution(model, buy, nutrition)

        ' Dispose of model and env
        model.Dispose()
        env.Dispose()

    Catch e As GRBException
        Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
    End Try
End Sub

Private Shared Sub PrintSolution(ByVal model As GRBModel, ByVal buy As GRBVar(), _
                                 ByVal nutrition As GRBVar())
    If model.Status = GRB.Status.OPTIMAL Then
```

(continues on next page)

(continued from previous page)

```
            Console.WriteLine(vbLf & "Cost: " & model.ObjVal)
            Console.WriteLine(vbLf & "Buy:")
            For j As Integer = 0 To buy.Length - 1
                If buy(j).X > 0.0001 Then
                    Console.WriteLine(buy(j).VarName & " " & buy(j).X)
                End If
            Next
            Console.WriteLine(vbLf & "Nutrition:")
            For i As Integer = 0 To nutrition.Length - 1
                Console.WriteLine(nutrition(i).VarName & " " & nutrition(i).X)
            Next
        Else
            Console.WriteLine("No solution")
        End If
    End Sub
End Class
```

facility_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' Facility location: a company currently ships its product from 5 plants
' to 4 warehouses. It is considering closing some plants to reduce
' costs. What plant(s) should the company close, in order to minimize
' transportation and fixed costs?
'
' Based on an example from Frontline Systems:
' http://www.solver.com/disfacility.htm
' Used with permission.

Imports System
Imports Gurobi

Class facility_vb
    Shared Sub Main()
        Try

            ' Warehouse demand in thousands of units
            Dim Demand As Double() = New Double() {15, 18, 14, 20}

            ' Plant capacity in thousands of units
            Dim Capacity As Double() = New Double() {20, 22, 17, 19, 18}

            ' Fixed costs for each plant
            Dim FixedCosts As Double() = New Double() {12000, 15000, 17000, 13000, _
                                                       16000}

            ' Transportation costs per thousand units
            Dim TransCosts As Double(,) = New Double(,) {{4000, 2000, 3000, 2500, 4500},␣
↪_
```

(continues on next page)

(continued from previous page)

```
                                                    {2500, 2600, 3400, 3000, 4000},␣
↪_
                                                    {1200, 1800, 2600, 4100, 3000},␣
↪_
                                                    {2200, 2600, 3100, 3700, 3200}}

            ' Number of plants and warehouses
            Dim nPlants As Integer = Capacity.Length
            Dim nWarehouses As Integer = Demand.Length

            ' Model
            Dim env As New GRBEnv()
            Dim model As New GRBModel(env)

            model.ModelName = "facility"

            ' Plant open decision variables: open(p) == 1 if plant p is open.
            Dim open As GRBVar() = New GRBVar(nPlants - 1) {}
            For p As Integer = 0 To nPlants - 1
                open(p) = model.AddVar(0, 1, FixedCosts(p), GRB.BINARY, "Open" & p)
            Next

            ' Transportation decision variables: how much to transport from
            ' a plant p to a warehouse w
            Dim transport As GRBVar(,) = New GRBVar(nWarehouses - 1, nPlants - 1) {}
            For w As Integer = 0 To nWarehouses - 1
                For p As Integer = 0 To nPlants - 1
                    transport(w, p) = model.AddVar(0, GRB.INFINITY, _
                                                   TransCosts(w, p), GRB.CONTINUOUS, _
                                                   "Trans" & p & "." & w)
                Next
            Next

            ' The objective is to minimize the total fixed and variable costs
            model.ModelSense = GRB.MINIMIZE

            ' Production constraints
            ' Note that the right-hand limit sets the production to zero if
            ' the plant is closed
            For p As Integer = 0 To nPlants - 1
                Dim ptot As GRBLinExpr = 0
                For w As Integer = 0 To nWarehouses - 1
                    ptot.AddTerm(1.0, transport(w, p))
                Next
                model.AddConstr(ptot <= Capacity(p) * open(p), "Capacity" & p)
            Next

            ' Demand constraints
            For w As Integer = 0 To nWarehouses - 1
                Dim dtot As GRBLinExpr = 0
                For p As Integer = 0 To nPlants - 1
                    dtot.AddTerm(1.0, transport(w, p))
```

(continues on next page)

(continued from previous page)

```
        Next
        model.AddConstr(dtot = Demand(w), "Demand" & w)
    Next

    ' Guess at the starting point: close the plant with the highest
    ' fixed costs; open all others

    ' First, open all plants
    For p As Integer = 0 To nPlants - 1
        open(p).Start = 1.0
    Next

    ' Now close the plant with the highest fixed cost
    Console.WriteLine("Initial guess:")
    Dim maxFixed As Double = -GRB.INFINITY
    For p As Integer = 0 To nPlants - 1
        If FixedCosts(p) > maxFixed Then
            maxFixed = FixedCosts(p)
        End If
    Next
    For p As Integer = 0 To nPlants - 1
        If FixedCosts(p) = maxFixed Then
            open(p).Start = 0.0
            Console.WriteLine("Closing plant " & p & vbLf)
            Exit For
        End If
    Next

    ' Use barrier to solve root relaxation
    model.Parameters.Method = GRB.METHOD_BARRIER

    ' Solve
    model.Optimize()

    ' Print solution
    Console.WriteLine(vbLf & "TOTAL COSTS: " & model.ObjVal)
    Console.WriteLine("SOLUTION:")
    For p As Integer = 0 To nPlants - 1
        If open(p).X > 0.99 Then
            Console.WriteLine("Plant " & p & " open:")
            For w As Integer = 0 To nWarehouses - 1
                If transport(w, p).X > 0.0001 Then
                    Console.WriteLine("  Transport " & _
                                      transport(w, p).X & _
                                      " units to warehouse " & w)
                End If
            Next
        Else
            Console.WriteLine("Plant " & p & " closed!")
        End If

    Next
```

(continues on next page)

(continued from previous page)

```
            ' Dispose of model and env
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

feasopt_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example reads a MIP model from a file, adds artificial
' variables to each constraint, and then minimizes the sum of the
' artificial variables.  A solution with objective zero corresponds
' to a feasible solution to the input model.
' We can also use FeasRelax feature to do it. In this example, we
' use minrelax=1, i.e. optimizing the returned model finds a solution
' that minimizes the original objective, but only from among those
' solutions that minimize the sum of the artificial variables.

Imports Gurobi
Imports System

Class feasopt_vb
    Shared Sub Main(ByVal args As String())

        If args.Length < 1 Then
            Console.WriteLine("Usage: feasopt_vb filename")
            Return
        End If

        Try
            Dim env As New GRBEnv()
            Dim feasmodel As New GRBModel(env, args(0))

            'Create a copy to use FeasRelax feature later
            Dim feasmodel1 As New GRBModel(feasmodel)

            ' Clear objective
            feasmodel.SetObjective(New GRBLinExpr())

            ' Add slack variables
            Dim c As GRBConstr() = feasmodel.GetConstrs()
            For i As Integer = 0 To c.Length - 1
                Dim sense As Char = c(i).Sense
                If sense <> ">"c Then
```

(continues on next page)

(continued from previous page)

```
                    Dim constrs As GRBConstr() = New GRBConstr() {c(i)}
                    Dim coeffs As Double() = New Double() {-1}
                    feasmodel.AddVar(0.0, GRB.INFINITY, 1.0, GRB.CONTINUOUS, _
                                     constrs, coeffs, _
                                     "ArtN_" & c(i).ConstrName)
                End If
                If sense <> "<"c Then
                    Dim constrs As GRBConstr() = New GRBConstr() {c(i)}
                    Dim coeffs As Double() = New Double() {1}
                    feasmodel.AddVar(0.0, GRB.INFINITY, 1.0, GRB.CONTINUOUS, _
                                     constrs, coeffs, _
                                     "ArtP_" & c(i).ConstrName)
                End If
            Next

            ' Optimize modified model
            feasmodel.Optimize()
            feasmodel.Write("feasopt.lp")

            ' Use FeasRelax feature */
            feasmodel1.FeasRelax(GRB.FEASRELAX_LINEAR, true, false, true)
            feasmodel1.Write("feasopt1.lp")
            feasmodel1.Optimize()

            ' Dispose of model and env
            feasmodel1.Dispose()
            feasmodel.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

fixanddive_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' Implement a simple MIP heuristic.  Relax the model,
' sort variables based on fractionality, and fix the 25% of
' the fractional variables that are closest to integer variables.
' Repeat until either the relaxation is integer feasible or
' linearly infeasible.

Imports System
Imports System.Collections.Generic
Imports Gurobi

Class fixanddive_vb
```

(continues on next page)

(continued from previous page)

```
    ' Comparison class used to sort variable list based on relaxation
    ' fractionality

    Private Class FractionalCompare : Implements IComparer(Of GRBVar)
        Public Function Compare(ByVal v1 As GRBVar, ByVal v2 As GRBVar) As Integer _
                            Implements IComparer(Of Gurobi.GRBVar).Compare
            Try
                Dim sol1 As Double = Math.Abs(v1.X)
                Dim sol2 As Double = Math.Abs(v2.X)
                Dim frac1 As Double = Math.Abs(sol1 - Math.Floor(sol1 + 0.5))
                Dim frac2 As Double = Math.Abs(sol2 - Math.Floor(sol2 + 0.5))
                If frac1 < frac2 Then
                    Return -1
                ElseIf frac1 > frac2 Then
                    Return 1
                Else
                    Return 0
                End If
            Catch e As GRBException
                Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
            End Try
            Return 0
        End Function
    End Class

    Shared Sub Main(ByVal args As String())

        If args.Length < 1 Then
            Console.WriteLine("Usage: fixanddive_vb filename")
            Return
        End If

        Try
            ' Read model
            Dim env As New GRBEnv()
            Dim model As New GRBModel(env, args(0))

            ' Collect integer variables and relax them
            Dim intvars As New List(Of GRBVar)()
            For Each v As GRBVar In model.GetVars()
                If v.VType <> GRB.CONTINUOUS Then
                    intvars.Add(v)
                    v.VType = GRB.CONTINUOUS
                End If
            Next

            model.Parameters.OutputFlag = 0
            model.Optimize()

            ' Perform multiple iterations. In each iteration, identify the first
            ' quartile of integer variables that are closest to an integer value
            ' in the relaxation, fix them to the nearest integer, and repeat.
```

(continues on next page)

(continued from previous page)

```
        For iter As Integer = 0 To 999

            ' create a list of fractional variables, sorted in order of
            ' increasing distance from the relaxation solution to the nearest
            ' integer value

            Dim fractional As New List(Of GRBVar)()
            For Each v As GRBVar In intvars
                Dim sol As Double = Math.Abs(v.X)
                If Math.Abs(sol - Math.Floor(sol + 0.5)) > 0.00001 Then
                    fractional.Add(v)
                End If
            Next

            Console.WriteLine("Iteration " & iter & ", obj " & _
                              model.ObjVal & ", fractional " & fractional.Count)

            If fractional.Count = 0 Then
                Console.WriteLine("Found feasible solution - objective " & _
                                  model.ObjVal)
                Exit For
            End If

            ' Fix the first quartile to the nearest integer value

            fractional.Sort(New FractionalCompare())
            Dim nfix As Integer = Math.Max(fractional.Count / 4, 1)
            For i As Integer = 0 To nfix - 1
                Dim v As GRBVar = fractional(i)
                Dim fixval As Double = Math.Floor(v.X + 0.5)
                v.LB = fixval
                v.UB = fixval
                Console.WriteLine("  Fix " & v.VarName & " to " & fixval & _
                                  " ( rel " & v.X & " )")
            Next

            model.Optimize()

            ' Check optimization result

            If model.Status <> GRB.Status.OPTIMAL Then
                Console.WriteLine("Relaxation is infeasible")
                Exit For
            End If
        Next

        ' Dispose of model and env
        model.Dispose()
        env.Dispose()

    Catch e As GRBException
```

(continues on next page)

(continued from previous page)

```
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

gc_pwl_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example formulates and solves the following simple model
' with PWL constraints:
'
'  maximize
'        sum c[j] * x[j]
'  subject to
'        sum A[i,j] * x[j] <= 0,  for i = 0, ..., m-1
'        sum y[j] <= 3
'        y[j] = pwl(x[j]),        for j = 0, ..., n-1
'        x[j] free, y[j] >= 0,    for j = 0, ..., n-1
'  where pwl(x) = 0,     if x  = 0
'               = 1+|x|, if x != 0
'
'  Note
'   1. sum pwl(x[j]) <= b is to bound x vector and also to favor sparse x vector.
'      Here b = 3 means that at most two x[j] can be nonzero and if two, then
'      sum x[j] <= 1
'   2. pwl(x) jumps from 1 to 0 and from 0 to 1, if x moves from negatie 0 to 0,
'      then to positive 0, so we need three points at x = 0. x has infinite bounds
'      on both sides, the piece defined with two points (-1, 2) and (0, 1) can
'      extend x to -infinite. Overall we can use five points (-1, 2), (0, 1),
'      (0, 0), (0, 1) and (1, 2) to define y = pwl(x)

Imports System
Imports Gurobi

Class gc_pwl_vb
    Shared Sub Main()
        Try
            Dim n As Integer = 5
            Dim m As Integer = 5
            Dim c As Double() = New Double() {0.5, 0.8, 0.5, 0.1, -1}
            Dim A As Double(,) = New Double(,) {{0, 0, 0, 1, -1}, _
                                                {0, 0, 1, 1, -1}, _
                                                {1, 1, 0, 0, -1}, _
                                                {1, 0, 1, 0, -1}, _
                                                {1, 0, 0, 1, -1}}
            Dim xpts As Double() = New Double() {-1, 0, 0, 0, 1}
            Dim ypts As Double() = New Double() {2, 1, 0, 1, 2}

            ' Env and model
```

(continues on next page)

(continued from previous page)

```
            Dim env As GRBEnv = New GRBEnv()
            Dim model As GRBModel = New GRBModel(env)
            model.ModelName = "gc_pwl_cs"

            ' Add variables, set bounds and obj coefficients
            Dim x As GRBVar() = model.AddVars(n, GRB.CONTINUOUS)
            For i As Integer = 0 To n - 1
                x(i).LB = -GRB.INFINITY
                x(i).Obj = c(i)
            Next

            Dim y As GRBVar() = model.AddVars(n, GRB.CONTINUOUS)

            ' Set objective to maximize
            model.ModelSense = GRB.MAXIMIZE

            ' Add linear constraints
            For i As Integer = 0 To m - 1
                Dim le As GRBLinExpr = 0.0
                For j As Integer = 0 To n - 1
                    le.AddTerm(A(i, j), x(j))
                Next
                model.AddConstr(le, GRB.LESS_EQUAL, 0, "cx" & i)
            Next

            Dim le1 As GRBLinExpr = 0.0
            For j As Integer = 0 To n - 1
                le1.AddTerm(1.0, y(j))
            Next
            model.AddConstr(le1, GRB.LESS_EQUAL, 3, "cy")

            ' Add piecewise constraints
            For j As Integer = 0 To n - 1
                model.AddGenConstrPWL(x(j), y(j), xpts, ypts, "pwl" & j)
            Next

            ' Optimize model
            model.Optimize()

            For j As Integer = 0 To n - 1
                Console.WriteLine("x[" & j & "] = " & x(j).X)
            Next
            Console.WriteLine("Obj: " & model.ObjVal)

            ' Dispose of model and environment
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
```

(continues on next page)

(continued from previous page)

```
End Class
```

genconstr_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' In this example we show the use of general constraints for modeling
' some common expressions. We use as an example a SAT-problem where we
' want to see if it is possible to satisfy at least four (or all) clauses
' of the logical form
'
' L = (x0 or ~x1 or x2)  and (x1 or ~x2 or x3)  and
'     (x2 or ~x3 or x0)  and (x3 or ~x0 or x1)  and
'     (~x0 or ~x1 or x2) and (~x1 or ~x2 or x3) and
'     (~x2 or ~x3 or x0) and (~x3 or ~x0 or x1)
'
' We do this by introducing two variables for each literal (itself and its
' negated value), one variable for each clause, one variable indicating
' whether we can satisfy at least four clauses, and one last variable to
' identify the minimum of the clauses (so if it is one, we can satisfy all
' clauses). Then we put these last two variables in the objective.
' The objective function is therefore
'
' maximize Obj0 + Obj1
'
'  Obj0 = MIN(Clause1, ... , Clause8)
'  Obj1 = 1 -> Clause1 + ... + Clause8 >= 4
'
' thus, the objective value will be two if and only if we can satisfy all
' clauses; one if and only if at least four but not all clauses can be satisfied,
' and zero otherwise.
'

Imports Gurobi

Class genconstr_vb

    Public Const n As Integer = 4
    Public Const NLITERALS As Integer = 4  'same as n
    Public Const NCLAUSES As Integer = 8
    Public Const NOBJ As Integer = 2

    Shared Sub Main()

        Try

            ' Example data:
            ' e.g. {0, n+1, 2} means clause (x0 or ~x1 or x2)
            Dim Clauses As Integer(,) = New Integer(,) { _
                {    0, n + 1, 2}, {    1, n + 2, 3}, _
```

(continues on next page)

(continued from previous page)

```
                {    2, n + 3, 0}, {    3, n + 0, 1}, _
                {n + 0, n + 1, 2}, {n + 1, n + 2, 3}, _
                {n + 2, n + 3, 0}, {n + 3, n + 0, 1}}

            Dim i As Integer, status As Integer

            ' Create environment
            Dim env As New GRBEnv("genconstr_vb.log")

            ' Create initial model
            Dim model As New GRBModel(env)
            model.ModelName = "genconstr_vb"

            ' Initialize decision variables and objective
            Dim Lit As GRBVar() = New GRBVar(NLITERALS - 1) {}
            Dim NotLit As GRBVar() = New GRBVar(NLITERALS - 1) {}
            For i = 0 To NLITERALS - 1
                Lit(i) = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, String.Format("X{0}",␣
↪i))
                NotLit(i) = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, String.Format("notX
↪{0}", i))
            Next

            Dim Cla As GRBVar() = New GRBVar(NCLAUSES - 1) {}
            For i = 0 To NCLAUSES - 1
                Cla(i) = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, String.Format("Clause{0}
↪", i))
            Next

            Dim Obj As GRBVar() = New GRBVar(NOBJ - 1) {}
            For i = 0 To NOBJ - 1
                Obj(i) = model.AddVar(0.0, 1.0, 1.0, GRB.BINARY, String.Format("Obj{0}",␣
↪i))
            Next

            ' Link Xi and notXi
            Dim lhs As GRBLinExpr
            For i = 0 To NLITERALS - 1
                lhs = New GRBLinExpr()
                lhs.AddTerm(1.0, Lit(i))
                lhs.AddTerm(1.0, NotLit(i))
                model.AddConstr(lhs, GRB.EQUAL, 1.0, String.Format("CNSTR_X{0}", i))
            Next

            ' Link clauses and literals
            For i = 0 To NCLAUSES - 1
                Dim clause As GRBVar() = New GRBVar(2) {}
                For j As Integer = 0 To 2
                    If Clauses(i, j) >= n Then
                        clause(j) = NotLit(Clauses(i, j) - n)
                    Else
                        clause(j) = Lit(Clauses(i, j))
```

(continues on next page)

(continued from previous page)

```
                End If
            Next
            model.AddGenConstrOr(Cla(i), clause, String.Format("CNSTR_Clause{0}", i))
        Next

        ' Link objs with clauses
        model.AddGenConstrMin(Obj(0), Cla, GRB.INFINITY, "CNSTR_Obj0")
        lhs = New GRBLinExpr()
        For i = 0 To NCLAUSES - 1
            lhs.AddTerm(1.0, Cla(i))
        Next
        model.AddGenConstrIndicator(Obj(1), 1, lhs, GRB.GREATER_EQUAL, 4.0, "CNSTR_
↪Obj1")

        ' Set global objective sense
        model.ModelSense = GRB.MAXIMIZE

        ' Save problem
        model.Write("genconstr_vb.mps")
        model.Write("genconstr_vb.lp")

        ' Optimize
        model.Optimize()

        ' Status checking
        status = model.Status

        If status = GRB.Status.INF_OR_UNBD OrElse _
           status = GRB.Status.INFEASIBLE OrElse _
           status = GRB.Status.UNBOUNDED Then
            Console.WriteLine("The model cannot be solved " & _
                      "because it is infeasible or unbounded")
            Return
        End If

        If status <> GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimization was stopped with status {0}", status)
            Return
        End If

        ' Print result
        Dim objval As Double = model.ObjVal

        If objval > 1.9 Then
            Console.WriteLine("Logical expression is satisfiable")
        ElseIf objval > 0.9 Then
            Console.WriteLine("At least four clauses can be satisfied")
        Else
            Console.WriteLine("Not even three clauses can be satisfied")
        End If

        ' Dispose of model and environment
```

(continues on next page)

(continued from previous page)

```
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: {0}. {1}", e.ErrorCode, e.Message)

        End Try
    End Sub
End Class
```

nlconstr_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example formulates and solves the following simple nonlinear model
' using the nonlinear API:
'
'     minimize    x - y
'     subject to  sin(x) * x + x^2 * y  <= 1
'                 y = cos(x) (<=> cos(x) - y = 0)
'                -1 <= x <= 2
'                 0 <= y <= 2
'
' The example is split into two functions that show two ways to build the
' nonlinear constraints with the new NL API:
'
'   - nlconstrNLAPI(): uses the nonlinear expression API. The left-hand sides
'     of the constraints are built as GRBNLExpr objects with the overloaded
'     operators, the nonlinear functions hosted on GRBNLExpr, and the Pow()
'     helper, and passed directly to AddNLConstr().
'
'   - nlconstrNLAPIAdv(): uses the advanced expression-tree variant of
'     AddNLConstr(), where the left-hand side of each constraint is described
'     with arrays of opcodes, data, and parent pointers.
'
' In both cases we retrieve a nonlinear constraint with GetNLConstrLHS(),
' delete it with Remove(), replace it with a simple linear constraint, and
' re-optimize.


Imports System
Imports Gurobi

Class nlconstr_vb
    ' Run both ways of building nonlinear constraints: the nonlinear
    ' expression API and the advanced expression-tree API.
    Shared Sub Main()
        Try
            ' First, the nonlinear expression API
            nlconstrNLAPI()
```

(continues on next page)

(continued from previous page)

```
        ' Then, the advanced expression-tree API
        nlconstrNLAPIAdv()

    Catch e As GRBException
        Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
    End Try
End Sub

' nlconstrNLAPI(): formulates the model with the nonlinear expression API,
' passing GRBNLExpr left-hand sides to AddNLConstr().
Shared Sub nlconstrNLAPI()
    ' Create environment
    Dim env As GRBEnv = New GRBEnv("nlconstr.log")

    ' Create empty model
    Dim model As GRBModel = New GRBModel(env)

    ' Create variables
    Dim x As GRBVar = model.AddVar(-1.0, 2.0, 1.0, GRB.CONTINUOUS, "x")
    Dim y As GRBVar = model.AddVar(0.0, 2.0, -1.0, GRB.CONTINUOUS, "y")

    ' Add nonlinear constraint: sin(x)*x + x^2*y <= 1.
    ' The left-hand side is built as a GRBNLExpr:
    '   GRBNLExpr.Sin(x)      -> sin(x)
    '   GRBNLExpr.Pow(x, 2.0) -> x^2 (a SQUARE node)
    Dim nlc1 As GRBNLConstr = model.AddNLConstr( _
        GRBNLExpr.Sin(x) * x + GRBNLExpr.Pow(x, 2.0) * y <= 1.0, _
        "NonlinearConstraint1")

    ' Add nonlinear constraint: cos(x) - y = 0
    Dim nlc2 As GRBNLConstr = model.AddNLConstr(GRBNLExpr.Cos(x) - y = 0.0, _
                                                "NonlinearConstraint2")

    ' Optimize model
    model.Optimize()

    Console.WriteLine("")
    Console.WriteLine("First solve (nonlinear constraints)")
    If model.Status = GRB.Status.OPTIMAL Then
        Console.WriteLine("Optimal objective: " & model.ObjVal.ToString("E4"))
        Console.WriteLine("  x=" & x.X.ToString("F6") & _
                          ", y=" & y.X.ToString("F6"))
    ElseIf model.Status = GRB.Status.INF_OR_UNBD Then
        Console.WriteLine("Model is infeasible or unbounded")
    Else
        Console.WriteLine("Optimization was stopped early")
    End If

    ' Retrieve the first nonlinear constraint as a GRBNLExpr and print it
    Dim lhs As GRBNLExpr = model.GetNLConstrLHS(nlc1)
    Console.WriteLine("")
```

(continues on next page)

(continued from previous page)

```
        Console.WriteLine("Retrieved NL constraint: """ & lhs.ToString() & """")

        ' Delete the nonlinear constraints
        model.Remove(nlc1)
        model.Remove(nlc2)
        model.Update()
        Console.WriteLine("Deleted nonlinear constraints")

        ' Add a simple linear constraint instead: x + y >= 1
        model.AddConstr(x + y, GRB.GREATER_EQUAL, 1.0, "LinearConstraint")

        ' Re-optimize
        model.Optimize()

        Console.WriteLine("")
        Console.WriteLine("Second solve (linear constraint)")
        If model.Status = GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimal objective: " & model.ObjVal.ToString("E4"))
            Console.WriteLine("  x=" & x.X.ToString("F6") & _
                              ", y=" & y.X.ToString("F6"))
        ElseIf model.Status = GRB.Status.INF_OR_UNBD Then
            Console.WriteLine("Model is infeasible or unbounded")
        Else
            Console.WriteLine("Optimization was stopped early")
        End If

        ' Dispose of model and env
        model.Dispose()
        env.Dispose()
    End Sub

    ' nlconstrNLAPIAdv(): formulates the model with the advanced
    ' expression-tree variant of AddNLConstr(), where the left-hand side of
    ' each constraint is described with arrays of opcodes, data, and parents.
    Shared Sub nlconstrNLAPIAdv()
        ' Create environment
        Dim env As GRBEnv = New GRBEnv("nlconstr.log")

        ' Create empty model
        Dim model As GRBModel = New GRBModel(env)

        ' Create variables
        Dim x As GRBVar = model.AddVar(-1.0, 2.0, 1.0, GRB.CONTINUOUS, "x")
        Dim y As GRBVar = model.AddVar(0.0, 2.0, -1.0, GRB.CONTINUOUS, "y")

        ' Expression tree for sin(x) * x + x^2 * y (10 nodes)
        '
        '   node 0: PLUS       (root)
        '   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
        '   node 2: SIN        (child of 1)
        '   node 3: VARIABLE x (child of 2)
        '   node 4: VARIABLE x (child of 1)
```

(continues on next page)

(continued from previous page)

```
        '   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
        '   node 6: POW        (child of 5)
        '   node 7: VARIABLE x (child of 6)
        '   node 8: CONSTANT 2 (child of 6)
        '   node 9: VARIABLE y (child of 5)

        Dim opcode1 As Integer() = New Integer() { _
            GRB.OPCODE_PLUS, _
            GRB.OPCODE_MULTIPLY, _
            GRB.OPCODE_SIN, _
            GRB.OPCODE_VARIABLE, _
            GRB.OPCODE_VARIABLE, _
            GRB.OPCODE_MULTIPLY, _
            GRB.OPCODE_POW, _
            GRB.OPCODE_VARIABLE, _
            GRB.OPCODE_CONSTANT, _
            GRB.OPCODE_VARIABLE _
        }
        Dim data1 As Double() = New Double() { _
            -1.0, -1.0, -1.0, _
            x.Index, _
            x.Index, _
            -1.0, -1.0, _
            x.Index, _
            2.0, _
            y.Index _
        }
        Dim parent1 As Integer() = New Integer() {-1, 0, 1, 2, 1, 0, 5, 6, 6, 5}

        ' Expression tree for cos(x) - y = 0 (4 nodes)
        '
        '   node 0: MINUS      (root)
        '   node 1: COS        (child of 0)
        '   node 2: VARIABLE x (child of 1)
        '   node 3: VARIABLE y (child of 0)

        Dim opcode2 As Integer() = New Integer() { _
            GRB.OPCODE_MINUS, _
            GRB.OPCODE_COS, _
            GRB.OPCODE_VARIABLE, _
            GRB.OPCODE_VARIABLE _
        }
        Dim data2 As Double() = New Double() { _
            -1.0, -1.0, _
            x.Index, _
            y.Index _
        }
        Dim parent2 As Integer() = New Integer() {-1, 0, 1, 0}

        ' Add nonlinear constraint: sin(x)*x + x^2*y <= 1
        Dim nlc1 As GRBNLConstr = model.AddNLConstr(opcode1, data1, parent1, _
                                                    GRB.LESS_EQUAL, 1.0, _
```

(continues on next page)

(continued from previous page)

```
                                                "NonlinearConstraint1")

    ' Add nonlinear constraint: cos(x) - y = 0
    Dim nlc2 As GRBNLConstr = model.AddNLConstr(opcode2, data2, parent2, _
                                                GRB.EQUAL, 0.0, _
                                                "NonlinearConstraint2")

    ' Optimize model
    model.Optimize()

    Console.WriteLine("")
    Console.WriteLine("First solve (nonlinear constraints)")
    If model.Status = GRB.Status.OPTIMAL Then
        Console.WriteLine("Optimal objective: " & model.ObjVal.ToString("E4"))
        Console.WriteLine("  x=" & x.X.ToString("F6") & _
                          ", y=" & y.X.ToString("F6"))
    ElseIf model.Status = GRB.Status.INF_OR_UNBD Then
        Console.WriteLine("Model is infeasible or unbounded")
    Else
        Console.WriteLine("Optimization was stopped early")
    End If

    ' Retrieve the first nonlinear constraint and print the number of nodes
    Dim nnodes As Integer
    model.GetNLConstrLHS(nlc1, nnodes, Nothing, Nothing, Nothing)
    Console.WriteLine("")
    Console.WriteLine("Retrieved NL constraint with " & nnodes & " nodes")

    ' Delete the nonlinear constraints
    model.Remove(nlc1)
    model.Remove(nlc2)
    model.Update()
    Console.WriteLine("Deleted nonlinear constraints")

    ' Add a simple linear constraint instead: x + y >= 1
    model.AddConstr(x + y, GRB.GREATER_EQUAL, 1.0, "LinearConstraint")

    ' Re-optimize
    model.Optimize()

    Console.WriteLine("")
    Console.WriteLine("Second solve (linear constraint)")
    If model.Status = GRB.Status.OPTIMAL Then
        Console.WriteLine("Optimal objective: " & model.ObjVal.ToString("E4"))
        Console.WriteLine("  x=" & x.X.ToString("F6") & _
                          ", y=" & y.X.ToString("F6"))
    ElseIf model.Status = GRB.Status.INF_OR_UNBD Then
        Console.WriteLine("Model is infeasible or unbounded")
    Else
        Console.WriteLine("Optimization was stopped early")
    End If
```

(continues on next page)

(continued from previous page)

```
        ' Dispose of model and env
        model.Dispose()
        env.Dispose()
    End Sub
End Class
```

nlobj_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example formulates and solves the following simple nonlinear model
' using the nonlinear objective API:
'
'     minimize    sin(x) * x + x^2 * y
'     subject to  x + y  >= 1
'                -1 <= x <= 2
'                 0 <= y <= 2
'
' The example is split into two functions that show two ways to build a
' nonlinear objective with the new NL API:
'
'   - nlobjNLAPI(): uses the nonlinear expression API. The nonlinear
'     objective is built as a GRBNLExpr object with the overloaded
'     operators, the nonlinear functions hosted on GRBNLExpr, and the Pow()
'     helper, and passed directly to SetNLObj().
'
'   - nlobjNLAPIAdv(): uses the advanced expression-tree variant of
'     SetNLObj(), where the nonlinear expression is described
'     with arrays of opcodes, data, and parent pointers.
'
' In both cases we retrieve the nonlinear objective with GetNLObj(),
' delete it with DelNLObj(), replace it with a simple linear objective, and
' re-optimize.


Imports System
Imports Gurobi

Class nlobj_vb
    ' Run both ways of building nonlinear objectives: the nonlinear
    ' expression API and the advanced expression-tree API.
    Shared Sub Main()
        Try
            ' First, the nonlinear expression API
            nlobjNLAPI()

            ' Then, the advanced expression-tree API
            nlobjNLAPIAdv()

        Catch e As GRBException
```

(continues on next page)

(continued from previous page)

```
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub

    ' nlobjNLAPI(): formulates the nonlinear objective with the nonlinear
    ' expression API, passing a GRBNLExpr object to SetNLObj().
    Shared Sub nlobjNLAPI()
        ' Create environment
        Dim env As GRBEnv = New GRBEnv("nlobj.log")

        ' Create empty model
        Dim model As GRBModel = New GRBModel(env)

        ' Create variables
        Dim x As GRBVar = model.AddVar(-1.0, 2.0, 0.0, GRB.CONTINUOUS, "x")
        Dim y As GRBVar = model.AddVar(0.0, 2.0, 0.0, GRB.CONTINUOUS, "y")

        ' Add constraint: x + y >= 1
        model.AddConstr(x + y, GRB.GREATER_EQUAL, 1.0, "c0")

        ' Add nonlinear objective: sin(x)*x + x^2*y.
        ' The nonlinear expression is built as a GRBNLExpr:
        '   GRBNLExpr.Sin(x)      -> sin(x)
        '   GRBNLExpr.Pow(x, 2.0) -> x^2 (a SQUARE node)
        model.SetNLObj(GRBNLExpr.Sin(x) * x + GRBNLExpr.Pow(x, 2.0) * y)

        ' Optimize model
        model.Optimize()

        Console.WriteLine("")
        Console.WriteLine("First solve (nonlinear objective)")
        If model.Status = GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimal objective: " & model.ObjVal.ToString("E4"))
            Console.WriteLine("  x=" & x.X.ToString("F6") & _
                              ", y=" & y.X.ToString("F6"))
        Else
            Console.WriteLine("Optimization did not produce an optimal solution")
        End If

        ' Retrieve the nonlinear objective as a GRBNLExpr and print it
        Dim nlobj As GRBNLExpr = model.GetNLObj()
        Console.WriteLine("")
        Console.WriteLine("Retrieved NL objective: """ & nlobj.ToString() & """")

        ' Delete the nonlinear objective
        model.DelNLObj()
        Console.WriteLine("Deleted nonlinear objective")

        ' Set a simple linear objective instead: minimize x + y
        model.SetObjective(x + y, GRB.MINIMIZE)

        ' Re-optimize
```

(continues on next page)

(continued from previous page)

```
        model.Optimize()

        Console.WriteLine("")
        Console.WriteLine("Second solve (linear objective)")
        If model.Status = GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimal objective: " & model.ObjVal.ToString("E4"))
            Console.WriteLine("  x=" & x.X.ToString("F6") & _
                              ", y=" & y.X.ToString("F6"))
        Else
            Console.WriteLine("Optimization did not produce an optimal solution")
        End If

        ' Dispose of model and env
        model.Dispose()
        env.Dispose()
    End Sub

    ' nlobjNLAPIAdv(): formulates the nonlinear objective with the advanced
    ' expression-tree variant of SetNLObj(), where the nonlinear expression
    ' is described with arrays of opcodes, data, and parent pointers.
    Shared Sub nlobjNLAPIAdv()
        ' Create environment
        Dim env As GRBEnv = New GRBEnv("nlobj.log")

        ' Create empty model
        Dim model As GRBModel = New GRBModel(env)

        ' Create variables
        Dim x As GRBVar = model.AddVar(-1.0, 2.0, 0.0, GRB.CONTINUOUS, "x")
        Dim y As GRBVar = model.AddVar(0.0, 2.0, 0.0, GRB.CONTINUOUS, "y")

        ' Add constraint: x + y >= 1
        model.AddConstr(x + y, GRB.GREATER_EQUAL, 1.0, "c0")

        ' Expression tree for sin(x) * x + x^2 * y (10 nodes)
        '
        '   node 0: PLUS       (root)
        '   node 1: MULTIPLY   (child of 0)  ->  sin(x) * x
        '   node 2: SIN        (child of 1)
        '   node 3: VARIABLE x (child of 2)
        '   node 4: VARIABLE x (child of 1)
        '   node 5: MULTIPLY   (child of 0)  ->  x^2 * y
        '   node 6: POW        (child of 5)
        '   node 7: VARIABLE x (child of 6)
        '   node 8: CONSTANT 2 (child of 6)
        '   node 9: VARIABLE y (child of 5)

        Dim opcode As Integer() = New Integer() { _
            GRB.OPCODE_PLUS, _
            GRB.OPCODE_MULTIPLY, _
            GRB.OPCODE_SIN, _
            GRB.OPCODE_VARIABLE, _
```

(continues on next page)

(continued from previous page)

```
            GRB.OPCODE_VARIABLE, _
            GRB.OPCODE_MULTIPLY, _
            GRB.OPCODE_POW, _
            GRB.OPCODE_VARIABLE, _
            GRB.OPCODE_CONSTANT, _
            GRB.OPCODE_VARIABLE _
        }
        Dim data As Double() = New Double() { _
            -1.0, -1.0, -1.0, _
            x.Index, _
            x.Index, _
            -1.0, -1.0, _
            x.Index, _
            2.0, _
            y.Index _
        }
        Dim parent As Integer() = New Integer() {-1, 0, 1, 2, 1, 0, 5, 6, 6, 5}

        ' Set nonlinear objective
        model.SetNLObj(opcode, data, parent)

        ' Optimize model
        model.Optimize()

        Console.WriteLine("")
        Console.WriteLine("First solve (nonlinear objective)")
        If model.Status = GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimal objective: " & model.ObjVal.ToString("E4"))
            Console.WriteLine("  x=" & x.X.ToString("F6") & _
                              ", y=" & y.X.ToString("F6"))
        Else
            Console.WriteLine("Optimization did not produce an optimal solution")
        End If

        ' Retrieve the nonlinear objective and print the number of nodes
        Dim nnodes As Integer
        model.GetNLObj(nnodes, Nothing, Nothing, Nothing)
        Console.WriteLine("")
        Console.WriteLine("Retrieved NL objective with " & nnodes & " nodes")

        ' Delete the nonlinear objective
        model.DelNLObj()
        Console.WriteLine("Deleted nonlinear objective")

        ' Set a simple linear objective instead: minimize x + y
        model.SetObjective(x + y, GRB.MINIMIZE)

        ' Re-optimize
        model.Optimize()

        Console.WriteLine("")
        Console.WriteLine("Second solve (linear objective)")
```

(continues on next page)

(continued from previous page)

```
        If model.Status = GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimal objective: " & model.ObjVal.ToString("E4"))
            Console.WriteLine("  x=" & x.X.ToString("F6") & _
                              ", y=" & y.X.ToString("F6"))
        Else
            Console.WriteLine("Optimization did not produce an optimal solution")
        End If

        ' Dispose of model and env
        model.Dispose()
        env.Dispose()
    End Sub
End Class
```

lp_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example reads an LP model from a file and solves it.
' If the model is infeasible or unbounded, the example turns off
' presolve and solves the model again. If the model is infeasible,
' the example computes an Irreducible Inconsistent Subsystem (IIS),
' and writes it to a file.

Imports System
Imports Gurobi

Class lp_vb
    Shared Sub Main(ByVal args As String())

        If args.Length < 1 Then
            Console.WriteLine("Usage: lp_vb filename")
            Return
        End If

        Try
            Dim env As GRBEnv = New GRBEnv("lp1.log")
            Dim model As GRBModel = New GRBModel(env, args(0))

            model.Optimize()

            Dim optimstatus As Integer = model.Status

            If optimstatus = GRB.Status.INF_OR_UNBD Then
                model.Parameters.Presolve = 0
                model.Optimize()
                optimstatus = model.Status
            End If

            If optimstatus = GRB.Status.OPTIMAL Then
```

(continues on next page)

(continued from previous page)

```
            Dim objval As Double = model.ObjVal
            Console.WriteLine("Optimal objective: " & objval)
        ElseIf optimstatus = GRB.Status.INFEASIBLE Then
            Console.WriteLine("Model is infeasible")
            model.ComputeIIS()
            model.Write("model.ilp")
        ElseIf optimstatus = GRB.Status.UNBOUNDED Then
            Console.WriteLine("Model is unbounded")
        Else
            Console.WriteLine("Optimization was stopped with status = " & _
                              optimstatus)
        End If

        ' Dispose of model and env
        model.Dispose()
        env.Dispose()

    Catch e As GRBException
        Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
    End Try
  End Sub
End Class
```

lpmethod_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' Solve a model with different values of the Method parameter;
' show which value gives the shortest solve time.

Imports System
Imports Gurobi

Class lpmethod_vb

  Shared Sub Main(ByVal args As String())

    If args.Length < 1 Then
      Console.WriteLine("Usage: lpmethod_vb filename")
      Return
    End If

    Try
      ' Read model and verify that it is a MIP
      Dim env As New GRBEnv()
      Dim model As New GRBModel(env, args(0))

      ' Solve the model with different values of Method
      Dim bestMethod As Integer = -1
      Dim bestTime As Double = model.get(GRB.DoubleParam.TimeLimit)
```

(continues on next page)

(continued from previous page)

```
            For i As Integer = 0 To 2
                model.Reset()
                model.Parameters.Method = i
                model.Optimize()
                If model.Status = GRB.Status.OPTIMAL Then
                    bestTime = model.Runtime
                    bestMethod = i
                    ' Reduce the TimeLimit parameter to save time
                    ' with other methods
                    model.Parameters.TimeLimit = bestTime
                End If
            Next

            ' Report which method was fastest
            If bestMethod = -1 Then
                Console.WriteLine("Unable to solve this model")
            Else
                Console.WriteLine("Solved in " & bestTime & _
                                  " seconds with Method: " & bestMethod)
            End If

            ' Dispose of model and env
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

lpmod_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example reads an LP model from a file and solves it.
' If the model can be solved, then it finds the smallest positive variable,
' sets its upper bound to zero, and resolves the model two ways:
' first with an advanced start, then without an advanced start
' (i.e. from scratch).

Imports System
Imports Gurobi

Class lpmod_vb
    Shared Sub Main(ByVal args As String())

        If args.Length < 1 Then
            Console.WriteLine("Usage: lpmod_vb filename")
            Return
```

(continues on next page)

(continued from previous page)

```
        End If

        Try
            ' Read model and determine whether it is an LP
            Dim env As New GRBEnv()
            Dim model As New GRBModel(env, args(0))
            If model.IsMIP <> 0 Then
                Console.WriteLine("The model is not a linear program")
                Environment.Exit(1)
            End If

            model.Optimize()

            Dim status As Integer = model.Status

            If (status = GRB.Status.INF_OR_UNBD) OrElse _
               (status = GRB.Status.INFEASIBLE) OrElse _
               (status = GRB.Status.UNBOUNDED) Then
                Console.WriteLine("The model cannot be solved because it is " & _
                                  "infeasible or unbounded")
                Environment.Exit(1)
            End If

            If status <> GRB.Status.OPTIMAL Then
                Console.WriteLine("Optimization was stopped with status " & status)
                Environment.Exit(0)
            End If

            ' Find the smallest variable value
            Dim minVal As Double = GRB.INFINITY
            Dim minVar As GRBVar = Nothing
            For Each v As GRBVar In model.GetVars()
                Dim sol As Double = v.X
                If (sol > 0.0001) AndAlso _
                   (sol < minVal) AndAlso _
                   (v.LB = 0.0) Then
                    minVal = sol
                    minVar = v
                End If
            Next

            Console.WriteLine(vbLf & "*** Setting " & _
                              minVar.VarName & " from " & minVal & " to zero ***" & vbLf)
            minVar.UB = 0

            ' Solve from this starting point
            model.Optimize()

            ' Save iteration & time info
            Dim warmCount As Double = model.IterCount
            Dim warmTime As Double = model.Runtime
```

(continues on next page)

(continued from previous page)

```
            ' Reset the model and resolve
            Console.WriteLine(vbLf & "*** Resetting and solving " & _
                              "without an advanced start ***" & vbLf)
            model.Reset()
            model.Optimize()

            Dim coldCount As Double = model.IterCount
            Dim coldTime As Double = model.Runtime

            Console.WriteLine(vbLf & "*** Warm start: " & warmCount & _
                              " iterations, " & warmTime & " seconds")

            Console.WriteLine("*** Cold start: " & coldCount & " iterations, " & _
                              coldTime & " seconds")

            ' Dispose of model and env
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

mip1_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example formulates and solves the following simple MIP model:
'
'    maximize    x +   y + 2 z
'    subject to  x + 2 y + 3 z <= 4
'                x +   y       >= 1
'                x, y, z binary

Imports System
Imports Gurobi

Class mip1_vb
    Shared Sub Main()
        Try
            Dim env As GRBEnv = New GRBEnv("mip1.log")
            Dim model As GRBModel = New GRBModel(env)

            ' Create variables

            Dim x As GRBVar = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, "x")
            Dim y As GRBVar = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, "y")
            Dim z As GRBVar = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, "z")
```

(continues on next page)

(continued from previous page)

```
            ' Set objective: maximize x + y + 2 z

            model.SetObjective(x + y + 2 * z, GRB.MAXIMIZE)

            ' Add constraint: x + 2 y + 3 z <= 4

            model.AddConstr(x + 2 * y + 3 * z <= 4.0, "c0")

            ' Add constraint: x + y >= 1

            model.AddConstr(x + 2 * y + 3 * z <= 4.0, "c1")

            ' Optimize model

            model.Optimize()

            Console.WriteLine(x.VarName & " " & x.X)
            Console.WriteLine(y.VarName & " " & y.X)
            Console.WriteLine(z.VarName & " " & z.X)

            Console.WriteLine("Obj: " & model.ObjVal)

            ' Dispose of model and env

            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

mip2_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example reads a MIP model from a file, solves it and
' prints the objective values from all feasible solutions
' generated while solving the MIP. Then it creates the fixed
' model and solves that model.


Imports System
Imports Gurobi

Class mip2_vb
    Shared Sub Main(ByVal args As String())
```

(continues on next page)

(continued from previous page)

```
        If args.Length < 1 Then
            Console.WriteLine("Usage: mip2_vb filename")
            Return
        End If

        Try
            Dim env As GRBEnv = New GRBEnv("lp1.log")
            Dim model As GRBModel = New GRBModel(env, args(0))

            If model.IsMIP = 0 Then
                Console.WriteLine("Model is not a MIP")
                Return
            End If

            model.Optimize()

            Dim optimstatus As Integer = model.Status

            If optimstatus = GRB.Status.INF_OR_UNBD Then
                model.Parameters.Presolve = 0
                model.Optimize()
                optimstatus = model.Status
            End If

            Dim objval As Double

            If optimstatus = GRB.Status.OPTIMAL Then
                objval = model.ObjVal
                Console.WriteLine("Optimal objective: " & objval)
            ElseIf optimstatus = GRB.Status.INFEASIBLE Then
                Console.WriteLine("Model is infeasible")
                model.ComputeIIS()
                model.Write("model.ilp")
                Return
            ElseIf optimstatus = GRB.Status.UNBOUNDED Then
                Console.WriteLine("Model is unbounded")
                Return
            Else
                Console.WriteLine("Optimization was stopped with status = " & _
                                  optimstatus)
                Return
            End If

            ' Iterate over the solutions and compute the objectives

            Console.WriteLine()
            For k As Integer = 0 To model.SolCount - 1
                model.Parameters.SolutionNumber = k
                Dim objn As Double = model.PoolNObjVal

                Console.WriteLine("Solution " & k & " has objective: " & objn)
            Next
```

(continues on next page)

(continued from previous page)

```
            Console.WriteLine()

            ' Solve fixed model
            Dim fixedmodel As GRBModel = model.FixedModel()
            fixedmodel.Parameters.Presolve = 0
            fixedmodel.Optimize()

            Dim foptimstatus As Integer = fixedmodel.Status
            If foptimstatus <> GRB.Status.OPTIMAL Then
                Console.WriteLine("Error: fixed model isn't optimal")
                Return
            End If

            Dim fobjval As Double = fixedmodel.ObjVal

            If Math.Abs(fobjval - objval) > 0.000001 * (1.0 + Math.Abs(objval)) Then
            End If

            Dim fvars() As GRBVar = fixedmodel.GetVars()
            Dim x() As Double = fixedmodel.Get(GRB.DoubleAttr.X, fvars)
            Dim vnames() As String = fixedmodel.Get(GRB.StringAttr.VarName, fvars)

            For j As Integer = 0 To fvars.Length - 1
                If x(j) <> 0 Then
                    Console.WriteLine(vnames(j) & " " & x(j))
                End If
            Next

            ' Dispose of models and env
            fixedmodel.Dispose()
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

multiobj_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' Want to cover four different sets but subject to a common budget of
' elements allowed to be used. However, the sets have different priorities to
' be covered; and we tackle this by using multi-objective optimization.

Imports Gurobi

Class multiobj_vb
```

(continues on next page)

(continued from previous page)

```
Shared Sub Main()

    Try
        ' Sample data
        Dim groundSetSize As Integer = 20
        Dim nSubsets As Integer = 4
        Dim Budget As Integer = 12

        Dim [Set] As Double(,) = New Double(,) { _
            {1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0}, _
            {0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1}, _
            {0, 0, 0, 1, 1, 0, 1, 1, 0, 0, 0, 0, 0, 1, 1, 0, 1, 1, 0, 0}, _
            {0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0}}

        Dim SetObjPriority As Integer() = New Integer() {3, 2, 2, 1}
        Dim SetObjWeight As Double() = New Double() {1.0, 0.25, 1.25, 1.0}
        Dim e As Integer, i As Integer, status As Integer, nSolutions As Integer

        ' Create environment
        Dim env As New GRBEnv("multiobj_vb.log")

        ' Create initial model
        Dim model As New GRBModel(env)
        model.ModelName = "multiobj_vb"

        ' Initialize decision variables for ground set:
        ' x[e] == 1 if element e is chosen for the covering.
        Dim Elem As GRBVar() = model.AddVars(groundSetSize, GRB.BINARY)
        For e = 0 To groundSetSize - 1
            Dim vname As String = "El" & e.ToString()
            Elem(e).VarName = vname
        Next

        ' Constraint: limit total number of elements to be picked to be at most
        ' Budget
        Dim lhs As New GRBLinExpr()
        For e = 0 To groundSetSize - 1
            lhs.AddTerm(1.0, Elem(e))
        Next
        model.AddConstr(lhs, GRB.LESS_EQUAL, Budget, "Budget")

        ' Set global sense for ALL objectives
        model.ModelSense = GRB.MAXIMIZE

        ' Limit how many solutions to collect
        model.Parameters.PoolSolutions = 100

        ' Set and configure i-th objective
        For i = 0 To nSubsets - 1
            Dim vname As String = String.Format("Set{0}", i)
            Dim objn As New GRBLinExpr()
```

(continues on next page)

(continued from previous page)

```
            For e = 0 To groundSetSize - 1
                objn.AddTerm([Set](i, e), Elem(e))
            Next

            model.SetObjectiveN(objn, i, SetObjPriority(i), SetObjWeight(i), _
                                1.0 + i, 0.01, vname)
        Next

        ' Save problem
        model.Write("multiobj_vb.lp")

        ' Optimize
        model.Optimize()

        ' Status checking
        status = model.Status

        If status = GRB.Status.INF_OR_UNBD OrElse _
           status = GRB.Status.INFEASIBLE OrElse _
           status = GRB.Status.UNBOUNDED Then
            Console.WriteLine("The model cannot be solved " & _
                      "because it is infeasible or unbounded")
            Return
        End If
        If status <> GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimization was stopped with status {0}", status)
            Return
        End If

        ' Print best selected set
        Console.WriteLine("Selected elements in best solution:")
        Console.Write(vbTab)
        For e = 0 To groundSetSize - 1
            If Elem(e).X < 0.9 Then
                Continue For
            End If
            Console.Write("El{0} ", e)
        Next
        Console.WriteLine()

        ' Print number of solutions stored
        nSolutions = model.SolCount
        Console.WriteLine("Number of solutions found: {0}", nSolutions)

        ' Print objective values of solutions
        If nSolutions > 10 Then
            nSolutions = 10
        End If
        Console.WriteLine("Objective values for first {0} solutions:", nSolutions)
        For i = 0 To nSubsets - 1
            model.Parameters.ObjNumber = i
```

(continues on next page)

(continued from previous page)

```
                Console.Write(vbTab & "Set" & i)
                For e = 0 To nSolutions - 1
                    model.Parameters.SolutionNumber = e
                    Console.Write("{0,8}", model.ObjNVal)
                Next
                Console.WriteLine()
            Next

            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code = {0}", e)
            Console.WriteLine(e.Message)

        End Try
    End Sub
End Class
```

multiscenario_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' Facility location: a company currently ships its product from 5 plants
' to 4 warehouses. It is considering closing some plants to reduce
' costs. What plant(s) should the company close, in order to minimize
' transportation and fixed costs?
'
' Since the plant fixed costs and the warehouse demands are uncertain, a
' scenario approach is chosen.
'
' Note that this example is similar to the facility_vb.vb example. Here we
' added scenarios in order to illustrate the multi-scenario feature.
'
' Based on an example from Frontline Systems:
' http://www.solver.com/disfacility.htm
' Used with permission.

Imports System
Imports Gurobi

Class multiscenario_vb
   Shared Sub Main()
   Try

   ' Warehouse demand in thousands of units
   Dim Demand As Double() = New Double() {15, 18, 14, 20}

   ' Plant capacity in thousands of units
   Dim Capacity As Double() = New Double() {20, 22, 17, 19, 18}
```

(continues on next page)

(continued from previous page)

```
' Fixed costs for each plant
Dim FixedCosts As Double() = New Double() {12000, 15000, 17000, 13000, 16000}

' Transportation costs per thousand units
Dim TransCosts As Double(,) = New Double(,) { {4000, 2000, 3000, 2500, 4500}, _
                                              {2500, 2600, 3400, 3000, 4000}, _
                                              {1200, 1800, 2600, 4100, 3000}, _
                                              {2200, 2600, 3100, 3700, 3200}}

' Number of plants and warehouses
Dim nPlants As Integer = Capacity.Length
Dim nWarehouses As Integer = Demand.Length

Dim maxFixed As Double = -GRB.INFINITY
Dim minFixed As Double = GRB.INFINITY
For p As Integer = 0 To nPlants - 1
   If FixedCosts(p) > maxFixed Then maxFixed = FixedCosts(p)
   If FixedCosts(p) < minFixed Then minFixed = FixedCosts(p)
Next

' Model
Dim env As GRBEnv = New GRBEnv()
Dim model As GRBModel = New GRBModel(env)

model.ModelName = "multiscenario"

' Plant open decision variables: open(p) == 1 if plant p is open.
Dim open As GRBVar() = New GRBVar(nPlants - 1) {}
For p As Integer = 0 To nPlants - 1
   open(p) = model.AddVar(0, 1, FixedCosts(p), GRB.BINARY, "Open" & p)
Next

' Transportation decision variables: how much to transport from a plant
' p to a warehouse w
Dim transport As GRBVar(,) = New GRBVar(nWarehouses - 1, nPlants - 1) {}
For w As Integer = 0 To nWarehouses - 1
   For p As Integer = 0 To nPlants - 1
      transport(w, p) = model.AddVar(0, GRB.INFINITY, TransCosts(w, p), _
                                     GRB.CONTINUOUS, "Trans" & p & "." & w)
   Next
Next

' The objective is to minimize the total fixed and variable costs
model.ModelSense = GRB.MINIMIZE

' Production constraints
' Note that the right-hand limit sets the production to zero if
' the plant is closed
For p As Integer = 0 To nPlants - 1
   Dim ptot As GRBLinExpr = 0.0
```

(continues on next page)

(continued from previous page)

```
    For w As Integer = 0 To nWarehouses - 1
        ptot.AddTerm(1.0, transport(w, p))
    Next

    model.AddConstr(ptot <= Capacity(p) * open(p), "Capacity" & p)
Next

' Demand constraints
Dim demandConstr As GRBConstr() = New GRBConstr(nWarehouses - 1) {}
For w As Integer = 0 To nWarehouses - 1
    Dim dtot As GRBLinExpr = 0.0

    For p As Integer = 0 To nPlants - 1
        dtot.AddTerm(1.0, transport(w, p))
    Next

    demandConstr(w) = model.AddConstr(dtot = Demand(w), "Demand" & w)
Next

' We constructed the base model, now we add 7 scenarios
'
' Scenario 0: Represents the base model, hence, no manipulations.
' Scenario 1: Manipulate the warehouses demands slightly (constraint right
'             hand sides).
' Scenario 2: Double the warehouses demands (constraint right hand sides).
' Scenario 3: Manipulate the plant fixed costs (objective coefficients).
' Scenario 4: Manipulate the warehouses demands and fixed costs.
' Scenario 5: Force the plant with the largest fixed cost to stay open
'             (variable bounds).
' Scenario 6: Force the plant with the smallest fixed cost to be closed
'             (variable bounds).

model.NumScenarios = 7

' Scenario 0: Base model, hence, nothing to do except giving the
'             scenario a name
model.Parameters.ScenarioNumber = 0
model.ScenNName = "Base model"

' Scenario 1: Increase the warehouse demands by 10%
model.Parameters.ScenarioNumber = 1
model.ScenNName = "Increased warehouse demands"

For w As Integer = 0 To nWarehouses - 1
    demandConstr(w).ScenNRHS = Demand(w) * 1.1
Next

' Scenario 2: Double the warehouse demands
model.Parameters.ScenarioNumber = 2
model.ScenNName = "Double the warehouse demands"

For w As Integer = 0 To nWarehouses - 1
```

(continues on next page)

(continued from previous page)

```
    demandConstr(w).ScenNRHS = Demand(w) * 2.0
Next

' Scenario 3: Decrease the plant fixed costs by 5%
model.Parameters.ScenarioNumber = 3
model.ScenNName = "Decreased plant fixed costs"

For p As Integer = 0 To nPlants - 1
    open(p).ScenNObj = FixedCosts(p) * 0.95
Next

' Scenario 4: Combine scenario 1 and scenario 3 */
model.Parameters.ScenarioNumber = 4
model.ScenNName = "Increased warehouse demands and decreased plant fixed costs"

For w As Integer = 0 To nWarehouses - 1
    demandConstr(w).ScenNRHS = Demand(w) * 1.1
Next

For p As Integer = 0 To nPlants - 1
    open(p).ScenNObj = FixedCosts(p) * 0.95
Next

' Scenario 5: Force the plant with the largest fixed cost to stay
'             open
model.Parameters.ScenarioNumber = 5
model.ScenNName = "Force plant with largest fixed cost to stay open"

For p As Integer = 0 To nPlants - 1

    If FixedCosts(p) = maxFixed Then
        open(p).ScenNLB = 1.0
        Exit For
    End If
Next

' Scenario 6: Force the plant with the smallest fixed cost to be
'             closed
model.Parameters.ScenarioNumber = 6
model.ScenNName = "Force plant with smallest fixed cost to be closed"

For p As Integer = 0 To nPlants - 1

    If FixedCosts(p) = minFixed Then
        open(p).ScenNUB = 0.0
        Exit For
    End If
Next

' Guess at the starting point: close the plant with the highest fixed
' costs; open all others
```

(continues on next page)

(continued from previous page)

```
   ' First, open all plants
   For p As Integer = 0 To nPlants - 1
      open(p).Start = 1.0
   Next

   ' Now close the plant with the highest fixed cost
   Console.WriteLine("Initial guess:")
   For p As Integer = 0 To nPlants - 1

      If FixedCosts(p) = maxFixed Then
         open(p).Start = 0.0
         Console.WriteLine("Closing plant " & p & vbLf)
         Exit For
      End If
   Next

   ' Use barrier to solve root relaxation
   model.Parameters.Method = GRB.METHOD_BARRIER

   ' Solve multi-scenario model
   model.Optimize()
   Dim nScenarios As Integer = model.NumScenarios

   For s As Integer = 0 To nScenarios - 1
      Dim modelSense As Integer = GRB.MINIMIZE

      ' Set the scenario number to query the information for this scenario
      model.Parameters.ScenarioNumber = s

      ' collect result for the scenario
      Dim scenNObjBound As Double = model.ScenNObjBound
      Dim scenNObjVal As Double = model.ScenNObjVal

      Console.WriteLine(vbLf & vbLf & "------ Scenario " & s & " (" & model.ScenNName &
↪")")

      ' Check if we found a feasible solution for this scenario
      If modelSense * scenNObjVal >= GRB.INFINITY Then
         If modelSense * scenNObjBound >= GRB.INFINITY Then
            ' Scenario was proven to be infeasible
            Console.WriteLine(vbLf & "INFEASIBLE")
         Else
            ' We did not find any feasible solution - should not happen in
            ' this case, because we did not set any limit (like a time
            ' limit) on the optimization process
            Console.WriteLine(vbLf & "NO SOLUTION")
         End If
      Else
         Console.WriteLine(vbLf & "TOTAL COSTS: " & scenNObjVal)
         Console.WriteLine("SOLUTION:")

         For p As Integer = 0 To nPlants - 1
```

(continues on next page)

(continued from previous page)

```
            Dim scenNX As Double = open(p).ScenNX

            If scenNX > 0.5 Then
               Console.WriteLine("Plant " & p & " open")

               For w As Integer = 0 To nWarehouses - 1
                  scenNX = transport(w, p).ScenNX
                  If scenNX > 0.0001 Then Console.WriteLine("  Transport " & scenNX & "␣
↪units to warehouse " & w)
               Next
            Else
               Console.WriteLine("Plant " & p & " closed!")
            End If
         Next
      End If
   Next

   ' Print a summary table: for each scenario we add a single summary line
   Console.WriteLine(vbLf & vbLf & "Summary: Closed plants depending on scenario" & vbLf)
   Console.WriteLine("{0,8} | {1,17} {2,13}", "", "Plant", "|")

   Console.Write("{0,8} |", "Scenario")
   For p As Integer = 0 To nPlants - 1
      Console.Write("{0,6}", p)
   Next

   Console.WriteLine(" | {0,6}  Name", "Costs")

   For s As Integer = 0 To nScenarios - 1
      Dim modelSense As Integer = GRB.MINIMIZE

      ' Set the scenario number to query the information for this scenario
      model.Parameters.ScenarioNumber = s

      ' Collect result for the scenario
      Dim scenNObjBound As Double = model.ScenNObjBound
      Dim scenNObjVal As Double = model.ScenNObjVal

      Console.Write("{0,-8} |", s)

      ' Check if we found a feasible solution for this scenario
      If modelSense * scenNObjVal >= GRB.INFINITY Then
         If modelSense * scenNObjBound >= GRB.INFINITY Then
            ' Scenario was proven to be infeasible
            Console.WriteLine(" {0,-30}| {1,6}  " & model.ScenNName, "infeasible", "-")
         Else
            ' We did not find any feasible solution - should not happen in
            ' this case, because we did not set any limit (like a Time
            ' limit) on the optimization process
            Console.WriteLine(" {0,-30}| {1,6}  " & model.ScenNName, "no solution found",
↪ "-")
         End If
```

(continues on next page)

(continued from previous page)

```
      Else

         For p As Integer = 0 To nPlants - 1
            Dim scenNX As Double = open(p).ScenNX

            If scenNX > 0.5 Then
               Console.Write("{0,6}", " ")
            Else
               Console.Write("{0,6}", "x")
            End If
         Next

         Console.WriteLine(" | {0,6}  " & model.ScenNName, scenNObjVal)
      End If
   Next

   model.Dispose()
   env.Dispose()
   Catch e As GRBException
   Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
   End Try
End Sub
End Class
```

params_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC */

' Use parameters that are associated with a model.

' A MIP is solved for a few seconds with different sets of parameters.
' The one with the smallest MIP gap is selected, and the optimization
' is resumed until the optimal solution is found.

Imports System
Imports Gurobi

Class params_vb
    Shared Sub Main(args As String())
        If args.Length < 1 Then
            Console.Out.WriteLine("Usage: params_vb filename")
            Return
        End If

        Try
            ' Read model and verify that it is a MIP
            Dim env As New GRBEnv()
            Dim m As New GRBModel(env, args(0))
            If m.IsMIP = 0 Then
                Console.WriteLine("The model is not an integer program")
```

(continues on next page)

(continued from previous page)

```
            Environment.Exit(1)
        End If

        ' Set a 2 second time limit
        m.Parameters.TimeLimit = 2.0

        ' Now solve the model with different values of MIPFocus
        Dim bestModel As New GRBModel(m)
        bestModel.Optimize()
        For i As Integer = 1 To 3
            m.Reset()
            m.Parameters.MIPFocus = i
            m.Optimize()
            If bestModel.MIPGap > m.MIPGap Then
                Dim swap As GRBModel = bestModel
                bestModel = m
                m = swap
            End If
        Next

        ' Delete the extra model, reset the time limit and
        ' continue to solve the best model to optimality
        m.Dispose()
        bestModel.Parameters.TimeLimit = GRB.INFINITY
        bestModel.Optimize()

        Console.WriteLine("Solved with MIPFocus: " & bestModel.Parameters.MIPFocus)

        ' Dispose of bestModel and env
        bestModel.Dispose()
        env.Dispose()

    Catch e As GRBException
        Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
    End Try
  End Sub
End Class
```

piecewise_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' This example considers the following separable, convex problem:
'
'    minimize    f(x) - y + g(z)
'    subject to  x + 2 y + 3 z <= 4
'                x +   y       >= 1
'                x,    y,    z <= 1
'
' where f(u) = exp(-u) and g(u) = 2 u^2 - 4 u, for all real u. It
```

(continues on next page)

(continued from previous page)

```
' formulates and solves a simpler LP model by approximating f and
' g with piecewise-linear functions. Then it transforms the model
' into a MIP by negating the approximation for f, which corresponds
' to a non-convex piecewise-linear function, and solves it again.

Imports System
Imports Gurobi

Class piecewise_vb
    Shared Function f(u As Double) As Double
        Return Math.Exp(-u)
    End Function
    Shared Function g(u As Double) As Double
        Return 2 * u * u - 4 * u
    End Function

    Shared Sub Main()
        Try
            ' Create environment

            Dim env As New GRBEnv()

            ' Create a new model

            Dim model As New GRBModel(env)

            ' Create variables

            Dim lb As Double = 0.0, ub As Double = 1.0

            Dim x As GRBVar = model.AddVar(lb, ub, 0.0, GRB.CONTINUOUS, "x")
            Dim y As GRBVar = model.AddVar(lb, ub, 0.0, GRB.CONTINUOUS, "y")
            Dim z As GRBVar = model.AddVar(lb, ub, 0.0, GRB.CONTINUOUS, "z")

            ' Set objective for y

            model.SetObjective(-y)

            ' Add piecewise-linear objective functions for x and z

            Dim npts As Integer = 101
            Dim ptu As Double() = New Double(npts - 1) {}
            Dim ptf As Double() = New Double(npts - 1) {}
            Dim ptg As Double() = New Double(npts - 1) {}

            For i As Integer = 0 To npts - 1
                ptu(i) = lb + (ub - lb) * i / (npts - 1)
                ptf(i) = f(ptu(i))
                ptg(i) = g(ptu(i))
            Next

            model.SetPWLObj(x, ptu, ptf)
```

(continues on next page)

(continued from previous page)

```
            model.SetPWLObj(z, ptu, ptg)

            ' Add constraint: x + 2 y + 3 z <= 4

            model.AddConstr(x + 2 * y + 3 * z <= 4.0, "c0")

            ' Add constraint: x + y >= 1

            model.AddConstr(x + y >= 1.0, "c1")

            ' Optimize model as an LP

            model.Optimize()

            Console.WriteLine("IsMIP: " & model.IsMIP)

            Console.WriteLine(x.VarName & " " & x.X)
            Console.WriteLine(y.VarName & " " & y.X)
            Console.WriteLine(z.VarName & " " & z.X)

            Console.WriteLine("Obj: " & model.ObjVal)

            Console.WriteLine()

            ' Negate piecewise-linear objective function for x

            For i As Integer = 0 To npts - 1
                ptf(i) = -ptf(i)
            Next

            model.SetPWLObj(x, ptu, ptf)

            ' Optimize model as a MIP

            model.Optimize()

            Console.WriteLine("IsMIP: " & model.IsMIP)

            Console.WriteLine(x.VarName & " " & x.X)
            Console.WriteLine(y.VarName & " " & y.X)
            Console.WriteLine(z.VarName & " " & z.X)

            Console.WriteLine("Obj: " & model.ObjVal)

            ' Dispose of model and environment

            model.Dispose()

            env.Dispose()
        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
```

(continues on next page)

(continued from previous page)

```
    End Sub
End Class
```

poolsearch_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' We find alternative epsilon-optimal solutions to a given knapsack
' problem by using PoolSearchMode

Imports Gurobi

Class poolsearch_vb

    Shared Sub Main()

        Try

            'Sample data
            Dim groundSetSize As Integer = 10

            Dim objCoef As Double() = New Double() { _
                32, 32, 15, 15, 6, 6, 1, 1, 1, 1}

            Dim knapsackCoef As Double() = New Double() { _
                16, 16, 8, 8, 4, 4, 2, 2, 1, 1}

            Dim Budget As Double = 33
            Dim e As Integer, status As Integer, nSolutions As Integer

            ' Create environment
            Dim env As New GRBEnv("poolsearch_vb.log")

            ' Create initial model
            Dim model As New GRBModel(env)
            model.ModelName = "poolsearch_vb"

            ' Initialize decision variables for ground set:
            ' x[e] == k if element e is chosen k-times.
            Dim Elem As GRBVar() = model.AddVars(groundSetSize, GRB.BINARY)
            model.[Set](GRB.DoubleAttr.Obj, Elem, objCoef)

            For e = 0 To groundSetSize - 1
                Elem(e).VarName = String.Format("El{0}", e)
            Next

            ' Constraint: limit total number of elements to be picked to be at most Budget
            Dim lhs As New GRBLinExpr()
            For e = 0 To groundSetSize - 1
                lhs.AddTerm(knapsackCoef(e), Elem(e))
```

(continues on next page)

(continued from previous page)

```
            Next
            model.AddConstr(lhs, GRB.LESS_EQUAL, Budget, "Budget")

            ' set global sense for ALL objectives
            model.ModelSense = GRB.MAXIMIZE

            ' Limit how many solutions to collect
            model.Parameters.PoolSolutions = 1024

            ' Limit how many solutions to collect
            model.Parameters.PoolGap = 0.1

            ' Limit how many solutions to collect
            model.Parameters.PoolSearchMode = 2

            ' save problem
            model.Write("poolsearch_vb.lp")

            ' Optimize
            model.Optimize()

            ' Status checking
            status = model.Status

            If status = GRB.Status.INF_OR_UNBD OrElse _
               status = GRB.Status.INFEASIBLE OrElse _
               status = GRB.Status.UNBOUNDED Then
                Console.WriteLine("The model cannot be solved because it is infeasible␣
↪or unbounded")
                Return
            End If
            If status <> GRB.Status.OPTIMAL Then
                Console.WriteLine("Optimization was stopped with status {0}", status)
                Return
            End If

            ' Print best selected set
            Console.WriteLine("Selected elements in best solution:")
            Console.Write(vbTab)
            For e = 0 To groundSetSize - 1
                If Elem(e).X < 0.9 Then
                    Continue For
                End If
                Console.Write("El{0} ", e)
            Next
            Console.WriteLine()

            ' Print number of solutions stored
            nSolutions = model.SolCount
            Console.WriteLine("Number of solutions found: ", nSolutions)

            ' Print objective values of solutions
```

(continues on next page)

(continued from previous page)

```
            For e = 0 To nSolutions - 1
                model.Parameters.SolutionNumber = e
                Console.Write("{0} ", model.PoolNObjVal)
                If e Mod 15 = 14 Then
                    Console.WriteLine()
                End If
            Next
            Console.WriteLine()

            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: {0}. {1}", e.ErrorCode, e.Message)

        End Try
    End Sub

End Class
```

qcp_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' This example formulates and solves the following simple QCP model:
'
'     maximize    x
'     subject to  x + y + z = 1
'                 x^2 + y^2 <= z^2 (second-order cone)
'                 x^2 <= yz        (rotated second-order cone)
'                 x, y, z non-negative

Imports Gurobi

Class qcp_vb
    Shared Sub Main()
        Try
            Dim env As New GRBEnv("qcp.log")
            Dim model As New GRBModel(env)

            ' Create variables

            Dim x As GRBVar = model.AddVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "x")
            Dim y As GRBVar = model.AddVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "y")
            Dim z As GRBVar = model.AddVar(0.0, GRB.INFINITY, 0.0, GRB.CONTINUOUS, "z")

            ' Set objective

            Dim obj As GRBLinExpr = x
            model.SetObjective(obj, GRB.MAXIMIZE)
```

(continues on next page)

(continued from previous page)

```
            ' Add linear constraint: x + y + z = 1

            model.AddConstr(x + y + z = 1.0, "c0")

            ' Add second-order cone: x^2 + y^2 <= z^2

            model.AddQConstr(x * x + y * y <= z * z, "qc0")

            ' Add rotated cone: x^2 <= yz

            model.AddQConstr(x * x <= y * z, "qc1")

            ' Optimize model

            model.Optimize()

            Console.WriteLine(x.VarName & " " & x.X)
            Console.WriteLine(y.VarName & " " & y.X)
            Console.WriteLine(z.VarName & " " & z.X)

            Console.WriteLine("Obj: " & model.ObjVal & " " & obj.Value)

            ' Dispose of model and env

            model.Dispose()

            env.Dispose()
        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

qp_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' This example formulates and solves the following simple QP model:
'
'     minimize    x^2 + x*y + y^2 + y*z + z^2 + 2 x
'     subject to  x + 2 y + 3 z >= 4
'                 x +   y       >= 1
'                 x, y, z non-negative
'
'   It solves it once as a continuous model, and once as an integer model.
'

Imports Gurobi
```

(continues on next page)

(continued from previous page)

```
Class qp_vb
    Shared Sub Main()
        Try
            Dim env As New GRBEnv("qp.log")
            Dim model As New GRBModel(env)

            ' Create variables

            Dim x As GRBVar = model.AddVar(0.0, 1.0, 0.0, GRB.CONTINUOUS, "x")
            Dim y As GRBVar = model.AddVar(0.0, 1.0, 0.0, GRB.CONTINUOUS, "y")
            Dim z As GRBVar = model.AddVar(0.0, 1.0, 0.0, GRB.CONTINUOUS, "z")

            ' Set objective

            Dim obj As New GRBQuadExpr()
            obj = x*x + x*y + y*y + y*z + z*z + 2*x
            model.SetObjective(obj)

            ' Add constraint: x + 2 y + 3 z >= 4

            model.AddConstr(x + 2 * y + 3 * z >= 4.0, "c0")

            ' Add constraint: x + y >= 1

            model.AddConstr(x + y >= 1.0, "c1")

            ' Optimize model

            model.Optimize()

            Console.WriteLine(x.VarName & " " & x.X)
            Console.WriteLine(y.VarName & " " & y.X)
            Console.WriteLine(z.VarName & " " & z.X)

            Console.WriteLine("Obj: " & model.ObjVal & " " & obj.Value)


            ' Change variable types to integer

            x.VType = GRB.INTEGER
            y.VType = GRB.INTEGER
            z.VType = GRB.INTEGER

            ' Optimize model

            model.Optimize()

            Console.WriteLine(x.VarName & " " & x.X)
            Console.WriteLine(y.VarName & " " & y.X)
            Console.WriteLine(z.VarName & " " & z.X)

            Console.WriteLine("Obj: " & model.ObjVal & " " & obj.Value)
```

(continues on next page)

(continued from previous page)

```
            ' Dispose of model and env

            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

sensitivity_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' A simple sensitivity analysis example which reads a MIP model from a
' file and solves it. Then uses the scenario feature to analyze the impact
' w.r.t. the objective function of each binary variable if it is set to
' 1-X, where X is its value in the optimal solution.
'
' Usage:
'     sensitivity_cs <model filename>

Imports System
Imports Gurobi

Class sensitivity_vb
   Shared Sub Main(args As String())

   If args.Length < 1 Then
      Console.Out.WriteLine("Usage: sensitivity_vb filename")
      Return
   End If

   Try
      ' Maximum number of scenarios to be considered
      Dim MAXSCENARIOS as Integer = 100

      ' Create environment
      Dim env As New GRBEnv()

      ' Read model
      Dim model As New GRBModel(env, args(0))

      Dim scenarios As Integer

      If model.IsMIP = 0 Then
         Console.WriteLine("Model is not a MIP")
         Return
```

(continues on next page)

(continued from previous page)

```
    End If

    ' Solve model
    model.Optimize()

    If model.Status <> GRB.Status.OPTIMAL Then
       Console.WriteLine("Optimization ended with status " & _
                         model.Status)
       Return
    End If

    ' Store the optimal solution
    Dim origObjVal As Double = model.ObjVal
    Dim vars As GRBVar()     = model.GetVars()
    Dim origX As Double()    = model.Get(GRB.DoubleAttr.X, vars)

    scenarios = 0

    ' Count number of unfixed, binary variables in model. For each we
    ' create a scenario.
    For i As Integer = 0 To vars.Length - 1
       Dim v As GRBVar   = vars(i)
       Dim vType As Char = v.VType

       If v.LB = 0.0                                        AndAlso _
          v.UB = 1.0                                        AndAlso _
          (vType = GRB.BINARY OrElse vType = GRB.INTEGER)           Then
          scenarios += 1

          If scenarios >= MAXSCENARIOS Then
             Exit For
          End If
       End If
    Next

    Console.WriteLine("###  construct multi-scenario model with " _
                      & scenarios & " scenarios")

    ' Set the number of scenarios in the model */
    model.NumScenarios = scenarios

    scenarios = 0

    ' Create a (single) scenario model by iterating through unfixed
    ' binary variables in the model and create for each of these
    ' variables a scenario by fixing the variable to 1-X, where X is its
    ' value in the computed optimal solution
    For i As Integer = 0 To vars.Length - 1
       Dim v As GRBVar   = vars(i)
       Dim vType As Char = v.VType

       If v.LB = 0.0                                        AndAlso _
```

(continues on next page)

(continued from previous page)

```
            v.UB = 1.0                                          AndAlso _
            (vType = GRB.BINARY OrElse vType = GRB.INTEGER) AndAlso _
            scenarios < MAXSCENARIOS                                    Then

            ' Set ScenarioNumber parameter to select the corresponding
            ' scenario for adjustments
            model.Parameters.ScenarioNumber = scenarios

            ' Set variable to 1-X, where X is its value in the optimal solution */
            If origX(i) < 0.5 Then
               v.ScenNLB = 1.0
            Else
               v.ScenNUB = 0.0
            End If

            scenarios += 1
         Else
            ' Add MIP start for all other variables using the optimal solution
            ' of the base model
            v.Start =  origX(i)
         End If
      Next

      ' Solve multi-scenario model
      model.Optimize()

      ' In case we solved the scenario model to optimality capture the
      ' sensitivity information
      If model.Status = GRB.Status.OPTIMAL Then
         Dim modelSense As Integer = model.ModelSense

         scenarios = 0

         For i As Integer = 0 To vars.Length - 1
            Dim v As GRBVar   = vars(i)
            Dim vType As Char = v.VType

            If v.LB = 0.0                                       AndAlso _
               v.UB = 1.0                                       AndAlso _
               (vType = GRB.BINARY OrElse vType = GRB.INTEGER)          Then

               ' Set scenario parameter to collect the objective value of the
               ' corresponding scenario
               model.Parameters.ScenarioNumber = scenarios

               ' Collect objective value and bound for the scenario
               Dim scenarioObjVal As Double = model.ScenNObjVal
               Dim scenarioObjBound As Double = model.ScenNObjBound

               Console.Write("Objective sensitivity for variable " _
                             & v.VarName & " is ")
```

(continues on next page)

(continued from previous page)

```
                ' Check if we found a feasible solution for this scenario
                If modelSense * scenarioObjVal >= GRB.INFINITY Then
                   ' Check if the scenario is infeasible
                   If modelSense * scenarioObjBound >= GRB.INFINITY Then
                      Console.WriteLine("infeasible")
                   Else
                      Console.WriteLine("unknown (no solution available)")
                   End If
                Else
                   ' Scenario is feasible and a solution is available
                   Console.WriteLine(modelSense * (scenarioObjVal - origObjVal))
                End If

                scenarios += 1

                If scenarios >= MAXSCENARIOS Then
                   Exit For

                End If
             End If
          Next
       End If

       ' Dispose of model and environment
       model.Dispose()
       env.Dispose()

    Catch e As GRBException
       Console.WriteLine("Error code: " & e.ErrorCode)
       Console.WriteLine(e.Message)
       Console.WriteLine(e.StackTrace)
    End Try
End Sub
End Class
```

sos_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' This example creates a very simple Special Ordered Set (SOS) model.
' The model consists of 3 continuous variables, no linear constraints,
' and a pair of SOS constraints of type 1.

Imports System
Imports Gurobi

Class sos_vb
    Shared Sub Main()
        Try
            Dim env As New GRBEnv()
```

(continues on next page)

(continued from previous page)

```
            Dim model As New GRBModel(env)

            ' Create variables

            Dim ub As Double() = {1, 1, 2}
            Dim obj As Double() = {-2, -1, -1}
            Dim names As String() = {"x0", "x1", "x2"}

            Dim x As GRBVar() = model.AddVars(Nothing, ub, obj, Nothing, names)

            ' Add first SOS1: x0=0 or x1=0

            Dim sosv1 As GRBVar() = {x(0), x(1)}
            Dim soswt1 As Double() = {1, 2}

            model.AddSOS(sosv1, soswt1, GRB.SOS_TYPE1)

            ' Add second SOS1: x0=0 or x2=0

            Dim sosv2 As GRBVar() = {x(0), x(2)}
            Dim soswt2 As Double() = {1, 2}

            model.AddSOS(sosv2, soswt2, GRB.SOS_TYPE1)

            ' Optimize model

            model.Optimize()

            For i As Integer = 0 To 2
                Console.WriteLine(x(i).VarName & " " & x(i).X)
            Next

            ' Dispose of model and env
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

sudoku_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' Sudoku example.
'
' The Sudoku board is a 9x9 grid, which is further divided into a 3x3 grid
' of 3x3 grids.  Each cell in the grid must take a value from 0 to 9.
' No two grid cells in the same row, column, or 3x3 subgrid may take the
' same value.

' In the MIP formulation, binary variables x(i,j,v) indicate whether
' cell <i,j> takes value 'v'.  The constraints are as follows:
'   1. Each cell must take exactly one value (sum_v x(i,j,v) = 1)
'   2. Each value is used exactly once per row (sum_i x(i,j,v) = 1)
'   3. Each value is used exactly once per column (sum_j x(i,j,v) = 1)
'   4. Each value is used exactly once per 3x3 subgrid (sum_grid x(i,j,v) = 1)
'
' Input datasets for this example can be found in examples/data/sudoku*.

Imports System
Imports System.IO
Imports Gurobi

Class sudoku_vb
    Shared Sub Main(ByVal args as String())
        Dim n As Integer = 9
        Dim s As Integer = 3

        If args.Length < 1 Then
            Console.WriteLine("Usage: sudoku_vb filename")
            Return
        End If

        Try
            Dim env As New GRBEnv()
            Dim model As New GRBModel(env)

            ' Create 3-D array of model variables

            Dim vars As GRBVar(,,) = New GRBVar(n - 1, n - 1, n - 1) {}

            For i As Integer = 0 To n - 1
                For j As Integer = 0 To n - 1
                    For v As Integer = 0 To n - 1
                        Dim st As String = "G_" & i & "_" & j & "_" & v
                        vars(i, j, v) = model.AddVar(0.0, 1.0, 0.0, GRB.BINARY, st)
                    Next
                Next
            Next

            ' Add constraints
```

(continues on next page)

(continued from previous page)

```
            Dim expr As GRBLinExpr

            ' Each cell must take one value

            For i As Integer = 0 To n - 1
                For j As Integer = 0 To n - 1
                    expr = 0
                    For v As Integer = 0 To n - 1
                        expr.AddTerm(1.0, vars(i, j, v))
                    Next
                    Dim st As String = "V_" & i & "_" & j
                    model.AddConstr(expr = 1, st)
                Next
            Next

            ' Each value appears once per row

            For i As Integer = 0 To n - 1
                For v As Integer = 0 To n - 1
                    expr = 0
                    For j As Integer = 0 To n - 1
                        expr.AddTerm(1.0, vars(i, j, v))
                    Next
                    Dim st As String = "R_" & i & "_" & v
                    model.AddConstr(expr = 1, st)
                Next
            Next

            ' Each value appears once per column

            For j As Integer = 0 To n - 1
                For v As Integer = 0 To n - 1
                    expr = 0
                    For i As Integer = 0 To n - 1
                        expr.AddTerm(1.0, vars(i, j, v))
                    Next
                    Dim st As String = "C_" & j & "_" & v
                    model.AddConstr(expr = 1, st)
                Next
            Next

            ' Each value appears once per sub-grid

            For v As Integer = 0 To n - 1
                For i0 As Integer = 0 To s - 1
                    For j0 As Integer = 0 To s - 1
                        expr = 0
                        For i1 As Integer = 0 To s - 1
                            For j1 As Integer = 0 To s - 1
                                expr.AddTerm(1.0, vars(i0 * s + i1, j0 * s + j1, v))
                            Next
                        Next
```

(continues on next page)

(continued from previous page)

```
                    Dim st As String = "Sub_" & v & "_" & i0 & "_" & j0
                    model.AddConstr(expr = 1, st)
                Next
            Next
        Next

        ' Fix variables associated with pre-specified cells

        Dim sr As StreamReader = File.OpenText(args(0))

        For i As Integer = 0 To n - 1
            Dim input As String = sr.ReadLine()
            For j As Integer = 0 To n - 1
                Dim val As Integer = Microsoft.VisualBasic.Asc(input(j)) - 48 - 1
                ' 0-based
                If val >= 0 Then
                    vars(i, j, val).LB = 1.0
                End If
            Next
        Next

        ' Optimize model

        model.Optimize()

        ' Write model to file
        model.Write("sudoku.lp")

        Dim x As Double(,,) = model.Get(GRB.DoubleAttr.X, vars)

        Console.WriteLine()
        For i As Integer = 0 To n - 1
            For j As Integer = 0 To n - 1
                For v As Integer = 0 To n - 1
                    If x(i, j, v) > 0.5 Then
                        Console.Write(v + 1)
                    End If
                Next
            Next
            Console.WriteLine()
        Next

        ' Dispose of model and env
        model.Dispose()
        env.Dispose()

    Catch e As GRBException
        Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
    End Try
  End Sub
End Class
```

tsp_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' Solve a traveling salesman problem on a randomly generated set of
' points using lazy constraints.   The base MIP model only includes
' 'degree-2' constraints, requiring each node to have exactly
' two incident edges.  Solutions to this model may contain subtours -
' tours that don't visit every node.  The lazy constraint callback
' adds new constraints to cut them off.

Imports Gurobi

Class tsp_vb
    Inherits GRBCallback
    Private vars As GRBVar(,)

    Public Sub New(xvars As GRBVar(,))
        vars = xvars
    End Sub

    ' Subtour elimination callback.    Whenever a feasible solution is found,
    ' find the smallest subtour, and add a subtour elimination constraint
    ' if the tour doesn't visit every node.

    Protected Overrides Sub Callback()
        Try
            If where = GRB.Callback.MIPSOL Then
                ' Found an integer feasible solution - does it visit every node?

                Dim n As Integer = vars.GetLength(0)
                Dim tour As Integer() = findsubtour(GetSolution(vars))

                If tour.Length < n Then
                    ' Add subtour elimination constraint
                    Dim expr As GRBLinExpr = 0
                    For i As Integer = 0 To tour.Length - 1
                        For j As Integer = i + 1 To tour.Length - 1
                            expr.AddTerm(1.0, vars(tour(i), tour(j)))
                        Next
                    Next
                    AddLazy(expr <= tour.Length - 1)
                End If
            End If
        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
            Console.WriteLine(e.StackTrace)
        End Try
    End Sub

    ' Given an integer-feasible solution 'sol', returns the smallest
    ' sub-tour (as a list of node indices).
```

(continues on next page)

(continued from previous page)

```
    Protected Shared Function findsubtour(sol As Double(,)) As Integer()
        Dim n As Integer = sol.GetLength(0)
        Dim seen As Boolean() = New Boolean(n - 1) {}
        Dim tour As Integer() = New Integer(n - 1) {}
        Dim bestind As Integer, bestlen As Integer
        Dim i As Integer, node As Integer, len As Integer, start As Integer

        For i = 0 To n - 1
            seen(i) = False
        Next

        start = 0
        bestlen = n+1
        bestind = -1
        node = 0
        While start < n
            For node = 0 To n - 1
                if Not seen(node)
                    Exit For
                End if
            Next
            if node = n
                Exit While
            End if
            For len = 0 To n - 1
                tour(start+len) = node
                seen(node) = true
                For i = 0 To n - 1
                    if sol(node, i) > 0.5 AndAlso Not seen(i)
                        node = i
                        Exit For
                    End If
                Next
                If i = n
                    len = len + 1
                    If len < bestlen
                        bestlen = len
                        bestind = start
                    End If
                    start = start + len
                    Exit For
                End If
            Next
        End While

        For i = 0 To bestlen - 1
          tour(i) = tour(bestind+i)
        Next
        System.Array.Resize(tour, bestlen)

        Return tour
    End Function
```

(continues on next page)

(continued from previous page)

```
    ' Euclidean distance between points 'i' and 'j'

    Protected Shared Function distance(x As Double(), y As Double(), _
                                       i As Integer, j As Integer) As Double
        Dim dx As Double = x(i) - x(j)
        Dim dy As Double = y(i) - y(j)
        Return Math.Sqrt(dx * dx + dy * dy)
    End Function

    Public Shared Sub Main(args As String())

        If args.Length < 1 Then
            Console.WriteLine("Usage: tsp_vb nnodes")
            Return
        End If

        Dim n As Integer = Convert.ToInt32(args(0))

        Try
            Dim env As New GRBEnv()
            Dim model As New GRBModel(env)

            ' Must set LazyConstraints parameter when using lazy constraints

            model.Parameters.LazyConstraints = 1

            Dim x As Double() = New Double(n - 1) {}
            Dim y As Double() = New Double(n - 1) {}

            Dim r As New Random()
            For i As Integer = 0 To n - 1
                x(i) = r.NextDouble()
                y(i) = r.NextDouble()
            Next

            ' Create variables

            Dim vars As GRBVar(,) = New GRBVar(n - 1, n - 1) {}

            For i As Integer = 0 To n - 1
                For j As Integer = 0 To i
                    vars(i, j) = model.AddVar(0.0, 1.0, distance(x, y, i, j), _
                                              GRB.BINARY, "x" & i & "_" & j)
                    vars(j, i) = vars(i, j)
                Next
            Next

            ' Degree-2 constraints

            For i As Integer = 0 To n - 1
                Dim expr As GRBLinExpr = 0
```

(continues on next page)

(continued from previous page)

```
                For j As Integer = 0 To n - 1
                    expr.AddTerm(1.0, vars(i, j))
                Next
                model.AddConstr(expr = 2.0, "deg2_" & i)
            Next

            ' Forbid edge from node back to itself

            For i As Integer = 0 To n - 1
                vars(i, i).UB = 0.0
            Next

            model.SetCallback(New tsp_vb(vars))
            model.Optimize()

            If model.SolCount > 0 Then
                Dim tour As Integer() = findsubtour(model.Get(GRB.DoubleAttr.X, vars))

                Console.Write("Tour: ")
                For i As Integer = 0 To tour.Length - 1
                    Console.Write(tour(i) & " ")
                Next
                Console.WriteLine()
            End If

            ' Dispose of model and environment
            model.Dispose()

            env.Dispose()
        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
            Console.WriteLine(e.StackTrace)
        End Try
    End Sub
End Class
```

tune_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC */
'
' This example reads a model from a file and tunes it.
' It then writes the best parameter settings to a file
' and solves the model using these parameters.

Imports System
Imports Gurobi

Class tune_vb
    Shared Sub Main(ByVal args As String())

```

(continues on next page)

(continued from previous page)

```
        If args.Length < 1 Then
            Console.Out.WriteLine("Usage: tune_vb filename")
            Return
        End If

        Try
            Dim env As New GRBEnv()

            ' Read model from file
            Dim model As New GRBModel(env, args(0))

            ' Set a time limit for the model
            model.Parameters.TimeLimit = 5

            ' Set a time limit for the whole tuning run
            ' Note that both time limits are chosen to have a quick demonstration.
            ' In general, a total tune time limit should be set such that the
            ' tuning tool can test several hundreds of parameter setting
            model.Parameters.TuneTimeLimit = 60

            ' Set the TuneResults parameter to 2
            '
            ' The first parameter setting is the result for the first solved
            ' setting. The second entry the parameter setting of the best
            ' parameter setting.
            model.Parameters.TuneResults = 2

            ' Tune the model
            model.Tune()

            ' Get the number of tuning results
            Dim resultcount As Integer = model.TuneResultCount

            If resultcount >= 2 Then

                ' Load the tuned parameters into the model's environment
                '
                ' Note, the first parameter setting is associated to the first
                ' solved setting and the second parameter setting to best tune
                ' result.
                model.GetTuneResult(1)

                ' Write the tuned parameters to a file
                model.Write("tune.prm")

                ' Solve the model using the tuned parameters
                model.Optimize()
            End If

            ' Dispose of model and environment
            model.Dispose()
            env.Dispose()
```

(continues on next page)

(continued from previous page)

```
        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

workforce1_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' Assign workers to shifts; each worker may or may not be available on a
' particular day. If the problem cannot be solved, use IIS to find a set of
' conflicting constraints. Note that there may be additional conflicts
' besides what is reported via IIS.

Imports System
Imports Gurobi

Class workforce1_vb
    Shared Sub Main()
        Try

            ' Sample data
            ' Sets of days and workers
            Dim Shifts As String() = New String() {"Mon1", "Tue2", "Wed3", "Thu4", _
                                                   "Fri5", "Sat6", "Sun7", "Mon8", _
                                                   "Tue9", "Wed10", "Thu11", _
                                                   "Fri12", "Sat13", "Sun14"}
            Dim Workers As String() = New String() {"Amy", "Bob", "Cathy", "Dan", _
                                                    "Ed", "Fred", "Gu"}

            Dim nShifts As Integer = Shifts.Length
            Dim nWorkers As Integer = Workers.Length

            ' Number of workers required for each shift
            Dim shiftRequirements As Double() = New Double() {3, 2, 4, 4, 5, 6, _
                                                              5, 2, 2, 3, 4, 6, _
                                                              7, 5}

            ' Amount each worker is paid to work one shift
            Dim pay As Double() = New Double() {10, 12, 10, 8, 8, 9, 11}

            ' Worker availability: 0 if the worker is unavailable for a shift
            Dim availability As Double(,) = New Double(,) { _
                        {0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1}, _
                        {1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0}, _
                        {0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1}, _
                        {0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1}, _
                        {1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1}, _
```

(continues on next page)

(continued from previous page)

```
                {1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1}, _
                {1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1}}

' Model
Dim env As New GRBEnv()
Dim model As New GRBModel(env)

model.ModelName = "assignment"

' Assignment variables: x(w)(s) == 1 if worker w is assigned
' to shift s. Since an assignment model always produces integer
' solutions, we use continuous variables and solve as an LP.
Dim x As GRBVar(,) = New GRBVar(nWorkers - 1, nShifts - 1) {}
For w As Integer = 0 To nWorkers - 1
    For s As Integer = 0 To nShifts - 1
        x(w, s) = model.AddVar(0, availability(w, s), pay(w), _
                               GRB.CONTINUOUS, _
                               Workers(w) & "." & Shifts(s))
    Next
Next

' The objective is to minimize the total pay costs
model.ModelSense = GRB.MINIMIZE

' Constraint: assign exactly shiftRequirements(s) workers
' to each shift s
For s As Integer = 0 To nShifts - 1
    Dim lhs As GRBLinExpr = 0
    For w As Integer = 0 To nWorkers - 1
        lhs.AddTerm(1.0, x(w, s))
    Next
    model.AddConstr(lhs = shiftRequirements(s), Shifts(s))
Next

' Optimize
model.Optimize()
Dim status As Integer = model.Status
If status = GRB.Status.UNBOUNDED Then
    Console.WriteLine("The model cannot be solved " & _
                      "because it is unbounded")
    Exit Sub
End If
If status = GRB.Status.OPTIMAL Then
    Console.WriteLine("The optimal objective is " & model.ObjVal)
    Exit Sub
End If
If (status <> GRB.Status.INF_OR_UNBD) AndAlso _
   (status <> GRB.Status.INFEASIBLE) Then
    Console.WriteLine("Optimization was stopped with status " & status)
    Exit Sub
End If
```

(continues on next page)

(continued from previous page)

```
            ' Do IIS
            Console.WriteLine("The model is infeasible; computing IIS")
            model.ComputeIIS()
            Console.WriteLine(vbLf & "The following constraint(s) " & _
                              "cannot be satisfied:")
            For Each c As GRBConstr In model.GetConstrs()
                If c.IISConstr = 1 Then
                    Console.WriteLine(c.ConstrName)
                End If

            Next

            ' Dispose of model and env
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

workforce2_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' Assign workers to shifts; each worker may or may not be available on a
' particular day. If the problem cannot be solved, use IIS iteratively to
' find all conflicting constraints.

Imports System
Imports System.Collections.Generic
Imports Gurobi

Class workforce2_vb
    Shared Sub Main()
        Try

            ' Sample data
            ' Sets of days and workers
            Dim Shifts As String() = New String() {"Mon1", "Tue2", "Wed3", "Thu4", _
                                                   "Fri5", "Sat6", "Sun7", "Mon8", _
                                                   "Tue9", "Wed10", "Thu11", _
                                                   "Fri12", "Sat13", "Sun14"}
            Dim Workers As String() = New String() {"Amy", "Bob", "Cathy", "Dan", _
                                                    "Ed", "Fred", "Gu"}

            Dim nShifts As Integer = Shifts.Length
            Dim nWorkers As Integer = Workers.Length
```

(continues on next page)

(continued from previous page)

```
        ' Number of workers required for each shift
        Dim shiftRequirements As Double() = New Double() {3, 2, 4, 4, 5, 6, _
                                                          5, 2, 2, 3, 4, 6, _
                                                          7, 5}

        ' Amount each worker is paid to work one shift
        Dim pay As Double() = New Double() {10, 12, 10, 8, 8, 9, 11}

        ' Worker availability: 0 if the worker is unavailable for a shift
        Dim availability As Double(,) = New Double(,) { _
                    {0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1}, _
                    {1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0}, _
                    {0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1}, _
                    {0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1}, _
                    {1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1}, _
                    {1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1}, _
                    {1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1}}

        ' Model
        Dim env As New GRBEnv()
        Dim model As New GRBModel(env)

        model.ModelName = "assignment"

        ' Assignment variables: x(w)(s) == 1 if worker w is assigned
        ' to shift s. Since an assignment model always produces integer
        ' solutions, we use continuous variables and solve as an LP.
        Dim x As GRBVar(,) = New GRBVar(nWorkers - 1, nShifts - 1) {}
        For w As Integer = 0 To nWorkers - 1
            For s As Integer = 0 To nShifts - 1
                x(w, s) = model.AddVar(0, availability(w, s), pay(w), _
                                       GRB.CONTINUOUS, _
                                       Workers(w) & "." & Shifts(s))
            Next
        Next

        ' The objective is to minimize the total pay costs
        model.ModelSense = GRB.MINIMIZE

        ' Constraint: assign exactly shiftRequirements(s) workers
        ' to each shift s
        For s As Integer = 0 To nShifts - 1
            Dim lhs As GRBLinExpr = 0
            For w As Integer = 0 To nWorkers - 1
                lhs.AddTerm(1.0, x(w, s))
            Next
            model.AddConstr(lhs = shiftRequirements(s), Shifts(s))
        Next

        ' Optimize
        model.Optimize()
        Dim status As Integer = model.Status
```

(continues on next page)

(continued from previous page)

```
            If status = GRB.Status.UNBOUNDED Then
                Console.WriteLine("The model cannot be solved " & _
                                  "because it is unbounded")
                Exit Sub
            End If
            If status = GRB.Status.OPTIMAL Then
                Console.WriteLine("The optimal objective is " & model.ObjVal)
                Exit Sub
            End If
            If (status <> GRB.Status.INF_OR_UNBD) AndAlso _
               (status <> GRB.Status.INFEASIBLE) Then
                Console.WriteLine("Optimization was stopped with status " & status)
                Exit Sub
            End If

            ' Do IIS
            Console.WriteLine("The model is infeasible; computing IIS")
            Dim removed As LinkedList(Of String) = New LinkedList(Of String)()

            ' Loop until we reduce to a model that can be solved
            While True
                model.ComputeIIS()
                Console.WriteLine(vbLf & "The following constraint cannot be satisfied:")
                For Each c As GRBConstr In model.GetConstrs()
                    If c.IISConstr = 1 Then
                        Console.WriteLine(c.ConstrName)
                        ' Remove a single constraint from the model
                        removed.AddFirst(c.ConstrName)
                        model.Remove(c)
                        Exit For
                    End If
                Next

                Console.WriteLine()
                model.Optimize()
                status = model.Status

                If status = GRB.Status.UNBOUNDED Then
                    Console.WriteLine("The model cannot be solved " & _
                                      "because it is unbounded")
                    Exit Sub
                End If
                If status = GRB.Status.OPTIMAL Then
                    Exit While
                End If
                If (status <> GRB.Status.INF_OR_UNBD) AndAlso _
                   (status <> GRB.Status.INFEASIBLE) Then
                    Console.WriteLine("Optimization was stopped with status " & _
                                      status)
                    Exit Sub
                End If
            End While
```

(continues on next page)

(continued from previous page)

```
            Console.WriteLine(vbLf & "The following constraints were removed " & _
                              "to get a feasible LP:")
            For Each s As String In removed
                Console.Write(s & " ")
            Next

            Console.WriteLine()

            ' Dispose of model and env
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub
End Class
```

workforce3_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC

' Assign workers to shifts; each worker may or may not be available on a
' particular day. If the problem cannot be solved, relax the model
' to determine which constraints cannot be satisfied, and how much
' they need to be relaxed.

Imports System
Imports Gurobi

Class workforce3_vb
    Shared Sub Main()
        Try

            ' Sample data
            ' Sets of days and workers
            Dim Shifts As String() = New String() {"Mon1", "Tue2", "Wed3", "Thu4", _
                                                   "Fri5", "Sat6", "Sun7", "Mon8", _
                                                   "Tue9", "Wed10", "Thu11", _
                                                   "Fri12", "Sat13", "Sun14"}
            Dim Workers As String() = New String() {"Amy", "Bob", "Cathy", "Dan", _
                                                    "Ed", "Fred", "Gu"}

            Dim nShifts As Integer = Shifts.Length
            Dim nWorkers As Integer = Workers.Length

            ' Number of workers required for each shift
            Dim shiftRequirements As Double() = New Double() {3, 2, 4, 4, 5, 6, _
                                                              5, 2, 2, 3, 4, 6, _
```

(continues on next page)

(continued from previous page)

```
                                                        7, 5}

        ' Amount each worker is paid to work one shift
        Dim pay As Double() = New Double() {10, 12, 10, 8, 8, 9, 11}

        ' Worker availability: 0 if the worker is unavailable for a shift
        Dim availability As Double(,) = New Double(,) { _
                    {0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1}, _
                    {1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0}, _
                    {0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1}, _
                    {0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1}, _
                    {1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1}, _
                    {1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1}, _
                    {1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1}}

        ' Model
        Dim env As New GRBEnv()
        Dim model As New GRBModel(env)

        model.ModelName = "assignment"

        ' Assignment variables: x[w][s] == 1 if worker w is assigned
        ' to shift s. Since an assignment model always produces integer
        ' solutions, we use continuous variables and solve as an LP.
        Dim x As GRBVar(,) = New GRBVar(nWorkers - 1, nShifts - 1) {}
        For w As Integer = 0 To nWorkers - 1
            For s As Integer = 0 To nShifts - 1
                x(w, s) = model.AddVar(0, availability(w, s), pay(w), _
                                       GRB.CONTINUOUS, _
                                       Workers(w) & "." & Shifts(s))
            Next
        Next

        ' The objective is to minimize the total pay costs
        model.ModelSense = GRB.MINIMIZE

        ' Constraint: assign exactly shiftRequirements[s] workers
        ' to each shift s
        For s As Integer = 0 To nShifts - 1
            Dim lhs As GRBLinExpr = 0.0
            For w As Integer = 0 To nWorkers - 1
                lhs.AddTerm(1.0, x(w, s))
            Next
            model.AddConstr(lhs = shiftRequirements(s), Shifts(s))
        Next

        ' Optimize
        model.Optimize()
        Dim status As Integer = model.Status
        If status = GRB.Status.UNBOUNDED Then
            Console.WriteLine("The model cannot be solved " & _
                              "because it is unbounded")
```

(continues on next page)

(continued from previous page)

```
            Return
        End If
        If status = GRB.Status.OPTIMAL Then
            Console.WriteLine("The optimal objective is " & model.ObjVal)
            Return
        End If
        If (status <> GRB.Status.INF_OR_UNBD) AndAlso _
           (status <> GRB.Status.INFEASIBLE) Then
            Console.WriteLine("Optimization was stopped with status " & _
                              status)
            Return
        End If

        ' Relax the constraints to make the model feasible
        Console.WriteLine("The model is infeasible; relaxing the constraints")
        Dim orignumvars As Integer = model.NumVars
        model.FeasRelax(0, False, False, True)
        model.Optimize()
        status = model.Status
        If (status = GRB.Status.INF_OR_UNBD) OrElse _
           (status = GRB.Status.INFEASIBLE) OrElse _
           (status = GRB.Status.UNBOUNDED) Then
            Console.WriteLine("The relaxed model cannot be solved " & _
                              "because it is infeasible or unbounded")
            Return
        End If
        If status <> GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimization was stopped with status " & status)
            Return
        End If

        Console.WriteLine(vbLf & "Slack values:")
        Dim vars As GRBVar() = model.GetVars()
        For i As Integer = orignumvars To model.NumVars - 1
            Dim sv As GRBVar = vars(i)
            If sv.X > 1E-06 Then
                Console.WriteLine(sv.VarName & " = " & sv.X)
            End If
        Next

        ' Dispose of model and environment
        model.Dispose()

        env.Dispose()
    Catch e As GRBException
        Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
    End Try
  End Sub
End Class
```

workforce4_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' Assign workers to shifts; each worker may or may not be available on a
' particular day. We use Pareto optimization to solve the model:
' first, we minimize the linear sum of the slacks. Then, we constrain
' the sum of the slacks, and we minimize a quadratic objective that
' tries to balance the workload among the workers.

Imports System
Imports Gurobi

Class workforce4_vb
    Shared Sub Main()
        Try

            ' Sample data
            ' Sets of days and workers
            Dim Shifts As String() = New String() {"Mon1", "Tue2", "Wed3", "Thu4", _
                                                   "Fri5", "Sat6", "Sun7", "Mon8", _
                                                   "Tue9", "Wed10", "Thu11", _
                                                   "Fri12", "Sat13", "Sun14"}
            Dim Workers As String() = New String() {"Amy", "Bob", "Cathy", "Dan", _
                                                    "Ed", "Fred", "Gu"}

            Dim nShifts As Integer = Shifts.Length
            Dim nWorkers As Integer = Workers.Length

            ' Number of workers required for each shift
            Dim shiftRequirements As Double() = New Double() {3, 2, 4, 4, 5, 6, _
                                                              5, 2, 2, 3, 4, 6, _
                                                              7, 5}

            ' Worker availability: 0 if the worker is unavailable for a shift
            Dim availability As Double(,) = New Double(,) { _
                        {0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1}, _
                        {1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0}, _
                        {0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1}, _
                        {0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1}, _
                        {1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1}, _
                        {1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1}, _
                        {1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1}}

            ' Model
            Dim env As New GRBEnv()
            Dim model As New GRBModel(env)

            model.ModelName = "assignment"

            ' Assignment variables: x(w)(s) == 1 if worker w is assigned
            ' to shift s. This is no longer a pure assignment model, so we
            ' must use binary variables.
```

(continues on next page)

(continued from previous page)

```
Dim x As GRBVar(,) = New GRBVar(nWorkers - 1, nShifts - 1) {}
For w As Integer = 0 To nWorkers - 1
    For s As Integer = 0 To nShifts - 1
        x(w, s) = model.AddVar(0, availability(w, s), 0, _
                               GRB.BINARY, _
                               Workers(w) & "." & Shifts(s))
    Next
Next

' Add a new slack variable to each shift constraint so that the
' shifts can be satisfied
Dim slacks As GRBVar() = New GRBVar(nShifts - 1) {}
For s As Integer = 0 To nShifts - 1
    slacks(s) = _
        model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS, _
                     Shifts(s) & "Slack")
Next

' Variable to represent the total slack
Dim totSlack As GRBVar = model.AddVar(0, GRB.INFINITY, 0, _
                                      GRB.CONTINUOUS, "totSlack")

' Variables to count the total shifts worked by each worker
Dim totShifts As GRBVar() = New GRBVar(nWorkers - 1) {}
For w As Integer = 0 To nWorkers - 1
    totShifts(w) = _
        model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS, _
                     Workers(w) & "TotShifts")
Next

Dim lhs As GRBLinExpr

' Constraint: assign exactly shiftRequirements(s) workers
' to each shift s, plus the slack
For s As Integer = 0 To nShifts - 1
    lhs = 0
    lhs.AddTerm(1.0, slacks(s))
    For w As Integer = 0 To nWorkers - 1
        lhs.AddTerm(1.0, x(w, s))
    Next
    model.AddConstr(lhs = shiftRequirements(s), Shifts(s))
Next

' Constraint: set totSlack equal to the total slack
lhs = 0
For s As Integer = 0 To nShifts - 1
    lhs.AddTerm(1.0, slacks(s))
Next
model.AddConstr(lhs = totSlack, "totSlack")

' Constraint: compute the total number of shifts for each worker
For w As Integer = 0 To nWorkers - 1
```

(continues on next page)

(continued from previous page)

```
        lhs = 0
        For s As Integer = 0 To nShifts - 1
            lhs.AddTerm(1.0, x(w, s))
        Next
        model.AddConstr(lhs = totShifts(w), "totShifts" & Workers(w))
    Next

    ' Objective: minimize the total slack
    model.SetObjective(1.0*totSlack)

    ' Optimize
    Dim status As Integer = _
        solveAndPrint(model, totSlack, nWorkers, Workers, totShifts)
    If status <> GRB.Status.OPTIMAL Then
        Exit Sub
    End If

    ' Constrain the slack by setting its upper and lower bounds
    totSlack.UB = totSlack.X
    totSlack.LB = totSlack.X

    ' Variable to count the average number of shifts worked
    Dim avgShifts As GRBVar = model.AddVar(0, GRB.INFINITY, 0, _
                                           GRB.CONTINUOUS, "avgShifts")

    ' Variables to count the difference from average for each worker;
    ' note that these variables can take negative values.
    Dim diffShifts As GRBVar() = New GRBVar(nWorkers - 1) {}
    For w As Integer = 0 To nWorkers - 1
        diffShifts(w) = _
            model.AddVar(-GRB.INFINITY, GRB.INFINITY, 0, _
                         GRB.CONTINUOUS, Workers(w) & "Diff")
    Next

    ' Constraint: compute the average number of shifts worked
    lhs = 0
    For w As Integer = 0 To nWorkers - 1
        lhs.AddTerm(1.0, totShifts(w))
    Next
    model.AddConstr(lhs = nWorkers * avgShifts, "avgShifts")

    ' Constraint: compute the difference from the average number of shifts
    For w As Integer = 0 To nWorkers - 1
        model.AddConstr(totShifts(w) - avgShifts = diffShifts(w), _
                        Workers(w) & "Diff")
    Next

    ' Objective: minimize the sum of the square of the difference
    ' from the average number of shifts worked
    Dim qobj As GRBQuadExpr = New GRBQuadExpr
    For w As Integer = 0 To nWorkers - 1
        qobj.AddTerm(1.0, diffShifts(w), diffShifts(w))
```

(continues on next page)

(continued from previous page)

```
            Next
            model.SetObjective(qobj)

            ' Optimize
            status = solveAndPrint(model, totSlack, nWorkers, Workers, totShifts)
            If status <> GRB.Status.OPTIMAL Then
                Exit Sub
            End If

            ' Dispose of model and env
            model.Dispose()
            env.Dispose()

        Catch e As GRBException
            Console.WriteLine("Error code: " & e.ErrorCode & ". " & e.Message)
        End Try
    End Sub

    Private Shared Function solveAndPrint(ByVal model As GRBModel, _
                                          ByVal totSlack As GRBVar, _
                                          ByVal nWorkers As Integer, _
                                          ByVal Workers As String(), _
                                          ByVal totShifts As GRBVar()) As Integer
        model.Optimize()
        Dim status As Integer = model.Status
        solveAndPrint = status
        If (status = GRB.Status.INF_OR_UNBD) OrElse _
           (status = GRB.Status.INFEASIBLE) OrElse _
           (status = GRB.Status.UNBOUNDED) Then
            Console.WriteLine("The model cannot be solved because " & _
                              "it is infeasible or unbounded")
            Exit Function
        End If
        If status <> GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimization was stopped with status " _
                              & status)
            Exit Function
        End If

        ' Print total slack and the number of shifts worked for each worker
        Console.WriteLine(vbLf & "Total slack required: " & totSlack.X)
        For w As Integer = 0 To nWorkers - 1
            Console.WriteLine(Workers(w) & " worked " & _
                              totShifts(w).X & " shifts")
        Next

        Console.WriteLine(vbLf)
    End Function
End Class
```

workforce5_vb.vb

```
' Copyright 2026, Gurobi Optimization, LLC
'
' Assign workers to shifts; each worker may or may not be available on a
' particular day. We use multi-objective optimization to solve the model.
' The highest-priority objective minimizes the sum of the slacks
' (i.e., the total number of uncovered shifts). The secondary objective
' minimizes the difference between the maximum and minimum number of
' shifts worked among all workers.  The second optimization is allowed
' to degrade the first objective by up to the smaller value of 10% and 2 */

Imports System
Imports Gurobi

Class workforce5_vb
    Shared Sub Main()

        Try

            ' Sample data
            ' Sets of days and workers
            Dim Shifts As String() = New String() { _
                "Mon1", "Tue2", "Wed3", "Thu4", "Fri5", "Sat6", "Sun7", _
                "Mon8", "Tue9", "Wed10", "Thu11", "Fri12", "Sat13", "Sun14"}

            Dim Workers As String() = New String() { _
                "Amy", "Bob", "Cathy", "Dan", "Ed", "Fred", "Gu", "Tobi"}

            Dim nShifts As Integer = Shifts.Length
            Dim nWorkers As Integer = Workers.Length

            ' Number of workers required for each shift
            Dim shiftRequirements As Double() = New Double() { _
                3, 2, 4, 4, 5, 6, 5, 2, 2, 3, 4, 6, 7, 5}

            ' Worker availability: 0 if the worker is unavailable for a shift
            Dim availability As Double(,) = New Double(,) { _
                {0, 1, 1, 0, 1, 0, 1, 0, 1, 1, 1, 1, 1, 1}, _
                {1, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0}, _
                {0, 0, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1}, _
                {0, 1, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1}, _
                {1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 1, 1}, _
                {1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 1, 1, 1}, _
                {0, 1, 1, 1, 0, 1, 1, 0, 1, 1, 1, 0, 1, 1}, _
                {1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1}}

            ' Create environment
            Dim env As New GRBEnv()

            ' Create initial model
            Dim model As New GRBModel(env)
            model.ModelName = "workforce5_vb"
```

(continues on next page)

(continued from previous page)

```
            ' Initialize assignment decision variables:
            ' x[w][s] == 1 if worker w is assigned to shift s.
            ' This is no longer a pure assignment model, so we must
            ' use binary variables.
            Dim x As GRBVar(,) = New GRBVar(nWorkers - 1, nShifts - 1) {}
            For w As Integer = 0 To nWorkers - 1
                For s As Integer = 0 To nShifts - 1
                    x(w, s) = model.AddVar(0, availability(w, s), 0, GRB.BINARY, _
                                           String.Format("{0}.{1}", Workers(w),␣
↪Shifts(s)))
                Next
            Next

            ' Slack variables for each shift constraint so that the shifts can
            ' be satisfied
            Dim slacks As GRBVar() = New GRBVar(nShifts - 1) {}
            For s As Integer = 0 To nShifts - 1
                slacks(s) = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS, _
                                         String.Format("{0}Slack", Shifts(s)))
            Next

            ' Variable to represent the total slack
            Dim totSlack As GRBVar = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
↪"totSlack")

            ' Variables to count the total shifts worked by each worker
            Dim totShifts As GRBVar() = New GRBVar(nWorkers - 1) {}
            For w As Integer = 0 To nWorkers - 1
                totShifts(w) = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS, _
                                            String.Format("{0}TotShifts", Workers(w)))
            Next

            Dim lhs As GRBLinExpr

            ' Constraint: assign exactly shiftRequirements[s] workers
            ' to each shift s, plus the slack
            For s As Integer = 0 To nShifts - 1
                lhs = New GRBLinExpr()
                lhs.AddTerm(1.0, slacks(s))
                For w As Integer = 0 To nWorkers - 1
                    lhs.AddTerm(1.0, x(w, s))
                Next
                model.AddConstr(lhs, GRB.EQUAL, shiftRequirements(s), Shifts(s))
            Next

            ' Constraint: set totSlack equal to the total slack
            lhs = New GRBLinExpr()
            lhs.AddTerm(-1.0, totSlack)
            For s As Integer = 0 To nShifts - 1
                lhs.AddTerm(1.0, slacks(s))
            Next
```

(continues on next page)

(continued from previous page)

```
            model.AddConstr(lhs, GRB.EQUAL, 0, "totSlack")

            ' Constraint: compute the total number of shifts for each worker
            For w As Integer = 0 To nWorkers - 1
                lhs = New GRBLinExpr()
                lhs.AddTerm(-1.0, totShifts(w))
                For s As Integer = 0 To nShifts - 1
                    lhs.AddTerm(1.0, x(w, s))
                Next
                model.AddConstr(lhs, GRB.EQUAL, 0, String.Format("totShifts{0}",␣
↪Workers(w)))
            Next

            ' Constraint: set minShift/maxShift variable to less <=/>= to the
            ' number of shifts among all workers
            Dim minShift As GRBVar = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
↪"minShift")
            Dim maxShift As GRBVar = model.AddVar(0, GRB.INFINITY, 0, GRB.CONTINUOUS,
↪"maxShift")
            model.AddGenConstrMin(minShift, totShifts, GRB.INFINITY, "minShift")
            model.AddGenConstrMax(maxShift, totShifts, -GRB.INFINITY, "maxShift")

            ' Set global sense for ALL objectives
            model.ModelSense = GRB.MINIMIZE

            ' Set primary objective
            model.SetObjectiveN(totSlack, 0, 2, 1.0, 2.0, 0.1, "TotalSlack")

            ' Set secondary objective
            model.SetObjectiveN(maxShift - minShift, 1, 1, 1.0, 0, 0, "Fairness")

            ' Save problem
            model.Write("workforce5_vb.lp")

            ' Optimize
            Dim status As Integer = _
                solveAndPrint(model, totSlack, nWorkers, Workers, totShifts)

            If status <> GRB.Status.OPTIMAL Then
                Return
            End If

            ' Dispose of model and environment
            model.Dispose()

            env.Dispose()
        Catch e As GRBException
            Console.WriteLine("Error code: {0}. {1}", e.ErrorCode, e.Message)
        End Try
    End Sub

    Private Shared Function solveAndPrint(ByVal model As GRBModel, _
```

(continues on next page)

(continued from previous page)

```
                                        ByVal totSlack As GRBVar, _
                                        ByVal nWorkers As Integer, _
                                        ByVal Workers As String(), _
                                        ByVal totShifts As GRBVar()) As Integer

        model.Optimize()
        Dim status As Integer = model.Status
        If status = GRB.Status.INF_OR_UNBD OrElse _
           status = GRB.Status.INFEASIBLE OrElse _
           status = GRB.Status.UNBOUNDED Then
            Console.WriteLine("The model cannot be solved " & _
                     "because it is infeasible or unbounded")
            Return status
        End If
        If status <> GRB.Status.OPTIMAL Then
            Console.WriteLine("Optimization was stopped with status {0}", status)
            Return status
        End If

        ' Print total slack and the number of shifts worked for each worker
        Console.WriteLine(vbLf & "Total slack required: {0}", totSlack.X)
        For w As Integer = 0 To nWorkers - 1
            Console.WriteLine("{0} worked {1} shifts", Workers(w), totShifts(w).X)
        Next
        Console.WriteLine(vbLf)
        Return status
    End Function

End Class
```